

VL-2488-1-O

DEVELOPMENT OF ELECTROPHORETIC PROCESS FOR
COATING T-53 AIR DIFFUSER, EXHAUST DIFFUSER, AND
COMBUSTION CHAMBER HOUSING WITH "SERMETEL W"®

AD 661317

PHASE I TECHNICAL REPORT

K. A. Gebler

21 June 1967 - 21 August 1967

Prepared for

Headquarters, U. S. Army Aviation Materiel Command
St. Louis, Missouri 63166

By

Vitro Laboratories
West Orange, New Jersey 07052

Prepared Under

Contract No. DAAJ01-67-C-2207(G)

Vitro Job No. 2488


Distribution of this Document is Unlimited

**LABORATORIES**

DIVISION OF VITRO CORPORATION OF AMERICA

200 Pleasant Valley Way, West Orange, N. J.

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield Va 22151



GFTI		W. H. SEC. 107
DNC		DIFF. SEC. 108
UNAPPROVED		
JUSTIFICATION		
BY		
DISTRIBUTION/AVAILABILITY CODES		
DIST.	AVAIL.	AND/OR SPECIAL
1		

NOTICES

DISCLAIMERS

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government endorsement or approval of commercial products or services referenced herein.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

AD

VL-2488-1-O

DEVELOPMENT OF ELECTROPHORETIC PROCESS FOR
COATING T-53 AIR DIFFUSER, EXHAUST DIFFUSER, AND
COMBUSTION CHAMBER HOUSING WITH "SERMETEL W" (F)

PHASE I TECHNICAL REPORT

K. A. Gebler

21 June 1967 - 21 August 1967

Prepared for

Headquarters, U. S. Army Aviation Materiel Command
St. Louis, Missouri 63166

By

Vitro Laboratories
West Orange, New Jersey 07052

Prepared Under

Contract No. DAAJ01-67-C-2207(G)

Vitro Job No. 2488

Distribution of this Document is Unlimited

ABSTRACT

This report covers activities accomplished during the first two months (Phase I) of a ten (10) month program to develop an electrophoretic coating method for the application of "SERMETEL W"®* to all critical surfaces of the exhaust diffuser, air diffuser and combustion chamber housing of the T-53 engine. "SERMETEL W" has been classified by various engine manufacturers and DOD agencies as the best coating available for corrosion protection. Its application to the complex parts included in this program has not been possible by other conventional means. The development of the electrophoretic methods to coat these parts will greatly extend the corrosion protection now afforded by sprayed-on high-temperature aluminum paint. During this phase, the design and procurement of coating tanks, power supplies, humidification chambers, and miscellaneous materials have been made. Utilizing drawings and sections cut from reject parts obtained from ARADMAC, the design and fabrication of jigs and fixtures were started. Design of three jigs and fixtures was accomplished to take advantage of any radial symmetry of the hardware item and to provide flexibility for modification that may be required in later phases of this program. All objectives in Phase I have been accomplished.

* Registered Trademark, Product of Teleflex, Inc., North Wales, Pa.

FOREWORD

This Phase I Technical Report covers work performed under Contract No. DAAJ01-67-C-2207(G) during the period 21 June 1967 to 21 August 1967.

This program is being conducted by the Chemistry and Arc Materials Department, West Orange Laboratory, Vitro Laboratories Division. The program is under the technical direction of F. E. Stevens, Directorate of Research, Development and Engineering, AVCOM, St. Louis, Missouri 63116.

Kenneth A. Gebler is the Vitro Project Leader. No other major contributions were made to this report by other persons.

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	i
FOREWORD	ii
OBJECTIVES	1
PROGRAM PLAN	2
EXPERIMENTAL PROGRESS	6
FUTURE WORK	6
DISTRIBUTION LIST	12

LIST OF ILLUSTRATIONS

Figure

1 Exhaust Diffuser for T-53 Engine P/N 1-150-110-01	3
2 Air Diffuser for T-53 Engine P/N 1-110-230-01	4
3 Combustion Chamber Housing for T-53 Engine P/N 1-130-020-05	5
4 Floor Plan, Electrophoretic Coating Equipment for Coating T-53 Engine Components	7
5 Exhaust Diffuser Sector with Trial Electrode	8
6 Air Diffuser Sector with Trial Electrode	9
7 Combustion Chamber Housing Sector with Trial Electrode.	10
8 Electrophoretic Coating Tank and Auxiliary Equipment	11

OBJECTIVES

The developmental effort under this program has two major objectives. The first is to develop the process methods and equipments to electro-phoretically coat "SERMETEL W" on all critical surfaces of three T-53 engine components. These components, the exhaust diffuser, air diffuser, and combustion chamber housing are shown in Figures 1, 2, and 3, respectively.

The second objective, after successful coating procedures and equipment have been developed, is to coat a minimum of two parts of each type and deliver these parts to a site selected by the Contracting Officer for evaluation and qualification of the coating.

PROGRAM PLAN

The developmental effort has been divided into five essential phases:

- I. Design and Installation of Coating Equipment
- II. Dummy Coating Runs and Refinement of Electrode Design
- III. Heat Treatment and Evaluation of Coated Components
- IV. Full Scale Coating Trials
- V. Delivery of Final Specimens.

Through necessity, the work in each of the five phases will overlap and efforts will, therefore, be concurrent in one or more phases as the program progresses.




FIGURE 1

EXHAUST DIFFUSER FOR T-53 ENGINE
P/N 1-150-110-01




FIGURE 2

AIR DIFFUSER FOR T-53 ENGINE
P/N 1-110-230-01




FIGURE 3

COMBUSTION CHAMBER HOUSING FOR T-53 ENGINE
P/N 1-130-020-05

EXPERIMENTAL PROGRESS

Phase I

The necessary cleaning, coating, drying, humidifying and sintering equipment have been designed and/or determined. Orders for all equipment and materials have been placed with vendors, and most of the equipment has been received and is being installed. Figure 4 is a layout of the equipment to be used for this program, showing coating tanks, furnace, humidification chamber, and other support equipment.

Utilizing drawings and sectors, each four inches wide, jigs and fixtures for the three components have been prepared for use in preliminary coating trials. Photographs of these parts are shown in Figures 5, 6, and 7. The first experimental anode for each part is also shown. These anodes are constructed of stainless steel wire mesh. It is planned to begin the coating trials on these assemblies by using a 75 liter coating facility which will permit more flexibility in initial tests of electrode placement and coating deposition rates than will be possible in a large volume tank. This coating facility is shown in Figure 8.

FUTURE WORK

1. Complete remaining work necessary to installation and construction of essential equipment required for the large coating tank to accommodate the full size components.
2. Begin coating trials on 4" wide sectors using 75 liter coating equipment to check coating coverage achieved with initially designed jigs and fixtures.
3. Investigate the effects of depletion of solids from the coating bath, dispersion stability and determine methods of reconstituting the coating bath when required for proper coatings.




FIGURE 4
FLOOR PLAN
ELECTROPHORETIC COATING EQUIPMENT
FOR COATING T-53 ENGINE COMPONENTS




FIGURE 5

EXHAUST DIFFUSER SECTOR WITH TRIAL ELECTRODE




FIGURE 6

AIR DIFFUSER SECTOR WITH TRIAL ELECTRODE




FIGURE 7
COMBUSTION CHAMBER HOUSING SECTOR
WITH TRIAL ELECTRODE




FIGURE 8
ELECTROPHORETIC COATING TANK
AND AUXILIARY EQUIPMENT

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Vitro Corporation of America Vitro Laboratories Division 200 Pleasant Valley Way, W. Orange, N. J. 07052		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP ---	
3 REPORT TITLE Development of Electrophoretic Process for Coating T-53 Air Diffuser, Exhaust Diffuser, and Combustion Chamber Housing with "SERMETEL [®] W".			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) R&D Phase I Technical Report, 21 June - 21 August 1967			
5 AUTHOR(S) (Last name, first name, initial) Gebler, Kenneth A.			
6 REPORT DATE August 1967		7a. TOTAL NO. OF PAGES 12	7b. NO OF REFS 0
8a. CONTRACT OR GRANT NO. DAAJ01-67-C-2207(G)		9a. ORIGINATOR'S REPORT NUMBER(S) VL-2488-1-O	
b. PROJECT NO. c. d.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned file report)	
10 AVAILABILITY/LIMITATION NOTICES Distribution of this Document is Unlimited			
11. SUPPLEMENTARY NOTES ---		12 SPONSORING MILITARY ACTIVITY Directorate Research, Development & Engineering, AVCOM, St. Louis, Mo. 63166	
13 ABSTRACT This report covers activities accomplished during the first two months (Phase I) of a ten (10)-month program to develop an electrophoretic coating method for the application of "SERMETEL W" [®] to all critical surfaces of the exhaust diffuser, air diffuser and combustion chamber housing of the T-53 engine. "SERMETEL W" has been classified by various engine manufacturers and DOD agencies as the best coating available for corrosion protection. Its application to the complex parts included in this program has not been possible by other conventional means. The development of the electrophoretic methods to coat these parts will greatly extend the corrosion protection now afforded by sprayed-on high-temperature aluminum paint. During this phase, the design and procurement of coating tanks, power supplies, humidification chambers, and miscellaneous materials have been made. Utilizing drawings and sections cut from reject parts obtained from ARADMAC, the design and fabrication of jigs and fixtures were started. Design of three jigs and fixtures was accomplished to take advantage of any radial symmetry of the hardware item and to provide flexibility for modification that may be required in later phases of this program. All objectives in Phase I have been accomplished. * Registered Trademark, Product of Teleflex, Inc., North Wales, Pa.			

DD FORM 1473
1 JAN 64UNCLASSIFIED
Security Classification

UNCLASSIFIED
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Electrophoretically Coated Exhaust Diffuser Air Diffuser Combustion Chamber Housing T-53 Engine Corrosion Protection						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, roles, and weights is optional.

UNCLASSIFIED
Security Classification