

AD



Research and Development Technical Report
ECOM- 0296-2

BALLISTIC WINDS STUDY

QUARTERLY REPORT

BY

FREDERICK P. OSTBY, JR.

APRIL 1968



ECOM

UNITED STATES ARMY ELECTRONICS COMMAND · FORT MONMOUTH, N.J.

CONTRACT NO. DAAB07-67-C0296

THE TRAVELERS RESEARCH CENTER, INC.

250 CONSTITUTION PLAZA, HARTFORD, CONNECTICUT 06103

DISTRIBUTION STATEMENT

This document has been approved for public release and sale; its distribution is unlimited.

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield, Va. 22151

27

AD 667912

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

TECHNICAL REPORT ECOM-0296-2

Reports Control Symbol
OSD-1366

April 1968
7486-278

BALLISTIC WINDS STUDY

Quarterly Report

Report No. 2

1 June 1967 to 31 August 1967

Contract No. DAAB07-67-C0296

Project No. IVO 25001 A 126 01 14

Prepared by

Frederick P. Ostby, Jr.

THE TRAVELERS RESEARCH CENTER, INC.

250 Constitution Plaza Hartford, Connecticut 06103

For

U.S. ARMY ELECTRONICS COMMAND, FORT MONMOUTH, N. J.

DISTRIBUTION STATEMENT

This document has been approved for
public release and sale; its distribu-
tion is unlimited.

ABSTRACT

Space and time variability studies were conducted for the 12-rain station mesonet network of southeastern Arizona.

The space variability studies showed that for low levels (below 1000 meters) there was only a slight increase in variability as a function of station separation. The root-mean square space difference of the vector wind (RMSSD) is 8.0 knots for stations within 20 km of each other, while the RMSSD is 9.6 knots for stations 120–140 km apart. At high levels (e.g., 8000 m) the variability difference with distance is sizeable.

Investigations of time variability indicated the increase in variability with increasing time lag is less at low levels than at high levels. At low levels (around 1000 m) there is not much difference between a 2-hr old observation and one that is 8 hours old. At about 8,000 meters, the variability increases markedly with increasing time lag. From time variability profiles this is seen to be the level of maximum time variability for all lags with the variability diminishing rapidly with height thereafter.

TABLE OF CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>
1.0	INTRODUCTION	1
2.0	SPACE AND TIME VARIABILITY STUDIES	2
2.1	Space Variability	2

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
1	Station Pairs, Distances, and Numbers of Observations	3

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1	Averaged RMSWD values for 20-km intervals of station spacing, all stations	7
2	Composite of time variability as a function of altitude and la_s , all stations	8
3	Time variability, Benson	9
4	Time variability, Bisbee Junction	10
5	Time variability, Douglas	11
6	Time variability, Fairbanks	12
7	Time variability, Hereford	13
8	Time variability, Ft. Huachuca	14
9	Time variability, Nogales	15
10	Time variability, Patagonia	16
11	Time variability, Parker Canyon	17
12	Time variability, Sonoita	18
13	Time variability, Tombstone	19
14	Time variability, Wilcox	20
	DISTRIBUTION LIST	21

1.0 INTRODUCTION

This report describes technical progress during the second quarter, June 1, 1967 through August 31, 1967 of the contract year, under Contract DAAB07-67-C2967

"Ballistic Winds Techniques Study."

Primary emphasis during the quarter concentrated on Task 2, Ballistic Winds Evaluation, concerned with space and time variability studies based on station data.

2.0 SPACE AND TIME VARIABILITY STUDIES

In both the space and time variability studies, zone winds were employed rather than the integrated or ballistic wind. This was done to permit examination of the characteristics of individual zones. The zones are non-uniform in thickness which should be kept in mind when considering the relationship of variability with altitude. Also worthy of note is that the wind differences which have been computed include instrumental errors as well as atmospheric variations and hence represent estimates of wind variability.

2.1 Space Variability

Wind component differences between every station pair in the 12 station rawinsonde network were computed for all 80 observation times for artillery zones 1 through 12. Root-mean square wind component differences $[\sigma(u_g), \sigma(v_g)]$ and vector differences $[\sigma(V_g)]$ were computed by the following:

$$\begin{aligned}\sigma(u_g) &= \left[\frac{1}{N} \sum_{i=1}^N (u_i - u_j)^2 \right]^{1/2} \\ \sigma(v_g) &= \left[\frac{1}{N} \sum_{i=1}^N (v_i - v_j)^2 \right]^{1/2} \\ \sigma(V_g) &= \left[\frac{1}{N} \sum \{ (u_i - u_j)^2 + (v_i - v_j)^2 \} \right]^{1/2}\end{aligned}$$

where the subscripts i, j refer to a pair of station locations for which differences are summed over N cases.

Table 1 lists the station pairs, distances between stations, and number of observations for which differences were computed. Because of missing data situations the maximum possible number of observations (80) was never realized.

The space variability was computed by averaging RMS vector difference values for 20-km intervals of station separation: 0-20 km, 20-40 km, etc. The results are shown in Fig. 1. For zone 1, the variability increases only slightly with increasing station spacing. The average variability for the 0-20 km range is 7.9 knots while for station spacing of 120-140 km the variability is 9.6 knots. On the other hand, the range of variability for some of the higher zones is substantial. At zone 10 the variability is 6.3 knots for a station separation of 0-20 km while the variability for stations

TABLE 1
STATION PAIRS, DISTANCES, AND NUMBERS OF OBSERVATIONS

Station pair	Distance kilometers	Number of observations per zone												Total
		1	2	3	4	5	6	7	8	9	10	11	12	
FR-HU	16.57	61	64	63	64	64	63	62	61	59	51	47	45	703
NO-PA	17.09	60	72	72	72	72	73	73	70	70	70	64	60	838
PA-SO	17.10	66	67	68	68	69	67	67	67	65	64	61	56	784
HU-PR	20.49	68	70	70	71	70	69	67	66	63	56	50	46	766
BI-HR	21.79	59	59	60	60	60	59	58	56	56	56	52	47	682
FR-TM	25.09	64	67	66	66	66	65	64	64	63	63	62	50	760
BE-FR	26.77	62	64	63	62	61	61	61	61	61	59	55	48	718
HR-TM	27.36	71	72	73	73	73	72	71	70	69	69	62	55	830
HR-HU	28.82	67	69	70	71	71	70	69	67	63	57	50	49	773
HU-SO	31.41	64	67	68	69	69	67	66	65	60	53	50	46	744
HU-TM	31.78	70	73	74	74	74	72	70	69	64	58	53	48	799
HR-PR	32.57	68	68	69	69	69	69	69	68	67	67	60	56	799
PA-PR	33.06	71	71	72	72	71	71	70	70	70	70	61	57	826
NO-SO	34.18	62	65	65	65	65	65	65	62	60	58	58	53	743
BI-DG	34.25	54	54	53	54	54	52	51	50	48	42	35	31	578
FR-SO	35.57	56	59	59	59	59	59	59	59	58	56	57	54	694
PR-SO	35.60	63	64	65	65	64	63	63	63	61	59	55	50	735
BI-TM	36.57	62	62	62	62	62	60	59	57	57	57	52	46	698
FR-HR	36.76	61	63	63	63	63	63	63	63	62	62	57	57	740
FR-PR	37.02	61	63	62	62	61	61	60	60	60	60	53	49	712
HU-PA	38.72	70	72	73	74	74	73	72	71	67	61	53	51	811
NO-PR	38.90	68	69	68	68	67	68	68	65	65	65	58	56	785
BE-TM	39.20	71	72	72	71	70	69	68	67	66	64	60	50	800
BE-HU	42.98	67	68	68	68	67	67	67	65	62	55	49	45	748
BE-WI	46.87	62	63	64	63	62	62	62	61	61	60	54	46	720
FR-PA	48.30	64	66	66	66	66	66	66	66	66	66	62	58	778
PR-TM	48.34	71	72	72	72	71	70	68	68	67	67	59	51	808
BE-SO	48.94	62	63	64	63	62	61	61	60	58	56	52	46	708
BI-HU	50.15	59	60	59	60	60	57	55	54	50	46	42	38	640
HU-NO	51.16	66	71	69	70	70	70	69	65	63	56	52	49	769
BI-PR	53.33	59	59	59	59	58	56	54	54	54	54	49	42	657
BI-FR	55.01	53	55	54	54	54	53	52	51	51	51	46	41	615
DG-HR	55.53	63	63	63	64	64	54	64	63	58	50	37	33	686
SO-TM	59.70	67	68	69	69	69	67	66	66	63	61	60	50	775
HR-SO	59.70	63	64	66	66	66	65	65	64	61	60	57	54	751
BE-TM	60.08	67	68	67	68	68	67	66	66	59	52	40	35	723

TABLE 1 (Continued)

Station pair	Distance kilometers	Number of observations per zone												Total
		1	2	3	4	5	6	7	8	9	10	11	12	
BE-HR	60.87	67	67	68	67	66	66	66	64	63	62	52	49	757
BE-PR	62.97	68	68	68	67	65	65	54	63	63	62	51	47	751
FR-NO	63.27	61	64	62	62	62	63	63	61	61	61	58	54	732
HR-PA	63.40	71	71	73	73	73	73	73	72	71	71	63	63	847
TM-WI	64.68	65	68	69	69	69	69	68	67	66	65	61	49	785
BE-PA	65.41	71	71	72	71	70	70	70	69	69	67	61	54	815
FR-WI	68.77	58	60	60	60	60	60	60	59	59	59	57	51	713
PA-TM	70.07	74	75	76	76	76	75	74	74	73	73	67	56	869
HR-NO	71.43	68	70	70	70	70	71	71	67	66	66	60	59	808
BE-BI	75.34	58	58	58	57	56	54	53	51	51	49	44	39	628
BI-SO	81.35	55	56	56	56	56	54	53	53	53	51	49	43	635
BE-NO	82.19	66	68	67	66	65	66	66	63	63	63	58	51	760
DG-HU	82.51	62	64	63	65	65	64	63	62	55	43	33	30	671
NO-TM	82.92	70	73	72	72	72	72	71	68	67	67	62	56	822
DG-FR	83.64	60	62	60	61	61	61	61	61	55	48	37	34	661
HU-WI	85.03	63	67	68	69	69	68	67	65	64	57	52	46	755
BI-PA	85.04	61	61	62	62	62	60	59	58	58	58	52	46	699
DG-PR	87.57	64	64	63	64	63	63	62	62	59	52	40	35	691
HR-WI	92.02	63	65	67	67	67	67	67	65	64	63	58	53	766
BI-NO	92.14	58	59	58	58	58	57	56	52	52	52	49	44	653
SO-WI	95.80	60	63	65	65	65	64	64	64	62	59	58	50	739
BI-WI	97.22	55	57	58	58	58	56	55	53	53	52	48	40	643
BE-DG	98.03	64	64	63	63	62	62	62	61	55	47	36	32	671
PR-WI	105.46	62	64	65	65	64	64	64	63	63	62	56	51	743
DG-WI	105.47	58	59	60	60	60	60	60	59	55	48	38	34	651
PA-WI	112.24	66	67	69	69	69	69	69	68	68	67	61	54	796
DG-SO	113.91	58	59	59	60	60	59	59	59	54	45	36	32	650
DG-PA	118.92	66	66	66	67	67	67	67	67	61	53	40	36	723
DG-NO	126.39	63	65	64	64	64	65	65	62	57	51	41	37	698
NO-WI	128.91	64	67	67	67	67	68	68	64	64	63	60	53	772

BE-Benson
BI-Bisbee
DG-Douglas
FR-Fairbanks

HR-Hereford
HU-Ft. Huachuca
NO-Nogales
PA-Patagonia

PR-Parker Canyon
SO-Sonoma
TM-Tombstone
WI-Wilcox

120—140 km apart is 14.6 knots. Thus, in terms of exterior ballistics, it can be seen that for low elevation firings, say up to line 3, there is not much to be gained from decreasing the station spacing, but for high elevation firings, such as line 10, there is a sizeable potential reduction in variability when the spacing between stations is decreased.

It is interesting to consider space variability as a function of altitude. For all station separations, there is a general decrease in variability with altitude starting from zone 1 to the middle zones, followed by an increase reaching a maximum around zone 11. Above zone 11 the variability decreases markedly.

The level of minimum space variability appears to be somewhat dependent on station separation. For stations within 60 km of each other, the level of minimum variability is zone 6 (2000—3000 m) while for stations farther apart, 60—140 km, the minimum is at zone 3 (500—1000 m).

The maximum variability at zone 11 (8000—10000 m) is near the level of maximum winds. Above zone 11 the space variability is much less, even though the westerly winds are still strong.

The fact that the space variability is larger at zone 1 than the middle zones is probably due to small-scale effects, part of which are undoubtedly due to terrain.

For stations close together (within 40 km), the maximum variability is at zone 1 with the secondary maximum, of lesser magnitude, at zone 11. For stations farther apart, the zone 11 maximum is considerably larger than the zone 1 variability. These differences are reasonable since stations close together would be expected to be influenced more by low-level small-scale variations than upper-level large-scale variations. For stations with greater separation, the reverse would be expected.

2.2 Time Variability

Time variability statistics for both u and v components and vector differences were computed for each station for lags of 2, 4, 6 and 8 hr. The basic variability measure is the root-mean square time difference $\sigma(V_t)$.

$$\sigma(V_t) = \left[\frac{1}{N} \sum (u_{t_1} - u_{t_2})^2 + (v_{t_1} - v_{t_2})^2 \right]^{1/2}$$

where the subscripts t_1, t_2 refer to different pairs of observation times at the same station for which differences are summed over N cases. Figure 2 shows the time variability as a function of altitude and lag for a composite of all 12 stations. The outstanding features are the general decrease in variability with altitude, up to around zone 3, followed by an increase to zone 6, little change to zone 8, followed by an increase to zone 10, the level of maximum variability. Above zone 10 the time variability decreases with altitude.

Figures 3 through 14 show the time variability by individual stations. Several of the stations exhibit an apparent decrease in variability with altitude between zones 7 and 8: Benson, Bisbee Junction, Hereford (between zones 6 and 7), and Wilcox. However, the number of cases is too small to show that the differences are significant.




Fig. 1. Averaged RMSWD values for 20-km intervals of station spacing. all stations.




Fig. 2. Composite of time variability as a function of altitude and lag, all stations.




Fig. 3. Time variability, Benson.




Fig. 4. Time variability, Bisbee Junction.




Fig. 5. Time variability. Douglas.




Fig. 6. Time variability, Fairbanks.




Fig. 7. Time variability, Hereford.




Fig. 8. Time variability, Ft. Huachuca.




Fig. 9. Time variability, Nogales.




Fig. 10. Time variability, Patagonia.




Fig. 11. Time variability, Parker Canyon.




Fig. 12. Time variability, Sonoita.




Fig. 13. Time variability, Tombstone.




Fig. 14. Time variability, Wilcox.

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINAL Sponsoring Activity (Corporate author) The Travelers Research Center, Inc. 250 Constitution Plaza Hartford, Connecticut 06103		2a. REPORT SECURITY CLASSIFICATION Unclassified
3. REPORT TITLE BALLISTIC WINDS STUDY		2b. GROUP N/A
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Quarterly Report, No. 2, 1 June 1967 to 31 August 1967		
5. AUTHOR(S) (Last name, first name, initial) Ostby, Frederick, P., Jr.		
6. REPORT DATE April 1968	7a. TOTAL NO. OF PAGES 32	7b. NO. OF REFS 1
8a. CONTRACT OR GRANT NO. DAAB07-57-C0296	9a. ORIGINATOR'S REPORT NUMBER(S) 7486-278	
b. PROJECT NO. IVC-25001-A126-01-14	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) ECOM-0296-2	
10. AVAILABILITY/LIMITATION NOTICES This document has been approved for public release and sale; its distribution is unlimited.		
11. SUPPLEMENTARY NOTES None	12. SPONSORING MILITARY ACTIVITY U.S. Army Electronics Command AMSEL-BL-TE Fort Monmouth, New Jersey 07703	
13. ABSTRACT Space and time variability studies were conducted for the 12-rain station mesonet network of southeastern Arizona. The space variability studies showed that for low levels (below 1000 meters) there was only a slight increase in variability as a function of station separation. The root-mean square space difference of the vector wind (RMSSD) is 8.0 knots for stations within 20 km of each other, while the RMSSD is 9.6 knots for stations 120-140 km apart. At high levels (e.g., 8000 m), the variability difference with distance is sizeable. Investigations of time variability indicated the increase in variability with increasing time lag is less at low levels than at high levels. At low levels (around 1000 m) there is not much difference between a 2-hr old observation and one that is 8 hours old. At about 8,000 meters, the variability increased markedly with increasing time lag. From time variability profiles this is seen to be the level of maximum time variability for all lags with the variability diminishing rapidly with height thereafter.		

DD FORM 1473
1 JAN 64

Security Classification

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT.	ROLE	WT.	ROLE	WT.
Ballistic Winds Time Variability of Ballistic Winds Space Variability of Ballistic Winds Mapping Techniques						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.
4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).
10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.