


AD 700 115

INVESTIGATIONS OF NEAR WAKE FLOW FIELD AND HEAT TRANSFER ON
TWO DIMENSIONAL AND AXIALLY SYMMETRIC BODIES AT SUPERSONIC
SPEEDS

Josef Rom

Technion - Israel Institute of Technology
Haifa, Israel

30 September 1969



This document has been approved for public release and sale.

AD700115

FINAL SCIENTIFIC REPORT

INVESTIGATIONS OF NEAR WAKE FLOW FIELD
AND HEAT TRANSFER ON TWO DIMENSIONAL
AND AXIALLY SYMMETRIC BODIES
AT SUPERSONIC SPEEDS.

1st September 1968 - 31st August 1969

JOSEF ROM

Technion - Israel Institute of Technology
Department of Aeronautical Engineering

Get AD#

~~DUPLICATE~~

EXCHANGE DOCUMENT
26 27 29 31
4 4 4 4



T. I. S. LIBRARY

RECEIVED
ALEX.A.
DEC 19 1968



חטפניון - מכון טכנולוגי לישראל
חפולטה לחניכה אירונוטית



TECHNION - ISRAEL INSTITUTE OF TECHNOLOGY
DEPARTMENT OF AERONAUTICAL ENGINEERING
HAIFA, ISRAEL

CLEARINGHOUSE

Contract : F 61052 69 C 0020

30 September 1969


FINAL SCIENTIFIC REPORT
INVESTIGATIONS OF NEAR WAKE FLOW FIELD
AND HEAT TRANSFER ON TWO DIMENSIONAL
AND AXIALLY SYMMETRIC BODIES
AT SUPERSONIC SPEEDS.

1st September 1968 - 31st August 1969

JOSEF ROM

Technion - Israel Institute of Technology
Department of Aeronautical Engineering

TAE REPORT No. 99



This document has been approved for public release and sale; its distribution is unlimited.

This research has been sponsored in part by the Aerospace Research Laboratories through the European Office of Aerospace Research (OAR) United States Air Force, under Contract F 61052 69 C 0050.

Abstract

This report summarizes some of the research carried out under contract F 61052-69-C-0020 during the year 1st September 1968 to 31st August 1969.

Laminar and transitional heat transfer rates were measured in various base type separated flows in the shock tube. It was found that maximum and average heat transfer rates are correlated by the parameter $(hRe_L^{1/2}/L)$ for models with an initial boundary layer and by Re_L for models with leading edge separation.

The application of the hot wire technique for measurements of the flow field in the supersonic near wake is studied. It is shown that using the measurements of a hot wire probe and a total pressure probe enable the determination of all the required physical parameters of the dissipative flow field in the near wake. The flow field behind a blunt two dimensional base model is measured at Mach number of 2.25 and $Re_L = 1.5 \times 10^6$. Mach number and total temperature profiles are determined and the various zones in the flow field are identified.

TABLE OF CONTENTS

| | <u>Page No</u> |
|--|----------------|
| Abstract | I |
| Table of Contents | II |
| List of Symbols | III |
| List of Figures | IV |
| I. Introduction | 1 |
| II. Heat transfer rate measurements in base type flows on the shock tube | 1 - 6 |
| III. Application of hot wire anemometer for supersonic near wake studies. | 7 - 10 |
| References | 11 - 13 |
| Tables | 14 - 15 |
| Figures | 16 - 36 |

LIST OF SYMBOLS

| | |
|------------|---|
| h | step height |
| Kn | Knudsen number |
| L | length of model ahead of separation, Hot-Wire length |
| M | Mach number |
| M_f | free stream flow Mach number over the model |
| M_s | shock Mach number |
| Nu | Nusselt number |
| Nu_x | local Nusselt number |
| Nu_m | measured Nusselt number |
| P_1 | initial pressure in the shock tube low pressure section |
| Pr | Prandtl number |
| q | local heat transfer rate |
| $q_{f.p.}$ | attached flow heat transfer rate |
| R_w | wire resistance |
| Re | Reynolds number |
| Re_h | Reynolds number based on h |
| Re_x | local Reynolds number |
| Re_L | Reynolds number at the separation position |
| T | temperature |
| t | time |
| V | voltage |
| x | local distance |
| Δx | distance from separation position |
| ρ | resistivity |
| δ_L | boundary layer thickness at separation |
| r | recovery temperature ration, T_{ad}/T_o |

LIST OF FIGURES

FIGURE No.

1. Models for heat transfer measurements
2. Time for establishment of steady conditions in the separated flows
3. $Nu_x / Pr Re_x^{1/2}$ as a function of $\Delta x/h$ for the two-dimensional step model
4. $Nu_x / Pr Re_x^{1/2}$ as a function of $\Delta x/h$ for the axisymmetric step model
5. $Nu_x / Pr Re_x^{1/2}$ as a function of $\Delta x/h$ for the sharp leading edge model
6. $Nu_x / Pr Re_x^{1/2}$ as a function of $\Delta x/h$ for the leading edge bubble model
7. $q/q_{f.p.}$ as a function of $hRe_L^{1/2}/L$
8. The hot-wire probes
9. A diagram of the measuring and recording system
10. Empirical correlation of cylinder heat-transfer at low Reynolds numbers
11. Reynolds number dependence on Mach number with Nusselt Number as a parameter
12. Recovery factor variation with Knudsen number
13. Flow chart of the data reduction stage 1
14. Flow chart of the data reduction stage 2
15. Typical results of a measurement with a hot-wire
16. Nusselt number distribution at $x = 13$ mm
17. Recovery Temperature distribution at $x = 13$ mm
18. Mach number distribution in the flow field
19. Total temperature distribution in the flow field
20. Shadow picture of the flow with a hot-wire probe
21. Flow field structure according to the present work
22. Mach number distribution along the center line and along the edge of the expansion fan

I. INTRODUCTION

The present report summarizes some of the research work carried out under contract F 61052 69 C 0020 during the year 1st September 1968 to 31st August 1969. This year's program included an extension of the heat transfer studies of base type flows in the shock tube which are discussed in Part II, as well as a program of near wake flow field study using the hot-wire anemometer discussed in Part III.

II. Heat transfer rate measurements in base type flows on the shock tube

Flow separation at supersonic and hypersonic speeds is known to have strong effects on the heat transfer rates to body surfaces particularly in the reattachment regions. In general, it was found that heat transfer rates are decreased in the "dead water" zone and increased in the reattachment zone in relation to flat plate heat transfer rates under similar flow conditions. The net effect of this variation of heat transfer on the heat transfer rate in the separated flow region as a whole is not easily determined since in many cases the increase in the heat transfer rate in the reattachment zone is much greater than the corresponding reduction found in the "dead water" zone. For the past several years, heat transfer rates in separated flows have been studied at the Aerodynamics Laboratory of the Technion's Aeronautical Department supported in part by EOAR contracts. These studies were conducted in the 3" x 3" shock tube and have included the following model configurations :

- (1) Two-Dimensional Backward Facing Step (Ref. 1).
- (2) Axisymmetric Backward Facing Step (Ref. 2).
- (3) Two-Dimensional Blunt Base (Ref. 3).

(4) Sharp Protruding Leading Edge (Ref. 4).

(5) Two-Dimensional Leading Edge Separation Bubble (Ref. 5).

In this report a summary of some of the more significant results of the previous studies is presented and is also correlated to determine the main parameters affecting the data.

The shock tube has been found to be a very useful facility for heat transfer studies. Using thin (or thick) film platinum resistance thermometers local heat transfer rates can be measured to an accuracy of better than $\pm 15\%$ and even up to $\pm 5\%$. These are as good as, and in many cases, even better accuracies than can be obtained in heat transfer measurements in conventional wind tunnels. The feasibility of measurements of heat transfer in separated flows in the shock tube and the shock tunnel was discussed by a number of investigators (Ref. 6, 7, and 8). Thus, based on measurements in the shock tube our previous results indicated that laminar heat transfer rates ~~in~~ⁱⁿ separated flows (with an attached boundary layer ahead of separation) can be correlated using the parameter $hRe_L^{1/2}/L$. This parameter is proportional to the ratio of step height to boundary layer thickness at separation, δ_L , and was found to correlate the laminar separated region pressure field as well. It is interesting to note that some measurements of the heat transfer rate distribution on various backward facing step models in a continuous supersonic wind tunnel reported in Ref. 9 support this correlation. Comparison of the shock tube data and the wind tunnel measurements reported in Ref. 9 are included in this paper. Although the flow conditions in the two experiments are very different, particularly the large differences in stagnation to wall temperature and the state of the boundary layer of

these experiments, the heat transfer rates in both experiments are found to be related by the parameter $hRe_L^{1/2}/L$.

The experimental apparatus and results are discussed in detail in Ref. 10. The main results are discussed herein. The variation of the local heat transfer rate along the model length as shown in Figs. 3, 4, 5 and 6 for various Mach numbers indicates that, for a given model, there is only slight variations in the position of the beginning of the reattachment zone and the point of the maximum local heat transfer rate as shock Mach varies from 5 to 10. Detection of any movement of these positions, however, was limited by gage size and location. Of importance is that all the curves exhibit qualitatively similar variations of local heat transfer rates. This similarity of the heat transfer rate distributions is found in spite of large variations (flow Mach numbers and stagnation to wall enthalpy ratios) as well as model geometry. With the exception of the leading edge separation bubble on the blunt nosed body, the heat transfer distribution over the sharp leading edge model, the backward facing step and the axisymmetric step models definitely show a zone of low heat transfer rate in the "dead water" zone. Following this is the reattachment zone as signified by a sharp rise in the heat transfer rate. It is expected that following reattachment the heat transfer rates would approach the flat plate values. In fact, many of the curves exhibit this tendency, however, in some cases, the gages available on the model were not sufficient to show this trend.

The extent of the low heat transfer rate zone in the "dead water" zone is found to be about 1 to 1.5 step heights from the two-dimensional and axisymmetric backward facing steps (Figs. 3 and 4) while it extends to about 4 step heights for the sharp leading edge model (Fig. 5). The maximum

transfer rate in the reattachment zone is found to occur at about 4 to 6 step heights for the two-dimensional and axisymmetric backward facing steps (Figures 3 and 4) and at about 8 step heights for the sharp leading edge model (Fig. 5). For the leading edge bubble case, closure of the bubble and reattachment is indicated at about 3 nose heights behind the leading edge (Fig. 6).

The results of wind tunnel measurements of the heat transfer rate distribution behind a backward facing step reported in Ref. 9 are also included. It is seen that the wind tunnel data seems to be extended so that the peak values of heat transfer rates are obtained after about 12 to 15 step heights while the shock tube data indicates that this occurs after about 4 to 6 step heights. On the other hand the results of Ref. 11, which are also obtained in the wind tunnel, show peak values at about 2 to 3 step heights. This does raise the question of whether or not these differences are dependent on errors due to the various experimental methods used. The heat transfer measurements in the wind tunnel require measurements of a number of physical parameters which must be corrected and are sensitive to errors, while the measurement of heat transfer in the shock tube involves a direct measurement of a single precalibrated transducer. Most separated flow measurements do indicate reattachment at 2 to 4 step heights therefore provide an additional support for the shock tube measurements.

The maximum heat transfer rate at reattachment is correlated by the use of the non-dimensional parameters as follows :

(1) in cases of an initial boundary layer at separation

$$q = A(hRe_L^{1/2}/L)^n \quad q_{f.p.}$$

(2) in cases of zero initial boundary layer at separation

(e.g. - sharp leading edge);

$$q = B \text{Re}_h^m \cdot q_{f.p.}$$

The empirical values of the parameters A and n and B and m for the various geometries are presented in Tables 1 and 2, respectively and in Fig. 7. The maximum heat transfer rate values obtained in the wind tunnel study of Ref. 9 are found to be in surprisingly good qualitative agreement with the shock tube data in spite of previous remarks and of the extreme differences in stagnation to wall enthalpy as well as state of flow. This seems to suggest that the heat transfer in laminar separated flow is not too sensitive to variations in flow Mach number (at least in the range of Mach number 1.5 to 3.0) and stagnation to wall enthalpy. The dominating parameter is found to be the value of $h \text{Re}_L^{1/2} / L$ for cases with initial laminar boundary layer thickness or Re_h for cases of zero boundary layer at separation. An additional important parameter seems to be the state of the boundary and mixing layers and the relative position of transition. It is suggested in our measurements and in those of Baker and Martin (Ref. 11) and actually demonstrated in the measurements of Sanford and Ginoux (Ref. 9) that when transition appears ahead of reattachment very high values of heat transfer rates at reattachment are experienced. In the completely laminar separation case the heat transfer rates are relatively low and even at reattachment the maximum values are not much larger than the corresponding attached flat plate values. In the completely turbulent case maximum values are in order of 2 to 4 times the attached flat plate value as found by Naysmith (Ref. 12) and Thomann (Ref. 13). However, in the transitional flow

cases, which we assume occurred in the shock tube tests at the higher Reynolds numbers, extremely high peak heat transfer rates of the order of 5 to 7 times the laminar flat plate values were detected. The measurements in Ref. 9 tend to support the explanation that these high heat transfer rates are associated with the movement of the transition point ahead of the reattachment position into the mixing layer. Therefore the present correlation may be taken to cover both the cases of completely laminar separation and transitional cases where the boundary layer is laminar ahead of separation and transition occurs at a position between separation and reattachment.

III. Application of hot wire anemometer for supersonic near wake studies

Determination of the physical parameters in the near wake flow require the measurements of at least three independent local physical quantities. In most previous wake flow measurements one physical parameter, e.g. - the total temperature has been assumed to be constant in the flow field. Measurements using the hot wire probe and a total pressure probe enable the determination of all the required physical parameters of the dissipative flow field in the near wake. Due to its relatively small dimensions, fast response and high signal to noise output the hot wire anemometer is particularly suitable for flow measurements in the wake. This part summarizes the method of measurements and data analysis for such measurements in the turbulent near wake behind a two-dimensional blunt base.

The measurements are conducted in the 10 cm x 10 cm supersonic wind-tunnel at Mach number 2.25 and Reynolds number based on model chord of 1.5×10^6 . The model is a wedge-flat plate with a blunt base and spans the wind-tunnel test section. The hot wire probe is a 0.005 mm platinum coated tungsten wire soldered to the two support needles. The wire length is about 1 mm (wire aspect ratio of about 200). Two probe geometries (Fig. 8) were tested in order to check the effects of these supports on the directional wire response in the recirculating flow. Both probe supports gave essentially identical response, so that this effect is found to be very small. The block diagram of the measuring system is shown in Fig. 9. Each probe is calibrated to determine its resistivity coefficient and is pretested in a calibration wind-tunnel. A detailed description of the experimental system is presented in Ref. 14.

The anemometer response is due to heat transfer from or to the probe's

wire from the flowing fluid. The analysis of the data requires finding a relation between the heat exchange coefficient, indicated by the wire Nusselt number, and the local Mach and Reynolds numbers of the flow. Empirical correlation of available data was presented in Ref. 15. For a constant temperature anemometer, used in the present investigation, the probe response is

$$Nu_w = \frac{r R_r}{r L R_o} \frac{d(V^2 / R_w)}{d(R_w - Ra_w)} \quad (1)$$

1 > 0

and the relation for $Nu(Re, M)$ is defined in Ref. 15 by relations of the form

$$Nu(Re, M) = Nu(Re, -) \phi(Re, M) \quad (2)$$

and is shown in Fig. 10. In a dissipative flow it is convenient to use a modified correlation of equation (2) writing the Mach number as a function of Nusselt and Reynolds numbers shown in Fig. 11.

The adiabatic temperature measurement is then corrected for the Knudsen and Mach numbers effects by the relation (Ref. 15)

$$n = n(M, Kn) \quad (3)$$

shown in Fig. 12.

Thus, the first stage in the data analysis is calculating for each measured hot wire output the local Nu_w and Taw_w , using the proper relations represented by equations (1), (2) and (3). These profiles are normalized by the free stream values in order to account for probe errors and losses. This calculation is performed on the Elliot 503 computer using the program shown in block diagram in Fig. 13.

The local Mach and Reynolds number profiles are evaluated from the previously determined Nu_m and Taw_m by an iteration procedure shown in a block diagram in Fig 14. For this calculation the local total pressure is obtained from previously measured pitot pressure profiles presented in Ref. 16.

The hot wire output at various wire overheat values is shown in Fig. 15. From these results the profiles of the Nusselt number and adiabatic temperatures are evaluated. Profiles of local Mach number and total temperature are then calculated using the pitot pressure data and the iteration procedure shown in Fig. 14. Typical profiles of Nu_m and Taw_m and of Mach number and T_t measured at about one base height behind the model are shown in Figures 16 and 17 respectively. A map of the Mach number and of the total temperature in the near wake is shown in Figures 18 and 19 respectively. A shadow photograph of the corresponding flow field is shown in Fig. 20. Using these measurements the various flow regions can be now specified as shown in Fig. 21.

It is found that there is an excellent correspondence between the hot wire measurements and flow field photographs in respect to the positions of the lip shock, trailing shock, expansion fan region, etc.

Furthermore, these measurements do show that the clearly seen bright white line emanating from the base corner does correspond to the position of peaks in the total temperature profiles. These peaks are found to be near the outer edge of the mixing zone. This may indicate a layer of high shear in this part of the mixing zone.

In the "dead water" zone the hot wire probe is sensitive to the absolute value of the local velocity with no regard to its direction. It is therefore interesting to note that Mach number values of about 0.4 to 0.6 are measured near the base. The Mach number variation on the wake center line is shown in Fig. 22. Near the reattachment zone the present iteration procedure failed to converge so that no Mach number values are available there. This effect may be due to either very high shear values at this zone (which cause erroneous probe output) or due to large flow inclination which results in considerable error in the total pressure measurements.

REFERENCES

1. Rom, J. and Seginer, A. - Laminar heat transfer to a two-dimensional backward facing step from the high enthalpy supersonic flow in the shock tube. AIAA Journal, Vol. 2, No. 2, Feb. 1964, pp. 251-255.
2. Rom, J. and Seginer, A. - Heat transfer in the laminar supersonic separated flow behind an axially symmetric backward facing step. Technion - Aeronautical Engineering Dept. TAE Report 82, Jan. 1968.
3. Rom, J. and Seginer, A. - Laminar heat transfer to a two-dimensional blunt base from the high enthalpy flow in the shock tube. Israel Journal of Technology, Vol. 5, No. 4, Feb. 1967.
4. Rom, J. and Seginer, A. - Laminar and transitional heat transfer in the two dimensional separated flow behind a sharp protruding leading edge. Technion - Aeronautical Engineering Dept. TAE Report 71, Aug. 1967.
5. Rom, J. and Seginer, A. - Laminar heat transfer to a two-dimensional blunt flat nosed body in transonic and supersonic flow. Technion - Aeronautical Engineering Dept. TAE Report 75, Sept. 1967.
6. Rabinowitz (Rom), J. - Measurement of turbulent heat transfer rates on the aft portion and blunt base of a hemisphere cylinder in the shock tube. Jet Propulsion, Vol. 28, No. 9, Sept. 1958, pp.651-620.
7. Rom, J. - Measurement of heat transfer rates in separated regions in a shock tube and in a shock tunnel. AIAA Journal, Vol. 1, No. 9, Sept. 1963, pp.2193-2194.
8. Holden, M.S. - Leading edge bluntness and boundary layer displacement effects on attached and separated laminar boundary layers in a compression corner. AIAA 6th Aerospace Science Meeting, Paper No. 68-60 Jan. 1968.

REFERENCES (CONT'D)

9. Sanford, J. and Ginoux, J.J. - Laminar transitional and turbulent heat transfer behind a backward facing step in supersonic flow. Von Karman Institute for Fluid Dynamics, Rhode-Saint Geneses, Belgium, Technical Note 38, October 1968.
10. Rom, J., Seginer, A., and Green, M. - Correlation of laminar and transitional heat transfer rates measured in base type separated flows in a shock tube. Technion - Israel Institute of Technology, Haifa, Israel, contract 61052-69-C-0020, Scientific Report No. 1, TAE Report 97, June 1969.
11. Baker, P.J. and Martin B.W. - Heat transfer in supersonic separated flow over a two-dimensional backward facing step. International Journal of heat and Mass Transfer, Vol. 9, 1966, pp. 1081-1088.
12. Naysmith, A. - Measurements of heat transfer in bubbles of separated flow in supersonic air streams. ASME and Inst. of Mechanical Engineers, London, International Heat Transfer Conference, Part II, 43, 378, (1961).
13. Thomann, H. - Measurements of heat transfer and recovery temperature in a separated flow in a Mach number of 1.8. FFA Rept. 82, 1959.
14. Volfman D. - Application of hot wire anemometer for supersonic near wake studies. M.Sc. Thesis, Technion Aeronautical Engineering Department, 1969.
15. Dewey C.F. - A correlation of convection heat transfer and recovery temperature data for cylinders in compressible flow. International Journal of Heat and Mass Transfer. 1965, pp. 245-252.

REFERENCES (CONT'D)

16. Rom, J., Kronzon, Y., and Seiginer, A. - The velocity, pressure and temperature distribution in the turbulent supersonic near wake behind a two-dimensional wedge-flat plate model. Israel Journal of Technology vol. 6, No. 1-2, 1968, pp. 84-94.

TABLE 1.

AVERAGE AND MAXIMUM HEAT TRANSFER RATE PARAMETERS FOR CASES WITH INITIAL BOUNDARY

LAYER.

$$q = A(hRe_L^{1/2}/L)^n q_{f.p.}$$


| | $q_{ave}/q_{f.p.}$ | | $q_{max}/q_{f.p.}$ | |
|---|--------------------|------|--------------------|-----|
| | A | n | A | n |
| Two-Dimensional Backward Facing Step | 0.02 | 1.2 | 0.0465 | 1.3 |
| Axially Symmetric Backward Facing Step | 0.037 | 1.0 | 0.068 | 1.0 |
| Two-Dimensional Blunt Base | 0.018 | 0.77 | 0.034 | 0.7 |

TABLE 2.


AVERAGE AND MAXIMUM HEAT TRANSFER RATE PARAMETERS FOR CASES WITH ZERO BOUNDARY LAYER AT SEPARATION

$$q = B Re_h^m q_{f.p.}$$


| | $q_{ave}/q_{f.p.}$ | | $q_{max}/q_{f.p.}$ | |
|-----------------------------------|--------------------|------|--------------------|------|
| | B | m | B | m |
| Sharp Protruding Leading Edge | 0.04 | 0.27 | 0.057 | 0.34 |
| Leading Edge Separation Bubble | 0.0057 | 0.45 | 0.0076 | 0.45 |




BACKWARD FACING STEP




AXISYMMETRIC STEP



BLUNT BASE



SHARP LEADING EDGE



LEADING EDGE BUBBLE

ALL DIMENSION - MILLIMETERS
 FIGURES NOT DRAWN TO SCALE

FIG. 1: Models for heat transfer measurements




FIG. 2: Time for establishment of steady conditions in the separated flows




FIG. 9 $\frac{Nu_x / Pr}{\sqrt{Re_x}}$ as a function of $\Delta x/h$ for the two-dimensional step model




FIG. 4: $Nu_x / Pr Re_x^{1/2}$ as a function of $\Delta X/h$ for the axisymmetric step model




FIG. 5: $Nu_x/Pr \cdot Re_x^{-1/2}$ as a function of x/h for the sharp leading edge model




FIG. 6: $Nu_x/Pr Re_x^{1/2}$ as a function of $\Delta x/h$ for the leading edge bubble model




FIG. 7: $q/q_{f.p.}$ as a function of $hRe_L^{1/2}/L$





FIG. 8 HOT WIRE PROBES




FIG. 9 A diagram of the calibration system in sub-sonic flow




FIG. 10 Empirical correlation of cylinder heat-transfer at low Reynolds numbers




FIG. 11 Reynolds number dependence on Mach number with Nusselt Number as a parameter




FIG. 12 Recovery factor variation with Knudsen number




FIG. 13 Flow chart of the Data Reduction Stage 1.




FIG. 15 Typical results of a measurement with a Hot-Wire




FIG. 16 Nusselt number distribution at $x = 13 \text{ mm}$




FIG. 17 Recovery Temperature distribution at $x = 13 \text{ mm}$




fig. 18 Mach number distribution in the flow field




fig 10 Total temperature distribution in the flow field



FIG. 20 Shadow picture of the flow with Hot-Wire probe




FIG 21 FLOW FIELD $M = 2.25$ ACCORDING TO THE PRESENT WORK

— PRESENT WORK
 - - - KRONZON (9)




FIG 22. MACH NUMBER DISTRIBUTION ALONG THE CENTERLINE AND AT THE END OF THE EXPANSION FAN

~~Unclassified~~
Security Classification

| DOCUMENT CONTROL DATA - R&D | | |
|---|--|-----------------------------------|
| <i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i> | | |
| 1 ORIGINATING ACTIVITY (Corporate author) | | 2a REPORT SECURITY CLASSIFICATION |
| TECHNION RESEARCH AND DEVELOPMENT FOUNDATION AERONAUTICAL ENGINEERING LABORATORY, HAIFA, ISRAEL. | | Unclassified |
| | | 2b GROUP |
| 3 REPORT TITLE | | |
| INVESTIGATIONS OF NEAR WAKE FLOW FIELD AND HEAT TRANSFER ON TWO DIMENSIONAL AND AXIALLY SYMMETRIC BODIES AT SUPERSONIC SPEEDS. | | |
| 4 DESCRIPTIVE NOTES (Type of report and inclusive dates) | | |
| Final Scientific Report | | |
| 5 AUTHOR(S) (Last name, first name, initial) | | |
| Dom, Josef | | |
| 6 REPORT DATE | 7a TOTAL NO OF PAGES | 7b NO OF REFS |
| September 1969 | 24 | 16 |
| 8a CONTRACT OR GRANT NO | 9a ORIGINATOR'S REPORT NUMBER(S) | |
| F61052-69-C-0020 | TAE Report No. 99 | |
| b PROJECT NO | 9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) | |
| 7063 | | |
| c | | |
| 61102F | | |
| d | | |
| 681307 | | |
| 10 AVAILABILITY/LIMITATION NOTICES | | |
| This document has been approved for public release and sale; its distribution is unlimited. | | |
| 11 SUPPLEMENTARY NOTES | 12 SPONSORING MILITARY ACTIVITY | |
| TECH OTHER | AEROSPACE RESEARCH LABORATORIES (ARN) WRIGHT-PATTERSON, AFB, OHIO, 45433. | |
| 13 ABSTRACT | | |
| <p>This report summarizes some of the research carried out under contract F 61052-69-C-0020 during the year 1st September 1968 to 31st August 1969.</p> <p>Laminar and transitional heat transfer rates were measured in various base type separated flows in the shock tube. It was found that maximum and average heat transfer rates are correlated by the parameter $(hRe_L^{1/2}/L)$ for models with an initial boundary layer and by Re_h for models with leading edge separation.</p> <p>The application of the hot wire technique for measurements of the flow field in the supersonic near wake is studied. It is shown that using the measurements of a hot wire probe and a total pressure probe enable the determination of all the required physical parameters of the dissipative flow field in the near wake. The flow field behind a blunt two dimensional base model is measured at Mach number of 2.25 and $Re_L = 1.5 \times 10^6$. Mach number and total temperature profiles are determined and the various zones in the flow field are identified.</p> | | |

DD FORM 1473

~~Unclassified~~
Security Classification

| 14 KEY WORDS | LINK A | | LINK B | | LINK C | |
|-------------------------------------|--------|----|--------|----|--------|----|
| | ROLE | WT | ROLE | WT | ROLE | WT |
| 1. Laminar Heat Transfer Rates | | | | | | |
| 2. Transitional Heat Transfer Rates | | | | | | |
| 3. Basic Type Separated Flow | | | | | | |

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.