

AD

AD 711983

USAAVSCOM TECHNICAL REPORT 70-9

UH-1B/D ARMORED HELICOPTER SEAT TEST PROGRAM

BY

W.H. REED

D.F. CARROLL

V.E. ROTHE


FEBRUARY 1966

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield Va. 22151

U.S. ARMY AVIATION SYSTEMS COMMAND
ST. LOUIS, MISSOURI

CONTRACT DA23-204-AMC-03825(T)
AVIATION SAFETY ENGINEERING AND RESEARCH
A DIVISION OF FLIGHT SAFETY FOUNDATION, INC.
PHOENIX, ARIZONA

Distribution of this
document is unlimited.



This document has been approved
for public release and sale; its
distribution is unlimited.


NOTICE TO USERS

Portions of this document have been judged by the Clearinghouse to be of poor reproduction quality and not fully legible. However, in an effort to make as much information as possible available to the public, the Clearinghouse sells this document with the understanding that if the user is not satisfied, the document may be returned for refund.

If you return this document, please include this notice together with the IBM order card (label) to:

Clearinghouse
Attn: 152.12
Springfield, Va. 22151

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST
QUALITY AVAILABLE. THE COPY
FURNISHED TO DTIC CONTAINED
A SIGNIFICANT NUMBER OF
PAGES WHICH DO NOT
REPRODUCE LEGIBLY.

REPRODUCED FROM
BEST AVAILABLE COPY

UH-1D/UH-1B/D ARMORED HELICOPTER

SEAT TEST PROGRAM

CONDUCTED FOR AERJET GENERAL CORPORATION

UNDER U. S. ARMY

CONTRACT DA 23-204-AMC-03825(T)

A-588 REPORT NO. M66-7

2 February 1966

Poor copy throughout. Refer
questions to source.

William H. Reed

Prepared: William H. Reed

Donald F. Carroll

Reviewed: Donald F. Carroll

Victor E. Rife

Approved: Victor E. Rife

UH-1B/D ARMORED SEAT TEST PROGRAM
VERTICAL DROP TEST SERIES NUMBER THREE

INTRODUCTION

The Aerojet-General Corporation is engaged in the development of an armored crew seat for the Bell UH-1B/D series helicopters. It is required that the armored seat developed in this program protect the seat occupant against impact at least as well as the standard UH-1D crew seat. To show compliance with this requirement, a test program was initiated in May 1965 during which the armored seat and a standard UH-1D crew seat were subjected to controlled vertical impacts. Measurements of the vertical accelerations applied to the seats and their occupants were recorded. Study of the recorded data and high-speed motion pictures provided a basis for comparison of the dynamic response of the seat-occupant systems and the forces transmitted to the seat occupants.

This report presents the results of two tests of a redesigned armored crew seat conducted 27 January 1966 by Aviation Safety Engineering and Research (AvSER), a Division of Flight Safety Foundation, Incorporated. The results of this series of tests are compared with the results of the first series of tests completed 21 May 1965

The results of the first series of tests conducted under this program are presented in AvSER Report M65-24, 4 June 1965. The second test series is reported in AvSER Report M66-1, 18 January 1966.

TEST OBJECTIVES

The objectives of this test series were:

1. To determine the response of a redesigned armored crew seat under 15G and 5G vertical impact conditions.
2. To compare the response of the redesigned armored seat with the response of a standard UH-1D crew seat tested in May 1965 under the same conditions.

TEST PROCEDURES

The following procedures were followed to conduct this test series.

1. The AvSER vertical drop tower facility was modified to accept the single test article. This modification included the addition of ballast weight to bring the total weight of the drop cage and test articles to 1,680 pounds. This ballast compensated for the weight of the UH-1D seat and dummy installed in the first test series. Of this weight, the armored seat accounted for approximately 137 pounds, the dummy occupant 186 pounds, and the drop cage and ballast weighed 1,357 pounds.
2. Instrumentation transducers were installed on the drop cage, on the seat frame, and in the dummy occupant.

NOT REPRODUCIBLE

3. Two high-speed movie cameras (500 frames per second) were installed, providing a front view and a 45° side view of the seat and dummy during the tests.
4. The armored seat and dummy occupant were installed in the drop cage and two drop tests were conducted.

TEST CONDITIONS

The test conditions specified by Aerojet General called for vertical impacts at the following acceleration levels:

Test No. 1 - 15G peak deceleration, half sine wave pulse,

0.05 second duration

Test No. 2 - 5G peak deceleration, half sine wave pulse,

0.05 second duration.

TEST INSTRUMENTATION

Transducers

The transducers used in this test series were Statham Instruments Model A5 accelerometers. These are strain gage type instruments which provide a frequency response in excess of 200 cycles per second. Transducers were installed at the following locations to measure vertical deceleration:

1. Drop Cage Frame
2. Armored Seat Frame - Right
3. Armored Seat Frame - Left

4. Armored Seat Occupant - Pelvic

5. Armored Seat Occupant - Head

NOT REPRODUCIBLE

Electronic Data Recording System

The measurements listed above were recorded on a magnetic tape recording system. This system utilizes a constant bandwidth FM/FM multiplex modulation technique in which the analog signal from the transducer is converted by a subcarrier oscillator into a frequency deviation proportional to the input signal amplitude. Seven of these subcarrier oscillator outputs are combined in a mixer amplifier and the resulting composite signal is then recorded on one track of a 14-track tape recorder. In this test series the data obtained from each test was recorded on one track of the tape recorder.

Electronic Data Processing System

The data recorded on the data recording system was recovered by utilizing a compatible data processing system. In this system a tape playback machine removes the composite signal from each track of the test tape and processes it through a series of FM discriminators. These discriminators separate the composite signal into various subcarrier frequency deviations. These frequency deviations are then converted to an analog signal which is recorded on an oscillograph plotter. The resulting oscillograph record is then available as an analog time history plot of the recorded parameter.

NOT REPRODUCIBLE

Photo Instrumentation

Photographic instrumentation was provided by two Photosonics 1B 16 mm motion picture cameras operating at approximately 500 frames per second. Timing and correlation was provided to aid in analyzing the motions of the seat and occupant and correlating this motion with the accelerations measured during each test.

TEST RESULTS

General

Examination of the results of these two drop tests indicates that the data from these tests are comparable with the data obtained from the earlier test series. Measurable permanent deformation of the seat structure occurred during the 15G test. This deformation was slight, however, and did not detract from the protection afforded the occupant in this test series. In both tests of this series the occupant remained upright and well restrained.

A summary of the data obtained from these tests, along with a summary of the data from the earlier tests is presented in Table I.

Pre- and post-test photographs of Test No. 1 are presented in Figures 1 through 6. These photographs are considered typical of the complete series. The acceleration-time histories of the data recorded during this test program is presented in Figures 7 through 11.

The acceleration-time histories of the data recorded during the January 1966 test program is presented in Appendix A. Appendix B contains the accelerometer data recorded during the May 1965 test series.

Data Analysis - Test No. 1 (15G Acceleration)

The input acceleration pulse (drop cage acceleration) achieved in this test is similar to the input acceleration in the May 1955 15G test, so that a comparison may be made between the results of this test and the earlier one.

Figure 7 presents superimposed curves showing data obtained from the 15G tests of each test series. Measurements of drop cage acceleration, seat acceleration, and occupant pelvic acceleration are included, to provide direct comparison of the results obtained from the three tests.

The armored seat occupant experienced a single acceleration pulse with a peak acceleration of 49G and a mean acceleration of 31G.

Because of the increased rate of onset and the high maximum acceleration, this acceleration environment would likely produce a more severe effect upon a human occupant than the occupant accelerations experienced in either of the 15G tests in the first two test series.

(Reference acceleration-time curves in Figure 7 and the Appendices.)

This test produced more deformation of the armored seat support structure than was experienced in earlier tests, also, indicating that loads developed in this test approach the structural limits for this seat. The most obvious deformation which indicated impending structural failure was forward bending of the right aft vertical support tube. The seat was raised to its highest position

for this test, and the support tube bent at the location of the highest exposed vertical positioning hole. This bending can be seen in Figure 4. Two cracks appeared in the right (sliding) side armor plate lower support bracket as shown in Figures 5 and 6, and this armor panel came out of the upper slide, but remained in place.

The right forward corner of the seat pan was permanently deflected downward $1-1/16$ inches and the left corner was permanently deflected downward $13/16$ inch. The dummy occupant settled downward in the seat enough (approximately $3/4$ inch) to allow approximately $1-1/2$ inches of slack in the lap belt. This permanent downward deflection is beneficial as an energy absorption mechanism for vertical impacts. The downward settling of the dummy must be controlled, however, so that slack does not develop in the occupant restraint harness which can add to amplification of occupant accelerations in combined vertical and longitudinal acceleration environments.

The severity of the acceleration experienced by the occupant in this test serves to point up the need for high capacity energy absorption to provide adequate occupant protection under even moderately severe impact conditions.

Data Analysis - Test No. 2 (5G Acceleration)

The 5G acceleration level test was performed after the 15G test in this section. The test conditions for this test were very similar

to the input for earlier tests. Occupant pelvic acceleration was less severe in this test than acceleration of the standard UH-1D seat occupant in the earlier test and approximately equivalent to the armored seat occupant accelerations in the earlier tests. The vertical acceleration environment was definitely within tolerable limits.

The seat was damaged in the 15G drop test which preceded this test, as mentioned earlier, but maintained enough load carrying capacity to prevent further deformation in this drop.

DISCUSSION OF TEST RESULTS

The armored crew seat tested in these two drop tests is similar to the seat tested on 11 January 1966 (second test series). The seat pan was changed to provide increased energy absorption.

Analysis of the test results indicates that the protection offered by this seat at low acceleration levels is adequate. At the higher acceleration level, however, this seat did not protect the occupant as well as the seat tested on 11 January 1966 (second test series). The protection offered by the revised seat was however comparable to that offered by the standard UH-1D crew seat.

Test Condition	Accelerometer Location	First Test Series (May 1965)		Second Test Series (January 11, 1966)		Third Test Series (January 27, 1966)	
		Mean "G"	Peak "G"	Mean "G"	Peak "G"	Mean "G"	Peak "G"
5G Acceleration Drop Height 1 Ft. Vertical Velocity 10 Ft./Sec.	Drop Cage	5	11	4	15	5	10
	Standard UH-1D Seat (Left)	6	12				
	Standard UH-1D Seat (Right)	5	12				
	Standard Seat Dummy Pelvic	8	14				
	Standard Seat Dummy Head	7	11				
	Armored Seat (Left)	7	15	5	18	4	11
	Armored Seat (Right)	5	11	5	14	4	11
	Armored Seat Dummy Pelvic	10	21	6	11	6	10
	Armored Seat Dummy Head	11	28	6	10	6	10
10G Acceleration Drop Height 4 Ft. Vertical Velocity 16 Ft./Sec.	Drop Cage	10	18	11	17		
	Standard UH-1D Seat (Left)	11	23				
	Standard UH-1D Seat (Right)	10	24				
	Standard Seat Dummy Pelvic	15	27				
	Standard Seat Dummy Head	12	23				
	Armored Seat (Left)	11	24	10	26		
	Armored Seat (Right)	10	18	8	23		
	Armored Seat Dummy Pelvic	13	27	15	28		
	Armored Seat Dummy Head	13	38	16	29		
15G Acceleration Drop Height 9 Ft. Vertical Velocity 24 Ft./Sec.	Drop Cage	15	22	15	27	14	27
	Standard UH-1D Seat (Left)	14	30				
	Standard UH-1D Seat (Right)	14	32				
	Standard Seat Dummy Pelvic	22	51				
	Standard Seat Dummy Head	20	30				
	Armored Seat (Left)	14	35	13	35	14	36
	Armored Seat (Right)	12	25	16	31	14	30
	Armored Seat Dummy Pelvic	15	50	23	43	31	49
	Armored Seat Dummy Head	15	30	30	50	30	47

TABLE I. SUMMARY OF ACCELEROMETER DATA

NOT REPRODUCIBLE




Figure 1. Left Side View of Armored Seat and Occupant, Pre-Test.





Figure 2. Orienting Left Front View of Armored Seat and Occupant, Pre-Test.



NOT REPRODUCIBLE

Figure 3. Left Side View of Armored Seat and Occupant After Test 1.




Figure 4. Front View of Armored Seat and Occupant After Test 1. (Bent right aft vertical support tube shown just below seat pan between legs of dummy.)

NOT REPRODUCIBLE




Figure 5. Cracked Sliding Armor Lower Support Bracket, Following Test 1. (Notice slack lap belt.)



Figure 6. Second Crack in Sliding Armor Lower Support Bracket, Following Test 1.






Figure 7. UH-1B/D Armored Seat Test No. 1 With Results of May 1965 and January 11, 1966 Tests Superimposed.





Figure 9. UH-1B/D ARMORED SEAT TEST NO. 1
THIRD TEST SERIES.




Figure 8. UH-1B/D ARMORED SEAT TEST NO. 1
THIRD TEST SERIES.




Figure 10. UH-1B/D ARMORED SEAT TEST NO. 2
THIRD TEST SERIES.





Figure 11. UH-1B/D ARMORED SEAT TEST NO. 2
THIRD TEST SERIES.

APPENDIX A
OSCILLOGRAPH DATA RECORDED DURING
SECOND TEST SERIES - JANUARY 1966






Figure A1. UH-1B/D ARMORED SEAT TEST NO. 1





Figure A2. UH-1B/D ARMORED SEAT TEST NO. 1






Figure A3. UH-1B/D ARMORED SEAT TEST NO. 2.





Figure A4. UH-1B/D ARMORED SEAT TEST NO. 2.




Figure A5. UH-1B/D ARMORED SEAT TEST NO. 3.





Figure A6. UH-1B/D ARMORED SEAT TEST NO. 3.

APPENDIX B
OSCILLOGRAPH DATA RECORDED DURING
FIRST TEST SERIES - MAY 1965




Figure B1. UH-1B/D SEAT TEST NO. 1.






Figure B2. UH-1B/D SEAT TEST NO. 1.






Figure B3. UH-1B/D SEAT TEST NO. 1.




Figure B'. UH-1B/D SEAT TEST NO. 2.




Figure B5. UH-1B/D SEAT TEST NO. 2.





Figure B6. UII-1B/D SEAT TEST NO. 2.




Figure B7. UH-1B/D SEAT TEST NO. 2.





Figure B8. UH-1B/D SEAT TEST NO. 3.





Figure B9. UH-1B/D SEAT TEST NO. 3.





Figure B10, UH-1B/D SEAT TEST NO. 3.





Figure B11. UH-1B/D SEAT TEST NO. 3.




Figure B12. UH-1B/D SEAT TEST NO. 3.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Aviation Safety Engineering and Research Division of Flight Safety Foundation, Inc Phoenix, Arizona		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE UH-1B/D Armor Helicopter Seat Test Program			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Final Report 27 January 1966			
5. AUTHOR(S) (Last name, first name, initial) Rothe, Victor E. Reed, William H. Carrol, Donald F.			
6. REPORT DATE February 1966	7a. TOTAL NO. OF PAGES 37	7b. NO. OF REFS 0	
8a. CONTRACT OR GRANT NO. DA23-204-AMC-03825(T)	9a. ORIGINATOR'S REPORT NUMBER(S) USAAVSCOM's Technical Report 70-9		
b. PROJECT NO. c. d.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) AVSER 66-7		
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY U.S. Army Aviation Systems Command St. Louis, Missouri	
13. ABSTRACT The dynamic response of the redesigned armored seat is compared to the dynamic response of the unarmored seat tested under the same conditions.			

DD FORM 1473
1 JAN 64

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBERS: If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words, but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

Security Classification