

AD 718443

NCL 71-8R

CARBON MONOXIDE LASER
SEMI-ANNUAL TECHNICAL REPORT
31 January 1971

Office of Naval Research
Contract No. N00014-71-C-0037
1 August 1970 to 31 ~~July 1961~~
Jan. 1971

Prepared by
Electromagnetics Laboratory
Northrop Corporate Laboratories

Sponsored by
Advanced Research Projects Agency
Order No. 306

Principal Investigator:

Dr. M. L. Bhaumik
Tel: (213) 675-4611,
Extension ~~4825~~

Scientific Officer
Director, Physics Programs
Physical Sciences Division
Office of Naval Research
Department of the Navy
Arlington, Virginia 22217

DDC
RECEIVED
FEB 18 1971
B

Amount of Contract \$59,986

The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Advanced Research Projects Agency or the U. S. Government

NORTHROP CORPORATE LABORATORIES
3401 West Broadway
Hawthorne, California 90250

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
Springfield, Va. 22151

SEMI-ANNUAL TECHNICAL REPORT
Contract N00014-71-C-0037

In this reporting period, the small signal gain coefficient and spectral characteristics of an electrically excited room-temperature CO laser have been investigated for the purpose of understanding the role of the necessary gas constituents and the possible excitation mechanisms involved.

The room temperature operation is possible only with higher partial pressures of the major constituents as compared to those at 77°K. The need for a higher partial pressure of CO at 20°C seems to be simply to compensate for the reduction in gain with increasing temperatures. A 6:1 ratio of N₂ to CO is also found to be necessary, while the optimum ratio at 77°K is nearly 1:1. The higher ratio of N₂ at 20°C seems to be needed primarily to shield the CO molecules against decomposition by collision with highly energetic electrons. The oxygen concentration necessary for room-temperature operation of the CO laser is critical since any excess of oxygen would help form an undesirable amount of CO₂.

The typical output spectrum of the CO laser at 20°C is given in Table I. The higher quantum numbers of the rotational lines, as compared to those observed at 77°K, are consistent with the theory of a molecular laser. The disappearance of the lower vibrational bands below the 9-8 band is a special feature of the room temperature operation. Since the vibrational temperatures are not expected to change drastically with the molecular kinetic temperature, the vibrational bands 6-5, 7-6, 8-7 which are present at 77°K should normally be expected at room temperature. This discrepancy may be explained in terms of the anharmonic decoupling, which seems to be a characteristic of a diatomic molecular laser with small anharmonicity.

The appearance of more than one rotational line in any particular vibrational band is a result of cascading. This is clearly established by a study of the time resolved spectroscopy of the CO laser. The gradual decrease of the rotational quantum number with increasing vibrational quantum number also lends support to cascading.

Semi-Annual Technical Report
Contract N00014-71-C-0037

The preliminary results of gain measurements of the optimum mixture for the room temperature CO laser has been obtained. The small signal gain for the strongest line in the absence of cascading has been measured to be 15% per meter. The actual gain in the presence of cascading must be higher, since the optimum coupling necessary for room temperature operation of a laser with a one meter discharge tube is nearly 15%.

The gain measurement and the spectral studies are being continued for the various lines and at different temperatures. Plans are being made for the measurement of vibrational relaxation rates.

TABLE I - SPECTRAL OUTPUT (IN μm) OF CO LASER AT 20°C

λ Obs. (Air)	λ Theo. (Air)	ν cm^{-1}	Vibrational Band	Transition	Rel. Intensity
5.3155	5.3152	1880.897	8-7	P(20)	80
5.3275	5.3273	1876.629		P(21)	9
5.3397	5.3395	1872.329		P(22)	10
5.3871	5.3876	1855.615	9-8	P(20)	100
5.3993	5.3999	1851.382		P(21)	16
5.4487	5.4494	1842.821	10-9	P(17)	52
		1834.577		P(19)	
5.5131	5.5127	1813.514	11-10	P(18)	17
5.5256	5.5252	1089.416		P(19)	1.8
5.5901	5.5901	1788.398	12-11	P(18)	2.2
5.6027	5.6028	1784.334		P(19)	0.9
5.6559	5.6567	1767.359	13-12	P(17)	0.3
5.6688	5.6695	1763.363		P(18)	0.5
5.6819	5.6825	1759.334		P(19)	--
5.6991	5.6996	1754.060	14-13	P(14)	0.3

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) NORTHROP CORPORATE LABORATORIES 3401 WEST BROADWAY HAWTHORNE, CALIFORNIA 90250		20. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		25. GROUP -	
3. REPORT TITLE CARBON MONOXIDE LASER SEMI-ANNUAL TECHNICAL REPORT			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) SEMI-ANNUAL			
5. AUTHOR(S) (First name, middle initial, last name) BHAUMIK, M. L.			
8. REPORT DATE 31 JANUARY 1971		7a. TOTAL NO. OF PAGES 4	7b. NO. OF REFS NONE
8a. CONTRACT OR GRANT NO. Contract N00014-71-C-0037		9a. ORIGINATOR'S REPORT NUMBER(S) NCL 71-8R	
8b. PROJECT NO. ARPA Order No. 306		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) NONE	
10. DISTRIBUTION STATEMENT NONE			
11. SUPPLEMENTARY NOTES NONE		12. SPONSORING MILITARY ACTIVITY Office of Naval Research Department of Navy Arlington, Virginia 22217	
13. ABSTRACT The small signal gain coefficient and spectral characteristics of an electrically excited room-temperature CO laser have been investigated for the purpose of understanding the role of the necessary gas constituents and the possible excitation mechanisms are discussed.			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
CO Laser Lasers Spectroscopy Studies						