COPY NO. 28

TECHNICAL REPORT 4300

AERODYNAMIC CHARACTERISTICS AND SUBSONIC FLIGHT PERFORMANCE OF THE SPIN-STABILIZED, 4.2 INCH M329A1E1 MORTAR PROJECTILE

AD 746977

R. KLINE
W. GAZDAYKA

DDC
RETRIEVED
AUG 23 1972

JUNE 1972

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
U S Department of Commerce
Springfield VA 22151

PICATINNY ARSENAL
DOVER, NEW JERSEY

The findings in this report are not to be construed as an official Department of the Army position.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Picatinny Arsenal, Dover, New Jersey 07801	2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED 2b. GROUP

3. REPORT TITLE

AERODYNAMIC CHARACTERISTICS AND SUBSONIC FLIGHT PERFORMANCE OF THE SPIN-STABILIZED 4.2 INCH M329A1E1 MORTAR PROJECTILE

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

5. AUTHOR(S) (First name, middle initial, last name)

R. Kline
W. Gazdayka

6. REPORT DATE	7a. TOTAL NO. OF PAGES 443	7b. NO. OF REFS 9
8a. CONTRACT OR GRANT NO. b. PROJECT NO. c. AMCMS Code 4810.16.2222.6 d.	9a. ORIGINATOR'S REPORT NUMBER(S) Technical Report 4300 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	

10. DISTRIBUTION STATEMENT

Approved for public release; distribution unlimited.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY

13. ABSTRACT

An extensive study of the aerodynamic characteristics of the 4.2" M329A1E1 Mortar Projectile has been conducted. A spectrum of yaw levels up to 40° and Mach numbers from 0.55 to 1.025 were covered in the Ballistic Research Laboratories (BRL) Transonic Range Facility. A Magnus wind tunnel test in the Ames 12' Pressure Wind Tunnel involved boom and boattail effects on Magnus as well as static forces from moments. Mach numbers from 0.3 to 0.95 and angles of attack from 0° to 30° (for a Mach number of 0.3) and 0° to 20° (for the higher Mach numbers) were considered. Shells instrumented with yaw sondes were fired at Wallops Island Facility of NASA. The theoretical differential equation of motion then was fitted to the resulting single plane angular motion data.

DD FORM 1 NOV 68 1473 REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED
Security Classification

I a

433

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Spin stabilized projectiles Aeroballistic characteristics Yaw sondes Transonic wind tunnel tests Transonic free flight range data Aerodynamic coefficients						

Technical Report 4300

AERODYNAMIC CHARACTERISTICS AND SUBSONIC FLIGHT PERFORMANCE OF THE SPIN-STABILIZED, 4.2 INCH M329A1E1 MORTAR PROJECTILE

by

R. Kline
W. Gazdayka

JUNE 1972

Approved for public release; distribution unlimited.

AMCMS Code 4810.16.2222.6

Engineering Sciences Division
Feltman Research Laboratory
Picatinny Arsenal
Dover, N.J.

IC

The citation in this report of the trade names of commercially available products does not constitute official indorsement or approval of the use of such products.

TABLE OF CONTENTS

	Page No.
Abstract	1
Introduction	2
Test Facilities	2
BRL Transonic Range	2
NASA Ames 12' Pressure Wind Tunnel	3
Performance Flight Tests	4
Yaw Sonde Program	4
Experimental Procedure	5
BRL Transonic Range	5
NASA Ames 12' Pressure Wind Tunnel	5
Performance Flight Tests	6
Yaw Sonde Program	6
Data Reduction Techniques	7
BRL Transonic Range	7
NASA Ames 12' Pressure Wind Tunnel	7
Performance Flight Tests	7
Yaw Sonde Program	7
Presentation of Test Results	7
BRL Transonic Range	7
NASA Ames 12' Pressure Wind Tunnel	7
Performance Flight Tests	8
Discussion and Analysis (BRL Range and Ames Wind Tunnel)	9
Pitching Moment Coefficient Derivative (C_{m_α})	9

Magnus Moment Coefficient Derivative ($C_{n_{p\alpha}}$) 10

Drag Coefficient (C_D) 10

Pitching Damping Coefficient ($C_{m_q} + C_{m_{\dot{\alpha}}}$) 11

Gyroscopic Stability 11
Dynamic Stability 11

Discussion and Analysis (Yaw Sondes) 13

Conclusions and Recommendations 14

References 14

Distribution List 431

Tables

1 Physical characteristics and launch conditions of M329A1E1 yaw sonde rounds 16

2 Ballistic Research Laboratories' range coefficients 17

Figures

1 4.2" M329A1E1 mortar projectile (all dimensions in calibers) 19

2 4.2" M329A1 projectile 20

3 Operating characteristics of the Ames 12' pressure wind tunnel (PWT) 21

4 Configuration NBT_1C_o mounted in 12' PWT 22

5 M329A1E1 projectile equipped with yaw sonde 23

If

6	Raw data chart from 12' PWT (pitch gauge readings vs model rpm)	24
7	Raw data chart from 12' PWT (yaw gauge readings vs model rpm)	25
8	Camera coverage for low charge high quadrant elevation firing of M329A1E1 projectile at Yuma Proving Ground	26
9	Normal force coefficient derivative vs angle of attack (BRL transonic range)	27
10	Pitching moment coefficient derivative vs angle of attack (BRL transonic range)	28
11	Pitch damping coefficient ($C_{m_q} + C_{m_{\dot{\alpha}}}$) and Magnus moment coefficient derivative vs angle of attack (BRL transonic range)	29
12-157	Normal force coefficient, pitching moment coefficient, and normal force center of pressure vs angle of attack. (Includes several configurations, Mach numbers, pd/2V's and Reynolds numbers [12' PWT].)	31-177
158-333	Magnus force coefficient, Magnus moment coefficient, Magnus force center of pressure vs angle of attack. (Includes several configurations, Mach numbers, pd/2V, s and Reynolds numbers [12' PWT].)	179-355
334-357	Pitching moment secant slopes, Magnus moment secant slopes vs angle of attack	357-381
358	Pitching moment coefficient derivative vs Mach No. (NBT_1C_1, NBT_1C_0, NBT_2C_1, NBG_1C_1)	382

359-360	Magnus moment coefficient derivative vs Mach No. (NBT_1C_1, NBT_1C_0, NBT_2C_1)	384-385
361-367	Magnus moment coefficient derivative vs pd/2V (NBT_1C_1)	387-394
368-369	Muzzle velocity vs range performance flight tests at Yuma Proving Ground	396-397
370-374	Yaw data translated from camera coverage shown in Figure 8	399-404
375	M329A1E1 projectile fired at low charge, with obturator still attached	405
376	Pitching moment coefficient derivative and normal force center of pressure vs Mach No. (SPINNER and the BRL Transonic Range) (NBG_1C_1, NBT_1C_1)	406
377	Normal force coefficient derivative and drag coefficient vs Mach No. (SPINNER and the BRL transonic range)	407
378	Mach No. and pd/2V vs time of flight for M329A1E1 six-degree of freedom trajectory computer simulations. (QE = 60°, V_{muzzle} = 1040 fps)	408
379	Mach No. and pd/2V vs time of flight for M329A1E1 six-degree of freedom trajectory computer simulations. (QE = 45°, V_{muzzle} = 1040 fps)	409
380	Pitch damping coefficient and spin damping coefficient vs Mach No.	410
381	Muzzle gyroscopic stability factors vs Mach No.	411

Ih

382-386 Damping factors vs angle of attack for configuration NBT_1C_1 at various Mach numbers 413-418

387-388 Solar aspect angle vs time of flight for M329A1E1 yaw sonde Round No. 4737 420-421

389-390 Solar aspect angle vs time of flight for M329A1E1 yaw sonde Round No. 4739 424-425

391-392 Solar aspect angle vs time of flight for M329A1E1 yaw sonde Round No. 4740 428-429

NOMENCLATURE

α	Angle of attack, degrees
β	Angle of sideslip, degrees
C_{D_o}	Axial force coefficient, $F_x/\bar{Q}S$
C_{l_p}	Roll damping moment coefficient, $L_p/\bar{Q}Sd\left(\frac{pd}{2V}\right)$
C_m	Pitching moment coefficient, $m/\bar{Q}Sd$
C_{m_α}	Pitching moment coefficient derivative, 1/rad
$C_{m_{\dot{\alpha}}}$	Flow lag moment coefficient, $m_{\dot{\alpha}}/\bar{Q}Sd\left(\frac{\dot{\alpha}d}{2V}\right)$
C_{m_q}	Damping moment coefficient, $m_q/\bar{Q}Sd\left(\frac{qd}{2V}\right)$
C_N	Normal force coefficient, $N/\bar{Q}S$
C_{N_α}	Normal force coefficient derivative, $\partial C_N/\partial\alpha$
C_{n_p}	Magnus moment coefficient, $n_M/\bar{Q}Sd\left(\frac{pd}{2V}\right)$
$C_{n_{p\alpha}}$	Magnus moment coefficient derivative, $\partial C_{n_p}/\partial\alpha$, 1/rad
C_{Y_p}	Magnus force coefficient, $F_Y/\bar{Q}Sd\left(\frac{pd}{2V}\right)$
$C_{Y_{p\alpha}}$	Magnus force coefficient derivative, $\partial C_{Y_p}/\partial\alpha$, 1/rad
d, D	Diameter, ft
F_X	Axial force, lb

I_x	Axial moment of inertia, slugs - ft^2
I_y	Transverse moment of inertia, slugs - ft^2
K_1	Magnitude of nutation arm, degrees
K_2	Magnitude of precession arm, degrees
L_p	Roll damping moment, ft-lb
λ_1	Quasi linear nutation arm damping factor, 1/sec
λ_2	Quasi linear precession arm damping factor, 1/sec
N	Normal force, lb
n_M	Magnus moment, ft-lb
F_Y	Magnus force lb
M	Mach number
m_q	Damping moment, due to pitching velocity, ft-lb
$m_{\dot{\alpha}}$	Flow lag moment, ft-lb
m	Pitching moment, ft-lb
p	Roll rate, rad/sec
$\bar{Q}$	Dynamic pressure, lb/ft^2
q	Pitch rate, rad/sec
QE	Quadrant elevation, mils or degrees, as noted
ρ	Air density, $slugs/ft^3$
s_g	Gyroscopic stability factor
S	Reference area, ft^2

V	Free stream or flight velocity, ft/sec
θ	Sun angle, degrees
ω_1	Nutation frequency, rad/sec
ω_2	Precession frequency, rad/sec
XCG	Center of gravity location, calibers from nose
XCP	Center of pressure of normal force, calibers from the CG
XCPM	Magnus force center of pressure, calibers from center of gravity

Subscripts

o	Initial condition
f	Final condition
2	Indicates second order coefficient of Maple-Synge polynomial expansion

Superscript

*	Secant slope

ABSTRACT

An extensive study of the aerodynamic characteristics of the 4.2", M329A1E1 Mortar Projectile has been conducted. A spectrum of yaw levels up to 40° and Mach numbers from 0.55 to 1.025 were ered in the Ballistic Research Laboratories (BRL) Transonic R facility. A Magnus wind tunnel test in the Ames 12' Pressure Wind Tu el involved boom and boattail effects on Magnus as well as static forces and moments. Mach numbers from 0.3 to 0.95 and angles of attack from 0°to 30°(for a Mach number of 0.3) and 0° to 20° (for the higher Mach numbers) were considered. Shell instrumented with yaw sondes were fired at the Wallops Island Facility of NASA. The theoretical differential equation of motion then was fitted to the resulting single plane angular motion data.

INTRODUCTION

The M329A1E1 projectile is the result of an accelerated product improvement program with the objective to provide a replacement for the M329A1 projectile. Because of the accelerated nature of the program only the improvements which are within the current state of the art have been incorporated. Figures 1 and 2 are drawings of the M329A1E1 and the M329A1 projectiles. The subcaliber cylindrical sections contain the ignition cartridge; they appreciably affect the aerodynamic characteristics of the shell.

The 4.2", M329A1 has been in use since 1940. Its extension to the cartridge housing was part of an attempt to upgrade the system performance by increasing the chamber volume and enabling the use of larger charges. The M329A1 has a history of occasionally erratic flights, the propensity for which increases when the extension to the cartridge housing is present. This extension generates a larger Magnus moment than the original short boom configuration and can lead to dynamic instabilities.

Several improvements have been incorporated into the M329A1E1 design. The drag is decreased by replacing the square base of the M329A1 by a 0.65 caliber boattail and adding a longer windshield. A fixed pre-engraved rotating band has been incorporated into the new design in an attempt to improve the spin performance. A constant chamber volume propellant system makes it possible to eliminate the extension to the cartridge housing.

Cumulatively, these configurational changes mean an improvement of the M329A1E1 in both high and low range capability.

TEST FACILITIES

BRL Transonic Range

The M329A1E1 projectile was fired at subsonic and low transonic velocities in the Ballistic Research Laboratories (BRL) Transonic Range Facility described in Reference 1.

NASA Ames 12' Pressure Wind Tunnel

The Ames 12' Pressure Wind Tunnel is a variable-density, low-turbulence tunnel that operates at subsonic speeds up to slightly less than Mach number 1.0. It is powered by a two-stage axial-force fan driven by electric motors. Airspeed in the test section is controlled by variation of the rotational speed of the fan. Eight fine mesh screens in the settling chamber together with the large contraction ratio of 25 to 1 provide an airstream of exceptionally low turbulence. A special mounting drive system was available for angles of attack over 20°. Figure 3 is a plot of the operating characteristics of this wind tunnel. The full scale test configurations and strain gage balance beams were constructed by the Supersonic Wind Tunnel Branch of BRL. The two beams prepared for the test are SB228A and backup beam SB228B, but only the former was used. They are five component strain gage balances, each of which has two pitch gages and three yaw gages specifically designed for the forces and moments anticipated in this test. The exterior of the model consisted of three basic parts.:

a. Ogive and cylindrical section

b. Tail section (square base or boattail)

c. Boom

Model designations are as follows:

Designation	Drawing Number	Item
NB	SSK2590B - 1 SSK2590A	M329A1E1 nose and cylindrical body
T_1	SSK2590 - B2	Boattail on the aft 0.65 calibers of the model
T_2	SSK2590 - B3	Square base (same length as boattail)
C_1	SSK2590 - B4	Cartridge housing

C_o	No cartridge housing
NBG_1C_1	Configuration NBT_1C_1 with grit on the last inch of cartrdige housing


The M329A1E1 is designated by NBT_1C_1. The configuration shown in Figure 4 is NBT_1C_o.

Performance Flight Tests

Performance flight tests have been conducted, the majority of them at Yuma Proving Ground. Firings in January 1969 involved two preliminary designs with different boattail lengths, which will be called the "long" boattail (0.85 calibers) and the "short" boattail (0.65 calibers). The objective of subsequent firings was the development of an effective rotating band and obturator. Camera coverage was requested for some of these rounds to obtain a yaw record over and past the peak. All rounds were fired from the M30, 4.2 inch Mortar tube, which has a progressive twist resulting in one turn of the projectile in 20 calibers of linear travel.

Yaw Sonde Program

Yaw sondes and their use are fully described in Reference 2. Briefly, a yaw sonde fuze consists of two strips of photovoltaic material arranged to intercept a ray of light which is passed through a pin hole in the side of the fuze body. The strips are placed on a plane containing the axis of symmetry of the projectile in the form of an inverted V. As the projectile rotaies in flight a sun ray impinges on each arm of the V. The resulting signals which take the form;



are transmitted to a recording station. As the projectile yaws while rotating, the sun ray moves up or down the axis of the projectile. Thus the ray takes a shorter or longer time to cross from the first to the second arm of the V. Therefore, as the yaw angle and the spin rate decay various values of x and y are obtained. Having previously calibrated the yaw sonde with a fixed light source and special angle measuring devices, a graph of sun angle vs a function of x and y can be determined. This calibration is then applied to the signals obtained from free flight and a plot of sun angle vs time of flight is obtained.

The yaw sonde firings of the M329A1E1 projectile were a joint effort of the BRL at Aberdeen Proving Ground and Picatinny Arsenal. Wallops Island was chosen as the site of the test, primarily because of the quality of instrumentation available there. Tracking instrumentation included a MPS-19 radar.

Six yaw sonde-equipped M329A1E1 rounds were fired on 22 and 23 October 1969 under the conditions listed in Table 1. Since the yaw sonde package is lighter than the standard fuze, the physical characteristics of the projectile differ from the standard M329A1E1 projectile. They are also listed in Table 1. Figure 5 shows a yaw sonde-equipped M329A1E1 projectile.

EXPERIMENTAL PROCEDURE

BRL Transonic Range

For small yaw angles the BRL Transonic Range test was conventional. However, to reproduce the rather large yaw levels (due to yaw of repose) which have been measured for low velocity and high quadrant elevation fire, a four-kilogram Lexan cylinder was placed 75 centimeters from the muzzle. By glancing the projectile off this cylinder, yaws in excess of 30° were produced without damage to the shell.

NASA Ames 12' Pressure Wind Tunnel

The preparations and techniques used for obtaining Magnus data in wind tunnels are outlined in Reference 3. The Reynolds number-Mach number combinations at which data was recorded in the Ames 12' Pressure Wind Tunnel are plotted in Figure 3. Where possible, the stagnation pressure was atmospheric. Reynolds numbers above and

below this value also were considered. When tunnel conditions were proper and the Mach number correct, the angle of attack was set and the model spun-up to approximately 12,000 rpm. As it was allowed to spin down, readings from all gauges were taken as a function of spin rate on Mosley X - Y Recorders. For the pitch recorders zero moment was positioned in a convenient place on the chart while static tunnel conditions existed. The tunnel then was put into operation and the model rotated through the angle of attack range. For the yaw recorders zero moment was extrapolated back to the point of zero spin rate. Figures 6 and 7 are typical raw data charts. After all Mach number and Reynolds number combinations had been run, a special mounting drive system was used to obtain data to 30° for a Mach number of 0.3 and the Reynolds numbers involved. Considerable overlap was allowed in order to maintain the continuity of the reduced data. A sand band of No. 20 grit was attached to the last inch of the boom for two Mach number - Reynolds number combinations to aid in the investigation of subcaliber after body effects. Mach numbers of 0.3 and 0.55 and their respective Reynolds numbers of 1.7×10^6 and 2.9×10^6 were involved.

Performance Flight Tests

Flight tests at Yuma Proving Ground were established to examine the performance at high and low charges as well as high and low quadrant elevations. Muzzle velocity was determined by use of velocity coils and magnetized shell. Range and deflection were measured by spotting personnel. In addition, for some rounds, cameras were positioned at the muzzle for spin and yaw measurements and under the trajectory peak of a low charge, high quadrant elevation flight for a determination of the yaw of repose (Fig 8).

Yaw Sonde Program

In setting up the yaw sonde test, the tube was positioned 1,300 ft from the radar along an azimuth of 143°. Line of fire of the low charge rounds was along an azimuth of 115°, while high charge rounds were along 130°. The muzzle velocity of each round was measured by a Fastax camera. Trajectory data, including range, altitude, and deflection, were obtained from an MPS-19 tracking radar for each projectile.

DATA REDUCTION TECHNIQUES

BRL Transonic Range

The methods used in the analysis of the transonic range data are documented in References 4 and 5. The angular orientation as well as the position of the projectile in the range are fitted to a closed form solution of the linearized equations of motion by differential correction and least square fits. If a nonlinear system is indicated, the total results must be reviewed on a quasi-linear basis to determine the aerodynamic coefficients.

NASA Ames 12' Pressure Wind Tunnel

Reduction of wind tunnel data is fairly straightforward; however, a determination had to be made concerning the extent of sting interference on the contribution of the boom to Magnus forces and moments. The circulatory flow about the boom itself was felt to be a stronger Magnus generator than boom-end effects; and since the sting was not expected to have greatly disturbed this flow (Refs 6, 7, and8) data could be considered meaningful. Wind tunnel data reduction was performed by two independent units, the Data Reduction Section at Aberdeen Proving Ground, and a reduction unit at Picatinny Arsenal. At Picatinny Arsenal a computer program was developed to reduce readings from the Mosley recorders, shift the resulting force and moment coefficients to pass through zero at zero angle of attack, and plot the shifted coefficients. A 5^{th} - 11^{th} order fit (depending on the data) is represented by the solid line on each plot. Secant slopes of the Magnus and pitching moment coefficients vs angle of attack have been plotted for the reduced data points as well as the higher order fits. All moments and centers of pressure are referenced to the center of gravity (2.48 calibers from the nose) and Magnus force and moment coefficients were calculated using the nondimensional spin parameter pd/2V.

Performance Flight Tests

For the most part performance flight tests yielded only statistical data. Plots of range and deflection vs muzzle velocity help to indicate short rounds, and computation of standard deviations of range, velocity, and deflection are a means of comparing performance of the M329A1E1 with the M329A1. Spin rate calculations were made from

camera coverage at the muzzle for specially painted shell. Yaw histories were measured directly from the muzzle and the downrange camera records, and are discussed in the Section "Experimental Procedures/Performance Flight Tests".

Yaw Sonde Program

Raw data from the yaw sondes was transformed into sun angle and time of flight data and placed on magnetic tape by BRL. These values were then plotted (sun angle vs time of flight) with the aid of the high speed computer. The method of Chapman and Kirk (Ref 9) and a specially modified six degree of freedom trajectory program were used in an effort to reduce the angular motion output of the yaw sonde to aerodynamic coefficient form. Briefly, the size of the section of data to be fitted by the method of Chapman and Kirk was limited by the change in Mach number, since it is not yet one of the fitted parameters. This allowed Mach number variation was established by plotting wind tunnel and range data vs Mach number and then limiting the

$$\frac{\Delta C_{m_\alpha}}{\Delta \text{Mach No.}}, \quad \frac{\Delta C_{m_q}}{\Delta \text{ Mach No.}}, \quad \frac{\Delta C_{n_{p_\alpha}}}{\Delta \text{ Mach No.}}$$

to $\pm 2\%$ of the value at the average Mach number of the section. Certain differential equations of angular motion were then fitted to these sections of data. Both linear and nonlinear C_{m_α}, C_{m_q}, and $C_{n_{p_\alpha}}$ were considered.

PRESENTATION OF TEST RESULTS

BRL Transonic Range

Data from the BRL transonic range is presented in Table 2. Coefficient values within selected Mach number ranges have been plotted vs angle of attack (Figs 9, 10 and 11).

NASA Ames 12' Pressure Wind Tunnel

The results from the Ames 12' Pressure Wind Tunnel have been plotted vs angle of attack. As was previously mentioned, the solid line through the data points represents a 5^{th} - 11^{th} order fit.

Figures 12 through 157 are plots of normal force coefficient, pitching moment coefficient, and normal force center of pressure vs angle of attack. Several nondimensional spin rates and Reynolds numbers are included for each Mach number.

Early in the test it was noted that the output on the forward pitch recorder was of poor quality. The difficulty was traced to a crushed lead wire to the forward pitch recorder. Normal force data on configuration NBT1C1 taken at Mach numbers of 0.3 and 0.55 at various Reynolds numbers was affected by the faulty lead wire, could not be rerun, and is not reported here.

Magnus force coefficient, Magnus moment coefficient and Magnus force center of pressure are plotted in Figures 158 through 333.

From this data, secant slopes of pitching moment and Magnus moment vs angle of attack have been calculated and are presented in Figures 334 through 357. The symbols on slope plots represent Cm_{α}'s and Cnp_{α}'s for each data point. The solid line is the calculated Cm_{α} or Cnp_{α} vs angle of attack from the fit to the original data. Figures 358 through 367 show the relationship of Cm_{α} and Cnp_{α} to Mach number, $\frac{pd}{2V}$, and Reynolds number. Agreement between the two independent reductions of this data is excellent. An average deviation of ±2% was found in the check cases.

Performance Flight Tests

Results from performance flight tests include some plots displaying range vs velocity performance (Figs 368 and 369).

In addition, some of the film records were translated into pitch and yaw data at various points throughout the trajectory (Figs 370 through 374). At the time of these firings, the rubber obturator had failed to separate from the projectile at low charges. Figure 375 is a photograph of the M329A1E1 soon after exiting the muzzle at a velocity of 255 feet per second. The obturator is clearly on, although displaced from its original setting, undoubtedly causing adverse aerodynamic loads. This displacement is caused by the force of the muzzle gases as they pass over the projectile shortly after it exists the muzzle.

At high charges, the obturator is broken by the blast but at some intermediate charges it is possible that it will be forced to a position anywhere along the projectile.

DISCUSSION AND ANALYSIS
(BRL Range and Ames Wind Tunnel)

The following discussion and analysis directly compares results from the BRL Range and the Ames Wind Tunnel. Yaw Sonde results will be discussed separately, due to the unique methods by which they are obtained and the care with which they must be interpreted.

Pitching Moment Coefficient Derivative (Cm_α)

Referring to Figure 376, the range, wind tunnel and SPINNER (Ref 10) agree well for this parameter. The increase in the transonic region is partially due to an increase in the normal force coefficient and largely due to a forward (meaning towards the nose) movement of the normal force center of pressure with increasing Mach number (Fig 376). A plot comparing Cm_α for the three configurations tested in the Ames Wind Tunnel appears as Figure 358. The Reynolds number effects are small (less than 3%). Cm_α is about 44% lower for the square base configuration NBT_2C_1. Although the normal force of NBT_2C_1 is greater, the center of pressure is considerably closer to the center of gravity than NBT_1C_1. At the lower Mach numbers the pitching moment coefficient derivative of NBT_1C_1 is greatest because its normal force center of pressure is slightly more forward of the center of gravity than for NBT_1C_0. The normal forces are the same. At the high Mach number (0.85 - 0.95) NBT_1C_1 has an 8% lower normal force than NBT_1C_0. Its center of pressure remains more forward of its center of gravity. Thus NBT_1C_1 and NBT_1C_0 have nearly the same Cm_α's at M = 0.85 and 0.95. The effect of angle of attack on Cm_α is most clearly demonstrated at M = 0.305 (Figs 340 and 342). This decrease in Cm_α is due to a rearward movement of the normal force center of pressure with an increase in angle of attack. For the other Mach numbers, the angle of attack ranges are not nearly so large, and Cm_α tends to remain nearly constant. A linear approximation up to 10° appears to be an accurate one here.

At high charges, the obturator is broken by the blast; but at some intermediate charges it is possible that it will be forced to a position anywhere along the projectile.

DISCUSSION AND ANALYSIS
(BRL Range and Ames Wind Tunnel)

The following discussion and analysis directly compares results from the BRL Range and the Ames Wind Tunnel. Yaw Sonde results will be discussed separately, due to the unique methods by which they are obtained and the care with which they must be interpreted.

Pitching Moment Coefficient Derivative (Cm_α)

Referring to Figure 376, the range, wind tunnel and SPINNER (Ref 10) agree well for this parameter. The increase in the transonic region is partially due to an increase in the normal force coefficient and largely due to a forward (meaning towards the nose) movement of the normal force center of pressure with increasing Mach number (Fig 376). A plot comparing Cm_α for the three configurations tested in the Ames Wind Tunnel appears as Figure 358. The Reynolds number effects are small (less than 3%). Cm_α is about 44% lower for the square base configuration NBT_2C_1. Although the normal force of NBT_2C_1 is greater, the center of pressure is considerably closer to the center of gravity than NBT_1C_1. At the lower Mach numbers the pitching moment coefficient derivative of NBT_1C_1 is greatest because its normal force center of pressure is slightly more forward of the center of gravity than for NBT_1C_0. The normal forces are the same. At the high Mach number (0.85 - 0.95) NBT_1C_1 has an 8% lower normal force than NBT_1C_0. Its center of pressure remains more forward of its center of gravity. Thus NBT_1C_1 and NBT_1C_0 have nearly the same Cm_α's at M = 0.85 and 0.95. The effect of angle of attack on Cm_α is most clearly demonstrated at M = 0.305 (Figs 340 and 342). This decrease in Cm_α is due to a rearward movement of the normal force center of pressure with an increase in angle of attack. For the other Mach numbers, the angle of attack ranges are not nearly so large, and Cm_α tends to remain nearly constant. A linear approximation up to 10° appears to be an accurate one here.

Magnus Moment Coefficient Derivative ($C_{n_{p_\alpha}}$)

Figures 193, 204, and 218 show reasonably good agreement of the BRL Range and the Ames Wind Tunnel data for this difficult-to-measure parameter. Of particular interest is the fact that the range as well as the wind tunnel data shows a negative Cn_{p_α} at Mach number 0.567 and 9° angle of attack. The effect of this on stability will be discussed in a later section.

The point should here be made that small force and moment Magnus data, normally at the lower angles of attack, may contain considerable percentage error; however, relative magnitudes and consistent trends are of value. Cn_{p_α} versus Mach number for the three configurations tested in the Ames Wind Tunnel are shown in Figures 359 and 360. As Mach number increases in the transonic region Cn_{p_α} for Configuration NBT_1C_1 peaks sharply due to a sharp rise in Magnus force. NBT_2C_1, however, behaves quite differently, remaining nearly constant throughout the same region. It is not uncommon for square base projectiles to peak at higher Mach numbers than boattail projectiles. The boomless Configuration NBT_1C_0 has a lower Cn_{p_α} throughout most of the Mach number range tested, supporting the belief that the boom is a Magnus generator even at low angles of attack. Figures 361 and 367 show the variation of Cn_{p_α} with both pd/2V and angle of attack. At the lower angles of attack and pd/2V's, Cn_{p_α} tends to be negative. This is primarily due to a positive Magnus force in this region of somewhat uncertain data. The trend, however, is consistent throughout the entire Mach number range.

Drag Coefficient (C_D)

The drag coefficient, for small yaws, as measured in the BRL Range, agrees well with the SPINNER data bank (Fig 317). Six-degree of freedom trajectory simulations using such drag data closely agree with full range firings at Yuma Proving Ground.

Pitch Damping Coefficient ($C_{m_q} + C_{m_{\dot{\alpha}}}$)

($C_{m_q} + C_{m_{\dot{\alpha}}}$) as determined by the BRL Range appears constant above 4° for Mach numbers below 0.543. Between M = 0.638 and 0.867, $C_{m_q} + C_{m_{\dot{\alpha}}}$ is constant above 2° (Figs 11 and 380). Below these angles of attack, $C_{m_q} + C_{m_{\dot{\alpha}}}$ becomes less negative, indeed, has been measured as positive at some low angles of attack. This could be caused by a dominance of the $C_{m_{\dot{\alpha}}}$ term.

Gyroscopic Stability

Referring to Figure 381, the gyroscopic stability factor of the M329A1E1 remains within acceptable bounds throughout the Mach number range. The improvement over the M329A1 Projectile also is clear. Simulating -26.3°F lowers the gyroscopic term over 16% but it still remains well within the region of gyroscopic stability.

Dynamic Stability

Nonlinear damping factors, $\lambda^*_{1,2}$ from the quasi-linear theory, were calculated using data from the Ames Wind Tunnel, and plotted vs angle of attack in Figures 382 through 386. These parameters give an insight into what can be expected in terms of angular motion as the projectile traverses a trajectory. One may qualitatively explain the motion of a low charge high quadrant elevation round with the aid of Figure 382 in the following way: As the projectile exits the muzzle, it receives an initial disturbance resulting in an average maximum yaw of 1 or 2 degrees. At this point the precessional mode appears to be slightly undamped. Of course, due to the error in the data and the sensitivity of $\lambda^*_{1,2}$ to Magnus and damping, the precessional mode may be slightly damped. On the way to the trajectory peak a rather large yaw of repose appears and carries the projectile into a region where the precessional mode is heavily damped while the nutational mode is strongly undamped. From here on it becomes a race up to the ground impact, as the K_1 arm grows and the K_2 arm damps. The damping factors are functions of Mach number and angle of attack (Figs 382 through 386). As the Mach number decreases, there are changes in the size of the small angle precessional limit cycle until eventually a nutational limit cycle will appear.

Similarly, if the projectile is disturbed upon launch from the muzzle to an angle of attack of 12°, below M = .75, the angular motion will diverge due to a nutational instability. The result of this is, of course, a short range.

DISCUSSION AND ANALYSIS
(Yaw Sondes)

Many attempts have been made to fit the differential equation of motion to the angular motion data obtained from the yaw sonde. While performing these fits, in addition to holding the coefficients C_{m_α}, $(C_{m_q} + C_{m_{\dot{\alpha}}})$, and $C_{n_{p_\alpha}}$ constant, various combinations of higher order terms were considered. Convergence of the equation of motion to the data was achieved for many of these combinations resulting in some reasonable fits. Some of the coefficients which generated such motion are, however, not in good agreement with those of the wind tunnel and transonic range. Among the questions raised due to these disappointing results are:

1. What accuracies are needed in yaw sonde manufacture and calibration ?

2. How sensitive is the motion and thus the fit, to rather large nonlinearities in the coefficients ?

3. For a given set of yaw sonde sun angle data, radar data, and projectile physical parameters, how accurately can we separate and determine the Magnus and damping moments ?

While we are not ruling out fitting the equation of motion to yaw sonde data as a powerful tool in stability coefficient determination, the results of our analysis do not, at this time, merit publication until additional efforts in the area can answer some of these important questions. A qualitative discussion of the results from the yaw sonde follows.

Figures 387 through 392 show solar aspect angle data from the yaw sonde for a projectile fired at a 45° quadrant elevation and two projectiles fired at a 60° quadrant elevation. All three projectiles had a muzzle velocity of approximately 1050 feet per second.

Referring to the damping factor plots (Figs 382 through 386) one can see that the precession arm will undamp up to two degrees at a Mach number of 0.95 and up to almost five degrees for a Mach number of 0.85. We can expect, therefore, that the precessional arm should be slightly undamped near the muzzle. This is the case for the three examples shown. The initial magnitude of the nutational arm may be attributed to the muzzle disturbance. As the Mach number decreases on the up leg of the trajectory the precession damps as shown by the damping factors of Figures 382 through 386, and the nutational arm can be expected to grow to one or two degrees. This behavior will be enhanced by the increase in $Cn_{p\alpha}$ due to the increased pd/2V in this region. The precession damps as the peak of the trajectory is traversed due to the decreasing Mach number. On the down leg of the trajectory, the combined effects of the yaw of repose, the Mach number increase, and the pd/2V decrease, cause the precessional arm to reappear.

CONCLUSIONS AND RECOMMENDATIONS

The M329A1E1 has adequate damping characteristics and therefore adequate stability throughout its Mach number regime. A problem area appears in the low charge and high quadrant elevation firings due to a rather large gyroscopic term and resulting yaw of repose. When fired with a tail wind this problem becomes greater, and fuze functioning may be affected due to impact at large yaws. In addition, the rubber obturating band has been observed to remain with the round at this minimum charge. Such an occurrence will result in a decrease in accuracy and an unpredictable ground impact angle.

REFERENCES

1. Rogers, W. R., Jr., "The Transonic Free Flight Range", BRL Report 1040, June 1958 (AD 200177)

2. Amery, I. O. F., Henning, H.G.E., Lawrie, K. G. A., Latnig, E. J. M., "A Telemetry System for the Measurement of the Yaw of a Projectile Throughout the Major Part of its Trajectory (U)", RARDE, Guns and Ammunition Division, Fort Halsted, Kent, United Kingdom, Report No. 1/65 (CONF)

3. Platou, A. S., Colburn, R., and Pedgonay, J. S., "The Design and Dynamic Balancing of Spinning Models and a Testing Technique for Obtaining Magnus Data in Wind Tunnels", BRL Memorandum Report 2019, October 1969

4. Murphy, C. H., "Data Reduction for the Free Flight Spark Ranges", BRL Report 900, (AD35833) February 1954

5. Murphy, C. H., "The Measurement of Nonlinear Forces and Moments by Means of Free Flight Tests", BRL Report 974 (AD93521) February 1956

6. Tunnel, P., "An Investigation of Sting Support Interference on Base Pressure and Forebody Chord Force at Mach Numbers from 0.60 to 1.30", NACA RM A54K16, January 1955

7. Love, E., "A Summary of Interference at Transonic and Supersonic Speeds", NACA RM L53K12, January 1954

8. Zonars, D., "Large Angle of Attack Model-Sting Interference Effects at Transonic Speeds", AGARD Report 301, March 1959

9. Chapman, G., and Kirk, D., "A New Method for Extracting Aerodynamic Coefficients from Free Flight Data", AIAA Paper at 7th Aerospace Science g, January 1969

10. Whyte, R. H., "SPINNER - A C Program for Empirically Predicting the Aer ic Coefficients of Spin Stabilized Projectiles", Pica Arsenal, ESL IR 319, February 1967;

"SPINNER - A Computer Program for Predicting the Aerodynamic Coefficients of Spin Stabilized Projectiles", General Electric, Technical Information Series, No. 69APB3, August 1969

TABLE 1

Physical characteristics and launch conditions of M329A1E1 yaw sonde rounds

Round No.	V Muzzle (fps)	Q E (deg)	I_x (lb - in.^{2})	I_y (lb - in.^{2})	Weight (lb)	Center of Gravity (inches from base)
4729	267	60	-----	-----	----	-----
4731	255	60	-----	-----	----	-----
4737	1052	45	50.89	386.7	21.0	6.432
4738	1058	45	50.84	387.9	21.01	6.437
4739	1064	60	50.84	385.8	20.96	6.427
4740	1052	60	50.93	386.2	21.0	6.43
Standard M329A1E1			53.0	446.0	22.2	6.8

TABLE 2

Ballistic Research Laboratories' range coefficients

MACH NO.	$\overline{\alpha^2}$	C_D	$C_{m_{\alpha}}$	$C_{N_{\alpha}}$	C_{P_N}	$C_{n_{p_{\alpha}}}$	$C_{y_{\beta}}$	$C_{m_q} + C_{m_{\dot{\alpha}}}$	S_g	$l_1(10^3)$	$l_2(10^3)$
.523	15.53	.2712	2.5441	1.6720	3.3172	.3008	-.6433	-2.5852	3.13	.0261	- 2289
.543	8.96	.1741	2.9755	1.4035	3.7357	-.1803	.0566	-2.8199	2.64	-.2317	.0328
.517	2.31	.1118	3.0460	0.9987	4.6655	.3710	-.5232	-3.8057	2.54	.0017	-.2253
.527	3.27	.1182	3.0787	1.3353	3.9212	.1282	-.7781	-.9204	2.45	.0344	-.1417
.425	1.38	.1109	2.8179	1.3287	3.7364	-1.0006	-1.0825	10.3487	2.60	.0513	.3838
.435	3.45	.1236	3.0436	1.3305	3.9031	.0404	-.9203	-1.3238	2.45	-.0352	-.0894
.638	4.42	.1277	3.1257	1.3741	3.8904	.1686	-.5005	-3.9880	2.55	-.1120	-.1409
.684	0.69	.1031	3.2785	1.4063	3.9469	-.1034	-.2408	-3.0283	2.32	-.2079	-.0043
.727	3.48	.1185	3.1450	1.2307	4.1712	.2856	.4720	-3.7092	2.40	-.0350	-.1991
.483	14.17	.2160	2.5558	1.5599	3.2541	.2265	-.7287	-1.9454	3.03	.0239	-.1913
.720	3.29	.1195	3.1980	1.6291	3.5786	.2609	.5106	-3.7596	2.43	-.0469	-.2092
.777	1.38	.1075	3.2302	1.5295	3.7275	.1104	-.8910	-2.3079	2.40	-.0493	-.1328
.776	2.31	.1088	3.2737	1.6725	3.5742	.1223	-.7027	-3.2853	2.38	-.0943	-.1408
.797	1.28	.1062	3.2025	.9917	4.8470	.0635	-1.0305	-3.0522	2.38	-.1222	-.0697

TABLE 2 (Cont'd)

MACH NO.	[illegible]	C_D	$C_{m_{[illegible]}}$	$C_{N_{[illegible]}}$	C_{P_N}	$C_{n_{P_{[illegible]}}}$	$C_{y_{p_{[illegible]}}}$	$C_{m_q} + C_{m_{\dot{[illegible]}}}$	S_g	$l^{(10^3)}$	$2^{(10^3)}$
.815	3.90	.1252	3.3426	1.2097	4.3017	.2047	-.3038	-3.0189	2.32	-.0400	-.1607
.840	2.90	.1193	3.3211	1.9091	3.3552	.2021	.1270	-3.7254	2.22	-.0740	-.1997
.861	4.61	.1381	3.3840	1.8414	3.4534	.1800	.1627	-3.1066	2.26	-.0544	-.1867
.867	4.82	.1411	3.3973	1.6237	3.6934	.1438	-.4448	-3.6415	2.22	-.1067	-.1504





Fig 1 4.2" M329A1E1 mortar projectile
(all dimensions in calibers)



CONFIG	WGT LBS	AXIAL LB-FT²	TRANSVERSE LB-FT²	C.G. CAL. FOM NOSE	A²/B LB-FT² X10
W/O BOOM	25.7*	0.4479*	5.208*	2.89*	385*
W/O EXT	23.9*	0.4479*	5.408*	3.01*	371*
W EXT	24.1	0.4479	5.610	3.03*	.358

* ESTIMATED
A = AXIAL MOMENT OF INERTIA
B = TRANSVERSE MOMENT OF INERTIA
(ALL DIMENSIONS IN CALIBERS)

Fig 2 4.2" M329A1 projectile




Fig 3 Operating characteristics of the Ames 12' pressure wind tunnel (PWT)




Fig 4 Configuration NBT_1C_o mounted in 12' PWT




Fig 5 M329A1E1 projectile equipped with yaw sonde




Fig 6 Raw data chart from 12' PWT (pitch gauge readings vs model rpm)




Fig 7 Raw data chart from 12' PWT (yaw gauge readings vs model rpm)




Fig 8 Camera coverage for low charge high quadrant elevation firing of M329A1E1 projectile at Yuma Proving Ground




Fig 9 Normal force coefficient derivative vs angle of attack (BRL transonic range)




Fig 10 Pitching moment coefficient derivative vs angle of attack (BRL transonic range)




Fig 11 Pitch damping coefficient ($Cm_q + Cm_{\dot{\alpha}}$), Magnus moment coefficient derivative vs angle of attack (BRL transonic range)

Figures 12 through 157

Normal force coefficient, pitching moment coefficient, and normal force center of pressure vs angle of attack. (Includes several configurations, Mach numbers, pd/2V's and Reynolds numbers [12' PWT] .)

Preceding page blank



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0
REYNOLDS NO.
1.68E+06
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 12



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.021
REYNOLDS NO.
1.68E+06
NORMAL FORCE C.P. (FROM C.G.)
A NORMAL FORCE * PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 13



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.042
REYNOLDS NO.
1.68E+06
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK, DEGREES

Fig 14



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.063
REYNOLDS NO.
1.68E+06
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
-1.00
0.0
1.00
3.00
5.00
7.00
9.00
11.00
2.00
1.50
1.00
.75
.50
.25
0
-.25
-.50

Fig 15



CONFIG.
T:C1
MACH NO.
0.727
PD/2V
0.0684
REYNOLDS NO.
1.62E+06
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
-1.00
0.0
1.00
4.00
6.00
9.00
11.00

Fig 16



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.126
REYNOLDS NO.
1.68E+06
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1E1

Fig 17




CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.168
REYNOLDS NO.
1.68E+06
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
▲ NORMAL FORCE
★ PITCHING MOMENT
M328A1E1

Fig 18


CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.210
REYNOLDS NO.
1.68E+06
NORMAL FORCE C.P. FROM C.G.
A NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
FIG 17




CONFIG.
T1C1
MACH NO.
.742
PD/2V
.104
REYNOLDS NO.
2.28E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 39


CONFIG.
T1C1
MACH NO.
.742
PQ/2V
.145
REYNOLDS NO.
2.28E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
Fig 21
ANGLE OF ATTACK, DEGREES





CONFIG.
T1C1
MACH NO.
.742
PD/2V
.249
REYNOLDS NO.
2.28E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M829A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 22


CONFIG.
T1C1
MACH NO.
.850
PO/2V
.018
REYNOLDS NO.
1.35E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1E1
Fig 23


CONFIG.
T1C1
MACH NO.
.850
PD/2V
0.036
REYNOLDS NO.
1.35E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1E1
Fig 24





CONFIG.
T1C1
MACH NO.
.850
PD/2V
0.054
REYNOLDS NO.
1.35E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
A NORMAL FORCE
* PITCHING MOMENT
M329A1F1

Fig 25


CONFIG.
T1C1
MACH NO.
.850
PD/2V
0.072
REYNOLDS NO.
1.35E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 24


CONFIG.
T1C1
MACH NO.
.850
PD/2V
0.109
REYNOLDS NO.
1.35E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE + PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 27



CONFIG.
T1C1
MACH NO.
.850
PD/2V
.145
REYNOLDS NO.
1.35E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-2.00
0.0
1.50
3.00
4.50
6.00
7.50
9.00
11.50

Fig 28




CONFIG.
T1C1
MACH NO.
.850
PT/2V
0.181
REYNOLDS NO.
1.35E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE
* PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 29


CONFIG.
T1C1
MACH NO.
0.850
PO/2V
0
REYNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
A NORMAL FORCE
PITCHING MOMENT
M329A1F1



CONFIG.
T1C1
MACH NO.
0.850
PO/2V
0.017
REYNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 31



CONFIG.
11C1
MACH NO.
0.850
PD/2V
0.056
REYNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.F. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
A NORMAL FORCE
PITCHING MOMENT
M329A1F1
-7.50
-5.00
-2.50
2.50
5.00
7.50
10.00

Fig 32



CONFIG.
T1C1
MACH NO.
0.850
PO, PSF
0.154
REYNOLDS NO.
1.79E+06
DEGREES
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M829A1F1

Fig 33



CONFIG.
11C1
MACH NO.
0.850
PD/2V
0.072
REYNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
-1.50
-3.00
Δ NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
0.75
0.50
0.25
-0.25
-0.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
0.75
0.50
0.25
-0.25
-0.50
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 34



CONFIG.
T1C1
MACH NO.
0.850
PO/2V
0.108
RETNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF HITACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1E1
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 35



CONFIG.
11C1
MACH NO.
0.850
PD/2V
0.144
REYNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 36



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.166
REYNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
A NORMAL FORCE
PITCHING MOMENT
M329A1F1
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 37



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.216
REYNOLDS NO.
1.79E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M829A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 38






CONFIG.
T1C1
MACH NO.
.949
PD/2V
.096
REYNOLDS NO.
1.18E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-4.00
-2.00
0
2.00
4.00
6.00
8.00

Fig 39


CONFIG.
T1C1
MACH NO.
.949
PD/2V
.144
REYNOLDS NO.
1.15E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-4.00
-2.00
0
2.00
4.00
6.00
8.00


NORMAL FORCE COEFFICIENT
NORMAL FORCE C.P. (FROM C.G.)
ANGLE OF ATTACK, DEGREES
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
CONFIG.
FIG.
MACH NO.
.949
RD/2V
.193
REYNOLDS NO.
1.18E+06
NUMBER
11


CONFIG.
G1C1
MACH NO.
.307
PO/2V
.103
REYNOLDS NO.
1.78E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
Fig 42
62



CONFIG.
G1C1
MACH NO.
.306
PD/2V
.104
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 43




CONFIG.
G1C1
MACH NO.
.307
PD/2V
.154
REYNOLDS NO.
1.78E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.50
-7.50
-4.50
-1.50
0.0
1.50
4.50
7.50
10.50

Fig 11


CONFIG.
DIC1
MACH NO.
.306
PD/2V
.156
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
A NORMAL FORCE
PITCHING MOMENT
M329A1F1
Fig. 45
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00




CONFIG.
GIC1
MACH NO.
.307
I*D/2V
.257
REYNOLDS NO.
1.78E+06
ORDER
5
NORMAL FORCE C.P. 1/4CHORD FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.50
-7.50
-4.50
-1.50
0.0
1.50
4.50
7.50
10.50

Fig 46


CONFIG.
C1C1
MACH NO.
.306
PO/2V
.260
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 41



CONFIG.
G1C1
MACH NO.
.307
PQ/2V
.360
REYNOLDS NO.
1.78E+06
ORDER
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.50
-7.50
-4.50
-1.50
0.0
1.50
4.50
7.50
10.50

Fig 48



CONFIG.
GIC1
MACH NO.
.567
PD/2V
.083
REYNOLDS NO.
2.92E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 5



CONFIG.
G1C1
MACH NO.
.306
PD/2V
.964
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 49




CONFIG.
G1C1
MACH NO.
.567
PD/2V
.138
REYNOLDS NO.
2.92E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 51


CONFIG.
G1C1
MACH NO.
.567
PO/2V
.248
REYNOLDS NO.
2.92E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
Fig 52
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES



CONFIG.
T1CO
MACH NO.
.306
PO/2V
.052
REYNOLDS NO.
1.76E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
3.00
.50
0
-1.50
-3.00
Δ NORMAL FORCE
* PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
1.20
.80
.40
0
-.40
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.40
.20
0
-.40
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES

Fig 53



CONFIG.
T1CO
MACH NO.
.306
PD/2V
.104
REYNOLDS NO.
1.76E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES

Fig. 5



CONFIG.
T1CO
MACH NO.
.306
PD/2V
.156
REYNOLDS NO.
1.76E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M829A1E1
ANGLE OF ATTACK, DEGREES

Fig 99



CONFIG.
T1CO
MACH NO.
.306
PO/2V
.208
REYNOLDS NO.
1.76E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 56



CONFIG.
T1CO
MACH NO.
.306
PO/2V
.312
REYNOLDS NO.
1.75E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES

Fig. 57



CONFIG.
TICO
MACH NO.
.305
PD/2V
.416
REYNOLDS NO.
1.76E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
1.20
.80
.40
0
-.40
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
1.60
1.20
.80
.40
0
-.40
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES

Fig 58



CONFIG.
TICO
MACH NO.
.306
PD/2V
.520
REYNOLDS NO.
1.76E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES

Fig 50



CONFIG.
T1C0
MACH NO.
.306
PQ/2V
.624
REYNOLDS NO.
1.76E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES

Fig 60



CONFIG.
TICO
MACH NO.
.307
PD/2V
0
REYNOLDS NO.
2.36E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1E1
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 61



CONFIG.
T1CO
MACH NO.
.307
PD/2V
.051
REYNOLDS NO.
2.36E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK, DEGREES

Fig 62



CONFIG.
T1CO
MACH NO.
.307
PD/2V
.102
REYNOLDS NO.
2.36E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329B1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 63



CONFIG.
T1CO
MACH NO.
.307
PO/2V
.153
REYNOLDS NO.
2.36E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK, DEGREES

Fig 64




CONFIG.
T1CO
MACH NO.
.307
PO/2V
.204
REYNOLDS NO.
2.36E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
A NORMAL FORCE
* PITCHING MOMENT
M329A1E1
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK, DEGREES

Fig. 65


CONFIG.
TICO
MACH NO.
.307
PD/2V
.306
REYNOLDS NO.
2.36E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
2.00
1.60
1.20
.80
.40
0
-.40
-.80
-1.20
-1.60
-2.00
-2.40
-2.80
-3.20
-3.60
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.80
.76
.60
.50
.40
.25
0
-.25
-.40
-.50
-.60
-.76
-.80
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK, DEGREES
86




CONFIG.
T1CO
MACH NO.
.307
PD/2V
.408
REYNOLDS NO.
2.35E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 57


CONFIG.
TICO
MACH NO.
.907
PD/2V
.510
REYNOLDS NO.
2.38E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
Fig 68
ANGLE OF ATTACK, DEGREES




CONFIG.
T1CO
MACH NO.
.550
PO/2V
.084
REYNOLDS NO.
9.00E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 69


CONFIG.
TICO
MACH NO.
.557
PD/2V
.105
REYNOLDS NO.
2.89E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE
* PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 70
90



CONFIG.
T1C0
MACH NO.
.550
PD/2V
.140
REYNOLDS NO.
3.00E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
5.00
7.50
10.00

Fig 71



CONFIG.
71CO
MACH NO.
.557
PD/2V
.163
REYNOLDS NO.
2.89E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE * PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 72



CONFIG.
T1CO
MACH NO.
.557
PD/2V
.245
REYNOLDS NO.
2.89E+06
ORDER
1
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE
+ PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 73



CONFIG.
T1CO
MACH NO.
.550
PD/2V
.253
REYNOLDS NO.
3.00E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig. 74



CONFIG.
TICO
MACH NO.
.550
PD/2V
.397
REYNOLDS NO.
3.00E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 75.



CONFIG.
T1CO
MACH NO.
.565
PD/2V
0
REYNOLDS NO.
3.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
Δ NORMAL FORCE * PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.76
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES

Fig. 76




CONFIG.
T1CO
MACH NO.
.565
PD/2V
.027
REYNOLDS NO.
3.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
.60
0
-.60
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.76
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK,DEGREES

Fig 77


CONFIG.
T1CO
MACH NO.
.565
PD/2V
.054
REYNOLDS NO.
3.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 7B



CONFIG.
T1CO
MACH NO.
.565
PD/2V
.081
REYNOLDS NO.
3 37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M829A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 79



CONFIG.
T1CO
MACH NO.
.505
PD/2V
108
REYNOLDS NO.
3.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 80



CONFIG.
T1CO
MACH NO.
.565
PD/2V
.163
REYNOLDS NO.
3.37E+06
ORDER
1
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 81



CONFIG.
TICO
MACH NO.
.565
PD/2V
.217
REYNOLDS NO.
3.97E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK.DEGREES

Fig. 82



CONFIG.
T1CO
MACH NO.
.565
PD/2V
.271
REYNOLDS NO.
3.97E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-0.00
0
5.00
8.00
12.00
15.00

Fig 83



CONFIG.
T1CO
MACH NO.
.747
PO/2V
0
REYNOLDS NO.
1.69E+06
ORDER
11
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M829A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 84



CONFIG.
T1CO
MACH NO.
.747
PO/2V
.021
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 85



CONFIG.
T1CO
MACH NO.
.747
PD/2V
.042
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 86



CONFIG.
T1CO
MACH NO.
.747
PO/2V
.063
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 87



CONFIG.
TICO
MACH NO.
.747
PO/2V
.083
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 88



CONFIG.
TICO
MACH NO.
.747
PQ/2V
.125
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-5.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 89



CONFIG.
TICO
MACH NO.
.747
PD/2V
.167
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
Δ NORMAL FORCE * PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 90



CONFIG.
T1C0
MACH NO.
.747
PO/2V
.209
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 91



CONFIG.
TICO
MACH NO.
.747
PD/2V
.250
REYNOLDS NO.
1.69E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-5.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 92



CONFIG.
TICO
MACH NO.
.745
PO/2V
.103
REYNOLDS NO.
2.27E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 93



CONFIG.
T1CO
MACH NO.
.745
PD/2V
.144
REYNOLDS NO.
2.27E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 94



CONFIG.
TICO
MACH NO.
.745
PD/2V
.247
REYNOLDS NO.
2.27E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-5.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 95



CONFIG.
T1CO
MACH NO.
.847
PD/2V
0
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK.DEGREES

Fig 96



CONFIG.
T1CO
MACH NO.
.847
PD/2V
.018
REYNOLDS NO.
1.97E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 97



CONFIG.
T1CO
MACH NO.
.847
PO/2V
.036
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 98



CONFIG.
TICO
MACH NO.
.847
PD/2V
.054
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 99



CONFIG.
TICO
MACH NO.
.847
PO/2V
.072
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES

Fig. 100



CONFIG.
T1CO
MACH NO.
.847
PD/2V
.108
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 10



CONFIG.
T1CO
MACH NO.
.847
PD/2V
.144
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 102



CONFIG.
T1CO
MACH NO.
.847
PD/2V
.180
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES

Fig 103



CONFIG.
TICO
MACH NO.
.847
PO/2V
.216
REYNOLDS NO.
1.37E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1E1
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 104



CONFIG.
TICO
MACH NO.
.846
PD/2V
.090
REYNOLDS NO.
1.86E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1E1
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 105



CONFIG.
TICO
MACH NO.
.845
PD/2V
.143
REYNOLDS NO.
1.85E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 106



CONFIG.
TICO
MACH NO.
.846
PO/2V
.215
REYNOLDS NO.
1.86E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 107



CONFIG.
T1CO
MACH NO.
.948
PD/2V
.096
REYNOLDS NO.
1.20E+06
ORDER
?
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE
★ PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 108



CONFIG.
T1CO
MACH NO.
.948
PD/2V
.144
REYNOLDS NO.
1.20E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 109



CONFIG.
TICO
MACH NO.
.948
PD/2V
.192
REYNOLDS NO.
1.20E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
Δ NORMAL FORCE * PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 110



CONFIG.
T1CO
MACH NO.
.949
PD/2V
.096
REYNOLDS NO.
1.62E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 111



CONFIG.
T1CO
MACH NO.
.949
PØ/2V
.144
REYNOLDS NO.
1.62E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 112



CONFIG.
TICO
MACH NO.
.949
PD/2V
.192
REYNOLDS NO.
1.6EE+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 113



CONFIG.
T2C1
MACH NO.
.306
PD/2V
0
REYNOLDS NO.
1.75E+06
ORDER
2
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 114



CONFIG.
T2C1
MACH NO.
.306
PD/2V
052
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 115



CONFIG.
T2C1
MACH NO.
.306
PO/2V
.105
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.P.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 116




CONFIG.
T2C1
MACH NO.
.306
PD/2V
.157
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
Δ NORMAL FORCE
PITCHING MOMENT
M329A1E1
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00
ANGLE OF ATTACK, DEGREES

Fig 117


CONFIG.
T2C1
MACH NO.
.306
PO/2V
.209
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00



CONFIG.
T2C1
MACH NO.
.306
PO/2V
.314
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 119



CONFIG.
T2C1
MACH NO.
.305
PD/2V
.419
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
NORMAL FORCE
PITCHING MOMENT
M329A1E1
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 130



CONFIG.
T2C1
MACH NO.
.306
PD/2V
.523
REYNOLDS NO.
1.75E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 121



CONFIG.
T2C1
MACH NO.
.308
PO/2V
.610
REYNOLDS NO.
1.76E+06
ORDER
7
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
3.00
1.50
0
-1.50
-3.00
.75
.50
.25
0
-.25
-.50
-.75
-12.00
-9.00
-6.00
-3.00
0
3.00
6.00
9.00

Fig 122



CONFIG.
T2C1
MACH NO.
.569
PD/2V
0
REYNOLDS NO.
2.93E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
2.00
1.50
1.00
.50
0
-.50
-1.00
-1.50
-2.00
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
Δ NORMAL FORCE
◆ PITCHING MOMENT
M329A1E1
-5.00
-3.00
0
3.00
5.00
8.00
12.00
15.00
ANGLE OF ATTACK.DEGREES

Fig. 123



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.027
REYNOLDS NO.
2.93E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 124



CONFIG.
T2C1
MACH NO.
.569
PD/2V
054
REYNOLDS NO.
2.93E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES

Fig 125



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.080
REYNOLDS NO.
2.93E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES

Fig 126



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.107
REYNOLDS NO.
2.93E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 127



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.161
REYNOLDS NO.
2.93E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 128



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.214
REYNOLDS NO.
2.98E+06
ORDER
9
NORMAL FORCE C.F. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
0
5.00
6.00
9.00
12.00
15.00

Fig 129




CONFIG.
T2C1
MACH NO.
.569
PD/2V
.268
REYNOLDS NO.
2.93E+06
ORDER
9
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
0
3.00
6.00
9.00
12.00
15.00

Fig 130


CONFIG.
T2C1
MACH NO.
.740
PD/2V
0
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 131



CONFIG.
12C1
MACH NO.
.740
PD/2V
.021
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
NORMAL FORCE
PITCHING MOMENT
M329A1F1

Fig 132



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.041
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK, DEGREES

Fig 133



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.062
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 134



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.083
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
A NORMAL FORCE
* PITCHING MOMENT
M329A1F1
ANGLE OF ATTACK, DEGREES

Fig 135



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.124
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig. 136



CONFIG.
12C1
MACH NO.
.740
PD/2V
.166
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 137



CONFIG
T2C1
MACH NO
.740
PO/2V
.207
REYNOLDS NO.
1.67E+00
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
Δ NORMAL FORCE ★ PITCHING MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES

Fig 138



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.249
REYNOLDS NO.
1.67E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
-1.00
1.00
3.00
5.00
7.00
9.00
11.00

Fig 139



CONFIG.
T2C1
MACH NO.
.852
PD/2V
0
REYNOLDS NO.
1.39E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
A NORMAL FORCE + PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK, DEGREES

Fig 110




CONFIG.
T2C1
MACH NO.
.852
PD/2V
.018
REYNOLDS NO.
1.3E+06
ORDER
2
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 141


CONFIG.
T2C1
MACH NO.
.852
PD/2V
.036
REYNOLDS NO.
1.39E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
A NORMAL FORCE
* PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 142



CONFIG.
T2C1
MACH NO.
.852
PD/2V
.054
REYNOLDS NO.
1.39E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig. 143



CONFIG.
T2C1
MACH NO.
.852
PO/2V
.071
REYNOLDS NO.
1.39E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 141




CONFIG.
T2C1
MACH NO.
.852
PD/2V
.107
REYNOLDS NO.
1.93E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 145


CONFIG.
T2C1
MACH NO.
.852
PO/2V
.143
REYNOLDS NO.
1.39E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1F1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 146




CONFIG.
T2C1
MACH NO.
.852
PD/2V
.178
REYNOLDS NO.
1.39E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 147


CONFIG.
T2C1
MACH NO.
.852
PD/2V
.214
REYNOLDS NO.
1.39E+06
ORDER
7
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK, DEGREES



CONFIG.
T2C1
MACH NO.
.950
PD/2V
0
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 149



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.016
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 150



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.032
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 151



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.048
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-.60
-3.00
Δ NORMAL FORCE + PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK, DEGREES

Fig 152



CONFIG.
T2C1
MACH NO.
.950
PO/ZV
.064
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
1.50
4.00
6.50
9.00
11.50

Fig 153



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.097
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
.75
.50
.25
0
-.25
-.50
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
.75
.50
.25
0
-.25
-.50
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK, DEGREES

Fig 154



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.129
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 155



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.161
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 156



CONFIG.
T2C1
MACH NO.
.950
PO/2V
.193
REYNOLDS NO.
1.18E+06
ORDER
5
NORMAL FORCE C.P. (FROM C.G.)
NORMAL FORCE
PITCHING MOMENT
M329A1E1
NORMAL FORCE COEFFICIENT
PITCHING MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 157

Figures 158 through 333

Magnus force coefficient, Magnus moment coefficient, Magnus force center of pressure vs angle of attack. (Includes several configurations, Mach numbers, pd/2V's and Reynolds numbers [12' PWT] .)

Preceding page blank



CONFIG.
T1C1
MACH NO.
0.305
PD/2V
0.052
REYNOLDS NO.
1.25E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
3.00
1.50
0
-1.50
-3.00
0.30
0.10
0.0
-0.10
-0.30
-0.50
0.50
0.30
0.10
0.0
-0.10
-0.30
-0.50

Fig. 158



CONFIG.
TICI
MACH NO.
0.305
PD/2V
0.105
REYNOLDS NO.
1.25E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 159



CONFIG.
TICT
MACH NO.
0.305
PD/2V
0.157
REYNOLDS NO.
1.25E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 160



CONFIG.
TIC1
MACH NO.
0.305
PB/2V
0.210
REYNOLDS NO.
1.25E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK, DEGREES

Fig 161



CONFIG.
T1C1
MACH NO.
0.305
PD/2V
0.315
REYNOLDS NO.
1.25E+06
MAGNUS FORCE C.P. AFROM C.G.
MAGNUS FORCE
MAGNUS MOMENT
M329B1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 162



CONFIG.
T1C1
MACH NO.
0.305
PD/2V
0.420
REYNOLDS NO.
1.25E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 163



CONFIG.
T1C1
MACH NO.
0.305
PD/2V
0.525
REYNOLDS NO.
1.25E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 164



CONFIG.
T1C1
MACH NO.
0.305
PD/2V
0.630
REYNOLDS NO.
1.25E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 163



CONFIG.
T1C1
MACH NO.
.306
PD/2V
.104
REYNOLDS NO.
1.78E+06
ORDER
11
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 166



CONFIG.
T1C1
MACH NO.
.306
PD/2V
.156
REYNOLDS NO.
1.73E+06
ORDER
11
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 167



CONFIG.
T1C1
MACH NO.
.306
PO/2V
.260
REYNOLDS NO.
1.73E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 168



CONFIG.
T1C1
MACH NO.
.306
PD/2V
.364
REYNOLDS NO.
1.73E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 169



CONFIG.
T1C1
MACH NO.
.303
PD/2V
.052
REYNOLDS NO.
2.31E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 170



CONFIG.
T1C1
MACH NO.
.303
PD/2V
.105
REYNOLDS NO.
2.31E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 17



CONFIG.
1C1
MACH NO.
.303
PQ/2V
.157
REYNOLDS NO.
2.31E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 17a



CONFIG.
T1C1
MACH NO.
.303
PD/2V
.210
REYNOLDS NO.
2.31E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
3.00
1.50
0
-1.50
-3.00
2.00
1.00
0
-1.00
-2.00
-3.00

Fig 175



CONFIG.
T1C1
MACH NO.
.304
PD/2V
.314
REYNOLDS NO.
2.31E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 17



CONFIG.
TIC1
MACH NO.
.304
PD/2V
.419
REYNOLDS NO.
2.31E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
2.00
1.00
0
-1.00
-2.00
-3.00
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-11.00
-5.50
0
5.50
11.00
27.50
ANGLE OF ATTACK.DEGREES

Fig 175



CONFIG.
1C1
MACH NO.
.307
PD/2V
.521
REYNOLDS NO.
2.29E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 176



CONFIG.
T1C1
MACH NO.
.560
PQ/2V
.027
REYNOLDS NO.
2.18E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT ABOUT C.G.
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
0
3.00
5.00
8.00
12.00
15.00

Fig 177



CONFIG.
T1C1
MACH NO.
.567
PD/2V
0.054
REYNOLDS NO.
2.1BE+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT ABOUT C.G.
ANGLE OF ATTACK.DEGREES
-5.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 178



CONFIG.
T1C1
MACH NO.
.567
PD/2V
.081
REYNOLDS NO.
2.18E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 179



CONFIG.
T1C1
MACH NO.
.567
PD/2V
0.109
REYNOLDS NO.
2.18E+06
ORDER
9
MAGNUS FORCE C.P. FROM C.G.
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT ABOUT C.G.
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 180



CONFIG.
T1C1
MACH NO.
0.567
PD/2V
0.163
REYNOLDS NO.
2.17E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 181



CONFIG.
T1C1
MACH NO.
.567
PD/2V
0.217
REYNOLDS NO.
2.18E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 183



CONFIG.
T1C1
MACH NO.
.567
PD/2V
0271
REYNOLDS NO.
2.18E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 183



CONFIG.
T1C1
MACH-NO.
.567
PD/2V
0.326
REYNOLDS NO.
2.18E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 181



CONFIG.
T1C1
MACH NO.
.550
PD/2V
.084
REYNOLDS NO.
3.00E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
.60
.30
0.0
-.30
-.60
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
.60
.30
.10
0.0
-.10
-.30
-.60
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK,DEGREES

Fig 185



CONFIG.
T1C1
MACH NO.
.550
PD/2V
.140
REYNOLDS NO.
3.00E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 186




CONFIG.
T1C1
MACH NO.
.550
PD/2V
.253
REYNOLDS NO.
3.00E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 187


CONFIG.
T1C1
MACH NO.
.550
PD/2V
.337
REYNOLDS NO.
3.00E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
MB29A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00




CONFIG.
T1C1
MACH NO.
0.567
PD/2V
0.027
REYNOLDS NO.
3.45E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 189


CONFIG.
T1C1
MACH NO.
0.567
PD/2V
0.054
REYNOLDS NO.
3.45E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00




CONFIG.
T1C1
MACH NO.
.567
PD/2V
.081
REYNOLDS NO.
3.46E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 191


CONFIG
T1C1
MACH NO.
.567
PD/2V
.109
REYNOLDS NO.
3.45E+06
ORDER
11
MAGNUS FORCE C.P. FROM C.G.
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00




CONFIG.
T1C1
MACH NO.
.567
PD/2V
.163
REYNOLDS NO.
3.46E+06
ORDER
11
BRL FREE FLIGHT RANGE RESULTS
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 198


CONFIG.
T1C1
MACH NO.
.567
PD/2V
.217
REYNOLDS NO.
3.46E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
▲ MAGNUS FORCE * MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
.30
.10
0.0
-.10
-.30
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
.30
.10
0.0
-.10
-.30
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES




CONFIG.
T1C1
MACH NO.
.567
PD/2V
.272
REYNOLDS NO.
3.46E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
* MAGNUS FORCE * MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
.30
.10
0.0
-.10
-.30
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
.60
.30
0.0
-.30
-.60
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES

Fig 195


CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.021
REYNOLDS NO.
1.68E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
1.50
4.00
6.50
9.00
11.50




CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.042
REYNOLDS NO.
1.68E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 197


CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.063
REYNOLDS NO.
1.68E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
1.50
4.00
6.50
9.00
11.50
3.00
1.50
0
-1.50
-3.00
0.50
0.30
0.10
0.0
-0.10
-0.30
-0.50



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.084
REYNOLDS NO.
1.68E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
3.00
1.50
0
-1.50
-3.00
0.50
0.30
0.10
0.0
-0.10
-0.30
-0.50

Fig 199



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.084
REYNOLDS NO.
1.68E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 199



CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.126
REYNOLDS NO.
1.68E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M629A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.3
1.50
4.00
6.50
9.00
11.50

Fig 200




CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.168
REYNOLDS NO.
1.68E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 201


MAGNUS FORCE COEFFICIENT
MAGNUS FORCE C.P. (FROM C.G.)
CONFIG.
T1C1
MACH NO.
0.727
PD/2V
0.210
REYNOLDS NO.
1.68E+06
M829A1E1
MAGNUS FORCE
MAGNUS MOMENT
ANGLE OF ATTACK (DEGREES)
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 202
224





CONFIG.
T1C1
MACH NO.
.742
PD/2V
.104
REYNOLDS NO.
2.28E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25

Fig 203


CONFIG.
T1C1
MACH NO.
.742
PD/2V
.145
REYNOL. NO.
2.28E+06
ORDER
5
O BRL FREE FLIGHT RANGE RESULTS
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT ABOUT C.G.
Fig 20
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES


CONFIG.
T101
MACH NO.
.742
PQ/2V
.249
REYNOLDS NO.
2.28E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 205
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES



CONFIG.
T1C1
MACH NO.
.850
PD/2V.
.018
REYNOLDS NO.
1.35E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 206



CONFIG.
T1C1
MACH NO.
.850
PD/2V
0.036
REYNOLDS NO.
1.35E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 207



CONFIG.
T1C1
MACH NO.
.850
PD/2V
.054
REYNOLDS NO.
1.35E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 20a



CONFIG.
T1G1
MACH NO.
.850
PD/2V
0.072
REYNOLDS NO.
1.35E+06
ORDER
1
MAGNUS FORCE C(P_(ERON C(A-))
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C(G.))
ANGLE OF ATTACK, DEGREES
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 209



CONFIG.
T1C1
MACH NO.
.850
PD/2V
0.109
REYNOLDS NO.
1.35E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
2.0
1.50
4.00
6.50
9.00
11.50

Fig 210




CONFIG.
T1C1
MACH NO.
.850
PD/2V
.145
REYNOLDS NO.
1.35E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 21


CONFIG.
T1C1
MACH NO.
.850
PO/2V
0.181
REYNOLDS NO.
1.35E+06
ORDER
7
MAGNUS FORCE C
A MAGNUS FORCE
* MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-3.00
-1.00
0.0
1.50
4.00
6.50
9.00
11.00
ANGLE OF ATTACK, DEGREES



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.017
REYNOLDS NO.
1.79E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 213



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.036
REYNOLDS NO.
1.79E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
0.50
0.30
0.10
0.0
-0.10
-0.30
-0.50
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
0.50
0.30
0.10
0.0
-0.10
-0.30
-0.50
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 21d



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.054
REYNOLDS NO.
1.79E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 215



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.072
REYNOLDS NO.
1.79E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 21



CONFIG.
T1C1
MACH NO.
0.850
RD/2V
0.108
REYNOLDS NO.
1.78E+06
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 21.7



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.144
REYNOLDS NO.
1.79E+06
BRL FREE FLIGHT RANGE RESULTS
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
0.50
0.30
0.10
0.0
-0.10
-0.30
-0.50
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 218



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.180
REYNOLDS NO.
1.79E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 219



CONFIG.
T1C1
MACH NO.
0.850
PD/2V
0.216
REYNOLDS NO.
1.79E+06
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 120



CONFIG.
TIC1
MACH NO.
.949
PD/2V
.096
REYNOLDS NO.
1.18E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-5.00
-4.00
-2.00
0
2.00
4.00
6.00
8.00
ANGLE OF ATTACK, DEGREES

Fig 221




CONFIG.
TICI
MACH NO.
.949
PD/2V
.144
REYNOLDS NO.
1.18E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-4.00
-2.00
2.00
4.00
5.00
6.00

Fig 222


CONFIG.
T1C1
MACH NO.
.949
PD/2V
.193
REYNOLDS NO.
1.18E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 223



CONFIG.
6(C
MACH NO.
.307
PO/2V
.103
REYNOLDS NO.
1.78E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.50
-7.50
-4.50
-1.50
0.0
1.50
4.50
7.50
10.50

Fig 224




CONFIG.
G1C1
MACH NO.
.306
PO/2V
.104
REYNOLDS NO.
1.75E+06
ORDER
2
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 225


CONFIG.
GIC
MACH NO.
.307
PD/2V
.154
REYNOLDS NO.
1.78E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 225
ANGLE OF ATTACK, DEGREES



CONFIG.
GICI
MACH NO.
.306
PD/2V
.156
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00
3.00
1.50
0
-1.50
-3.00
2.00
1.00
0
-1.00
-2.00
-3.00

Fig 227



CONFIG.
G1C1
MACH NO.
.307
PQ/P2M
.257
REYNOLDS NO.
1.78E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.50
-7.50
-4.50
-1.50
0.0
1.50
4.50
7.50
10.50

Fig 22a



CONFIG.
G1C1
MACH NO.
.306
PD/2V
.260
REYNOLDS NO.
1.75E+06
ORDER
2
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 229



CONFIG.
GICI
MACH NO.
.307
PD/2V
.360
REYNOLDS NO.
1.78E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
.50
.30
.10
0.0
-.10
-.30
-.50
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-10.50
-7.50
-4.50
-1.50
0.0
1.50
4.50
7.50
10.50
ANGLE OF ATTACK, DEGREES

Fig. 230




CONFIG.
G1C1
MACH NO.
.306
PD/2V
.364
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
3.00
1.50
0
-1.50
-3.00
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
2.00
1.00
0
-1.00
-2.00
-3.00
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
2.00
1.00
0
-1.00
-2.00
-3.00
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00
ANGLE OF ATTACK, DEGREES

Fig 231


CONFIG.
GIC1
MACH NO.
.567
PQ/2V
.083
REYNOLDS NO.
2.92E+06
ORDER
6
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig. 232
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES



CONFIG.
GIC1
MACH NO.
.567
PO/2V
.138
REYNOLDS NO.
2.92E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-5.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 233




CONFIG.
GICT
MACH NO.
.567
PO/2V
.248
REYNOLDS NO.
2.92E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 234


CONFIG.
TICO
MACH NO.
.306
PD/2V
.052
REYNOLDS NO.
1.76E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 235
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES



CONFIG.
TICO
MACH NO.
.306
PD/2V
.104
REYNOLDS NO.
1.76E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 236



CONFIG.
TIC O
MACH NO.
.306
PD/2V
.156
REYNOLDS NO.
1.76E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig 237







CONFIG.
TICQ
MACH NO.
.306
PD/2V
.208
REYNOLDS NO.
1.76E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50

Fig.238


CONFIG.
TICO
MACH NO.
.306
PD/2V
.312
REYNOLDS NO.
1.76E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 237
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK,DEGREES


CONFIG.
T/C 0
MACH NO.
.305
PD/2V
.416
REYNOLDS NO.
1.7FE+06
ORDER
11
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE C.P. FROM C.G.
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
3.00
1.00
0
-1.00
-2.00
-3.00
2.00
1.00
0
-5.00


CONFIG-
TICO
MACH NO.
.306
PD/2V
.520
REYNOLDS NO.
1.76E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50


CONFIG.
T1C0
MACH NO.
.306
PD/2V
.624
REYNOLDS NO.
1.76E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 262
ANGLE OF ATTACK,DEGREES
-11.00
-5.50
0
5.50
16.50
22.00
27.50



CONFIG.
T1CO
MACH NO.
.307
PD/2V
.051
REYNOLDS NO.
2.36E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 243



CONFIG.
TICO
MACH NO.
.307
RD/2V
.102
REYNOLDS NO.
2.36E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 21






CONFIG.
TICO
MACH NO.
.307
PD/2V
.159
REYNOLDS NO.
2.36E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 245


CONFIG.
T1CO
MACH NO.
.307
PD/2V
.204
REYNOLDS NO.
2.36E+06
ORDER
11
MAGNUS FORCE C(P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C(G.)
Fig 2.6
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK,DEGREES


CONFIG.
T1CO
MACH NO.
.307
PD/2V
.306
REYNOLDS NO.
2.36E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
Fig 247
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK, DEGREES


CONFIG.
T1CO
MACH NO.
.307
PD/2V
.408
REYNOLDS NO.
2.36E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
Fig 24







CONFIG.
TICO
MACH NO.
.907
PD/2V
.510
REYNOLDS NO.
2.36E+06
ORDER
11
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00
ANGLE OF ATTACK, DEGREES

Fig 211


CONFIG.
T1C0
MACH NO.
.557
PD/2V
.109
REYNOLDS NO.
2.89E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK (DEGREES)
-6.00
-3.00
0
3.00
12.00
15.00


CONFIG.
TICO
MACH NO.
.557
PD/2V
.163
REYNOLDS NO.
2.89E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT ABOUT C.(G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00


CONFIG.
T1CO
MACH NO.
.557
PD/2V
.245
REYNOLDS NO.
2.89E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
Fig 23.2


CONFIG.
T1CO
MACH NO.
.565
PD/2V
.027
REYNOLDS NO.
3.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 253
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00




CONFIG.
T1CO
MACH NO.
.56$
PD/2V
.054
REYNOLDS NO.
3.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 264


CONFIG.
T1CO
MACH NO.
.565
PD/2V
.081
REYNOLDS NO.
3.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 255
ANGLE OF ATTACK, DEGREES



CONFIG.
T1CO
MACH NO.
.565
PD/2V
.103
REYNOLDS NO.
3.37E+06
ORDER
1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 256



CONFIG.
T1CC
MACH NO.
.565
PD/2V
.108
REYNOLDS NO.
3.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-4.00
0
2.00
4.00
6.00

Fig 257



CONFIG.
T1CO
MACH NO.
.565
PD/2V
.217
REYNOLDS NO.
3.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 258



CONFIG.
T1CO
MACH NO.
.565
PD/2V
.271
REYNOLDS NO.
3.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
0
5.00
8.00
12.00
15.00

Fig 259



CONFIG.
T1CO
MACH NO.
.747
PD/2V
.021
REYNOLDS NO.
1.69E+06
ORDER
S
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 260




CONFIG.
MACH NO.
PD/2V
REYNOLDS NO.
ORDER
T1CO
.747
.042
1.69E+06
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 24


CONFIG.
TICO
MACH NO.
.747
PO/2V
.063
REYNOLDS NO.
1.69E+06
ORDER
2
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 262
ANGLE OF ATTACK, DEGREES



CONFID.
TICO
MACH NO.
.747
PD/2V
.089
REYNOLDS NO.
1.69E+06
ORDER
2
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 263



CONFIG.
T1CO
MACH NO.
.747
PD/2V
.125
REYNOLDS NO.
1.69E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
ANGLE OF ATTACK, DEGREES

Fig 264



CONFIG.
TLCO
MACH NO.
.747
PD/2V
.167
REYNOLDS NO.
1.69E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK,DEGREES

Fig 265



CONFIG.
T1CO
MACH NO.
.747
PD/2V
.209
REYNOLDS NO.
1.69E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25

Fig 366




CONFIG.
TICO
MACH NO.
.747
PO/2V
.250
REYNOLDS NO.
1.69E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 267


CONFIG.
TICO
MACH NO.
.745
PD/2V
.103
REYNOLDS NO.
2.27E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 268
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES



CONFIG.
T1C0
MACH NO.
.745
PO/2V
.144
REYNOLDS NO.
2.27E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25

Fig 269



CONFIG.
TICO
MACH NO.
.745
PD/2V
.247
REYNOLDS NO.
2.27E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25

Fig Z7D




CONFIG.
T1CO
MACH NO.
.847
PD/2V
.018
REYNOLDS NO.
1.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 271


CONFIG.
T1CO
MACH NO.
.847
PD/2V
.036
REYNOLDS NO.
1.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 272
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES



CONFIG.
T1CO
MACH NO.
.847
PD/2V
.054
REYNOLDS NO.
1.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 273



CONFIG.
TLCO
MACH NO.
.842
PD/2V
.072
REYNOLDS NO.
1.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
-10.00
-5.00
-2.00
0
2.00
5.00
7.00
10.00
ANGLE OF ATTACK, DEGREES

Fig 274



CONFIG.
TICO
MACH NO.
.847
PD/2V
.108
REYNOLDS NO.
1.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.B.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 275




CONFIG.
T1CO
MACH NO.
.847
PD/2V
.144
REYNOLDS NO.
1.97E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-2.00
0
2.00
5.00
7.50
10.00

Fig 276


CONFIG.
T1CO
MACH NO.
.847
PD/2V
.180
REYNOLDS NO.
1.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 277
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK,DEGREES



CONFIG.
T1CO
MACH NO.
.847
PØ/2V
.216
REYNOLDS NO.
1.37E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 27B



CONFIG.
TIGO
MACH NO.
.846
PD/2V
.090
REYNOLDS NO.
1.86E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 279



CONFIG.
TICO
MACH NO.
.846
PD/2V
.143
REYNOLDS NO.
1.86E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 280




CONFIG.
T1CO
MACH NO.
.846
PD/2V
.215
REYNOLDS NO.
1.86E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 281


CONFIG.
T1C0
MACH NO.
.948
PD/2V
.096
REYNOLDS NO.
1.2DE+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig. 282
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES



CONFIG.
T1CO
MACH NO.
.948
PD/2V
.144
REYNOLDS NO.
1.2DE+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 283



CONFIG.
TICO
MACH NO.
.948
PD/2V
.192
REYNOLDS NO.
1.20E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 384



CONFIG.
T1CO
MACH NO.
.949
PD/2V
.096
REYNOLDS NO.
1.62E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 285



CONFIG.
T1C0
MACH NO.
.949
PD/2V
.144
REYNOLDS NO.
1.62E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 286



CONFIG.
TICO
MACH NO.
.949
PD/2V
.192
REYNOLDS NO.
1.62E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0.
2.50
5.00
7.50
10.00

Fig 287




CONFIG.
T2C1
MACH NO.
.308
PQ/2V
.051
REYNOLDS NO.
1.78E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-12.00
-9.00
-6.00
-3.00
0
3.00
6.00
9.00

Fig 288


CONFIG.
T2C1
MACH NO.
.306
PD/2V
.052
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 289
ANGLE OF ATTACK, DEGREES
311



CONFIG.
T2C1
MACH NO.
.308
PD/2V
.103
REYNOLDS NO.
1.78E+06
ORDER
5
MAGNUS FORCE C.P. - AERON C.G.
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-12.00
-9.00
-6.00
-3.00
0
3.00
6.00
9.00

Fig 290




CONFIG.
T2C1
MACH NO.
.306
PD/2V
.105
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M82S91E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 291


CONFIG.
T2C1
MACH NO.
.308
PD/2V
.152
REYNOLDS NO.
1.78E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK.DEGREES
-12.00
-9.00
-6.00
-3.00
0
3.00
6.00
9.00




CONFIG.
T2C1
MACH NO.
.306
RD/2V
.157
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 293


CONFIG.
T2C1
MACH NO.
.308
PD/2V
.203
REYNOLDS NO.
1.78E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 29a
-12.00
-9.00
-6.00
-3.00
0
3.00
6.00
9.00
ANGLE OF ATTACK, DEGREES




CONFIG.
T2C1
MACH NO.
.306
PD/2V
.209
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 295


CONFIG.
T2C1
MACH NO.
.308
PD/2V
.305
REYNOLDS NO.
1.78E+06
ORDER
7
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 296




CONFIG.
T2C1
MACH NO.
.306
PD/2V
.314
REYNOLDS NO.
1.75E+06
ORDER
2
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00
3.00
1.50
0
-1.50
-3.00
.60
0
-.60
-1.20
-2.40
.90
0
-.90
-1.80
-2.70
-3.60

Fig 297


CONFIG.
T2C1
MACH NO.
.308
PO/2V
.407
REYNOLDS NO.
1.78E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 298
-12.00
-9.00
-6.00
-3.00
0
3.00
6.00
9.00
ANGLE OF ATTACK, DEGREES




CONFIG.
T2C1
MACH NO.
.306
PD/2V
.419
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 299


CONFIG.
T2C1
MACH NO.
.308
PD/2V
.508
REYNOLDS NO.
1.78E+06
ORDER
7
MAGNUS FORCE C.P. FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 300
ANGLE OF ATTACK, DEGREES






CONFIG.
T2C1
MACH NO.
.306
PD/2V
.523
REYNOLDS NO.
1.75E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
ANGLE OF ATTACK,DEGREES
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00

Fig 301


CONFIG.
T2C1
MACH NO.
.308
PD/2V
.610
REYNOLDS NO.
1.78E+06
ORDER
1
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 302
-12.00
-9.00
-6.00
-3.00
0
3.00
6.00
9.00
ANGLE OF ATTACK, DEGREES


CONFIG.
T2C1
MACH NO.
.569
PD/2V
.027
REYNOLDS NO.
2.93E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 303
-6.00
-3.00
0.
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES


CONFIG.
12C1
MACH NO.
.569
PD/2V
.054
REYNOLDS NO.
2.93E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fig 30e
ANGLE OF ATTACK, DEGREES



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.080
REYNOLDS NO.
2.93E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 305



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.107
REYNOLDS NO.
2.98E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
0
5.00
10.00
15.00

Fig 305



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.161
REYNOLDS NO.
2.93E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
MB29A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00

Fig 307



CONFIG.
T2C1
MACH NO.
.569
PD/2V
.214
REYNOLDS NO.
2.93E+06
ORDER
3
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
0
5.00
10.00
15.00

Fig 308



CONFIG.
T201
MACH NO.
.569
PD/2V
.268
REYNOLDS NO.
2.93E+06
ORDER
9
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
0
5.00
10.00
12.00
15.00

Fig 309



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.021
REYNOLDS NO.
1.67E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 319



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.041
REYNOLDS NO.
1.67E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
ANGLE OF ATTACK, DEGREES

Fig 3.1



CONFIG.
T2C1
MACH NO.
.740
PQ/2V
.062
REYNOLDS NO.
1.67E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
3.00
5.50
9.00
11.50

Fig 312



CONFIG.
T2C1
MACH NO.
.740
PD/2V
.083
REYNOLDS NO.
1.6VE+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK.DEGREES

Fig 313

CONFIG.
T2C1
MACH NO.
.740
PD/2V
.124
REYNOLDS NO.
1.67E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 314




CONFIG.
T2C1
MACH NO.
.740
PD/2V
.166
REYNOLDS NO.
1.67E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES
-5.00
-3.00
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 315


CONFTG.
T2C1
MACH NO.
.740
RD/2V
.207
REYNOLDS NO.
1.67E+00
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
Fin 316
ANGLE OF ATTACK,DEGREES



CONFIG
T2C1
MACH NO
.740
PD/2V
.249
REYNOLDS NO
1.67E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
ANGLE OF ATTACK DEGREES

Fig 317



CONFIG.
T2C1
MACH NO.
.852
PD/2V
.018
REYNOLDS NO.
1.39E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES

Fig 318




CONFIG.
T2C1
MACH NO.
.852
PD/2V
.036
REYNOLDS NO.
1.99E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
ANGLE OF ATTACK, DEGREES

Fig 319


CONFIG.
T2C1
MACH NO.
.852
PD/2V
.054
REYNOLDS NO.
1.39E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
Fig 320
ANGLE OF ATTACK, DEGREES
372



CONFIG.
T2C1
MACH NO.
.852
PD/2V
.071
REYNOLDS NO.
1.39E+06
ORDER
7
MAGNUS FORCE C.P. FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-2.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 321



CONFIG.
T2C1
MACH NO.
.852
PB/2V
.107
REYNOLDS NO.
1.98E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 32d



CONFIG.
T2C1
MACH NO.
.852
PO/2V
.143
REYNOLDS NO.
1.39E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1F1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 323



CONFIG.
T2C1
MACH NO.
.852
PB/2V
.178
REYNOLDS NO.
1.39E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES

Fig 324



CONFIG.
T2C1
MACH NO.
.852
PD/2V
.214
REYNOLDS NO.
1.59E+06
ORDER
7
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
ANGLE OF ATTACK, DEGREES

Fig 325



CONFIG.
T2C1
MACH NO.
.950
PB/2V
.016
REYNOLDS NO.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
-5.00
-3.50
-1.00
0.0
1.50
3.00
5.50
8.00
11.50
ANGLE OF ATTACK, DEGREES

Fig 326





CONFIG.
T2C1
MACH NO.
.950
PD/P.V
.032
REYNOLDS NO.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 327


CONFIG.
T2C1
MACH NO.
.950
PD/2V
.048
REYNOLDS NO.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
Fig 328
950

CONFIG.
T2C1
MACH NO.
.950
PB/2V
.064
REYNOLDS NO.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
ANGLE OF ATTACK, DEGREES

Fig 329


CONFIG.
T2C1
MACH NO.
.950
PD/2V
.087
REYNOLDS NO.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
Fig 330



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.129
REYNOLDS NO.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M329A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK, DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 33



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.161
REYNOLDS NO.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-5.00
-3.50
-1.00
0.0
1.50
3.00
5.50
9.00
11.50

Fig 332




CONFIG.
T2C1
MACH NO.
.950
PD/2V
.193
REYNOLDS NU.
1.18E+06
ORDER
5
MAGNUS FORCE C.P. (FROM C.G.)
MAGNUS FORCE
MAGNUS MOMENT
M829A1E1
MAGNUS FORCE COEFFICIENT
MAGNUS MOMENT COEFFICIENT (ABOUT C.G.)
ANGLE OF ATTACK,DEGREES
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50

Fig 333

Figures 334 through 357

Pitching moment secant slope, Magnus moment secant slope vs angle of attack

Preceding page blank


CONFIG.
T1C1
MACH NO.
.727
PD/2V
.168
REYNOLDS NO.
1.63E+06
ORDER
11
PITCH MOMENT SECANT SLOPE ABOUT C.G.
3.50
3.25
3.00
2.75
2.50
2.25
M329A1E1
NORMAL MOMENT SECANT SLOPE ABOUT C.G.
1.00
.75
.50
.25
0
Fig 33i
-5.25
-3.75
-1.25
0.0
1.25
3.75
5.25
8.75
11.25
ANGLE OF ATTACK,DEGREES



CONFIG.
T1C1
MACH NO.
.742
PD/2V
.145
REYNOLDS NO.
2.28E+06
ORDER
5
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M829A1E1
ANGLE OF ATTACK, DEGREES

Fig 335




CONFIG.
T1C1
MACH NO.
.850
PD/2V
.145
REYNOLDS NO.
1.35E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
3.50
3.25
3.00
2.75
2.50
M32SA1E1
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
.50
.25
0
-.25
-.50
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK, DEGREES

Fig 33A


CONFIG.
T1C1
MACH NO.
.850
PD/2V
.144
REYNOLDS NO.
1.80E+06
ORDER
7
PITCH MOMENT SECANT SLOPE ABOUT C.G.
3.50
3.25
3.00
2.75
2.50
MAGNUS MOMENT SECANT SLOPE ABOUT C.G.
.40
.20
0
-.20
-.40
M329A1E1
Fig 337
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES



CONFIG.
T1C1
MACH NO.
.948
PD/2V
.144
REYNOLDS NO.
1.18E+06
ORDER
11
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1F1
ANGLE OF ATTACK, DEGREES
-5.00
-4.00
-2.00
0
2.00
4.00
5.00
6.00

Fig 33b




CONFIG.
G1C1
MACH NO.
.307
PO/2V
.154
REYNOLDS NO.
1.78E+06
ORDER
5
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1E1
ANGLE OF ATTACK, DEGREES
-10.50
-7.50
-4.50
-1.50
0.0
1.50
4.50
7.50
10.50

Fig. 339


CONFIG.
G1C1
MACH NO.
.306
PD/2V
.156
REYNOLDS NO.
1.75E+06
ORDER
9
PITCH MOMENT SECANT SLOPE ABOUT C.G.
MAGNUS MOMENT SECANT SLOPE ABOUT C.G.
M329A1E1
Fig 340
ANGLE OF ATTACK.DEGREES



CONFIG.
GICI
MACH NO.
.567
PD/2V
.138
REYNOLDS NO.
2.92E+06
ORDER
5
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
3.75
3.50
3.25
3.00
2.75
2.50
M329A1E1
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
2.00
1.00
0
-1.00
-2.00
-5.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES

Fig 341



CONFIG.
TICO
MACH NO.
.306
PD/2V
.158
REYNOLDS NO.
1.75E+06
ORDER
11
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1F1
-11.00
-5.50
0
5.50
11.00
16.50
22.00
27.50
ANGLE OF ATTACK, DEGREES

Fig 312



CONFIG.
TICO
MACH NO.
.907
PD/2V
.153
REYNOLDS NO.
2.36E+06
ORDER
11
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1F1
ANGLE OF ATTACK, DEGREES
-10.00
-6.00
-2.00
0.0
2.00
6.00
10.00
14.00
18.00

Fig 343



CONFIG.
T1CO
MACH NO.
.557
PD/2V
.163
REYNOLDS NO.
2.89E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
3.50
3.25
3.00
2.75
2.50
1.00
.50
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
-.50
-1.00
M329A1E1
-6.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK.DEGREES

Fig 344





CONFIG.
T1CO
MACH NO.
.565
PD/2V
.163
REYNOLDS NO.
3.37E+06
ORDER
7
PITCH MOMENT SECANT SLOPE ABOUT C.G.
3.00
2.75
2.50
2.25
2.00
.30
MB29A1E1
MAGNUS MOMENT SECANT SLOPE ABOUT C.G.
0
-.30
-.60
-.90
-1.20
-6.00
-3.00
0
3.00
6.00
9.00
12.00
15.00
ANGLE OF ATTACK, DEGREES

Fig 345


CONFIG.
TICO
MACH NO.
.747
PD/2V
.167
REYNOLDS NO.
1.69E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1E1
ANGLE OF ATTACK, DEGREES
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25


CONFIG.
T1CO
MACH NO.
.745
PD/2V
.144
REYNOLDS NO.
2.27E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
3.50
3.25
3.00
2.75
2.50
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
3.00
2.00
1.00
0
-1.00
-2.00
M329A1F1
Fig 347
-6.25
-3.75
-1.25
0.0
1.25
3.75
6.25
8.75
11.25
ANGLE OF ATTACK,DEGREES



CONFIG.
TICO
MACH NO.
.847
PD/2V
.144
REYNOLDS NO.
1.97E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1F1
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK,DEGREES

Fig 348



CONFIG.
TICO
MACH NO.
.846
PD/2V
.143
REYNOLDS NO.
1.86E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M829A1E1
4.00
3.75
3.50
3.25
3.00
1.00
0
-1.00
-2.00
-3.00
-4.00
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK,DEGREES

Fig 349



CONFIG.
T1CD
MACH NO.
.948
PD/2V
.144
REYNOLDS NO.
1.2DE+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1F1
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00
ANGLE OF ATTACK, DEGREES

Fig 350




CONFIG.
TICO
MACH NO.
.949
PD/2V
.144
REYNOLDS NO.
1.62E+06
ORDER
5
PITCH MOMENT SECANT SLOPE ABOUT C.G.
MAGNUS MOMENT SECANT SLOPE ABOUT C.G.
M329A1E1
ANGLE OF ATTACK, DEGREES
-7.50
-5.00
-2.50
0
2.50
5.00
7.50
10.00

Fig 35


CONFIG.
T2C1
MACH NO.
.308
PD/2V
.152
REYNOLDS NO.
1.78E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M829A1E1
Fig 352
ANGLE OF ATTACK, DEGREES
-12.00
-9.00
-6.00
-3.00
0.
3.00
6.00
9.00
2.50
2.00
1.50
1.00
.50
0
-.50
-1.00
-1.50
-2.00
-2.50
1776



CONFIG.
T2C1
MACH NO.
.305
PD/2V
.157
REYNOLDS NO.
1.75E+06
ORDER
9
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
2.50
2.25
2.00
1.75
1.50
1.25
1.00
.50
0
-.50
M329A1F1
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
0
4.00
8.00
12.00
16.00
20.00
24.00
28.00
ANGLE OF ATTACK,DEGREES

Fig 353





CONFIG.
T2C1
MACH NO.
.569
PO/2V
.161
REYNOLDS NO.
2.9EE+06
ORDER
9
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
M329A1F1
ANGLE OF ATTACK,DEGREES
-5.00
0
5.00
10.00
15.00

Fig 95a


CONFIG.
T2C1
MACH NO.
.740
PD/2V
.166
REYNOLDS NO.
1.67E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
2.75
2.50
2.25
2.00
1.75
1.50
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
.25
0
-.25
-.50
-.75
M829A1E1
Rig 355
-6.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK,DEGREES


CONFIG.
T2C1
MACH NO.
.852
PD/2V
.145
REYNOLDS NO.
1.39E+06
ORDER
7
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
3.00
2.75
2.50
2.25
2.00
1.75
M829A1E1
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
-.50
-.80
-1.10
-1.40
-1.70
FIG 356
-5.00
-3.50
-1.00
0.0
1.50
4.00
6.50
9.00
11.50
ANGLE OF ATTACK,DEGREES
380



CONFIG.
T2C1
MACH NO.
.950
PD/2V
.161
REYNOLDS NO.
1.18E+06
ORDER
5
PITCH MOMENT SECANT SLOPE (ABOUT C.G.)
3.00
2.75
2.50
2.25
2.00
M329A1E1
MAGNUS MOMENT SECANT SLOPE (ABOUT C.G.)
.30
.20
-5.00
-3.50
-1.00
0.0
4.00
6.50
9.00
11.50
ANGLE OF ATTACK, DEGREES

Fig 367




Fig 358 Pitching moment coefficient derivative vs Mach No.
(NBT_1C_1, NBT_1C_0, NBT_2C_1, NBG_1C_1)

Figures 359 and 360

Magnus moment coefficient derivative vs Mach No.
(NBT_1C_1, NBT_1C_0, NBT_2C_1)



ANGLE OF ATTACK = 4°
pd/2V = 0.16
○ N2T1C1
□ N3T1C2
◇ N4T2C1
MAGNUS MOMENT COEFFICIENT DERIV. $C_{n_{pa}}$
(Per Rad.)
2
1
0
-1
-2
0.1
0.2
0.4
0.5
0.6
0.7
0.8
0.9
1.0

Fig. 359



ANGLE OF ATTACK = 5°
pd/2V = 0.16
MST, C1
MST2C0
MST2C1
MAGNUS MOMENT COEFFICIENT DERIV Cnp*
(PER RAD)
3.0
2.0
1.0
0
-1.0
-2.0
0.1
0.2
.4
.5
.6
.7
.8
.9
1.0
MACH NUMBER

Fig 360

Figures 361 through 367

Magnus moment coefficient derivative vs pd/2V
(NBT_1C_1)

Preceding page blank



MACH NO. = 0.302
ANGLE OF ATTACK
2°
4°
8°
12°
16°
MAGNUS MOMENT COEFFICIENT DERIV $C_{n_{pa}}$ (1/RAD)
6
4
2
0
-2
-4
-6
0.1
0.2
0.3
0.4
NON-DIMENSIONAL SPIN pd/2V

Fig 361



MACH NO. = 0.303
ANGLE OF ATTACK
20°
24°
28°
30°
MAGNUS MOMENT COEFFICIENT DERIV. $C_{n_p\alpha}$ (1/RAD)
6
4
2
0
-2
-4
-6
0.1
0.2
0.3
0.4
NON-DIMENSIONAL SPIN (pd/2v)

Fig 362



MACH No. = 0.567
ANGLE OF ATTACK
MAGNUS MOMENT COEFFICIENT DERIV C_{mpa} (1/RAD)
6
4
2
0
-2
-4
-6
0.2
0.3
0.4
NON-DIMENSIONAL SPIN $Pb/2V$

Fig 363



MACH No. = 0.567
ANGLE OF ATTACK
10°
12°
14°
16°
MAGNUS MOMENT COEFFICIENT DERIV $C_{n_{pk}}$ (1/RAD)
6
4
2
0
-2
-4
-6
0.1
0.2
0.3
0.4
NON-DIMENSIONAL SPIN Pd/2V

Fig 364



MACH No = 0.742
ANGLE OF ATTACK
2°
4°
6°
8°
10°
12
MAGNUS MOMENT COEFFICIENT DERIV C_{n_p} (1/RAD)
4
2
0
-2
-4
0.1
0.2
0.3
0.4
NON-DIMENSIONAL SPIN Pd/2V

Fig 365



MACH NO. = 0.85
ANGLE OF ATTACK
2°
4°
6°
8°
10°
MAGNUS MOMENT COEFFICIENT DERIV $C_{n_{pa}}$ (1/RAD)
6
4
2
0
2
4
6
0.2
0.3
0.4
NON-DIMENSIONAL SPIN pd/2V

Fig 366



MACH NO. = 0.949
ANGLE OF ATTACK
4.2°
6.4°
MAGNUS MOMENT COEFFICIENT DERIV $C_{n_{P_\alpha}}$ (1/RAD)
6
4
2
-2
-4
0.1
0.2
0.3
0.4
NON-DIMENSIONAL SPIN Pd/2V

Fig 367

Figures 368 through 369

Muzzle velocity vs range for performance flight tests at Yuma Proving Ground



LOW CHARGE
QUADRANT ELEVATION = 1066 MILS
FIRED JULY 1970 AT YUMA PROVING GROUND
270
260
250
MUZZLE VELOCITY (fps)
500
520
540
560
RANGE (METERS)

Fig 368



HIGH CHARGE
QUADRANT ELEVATION = 800 MILS
FIRED JUNE 1969 AT YUMA PROVING GROUND
1100
1000
900
800
MUZZLE VELOCITY (f.p.s.)
5000
5500
6000
6500
7000
7500
8000
RANGE (METERS)

FIG 867

Figures 370 through 374

Yaw data translated from camera coverage shown in Figure 8

Preceding page blank



ALPHA (PITCH ANGLE) VS TIME IN FLIGHT
MISSILE IS JUNE 1969
MUZZLE CAMERA S-2
R.E. = 1044.7 MILS
ROUND 2148 257 fps
ROUND 2150 257 fps
ROUND 2151 257 fps
ALPHA (DEGREES)
TIME (SEC.)
0.1
0.15
0.2
0.25
0.3
0
5
10
15
20
30

FIG 320



BETA (YAW ANGLE) VS TIME IN FLIGHT
M329A1E1 13 JUNE 1969
MUZZLE CAMERA 6-1
QE = 1066.7 MILS
ROUND 2148 Vm 852 fps
ROUND 2150 257 fps
ROUND 2151 257 fps
15
10
5
0
-5
-10
-15
BETA (DEGREES)
0.1
0.15
0.2
0.25
0.3
TIME (SEC.)

FIG 3.7.1



M329A1E1 13 JUNE 969 ROUND 2151 QE = 964.7 MILS
CAMERA B-2
VM = 257 FPS
YAW ANGLE (DEGREES)
50
40
30
20
10
10
20
30
40
50
60
70
80 FRAMES
5.0
5.5
6.0
6.5
7.0
7.5 SECONDS
FRAME NUMBER
APPROX. TIME IN FLIGHT (SECONDS)

Fig 372



CAMERA C-1
CAMERA C-3
M32QA3E1 3 JUNE 1969 2QUND 2151 QE = 1066.7 m/s
Vm = 257 fps
ANGLE (DEGREES)
40
30
20
10
100
110
120
130
140
150
160 FRAMES
8.0
8.5
9.0
9.5
10.0 SECONDS
FRAME NUMBER
APPROX TIME IN FLIGHT (SECONDS)

Fig 373



50
40
30
20
10
YAW ANGLE (DEGREES)
M329A1E1 18 JUNE 1969 ROUND 2151 QE = 1066.7 MILS
CAMERA B-3
VM = 257 fps
170
180
190
200
210
220
230
240 FRAMES
SECONDS
105
110
115
FRAME NUMBER
APPROX TIME IN FLIGHT (SECONDS)

Fig 374



Fig 375 M329A1E1 projectile fired at low charge, with obturator still attached




Fig 376 Pitching moment coefficient derivative and normal force center of pressure vs Mach No. (SPINNER and the BRL Transonic Range) (NBG_1C_1, NBT_1C_1)




Fig 377 Normal force coefficient derivative and drag coefficient vs Mach No.
(SPINNER and the BRL Transonic Range)




Fig 378 Mach No. and pd/2V vs time of flight for M329A1E1 six-degree of freedom trajectory computer simulations. (QE = 60°, V_{muzzle} = 1040 fps)




Fig 379 Mach No. and pd/2V vs time of flight for M329A1E1 six-degree of freedom trajectory computer simulations. (QE = 45° , V_{muzzle} = 1040 fps)




Fig 380 Pitch damping coefficient and spin damping coefficient vs Mach No.




Fig 381 Muzzle gyroscopic stability factors vs Mach No.

Figures 382 through 386

Damping factors vs angle of attack for configuration NBT_1C_1 at various Mach numbers

Preceding page blank



MACH NUMBER = 0.505
○ λ1*
□ λ2*
MUZZLE CONDITION
NUTATION & PRECESSION DAMPING FACTORS (1/SEC.)
λ1* & λ2*
1.0
0.5
0
-0.5
-1.0
-1.5
10
20
30
ω1 DEG.

Fig 382



MACH NO. = 0.550
MUZZLE CONDITION
λ_1^*
λ_2^*
NUTATION & PRECESSION DAMPING FACTORS (1/SEC)
λ_1^* & λ_2^*
1.0
0.5
0
-0.5
10
20
α, DEG.

Fig 383



MACH NO = 0.757
MUZZLE CONDITION
NUTATION & PRECESSION DAMPING FACTORS (1/SEC)
0.5
0
-0.5
-1.0
5
10
DEG

Fig 38+



MACH NO. = 0.850
MUZZLE CONDITIONS
λ_1^*
λ_2^*
NUTATION AND PRECESSION DAMPING FACTORS (1/SEC)
0.5
0
-0.5
-1.0
10
α, DEG

Fig 385



MACH NUMBER = 0.949
MUZZLE CONDITION
○ λ_1^*
□ λ_2^*
1.5
1.0
0.5
0
-0.5
-1.0
-1.5
-2.0
-2.5
5
10
x, DEG.
NUTATION & PRECESSION DAMPING FACTORS (1/SEC)
λ_1^* & λ_2^*

Fig 386

Figures 387 and 388

Solar aspect angle vs time of flight for M329A1E1
yaw sonde Round No. 4737



YAW SONDE ROUND
4737
QE = 45° VEL$_m$ = 1050 fps
5.2 5.4 5.6 5.8 6.0 6.2 6.4 6.6 6.8 7.0 7.2 7.4 7.6 7.8
TIME - SEC.
YAW (DEGREES)
17.6 17.8 18.0 18.2 18.4 18.6 18.8 19.0 19.2 19.4 19.6 19.8 20.0 20.2
TIME - SEC.

Fig 387



ROUND 4737
THETA (2DEG/IN)
33.0
33.2
33.4
33.6
33.8
34.0
34.2
34.4
34.6
34.8
35.0
35.2
35.4
35.6
TIME — SEC.

Fig 388

Figures 389 and 390

Solar aspect angle vs time of flight for M329A1E1
yaw sonde Round No. 4739

Preceding page blank



YAW SONDE ROUND 4739
QE = 60° VEL_m = 1050 fps
3.2
3.4
3.6
3.8
4.0
4.2
4.4
4.6
4.8
5.0
TIME — SEC
20.0
20.2
20.4
20.6
20.8
2.0
2.2
2.4
2.6
TIME — SEC

Fig 389



ROUND 4739
TIME — SEC.
41.8
42.0
42.2
42.4
42.6
42.8
43.0
43.2
43.4
43.6
43.8
THETA (2 DEG/IN.)

Fig 390

Figures 391 and 392

Solar aspect angle vs time of flight for M329A1E1
yaw sonde Round No. 4740

Preceding page blank



YAW SONDE ROUND
4740
QE=60° VEL$_m$=1050
TIME - SEC.
7.6
7.8
8.0
8.2
8.4
8.6
8.8
9.0
9.2
9.4
9.6
9.8
10.0
10.2
22.2
22.4
22.6
22.8
23.0
23.2
23.4
23.6
23.8
24.0
24.2
24.4
24.6
24.8

Fig 391



ROUND 4740
THETA (2 DEG/IN)
44.8
45.0
45.2
45.4
45.6
45.8
46.0
46.2
46.4
46.6
46.8
47.0
47.2
47.4
TIME – SEC.

Fig 392