

AD-778 586

THE INFLUENCE OF HEATING OF LOW
PRESSURE GAS IN A SHOCK TUBE ON THE
INCREASE OF THE ATTAINABLE STAGNATION
TEMPERATURE

G. L. Grodzovskii

Foreign Technology Division
Wright-Patterson Air Force Base, Ohio

10 April 1974

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE
5285 Port Royal Road, Springfield Va. 22151

Security Classification

DOCUMENT CONTROL DATA - R & D

AD 778 586

(Security classification of title, body of abstract and indexing annotation must be entered when the original report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Foreign Technology Division Air Force Systems Command U. S. Air Force		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
3. REPORT TITLE THE INFLUENCE OF HEATING OF LOW PRESSURE GAS IN A SHOCK TUBE ON THE INCREASE OF THE ATTAINABLE STAGNATION TEMPERATURE		2b. GROUP	
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Translation			
5. AUTHOR(S) (Last name, middle initial, first name) G. L. Grodzovskiy			
6. REPORT DATE 1970	7a. TOTAL NO. OF PAGES 8	7b. NO. OF PAGES 3	
8a. CONTRACT OR GRANT NO.	8b. ORIGINATOR'S REPORT NUMBER(S) FTD-HT-23-1169-74		
9. PROJECT NO. AEDC Project G101	9a. OTHER REPORT NUM(S) (Any other numbers that may be assigned this report)		
10. DISTRIBUTION STATEMENT Approved for public release; distribution unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Foreign Technology Division Wright-Patterson AFB, Ohio	
13. ABSTRACT 01			

Approved by
NATIONAL TECHNICAL
INFORMATION SERVICE
U. S. Department of Commerce
Springfield MA 01103

I

EDITED TRANSLATION

FTD-HT-23-1169-74

10 April 1974

THE INFLUENCE OF HEATING OF LOW PRESSURE GAS IN A
SHOCK TUBE ON THE INCREASE OF THE ATTAINABLE
STAGNATION TEMPERATURE

By: G. L. Grodzovskiy

English pages: 4

Source: Uchenyye Zapiski Tsagi. Tsentralnyy
Aerodidrodinamicheskiy Institut Im
N. Ye. Zhukovskogo., Vol. 1, Nr. 2,
1970, pp. 101-103

Country of Origin: USSR

Translated by: Robert Allen Potts

Requester: AEDC/DYP

Approved for public release;
distribution unlimited.

THIS TRANSLATION IS A REKDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP-AFB, OHIO.

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	А а	A, a	Р р	Р р	R, r
Б б	Б б	B, b	С с	С с	S, s
В в	В в	V, v	Т т	Т т	T, t
Г г	Г г	G, g	У у	У у	U, u
Д д	Д д	D, d	Ф ф	Ф ф	F, f
Е е	Е е	Ye, ye; E, e*	Х х	Х х	Kh, kh
Ж ж	Ж ж	Zh, zh	Ц ц	Ц ц	Ts, ts
З з	З з	Z, z	Ч ч	Ч ч	Ch, ch
И и	И и	I, i	Ш ш	Ш ш	Sh, sh
Я я	Я я	Y, y	Щ щ	Щ щ	Shch, shch
К к	К к	K, k	Ъ ъ	Ъ ъ	"
Л л	Л л	L, l	Ы ы	Ы ы	Y, y
М м	М м	M, m	Ь ь	Ь ь	'
Н н	Н н	N, n	Э э	Э э	E, e
О о	О о	O, o	Ю ю	Ю ю	Yu, yu
П п	П п	P, p	Я я	Я я	Ya, ya

* ye initially, after vowels, and after ъ, ѓ; e elsewhere.
 When written as ѣ in Russian, transliterate as yě or ě.
 The use of diacritical marks is preferred, but such marks
 may be omitted when expediency dictates.

THE INFLUENCE OF HEATING OF LOW
PRESSURE GAS IN A SHOCK TUBE ON
THE INCREASE OF THE ATTAINABLE
STAGNATION TEMPERATURE

G. S. Grodzovskiy

The problem of increase of the attainable stagnation temperature of the gas flow in a shock tube is investigated. It is shown that for this purpose the heating of low pressure gas is advisable. There is analyzed the effect of heating of low pressure gas on the increase of the attainable stagnation temperature in flow behind the shock wave for the case of a single-diaphragm cylindrical shock tube.

To the gas-dynamics of flows in shock tubes there is dedicated a large number of investigations (see, for example, [1]-[3]). The main attention in these investigations is given to the problem of attaining the maximum ratio of the shock wave velocity U to the speed of sound in stationary gas in front of the wave a_1 :

$$M_1 = \frac{U}{a_1}.$$

where

$$a_1 = \sqrt{\gamma_1 g R_1 T_1}.$$

T_1 - static temperature of low-pressure gas before the wave,

γ_1 and R_1 - adiabatic index and gas constant of this gas.

For the simplest cylindrical single-diaphragm shock tube

(Fig. 1) the maximum value of number M_1 , as is known, is attained with infinite pressure drop on the diaphragm:

$$M_{1\max} = \frac{(z_2+1)\epsilon_1}{(z_2-1)\epsilon_1} = \frac{z_2+1}{z_2-1} \sqrt{\frac{z_2 R_2 T_2}{z_1 R_1 T_1}} \quad (1)$$

where subscript 4 notes the parameters of high pressure gas.

In accordance with relationship (1) the number M_1 grows with increase of the temperature of high-pressure gas T_2 and with increase of its gas constant R_2 . Therefore much attention in [1], [3] is given to the problems of heating high-pressure gas with the use of high-temperature gases with low molecular weight. From these positions the low-pressure gas (T_1) was considered cold.

We investigated the problem of increase of the attainable stagnation temperature T_0 of gas flow in the shock tube. It is shown that for this purpose the heating of low-pressure gas is advisable. This effect was independently found earlier by N. I. Khvostov by calculation for finite pressure drops on the diaphragm. Below on the basis of analytical solution there is obtained the universal dependence of the attainable stagnation temperature of gas flow in the shock tube on the degree of heating of low-pressure gas.

Let us conduct analysis for the simplest scheme of shock tube for ideal gases (see Fig. 1). The obtained results can be spread to the cases of more complex schemes and for gases.




Fig. 1. 1 - high-pressure chamber; 2 - low-pressure chamber; 3 - diaphragm; 4 - shock wave; 5 - contact surface; 6 - centered rarefaction wave.

The stagnation temperature T_0 of gas flow in region 2 (behind the shock wave), naturally, depends on the flow velocity $u_2 = u_3 = V$ and parameters of low-pressure gas. The limiting value of gas flow velocity V is achieved with infinitely large pressure drop on the diaphragm, the value of V_{MAX} depends only on the parameters of high-pressure gas:

$$V_{\text{MAX}} = \frac{2}{\gamma_1 - 1} a_1 = \frac{2}{\gamma_1 - 1} \sqrt{\gamma_1 g R_1 T_1} \quad (2)$$

For fixed value of V we come to the problem of maximum attainable stagnation temperature T_0 in the flow behind the shock wave in gas, compressed by a piston moving at speed V (the contact surface plays the role of piston, see Fig. 1).

From equations of propagation of the shock wave it is possible to obtain the following expression for the relative flow velocity behind the shock wave:

$$\frac{V}{a_1} = \frac{V}{\sqrt{\gamma_1 g R_1 T_1}} = M_1 \left[1 - \frac{2 \left(1 + \frac{\gamma_1 - 1}{2} M_1^2 \right)}{(\gamma_1 + 1) M_1^2} \right] = \Phi(M_1) \quad (3)$$

The gradient of static temperatures T_2/T_1 on the shock wave is determined by known relationship

$$\frac{T_2}{T_1} = \frac{\left(\gamma_1 M_1^2 - \frac{\gamma_1 - 1}{2} \right) \left(\frac{\gamma_1 - 1}{2} M_1^2 + 1 \right)}{\left(\frac{\gamma_1 + 1}{2} M_1^2 \right)} = f(M_1) \quad (4)$$

Accordingly the ratio of the sought stagnation temperature T_0 in the flow behind the shock wave to the static temperature of low-pressure gas T_1 can be written in the form

$$\frac{T_0}{T_1} = f(M_1) \div \frac{\gamma_1 - 1}{2} \Phi^2(M_1) \quad (5)$$

whence follows the expression for the dimensionless value of stagnation temperature in the flow behind the shock wave

$$\bar{T}_0 = \frac{T_0}{\sqrt{\gamma_1 g R_1 T_1}} = \frac{f(M_1)}{\Phi^2(M_1)} \div \frac{\gamma_1 - 1}{2} \quad (6)$$

One should consider that according to equation (3) to each value of parameter M_1 there corresponds a certain value of relative flow velocity behind the shock wave (speed of piston) V/a_1 .




Fig. 2.

Figure 2 shows the change of the dimensionless value of stagnation temperature \bar{T}_0 depending on the relative velocity V/a_1 . It is evident that with assigned value of flow velocity V behind the shock wave (speed of piston), increase of the temperature of low-pressure gas T_1 , leads to increase of the attainable stagnation temperature T_0 . So, for example, if parameter M_1 was in the range $10 \leq M_1 \leq 20$, then with heating of low-pressure gas in the shock tube it is possible to raise the stagnation temperature T_0 in the flow behind the shock wave by more than twice.

BIBLIOGRAPHY

1. Ударные трубы. Сб. статей. Изд. иностр. яз., 1962.
2. Ступоченко Е. В., Лазар С. А., Осипов А. Н. Реакционные процессы в ударных волнах: М., «Наука», 1965.
3. Oertel H. Shock tubes. Springer-Verlag, Wien-New York, 1966.