

AD-782 065

A SURVEY AND COMPARISON OF METHODS FOR
DETERMINING CONFIDENCE BOUNDS ON
SYSTEM RELIABILITY FROM SUB-SYSTEM
DATA

Nancy R. Mann

Rockwell International Corporation

Prepared for:

Air Force Office of Scientific Research

8 September 1972

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE
5285 Port Royal Road, Springfield Va. 22151

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AFOSR - TR - 74 - 1133	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER AD-782 065
4. TITLE (and Subtitle) A SURVEY AND COMPARISON OF METHODS FOR DETERMINING CONFIDENCE BOUNDS ON SYSTEM RELIABILITY FROM SUBSYSTEM DATA		5. TYPE OF REPORT & PERIOD COVERED Interim
7. AUTHOR(s) Nancy R. Mann		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Rockwell International Rocketdyne Division Canoga Park, California 91304		8. CONTRACT OR GRANT NUMBER(s) F44620-71-C-0029
11. CONTROLLING OFFICE NAME AND ADDRESS Air Force Office of Scientific Research/NM 1400 Wilson Blvd Arlington, Virginia 22209		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 61102F 9769-05
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE 4-8 SEP 1972
		13. NUMBER OF PAGES 25
		15. SECURITY CLASS (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) A. Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES PROCEEDINGS - 1972 NATO Conference Proceedings on Reliability Testing and Reliability Evaluation, The Hague, Netherlands, 4-8 September 1972, p1B1-1B21		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Reproduced by NATIONAL TECHNICAL INFORMATION SERVICE U.S. Department of Commerce Springfield, VA 22151		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) In this paper, methods of obtaining lower confidence bounds on the reliability of non-maintained systems are surveyed, and numerical comparisons are given. It is assumed that failure data have been collected from life tests performed on prototypes of the various subsystems which make up the system, but that the system has not been tested as a whole, for some particular reason. The reason may be, for example, expense or simple		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

#20/Abstract

that it is virtually impossible to test the entire system without destroying it. Methods applicable to series and/or parallel and more logically complex systems are discussed.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

AFOSR - TR - 74 - 1133

PROCEEDINGS

of the

NATO CONFERENCE

on

RELIABILITY TESTING AND RELIABILITY EVALUATION

The Hague, Netherlands
4 - 8 September 1972

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)
NOTICE OF TRANSMITTAL TO DDC

This technical report has been reviewed and is
approved for public release (AWR 190-12 (7b)).
Distribution is unlimited.


D. W. TAYLOR
Technical Information Officer

Ernest M. Scheuer, Editor

Published by

Bureau of Business Services and Research
California State University, Northridge
Northridge, California 91324, U.S.A.

iii



A SURVEY AND COMPARISON OF METHODS FOR DETERMINING
CONFIDENCE BOUNDS ON SYSTEM RELIABILITY FROM SUBSYSTEM DATA*

Nancy R. Mann
Rocketdyne, North American Rockwell
Canoga Park, California 91304, U.S.A.

In this paper, methods of obtaining lower confidence bounds on the reliability of non-maintained systems are surveyed, and numerical comparisons are given. It is assumed that failure data have been collected from life tests performed on prototypes of the various subsystems which make up the system, but that the system has not been tested as a whole, for some particular reason. The reason may be, for example, expense or simply that it is virtually impossible to test the entire system without destroying it. Methods applicable to series and/or parallel and more logically complex systems are discussed.

OPTIMUM CONFIDENCE BOUNDS FOR SPECIFIC SYSTEM MODELS

There are two types of models for which one can theoretically calculate, from subsystem failure data, confidence bounds on system reliability which are known to be optimum in some sense. For a series system made up of k independent subsystems each having exponentially distributed failure time, T , there exists a lower confidence bound which is most accurate (has the highest probability of being close to the true system reliability) for all values of system reliability among exact bounds which are unbiased. (A family of lower confidence bounds $\underline{\theta}(X)$ on θ at confidence level $1-\alpha$ is unbiased if $\text{Prob}[\underline{\theta}(X) \leq \theta'] \leq 1-\alpha$ for all $\theta' < \theta$ and for all values of nuisance parameters. The restriction of unbiasedness is necessary here because of the nuisance parameters $\lambda_1, \dots, \lambda_k$, the failure rates for the k independent subsystems.) For this model, series system reliability $R(t_m)$ at time $t_m > 0$ is equal to $\prod_{j=1}^k \exp(-t_m \lambda_j) = \exp(-t_m \sum_{j=1}^k \lambda_j)$, $\lambda_j > 0$, $j=1, \dots, k$, so that one can also think of obtaining an upper confidence bound on system failure rate, $\phi = \sum_{j=1}^k \lambda_j$.

*The writing of this paper was sponsored by the Air Force Office of Scientific Research, AFSC, USAF under Contract F44620-71-C-0029. Work of the author described in the paper was supported in part by this contract and in part by the North American Rockwell Interdivisional Technology Program, Mathematics and Statistics Technical Panel.

The optimum lower confidence bound on series-system reliability, derived for two subsystems with exponential failure data by Lentner and Buehler (1963) and generalized to $k \geq 2$ subsystems by El Mawaziny (1965), depends upon the assumption that for the j th subsystem, n_j prototypes have been tested until r_j , with $1 \leq r_j \leq n_j$, failures occur, $j=1, \dots, k$. One observes for the j th subsystem, $t_{i,j}$, $i=1, \dots, r_j$, and computes $z_j = \sum_{i=1}^{r_j} t_{i,j} + (n_j - r_j)t_{r,j}$, $j=1, \dots, k$. Calculation of a confidence bound by El Mawaziny's method must be performed iteratively on a computer, and if the product of the number of subsystems and the total number of failures is large, problems of loss of precision result. See Mann (1970).

The other system model for which a method of obtaining optimum confidence bounds on system reliability has been derived is one in which binomially distributed attribute or pass-fail data are collected. No assumptions are made concerning the form of failure-time distributions; the assumptions are that the system is serial or parallel-redundant, the subsystems and the subsystem prototype tests are independent, the failure distribution for any specified subsystem is the same for each prototype of that subsystem tested and the duration of each test is the intended operating time applying to the particular subsystem in the system. For the binomially distributed data obtained for this model, Buehler (1957) defines a small-sample method of obtaining confidence bounds on system reliability. These bounds, however, like binomial confidence bounds for a single component, are conservative in general rather than exact because of the discreteness of the numbers of failures. In order to obtain a confidence bound which is exact in general and uniformly most accurate unbiased, a random number uniformly distributed on $(0,1)$ must be generated and used in calculating the bound. (Confidence bounds which depend upon a uniform random variate in addition to the failure data will be referred to as randomized, while the conservative bounds which do not depend upon a generated random number will be called nonrandomized.)

Lipow and Riley (1959) have used Buehler's definition to compute and tabulate nonrandomized lower confidence bounds on series system reliability R_s for systems containing one, two, or three subsystems and attribute subsystem data. In all of their tabulations, the number n of items tested is the same for each component because of the problem of ordering the failure combinations in calculating each confidence bound.

The value of n ranges from 5 to several hundred. The number of failures is not required to be the same for each component and ranges from zero to about $n/2$. The tabulated lower confidence bounds on series system reliability are known to be optimum (correspond to shortest intervals with plus one as an upper bound) among non-randomized confidence bounds based on the subsystem attribute data for two independent subsystems when the sum of the numbers of failures is less than $2\sqrt{n}$. For three subsystems, the problem of ordering the failure combinations prevents the authors from claiming optimality for the bounds based on their particular ordering of the failure combinations. Steck (1957) gives in graphical form the same sort of conservative nonrandomized confidence bounds for parallel-system reliability R_p , for systems composed of two independent subsystems and at most one observed failure.

APPROXIMATE AND NON-OPTIMAL EXACT CONFIDENCE BOUNDS FOR THE EXPONENTIAL MODEL

For each of these system models, there are a number of methods that have been derived for approximating the optimum bounds. In some cases, the approximations were derived before the optimum bounds. In other cases, they were derived because of the problem involved with calculating the optimum bounds.

For the exponential series-system model, the method of Kraemer (1963) yields bounds which are exact and depend upon only the smallest sample mean subsystem failure time. This method gives confidence bounds which are very inaccurate (i.e., they exhibit a high probability of being far from the true system reliability) unless one failure only occurs for either every subsystem or every subsystem except one. In these two special cases, Kraemer's method gives the optimum confidence bounds under certain conditions.

The methods of Sarkar (1971) and Lieberman and Ross (1971), developed for the exponential series-system model, depend upon combinations of failure times selected from the various subsystems rather than the sufficient statistics, Z_1, \dots, Z_k , observed as z_1, \dots, z_k . As Lieberman and Ross (1971) point out, in using their method one can obtain different

bounds by ordering the subsystem tests differently, and thus combining the subsystem test data differently. The confidence intervals of Lieberman and Ross are exact and stochastically shorter in general than those of both Sarkar and Kraemer.

Grubbs (1969) uses what will be called here the fiducial approach to approximate the distribution of series-system failure rate, given the exponential subsystem failure data. That is, he assumes that since the distribution of $2z_j$ is $\lambda_j^{-1} \chi^2(2r_j)$, then λ_j is distributed as $\chi^2(2r_j)/2z_j$, $j=1, \dots, k$. Grubbs employs an approach which uses the mean $\sum_{j=1}^k r_j/z_j$ and variance $\sum_{j=1}^k r_j/z_j^2$ of the fiducial distribution of system failure rate $\phi \sum_{j=1}^k \lambda_j$ to fit a noncentral Chi-square distribution.

Burnett and Wales (1961) and Levy and Moore (1967) suggest for this series-system model, and also for other models which are more logically complex than a series system, Monte Carlo simulation of the fiducial distribution of system reliability, given the subsystem failure data. Such an approach yields, for the series-system model essentially the same result as the method of Grubbs; see Mann (1970) and Grubbs (1971). The fiducial approach is equivalent to obtaining Bayesian bounds on system reliability at time t_m with the prior density for the j th subsystem failure rate $\lambda_j > 0$ equal to λ_j^{-1} , $j=1, \dots, k$.

Although lower confidence bounds on system reliability obtained by the fiducial method are optimum for one subsystem and approach the optimum confidence bounds as the numbers of failures increase for all subsystems, they are conservative in general. That is, for this series-system model, the fiducial lower bound on system reliability is always less than the corresponding optimum exact classical lower confidence bound, and sometimes by a considerable amount. This can be seen in Table 1.

The confidence bounds on series-system reliability derived by El Mawaziny and Buehler (1967) for the exponential model depend upon the asymptotic normality of system failure rate, given the subsystem data as it is assumed given in the derivation of the optimum bounds of El Mawaziny. That is, one assumes z_1 , and $u_2 = z_1 - z_2, \dots, u_k = z_1 - z_k$, are given, where the subscript 1 is arbitrarily assigned. As shown in Table 1, a lower

confidence bound obtained by this method is always greater than the corresponding optimum bound when the number of failures is small for any subsystem. One of the most serious problems inherent in this method of obtaining lower confidence bounds on system reliability is that subsystems for which a single failure occurs are ignored. The consequences of this fact are exhibited in Table 1.

The methods of Rosenblatt (1963) and Madansky (1965) yield asymptotic lower confidence bounds on series-system reliability which, like the method of El Mawaziny and Buehler, tend to be very much too large when only a single failure occurs for any subsystem. These methods are discussed in more detail in the section dealing with confidence bounds based on binomial subsystem data.

The Approximately Optimum confidence bounds of Mann and Grubbs (1972) are based on a combination of the approach of Grubbs (1971) and that of El Mawaziny and Buehler (1967) for the exponential series-system model. One conditions on z_1 , and u_2, \dots, u_k , as in deriving the optimum confidence bounds on R_s and determines expressions for the approximate conditional mean and variance of system failure rate ϕ . The conditional variate Z_1 , given \underline{u} , belongs to the Koopman-Darmois exponential family with parameter ϕ and nuisance parameters $\lambda_1, \dots, \lambda_k$, so that by the discussion given by Lehmann (1959, sec. 4.5), a uniformly most accurate unbiased upper confidence bound for ϕ can be obtained from z_1 and \underline{u} .

Once the approximate conditional mean and variance of system failure rate are calculated, one can approximate very accurately the noncentral Chi-square conditional distribution of system failure rate by another central Chi-square distribution [see Patnaik (1949)] and thus obtain approximately optimum lower confidence bounds on series-system reliability. A Wilson-Hilferty (1951) approximation of Chi-square by a Gaussian variate can be used to facilitate the calculations when noninteger degrees of freedom are encountered. The expressions for the conditional mean m and variance v of system failure rate ϕ derived by Mann and Grubbs have been simplified by Mann (1972) and are

$$m = \sum_{j=1}^k (r_j - 1) / z_j + z(1)^{-1} \quad (1)$$

TABLE 1. LOWER 50%, 75%, AND 90% CONFIDENCE BOUNDS, ON SERIES-SYSTEM RELIABILITY:
EXPONENTIAL SUBSYSTEM FAILURE DATA, WITH MISSION TIME $t_m = 1$

r_j = Number of Failures	Observed Values of $z_j = r_j \sqrt{j}$					Confidence Level	E1 Mawaziny-Optimum Lower Bound	Approx. χ^2 (fiducial)	Approx. χ^2 Based on (1), (2) & (3)	E1 Mawaziny-Buehler Normal Approx.
	z_1	z_2	z_3	z_4	z_5					
	4, 2, 2, 5, 5	9.919	15.996	26.897	26.511					
4, 2, 2, 5, 5	28.412	15.992	9.990	98.228	44.667	0.50	0.670	0.657	0.710	
1, 2, 2, 5, 5	0.565	4.609	21.045	25.528	11.419	0.90	0.010	0.009	0.426	
1, 2, 2, 5, 5	9.976	2.581	20.275	10.044	51.118	0.75	0.242	0.235	0.565	
1, 2, 2, 5, 5	0.565	4.609	21.045	25.528	11.419	0.50	0.179	0.173	0.595	
2, 5, 4	25.059	52.504	57.188	--	--	0.50	0.812	0.804	0.851	
2, 5, 4	75.758	16.084	57.505	--	--	0.90	0.671	0.669	0.755	
2, 5, 4	75.758	16.084	57.505	--	--	0.50	0.795	0.766	0.827	
2, 5, 4	19.755	51.249	21.521	--	--	0.75	0.692	0.688	0.721	
2, 2, 2	16.966	42.258	15.518	--	--	0.50	0.828	0.824	0.865	
2, 2, 2	16.966	42.258	15.518	--	--	0.75	0.764	0.760	0.817	
4, 5, 2	42.755	45.791	51.890	--	--	0.90	0.772	0.766	0.801	
4, 5, 2	84.794	56.989	4.165	--	--	0.90	0.559	0.558	0.526	
4, 5, 2	28.274	44.690	9.480	--	--	0.90	0.566	0.559	0.658	
4, 5, 2	171.581	29.062	11.295	--	--	0.90	0.649	0.642	0.757	
4, 5, 2	78.668	54.968	57.296	--	--	0.90	0.849	0.846	0.868	
4, 5, 2	25.527	56.469	25.476	--	--	0.75	0.750	0.746	0.777	

and

$$v = \sum_{j=1}^k (r_j - 1) / z_j^2 + z_{(1)}^{-2} \quad (2)$$

where $z_{(1)}$ is the smallest of the z 's. To approximate the optimum lower bound on $R_s(t_m)$ at confidence level $1-\alpha$ using the Wilson-Hilferty transformation, one calculates

$$\underline{R}_s(t_m) = \exp \left[-t_m \left\{ 1 - v / (9m^2) + Z_{1-\alpha} v^{1/2} / (5m) \right\}^3 \right], \quad (3)$$

where Z_v is the $100v$ th percentile of a standard normal distribution. Confidence bounds based on formulas (1), (2) and (3) are compared in Table 1 with the optimum classical exact confidence bounds of El Mawaziny and with the fiducial bounds and the asymptotic approximation of El Mawaziny and Buehler. The data used for the comparisons were generated in conjunction with the study described by Mann (1970). The Approximately Optimum lower confidence bounds $\underline{R}_s(t_m)$ on $R_s(t_m)$ agree to within about a unit in the second decimal place with optimum lower confidence bounds of El Mawaziny (1965).

APPROXIMATE AND NON-OPTIMAL EXACT CONFIDENCE BOUNDS FOR THE BINOMIAL MODEL

For series or parallel-redundant models and the case in which only pass-fail binomially distributed data are collected for each subsystem, many methods involving large- or small-sample approximations or Bayesian techniques have been derived for obtaining nonrandomized confidence bounds on the probability of successful operation of a system. Among the large-sample methods is one derived by Madansky (1965). Extension of Madansky's method to logically complex systems has been accomplished by Myhre and Saunders (1968b). In using this method, one parameterizes so as to determine iteratively parameter values which make the negative of the logarithm of the likelihood ratio equal to one half of a specified percentile of the Chi-square distribution with one degree of freedom; see Wilks (1938). In determining the likelihood ratio by this method, one must maximize the joint binomial density function subject to a constraint specified by the equation relating system reliability to the subsystem reliabilities.

The principal disadvantage associated with use of the likelihood-ratio procedure is that any component exhibiting zero failures in a life-test situation is ignored in the determination of a series-system reliability confidence bound and tends to bias parallel system confidence bounds on the high side. Thus, the procedure yields lower confidence bounds that are too high whenever zero failures are observed during the life test, no matter how large the sample size for all components. This method is, in fact, not appropriate for highly reliable systems.

Another method suggested for obtaining confidence bounds on system reliability is one based on the asymptotic normality of the unbiased simulation estimator (often equivalent to the maximum-likelihood estimator) of system reliability. Such a procedure and its theoretical rationale are discussed at length by Rosenblatt (1963). Easterling (1972) investigated a variation of this procedure in which psuedo numbers of system tests and successes are determined from the estimate of the variance of the maximum-likelihood estimator of system reliability. These numbers are then substituted into the incomplete Beta function, and confidence bounds obtained as in determining usual optimum nonrandomized confidence bounds for a single component and binomial sampling. Easterling found his approximation to be better for several series, parallel and series-parallel systems which he investigated than that based on the asymptotic normality of maximum-likelihood estimators and comparable to that based on the asymptotic Chi-square distribution of the logarithm of the likelihood-ratio function (which is more difficult to implement).

Woods and Borsting (1968) have approximated the distribution of $-2 \ln \hat{R}_s$, with \hat{R}_s the maximum-likelihood estimator of series-system reliability, by a continuity-corrected Gamma distribution. The approximation appears to give exact bounds when sample sizes are large, but does not appear to perform well for sample sizes as small as 10.

Murchland and Weber (1972) describe a method similar to that detailed by Rosenblatt for obtaining confidence bounds on the reliability of a complex system. These authors, however, suggest the use of Chebyshev inequalities rather than settling on any particular assumptions concerning

the distribution (asymptotic or otherwise) of the unbiased simulation estimator of system reliability, and their bounds involve the expression for the exact rather than the asymptotic variance of the estimator of R_s . Their procedure presents no particular computational difficulties as long as the system remains logically simple. Calculation of their variance estimate for the reliability estimator becomes very complicated, however, as the system increases in complexity.

A more serious difficulty inherent in this method and all methods dependent upon the maximum-likelihood or simulation estimator of system reliability is similar to that given for the likelihood-ratio method. It is the fact that any component exhibiting no failures during the life tests is ignored in the determination of bounds for strictly serial systems and yields a lower confidence bound on parallel-system reliability that is always unity. The maximum-likelihood and simulation estimators are also inappropriate for providing the basis for confidence bounds on the reliability of highly reliable systems.

Table 2 gives for series systems the optimum nonrandomized confidence bounds of Lipow and Riley (1959), likelihood-ratio (LR) and maximum-likelihood (ML) approximations calculated by Myhre and Saunders (1968a) and Easterling's modified maximum likelihood (MMLI) approximations, all for data sets in which at least one failure occurs for each component. Results based on the Woods and Borsting approximation are shown in Table 3.

Small-sample approximate confidence bounds on R_s for an independent series system and binomial data have been derived by Garner and Vail (1961), Connor and Wells (1962), Abraham (1962), and Lindstrom and Madden [see Lloyd and Lipow (1962)]. The first two of these approaches use various methods of combining confidence bounds on subsystem reliability to obtain the desired bounds on system reliability. The other two use binomial or Poisson approximations for certain statistics. Some of these methods are sensitive to inequality of sample sizes for subsystems. Lower confidence bounds obtained by most of these approximate methods have been compared by the use of three sets of data by Schick and Prior (1966) with optimum nonrandomized bounds obtained using results of Lipow

and Riley (1959). The data apply to series systems composed of two subsystems, and in each of the three cases the sample sizes are equal. Only the Lindstrom and Madden method compares favorably with the Lipow and Riley (1959) bounds. The Lindstrom and Madden method, however, is one which is sensitive to unequal sample sizes for subsystems.

One can also obtain Bayesian bounds on system reliability by choosing, for a system composed of k components, a prior density function for the j th component reliability, R_j , $j=1, \dots, k$, and then simulating (or obtaining through a Mellin-transform technique) the posterior distribution of system reliability, given the component failure data. Zimmer, Prairie and Breipohl (1965) and Springer and Thompson (1966) have suggested the use of prior densities on component reliabilities that are uniform on $(0,1)$. Mastran (1968) and Parker (1972) prefer to assign prior densities in such a way that the prior density for system reliability is uniform.

Results of Raiffa and Schlaifer (1961) suggest that any prior density approximating the prior yielding an optimum confidence bound should be improper (i.e., be such that its integral cannot be made equal to unity by affixing a constant factor) as is the prior density function $p(R) = R^{-1}$ (or, equivalently, $p(-\ln R)$ uniform on the positive half real line) associated with the optimum nonrandomized binomial confidence bound for a single component. Results of Fertig (1972) and Mann (1970) relating to series systems with exponential subsystem data corroborate this conjecture. Their results show further that for the exponential model, the prior densities on component reliabilities (which we shall refer to henceforth as posterior prior densities) associated with the optimum classical lower confidence bound on series-system reliability contain component failure data. The Approximately Optimum lower confidence bounds on R_s based on the conditional mean m and variance v of system failure rate, given by formulas (1) and (2), implicitly depend upon an assumption of a posterior prior density for λ_j of $\lambda_j^{-2+z_j/(kz(1))}$, $j=1, \dots, k$, where $z(1)$ is the smallest of the z 's. Finally, results of Mann (1971) indicate that both randomized and nonrandomized optimum confidence bounds for the reliability of series and parallel systems with

binomial subsystem data are associated with prior densities containing failure data.

Use of component-reliability posterior prior density functions which are not approximately optimum can yield Monte Carlo lower confidence bounds having a high probability of being inordinately far from the true system reliability. For example, if one uses as a prior for R_j , $p(R_j) = R_j^{-k}$, $j=1, \dots, k$, with $k > 1$, the optimum (nonrandomized) prior density for $k=1$, then the lower confidence bound obtained (referred to henceforth as fiducial bounds) for system reliability R are uniformly lower than the optimum nonrandomized lower confidence bounds. For a parallel system the difference between the two types of confidence bounds is not large unless sample sizes n_j , $j=1, \dots, k$ are very small. However, one obtains for a series system with $n_1=10$, $n_2=9$, $n_3=9$, $x_1=2$, $x_2=1$ and $x_3=0$, where the x 's are numbers of failures, an optimum nonrandomized lower confidence bound of 0.504 and a fiducial bound of 0.548. These results are shown by Mann (1971) and other comparisons with optimum nonrandomized confidence bounds are shown in Tables 3 and 4.

Using a bound based on uniform prior densities for the component reliabilities is equivalent to using the fiducial bound with n_j , $j=1, \dots, k$, each increased by one. Thus, for the data set above, the bound based on uniform priors for component reliabilities is 0.587. For more discussion concerning the use of uniform prior densities, see Mann and Fertig (1972).

Harris (1971) has derived a procedure for obtaining nonrandomized and optimum randomized confidence bounds on products and quotients of Poisson parameters. Since for large sample sizes and small probabilities the Poisson distribution can be used to approximate binomial distributions, Harris has suggested using his randomized results to approximate parallel system reliability confidence bounds under appropriate conditions. The appropriate conditions are, of course, large sample sizes and high reliabilities for all components.

Harris compares numerically, for a selection of Poisson failure data applying to parallel systems composed of two subsystems, his Poisson lower bounds and the Poisson approximation of Buehler (1957) to

the optimum nonrandomized lower confidence bounds on R_p . Harris' randomized lower confidence bounds on R_p are optimum (uniformly most accurate unbiased) for Poisson data, but his nonrandomized lower confidence bounds are extremely conservative.

The method of Harris is rather difficult to implement, involving the calculation of the percentiles of the modified Bessel function; and, unfortunately, there is no procedure by which Harris' bounds can be made to apply to at least moderately reliable series systems with binomial subsystem data.

Mann (1971) has used the approach used by Mann and Grubbs (1972) for exponential-subsystem failure data to approximate both optimum randomized and optimum nonrandomized lower confidence bounds on series- and parallel-system reliability for systems with binomial subsystem data. For sample sizes large and the numbers of failures small, Mann's Approximately Optimum (AO) randomized lower confidence bounds on parallel-system reliability R_p agree very well with the optimum randomized Poisson bounds of Harris (see Table 5). To obtain the Approximately Optimum randomized lower confidence bounds on R_p , one first calculates

$$m_p(\delta) = \sum_{j=1}^k \sum_{i=x_{j+1}}^{n_j} (1/i) + .5/x(1)^{-.5} \sum_{j=1}^k \delta/x_j \quad (4)$$

and

$$v_p(\delta) = \sum_{j=1}^k \sum_{i=x_{j+1}}^{n_j} (1/i)^2 + .5/x(1)^{-.5} \sum_{j=1}^k \delta/x_j \quad (5)$$

with $x(1)$ equal to the smallest of the x 's and δ equal to both +1 and -1. Then $m'_p = u m_p(1) + (1-u) m_p(-1)$ and $v'_p = u v_p(1) + (1-u) v_p(-1)$ where u is a realization of a random variate U uniform on $(0,1)$. Use of m'_p and v'_p with the Wilson-Hilferty (1951) transformation for the approximate noncentral Chi-square distribution of $-\ln(1-R_p)$ gives

$$\text{Prob} \left\{ 1-R_p \leq \exp \left[-m'_p \left\{ 1 - v'_p / (\sqrt{3} m'_p)^2 + Z_{\alpha} \sqrt{v'_p} / (\sqrt{3} m'_p) \right\} \right] \right\} \approx 1-\alpha, \quad (6)$$

with Z_{α} the 100α th percentile of a standard normal distribution.

One obtains a similar approximation to optimum exact lower confidence bounds on R_s by calculating $m_s(\delta)$ and $v_s(\delta)$ [$m_p(\delta)$ and $v_p(\delta)$], respectively, with x_j replaced by $n_j - x_j$ and $x(1)$ replaced by $n(1) - x(1)$, the smallest value of $n_j - x_j$, $j=1, \dots, k$. One then substitutes in (6), R_s for $1-R_p$, \geq for \leq , $Z_{1-\alpha}$ for Z_α , $m'_s = u m_s(-1) + (1-u)m_s(1)$ for m'_p and $v'_s = u v_s(-1) + (1-u)v_s(1)$ for v'_p to obtain the AO randomized approximately exact lower confidence bound on R_s . The expressions (4) and (5) given for $m_p(\delta)$ and $v_p(\delta)$ are approximations for differences of polygamma functions, derivatives of the logarithm of the Gamma function; see Mann and Fertig (1972).

Expressions for m_p and m_s and v_p and v_s from which Approximately Optimum nonrandomized lower confidence bounds on system reliability can be obtained are similar to, though somewhat more complicated than, those given by formulas (4) and (5), respectively. Table 2 gives, for a series system with failures occurring in all subsystems, comparisons of these confidence bounds with the optimum nonrandomized confidence bounds calculated by Lipow and Riley (1959), those based on the likelihood-ratio (LR) and maximum-likelihood (ML) approximations, calculated by Myhre and Saunders (1968a), and that based on the modified maximum-likelihood (MMLI) approximation of Easterling (1971). Table 3 gives comparisons of the optimum nonrandomized lower confidence bounds, the AO nonrandomized confidence bounds, fiducial bounds and those based on the Gamma approximation of Woods and Borsting (1968) to the distribution of $-2n\hat{R}_s$, with \hat{R}_s the maximum-likelihood estimator of series-system reliability. Table 4 applies to parallel systems and compares optimum nonrandomized and AO nonrandomized lower confidence bounds with fiducial bounds on R_p .

Table 5 applies to parallel systems, large sample sizes and small numbers of failures, and exhibits the optimum nonrandomized Poisson lower confidence bounds on R_p of Buehler (1957), the optimum "randomized" Poisson bounds, calculated by Harris (1971) from his formulas by using the expected value, .5, of a random variate uniform on (0,1), and the nonrandomized version of Harris' lower confidence bounds on R_p , the bottom of the range of possible lower confidence bounds to be obtained by randomizing with his method. Also shown in Table 5 are the AO lower

TABLE 2. NONRANDOMIZED LOWER CONFIDENCE BOUNDS ON RELIABILITY FOR A SERIES SYSTEM OF TWO OR THREE COMPONENTS

k	No. of Failures		Confidence Level														
			.90					.95									
			x ₁	x ₂	ML	LR	Opti- mum	A0	NMLI	ML	LR	Opti- mum	A0	NMLI			
k = 2																	
n = 10	1	1	.655	.629	.607	.615	.585	.611	.571	.548	.560	.530					
	1	2	.545	.529	.497	.512	.489	.495	.473	.443	.459	.436					
	2	2	.456	.451	.445	.443	.441	.405	.397	.392	.392	.391					
	1	4	.317	.350	.344	.344	.318	.292	.301	.298	.298	.271					
	2	3	.373	.375	.364	.371	.362	.320	.326	.304	.325	.315					
	1	2	.756	.739	.716	.720	.709	.728	.700	.677	.682	.671					
n = 20	2	2	.701	.687	.683	.683	.669	.670	.647	.643	.645	.631					
	1	3	.697	.683	.660	.665	.655	.665	.643	.620	.626	.616					
	2	3	.647	.636	.622	.624	.619	.614	.597	.582	.586	.580					
	3	3	.599	.591	.585	.582	.570	.565	.551	.544	.543	.532					
	1	x ₂															
	1	1	.760	.743	.747	.740	.721	.732	.705	.709	.703	.684					
n = 20	1	2	.704	.690	.693	.683	.669	.673	.651	.644	.645	.631					
	1	2	.654	.643	.639	.637	.619	.621	.604	.598	.599	.580					
	1	3	.605	.596	.595	.591	.587	.571	.557	.544	.553	.549					
	1	3	.723	.714	.705	.707	.669	.698	.683	.674	.677	.638					
	1	1	.835	.822	.825	.818	.803	.816	.794	.796	.791	.775					
	2	2	.725	.715	.712	.711	.703	.700	.685	.681	.681	.672					
n = 50	1	2	.805	.798	.789	.791	.788	.788	.776	.767	.770	.766					
	1	2	.874	.865	.861	.859	.852	.860	.845	.841	.840	.833					
	1	2	.936	.931	.929	.927	.923	.929	.920	.918	.916	.913					
	2	3	.866	.861	.858	.858	.856	.855	.848	.844	.845	.842					
	1	x ₂															
	1	1	.760	.743	.747	.740	.721	.732	.705	.709	.703	.684					
n = 100	1	2	.704	.690	.693	.683	.669	.673	.651	.644	.645	.631					
	1	2	.654	.643	.639	.637	.619	.621	.604	.598	.599	.580					
	1	3	.605	.596	.595	.591	.587	.571	.557	.544	.553	.549					
	1	3	.723	.714	.705	.707	.669	.698	.683	.674	.677	.638					
	1	1	.835	.822	.825	.818	.803	.816	.794	.796	.791	.775					
	2	2	.725	.715	.712	.711	.703	.700	.685	.681	.681	.672					

TABLE 3. NONRANDOMIZED NINETY PERCENT LOWER CONFIDENCE BOUNDS
ON SERIES SYSTEM RELIABILITY FOR UNEQUAL SAMPLE SIZES

k = 1	No. of Tests		No. of Failures			Opti- mum	A0	Fidu- cial	Gamma	
	n ₁		x ₁							
	7		1			.547	.548	.548	.257	
	7		0			.720	.722	.722	1.00	
	10		4			.354	.354	.354	.583	
	10		1			.663	.664	.664	.586	
k = 2	n ₁	n ₂	x ₁	x ₂		Opti- mum	A0	Fidu- cial	Gamma	
	15	10	0	0						.794
	5	10	0	1		.587	.592	.475	.586	
k = 3	n ₁	n ₂	n ₃	x ₁	x ₂	x ₃	Opti- mum	A0	Fidu- cial	Gamma
	10	5	4	1	1	0				
	10	10	9	0	1	1	.588	.582	.417	.450
	10	9	9	2	1	0	.504	.505	.548	.180

TABLE 4. NONRANDOMIZED NINETY PERCENT LOWER CONFIDENCE BOUNDS
ON PARALLEL SYSTEM RELIABILITY

k = 2	No. of Tests		No. of Failures			Opti- mum	A0	Fidu- cial	
	n ₁	n ₂	x ₁	x ₂					
	10	10	0	1		.968	.968	.956	
	2	2	0	1		.54	.537	.492	
	10	10	0	0		.988	.981	.976	
	50	50	0	1		.9985	.9985	.9978	
	20	20	0	1		.991	.990	.987	
k = 3	n ₁	n ₂	n ₃	x ₁	x ₂	x ₃	Opti- mum	A0	Fidu- cial
	5	5	5	0	0	0			
	10	10	10	0	0	0	.999	.998	.998

TABLE 5. NINETY PERCENT LOWER CONFIDENCE BOUNDS
ON PARALLEL SYSTEM RELIABILITY, LARGE SAMPLE SIZES

Number of Failures		Buehler's Poisson Approximation	Harris' Nonrandomized Confidence Bound (Poisson Approx.)	Harris' "Randomized" Confidence Bound	AO Nonrandomized Conf. Bound ($m_1=m_2=m_3=100$)	AO "Randomized" Conf. Bound ($m_1=m_2=m_3=100$)
x_1	x_2					
5	5	1-41.2 / ($n_1 n_2$)	1-48.6 / ($n_1 n_2$)	1-41.6 / ($n_1 n_2$)	1-42.0 / n^2	1-41.7 / n^2
1	4	1-18.8 / ($n_1 n_2$)	1-25.5 / ($n_1 n_2$)	1-18.4 / ($n_1 n_2$)	1-20.0 / n^2	1-19.4 / n^2
2	2	1-16.8 / ($n_1 n_2$)	1-21.1 / ($n_1 n_2$)	1-17.0 / ($n_1 n_2$)	1-16.9 / n^2	1-16.4 / n^2
10	0	1-25.4 / ($n_1 n_2$)	1-35.9 / ($n_1 n_2$)	1-24.5 / ($n_1 n_2$)	1-24.2 / n^2	1-22.7 / n^2
x_1	x_2	x_3				
1	2	1	1-40.0 / ($n_1 n_2 n_3$)	1-27.0 / ($n_1 n_2 n_3$)	1-20.7 / n^3	1-27.2 / n^3
2	3	5	1-186 / ($n_1 n_2 n_3$)	1-145 / ($n_1 n_2 n_3$)	1-135 / n^3	1-146 / n^3

confidence bounds of Mann (1971) corresponding to the optimum nonrandomized lower confidence bounds on R_p and the optimum "randomized" lower confidence bounds (calculated by setting the uniform random variate U equal to .5 in evaluating m'_p and v'_p).

METHODS APPLYING TO COMPLEX SYSTEMS

For binomial subsystem data, several of the methods described above for application in particular to series and parallel systems, have been used to obtain confidence bounds on the reliability of logically complex coherent systems. Coherent systems are defined here as defined by Birnbaum, Esary, and Saunders (1961); i.e., systems which if they perform when a given set of components perform also perform when a set of components containing the given set perform and which fail when all their components fail and perform when all components perform.

Use has been made of the approximate methods of Rosenblatt (1963), Madansky (1965), as generalized by Myhre and Saunders (1968b), Easterling (1971) and Murchland and Weber (1972), discussed earlier. The modified maximum likelihood (MMLI) method of Easterling probably gives as good an approximation to the optimum nonrandomized confidence bounds as any of these methods (see Table 2), and is not difficult to implement. As noted earlier, however, none of the methods based on the likelihood ratio or the simulation or maximum-likelihood estimator \hat{R}_s of system reliability should be used if the system is highly reliable so that zero failures are exhibited for any subsystem. The results in Table 3 applying to the Gamma approximation to the distribution of $-\ln \hat{R}_s$ of Woods and Borsting (1968) demonstrate how zero failures are ignored in the application of these methods for obtaining lower confidence bounds on series-system reliability, and Harris (1971) demonstrates similar results for the maximum-likelihood and likelihood-ratio methods applied to parallel systems.

Monte Carlo simulation procedures have been used widely, though incorrectly, for obtaining confidence bounds on the reliability of a logically complex coherent system. Because of the fact that subsystem failure data appear in the posterior prior density functions associated

with optimum confidence bounds for series and parallel systems, a straightforward Monte Carlo approach for logically complex systems seems infeasible if meaningful confidence bounds are to be obtained.

A new approach is given by Mann and Fertig (1972). It is assumed that for a logically complex coherent system, all of the most basic subsystems which are made up of effective components only (earlier called subsystems, but tested as a single unit) have been identified. It is assumed further that for each of these basic subsystems, either m_s and v_s or m_p and v_p applying to AO nonrandomized confidence bounds have been determined, accordingly as each subsystem is series or parallel. (One can also randomize using this procedure and thus calculate various values of m'_s , v'_s , m'_p and v'_p .)

The next step is to consider each subsystem for which means and variances have been calculated as a single effective component with an effective number n^* of prototypes subjected to life test and exhibiting an effective number x^* of failures, with n^* and x^* not necessarily integers. Each x^* and n^* must be determined iteratively. Then, having found values of n^* and x^* for each effective component applying to all most basic subsystems, these new data are combined with each other and with the failure data from other single components to determine effective component sample sizes and failure numbers for the next most basic set of subsystems in the total system. This procedure is continued until the effective failure number and sample size are determined for the entire system. The details involved in the process are given by Mann and Fertig. (1972).

This method is rather difficult to implement if the system is extremely complex, but provides an approach for obtaining confidence bounds that are approximately optimum for any coherent system, no matter how reliable.

REFERENCES

- Abraham, John K. (1962), A Confidence interval for the reliability of multicomponent systems Proceedings Seventh Conference on the Design of Experiments in Army Research, Development and Testing, ARODR 62-2, 485-518.
- Birnbaum, Z. W., J. D. Esary and S. C. Saunders (1961), Multi-component systems and structures and their reliability, Technometrics 3, 55-77.
- Buehler, R. J. (1957), Confidence intervals for the product of two binomial parameters, J. Amer. Statist. Assoc. 52, 482-93.
- Burnett, T. L. and B. A. Wales (1961) System reliability confidence limits, Proceedings of the Seventh National Symposium on Reliability and Quality Control, 118-28.
- Conner, W. S. and W. T. Wells (1962), Simulating tests of a system from tests of its components, Proceedings of the Eighth National Symposium on Reliability and Quality Control, 14-16.
- Easterling, Robert G. (1972), Approximate confidence limits for system reliability, J. Amer. Statist. Assoc. 67, 220-22.
- El Mawaziny, A. H. (1965). "Chi-Square Distribution Theory with Applications to Reliability Problems," Ph.D. Thesis, Iowa State Univ., Ames.
- El Mawaziny, A. H. and R. J. Buehler (1967), Confidence limits for the reliability of a series system, J. Amer. Statist. Assoc. 62, 1452-9.
- Fertig, K. W. (1972) Bayesian prior distributions for systems with exponential failure-time data. Ann. Math. Statist. (To appear).
- Garner, Norman R. and Richard W. J. Vail (1961), Confidence limits for system reliability, Military Systems Design, Vol. 7, No. 5.
- Grubbs, Frank (1971). Approximate fiducial bounds for the reliability of a series system for which each component has an exponential time-to-fail distribution. Technometrics. 13, 865-71.
- Harris, Bernard (1971), Hypothesis testing and confidence intervals for products and quotients of Poisson parameters with applications to reliability, J. Amer. Statist. Assoc. 66, 609-13.
- Kraemer, H. C. (1965). One-sided confidence intervals for the quality indices of a complex item. Technometrics 7, 400-3.
- Lehmann, E. L. (1959), Testing Statistical Hypotheses, John Wiley, New York.
- Lentner, M. M. & R. J. Buehler (1965). Some inferences about gamma parameters with an application to a reliability problem. J. Amer. Statist. Assoc. 58, 670-7.

Levy, L. and A. H. Moore (1967), A Monte Carlo technique for obtaining system reliability confidence limits from component test data, I.E.E.E. Trans. Reliability R-16, 69-72.

Lieberman, Gerald J. and Sheldon M. Ross (1971), Confidence intervals for independent exponential series systems, J. Amer. Statist. Assoc. 857-40.

Lipow, M. and J. Riley (1959), "Tables of Upper Confidence Bounds on Failure Probability of 1, 2, and 3 Component Serial Systems." Vols. I and II, Space Technology Laboratories AD-609-100, AD-636-718.

Lloyd, D. K. and M. Lipow (1962), Reliability: Management, Methods, and Mathematics, Prentice-Hall, New Jersey.

Madansky, Albert (1965), Approximate confidence limits for the reliability of series and parallel systems, Technometrics, 7, 495-503.

Mann, Nancy R. (1970), Computer-aided selection of prior distributions for generating Monte Carlo confidence bounds on system reliability, Nav. Research Log. Quart. 17, 41-54.

Mann, Nancy R. (1971), "Approximately Optimum (Randomized and Nonrandomized) Confidence Bounds on Series- and Parallel-System Reliability for Systems with Binomial Subsystem Data." Rocketdyne Research Report RR 71-01, Rocketdyne, Canoga Park, California 91304. (Submitted for publication.)

Mann, Nancy R. (1972), A note on simplifying the procedure for obtaining approximately optimum confidence bounds on series-system reliability for exponential time to failure. (To be submitted for publication.)

Mann, Nancy R. and Frank E. Grubbs (1972), Approximately optimum confidence bounds on series-system reliability for exponential time to fail data, Biometrika, April 1972.

Mann, Nancy R. and Kenneth W. Fertig (1972), "Approximately Optimum (Randomized and Nonrandomized) Confidence Bounds on the Reliability of a Logically Complex Coherent System, Rocketdyne Research Report RR 72-02, Rocketdyne, Canoga Park, California. (To be submitted for publication.)

Mastran, David V. (1968), A Bayesian approach for assessing the reliability of Air Force re-entry systems, Proceedings of the ASME Reliability and Maintainability Symposium, 380-383.

Murchland, J. D. and Gunter G. Weber (1972), A moment method for the calculation of a confidence interval for the failure of a probability of a system, Proceedings of the 1972 Annual Reliability and Maintainability Symposium, 565-75.

Myhre, Janet and Sam C. Saunders (1968a), Comparison of two methods of obtaining approximate confidence intervals for system reliability, Technometrics, 10, 37-49.

Myhre, J. M. and S. C. Saunders (1968b), On confidence limits for the reliability of systems, Ann. Math. Statist. 39, 1463-72.

Parker, J. B. (1972), Bayesian prior distributions for multi-component systems, Nav. Research Logist. Quart. (To appear).

Patnaik, P. B. (1949), The non-central χ^2 and F distributions and their applications, Biometrika, 36, 202-252.

Raiffa, H. and R. Schlaifer (1961), Applied Statistical Decision Theory, Graduate School of Business Administration, Harvard University.

Rosenblatt, Joan Raup (1963), Confidence limits for the reliability of complex systems, Statistical Theory of Reliability (Ed. Marvin Zelen) (The University of Wisconsin Press, Madison, Wisconsin).

Sarkar, Tapas K. (1971), An exact lower confidence bound for the Reliability of a series system where each component has an exponential time to failure distribution, Technometrics, 535-546.

Schick, G. J. and R. J. Prior (1966), Reliability and confidence of serially connected systems, Proceedings of the Third Space Congress, Cocoa Beach, Florida, 352-360.

Springer, M. D. and W. E. Thompson (1968), Bayesian confidence limits for reliability of redundant systems when tests are terminated at first failure, Technometrics, 10, 29-36.

Steck, G. P. (1957), "Upper Confidence Limits for the Failure Probability of Complex Networks," Sandia Corporation SC-433 (TR).

Wilks, S. S. (1958), The large-sample distribution of the likelihood ratio for testing composite hypotheses, Ann. Math. Statist. 9, 60-62.

Wilson, E. B. and M. M. Hilferty (1951), The distribution of Chi-square, Proc. National Academy Sciences 17, 684-88.

Woods, M. and J. Borsting (1968), "A Method for Computing Lower Confidence Limits on System Reliability Using Component Failure Data with Unequal Sample Sizes," U.S. Naval Postgraduate Report NPS55 wo/Bg 8061A.

Zimmer, W. J., R. R. Prairie, and A. M. Breipohl (1965), A consideration of the Bayesian approach in reliability evaluation, I.E.E.E. Transactions on Reliability R-14, 107-115.