

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED.

DR-116
NOVEMBER 1966

AD

803407

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV (SR-041)
(25 October 1966)

BY

LEN E. CARTER

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

E COM

UNITED STATES ARMY ELECTRONICS COMMAND

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV (SR-041)
(25 October 1966)

By

Len E. Carter

DR-116

November 1966

DA Task IV650212A127-02

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

Distribution of this document is unlimited.

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

*OR are
Blank pgs
that have
Been Removed*

**BEST
AVAILABLE COPY**

ABSTRACT

Metecrological data gathered for the launching of Nike-Hydrac STV (SR-041) are presented for the Ballistic Systems Division of the U. S. Air Force, Avco Corporation and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

CONTENTS

	PAGE
ABSTRACT -----	111
INTRODUCTION -----	1
DISCUSSION -----	1
TABLES	
I. Theoretical Rocket Performance Values -----	2
II. Ballistic Factors -----	3
III. Anemometer-Wind Speed and Direction -----	4
IV. Pilot-Balloon-Measured Wind Data -----	5
V. Rawinsonde Measured Wind Data -----	6
VI. Computer-Calculated Upper Air Data (Release Time: 1035 MST) -----	7
VII. Computer-Calculated Upper Air Data (Release Time: 1320 MST) -----	15
VIII. Impact Prediction Data -----	23

INTRODUCTION

Nike-Hydroc STV (SR-041) was launched from Launch Complex 33, L-314, White Sands Missile Range (WSMR), New Mexico, at 1320 hours MST, 25 October 1966.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Division, Atmospheric Sciences Laboratory (ASL), WSMR, New Mexico. The Ballistics Meteorologists for this firing were Len E. Carter and John H. Sharpe.

DISCUSSION

Wind data for the first 216 feet above the surface were obtained from a system composed of 5 Aerovanes mounted on a 216-foot tower and cabled to five component wind indicators.

From 216 to 4,000 feet above the surface, wind data were obtained from double-theodolite-observed balloon ascents.

Temperature, pressure, and humidity data, along with upper wind data from 4,000 to 73,497 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic axis were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and ballistic factors as a function of altitude were provided by ASL, and are the basis for data appearing in Table VIII.

PAYLOAD		233	Pounds
CORIOIIS DISPLACEMENT	WEST	4.9	Miles
SECOND-STAGE IGNITION	TIME	20.2	Seconds
	ALTITUDE	36,673	Feet NSL
PEAK	TIME	236.2	Seconds
	ALTITUDE	718,586	Feet NSL
UNIT WIND EFFECT			Miles/MPH
		2.575	Miles/MPH
			Miles/MPH
TOWER TILT EFFECT		14.08	Miles/Degree

TABLE I. THEORETICAL ROCKET PERFORMANCE VALUES
NIKE-HYDAC STV (SR-041)

LAYERS IN MINE ABOVE GROUND	BALISTIC FACTORS
8600-32617	-.0057
32617-32000	.0213
32000-30000	.0315
30000-11000	.0313
11000-16000	.0126
16000-51000	.0055
51000-50000	.0015
50000-61000	.0084
61000-60000	.0009
60000-72197	.0009

LAYERS IN MINE ABOVE GROUND	BALISTIC FACTORS
1000-1400	.0703
1400-2000	.0563
2000-2500	.0899
2500-3000	.0166
3000-3500	.0803
3500-4000	.0011
4000-4863	-.0067
4863-9000	-.0109
9000-15000	-.0124
15000-21000	-.0104
21000-24000	-.0072

LAYERS IN MINE ABOVE GROUND	BALISTIC FACTORS
0-11	.0000
11-60	.1482
60-100	.1088
100-148	.0671
148-184	.0534
184-216	.0315
216-300	.0835
300-400	.0681
400-600	.0787
600-800	.0503
800-1000	.0432

TABLE II. BALISTIC FACTORS
MINE-HYDRO STV (SR-041)

AERO-VANE NO. *	MEAN WIND COMPONENTS IN KILMS. PER HOUR														
	1 1150 MST		2 1200 MST		3 1235 MST		4 1250 MST		5 1300 MST		6 1300 MST		7 1320 MST		
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	
1	0.0	2.0E	1.0N	0.5E	2.0N	0.0	1.0N	0.0	1.0N	1.0E	1.0E	1.0N	4.0E	0.0	2.0E
2	0.0	2.0	0.0	2.0	3.0	0.0	0.0	2.0E	0.0	2.0	0.0	0.0	4.0	0.0	2.0
3	0.0	2.0	0.0	0.0	2.0	0.0	1.0N	0.0	1.0N	0.0	0.0	1.0N	3.0	0.0	2.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0	2.0E	2.0
5	0.0	2.0E	0.0	2.0E	0.0	0.0	0.0	2.0E	0.0	2.0N	2.0N	4.0N	0.0	2.0	2.0

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION
NIKE-HIDAC STY (SR-041)

* Heights corresponding to Aerovane Numbers: 1 = 35 Feet 2 = 58 Feet 3 = 128 Feet 4 = 168 Feet 5 = 200 Feet

LAYER IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KILOMETERS PER HOUR														
	1		2		3		4		5		6		7		
	1150 MST	1200 MST	1235 MST	1250 MST	1300 MST	1310 MST	1350 MST	1400 MST	1435 MST	1450 MST	1500 MST	1510 MST	1550 MST	1600 MST	
N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
206-300	2.0	1.0	1.0	0.0	2.0	0.5	1.0	2.0	1.0	2.0	2.0	2.0	0.5	1.5	1.0
300-400	3.5	2.0	2.5	0.5	2.0	0.5	1.0	2.0	2.0	2.0	2.0	0.5	1.5	0.0	0.5
400-600	2.5	2.0	4.0	2.0	2.0	2.0	2.0	2.0	4.5	2.0	2.0	0.0	2.0	0.0	0.5
600-800	2.0	4.0	4.5	1.5	2.0	2.0	2.0	1.0	4.0	2.5	0.0	0.0	3.0	0.0	0.0
800-1000	2.5	3.0	4.5	2.0	2.0	4.5	2.0	2.0	4.0	3.0	0.0	0.0	2.0	0.0	1.5
1000-1400	2.5	2.5	4.5	2.5	0.5	4.5	2.0	0.5	2.0	3.0	0.5	0.5	0.0	0.0	3.0
1400-2000	3.0	0.5	3.5	2.0	2.0	2.0	2.0	1.0	0.0	2.0	0.0	0.0	0.0	1.5	3.0
2000-2500	3.0	1.5	0.0	2.0	0.0	0.0	0.0	0.0	2.0	0.0	0.0	0.0	0.0	0.0	0.5
2500-3000	4.0	1.0	2.5	0.0	1.0	0.0	1.0	1.0	2.0	2.5	2.5	1.5	1.0	1.5	0.5
3000-3500	0.0	3.0	2.5	2.0	2.0	2.0	3.0	2.0	2.5	2.5	2.0	2.0	1.5	2.5	0.0
3500-4000	4.0	3.0	4.5	4.0	3.5	4.0	5.0	3.5	7.5	2.0	3.0	3.0	2.5	2.0	0.5

TABLE IV. PILOT-BALLOON-OBSERVED WIND DATA
NINH-TRUNG STN (GR-01A)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS					
	1 1035 MST			2 1320 MST		
	N-S	E-W	N-S	E-W	N-S	E-W
8000-8263	2.0S	6.0E	4.0S	0.5W		
8263-13000	2.5N	8.0	1.5	5.0E		
13000-19000	17.0	0.0	16.0W	3.0		
19000-25000	21.5	4.0W	18.5	3.5		
25000-30000	17.0	6.0E	8.0	2.5		
30000-36647	10.5	9.0	6.5	7.5		
36647-38000	13.0	7.5	10.5	6.0		
38000-40000	14.0	8.0	11.0	6.5		
40000-45000	17.0	0.0	19.0	7.0W		
45000-50000	12.0	7.0W	14.5	12.0		
50000-55000	9.5	5.5	9.0	7.5		
55000-60000	2.5	8.0E	2.0S	6.0E		
60000-65000	9.0S	1.5	0.0	6.0		
65000-70000	0.5N	4.0	2.5S	6.0		

TABLE V. RAWINSONDE-MEASURED WIND DATA
NIKE-HYDAC STY (SR-041)

STATION ALTITUDE. 3989.0 FEET MSL
 25 OCT. 66
 ASCENSION NO. 835

UPPER AIR DATA
 0284003904
 WHITE SANDS SITE
 TABLE VI

MSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	890.0	17.8	-3.6	23.0	1063.7	664.8	30.0	7.0	1.000258	
4000.0	889.6	17.7	-3.7	23.0	1063.6	664.7	29.9	7.0	1.000258	
4500.0	873.8	14.0	-6.8	23.0	1058.5	660.3	26.8	6.2	1.000253	
5000.0	858.1	14.0	-6.8	23.0	1039.6	660.4	23.8	5.5	1.000248	
5500.0	842.7	14.7	-6.2	23.0	1018.2	661.2	20.7	4.7	1.000244	
6000.0	827.5	13.8	-7.0	23.0	1003.1	660.1	17.6	4.0	1.000240	
6500.0	812.5	12.9	-7.8	23.0	988.2	659.0	32.3	3.2	1.000236	
7000.0	797.7	11.9	-8.6	23.0	973.6	657.9	65.5	2.5	1.000232	
7500.0	783.3	11.0	-9.4	23.0	959.2	656.8	92.5	2.8	1.000228	
8000.0	769.1	10.0	-10.2	23.0	945.0	655.7	113.3	4.3	1.000224	
8500.0	755.2	9.1	-11.0	23.0	931.0	654.6	123.6	5.4	1.000220	
9000.0	741.5	8.1	-11.8	23.0	917.3	653.5	127.1	6.2	1.000216	
9500.0	728.0	7.2	-12.6	23.0	903.7	652.3	121.1	6.0	1.000213	
10000.0	714.8	6.2	-13.4	23.1	890.4	651.2	112.6	5.5	1.000209	
10500.0	701.5	5.1	-14.1	23.5	877.4	649.9	95.9	4.9	1.000206	
11000.0	688.5	4.0	-14.9	23.9	864.7	648.5	78.6	4.3	1.000202	
11500.0	675.7	2.9	-15.6	24.3	852.1	647.2	63.1	5.2	1.000199	
12000.0	663.1	1.7	-16.4	24.7	839.7	645.9	47.7	6.2	1.000196	
12500.0	650.8	0.9	-16.9	25.1	826.7	644.9	37.2	7.4	1.000192	
13000.0	638.5	0.5	-17.1	25.4	812.3	644.4	26.8	8.7	1.000189	
13500.0	626.5	0.1	-17.3	25.8	798.2	643.9	17.7	10.3	1.000186	
14000.0	614.7	-0.4	-17.8	25.8	784.6	643.3	9.5	11.7	1.000183	
14500.0	603.1	-1.3	-18.8	25.0	772.3	642.3	4.9	12.3	1.000179	
15000.0	591.7	-2.2	-19.9	24.3	760.1	641.2	2.3	13.1	1.000176	
15500.0	580.4	-3.0	-21.1	23.5	748.1	640.2	3.1	14.1	1.000173	
16000.0	569.4	-3.9	-22.1	22.9	736.3	639.1	3.8	15.3	1.000169	
16500.0	558.3	-5.0	-23.2	22.5	724.9	637.9	4.7	16.7	1.000166	
17000.0	547.5	-6.0	-24.3	22.2	713.6	636.6	5.3	18.3	1.000164	
17500.0	536.9	-7.0	-25.3	21.8	702.5	635.4	5.8	20.1	1.000161	
18000.0	526.5	-8.0	-26.4	21.5	691.5	634.2	5.9	20.8	1.000158	

UPPER AIR DATA
0284003904
WHITE SANDS SITE
TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
25 OCT. 66 1035 HRS MST
ASCENSION NO. 835

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
18500.0	516.3	-9.0	-27.4	21.1	680.8	632.9	5.8	21.3	1.000155	
19000.0	506.3	-10.1	-28.5	20.7	670.2	631.7	7.3	21.3	1.000152	
19500.0	496.5	-11.1	-29.5	20.4	659.8	630.5	9.1	21.2	1.000150	
20000.0	486.8	-12.1	-30.6	20.0	649.6	629.2	9.9	21.4	1.000147	
20500.0	477.0	-13.3	-31.4	20.2	639.3	627.8	10.5	21.5	1.000145	
21000.0	467.4	-14.4	-32.3	20.5	629.2	626.4	10.1	21.8	1.000142	
21500.0	457.9	-15.6	-33.2	20.7	619.2	625.0	9.5	22.2	1.000140	
22000.0	448.7	-16.7	-34.0	21.0	609.4	623.6	7.3	22.6	1.000138	
22500.0	439.6	-17.9	-34.9	21.2	599.8	622.2	5.4	22.8	1.000135	
23000.0	430.7	-19.0	-35.8	21.4	590.3	620.8	4.6	22.3	1.000133	
23500.0	422.0	-20.2	-36.7	21.7	581.0	619.4	4.2	21.7	1.000131	
24000.0	413.4	-21.3	-37.5	21.9	571.9	618.0	5.2	21.2	1.000129	
24500.0	405.1	-22.5	-38.4	22.2	562.9	616.5	6.9	20.6	1.000127	
25000.0	396.9	-23.6	-39.3	22.4	554.1	615.1	9.9	20.0	1.000125	
25500.0	388.8	-24.8	-40.2	22.7	545.4	613.7	12.4	19.1	1.000123	
26000.0	381.0	-26.0	-41.1	22.9	536.9	612.2	14.5	18.0	1.000121	
26500.0	373.1	-27.0	-42.0	23.0	527.9	611.0	15.5	17.3	1.000119	
27000.0	365.2	-27.9	-42.7	23.0	518.7	609.9	16.0	16.8	1.000116	
27500.0	357.5	-28.8	-43.5	23.0	509.7	608.7	16.3	16.2	1.000114	
28000.0	350.0	-29.7	-44.3	23.0	500.8	607.6	16.6	15.5	1.000112	
28500.0	342.6	-30.6	-45.1	23.0	492.1	606.4	18.6	15.3	1.000110	
29000.0	335.4	-31.5	-45.9	23.0	483.6	605.3	20.9	15.3	1.000108	
29500.0	328.3	-32.5	-46.7	23.0	475.2	604.1	25.3	14.8	1.000106	
30000.0	321.3	-33.8	-47.9	23.0	467.6	602.5	30.0	14.5	1.000105	
30500.0	314.4	-35.1	-49.1	23.0	460.1	600.8	36.3	14.7	1.000103	
31000.0	307.6	-36.5	-50.2	23.0	452.8	599.0	41.6	15.0	1.000101	
31500.0	300.7	-37.8	-51.8	21.8**	445.1	597.4	42.6	15.1	1.000099	
32000.0	293.9	-39.0	-53.5	20.3**	437.3	595.8	43.5	15.1	1.000098	
32500.0	287.3	-40.3	-55.2	18.8**	429.8	594.2	44.2	14.4	1.000096	
33000.0	280.8	-41.5	-57.0	17.2**	422.3	592.6	42.7	13.7	1.000094	

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66
 ASCENSION NO. 835

UPPER AIR DATA
 0284003904
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	AIR TEMPERATURE DEGREES CENTIGRADE	DEWPOINT DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES(TN)	WIND SPEED KNOTS	INDEX OF REFRACTION
33500.0	274.5	-42.8	-58.8	15.7**	415.0	591.0	38.7	12.9	1.000093
34000.0	268.3	-44.0	-60.6	14.2**	407.9	589.4	35.8	12.5	1.000091
34500.0	262.2	-45.3	-62.5	12.7**	400.8	587.8	33.6	12.2	1.000089
35000.0	256.3	-46.5	-64.5	11.1**	393.9	586.2	33.2	12.7	1.000088
35500.0	250.5	-47.8	-66.6	9.6**	387.2	584.6	33.1	13.4	1.000086
36000.0	244.8	-49.0	-68.8	8.1**	380.6	583.0	32.0	13.8	1.000085
36500.0	239.3	-50.3	-71.3	6.5**	374.0	581.3	30.9	14.3	1.000083
37000.0	233.9	-51.5	-74.0	5.0**	367.7	579.7	29.4	14.5	1.000082
37500.0	228.6	-52.7	-77.3	3.5**	361.4	578.1	27.9	14.7	1.000080
38000.0	223.4	-54.0	-81.8	2.0**	355.2	576.4	27.0	15.3	1.000079
38500.0	218.4	-55.2	-91.1	0.4**	349.2	574.8	26.2	15.8	1.000078
39000.0	213.3	-56.2	0.	0.	342.5	573.5	28.4	16.2	1.000076
39500.0	208.2	-57.0	0.	0.	335.7	572.4	31.1	16.5	1.000075
40000.0	203.3	-57.9	0.	0.	329.0	571.3	29.6	16.6	1.000073
40500.0	198.4	-58.7	0.	0.	322.4	570.2	27.5	16.7	1.000072
41000.0	193.7	-59.4	0.	0.	315.8	569.2	18.1	16.7	1.000070
41500.0	189.1	-58.5	0.	0.	307.0	570.5	8.1	16.8	1.000068
42000.0	184.6	-57.6	0.	0.	298.3	571.7	356.4	18.6	1.000066
42500.0	180.2	-57.3	0.	0.	290.9	572.1	344.6	20.4	1.000065
43000.0	175.9	-58.1	0.	0.	284.8	571.1	341.8	21.3	1.000063
43500.0	171.6	-58.8	0.	0.	279.0	570.1	339.2	22.1	1.000062
44000.0	167.5	-59.6	0.	0.	273.2	569.1	337.6	21.0	1.000061
44500.0	163.5	-60.3	0.	0.	267.6	568.1	336.0	19.8	1.000060
45000.0	159.5	-61.1	0.	0.	262.0	567.1	335.4	18.1	1.000058
45500.0	155.7	-61.8	0.	0.	256.6	566.1	334.8	16.4	1.000057
46000.0	151.9	-62.6	0.	0.	251.4	565.1	328.2	14.2	1.000056
46500.0	148.3	-63.3	0.	0.	246.2	564.1	321.2	11.9	1.000055
47000.0	144.7	-64.1	0.	0.	241.1	563.1	312.3	11.9	1.000054
47500.0	141.2	-64.6	0.	0.	235.8	562.4	303.1	12.1	1.000052
48000.0	137.7	-65.0	0.	0.	230.5	561.8	300.2	12.5	1.000051

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0284003904
 WHITE SANDS SITE
 TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1035 HRS MST
 ASCENSION NO. 835

WSTM SITE COORDINATES
 E 486,590 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	DIRECTION DEGREES(TM)	SPEED KNOTS	INDEX OF REFRACTION
48500.0	134.3	-65.5	-0. **	225.3	561.2	299.2	13.0	1.000050
49000.0	131.0	-65.9	-0. **	220.2	560.6	301.6	13.4	1.000049
49500.0	127.8	-66.4	-0. **	215.2	559.9	305.2	13.7	1.000048
50000.0	124.6	-66.3	-0. **	209.9	560.0	310.5	13.2	1.000047
50500.0	121.5	-65.6	-0. **	204.1	560.9	316.5	12.3	1.000045
51000.0	118.6	-65.0	-0. **	198.4	561.8	320.0	11.1	1.000044
51500.0	115.6	-65.0	-0. **	193.6	561.7	322.5	9.8	1.000043
52000.0	112.8	-66.0	-0. **	189.6	560.3	322.0	9.5	1.000042
52500.0	110.0	-66.9	-0. **	185.7	559.2	319.9	9.8	1.000041
53000.0	107.2	-67.8	-0. **	182.0	557.9	321.4	9.9	1.000041
53500.0	104.6	-68.8	-0. **	178.3	556.7	326.3	9.9	1.000040
54000.0	102.0	-69.7	-0. **	174.6	555.4	333.8	9.4	1.000039
54500.0	99.4	-69.4	-0. **	170.0	555.9	346.1	8.0	1.000038
55000.0	96.9	-69.0	-0. **	165.5	556.3	358.8	6.9	1.000037
55500.0	94.5	-68.7	-0. **	161.1	556.8	13.6	6.7	1.000036
56000.0	92.2	-68.3	-0. **	156.8	557.3	28.4	6.4	1.000035
56500.0	89.9	-68.0	-0. **	152.6	557.7	43.3	6.7	1.000034
57000.0	87.6	-67.7	-0. **	148.5	558.2	58.3	7.0	1.000033
57500.0	85.4	-67.4	-0. **	144.7	558.5	67.5	6.7	1.000032
58000.0	83.3	-67.6	-0. **	141.2	558.3	75.5	6.2	1.000031
58500.0	81.3	-67.1	-0. **	137.4	558.9	84.5	7.9	1.000031
59000.0	79.3	-66.5	-0. **	133.7	559.7	93.9	10.5	1.000030
59500.0	77.3	-66.0	-0. **	130.0	560.5	105.0	11.7	1.000029
60000.0	75.4	-65.4	-0. **	126.5	561.3	116.9	12.2	1.000028
60500.0	73.6	-64.8	-0. **	123.0	562.0	124.2	11.9	1.000027
61000.0	71.8	-64.2	-0. **	119.7	562.8	129.8	11.3	1.000027
61500.0	70.0	-63.7	-0. **	116.4	563.6	139.5	10.0	1.000026
62000.0	68.3	-63.1	-0. **	113.3	564.3	150.3	8.4	1.000025
62500.0	66.6	-62.5	-0. **	110.2	565.1	154.7	7.5	1.000025
63000.0	65.0	-62.3	-0. **	107.4	565.4	157.5	6.7	1.000024

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1035 HRS MST
 ASCENSION NO. 835

UPPER AIR DATA
 0284003904
 WHITE SANDS SITE
 TABLE VI (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
63500.0	63.4	-62.3	0.	-0. **	104.8	565.4	165.4	5.0	1.000023
64000.0	61.9	-60.6	0.	-0. **	101.5	567.7	174.5	3.1	1.000023
64500.0	60.4	-58.3	0.	-0. **	97.9	570.8	211.5	2.7	1.000022
65000.0	59.0	-57.7	0.	-0. **	95.4	571.5	257.0	2.6	1.000021
65500.0	57.6	-57.8	0.	-0. **	93.2	571.4	286.1	3.9	1.000021
66000.0	56.2	-58.0	0.	-0. **	91.0	571.2	308.6	5.6	1.000020
66500.0	54.9	-58.1	0.	-0. **	88.9	571.0	327.8	6.0	1.000020
67000.0	53.6	-58.2	0.	-0. **	86.8	570.8	343.8	5.2	1.000019
67500.0	52.3	-57.7	0.	-0. **	84.6	571.6	0.1	4.5	1.000019
68000.0	51.1	-56.5	0.	-0. **	82.1	573.1	19.0	4.3	1.000018
68500.0	49.9	-55.3	0.	-0. **	79.8	574.6	37.9	4.1	1.000018
69000.0	48.7	-54.6	0.	-0. **	77.6	575.6	53.1	3.9	1.000017
69500.0	47.6	-55.1	0.	-0. **	76.0	574.9	65.8	3.5	1.000017
70000.0	46.4	-55.6	0.	-0. **	74.4	574.3	77.4	3.2	1.000017
70500.0	45.3	-56.2	0.	-0. **	72.8	573.6	72.0	2.9	1.000016
71000.0	44.3	-56.7	0.	-0. **	71.3	572.9	66.7	2.5	1.000016
71500.0	43.2	-56.5	0.	-0. **	69.6	573.1	65.5	2.3	1.000015
72000.0	42.2	-56.2	0.	-0. **	67.8	573.6	68.0	2.0	1.000015
72500.0	41.3	-55.8	0.	-0. **	66.1	574.0	70.4	1.8	1.000015
73000.0	40.3	-55.4	0.	-0. **	64.5	574.5	86.3	2.6	1.000014
73500.0	39.4	-55.1	0.	-0. **	62.9	575.0	102.6	3.6	1.000014
74000.0	38.4	-54.7	0.	-0. **	61.3	575.5	119.9	4.0	1.000014
74500.0	37.5	-54.4	0.	-0. **	59.8	576.0	139.2	3.6	1.000013
75000.0	36.7	-54.0	0.	-0. **	58.3	576.4	158.5	3.2	1.000013
75500.0	35.8	-53.6	0.	-0. **	56.8	576.9	121.6	2.3	1.000013
76000.0	35.0	-53.3	0.	-0. **	55.4	577.4	64.2	1.3	1.000012
76500.0	34.2	-52.9	0.	-0. **	54.1	577.9	14.1	0.7	1.000012
77000.0	33.4	-52.5	0.	-0. **	52.7	578.3	22.9	2.8	1.000012
77500.0	32.6	-52.2	0.	-0. **	51.4	578.8	31.8	4.9	1.000011
78000.0	31.8	-51.8	0.	-0. **	50.1	579.3	41.9	6.9	1.000011

H

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0284003904
 WHITE SANDS SITE
 TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1035 HRS MST
 ASCENSION NO. 835

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			SOUND KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS		
93500.0	15.5	-45.8	0.	-0.	23.8	587.1	77.5	18.3	1.000005	
94000.0	15.2	-45.6	0.	-0.	23.2	587.4	81.5	18.2	1.000005	
94500.0	14.8	-45.3	0.	-0.	22.7	587.7	86.2	17.5	1.000005	
95000.0	14.5	-45.1	0.	-0.	22.2	588.0	91.0	16.8	1.000005	
95500.0	14.2	-44.9	0.	-0.	21.6	588.3	96.4	16.2	1.000005	
96000.0	13.9	-44.6	0.	-0.	21.1	588.6	103.3	15.5	1.000005	
96500.0	13.6	-44.4	0.	-0.	20.7	588.9	110.3	14.8	1.000005	
97000.0	13.3	-44.2	0.	-0.	20.2	589.2	117.5	14.1	1.000004	
97500.0	13.0	-43.9	0.	-0.	19.7	589.5	127.6	13.4	1.000004	
98000.0	12.7	-43.7	0.	-0.	19.3	589.8	137.7	12.7	1.000004	
98500.0	12.4	-43.5	0.	-0.	18.8	590.1	147.9	11.9	1.000004	
99000.0	12.1	-43.3	0.	-0.	18.4	590.4	157.4	12.2	1.000004	
99500.0	11.9	-43.0	0.	-0.	18.0	590.7	166.9	12.7	1.000004	
100000.0	11.6	-42.8	0.	-0.	17.5	591.0	176.3	13.1	1.000004	
100500.0	11.3	-42.6	0.	-0.	17.1	591.3	181.8	13.3	1.000004	
101000.0	11.1	-42.3	0.	-0.	16.7	591.6	185.2	13.5	1.000004	
101500.0	10.8	-42.1	0.	-0.	16.3	591.9	188.7	13.6	1.000004	
102000.0	10.6	-41.9	0.	-0.	16.0	592.2	191.4	13.5	1.000004	
102500.0	10.4	-41.6	0.	-0.	15.6	592.4	193.4	13.1	1.000003	
103000.0	10.1	-41.4	0.	-0.	15.2	592.7	195.4	12.6	1.000003	
103500.0	9.9	-41.2	0.	-0.	14.9	593.0	197.8	12.2	1.000003	
104000.0	9.7	-41.0	0.	-0.	14.5	593.3	201.9	11.7	1.000003	
104500.0	9.5	-40.7	0.	-0.	14.2	593.6	205.9	11.2	1.000003	
105000.0	9.3	-40.5	0.	-0.	13.9	593.9	210.0	10.7	1.000003	
105500.0	9.1	-40.3	0.	-0.	13.6	594.2	221.2	10.1	1.000003	
106000.0	8.9	-39.3	0.	-0.	13.2	595.4	232.5	9.4	1.000003	
106500.0	8.7	-38.1	0.	-0.	12.9	596.9	243.8	8.8	1.000003	
107000.0	8.5	-36.9	0.	-0.	12.5	598.4	244.1	9.0	1.000003	
107500.0	8.3	-36.5	0.	-0.	12.2	598.9	240.4	9.4	1.000003	
108000.0	8.1	-36.8	0.	-0.	12.0	598.6	236.8	9.9	1.000003	

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0284003904
 WHITE SANDS SITE
 TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1035 HRS MST
 ASCENSION NO. 835

MSTM SITE COORDINATES
 E 488,580 FEET
 W 103,043 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(THD)	SPEED KNOTS	
108500.0	7.9	-37.0	0.	**	11.7	598.5	231.7	10.1	1.0000003	
109000.0	7.8	-37.3	0.	**	11.5	598.0	224.0	10.1	1.0000003	
109500.0	7.6	-37.6	0.	**	11.2	597.7	210.0	10.1	1.0000003	
110000.0	7.4	-37.8	0.	**	11.0	597.3			1.0000002	
110500.0	7.3	-38.1	0.	**	10.8	597.0			1.0000002	
111000.0	7.1	-38.3	0.	**	10.6	596.7			1.0000002	
111500.0	7.0	-38.6	0.	**	10.3	596.4			1.0000002	
112000.0	6.8	-38.8	0.	**	10.1	596.0			1.0000002	
112500.0	6.7	-39.1	0.	**	9.9	595.7			1.0000002	

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO. 836

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII

WSTM SITE COORDINATES
 E 488,580 FFFT
 N 105,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REF. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT/ CENTIGRADE				DIRECTION DEGREES (TN)	SPEED KNOTS	
3989.0	687.8	22.5	-2.3	19.0	1043.9	670.3	180.0	1.9	1.000255
4000.0	887.5	22.5	-2.3	19.0	1043.7	670.2	179.8	1.9	1.000255
4500.0	871.8	20.8	-3.2	19.7	1031.3	668.2	172.6	1.9	1.000251
5000.0	856.3	19.1	-4.1	20.4	1019.1	666.3	165.3	1.8	1.000247
5500.0	841.2	17.3	-5.1	21.1	1007.0	664.3	158.1	1.7	1.000243
6000.0	826.3	15.6	-6.1	21.9	995.2	662.3	150.9	1.7	1.000239
6500.0	811.7	13.9	-7.1	22.6	983.5	660.3	154.5	2.0	1.000236
7000.0	797.1	12.4	-8.0	23.2	970.9	658.6	176.5	2.9	1.000232
7500.0	782.4	11.3	-8.8	23.6	956.9	657.2	109.0	3.7	1.000228
8000.0	768.0	10.2	-9.5	24.0	943.2	655.9	187.6	4.4	1.000224
8500.0	753.9	9.0	-10.3	24.5	929.6	654.5	186.0	4.1	1.000220
9000.0	740.0	7.9	-11.0	24.9	916.3	653.2	184.2	3.4	1.000217
9500.0	726.4	6.7	-11.8	25.3	903.1	651.9	175.5	2.2	1.000213
10000.0	713.0	5.6	-12.6	25.7	890.2	650.5	149.0	1.6	1.000210
10500.0	699.9	4.4	-13.4	26.2	877.4	649.1	76.0	2.6	1.000206
11000.0	687.0	3.3	-14.2	26.6	864.9	647.8	48.0	4.0	1.000203
11500.0	674.4	2.1	-15.0	27.0	852.5	646.4	51.7	5.6	1.000200
12000.0	661.9	1.0	-15.8	27.4	840.4	645.0	48.0	8.1	1.000196
12500.0	649.8	-0.1	-16.6	27.9	828.4	643.7	42.8	10.5	1.000193
13000.0	637.6	-0.8	-17.4	27.3	814.8	642.9	35.4	12.0	1.000190
13500.0	625.5	-1.2	-18.2	26.3	800.6	642.4	27.9	13.5	1.000186
14000.0	613.7	-1.6	-19.0	25.3	786.6	642.0	20.5	14.9	1.000182
14500.0	602.0	-2.0	-19.8	24.3	772.9	641.5	14.8	15.9	1.000179
15000.0	590.6	-2.4	-20.6	23.0	759.4	641.0	9.6	16.7	1.000175
15500.0	579.4	-3.6	-22.0	22.6	748.5	639.4	8.2	16.8	1.000172
16000.0	568.3	-5.3	-23.8	22.0	739.0	637.4	6.8	16.9	1.000169
16500.0	557.4	-5.4	-24.2	21.3	724.9	637.3	5.4	17.4	1.000166
17000.0	546.7	-6.1	-25.3	20.5	713.0	636.4	4.9	17.7	1.000163
17500.0	536.1	-7.3	-26.5	20.0	702.2	635.0	6.1	17.6	1.000160
18000.0	525.6	-8.3	-27.3	20.0	691.1	633.9	8.0	18.0	1.000157

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO. 836

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 188,589 FEET
 N 185,049 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
18500.0	515.4	-9.2	-28.1	20.0	680.0	632.7	10.6	16.8	1.000155
19000.0	505.3	-10.1	-28.9	20.0	669.2	631.6	11.9	19.1	1.000152
19500.0	495.5	-11.1	-29.7	20.0	658.5	630.5	12.8	19.3	1.000150
20000.0	485.8	-12.0	-30.5	20.0	648.0	629.3	11.8	20.1	1.000147
20500.0	476.2	-13.1	-31.3	20.2	637.8	628.0	10.7	20.8	1.000145
21000.0	466.7	-14.4	-32.1	20.8	628.2	626.5	9.7	21.0	1.000142
21500.0	457.4	-15.7	-32.9	21.4	618.7	624.9	9.4	21.1	1.000140
22000.0	448.3	-16.9	-33.8	21.9	609.4	623.3	10.2	21.2	1.000138
22500.0	439.3	-18.2	-34.6	22.5	600.3	621.8	11.1	20.6	1.000136
23000.0	430.5	-19.5	-35.4	23.0	591.1	620.3	12.1	19.7	1.000133
23500.0	421.6	-20.4	-36.3	22.9	581.0	619.1	12.2	18.7	1.000131
24000.0	412.9	-21.3	-37.1	22.8	571.1	618.0	12.1	17.6	1.000129
24500.0	404.4	-22.2	-38.0	22.7	561.4	616.9	10.8	17.0	1.000126
25000.0	396.1	-23.1	-38.8	22.6	551.8	615.7	9.6	16.5	1.000124
25500.0	387.9	-24.1	-39.6	22.5	542.4	614.6	8.7	15.8	1.000122
26000.0	379.9	-25.0	-40.5	22.4	533.2	613.5	7.6	15.3	1.000120
26500.0	372.1	-25.9	-41.3	22.3	524.2	612.3	6.0	15.0	1.000118
27000.0	364.4	-26.8	-42.1	22.2	515.3	611.2	5.4	14.2	1.000116
27500.0	356.9	-27.7	-43.0	22.1	506.6	610.0	6.4	12.9	1.000114
28000.0	349.5	-28.7	-43.8	22.0	498.0	608.9	8.8	11.5	1.000112
28500.0	342.2	-29.8	-44.8	22.1	489.8	607.5	12.7	10.0	1.000110
29000.0	334.9	-31.1	-45.8	22.3	482.0	605.8	21.4	8.6	1.000108
29500.0	327.7	-32.4	-46.9	22.5	474.3	604.2	33.0	7.3	1.000106
30000.0	320.8	-33.7	-47.9	22.7	466.7	602.5	41.7	7.0	1.000104
30500.0	313.5	-35.0	-49.0	22.9	459.3	600.9	49.5	7.1	1.000103
31000.0	307.1	-36.3	-50.8	21.2**	451.7	599.3	46.0	7.8	1.000101
31500.0	300.3	-37.6	-53.0	18.6**	444.1	597.6	42.8	8.6	1.000099
32000.0	293.6	-38.9	-55.3	16.1**	436.7	596.0	41.2	9.7	1.000097
32500.0	287.1	-40.2	-57.8	13.5**	429.4	594.3	39.8	10.6	1.000096
33000.0	280.8	-41.5	-60.5	11.0**	422.2	592.7	39.2	10.9	1.000094

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO. 836

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII (Cont)

HSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
33500.0	274.6	-42.7	-63.5	8.4**	415.2	591.0	39.9	11-2	1.000093
34000.0	268.5	-44.0	-67.1	5.9**	408.3	589.4	43.0	11.4	1.000091
34500.0	262.6	-45.3	-72.0	3.3**	401.5	587.7	45.8	11.3	1.000089
35000.0	256.8	-46.6	-82.0	0.8**	394.9	586.1	44.5	10.9	1.000088
35500.0	250.9	-47.8	0.	-0.0**	388.0	584.5	40.3	10.7	1.000086
36000.0	245.1	-49.0	0.	-0.0**	381.0	582.9	33.0	10.7	1.000085
36500.0	239.4	-50.2	0.	-0.0**	374.1	581.4	28.1	10.7	1.000083
37000.0	233.9	-51.4	0.	-0.0**	367.4	579.8	24.8	10.7	1.000082
37500.0	228.4	-52.6	0.	-0.0**	360.9	578.3	28.2	10.9	1.000080
38000.0	223.2	-53.8	0.	-0.0**	354.4	576.7	33.7	11.1	1.000079
38500.0	218.0	-55.0	0.	-0.0**	348.1	575.2	36.6	12.6	1.000078
39000.0	212.9	-56.2	0.	-0.0**	341.9	573.6	39.3	14.2	1.000076
39500.0	208.0	-57.2	0.	-0.0**	335.6	572.2	34.1	14.1	1.000075
40000.0	203.0	-57.8	0.	-0.0**	328.4	571.4	28.7	14.1	1.000073
40500.0	198.2	-58.4	0.	-0.0**	321.5	570.7	13.2	15.7	1.000072
41000.0	193.5	-58.9	0.	-0.0**	314.7	569.9	337.7	17.2	1.000070
41500.0	188.8	-59.4	0.	-0.0**	307.8	569.3	347.2	19.1	1.000069
42000.0	184.3	-57.3	0.	-0.0**	297.5	572.1	397.1	20.9	1.000066
42500.0	179.9	-57.8	0.	-0.0**	291.1	571.4	332.6	22.5	1.000065
43000.0	175.6	-58.3	0.	-0.0**	284.8	570.7	28.5	23.6	1.000063
43500.0	171.4	-58.9	0.	-0.0**	278.7	570.0	326.8	22.6	1.000062
44000.0	167.3	-59.4	0.	-0.0**	272.6	569.3	324.5	21.3	1.000061
44500.0	163.3	-59.9	0.	-0.0**	266.8	568.6	320.6	19.6	1.000059
45000.0	159.3	-60.4	0.	-0.0**	261.0	567.9	314.2	17.9	1.000058
45500.0	155.5	-61.0	0.	-0.0**	255.4	567.2	301.8	16.5	1.000057
46000.0	151.8	-61.5	0.	-0.0**	249.9	566.5	293.5	15.9	1.000056
46500.0	148.1	-62.0	0.	-0.0**	244.5	565.8	294.6	17.1	1.000054
47000.0	144.6	-62.6	0.	-0.0**	239.2	565.0	297.2	18.4	1.000053
47500.0	141.0	-63.3	0.	-0.0**	234.1	564.1	303.0	19.4	1.000052
48000.0	137.6	-64.0	0.	-0.0**	229.1	563.2	310.2	20.4	1.000051

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO: 836

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES(TN)	SPEED KNOTS	
48500.0	134.2	-64.6	-0.	224.3	562.2	320.6	21.4	1.000050
49000.0	130.9	-65.3	-0.	219.5	561.3	328.8	21.7	1.000049
49500.0	127.7	-66.0	-0.	214.8	560.4	331.2	19.9	1.000048
50000.0	124.6	-66.5	-0.	210.0	559.7	333.3	17.9	1.000047
50500.0	121.5	-66.8	-0.	205.1	559.3	334.0	15.4	1.000046
51000.0	118.5	-67.1	-0.	200.3	559.0	333.9	13.0	1.000045
51500.0	115.5	-67.4	-0.	195.6	558.6	328.9	11.4	1.000044
52000.0	112.7	-67.6	-0.	191.0	558.2	323.9	9.8	1.000043
52500.0	109.9	-67.9	-0.	186.5	557.8	327.4	9.4	1.000042
53000.0	107.1	-68.8	-0.	182.6	556.6	330.8	9.0	1.000041
53500.0	104.4	-69.7	-0.	178.8	555.5	335.8	7.0	1.000040
54000.0	101.8	-70.5	-0.	175.0	554.3	340.8	4.9	1.000039
54500.0	99.2	-70.1	-0.	170.3	554.8	353.1	4.0	1.000038
55000.0	96.8	-68.4	-0.	164.6	557.2	6.2	3.2	1.000037
55500.0	94.4	-68.2	-0.	160.4	557.5	38.6	3.4	1.000036
56000.0	92.0	-68.0	-0.	156.2	557.7	74.5	3.7	1.000035
56500.0	89.7	-67.8	-0.	152.2	558.0	89.8	3.9	1.000034
57000.0	87.5	-67.6	-0.	148.3	558.3	96.8	4.0	1.000033
57500.0	85.3	-67.4	-0.	144.4	558.6	102.3	4.5	1.000032
58000.0	83.2	-67.1	-0.	140.7	558.9	105.9	5.5	1.000031
58500.0	81.1	-66.9	-0.	137.1	559.1	112.1	6.3	1.000030
59000.0	79.1	-66.7	-0.	133.5	559.4	131.5	6.4	1.000029
59500.0	77.2	-66.5	-0.	130.1	559.7	151.0	6.6	1.000028
60000.0	75.3	-66.1	-0.	126.6	560.3	159.6	5.4	1.000027
60500.0	73.4	-65.4	-0.	123.1	561.3	167.1	4.0	1.000026
61000.0	71.6	-64.6	-0.	119.7	562.3	187.9	2.8	1.000025
61500.0	69.9	-63.9	-0.	116.4	563.3	211.4	1.5	1.000024
62000.0	68.2	-63.1	-0.	113.2	564.3	290.4	1.1	1.000023
62500.0	66.6	-62.4	-0.	110.0	565.3	17.3	1.0	1.000022
63000.0	64.9	-61.6	-0.	107.0	566.3	56.1	1.0	1.000021

18

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO. 836

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
63500.0	63.4	-60.9	0.	-0.	104.0	567.3	90.5	1.0	1.000023
64000.0	61.8	-60.1	0.	-0.	101.1	568.3	100.8	1.3	1.000023
64500.0	60.3	-59.4	0.	-0.	98.3	569.3	109.0	1.7	1.000022
65000.0	58.9	-58.7	0.	-0.	95.7	570.2	87.9	2.3	1.000021
65500.0	57.5	-59.0	0.	-0.	93.5	569.8	61.1	2.9	1.000021
66000.0	56.1	-59.3	0.	-0.	91.4	569.4	57.0	3.6	1.000020
66500.0	54.8	-59.6	0.	-0.	89.3	569.0	64.0	4.2	1.000020
67000.0	53.5	-59.4	0.	-0.	87.1	569.3	77.4	3.9	1.000019
67500.0	52.2	-58.5	0.	-0.	84.7	570.5	97.5	2.8	1.000019
68000.0	50.9	-57.6	0.	-0.	82.3	571.7	122.9	2.1	1.000018
68500.0	49.7	-56.7	0.	-0.	80.1	572.9	160.2	2.0	1.000018
69000.0	48.6	-55.7	0.	-0.	77.8	574.1	197.6	1.9	1.000017
69500.0	47.4	-55.2	0.	-0.	75.8	574.8	216.3	2.5	1.000017
70000.0	46.3	-55.1	0.	-0.	74.0	575.0	230.4	3.1	1.000016
70500.0	45.2	-54.9	0.	-0.	72.2	575.2	244.5	3.8	1.000016
71000.0	44.2	-54.7	0.	-0.	70.5	575.4	264.4	3.3	1.000016
71500.0	43.2	-54.6	0.	-0.	68.8	575.6	284.6	2.7	1.000015
72000.0	42.1	-54.4	0.	-0.	67.1	575.9	299.4	2.2	1.000015
72500.0	41.2	-54.3	0.	-0.	65.5	576.1	272.5	1.6	1.000015
73000.0	40.2	-54.1	0.	-0.	63.9	576.3	245.7	1.0	1.000014
73500.0	39.3	-54.0	0.	-0.	62.4	576.5	235.7	0.6	1.000014
74000.0	38.3	-53.8	0.	-0.	60.9	576.7	272.9	1.1	1.000014
74500.0	37.5	-53.7	0.	-0.	59.4	576.9	310.1	1.6	1.000013
75000.0	36.6	-53.5	0.	-0.	58.0	577.1	334.0	2.4	1.000013
75500.0	35.7	-53.3	0.	-0.	56.6	577.3	339.0	3.7	1.000013
76000.0	34.9	-53.2	0.	-0.	55.3	577.5	343.9	4.9	1.000012
76500.0	34.1	-53.2	0.	-0.	54.0	577.4	351.9	6.4	1.000012
77000.0	33.3	-53.3	0.	-0.	52.8	577.4	1.7	7.9	1.000012
77500.0	32.5	-53.3	0.	-0.	51.5	577.3	11.5	9.4	1.000011
78000.0	31.8	-53.4	0.	-0.	50.4	577.2	19.9	9.8	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO. 836

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
78500.0	31.0	-53.4	0.	-0.	49.2	577.2	28.1	10.0	1.000011
79000.0	30.3	-53.5	0.	-0.	48.1	577.1	36.7	10.4	1.000011
79500.0	29.6	-53.5	0.	-0.	47.0	577.1	47.5	11.2	1.000010
80000.0	28.9	-53.5	0.	-0.	45.9	577.0	58.2	12.1	1.000010
80500.0	28.2	-53.6	0.	-0.	44.8	577.0	67.1	12.4	1.000010
81000.0	27.6	-53.2	0.	-0.	43.7	577.5	73.9	12.0	1.000010
81500.0	27.0	-52.6	0.	-0.	42.6	578.3	80.6	11.6	1.000009
82000.0	26.3	-51.9	0.	-0.	41.5	579.2	80.3	11.9	1.000009
82500.0	25.7	-51.3	0.	-0.	40.4	580.0	77.4	12.5	1.000009
83000.0	25.1	-50.6	0.	-0.	39.4	580.8	74.6	13.0	1.000009
83500.0	24.6	-50.0	0.	-0.	38.4	581.7	75.3	13.9	1.000009
84000.0	24.0	-49.4	0.	-0.	37.4	582.5	76.0	14.8	1.000008
84500.0	23.5	-48.7	0.	-0.	36.4	583.3	76.2	15.6	1.000008
85000.0	22.9	-48.2	0.	-0.	35.5	584.0	75.2	15.9	1.000008
85500.0	22.4	-48.1	0.	-0.	34.7	584.1	74.2	16.2	1.000008
86000.0	21.9	-48.0	0.	-0.	33.9	584.2	74.1	16.3	1.000008
86500.0	21.4	-48.0	0.	-0.	33.1	584.3	75.2	16.0	1.000007
87000.0	20.9	-47.9	0.	-0.	32.3	584.4	76.4	15.7	1.000007
87500.0	20.4	-47.8	0.	-0.	31.6	584.5	77.6	14.8	1.000007
88000.0	20.0	-47.8	0.	-0.	30.9	584.6	79.0	13.6	1.000007
88500.0	19.5	-47.7	0.	-0.	30.2	584.7	80.4	12.3	1.000007
89000.0	19.1	-47.6	0.	-0.	29.5	584.8	80.7	12.3	1.000007
89500.0	18.7	-47.5	0.	-0.	28.8	584.9	80.2	13.1	1.000006
90000.0	18.2	-47.5	0.	-0.	28.1	585.0	79.7	14.0	1.000006
90500.0	17.8	-47.4	0.	-0.	27.5	585.1	85.5	14.9	1.000006
91000.0	17.4	-47.3	0.	-0.	26.9	585.2	94.1	15.8	1.000006
91500.0	17.0	-47.2	0.	-0.	26.3	585.2	102.6	16.8	1.000006
92000.0	16.6	-47.2	0.	-0.	25.7	585.3	109.9	18.0	1.000006
92500.0	16.3	-47.1	0.	-0.	25.1	585.4	116.8	19.3	1.000006
93000.0	15.9	-47.0	0.	-0.	24.5	585.5	123.8	20.6	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO. 836

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII (Cont)

WSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
93500.0	15.5	-46.9	0.	-0.	23.9	585.6	130.3	20.2	1.000005
94000.0	15.2	-46.9	0.	-0.	23.4	585.7	136.7	19.5	1.000005
94500.0	14.8	-46.8	0.	-0.	22.8	585.8	143.2	18.9	1.000005
95000.0	14.5	-46.7	0.	-0.	22.3	585.9	152.0	17.2	1.000005
95500.0	14.2	-46.7	0.	-0.	21.8	586.0	160.8	15.5	1.000005
96000.0	13.9	-46.6	0.	-0.	21.3	586.1	169.8	13.7	1.000005
96500.0	13.5	-46.5	0.	-0.	20.8	586.2	180.1	10.9	1.000005
97000.0	13.2	-46.1	0.	-0.	20.3	586.8	190.4	8.0	1.000005
97500.0	13.0	-45.5	0.	-0.	19.8	587.4	202.2	5.8	1.000004
98000.0	12.7	-45.0	0.	-0.	19.3	588.1	222.8	7.0	1.000004
98500.0	12.4	-44.5	0.	-0.	18.9	588.8	243.4	8.2	1.000004
99000.0	12.1	-44.0	0.	-0.	18.4	589.4	263.7	9.4	1.000004
99500.0	11.8	-43.5	0.	-0.	18.0	590.1	277.5	9.4	1.000004
100000.0	11.6	-43.0	0.	-0.	17.5	590.7	291.2	9.5	1.000004
100500.0	11.3	-42.5	0.	-0.	17.1	591.4	305.0	9.6	1.000004
101000.0	11.1	-41.9	0.	-0.	16.7	592.1	312.6	9.7	1.000004
101500.0	10.8	-41.4	0.	-0.	16.3	592.7	314.0	10.0	1.000004
102000.0	10.6	-40.9	0.	-0.	15.9	593.4	315.4	10.2	1.000004
102500.0	10.4	-40.4	0.	-0.	15.5	594.0	316.8	10.5	1.000003
103000.0	10.1	-39.9	0.	-0.	15.1	594.7	317.9	9.6	1.000003
103500.0	9.9	-39.6	0.	-0.	14.8	595.1	318.8	8.1	1.000003
104000.0	9.7	-39.6	0.	-0.	14.4	595.1	319.8	6.6	1.000003
104500.0	9.5	-39.5	0.	-0.	14.1	595.2	320.7	5.1	1.000003
105000.0	9.3	-39.5	0.	-0.	13.8	595.2	323.5	4.7	1.000003
105500.0	9.1	-39.5	0.	-0.	13.5	595.2	327.2	4.8	1.000003
106000.0	8.9	-39.4	0.	-0.	13.2	595.3	330.8	4.8	1.000003
106500.0	8.7	-39.4	0.	-0.	12.9	595.3	334.4	4.9	1.000003
107000.0	8.5	-39.4	0.	-0.	12.6	595.3	345.6	4.3	1.000003
107500.0	8.3	-39.3	0.	-0.	12.4	595.4	358.9	3.5	1.000003
108000.0	8.1	-39.3	0.	-0.	12.1	595.4	12.3	2.8	1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
 0284003905
 WHITE SANDS SITE
 TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
 25 OCT. 66 1320 HRS MST
 ASCENSION NO. 836

HSTM SITE COORDINATES
 E 488,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT				DIRECTION DEGREES(TM)	SPEED KNOTS	
103500.0	7.9	-39.3	0.	**	11.8	595.5	25.6	2.0	1.000003
109000.0	7.8	-39.3	0.	**	11.6	595.5	57.7	2.1	1.000003
109500.0	7.6	-39.2	0.	**	11.3	595.5	93.3	2.4	1.000003
110000.0	7.4	-39.2	0.	**	11.1	595.6	128.9	2.6	1.000002
110500.0	7.3	-39.2	0.	**	10.8	595.6	164.6	2.9	1.000002
111000.0	7.1	-39.1	0.	**	10.6	595.7			1.000002
111500.0	7.0	-39.1	0.	**	10.4	595.7			1.000002
112000.0	6.8	-39.1	0.	**	10.1	595.7			1.000002
112500.0	6.7	-39.0	0.	**	9.9	595.8			1.000002
113000.0	6.5	-39.0	0.	**	9.7	595.8			1.000002
113500.0	6.4	-39.0	0.	**	9.5	595.8			1.000002
114000.0	6.2	-39.0	0.	**	9.3	595.9			1.000002
114500.0	6.1	-38.9	0.	**	9.1	595.9			1.000002

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

RELEASE TIME (MST)	SECOND-STAGE IMPACT DISPLACEMENT IN MILES DUE TO WIND												AZI- MUTH (DEG- DEES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)					
	RAWIN- SONDE	PIBAL	11-216 FT				216-4000 FT				4000-73497 FT				TOTAL	RANGE	N-S	E-W	
			N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W							
1035	1150	0.0	1.5E	3.2N	1.7E	3.5N	0.8E	6.7N	4.0E	358.3	69.4	69.4N	2.1W						
1035	1220	0.4N	0.9E	3.7N	0.7E	3.5N	0.8E	7.6N	2.4E	357.0	71.1	71.0N	3.7W						
1035	1235	1.9N	0.0	3.5N	1.6E	3.5N	0.8E	8.9N	2.4E	357.0	72.4	72.3N	3.7W						
1035	1250	0.6N	0.7E	1.9N	1.6E	3.5N	0.8E	6.0N	3.1E	357.5	69.5	69.4N	3.0W						
1035	1300	0.6N	1.1E	2.3N	2.3E	3.5N	0.8E	6.4N	4.2E	358.4	69.8	69.8N	1.9W						
1035	1310	0.9N	3.2E	0.5N	1.6E	3.5N	0.8E	4.9N	5.6E	359.6	68.3	68.3N	0.5W						
1035	1320	0.4S	2.1E	0.8S	1.2E	3.5N	0.8E	2.3N	4.1E	358.3	65.7	65.7N	2.0W						
*1320	*1320	0.4S	2.1E	0.8S	1.2E	3.7N	1.0E	2.5N	4.3E	358.4	65.9	65.9N	1.8W						

* Post-Shoot Data

LAUNCHER SETTING (ELEVATION 85.5 DEGREES QR) NO WIND IMPACT PREDICTED SECOND-STAGE IMPACT SECOND-STAGE IMPACT, RADAR TRACK PREDICTED BOOSTER IMPACT ACTUAL BOOSTER IMPACT	AZIMUTH (DEG- DEES)	MILES FROM LAUNCHER		
		RANGE	N-S	E-W
	358.9	63.4	63.4N	1.2W
	353.4	63.6	63.4N	6.1W
	357.6	70.0	69.9N	2.9W
	356.5	68.0	67.9N	4.2W
	358.5	0.9	0.9N	0.0
	N/A	N/A	N/A	N/A

TABLE VIII. IMPACT PREDICTION DATA
NIKE-HYDAC STV (SR-041)

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing classification must be entered when the overall report is classified)</i>		
1. ORIGINATOR'S ACTIVITY (Corporate symbol) U. S. Army Electronics Command Fort Monmouth, New Jersey		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED
		2b. GROUP
3. REPORT TITLE METEOROLOGICAL DATA REPORT, NIKE-HYDAC STV (SR-041)		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial) CARTER, Len E.		
6. REPORT DATE November 1966	7a. TOTAL NO. OF PAGES 23	7b. NO. OF REFS None
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S) DR-116	
a. PROJECT NO. c. DA Task IV650212A127-02 d.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY U. S. Army Electronics Command Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico	
13. ABSTRACT Meteorological data gathered for the launching of Nike-Hydac STV (SR-041) are presented for the Ballistic Systems Division of the U. S. Air Force, Avco Corporation and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.		

DD FORM 1473
1 JAN 64

UNCLASSIFIED

Security Classification

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Ballistics 2. Meteorology 3. Wind						

DEFINITIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive S200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show this classification in all capitals in parentheses immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system number, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. _____ qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, rules, and weights is optional.