

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED.

DR-155
FEBRUARY 1967

AD

807280

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV (SR-46 and 47)
(24 January 1967)

BY

JOHN M. SHARPE

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

.....
ECOM

UNITED STATES ARMY ELECTRONICS COMMAND

METEOROLOGICAL DATA REPORT

**NIKE-HYDAC STV (SR 46 and 47)
(24 January 1967)**

By

John M. Sharpe

DR-155

February 1967

DA Task IV650212A127-02

**ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO**

Distribution of this document is unlimited.

ABSTRACT

Meteorological data gathered for the launching of two (2) Nike-Hydrac STV (SR 46 and 47) are presented for the Ballistic Systems Division, U.S. Air Force and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

CONTENTS

	PAGE
ABSTRACT -----	111
INTRODUCTION -----	1
DISCUSSION -----	1
TABLES	
I. Theoretical Rocket Performance Values -----	2
II. Ballistic Factors -----	3
III. Anemometer-Wind Speed and Direction -----	4
IV. Pilot-Balloon-Measured Wind Data -----	6
V. Rawinsonde Measured Wind Data -----	9
VI. Computer-Calculated Upper Air Data (Release Time: 0840 MST) -----	10
VII. Computer-Calculated Upper Air Data (Release Time: 1100 MST) -----	17
VIII. Impact Prediction Data (SR-46) -----	24
IX. Impact Prediction Data (SR-47) -----	25

INTRODUCTION

Two Nike-Hydac STV (SR-46 and 47) were launched from Launch Complex 33/L-314 White Sands Missile Range (WSMR), New Mexico on 24 January 1967.

Nike-Hydac STV (SR-46) was launched at 1100 MST.

Nike-Hydac STV (SR-47) was launched at 1329 MST.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Division, Atmospheric Sciences Laboratory (ASL), WSMR, New Mexico. The Ballistics Meteorologists for this firing were John M. Sharpe and SFC Glen E. Hudson.

DISCUSSION

Wind data for the first 216 feet above the surface were obtained from a system composed of 5 Aerovanes mounted on a 200-foot tower and cabled to component wind indicators.

From 216 to 4000 feet above the surface, wind data were obtained from T-9 RADAR observed balloon ascents.

Temperature, pressure and humidity data, along with upper wind data from 4000 to 100,000 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic zone were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and ballistic factors as a function of altitude were provided by ASL and are the basis for data appearing in Tables VIII and IX.

PAYLOAD		233.0	Pounds
CORLIOLIS DISPLACEMENT	WEST	4.9	MILES
SECOND-STAGE IGNITION	TIME	20.0	Seconds
	ALTITUDE	36,691	Feet NSL
PEAK	TIME	232.0	Seconds
	ALTITUDE	693,948	Feet NSL
UNIT WIND EFFECT	HEAD	2.3815	MILES/MPH
	GROSS	2.4678	MILES/MPH
	TAIL	2.3815	MILES/MPH
TOWER TILT EFFECT		13.83	Miles/Degree

TABLE I. THEORETICAL ROCKET PERFORMANCE VALUES

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
11- 60	.1440
60- 108	.0966
108- 148	.0629
148- 184	.0502
184- 216	.0286
216- 300	.0724
300- 400	.0533
400- 600	.0752
600- 800	.0537
800-1000	.0400

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
1000- 1400	.0535
1400- 2000	.0575
2000- 2500	.0288
2500- 3000	.0195
3000- 3500	.0112
3500- 4000	.0073
4000- 4253	.0012
4253- 8000	.0135
8000-15000	.0147
15000-21000	.0166

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
21000-26000	.0102
26000-32691	.0110
32691-54000	.0430
34000-36000	.0411
36000-41000	.0343
41000-46000	.0259
46000-51000	.0154
51000-56000	.0092
56000-61000	.0060
61000-66000	.0040
66000-72168	.0030

TABLE II. BALLISTIC FACTORS

AERO- VANE NO. #	MEAN WIND COMPONENTS IN MILES PER HOUR													
	1		2		3		4		5		6		7	
	0900 MST		0920 MST		0930 MST		1000 MST		1015 MST		1030 MST		1040 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	12.0N	0.0	12.0N	6.0E	12.0N	4.0E	12.0N	4.0E	12.0N	6.0E	4.0N	0.0	2.0N	4.0E
2	14.0	2.0E	16.0	8.0	16.0	4.0	12.0	4.0	8.0	6.0	4.0	0.0	2.0	4.0
3	14.0	4.0	18.0	8.0	18.0	4.0	14.0	4.0	8.0	6.0	4.0	0.0	2.0	4.0
4	18.0	4.0	18.0	4.0	20.0	4.0	18.0	4.0	8.0	6.0	6.0	0.0	2.0	4.0
5	20.0	0.0	22.0	0.0	20.0	2.0	18.0	2.0	10.0	2.0	10.0	0.0	4.0	2.0

MEAN WIND COMPONENTS IN MILES PER HOUR														
AERO- VANE NO. #	8 1050 MST		9 1100 MST		10 1145 MST		11 1215 MST		12 1230 MST		13 1245 MST		14 1255 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	0.0	0.0	0.0	0.0	0.0	0.0	2.08	0.0	6.08	2.08	7.08	3.08	6.08	2.08
2	0.0	0.0	0.0	0.0	0.0	0.0	2.0	0.0	6.0	2.0	7.0	3.0	6.0	2.0
3	0.0	0.0	0.0	0.0	0.0	0.0	2.0	0.0	6.0	2.0	9.0	5.0	6.0	2.0
4	0.0	0.0	0.0	0.0	0.0	0.0	2.0	0.0	6.0	2.0	10.0	4.0	6.0	2.0
5	0.0	0.0	0.0	0.0	0.0	0.0	2.0	0.0	6.0	0.0	7.0	1.0	2.0	2.0

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION

Heights corresponding to Aereane Number:

18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539

18 19
20 21
22 23
24 25
26 27
28 29
30 31
32 33
34 35
36 37
38 39
40 41
42 43
44 45
46 47
48 49
50 51
52 53
54 55
56 57
58 59
60 61
62 63
64 65
66 67
68 69
70 71
72 73
74 75
76 77
78 79
80 81
82 83
84 85
86 87
88 89
90 91
92 93
94 95
96 97
98 99
100 101
102 103
104 105
106 107
108 109
110 111
112 113
114 115
116 117
118 119
120 121
122 123
124 125
126 127
128 129
130 131
132 133
134 135
136 137
138 139
140 141
142 143
144 145
146 147
148 149
150 151
152 153
154 155
156 157
158 159
160 161
162 163
164 165
166 167
168 169
170 171
172 173
174 175
176 177
178 179
180 181
182 183
184 185
186 187
188 189
190 191
192 193
194 195
196 197
198 199
200 201
202 203
204 205
206 207
208 209
210 211
212 213
214 215
216 217
218 219
220 221
222 223
224 225
226 227
228 229
230 231
232 233
234 235
236 237
238 239
240 241
242 243
244 245
246 247
248 249
250 251
252 253
254 255
256 257
258 259
260 261
262 263
264 265
266 267
268 269
270 271
272 273
274 275
276 277
278 279
280 281
282 283
284 285
286 287
288 289
290 291
292 293
294 295
296 297
298 299
300 301
302 303
304 305
306 307
308 309
310 311
312 313
314 315
316 317
318 319
320 321
322 323
324 325
326 327
328 329
330 331
332 333
334 335
336 337
338 339
340 341
342 343
344 345
346 347
348 349
350 351
352 353
354 355
356 357
358 359
360 361
362 363
364 365
366 367
368 369
370 371
372 373
374 375
376 377
378 379
380 381
382 383
384 385
386 387
388 389
390 391
392 393
394 395
396 397
398 399
399 400
400 401
401 402
402 403
403 404
404 405
405 406
406 407
407 408
408 409
409 410
410 411
411 412
412 413
413 414
414 415
415 416
416 417
417 418
418 419
419 420
420 421
421 422
422 423
423 424
424 425
425 426
426 427
427 428
428 429
429 430
430 431
431 432
432 433
433 434
434 435
435 436
436 437
437 438
438 439
439 440
440 441
441 442
442 443
443 444
444 445
445 446
446 447
447 448
448 449
449 450
450 451
451 452
452 453
453 454
454 455
455 456
456 457
457 458
458 459
459 460
460 461
461 462
462 463
463 464
464 465
465 466
466 467
467 468
468 469
469 470
470 471
471 472
472 473
473 474
474 475
475 476
476 477
477 478
478 479
479 480
480 481
481 482
482 483
483 484
484 485
485 486
486 487
487 488
488 489
489 490
490 491
491 492
492 493
493 494
494 495
495 496
496 497
497 498
498 499
499 500
500 501
501 502
502 503
503 504
504 505
505 506
506 507
507 508
508 509
509 510
510 511
511 512
512 513
513 514
514 515
515 516
516 517
517 518
518 519
519 520
520 521
521 522
522 523
523 524
524 525
525 526
526 527
527 528
528 529
529 530
530 531
531 532
532 533
533 534
534 535
535 536
536 537
537 538
538 539
539 540
540 541
541 542
542 543
543 544
544 545
545 546
546 547
547 548
548 549
549 550
550 551
551 552
552 553
553 554
554 555
555 556
556 557
557 558
558 559
559 560
560 561
561 562
562 563
563 564
564 565
565 566
566 567
567 568
568 569
569 570
570 571
571 572
572 573
573 574
574 575
575 576
576 577
577 578
578 579
579 580
580 581
581 582
582 583
583 584
584 585
585 586
586 587
587 588
588 589
589 590
590 591
591 592
592 593
593 594
594 595
595 596
596 597
597 598
598 599
599 600
600 601
601 602
602 603
603 604
604 605
605 606
606 607
607 608
608 609
609 610
610 611
611 612
612 613
613 614
614 615
615 616
616 617
617 618
618 619
619 620
620 621
621 622
622 623
623 624
624 625
625 626
626 627
627 628
628 629
629 630
630 631
631 632
632 633
633 634
634 635
635 636
636 637
637 638
638 639
639 640
640 641
641 642
642 643
643 644
644 645
645 646
646 647
647 648
648 649
649 650
650 651
651 652
652 653
653 654
654 655
655 656
656 657
657 658
658 659
659 660
660 661
661 662
662 663
663 664
664 665
665 666
666 667
667 668
668 669
669 670
670 671
671 672

21 128 Feet
22 168 Feet

21 128 Feet
22 168 Feet

9087 003 - 5

AERO- VANE NO. #	MEAN WIND COMPONENTS IN MILES PER HOUR											
	15		16		17		18		MST		MST	
	1305 MST		1315 MST		1320 MST		1329 MST					
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	3.08	2.08	6.08	4.08	8.08	6.08	2.08	2.08				
2	3.0	2.0	6.0	4.0	8.0	6.0	4.0	4.0				
3	4.0	2.0	6.0	4.0	8.0	6.0	4.0	4.0				
4	4.0	2.0	6.0	4.0	8.0	6.0	4.0	4.0				
5	2.0	2.0W	6.0	2.0	8.0	4.0	4.0	4.0				

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION, (Cont)

* Heights corresponding to Aerovane Numbers: 1 = 35 Feet 3 = 120 Feet 5 = 200 Feet
2 = 80 Feet 4 = 160 Feet

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR											
	1		2		3		4		5		6	
	0900 MST		0915 MST		0930 MST		1000 MST		1015 MST		1030 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	19.0N	0.5E	22.0N	3.0E	20.0N	1.5E	16.0N	3.5E	11.0N	5.5E	8.0N	0.0
300- 400	18.0	1.5	21.0	4.0	21.0	0.0	11.0	6.0	10.0	11.0	8.0	1.5E
400- 600	17.0	2.0	24.0	7.0	22.0	1.5E	14.0	9.0	13.0	13.0	10.0	5.0
600- 800	16.0	3.5	20.0	5.0	16.0	4.0	19.0	7.0	8.5	8.0	8.0	6.0
800-1000	17.0	4.0	18.0	2.0	8.0	3.0	15.0	2.0	4.0	3.5W	6.0	7.0
1000-1400	14.0	3.0W	9.0	3.0W	6.0	4.0	6.0	3.0W	4.0	7.0	7.0	3.0W
1400-2000	16.0	15.0	14.0	15.0	6.0	10.0W	2.0	9.0	4.0	13.5	6.0	12.0
2000-2500	11.0	25.0	12.0	24.0	6.0	23.0	6.0	13.0	2.0	23.0	5.0	20.0
2500-3000	0.0	26.0	2.0E	31.0	0.0	28.0	2.0	24.0	4.0	30.0	2.0	25.0
3000-3500	2.0E	28.0	1.0	33.0	2.0E	30.0	3.0E	30.0	2.0	30.0	1.0E	29.0
3500-4000	0.0	34.0	6.0	30.0	4.0	35.0	6.0	31.0	0.0	32.0	3.0	34.0
											4.5N	2.5E
											3.0	3.0
											2.5	4.5
											3.0	4.0
											7.0	5.0
											6.0	6.0
											4.0	8.0W
											8.0	17.0
											4.0	30.0
											3.0E	29.0
											6.0	31.0

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA
NIKE-HYDAC STV (SR-46)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR													
	8		9		10		11		12		13		14	
	1050 MST		1100 MST		1145 MST		1215 MST		1230 MST		1245 MST		1255 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	1.0N	2.0E	2.0S	3.0E	2.5S	0.0	3.0S	1.0W	4.0S	2.0W	8.0S	1.0E	3.0S	1.5E
300- 400	0.0	2.0	3.0	5.0	6.0	3.0E	5.0	2.0	3.0	1.5	8.0	2.0	5.0	5.0
400- 600	2.0N	3.0	2.0	4.0	8.0	2.0	5.0	1.0	3.0	1.0	7.0	5.0	5.0	5.0
600- 800	0.0	4.0	0.0	4.0	6.0	3.0	5.0	1.0	4.0	0.0	6.0	6.0	5.0	5.0
800-1000	1.0S	2.0	1.0N	5.0	4.0	2.0	4.0	1.0	5.0	1.0W	4.0	6.0	3.0	3.0
1000-1100	4.0N	2.0	0.0	4.0	3.0	0.0	4.0	3.0	3.0	2.0	3.0	0.0	0.0	2.0W
1100-2000	2.0	4.0W	0.0	3.0W	4.0N	6.0W	1.0	4.0	0.5W	9.0	1.0	0.0	3.0N	7.0
2000-2500	2.0S	10.0	2.0S	11.5	6.0	15.0	2.0N	11.0	0.0	13.0	2.0N	5.0W	4.0	7.0
2500-3000	0.0	17.5	3.0	17.0	6.0	21.0	5.0	16.0	4.0N	20.0	6.0	14.0	5.0	10.0
3000-3500	3.0N	31.0	4.0N	28.0	0.0	20.0	4.0	22.0	4.0	20.0	0.0	14.0	1.0	20.0
3500-4000	0.0	26.0	2.0	30.0	3.0S	26.0	0.0	24.0	4.0	22.0	0.5W	28.0	1.0S	24.0

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA, (Cont)
NIFE-HYDAC STV (SR-16 and SR-47)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR									
	15 1305 MST		16 1315 MST		17 1320 MST		18 1330 MST		19 1345 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	2.5S	4.0E	5.0S	2.5E	4.5N	5.0E	4.5S	4.5E		
300- 400	4.0	9.0	3.0	3.0	0.0	4.5	4.5	5.5		
400- 600	6.0	8.0	4.0	6.0	1.0S	3.0	5.0	6.0		
600- 800	8.0	4.0	3.0	6.0	2.0N	3.0	4.0	4.5		
800-1000	9.0	7.0	2.0	7.0	1.0S	0.0	3.0	3.0		
1000-1400	8.0	2.0	4.0	4.0	1.5	0.0	1.0N	0.0		
1400-2000	1.0	0.0	1.0N	3.0W	2.0N	2.0W	0.0	0.0		
2000-2500	4.0N	3.0W	1.0	5.0	2.0	3.0	1.0S	4.0W		
2500-3000	1.0	8.0	3.0	10.0	0.0	6.0	2.0N	9.0		
3000-3500	0.0	20.0	7.0	17.0	0.0	20.0	1.0	16.0		
3500-4000	2.0S	30.0	6.0	33.0	1.0S	26.0	2.0S	23.0		

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA, (Cont)
NIKE-HYDAC STV (SR-47)

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS					
	1 0840 MST		2 1100 MST		3 * 1329 MST	
	N-S	E-W	N-S	E-W	N-S	E-W
4000-4253	0.0	30.0W	4.0S	22.5W	*	*
4253-9000	0.0	32.0	5.5	30.5		
9000-15000	8.0S	44.5	7.0	39.5		
15000-21000	7.0	38.5	7.0	40.5		
21000-26000	0.0	47.0	15.5	43.0		
26000-32691	11.0S	61.0	9.5	54.0		
32691-34000	0.0	45.0	10.0	57.0		
34000-36000	16.0S	44.0	18.5	50.5		
36000-41000	18.0	50.0	19.5	53.5		
41000-46000	14.0	38.5	19.5	53.5		
46000-51000	16.5	45.0	13.5	36.5		
51000-56000	15.5	43.0	19.5	34.0		
56000-61000	16.5	20.0	14.0	24.0		
61000-66000	7.0	8.5	7.5	12.0		
66000-74168	0.0	7.5	5.0N	8.5E		

TABLE V. RAWINSONDE-MEASURED WIND DATA

* - Balloon Burst Below 15,000 Feet MSL.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 0840 HRS MST
ASCENSION NO. 46

UPPER AIR DATA
0078003907
WHIWE SANDS SITE
TABLE VI

WSTM SITE COORDINATES
E 182.580 FEET
N 185.045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	881.0	5.3	-6.0	44.0	1100.5	650.3	30.0	8.0	1.000264
4000.0	880.6	5.3	-6.2	43.4	1100.1	650.3	29.4	8.0	1.000264
4500.0	864.4	5.8	-11.8	27.0	1078.7	650.6	3.8	11.8	1.000232
5000.0	848.5	6.6	-11.1	27.0	1053.4	651.7	338.1	15.6	1.000248
5500.0	832.7	5.9	-11.7	27.0	1038.5	650.8	312.4	19.3	1.000244
6000.0	817.3	5.0	-12.4	27.0	1022.5	649.8	286.7	23.1	1.000239
6500.0	802.1	4.2	-13.2	27.0	1006.7	648.8	279.5	25.6	1.000235
7000.0	787.2	3.3	-14.0	27.0	991.2	647.7	274.3	27.8	1.000231
7500.0	772.6	2.4	-14.7	27.0	975.9	646.7	271.6	29.0	1.000227
8000.0	758.3	2.0	-15.4	26.4	959.4	646.1	269.1	30.2	1.000223
8500.0	744.1	2.6	-16.0	24.0	939.5	646.9	266.9	31.4	1.000218
9000.0	730.2	2.4	-16.3	23.7	922.3	646.7	265.3	31.4	1.000214
9500.0	716.4	1.6	-16.4	25.0	907.7	645.7	265.2	30.4	1.000211
10000.0	703.0	0.8	-16.5	26.2	893.3	644.7	265.4	29.3	1.000208
10500.0	689.7	-0.1	-16.7	27.5	879.2	643.8	267.6	30.0	1.000204
11000.0	676.8	-0.9	-16.9	28.7	865.3	642.8	269.7	30.7	1.000201
11500.0	664.0	-1.7	-17.1	30.0	851.6	641.8	271.2	33.3	1.000198
12000.0	651.5	-2.4	-17.3	30.9	837.6	641.0	272.4	36.1	1.000195
12500.0	639.1	-2.4	-17.5	30.4	821.7	641.0	270.2	40.1	1.000191
13000.0	627.0	-2.6	-17.9	29.9	806.6	640.8	268.0	43.4	1.000187
13500.0	614.8	-3.7	-19.1	29.5	794.4	639.4	265.8	45.5	1.000184
14000.0	602.9	-4.9	-20.2	29.0	782.3	638.0	264.0	45.6	1.000181
14500.0	591.1	-6.0	-21.4	28.5	770.4	636.7	262.5	44.5	1.000177
15000.0	579.7	-7.1	-22.6	28.0	758.7	635.3	262.3	44.5	1.000174
15500.0	568.4	-8.3	-23.8	27.6	747.2	633.9	262.3	44.7	1.000171
16000.0	557.4	-9.4	-25.0	27.1	735.8	632.6	262.4	45.3	1.000168
16500.0	546.5	-10.5	-26.1	26.6	724.7	631.2	262.4	45.6	1.000165
17000.0	535.9	-11.6	-27.3	26.1	713.7	629.8	261.8	46.2	1.000163
17500.0	525.5	-12.8	-28.5	25.7	702.9	628.4	261.3	46.5	1.000160
18000.0	515.3	-13.9	-29.7	25.2	692.3	627.1	261.5	47.2	1.000157

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 0840 HRS MST
ASCENSION NO. 46

UPPER AIR DATA
0078003907
WHITE SANDS SITE
TABLE VI (Cont)

UPPER AIR DATA
0078003907
WHITE SANDS SITE
TABLE VI (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES C	TEMPERATURE DEWPOINT C	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
18500.0	505.2	-14.9	-30.3	25.7	681.3	625.8	261.6	47.7	1.000155
19000.0	495.1	-15.8	-30.6	27.0	670.1	624.7	261.0	46.3	1.000152
19500.0	485.2	-16.7	-30.9	28.3	659.0	623.6	261.0	44.9	1.000149
20000.0	475.3	-17.8	-31.6	29.0	648.3	622.3	262.1	43.5	1.000147
20500.0	465.3	-19.1	-32.7	29.1	637.9	620.8	262.9	41.3	1.000144
21000.0	455.6	-20.4	-33.8	29.2	627.8	619.2	263.3	38.4	1.000142
21500.0	446.1	-21.6	-34.9	29.2	617.8	617.6	264.7	36.9	1.000139
22000.0	436.8	-22.9	-36.1	29.3	608.0	616.0	266.7	36.2	1.000137
22500.0	427.6	-24.2	-37.2	29.3	598.3	614.5	268.8	35.9	1.000135
23000.0	418.7	-25.5	-38.3	29.4	588.9	612.9	270.8	35.8	1.000133
23500.0	410.0	-26.7	-39.4	29.5	579.6	611.3	271.4	37.2	1.000130
24000.0	401.4	-28.0	-40.5	29.5	570.4	609.7	271.7	39.0	1.000128
24500.0	393.0	-29.3	-41.6	29.6	561.4	608.1	271.1	41.6	1.000126
25000.0	384.8	-30.6	-42.8	29.7	552.6	606.5	270.1	44.4	1.000124
25500.0	376.7	-31.9	-43.9	29.7	543.9	604.9	268.5	46.9	1.000122
26000.0	368.9	-33.1	-45.0	29.8	535.4	603.3	266.3	49.0	1.000120
26500.0	361.1	-34.4	-46.1	29.8	527.0	601.7	264.5	50.5	1.000118
27000.0	353.6	-35.7	-47.2	29.9	518.8	600.1	264.1	50.2	1.000116
27500.0	346.2	-37.0	-48.4	30.0	510.7	598.4	263.7	49.9	1.000114
28000.0	338.6	-38.2	-50.1	28.1**	502.5	596.8	262.4	48.6	1.000112
28500.0	331.3	-39.6	-52.7	23.5**	494.1	595.1	261.2	47.4	1.000110
29000.0	323.9	-40.9	-55.6	19.0**	485.8	593.5	260.2	46.6	1.000108
29500.0	316.7	-42.2	-58.9	14.4**	477.7	591.8	259.3	46.0	1.000107
30000.0	309.7	-43.5	-62.9	9.9**	469.8	590.1	259.3	48.4	1.000105
30500.0	302.8	-44.8	-68.4	5.3**	462.0	588.4	259.6	51.7	1.000103
31000.0	296.1	-46.1	-81.9	0.8**	454.3	586.7	260.1	54.0	1.000101
31500.0	289.3	-47.3	0.	-0. **	446.3	585.1	260.8	56.1	1.000099
32000.0	282.6	-48.6	0.	-0. **	438.4	583.5	262.8	59.6	1.000098
32500.0	276.1	-49.8	0.	-0. **	430.6	582.0	264.4	62.6	1.000096
33000.0	269.7	-51.0	0.	-0. **	423.0	580.4	263.9	62.1	1.000094

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 0840 HRS MST
ASCENSION NO. 46

UPPER AIR DATA
0078003907
WHITE SANDS SITE
TABLE VI (Cont)

WSEN SITE COORDINATES
E 488,560 FEET
N 183,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
33500.0	263.4	-52.2	0.	-0. **	415.5	578.7	263.6	63.7	1.000093
34000.0	257.3	-53.5	0.	-0. **	408.1	577.1	263.6	69.1	1.000091
34500.0	251.4	-54.7	0.	-0. **	400.9	575.5	263.3	70.5	1.000089
35000.0	245.6	-55.9	0.	-0. **	393.9	573.9	262.8	67.7	1.000088
35500.0	239.9	-57.1	0.	-0. **	386.8	572.4	263.6	65.7	1.000086
36000.0	234.2	-58.0	0.	-0. **	379.2	571.2	265.1	64.0	1.000084
36500.0	228.6	-58.9	0.	-0. **	371.7	569.9	266.0	54.7	1.000083
37000.0	223.1	-57.5	0.	-0. **	360.6	571.7	266.8	49.3	1.000080
37500.0	217.8	-58.2	0.	-0. **	353.0	570.8	265.1	48.4	1.000079
38000.0	212.5	-59.0	0.	-0. **	345.8	569.8	263.5	47.5	1.000077
38500.0	207.4	-59.8	0.	-0. **	338.6	568.8	258.2	47.9	1.000075
39000.0	202.4	-60.5	0.	-0. **	331.7	567.8	252.9	48.3	1.000074
39500.0	197.5	-61.3	0.	-0. **	324.8	566.8	247.2	49.9	1.000072
40000.0	192.8	-62.0	0.	-0. **	318.2	565.7	241.5	51.8	1.000071
40500.0	188.1	-62.8	0.	-0. **	311.6	564.7	239.7	52.7	1.000069
41000.0	183.6	-63.5	0.	-0. **	305.1	563.8	238.9	53.4	1.000068
41500.0	179.1	-63.5	0.	-0. **	297.7	563.8	240.9	53.4	1.000066
42000.0	174.7	-63.5	0.	-0. **	290.4	563.8	244.1	53.3	1.000065
42500.0	170.5	-63.4	0.	-0. **	283.2	563.9	248.7	52.0	1.000063
43000.0	166.3	-62.9	0.	-0. **	275.6	564.6	254.1	50.0	1.000061
43500.0	162.3	-62.4	0.	-0. **	268.3	565.3	255.8	45.6	1.000060
44000.0	158.3	-62.3	0.	-0. **	261.6	565.4	255.2	39.7	1.000058
44500.0	154.5	-62.2	0.	-0. **	255.2	565.6	251.7	38.5	1.000057
45000.0	150.8	-62.1	0.	-0. **	248.9	565.6	247.3	38.9	1.000055
45500.0	147.1	-62.6	0.	-0. **	243.4	565.0	244.9	42.4	1.000054
46000.0	143.5	-63.1	0.	-0. **	238.1	564.3	243.0	44.4	1.000053
46500.0	140.0	-63.4	0.	-0. **	232.6	563.9	245.2	48.8	1.000052
47000.0	136.6	-63.0	0.	-0. **	226.5	564.4	249.4	53.9	1.000050
47500.0	133.3	-62.7	0.	-0. **	220.7	564.9	253.0	56.5	1.000049
48000.0	130.1	-62.3	0.	-0. **	214.9	565.4	255.7	54.7	1.000048

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0078003907
WHITE SANDS SITE
TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 0840 HRS MST
ASCENSION NO. 46

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL-HUM. PERCENT	DENSITY GM/CUBIC MEYER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
48500.0	126.9	-61.9	0.	-0. **	209.3	565.9	258.2	258.2	52.9	1.000047
49000.0	123.8	-61.5	0.	-0. **	203.9	566.4	258.5	258.5	51.3	1.000045
49500.0	120.8	-61.2	0.	-0. **	198.7	566.9	258.8	258.8	49.9	1.000044
50000.0	117.9	-61.6	0.	-0. **	194.2	566.4	257.5	257.5	51.1	1.000043
50500.0	115.1	-61.9	0.	-0. **	189.8	565.9	256.3	256.3	52.4	1.000042
51000.0	112.3	-62.3	0.	-0. **	185.5	565.5	256.2	256.2	53.3	1.000041
51500.0	109.5	-62.6	0.	-0. **	181.3	565.0	256.2	256.2	54.2	1.000040
52000.0	106.9	-62.0	0.	-0. **	176.4	565.8	256.1	256.1	54.3	1.000039
52500.0	104.3	-60.7	0.	-0. **	171.1	567.6	255.9	255.9	54.0	1.000038
53000.0	101.8	-60.6	0.	-0. **	166.9	567.7	254.3	254.3	52.1	1.000037
53500.0	99.4	-60.5	0.	-0. **	162.8	567.8	250.6	250.6	47.6	1.000036
54000.0	97.0	-60.5	0.	-0. **	158.9	567.8	246.7	246.7	43.5	1.000035
54500.0	94.6	-60.4	0.	-0. **	155.0	567.9	242.3	242.3	43.5	1.000035
55000.0	92.4	-60.3	0.	-0. **	151.2	568.0	237.8	237.8	43.4	1.000034
55500.0	90.1	-60.4	0.	-0. **	147.6	568.0	236.9	236.9	43.5	1.000033
56000.0	88.0	-60.5	0.	-0. **	144.1	567.8	236.6	236.6	43.6	1.000032
56500.0	85.9	-60.6	0.	-0. **	140.8	567.6	239.3	239.3	44.9	1.000031
57000.0	83.8	-60.8	0.	-0. **	137.5	567.4	243.2	243.2	46.7	1.000031
57500.0	81.8	-60.9	0.	-0. **	134.2	567.2	246.5	246.5	47.1	1.000030
58000.0	79.8	-61.1	0.	-0. **	131.1	567.0	249.3	249.3	46.4	1.000029
58500.0	77.9	-61.2	0.	-0. **	128.0	566.8	250.8	250.8	43.7	1.000029
59000.0	76.0	-61.4	0.	-0. **	125.0	566.6	250.3	250.3	38.2	1.000028
59500.0	74.2	-61.5	0.	-0. **	122.1	566.4	248.9	248.9	33.7	1.000027
60000.0	72.4	-61.7	0.	-0. **	119.2	566.3	244.5	244.5	32.4	1.000027
60500.0	70.6	-61.6	0.	-0. **	116.4	566.3	239.8	239.8	30.8	1.000026
61000.0	68.9	-61.6	0.	-0. **	113.5	566.4	227.7	227.7	23.1	1.000025
61500.0	67.3	-61.5	0.	-0. **	110.7	566.5	215.6	215.6	15.4	1.000025
62000.0	65.6	-61.4	0.	-0. **	108.0	566.6	218.7	218.7	18.2	1.000024
62500.0	64.1	-61.4	0.	-0. **	105.4	566.6	224.2	224.2	22.8	1.000023
63000.0	62.5	-61.3	0.	-0. **	102.8	566.7	224.5	224.5	22.1	1.000023

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 0840 HRS MST
ASCENSION NO. 46

UPPER AIR DATA
0078003907
WHITE SANDS SITE
TABLE VI (Cont)

MSTM SITE COORDINATES
E 488,580 FEET
N 185,043 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KN/TS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES(TN)	SPEED KN/TS	
63500.0	61.0	-61.2	-0. **	100.3	566.8	222.4	16.8	1.000022
64000.0	59.5	-61.2	-0. **	97.9	566.9	217.9	14.9	1.000022
64500.0	58.1	-61.1	-0. **	95.5	567.0	210.7	10.1	1.000021
65000.0	56.7	-61.0	-0. **	93.2	567.1	203.4	5.4	1.000021
65500.0	55.3	-61.0	-0. **	90.9	567.2	158.9	9.2	1.000020
66000.0	54.0	-60.9	-0. **	88.7	567.3	114.5	13.0	1.000020
66500.0	52.7	-60.8	-0. **	86.5	567.4	82.9	19.5	1.000019
67000.0	51.4	-60.8	-0. **	84.4	567.5	80.3	32.2	1.000019
67500.0	50.2	-60.7	-0. **	82.3	567.6	77.6	44.8	1.000018
68000.0	49.0	-60.6	-0. **	80.3	567.7	71.8	41.0	1.000018
68500.0	47.8	-60.5	-0. **	78.4	567.7	64.1	26.8	1.000017
69000.0	46.7	-60.4	-0. **	76.4	567.9	56.4	12.6	1.000017
69500.0	45.6	-60.1	-0. **	74.5	568.4	4.1	14.7	1.000017
70000.0	44.5	-59.7	-0. **	72.6	568.8	306.9	18.7	1.000016
70500.0	43.5	-59.4	-0. **	70.8	569.3	258.5	23.9	1.000016
71000.0	42.4	-59.1	-0. **	69.1	569.7	259.6	36.7	1.000015
71500.0	41.4	-58.7	-0. **	67.3	570.2	260.7	49.4	1.000015
72000.0	40.5	-58.4	-0. **	65.6	570.6	260.1	53.0	1.000015
72500.0	39.5	-58.1	-0. **	64.0	571.1	257.0	42.6	1.000014
73000.0	38.6	-57.7	-0. **	62.4	571.5	253.8	32.1	1.000014
73500.0	37.7	-57.4	-0. **	60.8	572.0	295.5	24.0	1.000014
74000.0	36.8	-57.0	-0. **	59.3	572.4	358.9	17.1	1.000013
74500.0	35.9	-56.7	-0. **	57.8	572.9	61.6	10.3	1.000013
75000.0	35.1	-56.4	-0. **	56.4	573.3	68.0	11.7	1.000013
75500.0	34.2	-56.0	-0. **	55.0	573.7	74.4	13.2	1.000012
76000.0	33.4	-55.7	-0. **	53.6	574.2	80.4	13.0	1.000012
76500.0	32.7	-55.4	-0. **	52.2	574.6	85.5	10.1	1.000012
77000.0	31.9	-55.0	-0. **	50.9	575.1	90.7	7.2	1.000011
77500.0	31.1	-54.7	-0. **	49.7	575.5	136.8	6.1	1.000011
78000.0	30.4	-54.4	-0. **	48.4	576.0	199.6	5.8	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0078003907
WHITE SANDS SITE
TABLE VI (Cont)

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 0840 HRS MST
ASCENSION NO. 46

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
78500.0	29.7	-54.0	-0. **	47.2	576.4	258.1	5.5	1.000011
79000.0	29.0	-53.7	-0. **	46.0	576.8	251.6	5.3	1.000010
79500.0	28.3	-53.4	-0. **	44.9	577.3	245.0	5.1	1.000010
80000.0	27.6	-53.0	-0. **	43.8	577.7	252.3	4.5	1.000010
80500.0	27.0	-52.7	-0. **	42.7	578.2	279.4	3.3	1.000009
81000.0	26.4	-52.3	-0. **	41.6	578.6	306.4	2.1	1.000009
81500.0	25.7	-52.0	-0. **	40.6	579.0	345.3	5.4	1.000009
82000.0	25.1	-51.7	-0. **	39.5	579.5	27.8	10.0	1.000009
82500.0	24.6	-51.5	-0. **	38.6	579.7	66.5	14.4	1.000009
83000.0	24.0	-51.4	-0. **	37.7	579.8	63.6	15.6	1.000008
83500.0	23.4	-51.3	-0. **	36.8	579.9	60.8	16.9	1.000008
84000.0	22.9	-51.2	-0. **	36.0	580.0	60.5	17.7	1.000008
84500.0	22.4	-51.2	-0. **	35.1	580.2	64.3	17.9	1.000008
85000.0	21.9	-51.1	-0. **	34.3	580.3	68.1	18.0	1.000008
85500.0	21.4	-51.0	-0. **	33.5	580.4	70.5	18.2	1.000007
86000.0	20.9	-50.9	-0. **	32.7	580.5	72.3	18.3	1.000007
86500.0	20.4	-50.8	-0. **	31.9	580.6	74.1	18.4	1.000007
87000.0	19.9	-50.7	-0. **	31.2	580.8	74.4	18.7	1.000007
87500.0	19.5	-50.6	-0. **	30.5	580.9	74.5	19.1	1.000007
88000.0	19.0	-50.4	-0. **	29.8	581.1	74.4	19.9	1.000007
88500.0	18.6	-50.3	-0. **	29.1	581.3	73.7	22.4	1.000006
89000.0	18.2	-50.1	-0. **	28.4	581.5	73.0	24.8	1.000006
89500.0	17.8	-49.9	-0. **	27.7	581.8	72.3	25.3	1.000006
90000.0	17.3	-49.8	-0. **	27.1	582.0	71.6	22.9	1.000006
90500.0	17.0	-49.6	-0. **	26.4	582.2	70.9	20.5	1.000006
91000.0	16.6	-49.4	-0. **	25.8	582.4	71.7	21.0	1.000006
91500.0	16.2	-49.3	-0. **	25.2	582.6	73.6	23.7	1.000006
92000.0	15.8	-49.1	-0. **	24.6	582.8	75.5	26.3	1.000005
92500.0	15.5	-48.9	-0. **	24.0	583.1	76.8	25.7	1.000005
93000.0	15.1	-48.8	-0. **	23.5	583.3	77.8	24.1	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 0840 HRS MST
ASCENSION NO. 46

UPPER AIR DATA
0078003907
WHITE SANDS SITE
TABLE VI (Cont)

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE HILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
93500.0	14.6	-48.6	-0. **	22.9	583.5	78.9	22.5	1.000005
94000.0	14.4	-48.4	-0. **	22.4	583.7	79.0	22.8	1.000005
94500.0	14.1	-48.3	-0. **	21.9	583.9	79.0	23.2	1.000005
95000.0	13.8	-48.1	-0. **	21.3	584.1	79.2	23.4	1.000005
95500.0	13.5	-47.9	-0. **	20.8	584.3	80.7	21.3	1.000005
96000.0	13.2	-47.8	-0. **	20.4	584.6	82.2	19.2	1.000005
96500.0	12.9	-47.6	-0. **	19.9	584.8	83.3	17.8	1.000004
97000.0	12.6	-47.4	-0. **	19.4	585.0	83.2	18.2	1.000004
97500.0	12.3	-47.3	-0. **	19.0	585.2	83.2	18.5	1.000004
98000.0	12.0	-47.1	-0. **	18.5	585.4	83.3	18.0	1.000004
98500.0	11.7	-46.9	-0. **	18.1	585.6	83.8	16.2	1.000004
99000.0	11.5	-46.7	-0. **	17.7	586.0	84.3	14.5	1.000004
99500.0	11.2	-45.7	-0. **	17.2	587.2	83.4	13.2	1.000004
100000.0	11.0	-44.7	-0. **	16.7	588.5	81.4	12.2	1.000004
100500.0	10.7	-43.8	-0. **	16.3	589.7	79.5	11.2	1.000004
101000.0	10.5	-42.8	-0. **	15.9	591.0	74.8	11.6	1.000004
101500.0	10.3	-41.8	-0. **	15.4	592.3	68.9	12.5	1.000003
102000.0	10.0	-40.8	-0. **	15.0	593.5	63.1	13.4	1.000003
102500.0	9.8	-40.7	-0. **	14.7	593.6	61.6	14.4	1.000003
103000.0	9.6	-40.7	-0. **	14.4	593.6	61.1	15.5	1.000003
103500.0	9.4	-40.8	-0. **	14.1	593.6	60.7	16.5	1.000003
104000.0	9.2	-40.8	-0. **	13.8	593.5	59.6	18.0	1.000003
104500.0	9.0	-40.8	-0. **	13.5	593.5	58.5	19.5	1.000003
105000.0	8.8	-40.8	-0. **	13.2	593.5	57.4	21.1	1.000003
105500.0	8.6	-40.9	-0. **	12.9	593.4			1.000003
106000.0	8.4	-40.9	-0. **	12.6	593.4			1.000003
106500.0	8.2	-40.9	-0. **	12.3	593.4			1.000003
107000.0	8.0	-40.9	-0. **	12.1	593.4			1.000003
107500.0	7.9	-41.0	-0. **	11.8	593.3			1.000003
108000.0	7.7	-41.0	-0. **	11.5	593.3			1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 1100 HRS MSY
ASCENSION NO. 47

UPPER AIR DATA
0091003903
WHITE SANDS SITE
TABLE VII

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	881.7	10.2	-6.6	30.0	1082.4	656.0	160.0	160.0	4.1	1.000259
4000.0	881.3	10.2	-6.6	30.0	1082.1	655.9	160.5	160.5	4.1	1.000259
4500.0	865.2	8.7	-7.7	30.5	1068.0	654.2	182.3	182.3	6.0	1.000254
5000.0	849.3	7.2	-8.8	31.1	1054.0	652.4	204.1	204.1	7.9	1.000250
5500.0	833.8	5.7	-9.9	31.6	1040.2	650.7	225.8	225.8	9.8	1.000246
6000.0	818.4	4.5	-10.9	31.7	1025.8	649.2	247.6	247.6	11.7	1.000242
6500.0	803.1	3.8	-11.9	30.9	1009.3	648.3	267.8	267.8	13.6	1.000237
7000.0	788.1	3.0	-12.9	30.1	993.2	647.5	266.2	266.2	17.1	1.000233
7500.0	773.4	2.3	-13.9	29.2	977.3	646.6	264.6	264.6	20.5	1.000228
8000.0	759.0	1.6	-14.8	28.4	961.6	645.7	262.2	262.2	23.9	1.000224
8500.0	744.8	0.9	-15.8	27.5	946.2	644.8	259.9	259.9	27.4	1.000220
9000.0	730.9	0.6	-16.6	26.3	929.3	644.6	257.5	257.5	28.9	1.000215
9500.0	717.2	1.3	-17.0	24.3	909.7	645.3	255.2	255.2	30.3	1.000211
10000.0	703.7	1.0	-17.0	24.8	893.6	645.0	256.7	256.7	30.5	1.000207
10500.0	690.5	0.5	-16.9	25.8	878.4	644.4	258.2	258.2	30.6	1.000204
11000.0	677.5	-0.5	-16.5	28.9	865.0	643.2	260.1	260.1	30.1	1.000201
11500.0	664.7	-1.6	-16.0	32.5	852.2	641.9	262.0	262.0	29.9	1.000199
12000.0	652.1	-1.4	-15.7	33.0	835.4	642.2	263.3	263.3	30.5	1.000195
12500.0	639.8	-1.2	-15.6	32.8	818.8	642.5	263.9	263.9	31.4	1.000192
13000.0	627.7	-1.8	-16.5	31.6	805.1	641.8	261.9	261.9	33.7	1.000188
13500.0	615.7	-2.6	-17.7	30.4	792.1	640.7	260.1	260.1	35.6	1.000184
14000.0	603.7	-3.8	-19.3	29.1	780.2	639.3	258.8	258.8	36.5	1.000181
14500.0	591.9	-5.0	-20.8	27.8	768.4	637.9	257.7	257.7	37.5	1.000177
15000.0	580.4	-6.1	-22.4	26.5	756.8	636.5	257.5	257.5	38.8	1.000174
15500.0	569.1	-7.3	-24.0	25.2	745.4	635.0	257.4	257.4	39.9	1.000171
16000.0	558.0	-8.5	-25.6	23.8	734.2	633.6	258.0	258.0	40.6	1.000168
16500.0	547.1	-9.7	-27.2	22.5	723.2	632.2	258.5	258.5	41.2	1.000165
17000.0	536.4	-10.9	-28.9	21.2	712.3	630.7	258.9	258.9	41.4	1.000162
17500.0	526.0	-12.0	-30.6	19.9	701.6	629.3	259.1	259.1	41.6	1.000159
18000.0	515.8	-13.2	-32.3	18.6	691.1	627.9	259.1	259.1	41.9	1.000156

UPPER AIR DATA
0091003903
WHITE SANDS SITE
TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 1100 HRS MST
ASCENSION NO. 47

WSTN SITE COORDINATES
E 488.188 MET
N 1887.045 MET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
18500.0	505.7	-14.4	17.2	680.7	626.4	259.1	42.1	1.000134
19000.0	495.9	-15.6	15.9	670.6	625.0	258.7	41.4	1.000131
19500.0	486.1	-16.8	15.6	660.4	623.5	258.3	40.7	1.000149
20000.0	476.3	-18.0	17.5	650.1	622.1	257.5	40.5	1.000146
20500.0	466.6	-19.2	19.5	640.0	620.6	256.7	40.3	1.000144
21000.0	457.2	-20.4	21.4	630.1	619.1	256.3	39.9	1.000142
21500.0	447.9	-21.6	23.4	620.3	617.6	256.0	39.3	1.000140
22000.0	438.8	-22.7	29.0	610.3	616.3	255.6	39.6	1.000138
22500.0	429.8	-23.8	36.4	600.4	614.9	255.2	40.3	1.000136
23000.0	420.8	-25.1	38.8	590.9	613.4	254.1	40.7	1.000133
23500.0	412.1	-26.4	40.7	581.6	611.7	252.7	41.1	1.000131
24000.0	403.5	-27.7	42.6	572.5	610.1	251.0	41.5	1.000129
24500.0	395.1	-29.0	44.5	563.6	608.5	249.3	42.0	1.000127
25000.0	386.8	-30.2	40.1	554.6	606.9	247.9	42.1	1.000125
25500.0	378.6	-31.5	33.5	545.8	605.3	246.5	42.3	1.000123
26000.0	370.4	-32.9	35.0	537.1	603.6	246.3	43.0	1.000120
26500.0	362.5	-34.2	37.1	528.5	601.9	246.1	43.5	1.000119
27000.0	354.6	-35.6	39.2	520.2	600.1	246.1	43.6	1.000117
27500.0	347.0	-37.0	41.3	511.9	598.4	246.4	44.3	1.000115
28000.0	339.5	-38.3	43.7	503.6	596.7	247.6	44.3	1.000113
28500.0	332.1	-39.3	47.4	494.7	595.4	248.3	48.2	1.000111
29000.0	324.8	-40.3	51.1	486.0	594.1	249.3	50.1	1.000109
29500.0	317.6	-41.5	51.2	477.5	592.7	250.0	52.1	1.000107
30000.0	310.5	-42.6	50.2	469.2	591.2	250.8	54.0	1.000105
30500.0	303.6	-43.7	49.2	461.1	589.8	251.1	54.8	1.000103
31000.0	296.6	-45.1	46.0**	453.1	588.1	251.3	55.2	1.000101
31500.0	289.7	-46.5	42.0**	445.3	586.3	252.2	56.8	1.000099
32000.0	283.0	-47.9	38.0**	437.7	584.4	253.4	58.8	1.000098
32500.0	276.4	-49.3	34.0**	430.2	582.6	254.4	58.1	1.000096
33000.0	270.0	-50.7	30.1**	422.9	580.8	255.3	57.1	1.000094

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
 24 JAN. 67 1100 HRS MST
 ASCENSION NO. 47

UPPER AIR DATA
 0091003903
 WHITE SANDS SITE
 TABLE VII (Cont.)

WSTM SITE COORDINATES
 E 408,580 FEET
 N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CM ³ MEYER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
33500.0	263.7	-52.1	26.1**	415.7	570.9	255.2	59.2	1.000093
34000.0	257.6	-53.5	22.1**	408.6	577.1	255.2	59.2	1.000091
34500.0	251.6	-54.9	18.1**	401.7	575.3	254.9	56.9	1.000089
35000.0	245.8	-56.3	14.2**	394.9	573.4	254.6	54.9	1.000088
35500.0	240.1	-57.7	10.2**	388.2	571.5	254.7	54.5	1.000086
36000.0	234.5	-59.1	6.2**	381.7	569.7	255.2	54.4	1.000085
36500.0	229.0	-60.5	2.2**	375.3	567.8	257.0	54.8	1.000084
37000.0	223.6	-61.4	-0. **	367.9	566.6	258.2	54.5	1.000082
37500.0	218.2	-61.7	-0. **	359.4	566.3	258.8	53.5	1.000080
38000.0	212.9	-61.9	-0. **	351.1	565.9	258.2	53.4	1.000078
38500.0	207.7	-62.1	-0. **	343.0	565.6	255.8	54.8	1.000076
39000.0	202.7	-62.4	-0. **	335.0	565.3	252.9	55.6	1.000075
39500.0	197.7	-62.6	-0. **	327.3	564.9	248.3	53.7	1.000073
40000.0	192.9	-62.9	-0. **	319.7	564.6	245.8	51.9	1.000071
40500.0	188.3	-63.2	-0. **	312.5	564.1	241.0	52.9	1.000070
41000.0	183.6	-64.1	-0. **	306.1	563.0	238.1	54.0	1.000068
41500.0	179.1	-65.0	-0. **	299.8	561.8	241.9	55.8	1.000067
42000.0	174.7	-65.8	-0. **	293.6	560.8	243.7	57.5	1.000065
42500.0	170.5	-64.9	-0. **	285.2	561.9	250.8	59.9	1.000064
43000.0	166.3	-64.1	-0. **	277.1	563.0	251.9	62.4	1.000062
43500.0	162.2	-63.2	-0. **	269.3	564.2	258.4	62.3	1.000060
44000.0	158.3	-62.4	-0. **	261.6	565.3	260.5	61.9	1.000058
44500.0	154.4	-62.4	-0. **	255.2	565.3	259.8	59.9	1.000057
45000.0	150.6	-62.8	-0. **	249.5	564.8	257.9	57.2	1.000056
45500.0	147.0	-63.2	-0. **	243.8	564.3	255.8	54.0	1.000054
46000.0	143.4	-63.6	-0. **	238.4	563.7	253.5	56.0	1.000053
46500.0	139.9	-63.9	-0. **	233.0	563.2	252.1	56.2	1.000052
47000.0	136.5	-64.3	-0. **	227.7	562.7	252.6	56.9	1.000051
47500.0	133.1	-64.0	-0. **	221.8	563.2	253.2	57.5	1.000049
48000.0	129.9	-63.4	-0. **	215.8	563.9	254.6	56.8	1.000048

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE HAS BEEN USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 1100 HRS MST
ASCENSION NO. 47

UPPER AIR DATA
0091003903
WHITE SANDS SITE
TABLE VII (Cont)

WSYM SITE COORDINATES
N 400,560 FEET
W 109,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES (TN)	SPEED KNOTS	
48500.0	126.7	-62.5	0.	-0. **	209.6	545.1	256.0	256.0	56.1	1.000047
49000.0	123.7	-61.6	0.	-0. **	203.6	564.4	256.1	256.1	54.5	1.000045
49500.0	120.7	-62.0	0.	-0. **	199.1	565.8	255.4	255.4	52.7	1.000044
50000.0	117.7	-62.5	0.	-0. **	194.7	565.1	255.4	255.4	51.2	1.000043
50500.0	114.9	-63.0	0.	-0. **	190.4	564.5	255.4	255.4	50.4	1.000042
51000.0	112.1	-63.2	0.	-0. **	186.0	564.2	255.3	255.3	49.6	1.000041
51500.0	109.4	-63.0	0.	-0. **	181.3	564.5	252.6	252.6	48.3	1.000040
52000.0	106.7	-62.7	0.	-0. **	176.7	564.8	249.7	249.7	40.8	1.000039
52500.0	104.1	-62.5	0.	-0. **	172.2	565.1	247.6	247.6	36.8	1.000038
53000.0	101.6	-62.3	0.	-0. **	167.8	565.5	245.8	245.8	38.0	1.000037
53500.0	99.1	-62.0	0.	-0. **	163.6	565.9	240.4	240.4	31.0	1.000036
54000.0	96.7	-61.8	0.	-0. **	159.4	566.1	231.4	231.4	30.9	1.000035
54500.0	94.4	-61.8	0.	-0. **	155.6	566.1	225.4	225.4	31.4	1.000035
55000.0	92.1	-61.9	0.	-0. **	151.9	566.0	228.9	228.9	33.6	1.000034
55500.0	89.9	-62.0	0.	-0. **	148.3	565.8	232.4	232.4	35.7	1.000033
56000.0	87.7	-62.1	0.	-0. **	144.8	565.7	235.4	235.4	37.3	1.000032
56500.0	85.6	-62.2	0.	-0. **	141.3	565.5	238.4	238.4	38.7	1.000031
57000.0	83.5	-62.2	0.	-0. **	137.9	565.5	241.7	241.7	39.9	1.000031
57500.0	81.5	-61.8	0.	-0. **	134.3	566.1	245.4	245.4	40.4	1.000030
58000.0	79.5	-61.3	0.	-0. **	130.8	566.7	249.1	249.1	41.4	1.000029
58500.0	77.6	-60.9	0.	-0. **	127.4	567.3	248.0	248.0	42.5	1.000028
59000.0	75.7	-60.5	0.	-0. **	124.1	567.9	246.5	246.5	43.5	1.000028
59500.0	73.9	-60.6	0.	-0. **	121.2	567.6	244.6	244.6	43.5	1.000027
60000.0	72.1	-61.2	0.	-0. **	118.6	566.8	242.0	242.0	42.2	1.000026
60500.0	70.4	-61.8	0.	-0. **	116.0	566.1	239.4	239.4	40.8	1.000026
61000.0	68.7	-62.4	0.	-0. **	113.5	565.3	238.7	238.7	35.7	1.000025
61500.0	67.0	-62.9	0.	-0. **	111.1	564.5	238.2	238.2	30.3	1.000025
62000.0	65.4	-62.8	0.	-0. **	108.3	564.8	236.4	236.4	26.0	1.000024
62500.0	63.8	-61.5	0.	-0. **	105.0	566.4	232.7	232.7	23.6	1.000023
63000.0	62.3	-61.8	0.	-0. **	102.6	566.1	229.0	229.0	21.1	1.000023

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 1100 HRS MST
ASCENSION NO. 47

UPPER AIR DATA
0091003903
WHITE SANDS SITE
TABLE VII (Cont)

WSM SITE COORDINATES
E 480,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL-HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
63500.0	60.7	-62.1	-0.00	100.3	565.7	223.8	16.6	1.000022
64000.0	59.3	-62.3	-0.00	98.0	565.4	218.4	11.9	1.000022
64500.0	57.8	-62.6	-0.00	95.7	565.0	215.2	10.2	1.000021
65000.0	56.4	-62.8	-0.00	93.5	564.7	214.4	11.9	1.000021
65500.0	55.1	-63.1	-0.00	91.3	564.3	213.9	13.5	1.000020
66000.0	53.7	-62.8	-0.00	89.0	564.7	222.6	11.9	1.000020
66500.0	52.4	-62.5	-0.00	86.7	565.2	231.3	10.3	1.000019
67000.0	51.2	-62.1	-0.00	84.5	565.6	235.0	11.1	1.000019
67500.0	49.9	-61.5	-0.00	82.2	566.4	233.5	13.5	1.000018
68000.0	48.7	-60.9	-0.00	80.0	567.3	237.2	14.4	1.000018
68500.0	47.6	-60.2	-0.00	77.9	568.2	243.8	9.3	1.000017
69000.0	46.4	-59.6	-0.00	75.8	569.0	250.5	4.1	1.000017
69500.0	45.3	-58.9	-0.00	73.7	569.9	238.6	2.9	1.000016
70000.0	44.2	-58.3	-0.00	71.8	570.7	222.5	2.5	1.000016
70500.0	43.2	-57.6	-0.00	69.8	571.6	187.8	3.1	1.000016
71000.0	42.2	-57.0	-0.00	68.0	572.5	128.8	6.9	1.000015
71500.0	41.2	-56.8	-0.00	66.3	572.7	73.1	6.6	1.000015
72000.0	40.2	-56.8	-0.00	64.7	572.8	120.5	5.2	1.000014
72500.0	39.2	-56.7	-0.00	63.2	572.9	167.8	3.7	1.000014
73000.0	38.3	-56.6	-0.00	61.7	573.0	160.6	4.7	1.000014
73500.0	37.4	-56.2	-0.00	60.1	573.5	116.8	7.4	1.000013
74000.0	36.5	-55.7	-0.00	58.5	574.2	73.1	10.1	1.000013
74500.0	35.7	-55.1	-0.00	57.0	574.9	68.3	9.6	1.000013
75000.0	34.8	-54.6	-0.00	55.5	575.7	64.9	8.9	1.000012
75500.0	34.0	-54.0	-0.00	54.1	576.4	62.5	8.3	1.000012
76000.0	33.2	-53.8	-0.00	52.8	576.6	65.8	7.6	1.000012
76500.0	32.5	-53.7	-0.00	51.6	576.9	69.2	7.0	1.000011
77000.0	31.7	-53.5	-0.00	50.3	577.1	73.5	6.4	1.000011
77500.0	31.0	-53.3	-0.00	49.1	577.3	79.9	5.6	1.000011
78000.0	30.3	-53.2	-0.00	48.0	577.5	86.3	4.9	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

UPPER AIR DATA
0091003903
WHITE SANDS SITE
TABLE VII (Cont)

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 1100 HRS MST
ASCENSION NO. 47

WSTM SITE COORDINATES
E 488.380 FEET
M 185.045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	DIRECTION DEGREES (TM)	SPEED KNOTS	INDEX OF REFRACTION
78500.0	29.6	-53.0	-0.00	46.8	577.7	102.7	4.4	1.000010
79000.0	28.9	-52.9	-0.00	45.7	577.9	130.5	4.4	1.000010
79500.0	28.2	-52.7	-0.00	44.6	578.2	138.3	4.3	1.000010
80000.0	27.6	-52.5	-0.00	43.5	578.4	149.9	5.2	1.000010
80500.0	26.9	-52.4	-0.00	42.5	578.6	118.9	6.7	1.000009
81000.0	26.3	-52.2	-0.00	41.5	578.8	87.9	8.3	1.000009
81500.0	25.7	-52.0	-0.00	40.5	579.0	80.0	9.7	1.000009
82000.0	25.1	-51.9	-0.00	39.5	579.2	78.9	11.0	1.000009
82500.0	24.5	-51.7	-0.00	38.6	579.4	77.9	12.4	1.000009
83000.0	24.0	-51.5	-0.00	37.7	579.7	75.8	13.9	1.000008
83500.0	23.4	-51.4	-0.00	36.8	579.9	73.5	15.4	1.000008
84000.0	22.9	-51.2	-0.00	35.9	580.1	71.2	16.8	1.000008
84500.0	22.3	-51.0	-0.00	35.0	580.3	69.0	18.1	1.000008
85000.0	21.8	-50.9	-0.00	34.2	580.5	66.8	19.5	1.000008
85500.0	21.3	-50.7	-0.00	33.4	580.7	64.9	13.5	1.000007
86000.0	20.8	-50.5	-0.00	32.6	580.9	64.5	12.1	1.000007
86500.0	20.4	-50.4	-0.00	31.8	581.1	64.1	11.4	1.000007
87000.0	19.9	-50.3	-0.00	31.1	581.3	63.8	10.8	1.000007
87500.0	19.4	-50.1	-0.00	30.4	581.5	63.9	10.3	1.000007
88000.0	19.0	-50.0	-0.00	29.7	581.7	63.9	10.4	1.000007
88500.0	18.6	-49.8	-0.00	29.0	581.9	65.9	11.1	1.000006
89000.0	18.1	-49.7	-0.00	28.3	582.1	70.3	12.6	1.000006
89500.0	17.7	-49.5	-0.00	27.6	582.3	74.7	14.1	1.000006
90000.0	17.3	-49.4	-0.00	27.0	582.4	76.7	15.0	1.000006
90500.0	16.9	-49.3	-0.00	26.3	582.6	76.5	15.4	1.000006
91000.0	16.5	-49.1	-0.00	25.7	582.8	76.4	15.8	1.000006
91500.0	16.2	-49.0	-0.00	25.1	583.0	76.7	17.3	1.000006
92000.0	15.8	-48.8	-0.00	24.5	583.2	77.4	19.5	1.000005
92500.0	15.4	-48.7	-0.00	24.0	583.4	78.1	21.8	1.000005
93000.0	15.1	-48.5	-0.00	23.4	583.6	77.5	21.4	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
24 JAN. 67 1100 HRS MST
ASCENSION NO. 47

UPPER AIR DATA
0091003903
WHITE SANDS SITE
TABLE VII (Cont)

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TM)	SPEED KNOTS	
93500.0	14.7	-48.4	0.	-0. **	22.9	583.8	76.5	76.5	20.3	1.000005
94000.0	14.4	-48.2	0.	-0. **	22.3	583.9	75.5	75.5	19.1	1.000005
94500.0	14.1	-48.1	0.	-0. **	21.8	584.1	76.5	76.5	19.1	1.000005
95000.0	13.8	-48.0	0.	-0. **	21.3	584.3	77.7	77.7	19.3	1.000005
95500.0	13.4	-47.8	0.	-0. **	20.8	584.5	79.0	79.0	19.4	1.000005
96000.0	13.1	-47.7	0.	-0. **	20.3	584.7	76.5	76.5	17.8	1.000005
96500.0	12.8	-47.1	0.	-0. **	19.8	585.5	73.9	73.9	16.1	1.000004
97000.0	12.6	-46.1	0.	-0. **	19.3	586.7	71.2	71.2	14.4	1.000004
97500.0	12.3	-45.1	0.	-0. **	18.8	588.0	69.0	69.0	13.4	1.000004
98000.0	12.0	-44.1	0.	-0. **	18.3	589.3	66.8	66.8	12.4	1.000004
98500.0	11.7	-44.1	0.	-0. **	17.8	589.3	63.6	63.6	11.2	1.000004
99000.0	11.5	-44.1	0.	-0. **	17.5	589.3	49.8	49.8	8.5	1.000004
99500.0	11.2	-44.1	0.	-0. **	17.1	589.3	36.0	36.0	5.7	1.000004
100000.0	11.0	-44.1	0.	-0. **	16.7	589.4	22.3	22.3	2.9	1.000004
100500.0	10.7	-44.0	0.	-0. **	16.3	589.4	2.4	2.4	2.2	1.000004
101000.0	10.5	-44.0	0.	-0. **	15.9	589.4	336.7	336.7	3.4	1.000004
101500.0	10.3	-44.0	0.	-0. **	15.6	589.4	311.0	311.0	4.5	1.000003
102000.0	10.0	-44.0	0.	-0. **	15.2	589.4	285.3	285.3	5.7	1.000003
102500.0	9.8	-44.0	0.	-0. **	14.9	589.4	259.5	259.5	6.9	1.000003
103000.0	9.6	-44.0	0.	-0. **	14.6	589.4				1.000003
103500.0	9.4	-44.0	0.	-0. **	14.2	589.5				1.000003
104000.0	9.2	-44.0	0.	-0. **	13.9	589.5				1.000003
104500.0	9.0	-44.0	0.	-0. **	13.6	589.5				1.000003
105000.0	8.8	-43.9	0.	-0. **	13.3	589.5				1.000003
105500.0	8.6	-43.9	0.	-0. **	13.0	589.5				1.000003
106000.0	8.4	-43.9	0.	-0. **	12.7	589.5				1.000003
106500.0	8.2	-43.9	0.	-0. **	12.4	589.5				1.000003
107000.0	8.0	-43.9	0.	-0. **	12.2	589.6				1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

RELEASE TIME (MST)		SECOND-STAGE IMPACT DISPLACEMENT IN MILES DUE TO WIND										AZI- MUTH (DEG- DEES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)		
		11-216 FT		216-4000 FT		4000-72168 FT		TOTAL							
		N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W						
RAWIN- SONDE	PIBAL	0840	0900	13.2N	1.6E	14.1N	4.5W	6.0S	16.4W	21.3N	19.3W	354.8	81.4	81.1N	7.4W
0840	0915	14.4N	5.7E	17.2N	4.4W	6.0S	16.4W	26.5N	15.1W	357.9	86.4	86.3N	3.2W		
0840	0930	14.5N	3.6E	12.7N	4.1W	6.0S	16.4W	21.2N	16.9W	356.5	81.2	81.0N	5.0W		
0840	1000	12.6N	3.6E	12.1N	1.1W	6.0S	16.4W	18.7N	13.9W	358.5	78.5	78.3N	2.0W		
0840	1015	7.5N	4.8E	8.5N	1.9W	6.0S	16.4W	10.0N	13.5W	358.7	69.8	69.8N	1.6W		
0840	1030	4.1N	0.0	8.1N	3.5W	6.0S	16.4W	6.2N	19.9W	353.1	66.5	66.0N	8.0W		
0840	1040	2.0N	3.6E	5.3N	1.8W	6.0S	16.4W	1.3N	14.6W	357.5	61.2	61.1N	2.7W		
0840	1050	0.0	0.0	1.0N	1.3W	6.0S	16.4W	5.0S	17.7W	353.9	54.8	54.5N	5.8W		
1100	1100	0.0	0.0	1.2S	0.0	7.5S	20.1W	8.7S	20.1W	350.9	51.8	51.1N	8.2W		

	AZIMUTH (DEG- DEES)	MILES FROM LAUNCHER		
		RANGE	N-S	E-W
LAUNCHER SETTING (ELEVATION 85.5 DEGREES QE) NO WIND IMPACT PREDICTED SECOND-STAGE IMPACT SECOND-STAGE IMPACT, RADAR TRACK PREDICTED BOOSTER IMPACT ACTUAL BOOSTER IMPACT	015.4	62.0	59.8N	16.5E
	011.2	60.9	59.8N	11.9E
	359.0	58.0	58.0N	1.0W
	355.0	45.0	44.8N	3.9W
	018.0	2.1	2.0N	0.6E
	N/A	N/A	N/A	N/A

TABLE VIII. IMPACT PREDICTION DATA
NIKE-HYDAC STV (SR-46)

RELEASE TIME (MST)		SECOND-STAGE IMPACT DISPLACEMENT IN MILES DUE TO WIND								AZI- MUTH (DEG- FEES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)			
		11-216 FT		216-4000 FT		4000-72168 FT								TOTAL
		RAWIN- SONDE	PITBAL	N-S	E-W	N-S	E-W	N-S	E-W		N-S	E-W	RANGE	N-S
1100	1145		0.0	0.0	2.7S	2.5W	7.5S	20.1W	10.2S	22.6W	352.8	75.6	75.0N	9.4W
1100	1215		1.9S	0.0	3.4S	4.2W	7.5S	20.1W	12.8S	24.3W	351.3	73.2	72.4N	11.1W
1100	1230		5.6S	1.7E	2.7S	5.0W	7.5S	20.1W	15.8S	23.4W	351.6	70.1	69.4N	10.2W
1100	1245		7.2S	3.1W	5.0S	1.1E	7.5S	20.1W	19.7S	22.1W	352.3	66.2	65.5N	8.9W
1100	1255		5.3S	1.6E	2.1S	0.9W	7.5S	20.1W	14.9S	19.4W	355.0	70.6	70.3N	6.3W
1100	1305		3.0S	1.6E	4.9S	3.3E	7.5S	20.1W	15.4S	15.2W	358.4	70.5	69.8N	2.0W
1100	1315		3.6S	5.6E	2.4S	1.5E	7.5S	20.1W	13.5S	13.0W	359.8	71.7	71.7N	0.2E
1100	1320		7.4S	5.4E	0.6S	0.7E	7.5S	20.1W	15.5S	14.0W	359.3	69.7	69.7N	0.8W
1100	1329		3.0S	3.0E	2.8S	1.8E	7.5S	20.1W	13.3S	15.3W	358.3	71.9	71.9N	2.1W

	LAUNCHER SETTING (ELEVATION 83.7 DEGREES QE) NO WIND IMPACT PREDICTED SECOND-STAGE IMPACT SECOND-STAGE IMPACT, RADAR TRACK PREDICTED BOOSTER IMPACT ACTUAL BOOSTER IMPACT	AZIMUTH (DEG- FEES)			MILES FROM LAUNCHER		
		RERS	RANGE	N-S	RANGE	N-S	E-W
		011.8	87.1	85.2N	87.1	85.2N	17.8E
		008.9	86.4	85.2N	86.4	85.2N	13.2E
		358.6	70.0	70.0N	70.0	70.0N	2.0W
		008.0	91.8	90.9N	91.8	90.9N	12.8E
		016.0	1.8	1.7N	1.8	1.7N	0.5E
		N/A	N/A	N/A	N/A	N/A	N/A

TABLE IX. IMPACT PREDICTION DATA
NIKE-HYDAC (SR-47)

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate Author)		2a. REPORT SECURITY CLASSIFICATION
U.S. Army Electronics Command Fort Monmouth, New Jersey		UNCLASSIFIED
		2b. GROUP
3. REPORT TITLE		
METEOROLOGICAL DATA REPORT, NIKE-HYDAC STV (SR-46 & 47)		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial)		
SHARPE, John M.		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
February 1967	25	None
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
a. PROJECT NO.	DR-155	
c. DA Task IV650212A127-02	9b. OTHER REPORT NO.(S) (Any other numbers that may be assigned this report)	
d.		
10. AVAILABILITY/LIMITATION NOTICE		
Distribution of this document is unlimited.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY	
	U.S. Army Electronics Command Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico	
13. ABSTRACT		
Meteorological data gathered for the launching of two (2) Nike-Hydac STV (SR-46 & 47) are presented for the Ballistic Systems Division, U.S. Air Force and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.		

DD FORM 1473
1 JAN 64UNCLASSIFIED
Security Classification

UNCLASSIFIED
Security Classification

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Ballistics 2. Winds 3. Meteorology						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Ballistics						
2. Winds						
3. Meteorology						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.