

UNCLASSIFIED

AD NUMBER

AD815090

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; JUN 1967. Other requests shall be referred to Air Force Flight Dynamics Laboratory, Wright-Patterson AFB, OH 45433. This document contains export-controlled technical data.

AUTHORITY

AFFDL ltr, 20 Dec 1974

THIS PAGE IS UNCLASSIFIED

AEDC-TR-67-93

**ARCHIVE COPY
DO NOT LOAN**

cy1

PROPERTY OF U. S. AIR FORCE
AEDC LIBRARY
AF 40(600)T 270

FREE-FLIGHT TESTING OF AERODYNAMIC DECELERATORS IN A SUPERSONIC WIND TUNNEL



L. K. Ward and A. W. Myers

ARO, Inc.

This document has been approved for public release
its distribution is unlimited. *SEP 15 14 26, 14*
Dtd 20 DEC, 74

June 1967

This document is subject to special export controls
and each transmittal to foreign governments or foreign
nationals may be made only with prior approval of
Air Force Flight Dynamics Laboratory (FDFR),
Wright-Patterson AFB, Ohio.

**VON KÁRMÁN GAS DYNAMICS FACILITY
ARNOLD ENGINEERING DEVELOPMENT CENTER
AIR FORCE SYSTEMS COMMAND
ARNOLD AIR FORCE STATION, TENNESSEE**

AEDC TECHNICAL LIBRARY



PROPERTY OF U. S. AIR FORCE
AEDC LIBRARY
AF 40(600)1200

ERRATA

AEDC-TR-67-93, June 1967

FREE-FLIGHT TESTING OF AERODYNAMIC DECELERATORS IN A SUPERSONIC WIND TUNNEL

L. K. Ward and A. W. Myers, ARO, Inc.

Arnold Engineering Development Center
Air Force Systems Command
Arnold Air Force Station, Tennessee

The model erroneously referred to as the supersonic glide surface parachute in the above report should consistently be referred to as the supersonic guide surface parachute.

NOTICES

When U. S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

FREE-FLIGHT TESTING OF AERODYNAMIC
DECELERATORS IN A SUPERSONIC WIND TUNNEL

L. K. Ward and A. W. Myers
ARO, Inc.

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Air Force Flight Dynamics Laboratory (FDFR), Wright-Patterson AFB, Ohio.

This document has been approved for public release
its distribution is unlimited. *PER 7113 7426*
246 20 Dec, 74

FOREWORD

The work reported herein was done at the request of the Air Force Flight Dynamics Laboratory (AFFDL), Air Force Systems Command (AFSC), under Program Element 62405364, Project 6065.

The results of the developments presented were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), AFSC, Arnold Air Force Station, Tennessee, under Contract AF 40(600)-1200. The work was conducted under ARO Project No. VT0626, and the manuscript was submitted for publication on April 17, 1967.

The authors wish to acknowledge their colleague, Mr. C. J. Schueler, who suggested testing the decelerators in the free-flight mode, for his efforts throughout the program and Mr. C. A. Babish of the Air Force Flight Dynamics Laboratory for supplying the parachute models.

Information in this report is embargoed under the Department of State International Traffic in Arms Regulations. This report may be released to foreign governments by departments or agencies of the U. S. Government subject to approval of Air Force Flight Dynamics Laboratory (FDFR), Wright-Patterson AFB, Ohio, or higher authority within the Department of the Air Force. Private individuals or firms require a Department of State export license.

This technical report has been reviewed and is approved.

James N. McCready
Major, USAF
AF Representative, VKF
Directorate of Test

Leonard T. Glaser
Colonel, USAF
Director of Test

ABSTRACT

A technique has been developed for use in the continuous flow, supersonic Tunnel A of the von Kármán Gas Dynamics Facility to obtain drag and performance data on flexible decelerators deployed behind models in free flight. The technique is described, and drag data obtained on two parachute configurations are compared with data obtained using a strut-supported model.

CONTENTS

	<u>Page</u>
ABSTRACT	iii
NOMENCLATURE	vi
I. INTRODUCTION	1
II. APPARATUS	
2.1 Wind Tunnel	1
2.2 Models	2
2.3 Model Supports	4
III. PROCEDURE	
3.1 Free-Flight Tests	6
3.2 Captive Tests	9
IV. RESULTS AND DISCUSSION	9
V. CONCLUDING REMARKS	13
REFERENCES	13

ILLUSTRATIONS

Figure

1. Sketch of the Parent Model	2
2. Hyperflo Parachute Construction and Design Specifications, Configs. 1 and 3	
a. Typical Hyperflo Construction	3
b. Hyperflo Design Specifications	3
3. Supersonic Glide Surface Parachute Construction and Design Specifications, Config. 74	3
4. Model Launcher	4
5. Tunnel A Launcher Support System	5
6. Forebody and Strut Support for the Captive Tests	6
7. Free-Flight Model-Parachute Assembly	7
8. Parachute Deployment Sequence	7
9. Free-Flight Deployment at Mach 4, Config. 1, $x/d = 4.9$	8
10. Parachute Drag Coefficient versus Reynolds Number, (Hyperflo) $x/d = 4.9$	
a. $\lambda_t = 5$ (Config. 3)	10
b. $\lambda_t = 15$ (Config. 1)	10

<u>Figure</u>	<u>Page</u>
11. Parachute Drag Coefficient versus Trailing Distance in Base Diameters, Config. 1 ($\lambda_t = 15$)	11
12. Parachute Drag Coefficient versus Reynolds Number, Supersonic Guide Surface, Config. 74, $x/d = 9.1$	11

TABLE

I. Parachute Performance	12
------------------------------------	----

NOMENCLATURE

A	Parachute frontal area, in. ²
a_X	Acceleration of the model in the X direction with respect to a tunnel fixed axis, ft/sec ²
C_D	Parent model total drag coefficient, drag/ $q_\infty A$
C_{DP}	Parachute drag coefficient
C_{DT}	System total drag coefficient ($C_D + C_{DP}$)
d	Model base diameter, in.
M_∞	Free-stream Mach number
m	Model mass, slug
Re_d	Free-stream Reynolds number, based on maximum diameter of parachute
V_{XF}	Velocity of the model in the X direction with respect to the media fixed axis, ft/sec
x	Distance from the model base to parachute canopy, in.
λ_t	Total parachute porosity, percent
ρ_∞	Free-stream density, slug/ft ³

SECTION I INTRODUCTION

Aerodynamic decelerators have been of interest for many years as a means of safely descending payloads through the lower atmosphere at very low speeds. With the advent of high-speed flight and later the "space age", deployable decelerators are being used to lessen the speed of re-entry vehicles at supersonic and even hypersonic speeds.

The wind tunnel may be used to advantage in the development of high-speed aerodynamic decelerators. Several tests have been conducted at the von Kármán Gas Dynamics Facility (VKF), AEDC and are summarized in Ref. 1. The most widely used technique for testing decelerators in a wind tunnel is to support the parent body (forebody) model by means of one or more side-mounted struts, leaving the region behind the base of this model unobstructed. The drag on the trailing decelerator is determined using a load cell which may be located in the forebody or outside of the wind tunnel. Because of the high loadings generally encountered in this type of test, the supporting struts are necessarily large and are therefore subject to generate unwanted interference in the forebody wake. Such interference could affect the decelerators' performance and drag characteristics.

A wind tunnel free-flight testing technique (Ref. 2) has been developed at VKF for testing at Mach numbers ranging from 1.5 through 10. This technique was used to obtain data on a parachute trailing behind a cone-cylinder-flare model at Mach 4. The technique is described and results of this test are reported herein for comparison with data obtained using a double strut support cone-cylinder-flare model. The tests were conducted in the 40-in. supersonic tunnel (Gas Dynamic Wind Tunnel, Supersonic (A)).

SECTION II APPARATUS


2.1 WIND TUNNEL

Tunnel A is a continuous, closed-circuit, variable density wind tunnel with an automatically driven, flexible-plate-type nozzle and a 40- by 40-in. test section. The tunnel operates at Mach numbers from 1.5 to 6 at maximum stagnation pressures from 29 to 200 psia, respectively, and stagnation temperatures up to 300°F ($M_\infty = 6$). Minimum

operating pressures range from about one-tenth to one-twentieth of the maximum pressures.

2.2 MODELS


The parent model used during the tests was a spherical nose, cone-cylinder-flare. Both the free-flight model and the captive model were of the size shown in Fig. 1.



All Dimensions in Inches

Fig. 1 Sketch of the Parent Model

Two types of parachutes, hyperflo and supersonic glide surface, were utilized during the investigation. The hyperflo parachutes, characterized by a truncated cone design, were constructed with porous roofs and solid-cloth, low porosity skirts. Construction and design details of the hyperflo parachutes are shown in Fig. 2.



a. Typical Hyperflo Construction

Config. Number	λ_t , percent	D_p , in.	D_m , in.	D_i , in.	a , in.	l_s , in.	w , in.	Suspension Line Material	Material	Roof Border and Radial Ribbon Material	Roof Screen Material
1	15	5.00	4.78	4.50	1.44	10.00	0.15	Cord, Nylon	Cloth, Nylon	Neoprene-Coated	Perlon Mesh
3	5	5.00	2.90	4.50	1.44	10.00	0.15	100-lb MIL-C-5040, Type I	300-lb/in. MIL-C-8021, Type II	Nylon Dantex® 5678	25/2/280, 64 by 64 Grid (per in.)

b. Hyperflo Design Specifications

Fig. 2 Hyperflo Parachute Construction and Design Specifications, Configs. 1 and 3

The supersonic glide surface parachutes were designed with a rigid conical centerbody at the inlet and a flexible, low porosity, cloth canopy. Details of the design and construction of the parachutes are shown in Fig. 3 and discussed in detail in Ref. 3.




Fig. 3 Supersonic Glide Surface Parachute Construction and Design Specifications, Config. 74

2.3 MODEL SUPPORTS

2.3.1 Free-Flight Tests

During the free-flight phase of the test program, the models were launched from a pneumatically operated launcher. A sketch of the launcher is shown in Fig. 4. The launcher consists of an aluminum piston which is contained in a stainless steel case and guide. The piston stroke is about 6.5 in. and will launch models at velocities up to 100 ft/sec.




Fig. 4 Model Launcher

The launcher, when used in Tunnel A, is supported on an injection/retraction system (Fig. 5), which is provided to allow the launching of several models without interrupting the operation of the tunnel. A more detailed description of the launcher system may be found in Ref. 2.




Fig. 5 Tunnel A Launcher Support System

2.3.2 Captive Tests

The support system for the captive forebody phase of the investigation consisted of a strut spanning the width of the tunnel and mounted to the sidewalls. The tensiometer for measuring parachute drag was housed in a vacuum tank, which was also mounted to the tunnel sidewall. The decelerator support line passed through the model and strut and into the vacuum tank, where it was attached to the tensiometer. Care was taken to duplicate the bridle riser-line attachment used during the free-flight testing. Details of the system are presented in Fig. 6.




Fig. 6 Forebody and Strut Support for the Captive Tests

SECTION III PROCEDURE

3.1 FREE-FLIGHT TESTS

The basic objective of the free-flight wind tunnel tests was to package the parachute inside the model and then to deploy it in an orderly fashion while the model was in flight. A model scale was chosen so that existing parachutes could be used. The final model-parachute assembly is shown in Fig. 7, and the sequence of events during chute deployment is shown in Fig. 8.




Fig. 7 Free-Flight Model-Parachute Assembly




Fig. 8 Parachute Deployment Sequence

During each run, model motion was recorded by two high-speed (4000-frames/sec), 16-mm motion-picture cameras. One camera was used to film the total viewing area, and selected frames taken by this camera are shown in Fig. 9. The second camera was used in conjunction with the tunnel schlieren system and viewed only the tunnel upstream window.




Fig. 9 Free-Flight Deployment at Mach 4, Config. 1, $x/d = 4.9$

All drag data were obtained using motion data recorded with the second camera. With the aid of a film reader, the models' motion time history was obtained, and the model and parachute drag coefficient was determined as

$$C_{DT} = \left(2m/\rho_{\infty} A V_{X_F}^2 \right) a_X$$

The above equation simply comes from Newton's Second Law, and a more detailed treatment of the development of the equations of motion may be found in Ref. 2.

Two models of the parent body were launched without the parachute to determine the total drag coefficient (C_D) of the parent model alone. The parachute drag coefficient may then be found as

$$C_{DP} = C_{DT} - C_D$$

where C_D is also based on the frontal area of the parachute.

3.2 CAPTIVE TESTS


Before each test run, the parachute canopy and suspension lines were packed in a deployment bag, which was then suspended near the base of the parent model by a pull cord routed from the rear of the bag through the tunnel sector. The pull cord was held taut manually during tunnel start, and when the desired test condition was established, a sharp pull on the cord removed the bag. The normal procedure for remotely varying x/d during tunnel operation was not used since all data were obtained with the parachute riser line attached to a bridle (Fig. 6) to duplicate the free-flight test configuration.

SECTION IV RESULTS AND DISCUSSION


Two basic parachute configurations, a hyperflo parachute model and a supersonic glide surface parachute model (Config. 74), were tested using the two techniques. Two total canopy porosities, $\lambda_t = 5$ (Config. 1) and $\lambda_t = 15$ (Config. 3), were tested for the hyperflo parachute.

Parachute drag data obtained on the hyperflo parachutes are shown in Figs. 10 and 11. The comparison of the data obtained during the

captive tests and the free-flight tests for $x/d = 4.9$ (Fig. 10) shows the captive model drag to be higher for both values of λ_t . Figure 11 shows that increasing the parachute trailing distance to about 4.5 base diameters did not affect the difference in drag obtained by the two testing techniques.



a. $\lambda_t = 5$ (Config. 3)



b. $\lambda_t = 15$ (Config. 1)

Fig. 10 Parachute Drag Coefficient versus Reynolds Number, (Hyperflo) $x/d = 4.9$




Fig. 11 Parachute Drag Coefficient versus Trailing Distance in Base Diameters, Config. 1 ($\lambda_t = 15$)

Data obtained on the supersonic glide surface parachute model (Config. 74) are given in Fig. 12 and again show the captive model data to be high with respect to the free-flight results.




Fig. 12 Parachute Drag Coefficient versus Reynolds Number, Supersonic Guide Surface, Config. 74, $x/d = 9.1$

A summary of the parachute's performance is given in Table I.

TABLE I
PARACHUTE PERFORMANCE

Configuration	λ_t , percent	M_∞	$Re_d \times 10^{-6}$	x/d	Remarks
1 (Hyperflo)	15	4.0	0.54	4.9	Free flight - Good canopy inflation with little or no oscillation. Shroud lines flexing lightly and canopy slowly spinning on most runs.
					Captive - Oscillations of 0.5 deg with very light canopy pumping. Shroud lines flexing lightly but not spinning.
				8.3	Free flight - Bad canopy opening. Model pitching and canopy pumping throughout run.
				9.5	Captive - Oscillations of 2 to 7 deg. Heavy pumping of canopy with shroud lines flexing moderately.
3 (Hyperflo)	5	4.0	0.54	4.9	Free flight - Canopy steady after initial opening.
					Captive - Oscillations from 2 to 8 deg accompanied by light to moderate canopy pumping. Shroud lines flexing lightly.
74 (Supersonic Glide Surface)	---	4.0	0.54	9.1	Free flight - Canopy steady after initial opening.
					Captive - Intermittent 5-deg oscillations. Canopy steady otherwise.

SECTION V

CONCLUDING REMARKS

A technique has been developed at VKF to deploy flexible decelerators from free-flight wind tunnel models at supersonic speeds. The free-flight data, when compared with data obtained using a strut-supported model, show that support interference effects possibly exist. The procedures reported for testing up to $M_\infty = 6$ may also be easily used to provide a capability for testing up to $M_\infty = 10$.

REFERENCES

1. Alexander, W. C. and Lau, R. A. "State-of-the-Art Study for High-Speed Deceleration and Stabilization Devices." NASA CR-66141, September 1966.
2. Ward, L. K., Hodapp, A. E., and Choate, R. H. "Description of a Model Launcher and Techniques Used for Obtaining Model Free-Flight Measurements in the VKF Continuous Flow Wind Tunnels at Mach Numbers from 1.5 through 10." AEDC-TR-66-112 (AD487477), August 1966.
3. Heinrich, H. G. "Aerodynamic Characteristics of the Supersonic Guide Surface and the Spiked Ribbon Parachutes." AFFDL-TR-65-104, December 1965.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center ARO, Inc., Operating Contractor Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP N/A	
3 REPORT TITLE FREE-FLIGHT TESTING OF AERODYNAMIC DECELERATORS IN A SUPERSONIC WIND TUNNEL			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5 AUTHOR(S) (Last name, first name, initial) Ward, L. K., and Myers, A. W., ARO, Inc.			
6 REPORT DATE June 1967		7a. TOTAL NO. OF PAGES 19	7b. NO OF REFS 3
8a CONTRACT OR GRANT NO. AF40(600)-1200 b. 6065 c. Program Element 62405364 d.		9a. ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-67-93 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A	
10 AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Air Force Flight Dynamics Laboratory (FDFR), Wright-Patterson AFB, Ohio.			
11. SUPPLEMENTARY NOTES Available in DDC.		12. SPONSORING MILITARY ACTIVITY Air Force Flight Dynamics Laboratory, Air Force Systems Command, Wright-Patterson AF Base, Ohio	
13 ABSTRACT A technique has been developed for use in the continuous flow, supersonic Tunnel A of the von Kármán Gas Dynamics Facility to obtain drag and performance data on flexible decelerators deployed behind models in free flight. The technique is described, and drag data obtained on two parachute configurations are compared with data obtained using a strut-supported model.			

This document has been approved for public release
its distribution is unlimited. *PER TAFB 24-26
Dtd 20 Dec., '74*

14	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	aerodynamic decelerators wind tunnels free flight supersonic flow <u>performance</u> <u>hyperflo parachutes</u> supersonic glide surface parachutes <i>1. Decelerators -- Performance</i> <i>2. " " " " Free flight testing</i> <i>3. " " " " Wind tunnel testing</i> <i>5. Parachutes</i>						
INSTRUCTIONS 1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report. 2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations. 2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized. 3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title. 4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered. 5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement. 6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication. 7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information. 7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report. 8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written. 8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc. 9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report. 9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s). 10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as: (1) "Qualified requesters may obtain copies of this report from DDC." (2) "Foreign announcement and dissemination of this report by DDC is not authorized." (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____." (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____." (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____." If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known. 11. SUPPLEMENTARY NOTES: Use for additional explanatory notes. 12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address. 13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached. It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U). There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words. 14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.							