

UNCLASSIFIED

AD NUMBER

AD819599

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited. Document partially illegible.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; 14 AUG 1967. Other requests shall be referred to Air Force Technical Applications Center, Washington, DC 20333. This document contains export-controlled technical data.

AUTHORITY

USAF ltr dtd 28 Feb 1972

THIS PAGE IS UNCLASSIFIED

AD819599

AD819599

LONG RANGE SEISMIC MEASUREMENTS

COMMODORE

20 MAY 1967

Prepared for

AIR FORCE TECHNICAL APPLICATIONS CENTER
Washington, D. C.

14 AUGUST 1967

By

TELEDYNE, INC.

Under

Project VELA UNIFORM

Sponsored by

ADVANCED RESEARCH PROJECTS AGENCY
Nuclear Test Detection Office
ARPA Order No. 626

DDC
SEP 12 1967
R
C

DISCLAIMER NOTICE

THIS DOCUMENT IS THE BEST
QUALITY AVAILABLE.

COPY FURNISHED CONTAINED
A SIGNIFICANT NUMBER OF
PAGES WHICH DO NOT
REPRODUCE LEGIBLY.

LONG RANGE SEISMIC MEASUREMENTS

COMMODORE

SEISMIC DATA LABORATORY REPORT NO. 193

AFTAC Project No.:	VELA T/6702
Project Title:	Seismic Data Laboratory
ARPA Order No.:	624
ARPA Program Code No.:	5810
Name of Contractor:	TELEDYNE, INC.
Contract No.:	F 33657-67-C-1313
Date of Contract:	2 March 1967
Amount of Contract:	\$ 1,736,617
Contract Expiration Date:	1 March 1968
Project Manager:	William C. Dean (703) 836-7644

P. O. Box 334, Alexandria, Virginia

AVAILABILITY

This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

This research was supported by the Advanced Research Projects Agency, Nuclear Test Detection Office, under Project VELA-UNIFORM and accomplished under the technical direction of the Air Force Technical Applications Center under Contract F 33657-67-C-1313.

Neither the Advanced Research Projects Agency nor the Air Force Technical Applications Center will be responsible for information contained herein which may have been supplied by other organizations or contractors, and this document is subject to later revision as may be necessary.

ABLE OF CONTENTS

	Page No.
EVENT DESCRIPTION	1
INTRODUCTION	2
INSTRUMENTATION AND PROCEDURE	2
DATA AND RESULTS	4
<u>TABLES</u>	
1 Station Status Report - COMMODORE	
2 Principal Phases - COMMODORE	
<u>FIGURES</u>	
1 Recording Stations and Signals Received	
2 Unified Magnitudes	
3 Adjusted Unified Magnitudes	
4 Travel-Time Residuals, $T-\Delta/8.1$; T-JB	
5 Maximum Amplitudes of Pn and P	
6 Maximum Amplitudes of Pg	
7 Maximum Amplitudes of Lg	
8 Maximum Amplitudes of LQ	
9 Maximum Amplitudes of LR	
<u>LIST OF APPENDICES</u>	
I(A) Recording Site Information	
I(B) Unified Magnitudes from Pn or P Waves	
II(A) Seismic Analysis Diagram	
II(B) Instrument Response Curves - LRSM	
II(C) Instrument Response Curves - LASA	
II(D) Instrument Response Curves - Other Short Period	

COMMODORE
EVENT DESCRIPTION

DATE: 20 May 1967

TIME OF ORIGIN: 15:00:00.2Z

YIELD:

MAGNITUDE: 5.68 ± 0.56

LOCATION:

SITE: Nevada Test Site, Area U2am

GEOGRAPHIC COORDINATES:

Lat: 37° 07' 49.0" N

Long: 116° 03' 50.0" W

ENVIRONMENT:

GEOLOGIC MEDIUM: TUFF

SURFACE ELEVATION: 4258 ft.

SHOT ELEVATION: 1773 ft.

SHOT DEPTH: 2485 ft.

COMPUTED EPICENTER: ALL STATIONS

GEOGRAPHIC COORDINATES:

Lat: 37° 07' 12.0" N

Long: 116° 09' 36.0" W

TIME OF ORIGIN: 15:00:013Z

DEPTH CONSTRAINED TO: 0 km


EPICENTER SHIFT: 8.6 km S 80° W

Code	Station	Final							Timing
		SPZ	SPR	SPT	LPZ	LPR	LPT	Tape	
MN-NV	Mina, Nevada	+	+	+	+	+	+	*	P
KM-UT	Kanab, Utah	+	+	+	+	+	+	*	P
TFSO	Tonto Forest Seismological Observatory, Arizona	+	+	+	+	+	+	*	P
MO-ID	Mountain Home, Idaho	+	+	+	+	+	+	*	P
UBSO	Uinta Basin, Seismological Observatory, Utah	+	+	+	+	+	+	*	S
BMSO	Blue Mountain, Seismological Observatory, Oregon	+	+	+	+	+	+	*	P
FK-CO	Franktown, Colorado	+	+	+	+	+	+	*	P
LAO	Subarray, AO-10, Montana	+	N	N	+	+	+		P
SA4TX	San Angelo, Texas	+	N	N	+	+	+		P
WMSO	Wichita Mountain Seismological Observatory, Oklahoma	+	+	+	+	+	+	*	P
ST2TX	Streeter, Texas	+	N	N	**	**	**		P
GR2TX	Grit, Texas	+	N	N	+	+	+		P
GR1TX	Grit, Texas	+	N	N	+	+	+		P
ST1TX	Streeter, Texas	**	N	N	+	-	-		P
PG-BC	Prince George, British Columbia, Canada	+	+	+	+	+	+	*	P
RK-ON	Red Lake, Ontario, Canada	+	+	+	+	+	+	*	P
CPSO	Cumberland Plateau, Seismo- logical Observatory, Tenn.	+	+	+	+	+	+	*	P
WH2YK	Whitehorse, Yukon Territory, Canada	+	+	+	+	+	+	*	P
HN-ME	Houlton, Maine	+	+	+	+	+	+	*	P
SV3QB	Schefferville, Quebec, Canada	+	+	+	+	+	+	*	P
NP-NT	Mould Bay, Northwest Territories, Canada	+	+	+	+	+	+	*	P

I	Inoperative	+	Signal
N	No Instrument	-	No Signal
P	Primary Timing	*	Magnetic Tape Available
S	Secondary Timing	**	Magnification Unreliable

Station Status Report - COMMODORE

Table 1



Recording Stations and Signals Received

Figure 1

INTRODUCTION

A long range seismic measurements (LRSM) program and several larger seismographic observatories were established under VELA-UNIFORM to record seismological data resulting from natural seismic activity and a planned series of U. S. underground nuclear tests. The LRSM teams are mobile and occupy locations selected to provide optimum data from events of special interest; the observatories are permanent installations as follows:

Wichita Mountains Seismological Observatory (WMSO)
Lawton, Oklahoma

Uinta Basin Seismological Observatory (UBSO)
Vernal, Utah

Tonto Forest Seismological Observatory (TFSO)
Payson, Arizona

Large Aperture Seismic Array (LASA)
Billings, Montana

The purpose of this report is to provide an analysis of data resulting from the COMMODORE event recorded by the LRSM teams and the VELA observatories and a preliminary summary of data reported by other permanent and temporary seismographic stations.

INSTRUMENTATION AND PROCEDURE

The instrumentation at each of the LRSM locations consists of three-component short-period and three-component long-period seismographs. In general, data are recorded on 35 millimeter film

and on one-inch 14 channel magnetic tape, although recently more portable instrumentation has been incorporated which records only on magnetic tape. The stations are all equipped to record WWV continuously to provide accurate time control. Calibration is accomplished once each day and just prior to each shot at the operational settings. Pertinent information useful for analysis of LRSM data is available to qualified users of this data and is contained in Technical Report 65-43, "Interpretation and Usage of Seismic Data, LRSM Program." General information on LRSM van and portable system equipment and operation is given in Technical Report 66-27, "The LRSM Mobile Seismological Laboratory," and 65-74, "A Portable Seismograph." Copies of these reports may be obtained from DDC. The AD control number of Technical Report 66-27 is 480343. All the observatories have both long-period and short-period, three-component instrumentation, in addition to their other specialized facilities.

Station information is presented in Appendix I(A). This includes the station name and code; the geographic coordinates; the distances and azimuths involved; the station elevations; and the type of instruments in use at each location. Representative instrumental response curves are shown in Appendix II(B), II(C), and II(D).

The procedures used in measuring amplitudes reported herein are illustrated in Appendix II(A) and the unified magnitude is calculated as shown in Appendix I(B). The distance factors (B) beyond 16° are

from Gutenberg and Richter*. For distance less than 16° values were read from a curve in the Gutenberg and Richter paper back to 10° and then extrapolated to 2° , using an inverse cube relationship. An additional magnitude for less than 16° was computed using a method described by Evernden**. (Figure 3)

A standard hypocenter location program for a digital computer is used to determine the location using data from all stations analyzed. Best-fit values of latitude, longitude, and time of origin are determined statistically by a least squares technique. This utilizes a Jeffreys-Bullen travel-time curve as modified by Herrin in 1961 on the basis of Pacific surface-focus recordings. Precision of the computation is limited primarily by the accuracy of arrival times, the validity of the standard travel-time curve, and by local velocity deviations. This method is based on P-wave arrivals with depth constrained to zero.

DATA AND RESULTS (LRSM AND VELA OBSERVATORIES)

The parameters of the COMMODORE event and a summary of the seismic evaluation is shown on the Event Description page. The operational status of the 21 LRSM stations and observatories is given in Table I, and illustrated in Figure 1.

*Gutenberg, B. and Richter, C. F., Magnitude and Energy of Earthquakes Ann. Geofis., 9 (1956), pp. 1-15.

**Evernden, J. F., Magnitude Determination at Regional and Near Regional Distances in the United States, AFTAC/VELA Seismological Center Technical Report VU-65-4A, (1965), pp. 6,13.

7

Table 2 summarizes the measurements made of the principal phases from the COMMODORE event at the LRSM and VELA stations. Included are the Pn and P arrival times, the maximum amplitudes (A/T) of Pn or P motion and other phases as seen on the short-period instruments. Long-period Love and Rayleigh wave motion are also tabulated in (A/T) form. In addition, individual station Rayleigh wave areas (mm^2) is indicated as measured on the LPZ only. Although reduced to 1K magnification, they have not been normalized to any magnitude. Twenty-one stations recorded short-period and long-period signals from this event.

The unified magnitudes determined from the LRSM and VELA observatories are shown in Figure 2. The average magnitude is 5.68 ± 0.56 . The adjusted unified magnitude is 5.41 ± 0.55 and is shown in Figure 3.

The travel-time residuals from the Pn and P phases are shown in Figure 4. Figures 5 through 9 illustrate plots of the amplitudes of P, Pg, Lg, LQ, and LR.

Attached to the report are illustrative seismograms showing the signals recorded at four stations. The most distant station analyzed that recorded COMMODORE was NP-NT at a distance of 4364 kilometers.

Code	Station	Distance (mi)	Inst.	Magni- fication (x) Film x 10	Phase	Observed Travel Time		Period (sec)	Maximum Amplitude A/T	Magnitude (m)		Area(mi ² LPS)
						(min)	(sec)			mb	ms	
MS-AT	Mesa, Nevada	234	SFS	0.296c	Pn		36.2	0.6	484c	5.94	5.63	863.93
			SFS	0.296c	Py		38.7	0.5	23,246			
			SPT	0.415	Lg			0.6	45,053			
			LPS	0.463	LR			10.0	17,893			
			LPS	0.463	e	9	55	11.0	5382			
MS-AT	Kanab, Utah	200	SFS	0.344	Pn		43.2	0.6	3424	6.03	5.77	
			SFS	0.344	e		44.5	0.6	4467			
			SFS	0.344	e		48.0	0.5	11,576			
			SFS	0.344	Py		49.1	0.6	18,779			
			SPT	3.34	Lg			0.8	25,567			
			LPS	0.817	LR			9.0	4125			
			LPS	0.817	e	2	01	(11.0)	(109)			
			SFS-60	5.5	Pn	1	15.1	0.3	477	6.03	5.74	
			SFS-60	5.5	e	1	21.4	0.5	346			
			SFS-60	1.0	Lg	1	29.1	0.75	1966			
MS-ED	Mountain View, Idaho	660	SPT	1.0	Lg			1.3	1419			342.31
			SFS	1.0	Lg			1.3	2995			
			LPS		LR			---	---			
			LPS	4.0	e	11	30	16.0	111			
			SFS	16.89	Pn	1	30.8	0.45	423	6.22	6.00	
			SFS	16.89	Py	1	(49.0)	(0.4)	(5131)			
			SPT		Lg			---	---			
			LPT	8.26	LQ			11.0	(3543)			
			LPS	1.28	LR			12.0	2510			
			LPS	13.9	e	12	22	(12.0)	(341)			
MS-BO	Unita Basin Seismological Observatory, Utah	667	SFS-10	5.0	Pn	01	33.2	0.9	1127	6.72	6.59	
			SFS-10	5.0	e	01	34.2	0.7	1007			
			SFS-10	5.0	Py	01	50.4	0.8	1610			
			SPT	0.9	Lg			1.2	5474			
			JPS	0.93	Lg			1.2	3632			
			LPS	2.25	LQ			16.0	(111)			
			LPS		LR			---	---			
			LPS	1.00	e	12	23	15.0	113			
			SFS-3	25.0	Pn	01	56.5	0.45	96.4	5.93	5.66	
			SFS-3	25.0	e	01	59.8	0.6	140			
MS-BO	Blue Mountain Seismological Observatory, Oregon	864	SFS-3	25.0	Py	02	23.4	---	---			430.00
			SPT		Lg			---	---			
			SFS		Lg			---	---			
			LPS	1.0	LR			15.0	742			
			LPS	8.8	e	13	25	15.0	108			
			SFS	30.0	Pn	02	19.4	(0.6)	(124)	(6.33)	(4.86)	
			SFS	30.0	e	02	32.0	0.6	137			
			SFS	30.0	Py	02	59.5	1.2	1111			
			SPT	29.45	Lg			1.8	2495			
			LPT	4.2	LQ			12.0	2198			
FS-CO	Fremont, Colorado	1049	LPS	0.637	LR			11.0	4116		598.72	

FD-CO	Franktown, Colorado	1049	LPS	1.0	LR				15.0	742	(4.86)	(6.22)	420.00
			LPS	8.6	e		13	25	15.0	108			
			SPE	30.0	Ph	02	02	19.4	(0.8)	(124)			
			SPE	30.0	e	02	02	32.0	0.6	137			
			SPE	30.0	Py	02	02	59.5	1.2	1111			
			SPE	29.45	Lq				1.8	2495			
			LPT	4.2	LQ				12.0	2190			
			LPS	0.627	LR				11.0	4116			
			LPS	0.627	e	14	25		12.0	452			
			LAD	Subarray, AO-10 Monte	1138	SPE	87.7	Ph	02	02			
SPE	87.7	e				02	02	55.1	0.7	38.6			
SPE	87.7	e				02	02	(08.2)	0.9	117			
SPE	87.7	e				03	03	14.5	(1.1)	(159)			
SPE	87.7	(Py)				02	02	40.6	(0.9)	(129)			
LPS		LR							---	---			
SPE-2	60.0	P				03	03	11.5	(1.0)	(154)			
SPE-2	60.0	e				03	03	17.4	1.0	106			
SPE-2	60.0	Py				03	03	22.6	1.0	142			
SPE-2	60.0	e				03	03	31.4	1.2	159			
WMO	Wichita Mountain Seismology and Observatory, Oklahoma	1467	SPE-2	60.0	LQ			02.8	1.1	(354)	5.03	5.41	218.09
			LPT	1.25	LQ				(13.0)	(384)			
			LPS	1.35	LR				(12.0)	(2123)			
			SPE-2	60.0	e	12	17.8		3.4	(833)			
			SPE-6	10.0	P	03	26.5		1.1	81.6			
			SPE-6	35.0	e	03	34.5		(1.5)	(202)			
			SPE-6	25.0	e	02	42.0		1.35	235			
			SPE-6	25.0	Py	04	29.5		0.9	216			
			SPW	10.5	Lq				(1.8)	(724)			
			SPE	10.0	Lq				(2.3)	(125)			
STXX	Streeter, Texas	1696	LPH	1.0	LQ				15.0	294	4.79	4.84	280.00
			LPS	2.5	LR				15.0	352			
			LPS	24.0	e	17	23		16.0	40.2			
			SPE-1	112	P	03	36.5		0.8	41.2			
			SPE-1	112	e	03	38.1		0.8	55.8			
			SPE-1	112	e	02	40.9		1.0	100			
			SPE-1	112	Py	04	(40.6)		0.8	62.6			
			LPS	00	LR				12.0	00			
			SPE-1	472	P	02	37.0		0.8	32.5			
			SPE-1	472	e	02	38.6		0.8	41.0			
GRXX	Grit, Texas	1689	SPE-2	112	e	03	42.2		1.0	102	4.70	4.74	218.15
			SPE-2	112	Py	02	49.7		0.9	51.9			
			SPE-2	112	e	02	54.2		0.8	42.7			
			SPE-2	112	(Py)	04	50.9		1.2	104			
			LPT	9.05	LQ				15.0	226			
			LPS	1.65	LR				13.0	1054			
			SPE-1	472	e	16	05.8		2.4	224			
			LPS	9.2	e	17	51		12.0	125			

Principal Phases- COMCDORE
Table 2 - Page 1

Code	Station	Distance (km)	Inst.	Magni- fication (k) film x 10	Phase	Observed Travel Time		Period τ (sec)	Maximum Amplitude A/τ	Magnitude (m)		Area (mm ²) LPS
						(min)	(sec)			mb	ms	
01XX	Grit, Texas	1692	SPZ-1	122.5	P	03	37.4	0.5	30.7	4.00	4.73	180.00
			SPZ-1	122.5	e	03	39.3	0.7	36.1			
			SPZ-1	122.5	(Pg)	04	41.8	1.2	152			
			LPT	0.5	LQ			15.0	336			
			LPS	0.5	LR			12.0	1159			
			LPS	0.5	e	18	00	(12.0)	(151)			
			SPZ-1	ee	P	03	37.6	0.9	ee			
			SPZ-1	ee	e	03	42.4	0.8	ee			
			SPZ-1	ee	(Pg)	04	41.8	0.8	ee			
			LPS	0.17	LR			12.0	1519			
02-02	Prince George, British Columbia, Canada	1940	SPZ	54.2	P	04	06.4	1.4	187	5.06		176.47
			SPZ	54.2	e	04	09.5	1.3	511			
			SPZ	54.2	e	04	13.1	1.3	321			
			SPZ	54.2	PP	04	22.7	1.2	187			
			LPR	47.4	S	07	24	20.0	7.3			
			SPR	54.7	Lg			1.8	253			
			SPT	56.9	Lg			1.8	177			
			LPR	47.4	LQ			13.0	209			
			LPT	43.8	LQ			13.0	704			
			LPS	5.6	LR			13.0	474			
03-01	Red Lake, Ontario, Canada	2340	LPS	5.6	e	19	33	12.0	104			116.07
			SPZ	8.85	-	04	45.4	0.9	713	5.95		
			SPZ	8.85	e	05	3.3	1.1	199			
			LPT	51.9	S	08	37	11.0	36.7			
			SPT	8.92	Lg			(1.6)	(183)			
			LPT	51.9	LQ			12.0	163			
			LPS	9.5	LR			12.0	391			
			LPS	93.0	e	21	37	12.0	102			
			SPZ	40.0	P	05	21.8	0.85	115	5.47		
			SPZ	40.0	e	05	23.4	0.9	184			
03-02	Cumberland Plateau Seis- mological Observatory, Tenn.	2730	LPS	4.0	S	09	41	(15.0)	(22.9)			125.26
			LPS	2.6	S	09	41	15.0	44.6			
			SPT		Lg			---	---			
			LPS	4.0	LQ			17.0	83.3			
			LPS	2.0	LR			15.0	824			
			LPS	2.0	e	23	(25)	12.0	158			
			SPZ	7.4	P	05	38.9	1.0	36.9	5.02		
			SPZ	47.4	e	05	40.9	0.85	41.4			
			SPZ	47.1	PP	06	28.0	1.2	36.3			
			SPZ	47.4	PCP	09	(04.2)	0.7	5.4			
03-03	Whitaborne, Yukon Territory Canada	2942	SPZ	36.7	Lg			(2.6)	(151)			350.00
			LPT	12.2	LQ			18.0	100			

WCHK	Whitehorse, Yukon Territory Canada	2942	LPH	4.0	LQ				17.6	83.3		
			LPE	2.0	LR				15.0	824		
			LPE	2.0	e	23	(25)		12.0	158		
			SPZ	47.4	P	05	38.9		1.0	36.9	5.02	
			SPZ	47.4	e	05	40.9		0.85	41.4		
			SPZ	47.4	PP	06	28.0		1.2	36.3		
			SPZ	47.4	PeP	09	(04.2)		0.7	5.4		
			SPT	36.7	Lg				(2.6)	(151)		
			LPT	17.2	LQ				18.0	120		
			LPE	1.94	LR				14.0	590		256.44
EP-WB	Boulton, Maine	4065	LPE	19.3	e	25	11		15.0	43.5		
			SPZ	40.7	P	07	07.7		1.3	222	5.89	
			SPZ	40.7	e	07	20.0		1.0	43.0		
			SPZ	40.7	e	07	23.6		0.95	39.3		
			SPZ	40.7	PP	08	(28.1)		1.4	43.8		
			SPZ	40.7	PeP	09	(30.6)		0.8	13.0		
			LPT	40.9	LQ				(15.0)	(183)		
			LPE	1.88	LR				15.0	229		
			LPE	20.8	e	30	45		17.0	36.5		119.68
			SPZ	54.4	P	07	15.9		1.2	240	5.88	
SWJUB	Schefferville, Quebec Canada	4186	SPZ	54.4	e	07	18.0		1.0	239		
			SPZ	54.4	e	07	20.2		1.0	115		
			SPZ	54.4	PP	08	39.8		0.8	30.4		
			SPR	59.0	Lg				(1.1)	(49.0)		
			SPT	56.2	Lg				(1.5)	(48.0)		
			LPR	28.6	LQ				14.0	62.5		
			LPT	26.2	LQ				13.0	55.9		
			LPE	17.9	LR				14.0	264		
			SPZ-1	134.0	P	07	30.4		0.85	161	5.61	
			SPZ-1	134.0	e	07	33.5		1.0	59.7		
EP-WT	Mould Bay, Northwest Territories, Canada	4364	SPZ-1	134.0	PP	08	59.6		1.40	107		
			SPZ-1	134.0	PeP	09	38.6		0.8	21.5		
			SPZ-1	134.0	e	09	40.2		1.0	31.7		
			SPZ-1	134.0	8	13	27.0		(1.4)	(43.5)		
			SPT	105.0	Lg				2.8	283		
			SPT	105.0	LQ				17.0	139		
			LPT	9.56*	LR				16.0	295		209.21
			LPE	11.47*	LR							

m/sec
 Redshift Values or Phases
 Measurements Made from Playouts
 Maximum Amplitudes Clipped on Film and Tape
 Magnification Unreliable




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9

Code	Station	Distance (km)	Geographic Latitude	Geographic Longitude	Elev. (km)	Computed Azimuth		Installed Azimuth		Large or Small sp	LP Inst.
						Epi. Sta.	Epi. Epi.	Radial	Tang.		
ME-3V	Mina, Nevada	234	38°26'10" N	118°08'53" W	1.52	309°	128°	308°	38°	L	X
ME-UT	Kanab, Utah	288	37°01'22" N	112°49'39" W	1.74	91°	273°	95°	185°	L	X
TE80-860*	Tonto Forest Seismological Observatory, Arizona	536	34°17'12" N	111°16'03" W	1.49	125°	307°	90°	0°	JM	X
MO-ID	Mountain Home, Idaho	660	43°04'19" N	116°15'56" W	0.79	359°	178°	359°	89°	L	X
US80-210*	Pinta Basin Seismo- logical Observatory, Utah	667	40°19'12" N	109°34'07" W	1.60	56°	240°	90°	0°	JM	X
US80-23*	Blue Mountain Seismo- logical Observatory, Oregon	864	44°50'56" N	117°18'20" W	1.19	353°	173°	0°	90°	JM	X
FE-CO	Franktown, Colorado	1049	39°35'12" N	104°27'42" W	1.80	71°	259°	79°	169°	L	X
LAO*	Subarray, MO-10, Montana	1338	46°41'19" N	106°13'20" W	0.90	34°	221°	90°	0°	HSZ	X
SA4TX	San Angelo, Texas	1466	31°49'29" N	101°25'29" W	0.79	109°	298°	118°	208°	Geotech	X
US80-36*	Wichita Mountain Seismo- logical Observatory, N. Mex.	1597	34°43'05" N	98°35'21" W	0.51	94°	285°	90°	0°	JM	X
ST2TX	Stratton, Texas	1606	30°47'32" N	99°26'52" W	0.58	110°	299°	119°	209°	Geotech	X
GR3-XX	Grat, Texas	1689	30°47'11" N	99°24'58" W	0.55	110°	299°	119°	209°	Geotech	X
GR1TX	Grit, Texas	1692	30°46'40" N	99°23'03" W	0.52	110°	299°	119°	209°	Geotech	X
ST1TX	Stratton, Texas	1696	30°45'08" N	99°21'20" W	0.52	110°	299°	119°	209°	Geotech	X
PO-BC*	Prince George, British Columbia, Canada	1940	53°55'50" N	122°31'23" W	0.91	347°	163°	110°	200°	L	X
HK-ON	Red Lake, Ontario, Canada	2340	50°50'20" N	93°40'20" W	0.37	42°	238°	58°	148°	S	X
CP80-28*	Cumberland Plateau Seismo- logical Observatory, Tenn.	2731	35°35'41" N	85°34'13" W	0.57	84°	283°	90°	0°	JM	X
WH2TX	Whitehorse, Yukon Terri- tory, Canada	2242	60°41'41" N	134°58'02" W	0.85	339°	144°	325°	55°	L	X
ME-ME	Houlton, Maine	4065	46°09'43" N	67°59'09" W	0.21	60°	273°	93°	183°	S	X
SV30B*	Schefferville, Quebec, Canada	4186	54°48'39" N	66°45'00" W	0.58	46°	263°	139°	229°	S	X
NP-WT	Mould Bay, Northwest Territories, Canada	4364	76°15'08" N	119°22'18" W	0.06	359°	176°	356°	86°	JME S	X

* Seismometer Not Oriented Toward NTS

Unified Magnitude: $m = \log_{10} (A/T) + B$

where

A = zero to peak ground motion in millimicrons
= $\frac{(\text{mm}) (1000)}{K}$

K

T = signal period in seconds




B = distance factor (see Table below)

mm = record amplitude in millimeters zero to peak

K = magnification in thousands at signal frequency

Table of Distance Factors (B) for Zero Depth

Dist (deg)	B	Dist (deg)	B	Dist (deg)	B	Dist (deg)	B
0°	-	27°	3.5	54°	3.8	80°	3.7
1	-	28	3.6	55	3.8	81	3.8
2	2.2	29	3.6	56	3.8	82	3.9
3	2.7	30	3.6	57	3.8	83	4.0
4	3.1	31	3.7	58	3.8	84	4.0
5	3.4	32	3.7	59	3.8	85	4.0
6	3.6	33	3.7	60	3.8	86	3.9
7	3.8	34	3.7	61	3.9	87	4.0
8	4.0	35	3.7	62	4.0	88	4.1
9	4.2	36	3.6	63	3.9	89	4.0
10	4.3	37	3.5	64	4.0	90	4.0
11	4.2	38	3.5	65	4.0	91	4.1
12	4.1	39	3.4	66	4.0	92	4.1
13	4.0	40	3.4	67	4.0	93	4.2
14	3.6	41	3.5	68	4.0	94	4.1
15	3.3	42	3.5	69	4.0	95	4.2
16	2.9	43	3.5	70	3.9	96	4.3
17	2.9	44	3.5	71	3.9	97	4.4
18	2.9	45	3.7	72	3.9	98	4.5
19	3.0	46	3.8	73	3.9	99	4.5
20	3.0	47	3.9	74	3.8	100	4.4
21	3.1	48	3.9	75	3.8	101	4.3
22	3.2	49	3.8	76	3.9	102	4.4
23	3.3	50	3.7	77	3.9	103	4.5
24	3.3	51	3.7	78	3.9	104	4.6
25	3.5	52	3.7	79	3.8	105	4.7
26	3.4	53	3.7				



Detail Showing Allowance
For Line Width



Pick time of Pn at beginning of "a" half cycle.

Pick amplitude of Pn as maximum " $d/2$ " within 2 or 3 cycles of "c".



Pick amplitudes of Pg and Lg at maximum of corresponding motion.

Seismic Analysis Diagram


APPENDIX II(A)



INSTRUMENT RESPONSE CURVES - LRSM



INSTRUMENT RESPONSE CURVE - LASA



INSTRUMENT RESPONSE CURVES - OTHER SHORT PERIOD

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION
TELEDYNE, INC. ALEXANDRIA, VIRGINIA		Unclassified
		2b. GROUP ---
3. REPORT TITLE		
Long Range Seismic Measurements - COMMODORE		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
Scientific		
5. AUTHOR(S) (Last name, first name, initial)		
Clark, Don M.		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
August 14, 1967	26	2
8a. CONTRACT OR GRANT NO.	8b. ORIGINATOR'S REPORT NUMBER(S)	
F 33657-67-C-1313	193	
a. PROJECT NO.		
VELA T/6702		
c.	8d. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
ARPA Order No. 624	---	
d. ARPA Program Code No. 5810		
9. AVAILABILITY/LIMITATION NOTICES		
This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, APTAC.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY	
---	ADVANCED RESEARCH PROJECTS AGENCY NUCLEAR TEST DETECTION OFFICE WASHINGTON, D. C.	
13. ABSTRACT		
An analysis of seismological data from an underground nuclear explosion as a continuing study to provide information to aid in distinguishing between earthquakes and explosions. A table of travel-times and amplitudes of P, Pg, Lg, and surface waves are included along with other unidentified phases.		

DD FORM 1473
1 JAN 64

Unclassified

Security Classification

Unclassified

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Seismic Magnitude Seismic Travel-Time Seismic Amplitude VELA-UNIFORM Nuclear Tests						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

Unclassified

Security Classification

COMMODORE

MN-NV


MINA, NEVADA

20 MAY 1967

$\Delta = 254$ km



SPZ-HI	UP	15:00:00.0Z
.296 K		
	308°	
SPR-HI		--
.300 K		
	38°	
SPT-HI		--
.300 K		
	UP	
LPZ-HI		--
.171 K		
	308°	
LPR-HI		--
.174 K		
	38°	
LPT-HI		--
.175 K		

00:00.0Z



2

0



21

3

3

4

COMMODORE

RK-ON


RED LAKE, ONTARIO, CANADA


20 MAY 1967

Δ = 2340 km

	UP	15:04:10.0Z
SPZ-HI		
3.84 K	58°	
LPR-HI		
3.84 K	148°	
SPT-HI		
3.87 K		
	UP	
LPZ-HI		
3.8 K		
	58°	
LPR-HI		
13.60 K		
	148°	
LPT-HI		
12.72 K		

4:10.0Z





3


4

4

5


5

6



6

7



7

8

8

9

9


10

10

11

11

12



12

13



COMMODORE

WH2YK


WHITEHORSE, YUKON TERRITORY
CANADA

20 MAY 1967

$\Delta = 2942$ km




00.0 Z




1

2





2

3



3

4




4

5


5


6



6


7






8

9



9

10



10

11

11


12

12

13

13

14



14

15


COMMODORE

SV308


SCHEFFERVILLE, QUEBEC, CANADA

20 MAY 1967

$\Delta = 4186$ km




15:06:40.0 Z



1

2



2

3

3

4

4


5

5

6

6

7



7


8

8

9


9

10




10

11



11

12




12

13

13

14



14

15