

UNCLASSIFIED

AD NUMBER

AD825515

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;  
Administrative/Operational Use; APR 1967. Other requests shall be referred to Naval Ship Research and Development Command, Washington, DC 20007.

AUTHORITY

USNSRDC ltr 18 Apr 1969

THIS PAGE IS UNCLASSIFIED

# NAVAL SHIP RESEARCH AND DEVELOPMENT CENTER

Washington, D.C. 20007



AD825515

## EFFECT OF LENGTH-BEAM RATIO ON THE PERFORMANCE OF A STEPPED PLANING BOAT WITH AN ADJUSTABLE STERN STABILIZER

by


Eugene P. Clement

This document is subject to special  
export controls and each transmittal  
to foreign governments or foreign  
nationals may be made only with prior  
approval of (CO/DIR NSRDC).

HYDROMECHANICS LABORATORY

RESEARCH AND DEVELOPMENT REPORT

~~This document has been approved for public release and sale;  
its distribution is unlimited.~~



August 1967

Report No. 2552

30

## ABSTRACT

Two models of stepped planing boats were tested to determine the effect of change in length-beam ratio. The models were tested with the same adjustable stern stabilizer at several loads and LCG locations. The model with the lower length-beam ratio ( $L_p/B_{PX} = 3.4$ ) had considerably more resistance than the other stepped model ( $L_p/B_{PX} = 4.7$ ) at low speed and slightly less resistance at high speed. The resistance of both stepped designs at high speed was considerably less than that of a representative unstepped planing boat design.

## TABLE OF CONTENTS

ABSTRACT

INTRODUCTION

DESCRIPTION OF THE MODELS

MODEL TESTS AND RESULTS

MODEL 4335-1

MODEL 4461-3

COMPARISON OF MODEL PERFORMANCE

REFERENCES

### LIST OF FIGURES

Figure 1 - Model 4335 as Originally Constructed

Figure 2 - Lines of Model 4335-1

Figure 3 - Lengths of Hull Components and Location of Shaftline,  
Model 4335-1

Figure 4 - Lines of Model 4461-3

Figure 5 - Dimensionless Hull Form Characteristics

Figure 6 - Model of the Plum Stabilizer

Figure 7 - Resistance and  $\alpha$  for Model 4335-1 at Three LCG Positions,  
 $A_p/\nabla^{2/3} = 7.0$

Figure 8 - Wetted Lengths for Model 4335-1 at Three LCG Positions,  
 $A_p/\nabla^{2/3} = 7.0$

Figure 9 - Resistance, Draft,  $\alpha$ , and Stabilizer Position for Model  
4461-3 at Three LCG Positions,  $A_p/\nabla^{2/3} = 6.84$

Figure 10- Resistance, Draft,  $\alpha$ , and Stabilizer Position for Model  
4461-3 at Two LCG Positions,  $A_p/\nabla^{2/3} = 6.05$

Figure 11 - Wetted Lengths for Model 4461-3 at Three LCG Positions,

$$A_p / \nabla^{2/3} = 6.84$$

Figure 12 - Wetted Lengths for Model 4461-3 at Two LCG Positions,

$$A_p / \nabla^{2/3} = 6.05$$

Figure 13 - Percent of Weight Carried by Stabilizer of Model 4461-3

Figure 14 - Comparison of Resistance,  $\alpha$ , and Wetted Surface for the  
Two Stepped Hulls and a Conventional Planing Boat Design

Table 1 - Planing Bottom Dimensions and Coefficients for Models 4124C,  
4335-1, and 4461-3

## NOTATION

$A_P$	Projected bottom area, excluding area of external spray strips (area bounded by chines and transom in plan view)
a.b.	Afterbody
$B_P$	Beam or breadth over chines, excluding external spray strips
$B_{PA}$	Mean breadth over chines, $A_P/L_P$
$B_{PT}$	Breadth over chines at transom
$B_{PX}$	Maximum breadth over chines, excluding external spray strips
B.L.	Baseline
$C_f$	Coefficient of frictional resistance
EHP	Effective horsepower
$F_\nabla$	Froude number based on volume, in any consistent units $v/\sqrt{g \nabla^{1/3}}$
g	Acceleration due to gravity
H	Draft to point of main step
$L_P$	Overall length of the area, $A_P$ , measured parallel to the baseline
LCG	Longitudinal center of gravity
R	Total resistance
S	Area of wetted surface (this is the actual wetted surface underway including the wetted bottom area of external spray strips; however, the area wetted by spray is excluded)
v	Speed in feet per second
V	Speed in knots
w	Weight density of water (weight per unit volume)
$WL_C$	Intersection of forebody chine with solid water, measured from step
$WL_K$	Wetted length of forebody keel, measured from step
$WL_{SP}$	Intersection of forebody chine with spray, measured from step

- $\alpha$  Angle with horizontal of tangent to straight portion of forebody keel in degrees
- $\beta$  Deadrise angle of planing bottom in degrees (this angle is obtained by approximating each body plan section by a straight line)
- $\lambda$  Linear ratio, ship to model
- $W$  Displacement at rest, weight of
- $\rho$  Mass density of water
- $\nabla$  Displacement at rest, volume of

Units are feet, pounds, seconds, except where shown otherwise.

#### Subscripts

- ab Afterbody
- fb Forebody
- o Zero speed
- m Model
- s Ship

## INTRODUCTION

For a number of years, the Naval Ship Research and Development Center has been working on a particular configuration of stepped planing boat and conducting model tests to evaluate the effects of changes in the various parameters of the design. This design has a shallow step at midlength and an adjustable planing surface, or stabilizer, at the stern. The stabilizer is of the type devised by John Plum of the Center staff. At high speeds, the flow separates from the hull bottom aft of the step and the hull is then supported dynamically by a portion of the forebody and by the adjustable stabilizer. Since the afterbody bottom is unwetted at high speeds, the wetted area - and accordingly the resistance - are considerably less than for the conventional (unstepped) planing boat.

Reference 1 presented the lines and model test results for the first model of this type which was designed and extensively tested at the Center (Model 4124). Subsequently, two additional models (4335-1 and 4461) were built and tested. The latter two differ from Model 4124 chiefly in the fact that they have considerably more deadrise in the bow. These two have identical body plan sections but differ in length-beam ratio. The ratio of chine length to average chine beam is 6.9 for Model 4335-1 and 5.0 for Model 4461. Additional dimensions and coefficients for all three models are given in Table 1.

This report presents the results of resistance tests of Models 4335-1 and 4461 at various weights and LCG locations. Comparisons of the results for the two models show the effect of change in length-beam ratio on the performance of this configuration of stepped planing boat.

## DESCRIPTION OF THE MODELS EMPLOYED

Figure 1 shows photographs of Model 4335, as originally constructed. Initial tests of the original model indicated that the angle of 3.0 degrees between forebody and afterbody keels was insufficient; it was therefore increased to 4.7 degrees (the same as for Model 4124 D). The hull lines of the revised model (designated 4335-1) are shown in Figure 2. The lengths of the hull components, and the location of the shaftline, are shown in Figure 3. Some preliminary testing of Model 4461 was done with different configurations of the main step. A satisfactory configuration was found, and for this case, the model was designated No. 4461-3. The lines of Model 4461-3 are shown in Figure 4.

The value of the ratio  $L_p/B_{PX}$  was 4.72 for Model 4335-1 and 3.43 for Model 4461-3. Both models consisted entirely of developable surfaces. Model 4335-1 was fitted with 1/8-inch square spray strips along the forebody and afterbody chines and Model 4461-3 was fitted with 3/16-inch spray strips. To reduce the suction forces at low speeds, each model was equipped with two 9/32-inch-diameter air ducts running from inside the hull to the vertical face of the after step. The dimensionless hull form characteristics for the models are given in Figure 5. It can be seen that these curves are nearly the same for the two models.

Both models were tested with the same model of a Plum stabilizer; the stabilizer is essentially formed as the intersection of two cylindrical surfaces meeting at an angle of 3 degrees; see Figure 6.

As explained in Reference 1, the stabilizer is connected to a piston working in a pneumatic cylinder, so that its vertical position can be controlled by compressed air. When the boat is at rest or moving at low

speeds, the stabilizer is held against the bottom of the stern extension. In this position, the lower surface of the stabilizer is approximately parallel to the afterbody keel. As the stabilizer is lowered it automatically pivots in such a direction as to increase its angle of attack until it lies flush against a longitudinal member (the foot) which is rigidly attached to the piston rod of the actuating mechanism. The moment at which the stabilizer lies against the foot coincides with the moment the leading edge of the stabilizer comes clear of the hull bottom. Thereafter as the stabilizer is lowered further it remains against the foot and accordingly at a fixed angle with respect to the forebody keel. For the tests of Model 4335-1 the bottom of the stabilizer, when lowered, was at + 1.8 degrees with respect to the forebody keel, and for the tests of Model 4461-3 the bottom of the stabilizer, when lowered, was at -  $\frac{1}{4}$  degree with respect to the forebody keel. The design has the least resistance at the lower speeds with the stabilizer in the retracted position. At speeds above  $F_{\nabla}$  equals about 1.8, however, minimum resistance is obtained with successively lower positions of the stabilizer. Additional details concerning the operation of the stabilizer and a drawing of the actuating mechanism are given in Reference 1.

## MODEL TESTS AND RESULTS

The models were towed in smooth water in the shaftlines shown in Figures 3 and 4, respectively. The only appendages attached for these tests were spray strips and the stabilizer. The models were tested at various displacements and LCG locations. The quantities measured were resistance, trim, rise, and forebody and afterbody wetted lengths.

In general, it was attempted to adjust the vertical position of the stabilizer to the position for minimum resistance at each test speed. In this way, a curve of minimum resistance versus speed was obtained. Data from the tests of Model 4124 provided guidance in selecting the stabilizer settings for minimum resistance.

Model 4335-1 was tested at a model weight of 158.5 pounds which corresponds to a value of the area coefficient  $A_p/\nabla^{2/3}$  of 7.0. Tests were made at three different LCG locations. Figures 7 and 8 give the model test results in dimensionless form. The forebody and afterbody wetted lengths presented in Figure 8 were nondimensionalized by dividing the observed wetted lengths by the overall length of forebody and afterbody, respectively. The overall forebody and afterbody lengths of Model 4335-1 are given in Figure 3.

The resistance data of Figure 7 show that for this stepped hull with a stabilizer for trim control, the resistance at the higher speeds (above a  $F_\nabla$  of about 2.4) is almost entirely unaffected by a shift in LCG location. The wetted length data of Figure 8 show that the wetted area of the afterbody bottom begins to diminish at about  $F_\nabla$  equals 1.6 (this coincides with ventilation of the step). At all speeds above  $F_\nabla = 3$ , the afterbody bottom is entirely dry. The data also show that the wetted length of the forebody chine will diminish to zero at about  $F_\nabla$  equals 4.8. At about that speed, therefore, the stagnation line will intersect the step, the main spray blister will wet the afterbody, and a significant drag rise will result. Satisfactorily low resistance can be maintained up to higher speeds, however, by changing the transverse step to one which is swept back, as explained in Reference 2.

MODEL 4461-3

Model 4461-3 was tested at weights corresponding to area coefficients of 6.85 and 6.05. The corresponding model weights were 165.3 and 198.4 pounds, respectively. In addition, tests were made at several LCG locations. Model values of resistance-weight ratio and angle of attack for the two test weights are given in Figures 9 and 10. These figures also include data showing the draft to the point of the step and the distance which the stabilizer was lowered. Both of those quantities were non-dimensionalized by dividing by  $\nabla^{1/3}$ . Wetted length data for the two displacements, in the same dimensionless form as was utilized for Model 4335-1, are given in Figures 11 and 12. Values of the percent of weight carried by the stabilizer are given in Figure 13.

In addition to presenting the performance data corresponding to optimum stabilizer position, Figures 10 and 12 include data (identified by symbols with tails) for a test in which the stabilizer was retracted at all speeds.

## COMPARISON OF MODEL PERFORMANCE

Figure 14 compares the resistance, trim, and wetted area data for the two stepped designs and for a conventional planing boat design. The resistance data have been corrected to correspond to 100,000 pound displacement. It can be seen that decreasing the length-beam ratio ( $L_P/B_{PA}$ ) of the stepped design from 6.9 to 5.0 reduced the resistance somewhat at high speeds (presumably because of the increase in the aspect ratio of the planing surface), but that this was accompanied by an appreciable increase in the low speed resistance. At a value of  $F_{\nabla} = 4.8$ , the unstepped design has 30 percent more resistance than the stepped design, represented by Model 4335-1.

TABLE 1

Planing Bottom Dimensions and Coefficients  
for Models 4124C, 4335-1, and 4461-3

	<u>Model No.</u>		
	<u>4124C</u>	<u>4335-1</u>	<u>4461-3</u>
$L_p$ , feet	9.14	9.48	8.09
$B_{PX}$ , feet	2.00	2.01	2.35
$B_{PA}$ , feet	1.35	1.38	1.62
$A_p$ , feet <sup>2</sup>	12.29	13.1	13.1
$L_p / B_{PX}$	4.57	4.72	3.43
$L_p / B_{PA}$	6.80	6.9	5.0
Location of main step, percent $L_p$	49	47	47
Deadrise at main step, degrees	16	16	16
Angle of a.b. keel, degrees	3.5	4.7	4.5
Centroid of $A_p$ , percent $L_p$	-	52.4	-
$B_{PX} / B_{PA}$	1.48	1.46	1.45
$B_{PT} / B_{PX}$	0.34	0.38	0.38
Angle of a.b. chine in plan view, degrees	5.0	6.0	7.6

## REFERENCES

1. Clement, E. P., "Model Tests of a Stepped Planing Boat with an Adjustable Stern Stabilizer," Naval Ship Research and Development Center Report 2414 (May 1967)
2. Clement, E. P., "The Planing Characteristics of a 15-Degree Deadrise Surface with Circular-Arc Camber," David Taylor Model Basin Report 2298 (Sep 1966)







Figure 1 - Model 4335 as Originally Constructed

TMB Model No. 4335-1

$L_p/B_{px} = 4.72$

Model Scale in Inches



Enlarged Step Section





Figure 2 - Lines of Model 4335-1




Figure 3 - Lengths of Hull Components and Location of Shaftline, Model 4335-1





Figure 4a - Profile and Plan Views

Figure 4 - Lines of Model 4461-3

MODEL 4461-3

MODEL SCALE IN INCHES

0 1 2 3 4 5 6 7 8 9 10 11 12





Figure 4b - Body Plan




Figure 5a - Model 4335-1




Figure 5b - Model 4461-3

Figure 5 - Dimensionless Hull Form Characteristics




Figure 6 - Model of the Plum Stabilizer




Figure 7 - Resistance and  $\alpha$  for Model 4335-1 at Three LCG Positions. Ap/v223-7.0




Figure 8 - Wetted Lengths for Model 4335-1 at Three LCG Positions,  $A_p/V^2 = 7.0$




Figure 9 - Resistance, Draft,  $\alpha$ , and Stabilizer Position for Model 4461-3 at Three LCG Positions,  $Ap/v^2 = 6.84$




Figure 10 - Resistance, Draft,  $\alpha$ , and Stabilizer Position for Model 4461-3 at Two LCG Positions,  $A_p/v^{2.0} = 6.05$




Figure 11 - Wetted Lengths for Model 4461-3 at Three LCG Positions,  $A_p/v^{2.5} = 6.84$




Figure 12 - Wetted Lengths for Model 4461-3 at Two CG Positions,  $A_p/v^{3/2} = 6.05$




Figure 13 - Percent of Weight Carried by Stabilizer of Model 4461-3




Figure 14 - Comparison of Resistance,  $\alpha$ , and Wetted Surface for the Two Stepped Hulls and a Conventional Planing Boat Design

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
<small>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</small>		
1. ORIGINATING ACTIVITY (Corporate author) Naval Ship Research and Development Center Washington, D. C. 20007		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE EFFECT OF LENGTH-BEAM RATIO ON THE PERFORMANCE OF A STEPPED PLANING BOAT WITH AN ADJUSTABLE STERN STABILIZER		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Final		
5. AUTHOR(S) (Last name, first name, initial) Eugene P. Clement		
6. REPORT DATE August 1967	7a. TOTAL NO. OF PAGES 32	7b. NO. OF REFS 2
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S) 2552
b. PROJECT NO. S-F 013 01 13		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
c. Task 11274		
d.		
10. AVAILABILITY/LIMITATION NOTICES <del>This document has been processed for automatic downgrading and declassification.</del>		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY NAVY DEPARTMENT
13. ABSTRACT <p>Two models of stepped planing boats were tested to determine the effect of change in length-beam ratio. The models were tested with the same adjustable stern stabilizer at several loads and LCG locations. The model with the lower length-beam ratio (<math>L_P/B_{BX} = 3.4</math>) had considerably more resistance than the other stepped model (<math>L_P/B_{PX} = 4.7</math>) at low speed and slightly less resistance at high speed. The resistance of both stepped designs at high speed was considerably less than that of a representative unstepped planing boat design.</p> <p style="text-align: center;">This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of (<u>NSRAC</u>).</p>		

DD FORM 1473  
1 JAN 64

UNCLASSIFIED

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
	Stepped planing hulls					
Planing boats						
Adjustable planing stabilizer						
Trim control for planing boats						
Length-beam ratio						

## INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).
10. **AVAILABILITY LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, roles, and weights is optional.

**SUPPLEMENTARY**

**INFORMATION**

NOTICE OF CHANGES IN CLASSIFICATION,  
DISTRIBUTION AND AVAILABILITY

69-18 15 SEPTEMBER 1969

AD-825 515  
Naval Ship Research  
and Development  
Center,  
Washington, D. C.  
Hydromechanics Lab.  
Research and  
development rept.  
Rept. no. NSRDC-2552  
Aug 67

No Foreign without  
approval of  
Commanding Officer,  
Naval Ship  
Research and  
Development Center,  
Washington, D. C.

No limitation

USNSRDC ltr,  
18 Apr 69