

UNCLASSIFIED

AD NUMBER
AD889893
LIMITATION CHANGES
TO: Approved for public release; distribution is unlimited.
FROM: Distribution authorized to U.S. Gov't. agencies only; Test and Evaluation; DEC 1971. Other requests shall be referred to Air Force Armament Laboratory, DLGC, Eglin AFB, FL 32542.
AUTHORITY
AFATL ltr, 24 Jun 1974

THIS PAGE IS UNCLASSIFIED

AEDC-TR-71-261

AFATL-TR-71-152

DEC 29 1971

AUG 15 1985

cy.2



**SEPARATION CHARACTERISTICS OF THE
M-117 RETARDED BOMB, FINNED BLU-1C/B BOMB,
AND SUU-42/A DISPENSER FROM THE A-7D AIRCRAFT
AT MACH NUMBERS FROM 0.33 TO 0.95**

David W. Hill, Jr.

ARO, Inc.

December 1971

This document is for internal use only; its distribution is unlimited.

its distribution is unlimited.

*Re TAB 74-17
16 August 74*

Distribution limited to U.S. Government agencies only; this report contains information on test and evaluation of military hardware; December 1971; other requests for this document must be referred to Air Force Armament Laboratory (DLGC), Eglin AFB, Florida 32542.

**TECHNICAL REPORTS
FILE COPY**

**PROPULSION WIND TUNNEL FACILITY
ARNOLD ENGINEERING DEVELOPMENT CENTER
AIR FORCE SYSTEMS COMMAND
ARNOLD AIR FORCE STATION, TENNESSEE**

PROPERTY OF THE UNITED STATES

AEDC 71-261

F40600-7200-0000

NOTICES

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

**SEPARATION CHARACTERISTICS OF THE
M-117 RETARDED BOMB, FINNED BLU-1C/B BOMB,
AND SUU-42/A DISPENSER FROM THE A-7D AIRCRAFT
AT MACH NUMBERS FROM 0.33 TO 0.95**

**David W. Hill, Jr.
ARO, Inc.**

This document has been approved for public release
its distribution is unlimited. *Per TAB 74-13
H2 16 Aug; 74.*

Distribution limited to U.S. Government agencies only;
this report contains information on test and evaluation
of military hardware; December 1971; other requests for
this document must be referred to Air Force Armament
Laboratory (DLGC), Eglin AFB, Florida 32542.

FOREWORD

The work reported herein was sponsored by the Air Force Armament Laboratory (DLGC/Lt S. C. Braud), Armament Development and Test Center, Air Force Systems Command (AFSC), under Program Element 27121F, System 337A.

The test results presented were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), AFSC, Arnold Air Force Station, Tennessee, under Contract F40600-72-C-0003. The test was conducted from September 11 through 16, 1971, under ARO Project No. PC0165. The manuscript was submitted for publication on November 4, 1971.

This technical report has been reviewed and is approved.

George F. Garey
Lt Colonel, USAF
AF Representative, PWT
Directorate of Test

Duncan W. Rabey, Jr.
Colonel, USAF
Director of Test

ABSTRACT

Tests were conducted in the Aerodynamic Wind Tunnel (4T) using 0.05-scale models to investigate the separation characteristics of the M-117 retarded bomb, finned BLU-1C/B bomb, and SUU-42/A dispenser when released from various wing pylon locations on the A-7D aircraft. Captive trajectory data were obtained at Mach numbers from 0.33 to 0.95 at simulated pressure altitudes from 4000 to 7000 ft. The parent-aircraft angle of attack was varied from 1.8 to 12.3 depending on Mach number, climb angle, and simulated altitude. At selected test conditions, parent climb angles of -70 deg were simulated. In general, for the trajectory intervals of the test, most of the stores separated from the parent aircraft without store-to-parent contact.

This document has been approved for public release
its distribution is unlimited.

Distribution limited to U.S. Government agencies only;
this report contains information on test and evaluation
of military hardware; December 1971; other requests for
this document must be referred to Air Force Armament
Laboratory (DLGC), Eglin AFB, Florida 32542.

*Per TAB 7413
Std 16 August 74*

CONTENTS

	<u>Page</u>
ABSTRACT	iii
NOMENCLATURE	vii
I. INTRODUCTION	1
II. APPARATUS	
2.1 Test Facility	1
2.2 Test Articles	2
2.3 Instrumentation	2
III. TEST DESCRIPTION	
3.1 Test Conditions	2
3.2 Data Acquisition	3
3.3 Corrections	3
3.4 Precision of Data	4
IV. RESULTS AND DISCUSSION	
4.1 General	4
4.2 Trajectories for Various Store and Wing-Loading Configurations	4

APPENDIXES

I. ILLUSTRATIONS

Figure

1. Isometric Drawing of a Typical Store Separation Installation and a Block Diagram of the Computer Control Loop	9
2. Schematic of the Tunnel Test Section Showing Model Location	10
3. Sketch of the A-7D Parent-Aircraft Model	11
4. Details and Dimensions of the A-7D Model Pylons	12
5. Details and Dimensions of the TER Model	13
6. Details and Dimensions of the MER Model	14
7. Details and Dimensions of the M-117R Model	15
8. Details and Dimensions of the BLU-1C/B Unfinned Model	16
9. Details and Dimensions of the BLU-1C/B Finned Model	17
10. Details and Dimensions of the SUU-42/A Model	18
11. Tunnel Installation Photograph Showing Parent Aircraft, Store, and CTS	19
12. Schematic of the TER and MER Store Stations and Orientations	20
13. Ejector Force Functions	
a. Function T_1 for M-117R on MER or TER	21
b. Function T_2 for BLU-1C/B on MAU-12 Pylon	21
c. Function T_3 for Empty SUU-42/A on MAU-12 Pylon	22

Figure**Page**

14. Effect of Mach Number and Climb Angle on the Separation Trajectories of the M-117R from Center Pylon Station, Inboard and Outboard Pylon Empty	
a. Configuration 1L	23
b. Configuration 2L	24
c. Configuration 3L	25
d. Configuration 4L	26
e. Configuration 5L	27
f. Configuration 6R	28
g. Configuration 7R	29
15. Effect of Mach Number and Climb Angle on the Separation Trajectories of the M-117R from Center Pylon Station, Finned BLU-1C/B on Inboard and Outboard Pylon	
a. Configuration 8R	30
b. Configuration 9R	31
c. Configuration 10R	32
d. Configuration 11R	33
e. Configuration 12R	34
16. Effect of Mach Number on the Separation Trajectories of M-117R from Center Pylon Station, Outboard Pylon Empty, and M-117R on Inboard Pylon	
a. Configuration 13R	35
b. Configuration 14R	36
c. Configuration 15R	37
d. Configuration 16R	38
e. Configuration 17R	39
f. Configuration 18R	40
17. Effect of Mach Number on the Separation Trajectories of the M-117R from Center Pylon Station, Unfinned BLU-1C/B on Outboard and Inboard Pylons	
a. Configuration 19L	41
b. Configuration 20L	42
18. Effect of Mach Number on the Separation Trajectories of the M-117R from Center Pylon Station, M-117R on Inboard, and SUU-42/A on Outboard Pylon	
a. Configuration 21L	43
b. Configuration 22L	44
c. Configuration 23L	45
d. Configuration 24L	46
e. Configuration 25L	47
f. Configuration 26L	48
19. Effect of Mach Number on the Separation Trajectories of the SUU-42/A from the Outboard Pylon, MER on Center Pylon, and Inboard Pylon Empty, Configuration 27R	
	49

<u>Figure</u>	<u>Page</u>
20. Effect of Mach Number on the Separation Trajectories of the SUU-42/A from the Outboard Pylon, MER with M-117R on Center Pylon, and an M-117R on Inboard Pylon, Configuration 28L	50
21. Effect of Mach Number and Climb Angle on the Separation Trajectories of the Finned BLU-1C/B from the Inboard Pylon, MER on Center Pylon, and Finned BLU-1C/B on Outboard Pylon	
a. Configuration 29L	51
b. Configuration 30R	52

II. TABLES

I. Full-Scale Store Parameters Used in Trajectory Calculations	53
II. Maximum Full-Scale Position Uncertainties Caused by Balance Inaccuracies	54
III. Aircraft Wing-Loading Configuration	55

NOMENCLATURE

BL	Aircraft buttock line from plane of symmetry, in., model scale
b	Store reference dimension, 1.688 ft, full scale
C_m	Store pitching-moment-coefficient, referenced to the store cg, pitching moment/ $q_\infty S b$
C_{m_q}	Store pitch-damping derivative, $dC_m/d(qb/2V_\infty)$
C_n	Store yawing-moment coefficient, referenced to the store cg, yawing moment/ $q_\infty S b$
C_{n_r}	Store yaw-damping derivative, $dC_n/d(rb/2V_\infty)$
F_Z	MER/TER ejector force, lb
F_{Z_1}	Pylon forward ejector force, lb
F_{Z_2}	Pylon aft ejector force, lb
H	Pressure altitude, ft
I_{yy}	Full-scale moment of inertia about the store Y_B axis, slug-ft ²
I_{zz}	Full-scale moment of inertia about the store Z_B axis, slug-ft ²

M_∞	Free-stream Mach number
$\bar{m}$	Full-scale store mass, slugs
p_∞	Free-stream static pressure, psfa
q	Store angular velocity about the Y_B axis, radians/sec
q_∞	Free-stream dynamic pressure, psf
$\dot{r}$	Store angular velocity about the Z_B axis, radians/sec
S	Store reference area, ft^2 , full scale
t	Real trajectory time from initiation of trajectory, sec
V_∞	Free-stream velocity, ft/sec
WL	Aircraft waterline from reference horizontal plane, in., model scale
X	Separation distance of the store cg parallel to the flight axis system X_F direction, ft, full scale measured from the prelaunch position
X_{cg}	Full-scale cg location, ft, from nose of store
X_L	Ejector piston location relative to the store cg, positive forward of store cg, ft, full scale
X_{L1}	Forward ejector piston location relative to the store cg, positive forward of store cg, ft, full scale
X_{L2}	Aft ejector piston location relative to the store cg, positive forward of store cg, ft, full scale
Y	Separation distance of the store cg parallel to the flight axis system Y_F direction, ft, full scale measured from the prelaunch position
Z	Separation distance of the store cg parallel to the flight-axis system Z_F direction, ft, full scale measured from the prelaunch position
ZE	Ejector stroke length, ft, full scale
α	Parent-aircraft model angle of attack relative to the free-stream velocity vector, deg
θ	Angle between the store longitudinal axis and its projection in the X_F - Y_F plane, positive when store nose is raised as seen by pilot, deg

$\bar{\theta}$	Simulated parent-aircraft climb angle. Angle between the flight direction and the earth horizontal, deg, positive for increasing altitude
ψ	Angle between the projection of the store longitudinal axis in the X_F - Y_F plane and the X_F axis, positive when the store nose is to the right as seen by the pilot, deg
ϕ	Angle between the projection of the store lateral axis in the Y_F - Z_F plane and the Y_F axis, positive for clockwise rotation when looking upstream, deg

FLIGHT-AXIS SYSTEM COORDINATES

Directions

X_F	Parallel to the free-stream wind vector, positive direction is forward as seen by the pilot
Y_F	Perpendicular to the X_F and Z_F directions, positive direction is to the right as seen by the pilot
Z_F	In the aircraft plane of symmetry, perpendicular to the free-stream wind vector, positive direction is downward

The flight-axis system origin is coincident with the aircraft cg and remains fixed with respect to the parent aircraft during store separation. The X_F , Y_F , and Z_F coordinate axes do not rotate with respect to the initial flight direction and attitude.

STORE BODY-AXIS SYSTEM COORDINATES

Directions

X_B	Parallel to the store longitudinal axis, positive direction is upstream in the prelaunch position
Y_B	Perpendicular to the store longitudinal axis, and parallel to the flight-axis system X_F - Y_F plane when the store is at zero roll angle, positive direction is to the right looking upstream when the store is at zero yaw and roll angles
Z_B	Perpendicular to both the X_B and Y_B axes, positive direction is downward as seen by the pilot when the store is at zero pitch and roll angles.

The store body-axis system origin is coincident with the store cg and moves with the store during separation from the parent airplane. The X_B , Y_B , and Z_B coordinate axes rotate with the store in pitch, yaw, and roll so that mass moments of inertia about the three axes are not time-varying quantities.

SECTION I INTRODUCTION

A captive trajectory test was conducted in the Aerodynamic Wind Tunnel (4T), Propulsion Wind Tunnel Facility, to determine the separation characteristics of the M-117R bomb, finned BLU-1C/B bombs, and a SUU-42/A dispenser. Separation trajectories were initiated from the carriage position with simulated ejector forces acting on the stores.

To determine the separation trajectories, 0.05-scale models of the A-7D aircraft and various stores were employed. The flight conditions simulated were Mach numbers from 0.33 to 0.95 and altitudes from 4000 to 7000 ft. At selected test conditions, parent-aircraft climb angles of 0 and -70 deg were simulated. The separation trajectories were initiated from various wing pylon locations on the parent aircraft. The ejector forces used were time-variant functions provided by the Air Force Armament Laboratory (AFATL).

SECTION II APPARATUS

2.1 TEST FACILITY

The Aerodynamic Wind Tunnel (4T) is a closed-loop, continuous flow, variable density tunnel in which the Mach number can be varied from 0.1 to 1.3. At all Mach numbers, the stagnation pressure can be varied from 300 to 3700 psfa. The test section is 4 ft square and 12.5 ft long with perforated, variable porosity (0.5- to 10-percent open) walls. It is completely enclosed in a plenum chamber from which the air can be evacuated, allowing part of the tunnel airflow to be removed through the perforated walls of the test section.

For store separation testing, two separate and independent support systems are used to support the models. The parent-aircraft model is inverted in the test section and supported by an offset sting attached to the main pitch sector. The store model is supported by the captive trajectory support (CTS) which extends down from the tunnel top wall and provides store movement (six degrees of freedom) independent of the parent-aircraft model. An isometric drawing of a typical store separation installation is shown in Fig. 1, Appendix I.

Also shown in Fig. 1 is a block diagram of the computer control loop used during captive trajectory testing. The analog system and the digital computer work as an integrated unit and, utilizing required input information, control the store movement during a trajectory. Store positioning is accomplished by use of six individual d-c electric motors. Maximum translational travel of the CTS is ± 15 in. from the tunnel centerline in the lateral and vertical directions and 36 in. in the axial direction. Maximum angular displacements are ± 45 deg in pitch and yaw and ± 360 deg in roll. A more complete description of the test facility can be found in the Test Facilities Handbook.¹ A schematic

¹Test Facilities Handbook (Ninth Edition). "Propulsion Wind Tunnel Facility. Vol. 4," Arnold Engineering Development Center, July 1971.

showing the test section details and the location of the models in the tunnel is shown in Fig. 2.

2.2 TEST ARTICLES

The test articles were 0.05-scale models of the A-7D parent aircraft and the various stores. A sketch showing the basic dimensions of the A-7D parent model is shown in Fig. 3. Details and dimensions of the pylons, Multiple Ejection Rack (MER), and Triple Ejection Rack (TER) are shown in Figs. 4, 5, and 6, and the store models are shown in Figs. 7 through 10.

The A-7D parent model was geometrically similar to the full-scale airplane except for some modifications incident to the wind-tunnel installation and CTS operation. Horizontal tail surfaces were removed because of interference with the CTS support. The parent model was inverted in the tunnel and attached by a 23-deg offset sting to the main sting support system (Fig. 2). Figure 11 shows a typical tunnel installation photograph of the parent aircraft and store model.

The A-7D aircraft has three pylon stations on each wing. The mounting surfaces of all three pylons are inclined at a 3.0-deg nose-down angle with respect to the aircraft waterline.

The store models were mounted on an internal balance which was an integral part of a 30-deg offset sting. The sting was in turn connected to the CTS support (Figs. 2 and 11).

2.3 INSTRUMENTATION

A five-component, internal strain-gage balance was used to obtain the force and moment data on the store models. Translational and angular positions of the store models were obtained from the CTS analog outputs. The parent-aircraft angle of attack was set using an absolute angle-of-attack indicator located in the nose of the parent model. The CTS was electrically connected to automatically stop and give a visual indication if the store model or sting contacted the parent-aircraft surface. Spring-loaded plungers were located in the pylons, MER, and TER in order to provide a position indication when the store model was in the launch position. The plunger circuit was independent of the parent-aircraft grounding circuit.

SECTION III

TEST DESCRIPTION

3.1 TEST CONDITIONS

Separation trajectory data were obtained at Mach numbers from 0.33 to 0.95. Tunnel dynamic pressure ranged from 250 psf at $M_\infty = 0.33$ to 500 psf at $M_\infty = 0.95$, and tunnel stagnation temperature was maintained near 110°F.

Tunnel conditions were held constant at the desired Mach number and stagnation pressure while data for each trajectory were obtained. The trajectories were terminated when the store or sting contacted the parent-aircraft model or when a CTS tunnel limit was reached.

3.2 DATA ACQUISITION

To obtain a trajectory, test conditions were established in the tunnel and the parent model was positioned at the desired angle of attack. The store model was then oriented to a position corresponding to the store carriage location. After the store was set at the desired initial position, operational control of the CTS was switched to the digital computer which controlled the store movement during the trajectory through commands to the CTS analog system (see block diagram, Fig. 1). Data from the wind tunnel, consisting of measured model forces and moments, wind-tunnel operating conditions, and CTS positions, were input to the digital computer for use in the full-scale trajectory calculations.

The digital computer was programmed to solve the six-degree-of-freedom equations to calculate the angular and linear displacements of the store relative to the parent-aircraft pylon. In general, the program involves using the last two successive measured values of each static aerodynamic coefficient to predict the magnitude of the coefficients over the next time interval of the trajectory. These predicted values are used to calculate the new position and attitude of the store at the end of the time interval. The CTS is then commanded to move the store model to this new position and the aerodynamic loads are measured. If these new measurements agree with the predicted values, the process is continued over another time interval of the same magnitude. If the measured and predicted values do not agree within the desired precision, the calculation is repeated over a time interval one-half the previous value. This process is repeated until a complete trajectory has been obtained.

In applying the wind-tunnel data to the calculations of the full-scale store trajectories, the measured forces and moments are reduced to coefficient form and then applied with proper full-scale store dimensions and flight dynamic pressure. Dynamic pressure was calculated using a flight velocity equal to the free-stream velocity component plus the components of store velocity relative to the aircraft, and a density corresponding to the simulated altitude.

The initial portion of each trajectory from the carriage position incorporated simulated ejector forces in addition to the measured aerodynamic forces acting on the store. The ejector force functions for the stores are presented in Fig. 13. The ejector force was considered to act perpendicular to the rack or pylon mounting surface. The locations of the applied ejector forces and other full-scale store parameters used in the trajectory calculations are listed in Table I, Appendix II.

3.3 CORRECTIONS

Balance, sting, and support deflections caused by the aerodynamic loads on the store models were accounted for in the data reduction program to calculate the true store-model

angles. Corrections were also made for model weight tares to calculate the net aerodynamic forces on the store model.

3.4 PRECISION OF DATA

The trajectory data are subject to error from several sources including tunnel conditions, balance measurements, extrapolation tolerances allowed in the predicted coefficients, computer inputs, and CTS positioning control. Maximum error in the CTS position control was ± 0.05 in. for the translational settings and ± 0.15 deg for angular displacement settings in pitch and yaw. Extrapolation tolerances were ± 0.10 for each of the aerodynamic coefficients. The maximum uncertainties in the full-scale position data caused by the balance precision limitations are given in Table II. The estimated uncertainty in setting Mach number was no greater than ± 0.003 , and the uncertainty in parent-model angle of attack was estimated to be ± 0.1 deg.

SECTION IV RESULTS AND DISCUSSION

4.1 GENERAL

The data presented herein were obtained to show the effects of wing-loading configuration and Mach number on the separation trajectories of the M-117R bomb, finned BLU-1C/B bomb, and the SUU-42/A dispenser. The time variant ejector forces and store parameters shown in Fig. 13 and Table I, respectively, were used in determining the trajectories.

In the trajectory data, the full-scale linear and angular displacements of the store relative to the carriage positions on the rack or pylon are presented versus full-scale trajectory time.

Table III describes the wing-loading configurations used in the data presentation. The L or R notation for each configuration number denotes left or right wing, respectively.

4.2 TRAJECTORIES FOR VARIOUS STORE AND WING-LOADING CONFIGURATIONS

Figures 14 through 18 show the effect of Mach number and climb angle on trajectories for the M-117R store released from the center pylon station. The M-117R was released at various stations on the MER or TER with the inboard and outboard pylons empty (Fig. 14), with dummy finned BLU-1C/B stores on the inboard and outboard pylons (Fig. 17), and with a dummy M-117R on the inboard pylon and a SUU-42/A on the outboard pylon (Fig. 18).

Figures 19 and 20 show the effect of Mach number on the separation trajectories of the SUU-42/A from the outboard pylon. Figure 21 shows the effect of Mach number and climb angle on the separation trajectories of the finned BLU-1C/B from the inboard pylon.

In general, for the trajectory intervals of this test, most of the stores separated from the parent aircraft without store-to-parent contact. A few of the trajectories were terminated as a result of reaching the vertical travel limit of the CTS or contact of the store-model-support sting with the parent-aircraft model.

APPENDIXES
I. ILLUSTRATIONS
II. TABLES





Fig. 1 Isometric Drawing of a Typical Store Separation Installation and a Block Diagram of the Computer Control Loop



TYPICAL PERFORATED WALL CROSS SECTION

ALL DIMENSIONS AND TUNNEL STATIONS IN INCHES




Fig. 2 Schematic of the Tunnel Test Section Showing Model Location





Fig. 3 Sketch of the A-7D Parent-Aircraft Model



	INBOARD	CENTER	OUTBOARD
B	1.030	1.030	0.515
C	4.580	4.850	4.437
D	1.630	1.905	2.008
E	0.575	0.575	0.513
F	0.950	0.950	0.750
G	1.350	1.350	1.150

ALL DIMENSIONS IN INCHES

Fig. 4 Details and Dimensions of the A-7D Model Pylons




Fig. 5 Details and Dimensions of the TER Model




Fig. 6 Details and Dimensions of the MER Model




Fig. 7 Details and Dimensions of the M-117R Model




Fig. 8 Details and Dimensions of the BLU-1C/B Unfinned Model




Fig. 9 Details and Dimensions of the BLU-1C/B Finned Model




Fig. 10 Details and Dimensions of the SUU-42/A Model






Fig. 11 Tunnel Installation Photograph Showing Parent Aircraft, Store, and CTS




NOTE: The square indicates the orientation of the suspension lugs.

TYPE RACK	STATION	ROLL ORIENTATION, deg
MER ↓	1	0
	2	0
	3	45
	4	45
	5	-45
	6	-45
TER ↓	1	0
	2	45
	3	-45

Fig. 12 Schematic of the TER and MER Store Stations and Orientations




a. Function T_1 for M-117R on MER or TER



b. Function T_2 for BLU-1C/B on MAU-12 Pylon


Fig. 13 Ejector Force Functions



c. Function T_3 for Empty SUU-42/A on MAU-12 Pylon
Fig. 13 Concluded

SYMBOL	CONF	M _L	α	H	$\bar{\sigma}$	EJECTOR FORCE
□	1L	0.33	12.3	4000	0	T I
○	1L	0.81	2.9	4000	0	T I
△*	1L	0.95	1.9	7000	-70	T I


* STING CONTACT



a. Configuration 1L


Fig. 14 Effect of Mach Number and Climb Angle on the Separation Trajectories of the M-117R from Center Pylon Station, Inboard and Outboard Pylon Empty

SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
□	2L	0.33	12.3	4000	0	T I
○	2L	0.81	2.1	4000	0	T I
△	2L	0.95	1.9	7000	-70	T I




b. Configuration 2L
Fig. 14 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
$\square$	3L	0.33	11.7	4000	0	T I
$\circ$	3L	0.81	2.9	4000	0	T I



c. Configuration 3L
Fig. 14 Continued


SYMBOL	CONF	M_0	α	H	$\bar{\omega}$	EJECTOR FORCE
○	4L	0.81	3.1	4000	0	T1
△	4L	0.95	2.0	7000	-70	T1



d. Configuration 4L
Fig. 14 Continued

SYMBOL	CONF	M_0	α	H	$\bar{\sigma}$	EJECTOR FORCE
□	5L	0.33	11.4 ✓	4000	0	T1
○	5L	0.81	2.9 ✓	4000	0	T1
△*	5L	0.95	1.9 ✓	7000	-70	T1


*STORE CONTACT



e. Configuration 5L
Fig. 14 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
□	6R	0.33	11.4	4000	0	T1
○	6R	0.81	2.9	4000	0	T1
△*	6R	0.95	1.9	7000	-70	T1


* STING CONTACT



f. Configuration 6R
Fig. 14 Continued


SYMBOL	CONF	M_0	α	H	$\bar{\sigma}$	EJECTOR FORCE
$\square$	7R	0.33	11.7	4000	0	TI
$\circ$	7R	0.81	2.9	4000	0	TI
Δ^*	7R	0.95	1.9	7000	-70	TI

*STORE CONTACT



g. Configuration 7R
Fig. 14 Concluded


SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
∇	8R	0.78	2.1	7000	-70	T I
Δ	8R	0.95	1.9	7000	-70	T I



a. Configuration 8R

Fig. 15 Effect of Mach Number and Climb Angle on the Separation Trajectories of the M-117R from Center Pylon Station, Finned BLU-1C/B on Inboard and Outboard Pylon


SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
∇	9R	0.78	2.2	7000	-70	T I
Δ	9R	0.95	2.0	7000	-70	T I



b. Configuration 9R
Fig. 15 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
$\triangleleft$	10R	0.78	2.2	7000	-70	T1
$\triangle^*$	10R	0.95	2.0	7000	-70	T1


*STING CONTACT



c. Configuration 10R
Fig. 15 Continued

SYMBOL	CONF	M_0	α	H	$\bar{\sigma}$	EJECTOR FORCE
$\triangle^*$	11R	0.78	2.1	7000	-70	T1
$\triangle^*$	11R	0.95	1.9	7000	-70	T1


* STORE CONTACT



d. Configuration 11R
Fig. 15 Continued


SYMBOL	CONF	M_0	α	H	$\bar{\omega}$	EJECTOR FORCE
$\triangleleft$	12R	0.78	2.1	7000	-70	T1
$\triangle^*$	12R	0.95	1.9	7000	-70	T1

*STORE CONTACT



e. Configuration 12R
Fig. 15 Concluded

SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
∇	13R	0.78	2.2	7000	-70	T1
Δ	13R	0.95	1.9	7000	-70	T1




a. Configuration 13R

Fig. 16 Effect of Mach Number on the Separation Trajectories of M-117R from Center Pylon Station, Outboard Pylon Empty, and M-117R on Inboard Pylon

SYMBOL	CONF	M_0	α	H	$\bar{\omega}$	EJECTOR FORCE
$\triangleleft$	14R	0.78	2.1	7000	-70	T1
$\triangle^*$	14R	0.95	1.9	7000	-70	T1


* STORE CONTACT



b. Configuration 14R
Fig. 16 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
∇^*	15R	0.78	2.1	7000	-70	T I
Δ	15R	0.95	1.9	7000	-70	T I


*STING CONTACT



c. Configuration 15R
Fig. 16 Continued


SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
$\triangle^*$	16R	0.78	2.1	7000	-70	T I
$\triangle^*$	16R	0.95	1.9	7000	-70	T I

*STING CONTACT




d. Configuration 16R
Fig. 16 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
◄	17R	0.78	2.1	7000	-70	T1
Δ	17R	0.95	1.9	7000	-70	T1



e. Configuration 17R
Fig. 16 Continued


SYMBOL	CONF	M_0	α	H	$\bar{\theta}$	EJECTOR FORCE
◁	18R	0.78	2.1	7000	-70	T I
△	18R	0.95	1.9	7000	-70	T I



f. Configuration 18R
Fig. 16 Concluded

SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
$\triangleleft^*$	19L	0.78	2.1	7000	-70	T1
$\triangle^*$	19L	0.95	1.9	7000	-70	T1


*STING CONTACT



a. Configuration 19L

Fig. 17 Effect of Mach Number on the Separation Trajectories of the M-117R from Center Pylon Station, Unfinned BLU-1C/B on Outboard and Inboard Pylons


SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
$\triangleleft$	20L	0.78	2.1	7000	-70	T1
$\triangle$	20L	0.95	1.9	7000	-70	T1



b. Configuration 20L
Fig. 17 Concluded

SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
∇^*	21L	0.78	2.2	7000	-70	T I
Δ	21L	0.95	1.9	7000	-70	T I


*STORE CONTACT



a. Configuration 21L

Fig. 18 Effect of Mach Number on the Separation Trajectories of the M-117R from Center Pylon Station, M-117R on Inboard, and SUU-42/A on Outboard Pylon


SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
∇	22L	0.78	2.1	7000	-70	T1
Δ	22L	0.95	1.9	7000	-70	T1



b. Configuration 22L
Fig. 18 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{p}$	EJECTOR FORCE
$\triangle$	23L	0.78	2.1	7000	-70	T1
$\triangle^*$	23L	0.95	1.9	7000	-70	T1


* STING CONTACT



c. Configuration 23L
Fig. 18 Continued


SYMBOL	CONF	M ₀	α	H	$\bar{\omega}$	EJECTOR FORCE
$\triangle^*$	24L	0.78	2.1	7000	-70	T1
$\triangle^*$	24L	0.95	1.9	7000	-70	T1

*STING CONTACT




d. Configuration 24L
Fig. 18 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{\theta}$	EJECTOR FORCE
∇	25L	0.78	2.1	7000	-70	T I
Δ	25L	0.95	1.9	7000	-70	T I



e. Configuration 25L
Fig. 18 Continued

SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
◁	26L	0.78	2.1	7000	-70	T I
△	26L	0.95	1.9	7000	-70	T I



f. Configuration 26L
Fig. 18 Concluded

SYMBOL	CONF	M_∞	α	H	$\bar{\omega}$	EJECTOR FORCE
□	27R	0.33	13.1	4000	0	T3
○	27R	0.81	3.0	4000	0	T3




Fig. 19 Effect of Mach Number on the Separation Trajectories of the SUU-42/A from the Outboard Pylon, MER on Center Pylon, and Inboard Pylon Empty, Configuration 27R

SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
□	28L	0.33	13.1	4000	0	T3
○	28L	0.81	3.0	4000	0	T3





Fig. 20 Effect of Mach Number on the Separation Trajectories of the SUU-42/A from the Outboard Pylon, MER with M-117R on Center Pylon, and an M-117R on Inboard Pylon, Configuration 28L


SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
□	29L	0.33	13.1	4000	0	T2
◇	29L	0.76	2.8	6000	-50	T2



a. Configuration 29L

Fig. 21 Effect of Mach Number and Climb Angle on the Separation Trajectories of the Finned BLU-1C/B from the Inboard Pylon, MER on Center Pylon, and Finned BLU-1C/B on Outboard Pylon

SYMBOL	CONF	M_∞	α	H	$\bar{\sigma}$	EJECTOR FORCE
□	30R	0.33	13.1	4000	0	T2
◇	30R	0.76	2.8	6000	-50	T2



b. Configuration 30R
Fig. 21 Concluded

TABLE I
FULL-SCALE STORE PARAMETERS USED IN TRAJECTORY CALCULATIONS

Parameter	Store		
	BLU-1/B (Finned)	M-117R	SUU-42/A (Empty)
$\bar{m}$	23.00	26.90	11.90
X_{cg}	5.45	2.80	7.08
I_{yy}	145.00	66.90	75.50
I_{zz}	145.00	66.90	75.50
b	1.550	1.333	1.895
S	1.887	1.396	2.820
C_{mq}	-48.0	-42.0	-43.4
C_{nr}	-48.0	-42.0	-43.4
Ejector Piston Distance Forward of Store cg, X_L , ft			
1. X_L , MER or TER	---	0.058	---
2. X_{L1} , MAU-12	0.916	---	0.666
3. X_{L2} , MAU-12	-0.750	---	-1.000
ZE	0.344	0.255	0.344

TABLE II
MAXIMUM FULL-SCALE POSITION UNCERTAINTIES
CAUSED BY BALANCE INACCURACIES

Store	M_∞	t	ΔX	ΔY	ΔZ	$\Delta \theta$	$\Delta \psi$
BLU-1C/B (Finned)	0.33	0.2	± 0.05	± 0.05	± 0.06	± 0.5	± 0.6
M-117R	0.33	0.2	± 0.03	± 0.04	± 0.01	± 0.2	± 0.1
SUU-42/A	0.33	0.2	± 0.05	± 0.03	± 0.02	± 0.3	± 0.3

TABLE III
AIRCRAFT WING-LOADING CONFIGURATION

Loading Configuration	Launch Store Model	Inboard Pylon	Center Pylon	Outboard Pylon
1L	M-117R	Empty	MER: M-117R (Dummy) Sta: 3,4,6 M-117R (Launch) Sta: 5	Empty
2L	M-117R	Empty	MER: M-117R (Dummy) Sta: 4 M-117R (Launch) Sta: 3	Empty
3L	M-117R	Empty	MER: M-117R (Launch) Sta: 4	Empty
4L	M-117R	Empty	MER: M-117R (Dummy) Sta: 2 - 6 M-117R (Launch) Sta: 1	Empty
5L	M-117R	Empty	TER: M-117R (Dummy) Sta: 2 M-117R (Launch) Sta: 3	Empty
6R	M-117R	Empty	TER: M-117R (Launch) Sta: 3	Empty
7R	M-117R	Empty	TER: M-117R (Dummy) Sta: 2,3 M-117R (Launch) Sta: 1	Empty
8R	M-117R	Finned BLU-1C/B (Dummy)	MER: M-117R (Dummy) Sta: 4 M-117R (Launch) Sta: 3	Finned BLU-1C/B (Dummy)

TABLE III (Continued)

Loading Configuration	Launch Store Model	Inboard Pylon	Center Pylon	Outboard Pylon
9R	M-117R	Finned BLU-1C/B (Dummy)	MER: M-117R (Dummy) Sta: 2 - 4 M-117R (Launch) Sta: 1	Finned BLU-1C/B (Dummy)
10R	M-117R	Finned BLU-1C/B (Dummy)	MER: M-117R (Dummy) Sta: 3,4 M-117R (Launch) Sta: 2	Finned BLU-1C/B (Dummy)
11R	M-117R	Finned BLU-1C/B (Dummy)	MER: M-117R (Launch) Sta: 4	Finned BLU-1C/B (Dummy)
12R	M-117R	Finned BLU-1C/B (Dummy)	TER: M-117R (Launch) Sta: 2	Finned BLU-1C/B (Dummy)
13R	M-117R	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 2 - 4 M-117R (Launch) Sta: 1	Empty
14R	M-117R	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 3,4 M-117R (Launch) Sta: 2	Empty
15R	M-117R	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 4 M-117R (Launch) Sta: 3	Empty
16R	M-117R	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 4	Empty

TABLE III (Continued)

Loading Configuration	Launch Store Model	Inboard Pylon	Center Pylon	Outboard Pylon
17R	M-117R	M-117R (Dummy)	TER: M-117R (Dummy) Sta: 2 M-117R (Launch) Sta: 1	Empty
18R	M-117R	M-117R (Dummy)	TER: M-117R (Launch) Sta: 2	Empty
19L	M-117R	Unfinned BLU-1C/B (Dummy)	MER: M-117R (Dummy) Sta: 6 M-117R (Launch) Sta: 5	Unfinned BLU-1C/B (Dummy)
20L	M-117R	Unfinned BLU-1C/B (Dummy)	TER: M-117R (Launch) Sta: 2	Unfinned BLU-1C/B (Dummy)
21L	M-117R	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 2 - 4 M-117R (Launch) Sta: 1	SUU-42 (Dummy)
22L	M-117R	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 3, 4 M-117R (Launch) Sta: 2	SUU-42 (Dummy)
23L	M-117R	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 4 M-117R (Launch) Sta: 3	SUU-42 (Dummy)
24L	M-117R	M-117R (Dummy)	MER: M-117R (Launch) Sta: 4	SUU-42 (Dummy)

TABLE III (Concluded)

Loading Configuration	Launch Store Model	Inboard Pylon	Center Pylon	Outboard Pylon
25L	M-117R	M-117R (Dummy)	TER: M-117R (Dummy) Sta: 2 M-117R (Launch) Sta: 1	SUU-42 (Dummy)
26L	M-117R	M-117R (Dummy)	TER: M-117R (Launch) Sta: 2	SUU-42 (Dummy)
27L	SUU-42	Empty	MER: Empty	SUU-42 (Launch)
28L	SUU-42	M-117R (Dummy)	MER: M-117R (Dummy) Sta: 1 - 4	SUU-42 (Launch)
29L	Finned BLU-1C/B	Finned BLU-1C/B (Launch)	MER: M-117R (Dummy) Sta: 1 - 4	Empty
30R	Finned BLU-1C/B	Finned BLU-1C/B (Launch)	MER: Empty	Empty

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center Arnold Air Force Station, Tennessee		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP N/A	
3. REPORT TITLE SEPARATION CHARACTERISTICS OF THE M-117 RETARDED BOMB, FINNED BLU-1C/B BOMB, AND SUU-42/A DISPENSER FROM THE A-7D AIRCRAFT AT MACH NUMBERS FROM 0.33 TO 0.95			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) September 11 through 16, 1971 - Final Report			
5. AUTHOR(S) (First name, middle initial, last name) David W. Hill, Jr., ARO, Inc. This document has been approved for public release its distribution is unlimited. <i>Rey TAB 74-17 16 Aug 74</i>			
6. REPORT DATE December 1971		7a. TOTAL NO. OF PAGES 67	7b. NO. OF REFS 1
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-71-261 AFATL-TR-71-152	
b. PROJECT NO.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) ARO-PWT-TR-71-213	
c. Program Element 27121F			
d. System 337A			
10. DISTRIBUTION STATEMENT Distribution limited to U.S. Government agencies only; this report contains information on test and evaluation of military hardware; December 1971; other requests for this document must be referred to Air Force Armament Laboratory (DLGC), Eglin AFB, Florida 32542.			
11. SUPPLEMENTARY NOTES Available in DDC		12. SPONSORING MILITARY ACTIVITY AFATL (DLGC) Eglin AFB, Florida 32542	

13. ABSTRACT Tests were conducted in the Aerodynamic Wind Tunnel (4T) using 0.05-scale models to investigate the separation characteristics of the M-117 retarded bomb, finned BLU-1C/B bomb, and SUU-42/A dispenser when released from various wing pylon locations on the A-7D aircraft. Captive trajectory data were obtained at Mach numbers from 0.33 to 0.95 at simulated pressure altitudes from 4000 to 7000 ft. The parent-aircraft angle of attack was varied from 1.8 to 12.3 depending on Mach number, climb angle, and simulated altitude. At selected test conditions, parent climb angles of -70 deg were simulated. In general, for the trajectory intervals of the test, most of the stores separated from the parent aircraft without store-to-parent contact.

Distribution limited to U.S. Government agencies only; this report contains information on test and evaluation of military hardware; December 1971; other requests for this document must be referred to Air Force Armament Laboratory (DLGC), Eglin AFB, Florida 32542.

14.

KEY WORDS

separation
characteristics
M-117 Retarded Bomb
BLU-1C/B Bomb (Finned)
SUU-42/A Dispenser
A-7D Aircraft
Mach numbers

LINK A

LINK B

LINK C

ROLE

WT

ROLE

WT

ROLE

WT