

Image Cover Sheet

CLASSIFICATION

UNCLASSIFIED

SYSTEM NUMBER

514934

**TITLE**

Numerical seakeeping predictions including interaction effects between two ships

System Number:**Patron Number:****Requester:****Notes:****DSIS Use only:****Deliver to:**

This page is left blank

This page is left blank

Copy No. 8



Numerical Seakeeping Predictions Including Interaction Effects Between Two Ships

L. Li

Y.J. He

C.C. Hsiung

*Centre for Marine Vessel Development and Research
DalTech, Dalhousie University*

DEFENCE RESEARCH ESTABLISHMENT ATLANTIC

Contractor Report

DREA CR 2000-050

April 2000



National
Defence

Défense
nationale

Canada



National Defence
Research and
Development Branch

Défense nationale
Bureau de recherche
et développement

DREA CR 2000-050

NUMERICAL SEAKEEPING PREDICTIONS INCLUDING INTERACTION EFFECTS BETWEEN TWO SHIPS

L. Li, Y.J. He and C.C. Hsiung

Centre for Marine Vessel Development and Research
DalTech, Dalhousie University
Halifax, Nova Scotia

Scientific Authority _____ signature on file _____

W7707-8-6038/001/HAL
Contract Number

April 2000

CONTRACTOR REPORT

Prepared for

**Defence
Research
Establishment
Atlantic**



**Centre de
Recherches pour la
Défense
Atlantique**

Canada

Numerical Seakeeping Predictions Including Interaction Effects between Two Ships

DREA CR 2000-050

L. Li, Y.J. He, and C.C. Hsiung, Centre for Marine Vessel Development and Research, DalTech, Dalhousie University

Abstract

A modified version of the SHIPINT program, SHIPINT2, has been developed to compute the restraining forces and motions of the two ship interaction problem in accordance with prescribed captive model test conditions. The coupled motions are computed using a three-dimensional panel method with zero forward speed Green's function and a simple forward speed correction. With this method, the field points and source points are distributed on the wetted surface of two ships (ship-a and ship-b). The unsteady hydrodynamic forces, wave exciting forces and coupled motion amplitudes are computed based on the two ships interacting. Two ship double-body flow is used to determine the steady flow disturbance potential and velocity distribution. In this computation, the m-term computation is performed by the integral equation method based on the double body flow of two ships interacting. Alternatively, with the uniform flow assumption, the approximate m-terms can also be used in this study. Schmitke's method is applied to compute the viscous roll damping coefficients for ship-a and ship-b separately. The viscous interaction between the two ships is neglected. Spectral analyses for irregular waves are also carried out for ship-a and ship-b.

Calculations have been carried out in regular waves with heading angles of 120, 150, and 180 degrees for two forward speeds of 12 knots and 0 knots. Also considered is a lateral separation distance of 52.705 m, and a longitudinal separation distance $d_x/L_{ALSC} = 0.25$. Ship motions in irregular waves, using the Bretschneider spectrum for Sea State 6 ($H_s = 5.0$ m, $T_p = 12.4$ s), have also been computed.

Résumé

Une version modifiée du programme SHIPINT, appelée SHIPINT2, a été mise au point pour résoudre les problèmes associés au calcul des forces de retenue et des mouvements de deux navires en interaction conformément aux conditions d'essai prescrites sur maquette entravée. Les mouvements conjugués sont calculés à l'aide de la méthode des panneaux à trois dimensions avec la fonction de Green pour une vitesse d'avance nulle et une correction simple de la vitesse d'avance. Cette méthode permet de distribuer les points de parcours et les points de source sur la surface mouillée des deux navires (navire a et navire b). Le calcul des forces hydrodynamiques non stationnaires, des forces d'excitation des vagues et de l'amplitude des mouvement conjugués repose sur l'interaction des deux navires. On utilise des paramètres d'écoulement doubles sur deux corps pour déterminer le potentiel de perturbation et la distribution de la vitesse de l'écoulement stationnaire. Le calcul du terme m est effectué par la méthode de l'équation intégrale axée sur l'écoulement double de deux corps (deux navires) en interaction. En

contrepartie, si l'hypothèse de l'écoulement uniforme est retenue, des termes m approximatifs peuvent aussi servir aux fins de l'étude. La méthode Schmitke est employée pour calculer séparément les coefficients d'amortissement en roulis visqueux du navire a et du navire b. L'interaction visqueuse entre les deux navires est négligeable. On a aussi procédé à l'analyse spectrale de vagues irrégulières pour le navire a et pour le navire b.

Des calculs ont été faits dans des vagues régulières avec des angles de cap de 120, 150 et 180 degrés à des vitesses d'avance de 12 nœuds et de 0 nœud. Les autres paramètres de calcul sont une distance de séparation latérale de 52,705 m et une distance de séparation longitudinale de $dx/L_{ALSC} = 0,25$. Les mouvements des navires dans des vagues irrégulières ont aussi été calculés à l'aide du spectre de Bretschneider pour des états de mer de niveau 6 ($H_s = 5,0$ m, $T_p = 12,4$ s).

DREA CR 2000-050

**NUMERICAL SEAKEEPING PREDICTIONS INCLUDING INTERACTION
EFFECTS BETWEEN TWO SHIPS**

by

L. Li, Y.J. He, and C.C. Hsiung

EXECUTIVE SUMMARY

Introduction

In anticipation of procurement of new naval supply ships, numerical and experimental studies have examined seakeeping of two ships within close proximity. The ships considered to date have been a concept design of the Afloat Logistic Support Capability (ALSC) and a frigate design similar to the Halifax class. During towing tank tests, the ALSC and frigate models were free in heave, roll, and pitch but were restrained in surge, sway, and yaw. This report describes numerical predictions of motions and restraining forces during the experiments.

Principal Results

The computer program SHIPINT formed the basis for the numerical predictions. It was necessary to modify the program to include the influence of restraining forces in specified modes. The modified program can compute wave-induced motions for unrestrained modes and restraining forces for restrained modes. The report gives comparisons of model motions and restraining forces for cases with each ship alone and for the ships in close proximity.

Significance of Results

The modified computer program SHIPINT2 is a promising tool for prediction of motions for two ships in close proximity. The numerical predictions presented in the report will permit validation with experimental results. The numerical predictions suggest that interaction effects can be significant for a smaller ship operating in the vicinity of a larger ship.

Future Plans

A report of experimental results will include comparisons with the present numerical predictions. These comparisons will be used to examine the validity of SHIPINT2 and to identify areas for improvement. The numerical model could be used in future studies of replenishment-at-sea.

Contents

List of Figures	iv
Nomenclature	v
Summary	1
1 Introduction	2
2 Description of the Problem	3
2.1 Basic assumptions	3
2.2 Solution methods	3
2.3 Formulation of the problem	3
3 Motions and Forces in Restrained Modes	6
3.1 Restrained motion and force components	6
3.2 Analysis of the restrained motion problem	7
3.3 Restrained radiation forces	8
3.4 Restrained wave exciting forces	9
3.5 Restrained restoring forces	9
3.6 Computation of unrestrained motions of the restrained hull	9
3.7 Computation of restrained force components	9
4 Code Modifications	10
4.1 Input	10
4.2 Numerical switch	11
4.3 Phase angles for motions and forces	11
4.4 Restraining force module	11
4.5 Unrestrained motion module	11
4.6 Output	12
5 Computed Results of Two Naval Ships: the ALSC and the SCAN frigate	13
5.1 Discretization of ship hulls	13
5.1.1 ALSC hull: ship-a	13
5.1.2 SCAN frigate hull: ship-b	16
5.2 Calculation of hull parameters for viscous damping	19
5.3 Computed Results	21
5.3.1 Run set 4-1	23
5.3.2 Run set 4-2	26
5.3.3 Run set 4-3	29
5.3.4 Run set 4-4	32
5.3.5 Run set 5-1 and 6-1	35
5.3.6 Run set 5-2 and 6-2	38
5.3.7 Run set 7-1	41
5.3.8 Run set 7-2	44

5.3.9	Run set 8-1 and 9-1	47
5.3.10	Run set 10-1	50
5.3.11	Run set 10-2	53
5.3.12	Run set 11-1 and 12-1	56
6	Concluding Remarks	59
	References	60
	Appendix A: ALSC Panel Data File	61
	Appendix B: SCAN Frigate Panel Data File	69
	Appendix C: Viscous Damping Data for ALSC	78
	Appendix D: Viscous Damping Data for SCAN Frigate	81
	Appendix E: Wave Input Data	84
	Appendix F: The Output Sample of Run Set 4-1	86
	Run set 4-1	86

List of Figures

1	Coordinate Systems	4
2	Panelized ALSC Hull	14
3	Body Plan of ALSC Hull	15
4	Panelized SCAN Frigate Hull	17
5	Body Plan of the SCAN Frigate Hull	18
6	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=0.0\text{m}$	23
7	Restraining Forces of Two Ships for Run Set 4-1	24
8	Motion Displacements of Two Ships for Run Set 4-1	25
9	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=45.0\text{m}$	26
10	Restraining Forces of Two Ships for Run Set 4-2	27
11	Motion Displacements of Two Ships for Run Set 4-2	28
12	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=0.0\text{m}$	29
13	Restraining Forces of Two Ships for Run Set 4-3	30
14	Motion Displacements of Two Ships for Run Set 4-3	31
15	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=45.0\text{m}$	32
16	Restraining Forces of Two Ships for Run Set 4-4	33
17	Motion Displacements of Two Ships for Run Set 4-4	34
18	Separation Distance of Two Ships: $G_y=2000.0\text{m}$, $dx=0.0\text{m}$	35
19	Restraining Forces of Two Ships for Run Set 5-1 and 6-1	36
20	Motion Displacements of Two Ships for Run Set 5-1 and 6-1	37
21	Separation Distance of Two Ships: $G_y=2000.0\text{m}$, $dx=0.0\text{m}$	38
22	Restraining Forces of Two Ships for Run Set 5-2 and 6-2	39
23	Motion Displacements of Two Ships for Run Set 5-2 and 6-2	40
24	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=0.0\text{m}$	41
25	Restraining Forces of Two Ships for Run Set 7-1	42
26	Motion Displacements of Two Ships for Run Set 7-1	43
27	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=45.0\text{m}$	44
28	Restraining Forces of Two Ships for Run Set 7-2	45
29	Motion Displacements of Two Ships for Run Set 7-2	46
30	Separation Distance of Two Ships: $G_y=2000.0\text{m}$, $dx=0.0\text{m}$	47
31	Restraining Forces of Two Ships for Run Set 8-1 and 9-1	48
32	Motion Displacements of Two Ships for Run Set 8-1 and 9-1	49
33	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=0.0\text{m}$	50
34	Restraining Forces of Two Ships for Run Set 10-1	51
35	Motion Displacements of Two Ships for Run Set 10-1	52
36	Separation Distance of Two Ships: $G_y=30.0\text{m}$, $dx=45.0\text{m}$	53
37	Restraining Forces of Two Ships for Run Set 10-2	54
38	Motion Displacements of Two Ships for Run Set 10-2	55
39	Separation Distance of Two Ships: $G_y=2000.0\text{m}$, $dx=0.0\text{m}$	56
40	Restraining Forces of Two Ships for Run Set 11-1 and 12-1	57
41	Motion Displacements of Two Ships for Run Set 11-1 and 12-1	58

Nomenclature

A_w^a	waterplane area of ship-a
A_w^b	waterplane area of ship-b
B	beam of ship
B_a	beam of ship-a
B_b	beam of ship-b
C_b	block coefficient
C_{jk}^a	restoring force coefficient matrix of ship-a
C_{jk}^b	restoring force coefficient matrix of ship-b
D	volume displacement of ship
dx	longitudinal separation distance of two ships
dy	lateral separation distance between the centerlines of two ships
d_{a1}	radius of inertia of the waterplane of ship-a around the $o_a y_a$ -axis
d_{a3}	radius of inertia of the waterplane of ship-a around the $o_a x_a$ -axis
d_{b1}	radius of inertia of the waterplane of ship-b around the $o_b y_b$ -axis
d_{b3}	radius of inertia of the waterplane of ship-b around the $o_b x_b$ -axis
f_j^{Raa}	time independent radiated force on ship-a due to the oscillation of ship-a itself while ship-b is at rest
f_j^{Rab}	time independent radiated force on ship-a due to the oscillation of ship-b while ship-a is at rest

f_j^{Rbb}	time independent radiated force on ship-b due to the oscillation of ship-b itself while ship-a is at rest
f_j^{Rba}	time independent radiated force on ship-b due to the oscillation of ship-a while ship-b is at rest
F_j^a	time dependent hydrodynamic force acting on ship-a
F_j^b	time dependent hydrodynamic force acting on ship-b
F_j^{aS}	hydrostatic force acting on ship-a
F_j^{bS}	hydrostatic force acting on ship-b
f_j^{Ra}	time independent radiated force on ship-a, $f_j^{Ra} = f_j^{Raa} + f_j^{Rba}$
f_j^{Rb}	time independent radiated force on ship-b, $f_j^{Ra} = f_j^{Rab} + f_j^{Rbb}$
f_j^{Da}	time independent diffracted force on ship-a
f_j^{Db}	time independent diffracted force on ship-b
f_j^{Ia}	time independent incident wave force on ship-a
f_j^{Ib}	time independent incident wave force on ship-b
f_j^{Wa}	time independent wave exciting force on ship-a, $f_j^{Wa} = f_j^{Ia} + f_j^{Ra} + f_j^{Da}$
f_j^{Wb}	time independent wave exciting force on ship-b, $f_j^{Wb} = f_j^{Ib} + f_j^{Rb} + f_j^{Db}$
F_j^{Ra}	time dependent radiated force on ship-a, $F_j^{Ra} = F_j^{Raa} + F_j^{Rba}$
F_j^{Rb}	time dependent radiated force on ship-b, $F_j^{Ra} = F_j^{Rab} + F_j^{Rbb}$
F_j^{Da}	time dependent diffracted force on ship-a
F_j^{Db}	time dependent diffracted force on ship-b
F_j^{Ia}	time dependent incident wave force on ship-a
F_j^{Ib}	time dependent incident wave force on ship-b
F_j^{Wa}	time dependent wave exciting force on ship-a, $F_j^{Wa} = F_j^{Ia} + F_j^{Da}$

F_j^{Wb}	time dependent wave exciting force on ship-b. $F_j^{Wb} = F_j^{Ib} + F_j^{Db}$
F_1	measurement surge force amplitude
F_2	measurement sway force amplitude
F_3	measurement heave force amplitude
$G, \bar{G}, \hat{G}$	Green's Functions
g	gravitational acceleration
Gy	lateral separation gap of two ships, $Gy = dx - 1/2(B_a + B_b)$
I_{jk}^a	moments of inertia of ship-a, $j,k=1,2,3$
I_{jk}^b	moments of inertia of ship-b, $j,k=1,2,3$
K	wave number
L	ship length between perpendiculars
L_a	ship-a length between perpendiculars
L_b	ship-b length between perpendiculars
m_j	m-terms, $j=1,2,3,\dots,6$
m_j^a	m-terms of ship-a, $j=1,2,3,\dots,6$
m_j^b	m-terms of ship-b, $j=1,2,3,\dots,6$
m_{jk}^a	generalized mass matrix of ship-a, $j,k=1,2,3,\dots,6$
m_{jk}^b	generalized mass matrix of ship-b, $j,k=1,2,3,\dots,6$
M^a	mass of ship-a
M^b	mass of ship-b
M_4	measurement roll force amplitude
M_5	measurement pitch force amplitude

M_6	measurement yaw force amplitude
$\vec{n}^a$	unit normal vector on wetted surface of ship-a pointing into the fluid
$\vec{n}^b$	unit normal vector on wetted surface of ship-b pointing into the fluid
$\vec{n}_j^a$	generalized unit normal on wetted surface of ship-a, $j=1,2,3,\dots,6$
$\vec{n}_j^b$	generalized unit normal on wetted surface of ship-a, $j=1,2,3,\dots,6$
oxyz	steady moving coordinate system
$o_a x_a y_a z_a$	ship-fixed coordinate system of ship-a
$o_b x_b y_b z_b$	ship-fixed coordinate system of ship-b
p	pressure
$p(x, y, z)$	field point
$q(\xi, \eta, \zeta)$	source point
R_{xx}	roll radius of gyration of the ship for ship-a in $o_a x_a y_a z_a$ coordinate system for ship-b in $o_b x_b y_b z_b$ coordinate system
R_{yy}	pitch radius of gyration of the ship for ship-a in $o_a x_a y_a z_a$ coordinate system for ship-b in $o_b x_b y_b z_b$ coordinate system
R_{zz}	yaw radius of gyration of the ship for ship-a in $o_a x_a y_a z_a$ coordinate system for ship-b in $o_b x_b y_b z_b$ coordinate system
$\vec{r}_a$	position vector from the centre of gravity of ship-a to a point $p(x_a, y_a, z_a)$ on the ship hull surface
$\vec{r}_b$	position vector from the centre of gravity of ship-b to a point $p(x_b, y_b, z_b)$ on the ship hull surface
$\vec{r}_g$	position vector from the centre of gravity of a ship to a point $p(x, y, z)$ on the ship hull surface
S_a	mean wetted surface of ship-a

S_b	mean wetted surface of ship-b
T	draft of a ship
T_1	modal period
T_p	peak wave period
t	time
U	steady forward speed of a ship
W	steady flow velocity, $W = \nabla(-Ux + \phi_s)$
x_1^a, x_1^b	surge motion of ship-a and ship-b
x_2^a, x_2^b	sway motion of ship-a and ship-b
x_3^a, x_3^b	heave motion of ship-a and ship-b
x_4^a, x_4^b	roll motion of ship-a and ship-b
x_5^a, x_5^b	pitch motion of ship-a and ship-b
x_6^a, x_6^b	yaw motion of ship-a and ship-b
(x_g^a, y_g^a, z_g^a)	coordinate of centre of gravity of ship-a in $o_a x_a y_a z_a$
(x_g^b, y_g^b, z_g^b)	coordinate of centre of gravity of ship-b in $o_b x_b y_b z_b$
$\bar{x}_k^a, \bar{x}_k^b$	time independent motion amplitudes of ship-a and ship-b, $k=1,2,\dots,6$
$\bar{x}_f^a$	x-coordinate of the centre of the floatation of ship-a
$\bar{x}_f^b$	x-coordinate of the centre of the floatation of ship-b
$\dot{x}_k^a$	velocity of ship-a, $k=1,2,3$ translation; $k=4,5,6$ rotation
$\dot{x}_k^b$	velocity of ship-b, $k=1,2,3$ translation; $k=4,5,6$ rotation
$\ddot{x}_k^a$	acceleration of ship-a, $k=1,2,3$ translation; $k=4,5,6$ rotation
$\ddot{x}_k^b$	acceleration of ship-b, $k=1,2,3$ translation; $k=4,5,6$ rotation

z_B^a	z-coordinate of the centre of bouyancy of ship-a in $o_a x_a y_a z_a$
z_B^b	z-coordinate of the centre of bouyancy of ship-b in $o_b x_b y_b z_b$
β	angle between the wave propagation direction and the x-axis $\beta = 180^\circ$ for head seas
Δ^a	displacement of ship-a
Δ^b	displacement of ship-b
ζ_a	incident wave amplitude
ξ_1	surge motion amplitude
ξ_2	sway motion amplitude
ξ_3	heave motion amplitude
ξ_4	roll motion amplitude
ξ_5	pitch motion amplitude
ξ_6	yaw motion amplitude
λ	incident wave length
λ_{jk}^{aa}	damping coefficient of ship-a due to the motion of ship-a while ship-b is at rest
λ_{jk}^{ab}	damping coefficient of ship-a due to the motion of ship-b. while ship-a is at rest
λ_{jk}^{bb}	damping coefficient of ship-b due to the motion of ship-b while ship-a is at rest
λ_{jk}^{ba}	damping coefficient of ship-b due to the motion of ship-a while ship-b is at rest
μ_{jk}^{aa}	added mass of ship-a due to the motion of ship-a while ship-b is at rest
μ_{jk}^{ab}	added mass of ship-a due to the motion of ship-b while ship-a is at rest

μ_{jk}^{bb}	added mass of ship-b due to the motion of ship-b while ship-a is at rest
μ_{jk}^{ba}	added mass of ship-b due to the motion of ship-a while ship-b is at rest
ν	wave number $= \omega^2/g$
ν_e	encounter wave number, $\nu_e = \omega_e^2/g$
ρ	water density
σ_S^a	steady flow source density on ship-a
σ_S^b	steady flow source density on ship-b
σ_D^a	diffraction source density on ship-a
σ_D^b	diffraction source density on ship-b
σ_k^{aa}	radiation source density on ship-a due to the motion of ship -a while ship-b is at rest
σ_k^{ab}	radiation source density on ship-a due to the motion of ship -b while ship-a is at rest
σ_k^{ba}	radiation source density on ship-b due to the motion of ship -a while ship-b is at rest
σ_k^{bb}	radiation source density on ship-b due to the motion of ship -b while ship-b is at rest
Φ	time dependent unsteady velocity potential
Φ_S	steady velocity potential, $\Phi_S = -Ux + \phi_s$
Φ_D	time dependent diffracted wave velocity potential
ϕ_D	time independent diffracted wave velocity potential
Φ_I	time dependent incident wave velocity potential
ϕ_I	time independent incident wave velocity potential
ϕ_k	canonical radiated wave velocity potential

ϕ_k^a	the radiated wave potential of k^{th} direction, $k = 1, 2, \dots, 6$ due to the oscillation of ship-a while ship-b is at rest
ϕ_k^b	the radiated wave potential of k^{th} direction, $k = 1, 2, \dots, 6$ due to the oscillation of ship-b while ship-a is at rest
Φ_R^a	time dependent radiated wave velocity potential of ship-a
Φ_R^b	time dependent radiated wave velocity potential of ship-b
ϕ_R	time independent radiated wave velocity potential
Φ_R	time dependent radiated wave velocity potential
Φ_T	time dependent total wave velocity potential
ϕ_s	steady disturbance velocity potential
Φ_R^a	time dependent radiated wave velocity potential of ship-a
ω	incident wave frequency
ω_e	frequency of wave encounter

Summary

A modified version of the SHIPINT program, SHIPINT22, has been developed to compute the restraining forces and motions of the two ship interaction problem in accordance with prescribed captive model test conditions. The coupled motions are computed using a three-dimensional panel method with zero forward speed Green's function and a simple forward speed correction. With this method, the field points and source points are distributed on the wetted surface of two ships (ship-a and ship-b). The unsteady hydrodynamic forces, wave exciting forces and coupled motion amplitudes are computed based on the two ships interacting. Two ship double-body flow is used to determine the steady flow disturbance potential and velocity distribution. In this computation, the m-term computation is performed by the integral equation method based on the double body flow of two ships interacting. Alternatively, with the uniform flow assumption, the approximate m-terms can also be used in this study. Schmitke's method is applied to compute the viscous roll damping coefficients for ship-a and ship-b, separately. The viscous interaction between the two ships is neglected. Spectral analyses for irregular waves are also carried out for ship-a and ship-b.

Calculations have been carried out in regular waves with heading angles of 120° , 150° and 180° for two forward speeds of 12 knots and 0 knots. Also considered is a lateral separation distance of $52.705m$, and a longitudinal separation distance $d_x/L_{ALSC} = 0.25$. Ship motions in irregular waves, using the Bretschneider spectrum for Sea State 6($H_s = 5.0m$ and $T_p = 12.4s$), have also been computed.

1 Introduction

In support of the procurement of the Afloat Logistics Support Capability (ALSC), a series of model tests is going to be conducted at the Institute for Marine Dynamics (IMD) to examine motions in waves of the ALSC and a frigate in close proximity.

In 1996, the Centre for Marine Vessel Development and Research (CMVDR) developed a computer program SHIPINT that predicts the motions of two ships involved in RAS operations. The original SHIPINT program computes the motions of two ships that are in free running modes without restraining forces. In order to use the model test results to validate the SHIPINT program, a new version of the program was needed to include the predictions for the model test conditions.

This report describes the work of the numerical seakeeping predictions project carried out by CMVDR for Defense Research Establishment Atlantic (DREA).

According to the project requirements, CMVDR was to provide numerical simulation results in accordance with model test cases that will be conducted at IMD for two ships interacting in waves. The model test cases have been well defined in the contract. CMVDR needed to modify the existing SHIPINT code to simulate the model test cases. This required making the existing SHIPINT code more flexible, so that each mode of motion of either ship can be restrained at the user's will. The task has been performed by adding a numerical switch in the program. The control parameters are specified in the input file *shipint.in* and the output format is modified to reflect the simulation results.

Hulls of the ALSC and the SCAN frigate have been panelized and viscous damping calculations have been prepared. Both ships can be restrained in certain specified modes of motion. A new module to calculate the radiation forces due to the unrestrained ship as well as the forces due to the remaining unrestrained motion of the other ship has been formulated and implemented. This report presents the simulation results corresponding to the intended test conditions.

2 Description of the Problem

In this study, two ships assumed to be rigid bodies, advancing with the same forward speed and heading in waves, are considered. It is also assumed that the two ships oscillate harmonically in time about their mean positions. Based on linear potential theory, the flow field will be a superposition of steady flow, incident wave, diffracted wave and radiated wave. The steady flow effect on the ship motion will be in the form of m-terms and is also considered in the unsteady force computations. Similar to the SHIPINT program developed for DREA [1][2], we use the following assumptions and solution methods.

2.1 Basic assumptions

We assumed that:

1. The fluid is inviscid, incompressible, and the flow is irrotational;
2. The linear free surface condition and small amplitude motions are considered;
3. The double-body steady flow model (solid free surface) is adopted; thus, the steady wave-making effect is neglected;
4. A zero-speed Green's function is employed, i.e. $U \frac{\partial}{\partial x} \ll \omega_e$;
5. The waterline integration term is ignored; and
6. The ships are moving in regular waves.

2.2 Solution methods

The solution methods consist of:

1. A 3-D panel Green's function method for the two ship coupled motions; and
2. A double-body flow method (the Hess-Smith method) for the m-terms and steady flow computations.

2.3 Formulation of the problem

To validate the computer program, we numerically simulated the model test conditions so that the computed results from the SHIPINT program can be directly compared with the model test results.

The problem of two ships interacting in waves can be described as two rigid bodies advancing in the same direction with a constant speed. The mathematical formulation of this problem is based on the same assumptions as in the previous reports[1][2]. The coordinate systems $o - xyz$, $o_a - x_a y_a z_a$ and $o_b - x_b y_b z_b$ are translating with the ships at a steady forward speed U , as shown in

Fig.1. The origins o_a and o_b are located at the centre of gravity of ship-a and ship-b, respectively. The z -axis is positive upward and o - xy is on the calm water surface. The regular incident waves make an angle β with the positive ox axis.




Figure 1: Coordinate Systems

As we assume that the ships are rigid bodies, the motions of the ships must satisfy Newton's second law:

$$m_{jk}^a \ddot{x}_k^a = F_j^{Wa} + F_j^{Ra} + F_j^{Sa} \quad (1)$$

$$m_{jk}^b \ddot{x}_k^b = F_j^{Wb} + F_j^{Rb} + F_j^{Sb} \quad (2)$$

where m_{jk}^a is the mass matrix of ship-a. m_{jk}^b is the mass matrix of ship-b; $\ddot{x}_k^a = \text{Re}[-\omega^2 \bar{x}_k^a e^{-i\omega t}]$ is the acceleration of ship-a; $\ddot{x}_k^b = \text{Re}[-\omega_e^2 \bar{x}_k^b e^{-i\omega_e t}]$ is the acceleration of ship-b; F_j^{Wa} and F_j^{Wb} are the wave exciting forces on ship-a and ship-b, respectively; and F_j^{Ra} and F_j^{Rb} are the radiation forces on ship-a and ship-b, respectively. F_j^{Sa} and F_j^{Sb} are the hydrostatic forces on ship-a and ship-b, respectively.

After solving the boundary value problems using potential flow theory, we are able to rewrite the equations of motion in the following forms:

$$\sum_{k=1}^6 [-\omega_e^2 (m_{jk}^a + \mu_{j,k}^{aa}) - i\omega_e \lambda_{jk}^{aa} + C_{jk}^a] \bar{x}_k^a + [-\omega_e^2 \mu_{j,k}^{ab} - i\omega_e \lambda_{jk}^{ab}] \bar{x}_k^b = f_j^{Wa} \quad (3)$$

$$\sum_{k=1}^6 [-\omega_e^2 \mu_{jk}^{ba} - i\omega_e \lambda_{jk}^{ba}] \bar{x}_k^a + [-\omega_e^2 (m_{jk}^b + \mu_{jk}^{bb}) - i\omega_e \lambda_{jk}^{bb} + C_{jk}^b] \bar{x}_k^b = f_j^{wb} \quad (4)$$

where

C_{jk}^a = restoring force coefficient matrix of ship-a

C_{jk}^b = restoring force coefficient matrix of ship-b

$\bar{x}_k^a$ = complex motion amplitudes of ship-a

$\bar{x}_k^b$ = complex motion amplitudes of ship-b

Furthermore, μ_{jk}^{aa} is the added mass of ship-a due to the motion of ship-a; μ_{jk}^{ab} is the added mass of ship-a due to the motion of ship-b; λ_{jk}^{aa} is the damping coefficient of ship-a due to the motion of ship-a; and λ_{jk}^{ab} is the damping coefficient of ship-a due to the motion of ship-b:

$$\mu_{jk}^{aa} = \rho \left\{ \int \int_{S_a} \text{Re}[\phi_k^a] n_j dS + \frac{U}{\omega_e} \int \int_{S_a} \text{Im} \left[\frac{\partial \phi_k^a}{\partial x} \right] n_j dS - \frac{1}{\omega_e} \int \int_{S_a} \text{Im}[\nabla \phi_k^a \cdot \nabla \phi_s] n_j dS \right\} \quad (5)$$

$$\mu_{jk}^{ab} = \rho \left\{ \int \int_{S_a} \text{Re}[\phi_k^b] n_j dS + \frac{U}{\omega_e} \int \int_{S_a} \text{Im} \left[\frac{\partial \phi_k^b}{\partial x} \right] n_j dS - \frac{1}{\omega_e} \int \int_{S_a} \text{Im}[\nabla \phi_k^b \cdot \nabla \phi_s] n_j dS \right\} \quad (6)$$

$$\lambda_{jk}^{aa} = \rho \left\{ \omega_e \int \int_{S_a} \text{Im}[\phi_k^a] n_j dS - U \int \int_{S_a} \text{Re} \left[\frac{\partial \phi_k^a}{\partial x} \right] n_j dS + \int \int_{S_a} \text{Re}[\nabla \phi_k^a \cdot \nabla \phi_s] n_j dS \right\} \quad (7)$$

$$\lambda_{jk}^{ab} = \rho \left\{ \omega_e \int \int_{S_a} \text{Im}[\phi_k^b] n_j dS - U \int \int_{S_a} \text{Re} \left[\frac{\partial \phi_k^b}{\partial x} \right] n_j dS + \int \int_{S_a} \text{Re}[\nabla \phi_k^b \cdot \nabla \phi_s] n_j dS \right\} \quad (8)$$

In the following equations, μ_{jk}^{bb} is the added mass of ship-b due to the motion of ship-b; μ_{jk}^{ba} is the added mass of ship-b due to the motion of ship-a; λ_{jk}^{bb} is the damping coefficient of ship-b due to the motion of ship-b; and λ_{jk}^{ba} is the damping coefficient of ship-b due to the motion of ship-a:

$$\mu_{jk}^{bb} = \rho \left\{ \int \int_{S_b} \text{Re}[\phi_k^b] n_j dS + \frac{U}{\omega_e} \int \int_{S_b} \text{Im} \left[\frac{\partial \phi_k^b}{\partial x} \right] n_j dS - \frac{1}{\omega_e} \int \int_{S_b} \text{Im}[\nabla \phi_k^b \cdot \nabla \phi_s] n_j dS \right\} \quad (9)$$

$$\mu_{jk}^{ba} = \rho \left\{ \int \int_{S_b} \text{Re}[\phi_k^a] n_j dS + \frac{U}{\omega_e} \int \int_{S_b} \text{Im} \left[\frac{\partial \phi_k^a}{\partial x} \right] n_j dS - \frac{1}{\omega_e} \int \int_{S_b} \text{Im}[\nabla \phi_k^a \cdot \nabla \phi_s] n_j dS \right\} \quad (10)$$

$$\lambda_{jk}^{bb} = \rho \left\{ \omega_e \int \int_{S_b} \text{Im}[\phi_k^b] n_j dS - U \int \int_{S_b} \text{Re} \left[\frac{\partial \phi_k^b}{\partial x} \right] n_j dS + \int \int_{S_b} \text{Re}[\nabla \phi_k^b \cdot \nabla \phi_s] n_j dS \right\} \quad (11)$$

$$\lambda_{jk}^{ba} = \rho \left\{ \omega_e \int \int_{S_b} \text{Im}[\phi_k^a] n_j dS - U \int \int_{S_b} \text{Re} \left[\frac{\partial \phi_k^a}{\partial x} \right] n_j dS + \int \int_{S_b} \text{Re}[\nabla \phi_k^a \cdot \nabla \phi_s] n_j dS \right\} \quad (12)$$

Please refer to reference [1] for more details.

3 Motions and Forces in Restrained Modes

3.1 Restrained motion and force components

When the motion of a ship is restrained in certain modes of motion, the actual motion displacements should be zero in those particular modes. In order to simulate this effect, the equations of motion are rewritten in the following form:

$$\sum_{k=1}^6 (-\omega_e^2 m_{jk}^a \bar{x}_k^a) = \sum_{k=1}^6 [(\omega_e^2 \mu_{j,k}^{aa} + i\omega_e \lambda_{jk}^{aa}) \bar{x}_k^a - \sum_{k=1}^6 C_{jk}^a \bar{x}_k^a + \sum_{k=1}^6 [\omega_e^2 \mu_{j,k}^{ab} + i\omega_e \lambda_{jk}^{ab}] \bar{x}_k^b + f_j^{Wa}] \quad (13)$$

$$\sum_{k=1}^6 (-\omega_e^2 m_{jk}^b \bar{x}_k^b) = \sum_{k=1}^6 [(\omega_e^2 \mu_{j,k}^{bb} + i\omega_e \lambda_{jk}^{bb}) \bar{x}_k^b - \sum_{k=1}^6 C_{jk}^b \bar{x}_k^b + \sum_{k=1}^6 [\omega_e^2 \mu_{j,k}^{ba} + i\omega_e \lambda_{jk}^{ba}] \bar{x}_k^a + f_j^{Wb}] \quad (14)$$

If we further examine the right-hand side of the above equations, it is understood that the first terms of equations (15) and (16) represent the radiation forces on ship-a, f_j^{Raa} , and ship-b, f_j^{Rbb} , due to the oscillatory motions of ship-a or ship-b itself. The second terms are the hydrostatic restoring forces, f_j^{Sa} for ship-a and f_j^{Sb} for ship-b, and the third terms are the radiation forces, f_j^{Rba} , f_j^{Rab} , due to the oscillatory motion effect of the other ship. The last terms are the wave exciting forces, f_j^{Wa} and f_j^{Wb} . Then we can rewrite equations (13) and (14) as:

$$\sum_{k=1}^6 (-\omega_e^2 m_{jk}^a \bar{x}_k^a) = f_j^{Raa} + f_j^{Sa} + f_j^{Rab} + f_j^{Wa} \quad (15)$$

$$\sum_{k=1}^6 (-\omega_e^2 m_{jk}^b \bar{x}_k^b) = f_j^{Rbb} + f_j^{Sb} + f_j^{Rba} + f_j^{Wb} \quad (16)$$

When conducting model tests, we usually measure the forces for the j^{th} mode of motion as F_j^{Ma} for ship-a and F_j^{Mb} for ship-b, by restraining the j^{th} mode of motion. The equations of motion for the model test then become:

$$\sum_{k=1}^6 (-\omega_e^2 m_{jk}^a \bar{x}_k^a) = F_j^{Ma} \quad (17)$$

$$\sum_{k=1}^6 (-\omega_e^2 m_{jk}^b \bar{x}_k^b) = F_j^{Mb} \quad (18)$$

Therefore, the measured forces on ship-a and ship-b should be:

$$F_j^{Ma} = f_j^{Raa} + f_j^{Sa} + f_j^{Rab} + f_j^{Wa} \quad (19)$$

$$F_j^{Mb} = f_j^{Rbb} + f_j^{Sb} + f_j^{Rba} + f_j^{Wb} \quad (20)$$

Thus the force measurement on each ship contains four components. If the motions in certain modes are restrained in a model test, the values of the force components will be changed and the sum of all components in that restrained mode is called the restraining force. In the following section, we will discuss how the restrained motion will affect each force component and how the restraining forces and motions are computed.

3.2 Analysis of the restrained motion problem

In a captive model test, the oscillatory motions in certain modes of a model may be restrained in order to measure the forces, while the motions in the remaining modes may not be restrained. In the case of a totally restrained mode, the model will not be able to oscillate. However, in the earlier SHIPINT code, the ship is free to move in any mode. Therefore, it is desirable to restrain the motions of a ship (or both ships) in any mode as specified. In formulating the two-ship interaction problem, ships are assumed to be fixed for the computations of the diffracted and incident wave problem. Only the radiation problem involves the oscillatory motion of the ships. Therefore, the motion of the ship(s) should be able to be restrained in certain modes in order to simulate the model test condition.

In the case of two ships freely oscillating in waves, the radiated waves are generated by the oscillation of both ships. The radiation waves of a ship are not only caused by the oscillation of itself but also by the oscillation of the other ship. This is a rather complicated situation. Since the motion is restrained, the velocity potential is zero in the restrained mode, and therefore, the added mass and damping coefficients in that mode are zero. However, this does not mean that the radiation force is zero. The other ship (if not restrained) and the radiation waves of the ship itself free to move in the remaining modes could generate radiation forces.

Considering the case, for example, of the motion of ship-a restrained in the j_a^{th} mode. The velocity potential per unit velocity in the k^{th} mode of motion of ship-a can be found by solving the following boundary value problem:

$$\begin{aligned}
 \nabla^2 \phi_k^a &= 0 \\
 (g \frac{\partial}{\partial z} + U^2 \frac{\partial^2}{\partial x^2} + 2i\omega_e U \frac{\partial}{\partial x} - \omega_e^2) \phi_k^a &= 0 \quad (z = 0) \\
 \frac{\partial \phi_k^a}{\partial n} |_{S_a} &= n_k^a - \frac{m_k^a}{i\omega_e} \\
 \frac{\partial \phi_k^a}{\partial n} |_{S_b} &= 0 \\
 \frac{\partial \phi_k^a}{\partial n} |_{z \rightarrow -\infty} &= 0
 \end{aligned} \tag{21}$$

and the radiation condition : outgoing ring waves

where S_a is the hull surface of ship-a; S_b is the hull surface of ship-b; ω_e is the frequency of encounter; k is the index of the mode of motion ($k=1,2, \dots, 6$); n_k^a is the generalized unit inner normal of ship-a; U is the ship steady forward speed; and g is the gravitational acceleration. Furthermore, m_k^a is the m-term of ship-a in the k^{th} mode, and is the steady flow effect on the radiation waves of ship-a.

If the motion in the j_a^{th} mode is restrained, the boundary condition on ship-a (the third equation of (21)) would be zero and therefore the solution of the radiation potential in the j_a^{th} mode will be zero. Hence we are concerned about the radiation problem in the unrestrained modes. This has

been implemented in the program by providing an automatical switch between the modes. Similarly, if the motion of ship-b is restrained in the j_b^{th} mode, we will only need the radiation potentials of remaining unrestrained modes. Once the radiation potentials are obtained, we can compute the radiation forces. Even though there is no oscillatory motion in the restrained mode, there still may exists radiation forces in this mode due to the contributions of the other ship's radiation waves or radiation waves due to unrestrained modes of motion of the same ship.

3.3 Restrained radiation forces

The radiation force in the j^{th} mode acting on ship-a is given by:

$$F_j^{Ra}(x, y, z, t) = Re[f_j^{Ra} e^{-\omega_e t}] \quad (22)$$

where $f_j^{Ra} = f_j^{Ra}(x, y, z)$ is the time independent spatial radiation force in the j^{th} mode on ship-a, and

$$f_j^{Ra} = f_j^{Raa} + f_j^{Rab} \quad (23)$$

where f_j^{Raa} is the radiation force on ship-a due to the oscillation of ship-a with ship-b fixed without oscillation; and f_j^{Rab} is the radiation force on ship-a due to the oscillation of ship-b with ship-a fixed.

By substituting the radiation potential of ship-a and introducing added mass and damping coefficients (see equations (5)-(12)), the radiation force can be expressed as:

$$\begin{aligned} f_j^{Raa} &= \sum_{k=1}^6 [-\ddot{x}_k^a \mu_{jk}^{aa} - \dot{x}_k^a \lambda_{jk}^{aa}] \\ f_j^{Rab} &= \sum_{k=1}^6 [-\ddot{x}_k^b \mu_{jk}^{ab} - \dot{x}_k^b \lambda_{jk}^{ab}] \end{aligned} \quad (24)$$

Similarly, the time independent spatial radiation force acting on ship-b is:

$$f_j^{Rb} = f_j^{Rbb} + f_j^{Rba} \quad (25)$$

with

$$\begin{aligned} f_j^{Rbb} &= \sum_{k=1}^6 [-\ddot{x}_k^b \mu_{jk}^{bb} - \dot{x}_k^b \lambda_{jk}^{bb}] \\ f_j^{Rba} &= \sum_{k=1}^6 [-\ddot{x}_k^a \mu_{jk}^{ba} - \dot{x}_k^a \lambda_{jk}^{ba}] \end{aligned} \quad (26)$$

and f_j^{Rbb} is the radiation force on ship-b due to the oscillation of ship-b, with ship-a fixed without oscillation; and f_j^{Rba} is the radiation force on ship-b due to the oscillation of ship-a, with ship-b fixed.

3.4 Restrained wave exciting forces

Since the wave exciting forces are not generated by the ship motion, the restrained wave exciting forces will be the same as the wave exciting forces that have been computed by solving the diffraction and incident wave problems as in the previous SHIPINT code.

3.5 Restrained restoring forces

The restoring forces depend on the motion displacements. If the motion of a ship is restrained in the j th mode, there will be no motion displacement in that mode and therefore, the restoring force should be zero. However, since the ship is not symmetric to all planes, there might be restoring force components in the restrained modes. The restoring forces are computed based on this consideration.

3.6 Computation of unrestrained motions of the restrained hull

For a restrained hull, there is no motion in the restrained modes. If N_r is the number of restrained modes, then when solving motions of the restrained hull, the number of unknown complex motion displacements $\bar{x}_k$ will be $(12 - N_r)$. The program has been modified to solve automatically for the motions of the restrained hull in the unrestrained modes.

3.7 Computation of restrained force components

The following steps are followed to compute the restrained radiation forces and restoring forces:

1. Solve the radiation problem and use the computed radiation potential to calculate the added mass and damping coefficients:

$$\mu_{j,k}^{aa}, \lambda_{j,k}^{aa}, \mu_{j,k}^{ab}, \lambda_{j,k}^{ab}, \mu_{j,k}^{bb}, \lambda_{j,k}^{bb}, \mu_{j,k}^{ba}, \text{ and } \lambda_{j,k}^{ba}.$$

2. Solve the equations of motion (3) and (4) for $\bar{x}_j^a$ and $\bar{x}_j^b$ in the unrestrained modes only.

3. Compute the restrained radiation force components:

$$f_j^{Raa} = \sum_{k=1}^6 [(\omega_e^2 \mu_{j,k}^{aa} + i\omega_e \lambda_{j,k}^{aa}) \bar{x}_k^a$$

$$f_j^{Rab} = \sum_{k=1}^6 [\omega_e^2 \mu_{j,k}^{ab} + i\omega_e \lambda_{j,k}^{ab}] \bar{x}_k^b$$

$$f_j^{Rbb} = \sum_{k=1}^6 [(\omega_e^2 \mu_{j,k}^{bb} + i\omega_e \lambda_{j,k}^{bb}) \bar{x}_k^b$$

$$f_j^{Rba} = \sum_{k=1}^6 [\omega_e^2 \mu_{j,k}^{ba} + i\omega_e \lambda_{j,k}^{ba}] \bar{x}_k^a$$

4. Compute the restrained restoring forces

$$f_j^{Sa} = \sum_{k=1}^6 C_{jk}^a \bar{x}_k^a$$

$$f_j^{Sb} = \sum_{k=1}^6 C_{jk}^b \bar{x}_k^b$$

The sum of the restrained radiation forces, restoring force and wave exciting forces gives the total force that corresponds to the force measurement in the model test.

4 Code Modifications

SHIPINT22 is a new version of the SHIPINT program with modifications described in the following sections:

4.1 Input

The input file *shipint.in* is modified with two extra lines added, one for each ship. Each line contains 6 integer parameters I_j , with $j = 1, 2, \dots, 6$ representing the six modes of motions. $I_j = 0$ means no restriction in the j^{th} mode, and $I_j = 1$ corresponds to the j^{th} mode being restrained. For example, if the I_j values are given

```
ship - a :      1 1 0 0 0 1
ship - b :      0 0 0 0 0 0
```

then for ship-a the surge, sway and yaw motions are restrained but heave, roll and pitch are not restrained; whereas ship-b has all 6 degrees of freedom of motions.

In this way, the user can control and have the flexibility to set-up restrains for any modes of motions of the two ships. An example input file *shipint.in* is shown below:

```
'Dec. 6, 1999'
'ALSC' 'alsc.panel'
180 30.633 8.5 27535 0.588
-1.688 0 3.925
8.047 45 45
1 1 0 0 0 1
'SCAN' 'scan.panel'
122 14.78 4.50 3925.54 0.484
3.284 0.0 2.06
4.921 30.5 30.5
1 1 0 0 0 1
2022.705 0.0
0.0
1
180.
7
0.25
0.5
0.75
1.0
1.25
1.5
2.0
1 1
```

4.2 Numerical switch

Numerical switches are added in the code to reflect the restrained motions and control the following:

- Solution of the solved radiated wave problem depending on the input restraining parameter values;
- Calculation of the restrained forces based on the input restraining parameters;
- Calculation of the motions based on the input restraining parameters; and
- Results based on the input restraining parameters.

4.3 Phase angles for motions and forces

According to the work requirement, the phase angles of ALSC for motions and forces are modified to be referenced to the center of gravity of the ALSC instead of the midship section of the ALSC, the phase angles of SCAN Frigate for motions and forces are modified to be referenced to the center of gravity of the SCAN Frigate. Details of the phase angle shifts are commented in subroutine **af4** of the code.

4.4 Restraining force module

A new module has been written for computing the total restraining forces (i.e. the measured forces in model tests as part of the results of the output). The restrained radiation force components are calculated from the added mass, damping coefficients and the motion displacements. The restoring forces and the wave exciting forces are then added into the radiated forces to form the total restraining forces as follows:

$$F_j^{Ma} = \sum_{k=1}^6 [(\omega_e^2 \mu_{jk}^{aa} + i\omega_e \lambda_{jk}^{aa}) \bar{x}_k^a - \sum_{k=1}^6 C_{jk}^a \bar{x}_k^a + \sum_{k=1}^6 [\omega_e^2 \mu_{jk}^{ab} + i\omega_e \lambda_{jk}^{ab}] \bar{x}_k^b + f_j^{Wa}] \quad (27)$$

$$F_j^{Mb} = \sum_{k=1}^6 [(\omega_e^2 \mu_{jk}^{bb} + i\omega_e \lambda_{jk}^{bb}) \bar{x}_k^b - \sum_{k=1}^6 C_{jk}^b \bar{x}_k^b + \sum_{k=1}^6 [\omega_e^2 \mu_{jk}^{ba} + i\omega_e \lambda_{jk}^{ba}] \bar{x}_k^a + f_j^{Wb}] \quad (28)$$

where F_j^{Ma} are the total forces on ship_a (i.e. the measured forces of ship_a); F_j^{Mb} are the total forces on ship_b (i.e. the measured forces of ship_b);

For more details see Section 3.

corresponding to the unrestrained modes need to be solved.

4.6 Output

The output modules are modified to include the wave exciting force, computed total restraining forces(measured forces), motion displacements, RMS displacements and accelerations of the two ships (see electronic format Excel files). A new module for formulating the output result of the restraining forces and phase angles is added in the code. For unrestrained modes, the output restraining force components are set to zero and the phase angles are set to "999" or "0" strings which have no physical meanings. The lateral separation gap is also defined and included in the output.

5 Computed Results of Two Naval Ships: the ALSC and the SCAN frigate

5.1 Discretization of ship hulls

For both the ALSC and the SCAN frigate, the origin of the panelization coordinate system is located on the baseline at the ship bow, Station 0. The x-axis is positive towards the stern of the ship, and the z-axis is positive upwards. The regular 21 stations are numbered from 0 to 20. Any inserted sections must be numbered in between the regular stations. The bow and stern profiles normally are taken at the first and last section locations, respectively. For details see the User's Guide of *PANELGEN*.

5.1.1 ALSC hull: ship-a

The ALSC hull was panelized using 21 stations and 20 waterlines. The principal dimensions are as follows:

$$\begin{aligned} L &= 180.m \\ B &= 30.633m \\ T &= 8.5m \\ D &= 28223.3tonnes \\ Cb &= 0.588 \\ Xg &= -1.688m, \text{ (aft midships)} \\ Yg &= 0.0m \\ Zg &= 3.925m \text{ (relative to the calm waterline)} \\ Rxx &= 8.047m \\ Ryy &= 45.0m \\ Rzz &= 45.0m \end{aligned}$$

The ALSC hull is panelized using *PANELGEN*, an automatic panelization program. The panelized ALSC hull is shown in Figure 2 and the body plan is shown in Figure 3. The detailed panel information is given in the file *alsc.panel* (Appendix A).




Figure 2: Panelized ALSC Hull




Figure 3: Body Plan of ALSC Hull

5.1.2 SCAN frigate hull: ship-b

The SCAN frigate is panelized with 26 stations and 19 waterlines. The principal dimensions of the SCAN Frigate are as follows:

$$\begin{aligned}
 L &= 122.m \\
 B &= 14.783m \\
 T &= 4.5m \\
 Trim &= 0.24m \text{ (by stern)} \\
 D &= 4023.7tonnes \\
 Cb &= 0.484 \\
 Xg &= 3.284m \text{ (forward midships)} \\
 Yg &= 0.0m \\
 Zg &= 2.049m \text{ (relative to the calm waterline)} \\
 Rxx &= 4.921m \\
 Ryy &= 30.5m \\
 Rzz &= 30.5m
 \end{aligned}$$

The SCAN frigate hull is also panelized using *PANELGEN*. The difference between the SCAN frigate and the ALSC in panelization is that a trim had to be considered for the SCAN frigate. The panelized SCAN frigate hull is shown in Figure 4 and the body plan is shown in Figure 5. Detailed panel information is given in the file *scan.panel* (Appendix B).




Figure 4: Panelized SCAN Frigate Hull




Figure 5: Body Plan of the SCAN Frigate Hull

5.2 Calculation of hull parameters for viscous damping.

The input file *vdamp-a.in* for the ALSC and *vdamp-b.in* for the SCAN frigate provide all the necessary data to compute the following viscous roll damping coefficients:

- The bilge keel viscous roll damping coefficients.
- The eddy-making viscous roll damping coefficients.
- The frictional viscous roll damping coefficients.
- The appendage (other than bilge keel) viscous roll damping coefficients.
- The lifting viscous roll damping coefficient of rudder and skeg.

or the sum of any combinations of the above components.

The Bilge Keel Data:

	ALSC	SCAN frigate
stations spanned:	8.0-13.0	8.3-12.8
bilge keel breadth:	0.5 m	0.8 m
bilge keel breadth-length ratio:	0.0111	0.0262

Sectional Parameters:

We obtained the sectional parameters of the ALSC and the SCAN frigate according to the User's Guide for *SHIPINT*.

Rudder and Deadwood Parameters:

The frigate has a single rudder and the ALSC has two podded propulsion units.

	ALSC	SCAN frigate
skeg span :	NONE	2.5 m
vertical distance of C.G. above waterline :	3.925 m	2.055m
rudder span:	NONE	5.3 m
skeg angular parameter:	NONE	1.02 rad
rudder area of single side:	NONE	25.97 m ²

Parameters of Appendages Other Than Bilge Keel:

The ALSC includes 2 vertical foils of elliptical cross-section to model the podded propulsion units. The dimension of these foils are based on preliminary estimates for likely propulsion units. The SCAN Frigate includes 4 pairs of propeller shaft brackets and a sonar dome.

The detailed parameters are as follows:

total number of appendages: ALSC: 2 SCAN frigate: 9

normal force coefficient for a flat plate inclined at a large angle to flow:
 ALSC: 1.17 SCAN frigate: 1.17

The appendage parameters:

For ALSC: (append No)	1	2
y at root of appendage(m):	9	-9.0
z at root of appendage(m):	8.3	8.3
appendage dihedral angle(deg.):	90.0	-90.0
end chord of appendage(m):	5.0	5.0
root chord of appendage (m):	5.0	5.0
span of appendage(m):	5.4	5.4

For SCAN frigate: (append No.)	1	2	3	4	5	6	7	8	9
y at root of appendage(m):	3.5	-3.5	1.9	-1.9	4.1	-4.1	1.0	-1.0	0.0
z at root of appendage(m):	2.9	2.9	2.3	2.3	3.6	3.6	2.9	2.9	4.5
appendage dihedral angle(deg.):	97.	-97	47	-47	104	-104	48	-48	90
end chord of appendage(m):	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	4.95
root chord of appendage(m)	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	4.95
span of appendage(m):	2.0	2.0	2.0	2.0	3.3	3.3	3.4	3.4	1.16

All of the above information is included in the input files *vdamp-a.in* (for the ALSC) in Appendix C, and *vdamp-b.in* (for the SCAN frigate) in Appendix D.

5.3 Computed Results

The computed results for the ALSC and the SCAN frigate interactions are organized according to the run set number of the model test matrix.

The computed results are:

For the ALSC:

- non-dimensional measurement surge force amplitude $F_1/\rho g \zeta_a L_a B_a$
- non-dimensional measurement sway force amplitude $F_2/\rho g \zeta_a L_a B_a$
- non-dimensional measurement heave force amplitude $F_3/\rho g \zeta_a L_a B_a$
- non-dimensional measurement roll force amplitude $M_4/\rho g \zeta_a L_a^2 B_a$
- non-dimensional measurement pitch force amplitude $M_5/\rho g \zeta_a L_a^2 B_a$
- non-dimensional measurement yaw force amplitude $M_6/\rho g \zeta_a L_a^2 B_a$
- non-dimensional surge motion amplitude ξ_1/ζ_a
- non-dimensional sway motion amplitude ξ_2/ζ_a
- non-dimensional heave motion amplitude ξ_3/ζ_a
- non-dimensional roll motion amplitude $\xi_4/\zeta_a K$
- non-dimensional pitch motion amplitude $\xi_5/\zeta_a K$
- non-dimensional yaw motion amplitude $\xi_6/\zeta_a K$
- root mean square amplitude of surge displacement D1
- root mean square amplitude of sway displacement D2
- root mean square amplitude of heave displacement D3
- root mean square amplitude of roll displacement D4
- root mean square amplitude of pitch displacement D5
- root mean square amplitude of yaw displacement D6
- root mean square amplitude of surge acceleration A1
- root mean square amplitude of sway acceleration A2
- root mean square amplitude of heave acceleration A3

- root mean square amplitude of roll acceleration A4
- root mean square amplitude of pitch acceleration A5
- root mean square amplitude of yaw acceleration A6

For the SCAN frigate:

- non-dimensional measurement surge force amplitude $F_1/\rho g \zeta_a L_b B_b$
- non-dimensional measurement sway force amplitude $F_2/\rho g \zeta_a L_b B_b$
- non-dimensional measurement heave force amplitude $F_3/\rho g \zeta_a L_b B_b$
- non-dimensional measurement roll force amplitude $M_4/\rho g \zeta_a L_b^2 B_b$
- non-dimensional measurement pitch force amplitude $M_5/\rho g \zeta_a L_b^2 B_b$
- non-dimensional measurement yaw force amplitude $M_6/\rho g \zeta_a L_b^2 B_b$
- non-dimensional surge motion amplitude ξ_1/ζ_a
- non-dimensional sway motion amplitude ξ_2/ζ_a
- non-dimensional heave motion amplitude ξ_3/ζ_a
- non-dimensional roll motion amplitude $\xi_4/\zeta_a K$
- non-dimensional pitch motion amplitude $\xi_5/\zeta_a K$
- non-dimensional yaw motion amplitude $\xi_6/\zeta_a K$
- root mean square amplitude of surge displacement D1
- root mean square amplitude of sway displacement D2
- root mean square amplitude of heave displacement D3
- root mean square amplitude of roll displacement D4
- root mean square amplitude of pitch displacement D5
- root mean square amplitude of yaw displacement D6
- root mean square amplitude of surge acceleration A1
- root mean square amplitude of sway acceleration A2
- root mean square amplitude of heave acceleration A3
- root mean square amplitude of roll acceleration A4
- root mean square amplitude of pitch acceleration A5
- root mean square amplitude of yaw acceleration A6

Where ζ_a is the incident wave amplitude, K is the wave number.

5.3.1 Run set 4-1

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $G_y = 30.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 180°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .




Figure 6: Separation Distance of Two Ships: $G_y=30.0$ m, $dx=0.0$ m












Figure 7: Restraining Forces of Two Ships for Run Set 4-1




Heave motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=30.0m dx=0.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=30.0m dx=0.0m U=0.0m/s

Figure 8: Motion Displacements of Two Ships for Run Set 4-1

5.3.2 Run set 4-2

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $G_y = 30.0$ m

Longitudinal separation distance $dx = 45.0$ m

Wave heading angle = 180°

Both ships are restrained in **surge, sway, yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .







Figure 9: Separation Distance of Two Ships: $G_y=30.0$ m, $dx=45.0$ m




Surge force on ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Surge force on Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Sway force on ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Sway force on Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Yaw force on ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Yaw force on Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s


Figure 10: Restraining Forces of Two Ships for Run Set 4-2




Heave motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s

Figure 11: Motion Displacements of Two Ships for Run Set 4-2

5.3.3 Run set 4-3

condition:

Forward speed $U=12.0$ knots= 6.180 m/s

Lateral separation gap $Gy = 30.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 180°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .




Figure 12: Separation Distance of Two Ships: $Gy=30.0$ m, $dx=0.0$ m












Figure 13: Restraining Forces of Two Ships for Run Set 4-3




Heave motion of ALSC at a separation
Gy=30.0m dx=0.0m U=6.18m/s




Heave motion of Frigate at a separation
Gy=30.0m dx=0.0m U=6.18m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=0.0m U=6.18m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=0.0m U=6.18m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=0.0m U=6.18m/s



Pitch motion of Frigate at a separation
Gy=30.0m dx=0.0m U=6.18m/s

Figure 14: Motion Displacements of Two Ships for Run Set 4-3

5.3.4 Run set 4-4

condition:

Forward speed $U=12.0$ knots= 6.180 m/s

Lateral separation gap $Gy = 30.0$ m

Longitudinal separation distance $dx = 45.0$ m

Wave heading angle = 180°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .




Figure 15: Separation Distance of Two Ships: $Gy=30.0\text{m}$, $dx=45.0\text{m}$












Figure 16: Restraining Forces of Two Ships for Run Set 4-4




Heave motion of ALSC at a separation
Gy=30.0m dx=45.0m U=6.18m/s




Heave motion of Frigate at a separation
Gy=30.0m dx=45.0m U=6.18m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=45.0m U=6.18m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=45.0m U=6.18m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=45.0m U=6.18m/s



Pitch motion of Frigate at a separation
Gy=30.0m dx=45.0m U=6.18m/s

Figure 17: Motion Displacements of Two Ships for Run Set 4-4

5.3.5 Run set 5-1 and 6-1

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $Gy = 2000.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 180°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .







Figure 18: Separation Distance of Two Ships: $Gy=2000.0m$, $dx=0.0m$




Surge force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Surge force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Sway force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$



Sway force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Yaw force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Yaw force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$


Figure 19: Restraining Forces of Two Ships for Run Set 5-1 and 6-1




Heave motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s

Figure 20: Motion Displacements of Two Ships for Run Set 5-1 and 6-1

5.3.6 Run set 5-2 and 6-2

condition:

Forward speed $U=12.0$ knots= 6.180 m/s

Lateral separation gap $Gy = 2000.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 180°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017 \text{ and } 1.356.$$

For **SCAN Frigate**:

$$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5 \text{ and } 2.0.$$




Figure 21: Separation Distance of Two Ships: $Gy=2000.0\text{m}$, $dx=0.0\text{m}$












Figure 22: Restraining Forces of Two Ships for Run Set 5-2 and 6-2




Heave motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=6.18m/s




Heave motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=6.18m/s




Roll motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=6.18m/s



Roll motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=6.18m/s



Pitch motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=6.18m/s



Pitch motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=6.18m/s

Figure 23: Motion Displacements of Two Ships for Run Set 5-2 and 6-2

5.3.7 Run set 7-1

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $Gy = 30.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 150°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .




Figure 24: Separation Distance of Two Ships: $Gy=30.0\text{m}$, $dx=0.0\text{m}$












Figure 25: Restraining Forces of Two Ships for Run Set 7-1




Heave motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s




Heave motion of Frigate At a separation
Gy=30.0m dx=0.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Pitch motion of Frigate At a separation
Gy=30.0m dx=0.0m U=0.0m/s

Figure 26: Motion Displacements of Two Ships for Run Set 7-1

5.3.8 Run set 7-2

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $Gy = 30.0$ m

Longitudinal separation distance $dx = 45.0$ m

Wave heading angle = 150°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .




Figure 27: Separation Distance of Two Ships: $Gy=30.0$ m, $dx=45.0$ m












Figure 28: Restraining Forces of Two Ships for Run Set 7-2




Heave motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s

Figure 29: Motion Displacements of Two Ships for Run Set 7-2

5.3.9 Run set 8-1 and 9-1

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $Gy = 2000.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 150°

Both ships are restrained in **surge, sway, yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .







Figure 30: Separation Distance of Two Ships: $Gy=2000.0\text{m}$, $dx=0.0\text{m}$




Surge force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Surge force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Sway force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$



Sway force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Yaw force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Yaw force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$


Figure 31: Restraining Forces of Two Ships for Run Set 8-1 and 9-1




Heave motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s

Figure 32: Motion Displacements of Two Ships for Run Set 8-1 and 9-1

5.3.10 Run set 10-1

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $Gy = 30.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 120°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .




Figure 33: Separation Distance of Two Ships: $Gy=30.0$ m, $dx=0.0$ m












Figure 34: Restraining Forces of Two Ships for Run Set 10-1




Heave motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=30.0m dx=0.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=0.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=30.0m dx=0.0m U=0.0m/s

Figure 35: Motion Displacements of Two Ships for Run Set 10-1

5.3.11 Run set 10-2

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $Gy = 30.0$ m

Longitudinal separation distance $dx = 45.0$ m

Wave heading angle = 120°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .




Figure 36: Separation Distance of Two Ships: $Gy=30.0\text{m}$, $dx=45.0\text{m}$












Figure 37: Restraining Forces of Two Ships for Run Set 10-2




Heave motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=30.0m dx=45.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=30.0m dx=45.0m U=0.0m/s

Figure 38: Motion Displacements of Two Ships for Run Set 10-2

5.3.12 Run set 11-1 and 12-1

condition:

Forward speed $U=0.0$ knots= 0.0 m/s

Lateral separation gap $Gy = 2000.0$ m

Longitudinal separation distance $dx = 0.0$ m

Wave heading angle = 120°

Both ships are restrained in **surge**, **sway**, **yaw** during the simulation.

Regular waves:

For **ALSC**:

$\lambda/L_a = 0.169, 0.339, 0.508, 0.678, 0.847, 1.017$ and 1.356 .

For **SCAN Frigate**:

$\lambda/L_b = 0.25, 0.5, 0.75, 1.0, 1.25, 1.5$ and 2.0 .







Figure 39: Separation Distance of Two Ships: $Gy=2000.0\text{m}$, $dx=0.0\text{m}$




Surge force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Surge force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Sway force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$



Sway force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Yaw force on ALSC at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$




Yaw force on Frigate at a separation
 $G_y=2000.0\text{m}$ $dx=0.0\text{m}$ $U=0.0\text{m/s}$


Figure 40: Restraining Forces of Two Ships for Run Set 11-1 and 12-1




Heave motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s




Heave motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s




Roll motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Roll motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Pitch motion of ALSC at a separation
Gy=2000.0m dx=0.0m U=0.0m/s



Pitch motion of Frigate at a separation
Gy=2000.0m dx=0.0m U=0.0m/s

Figure 41: Motion Displacements of Two Ships for Run Set 11-1 and 12-1

6 Concluding Remarks

- A modified version of the program SHIPINT, as SHIPINT22, has been developed for numerical seakeeping prediction of the restraining forces and motions of two ships: the ALSC and the SCAN frigate.
- The computed results corresponding to the model test runs are obtained by imposing artificial constraints upon various modes of motions. The computed results show:
 - The roll motions and yaw forces are greater in the case of oblique seas than those for the case of head seas.
 - The roll motion is much greater for $\beta = 120^\circ$ than that for $\beta = 150^\circ$ but the pitch is smaller.
 - The interaction motion responses of the ALSC have behavior very close to that of a single ship case, but the interaction motion responses of the SCAN frigate are much different from those of a single ship case.
 - In the case of head seas with forward speed, the pitch motion of the SCAN frigate is greater than the pitch motion without forward speed.
 - The interaction effect on motions decreases with increasing separation distance between the two ships.
- The results presented here are for a set of conditions that will be tested at the Institute of Marine Dynamics. The results of these model tests will provide a validation set against which the performance of SHIPINT22 can be measured.

References

1. C.C. Hsiung and Y.J. He, "Final report on frequency-domain analysis of interaction effects between two ships in waves using the 3-D panel method", Contract Report, DREA CR/96/446, August, 1996.
2. C.C. Hsiung and Y.J. He, "User's guide for SHIPINT - A computer program to compute two ship interaction in waves", Contract Report, DREA CR/96/445, August, 1996.
3. C.C. Hsiung, Y.J. He and X.G. Lu, "User's guide for an automatic panelization program PANELGEN", DREA Contract Report 96/419, 1996.

Appendix A: ALSC Panel Data File

264 210

```

1 90.419998 0.000000 0.000000
2 90.000000 -0.043756 0.000000
3 81.000000 -3.732279 0.000000
4 72.000000 -6.023938 0.000000
5 63.000000 -8.054297 0.000000
6 54.000000 -9.970940 0.000000
7 45.000000 -11.712228 0.000000
8 36.000000 -13.130206 0.000000
9 27.000000 -14.152325 0.000000
10 18.000000 -14.790794 0.000000
11 9.000000 -15.140757 0.000000
12 0.000000 -15.316323 0.000000
13 -9.000000 -15.376906 0.000000
14 -18.000000 -15.336169 0.000000
15 -27.000000 -15.183046 0.000000
16 -36.000000 -14.905368 0.000000
17 -45.000000 -14.486609 0.000000
18 -54.000000 -13.920826 0.000000
19 -63.000000 -13.183241 0.000000
20 -72.000000 -12.127666 -0.000001
21 -81.000000 -10.436591 0.000000
22 -90.000000 -7.784397 0.000000
23 97.064507 0.000000 -1.420000
24 90.000000 -2.155141 -1.932750
25 81.000000 -3.652483 -2.070750
26 72.000000 -5.640112 -2.105500
27 63.000000 -7.499502 -2.118250
28 54.000000 -9.288836 -2.123250
29 45.000000 -10.986279 -2.125000
30 36.000000 -12.512541 -2.125000
31 27.000000 -13.674471 -2.125000
32 18.000000 -14.415432 -2.125000
33 9.000000 -14.817267 -2.125000
34 0.000000 -15.002799 -2.125000
35 -9.000000 -15.032046 -2.125000
36 -18.000000 -14.922239 -2.124750
37 -27.000000 -14.648211 -2.110750
38 -36.000000 -14.229990 -2.052000
39 -45.000000 -13.629851 -1.917250
40 -54.000000 -12.895230 -1.676750
41 -63.000000 -11.987173 -1.331250
42 -72.000000 -10.799935 -0.927501
43 -81.000000 -9.268652 -0.511500
44 -90.000000 -7.294670 -0.125000
45 98.463814 0.000000 -2.840000
46 90.000000 -2.630154 -3.865500
47 81.000000 -3.958067 -4.141500
48 72.000000 -5.412258 -4.211000
49 63.000000 -7.008562 -4.236500
50 54.000000 -8.616744 -4.246500
51 45.000000 -10.243830 -4.250000
52 36.000000 -11.797916 -4.250000
53 27.000000 -13.038542 -4.250000
54 18.000000 -13.863455 -4.250000
55 9.000000 -14.318850 -4.250000
56 0.000000 -14.513623 -4.250000
57 -9.000000 -14.503290 -4.250000
58 -18.000000 -14.300338 -4.249500
59 -27.000000 -13.665146 -4.221500
60 -36.000000 -13.196884 -4.104000
61 -45.000000 -12.266318 -3.834500
62 -54.000000 -11.200510 -3.353500
63 -63.000000 -10.071073 -2.662500
64 -72.000000 -8.924306 -1.855000
65 -81.000000 -7.812329 -1.023000
66 -90.000000 -6.550479 -0.250000
67 97.668785 0.000000 -4.260000
68 90.000000 -2.101724 -5.798250
69 81.000000 -3.614637 -6.212250
70 72.000000 -4.916653 -6.316500

```

```

71 63.000000 -6.189781 -6.354750
72 54.000000 -7.556057 -6.369750
73 45.000000 -8.997342 -6.375000
74 36.000000 -10.506330 -6.375000
75 27.000000 -11.789650 -6.375000
76 18.000000 -12.733802 -6.375000
77 9.000000 -13.296309 -6.375000
78 0.000000 -13.514524 -6.375000
79 -9.000000 -13.424205 -6.375000
80 -18.000000 -13.023755 -6.374250
81 -27.000000 -12.143438 -6.332250
82 -36.000000 -10.864629 -6.156000
83 -45.000000 -9.429746 -5.751750
84 -54.000000 -8.208840 -5.030250
85 -63.000000 -7.182520 -3.993750
86 -72.000000 -6.384840 -2.782500
87 -81.000000 -5.786808 -1.534500
88 -90.000000 -5.531945 -0.375000
89 95.761040 0.000000 -5.680000
90 90.000000 -1.030075 -7.247812
91 81.000000 -2.235263 -7.765313
92 72.000000 -3.299800 -7.895625
93 63.000000 -4.255499 -7.943438
94 54.000000 -5.148168 -7.962187
95 45.000000 -6.279654 -7.968750
96 36.000000 -7.575930 -7.968750
97 27.000000 -8.992423 -7.968750
98 18.000000 -10.037380 -7.968750
99 9.000000 -10.795741 -7.968750
100 0.000000 -11.084138 -7.968750
101 -9.000000 -10.806528 -7.968750
102 -18.000000 -9.203257 -7.967813
103 -27.000000 -7.053152 -7.915313
104 -36.000000 -5.685424 -7.695000
105 -45.000000 -4.595151 -7.189688
106 -54.000000 -3.902956 -6.287812
107 -63.000000 -3.458346 -4.992188
108 -72.000000 -3.151884 -3.478125
109 -81.000000 -3.009066 -1.918125
110 -90.000000 -3.936743 -0.468750
111 92.119003 0.000000 -7.100000
112 90.000000 0.000000 -7.731000
113 81.000000 0.000000 -8.283000
114 72.000000 0.000000 -8.422000
115 63.000000 0.000000 -8.473000
116 54.000000 0.000000 -8.493000
117 45.000000 0.000000 -8.500000
118 36.000000 0.000000 -8.500000
119 27.000000 0.000000 -8.500000
120 18.000000 0.000000 -8.500000
121 9.000000 0.000000 -8.500000
122 0.000000 0.000000 -8.500000
123 -9.000000 0.000000 -8.500000
124 -18.000000 0.000000 -8.499000
125 -27.000000 0.000000 -8.443000
126 -36.000000 0.000000 -8.208000
127 -45.000000 0.000000 -7.669000
128 -54.000000 0.000000 -6.707000
129 -63.000000 0.000000 -5.325000
130 -72.000000 0.000000 -3.710000
131 -81.000000 0.000000 -2.046000
132 -90.000000 0.000000 -0.500000
133 90.419998 -0.000000 0.000000
134 90.000000 0.043756 0.000000
135 81.000000 3.732279 0.000000
136 72.000000 6.023938 0.000000
137 63.000000 8.054297 0.000000
138 54.000000 9.970940 0.000000
139 45.000000 11.712228 0.000000
140 36.000000 13.130206 0.000000
141 27.000000 14.152325 0.000000

```

142 18.000000 14.790794 0.000000
143 9.000000 15.140757 0.000000
144 0.000000 15.316323 0.000000
145 -9.000000 15.376906 0.000000
146 -18.000000 15.336169 0.000000
147 -27.000000 15.183046 0.000000
148 -36.000000 14.905368 0.000000
149 -45.000000 14.486609 0.000000
150 -54.000000 13.920826 0.000000
151 -63.000000 13.183241 0.000000
152 -72.000000 12.127666 -0.000001
153 -81.000000 10.436591 0.000000
154 -90.000000 7.784397 0.000000
155 97.064507 -0.000000 -1.420000
156 90.000000 2.155141 -1.932750
157 81.000000 3.652483 -2.070750
158 72.000000 5.640112 -2.105500
159 63.000000 7.499502 -2.118250
160 54.000000 9.288836 -2.123250
161 45.000000 10.986279 -2.125000
162 36.000000 12.512541 -2.125000
163 27.000000 13.674471 -2.125000
164 18.000000 14.415432 -2.125000
165 9.000000 14.817267 -2.125000
166 0.000000 15.002799 -2.125000
167 -9.000000 15.032046 -2.125000
168 -18.000000 14.922239 -2.124750
169 -27.000000 14.648211 -2.110750
170 -36.000000 14.229990 -2.052000
171 -45.000000 13.629851 -1.917250
172 -54.000000 12.895230 -1.676750
173 -63.000000 11.987173 -1.331250
174 -72.000000 10.799935 -0.927501
175 -81.000000 9.268652 -0.511500
176 -90.000000 7.294670 -0.125000
177 98.463814 -0.000000 -2.840000
178 90.000000 2.630154 -3.865500
179 81.000000 3.958067 -4.141500
180 72.000000 5.412258 -4.211000
181 63.000000 7.008562 -4.236500
182 54.000000 8.616744 -4.246500
183 45.000000 10.243830 -4.250000
184 36.000000 11.797916 -4.250000
185 27.000000 13.038542 -4.250000
186 18.000000 13.863455 -4.250000
187 9.000000 14.318850 -4.250000
188 0.000000 14.513623 -4.250000
189 -9.000000 14.503290 -4.250000
190 -18.000000 14.300338 -4.249500
191 -27.000000 13.865146 -4.221500
192 -36.000000 13.196884 -4.104000
193 -45.000000 12.266318 -3.834500
194 -54.000000 11.200510 -3.353500
195 -63.000000 10.071073 -2.662500
196 -72.000000 8.924306 -1.855000
197 -81.000000 7.812329 -1.023000
198 -90.000000 6.550479 -0.250000
199 97.668785 -0.000000 -4.260000
200 90.000000 2.101724 -5.798250
201 81.000000 3.614637 -6.212250
202 72.000000 4.916653 -6.316500
203 63.000000 6.189781 -6.354750
204 54.000000 7.556057 -6.369750
205 45.000000 8.997342 -6.375000
206 36.000000 10.506330 -6.375000
207 27.000000 11.789650 -6.375000
208 18.000000 12.733802 -6.375000
209 9.000000 13.296309 -6.375000
210 0.000000 13.514524 -6.375000
211 -9.000000 13.424205 -6.375000
212 -18.000000 13.023755 -6.374250

```

213 -27.000000 12.143438 -6.332250
214 -36.000000 10.864629 -6.156000
215 -45.000000 9.429746 -5.751750
216 -54.000000 8.208840 -5.030250
217 -63.000000 7.182520 -3.993750
218 -72.000000 6.384840 -2.782500
219 -81.000000 5.786808 -1.534500
220 -90.000000 5.531945 -0.375000
221 95.761040 -0.000000 -5.680000
222 90.000000 1.030075 -7.247812
223 81.000000 2.235263 -7.765313
224 72.000000 3.299800 -7.895625
225 63.000000 4.255499 -7.943438
226 54.000000 5.148168 -7.962187
227 45.000000 6.279654 -7.968750
228 36.000000 7.575930 -7.968750
229 27.000000 8.992423 -7.968750
230 18.000000 10.037380 -7.968750
231 9.000000 10.795741 -7.968750
232 0.000000 11.084138 -7.968750
233 -9.000000 10.806528 -7.968750
234 -18.000000 9.203257 -7.967813
235 -27.000000 7.053152 -7.915313
236 -36.000000 5.685424 -7.695000
237 -45.000000 4.595151 -7.189688
238 -54.000000 3.902956 -6.287812
239 -63.000000 3.458346 -4.992188
240 -72.000000 3.151884 -3.478125
241 -81.000000 3.009066 -1.918125
242 -90.000000 3.936743 -0.468750
243 92.119003 -0.000000 -7.100000
244 90.000000 -0.000000 -7.731000
245 81.000000 -0.000000 -8.283000
246 72.000000 -0.000000 -8.422000
247 63.000000 -0.000000 -8.473000
248 54.000000 -0.000000 -8.493000
249 45.000000 -0.000000 -8.500000
250 36.000000 -0.000000 -8.500000
251 27.000000 -0.000000 -8.500000
252 18.000000 -0.000000 -8.500000
253 9.000000 -0.000000 -8.500000
254 0.000000 -0.000000 -8.500000
255 -9.000000 -0.000000 -8.500000
256 -18.000000 -0.000000 -8.499000
257 -27.000000 -0.000000 -8.443000
258 -36.000000 -0.000000 -8.208000
259 -45.000000 -0.000000 -7.669000
260 -54.000000 -0.000000 -6.707000
261 -63.000000 -0.000000 -5.325000
262 -72.000000 -0.000000 -3.710000
263 -81.000000 -0.000000 -2.046000
264 -90.000000 -0.000000 -0.500000
1 1 23 24 2
2 2 24 25 3
3 3 25 26 4
4 4 26 27 5
5 5 27 28 6
6 6 28 29 7
7 7 29 30 8
8 8 30 31 9
9 9 31 32 10
10 10 32 33 11
11 11 33 34 12
12 12 34 35 13
13 13 35 36 14
14 14 36 37 15
15 15 37 38 16
16 16 38 39 17
17 17 39 40 18
18 18 40 41 19
19 19 41 42 20

```

20 20 42 43 21
21 21 43 44 22
22 23 45 46 24
23 24 46 47 25
24 25 47 48 26
25 26 48 49 27
26 27 49 50 28
27 28 50 51 29
28 29 51 52 30
29 30 52 53 31
30 31 53 54 32
31 32 54 55 33
32 33 55 56 34
33 34 56 57 35
34 35 57 58 36
35 36 58 59 37
36 37 59 60 38
37 38 60 61 39
38 39 61 62 40
39 40 62 63 41
40 41 63 64 42
41 42 64 65 43
42 43 65 66 44
43 45 67 68 46
44 46 68 69 47
45 47 69 70 48
46 48 70 71 49
47 49 71 72 50
48 50 72 73 51
49 51 73 74 52
50 52 74 75 53
51 53 75 76 54
52 54 76 77 55
53 55 77 78 56
54 56 78 79 57
55 57 79 80 58
56 58 80 81 59
57 59 81 82 60
58 60 82 83 61
59 61 83 84 62
60 62 84 85 63
61 63 85 86 64
62 64 86 87 65
63 65 87 88 66
64 67 89 90 68
65 68 90 91 69
66 69 91 92 70
67 70 92 93 71
68 71 93 94 72
69 72 94 95 73
70 73 95 96 74
71 74 96 97 75
72 75 97 98 76
73 76 98 99 77
74 77 99 100 78
75 78 100 101 79
76 79 101 102 80
77 80 102 103 81
78 81 103 104 82
79 82 104 105 83
80 83 105 106 84
81 84 106 107 85
82 85 107 108 86
83 86 108 109 87
84 87 109 110 88
85 89 111 112 90
86 90 112 113 91
87 91 113 114 92
88 92 114 115 93
89 93 115 116 94
90 94 116 117 95

91 95 117 118 96
92 96 118 119 97
93 97 119 120 98
94 98 120 121 99
95 99 121 122 100
96 100 122 123 101
97 101 123 124 102
98 102 124 125 103
99 103 125 126 104
100 104 126 127 105
101 105 127 128 106
102 106 128 129 107
103 107 129 130 108
104 108 130 131 109
105 109 131 132 110
106 133 134 156 155
107 134 135 157 156
108 135 136 158 157
109 136 137 159 158
110 137 138 160 159
111 138 139 161 160
112 139 140 162 161
113 140 141 163 162
114 141 142 164 163
115 142 143 165 164
116 143 144 166 165
117 144 145 167 166
118 145 146 168 167
119 146 147 169 168
120 147 148 170 169
121 148 149 171 170
122 149 150 172 171
123 150 151 173 172
124 151 152 174 173
125 152 153 175 174
126 153 154 176 175
127 155 156 178 177
128 156 157 179 178
129 157 158 180 179
130 158 159 181 180
131 159 160 182 181
132 160 161 183 182
133 161 162 184 183
134 162 163 185 184
135 163 164 186 185
136 164 165 187 186
137 165 166 188 187
138 166 167 189 188
139 167 168 190 189
140 168 169 191 190
141 169 170 192 191
142 170 171 193 192
143 171 172 194 193
144 172 173 195 194
145 173 174 196 195
146 174 175 197 196
147 175 176 198 197
148 177 178 200 199
149 178 179 201 200
150 179 180 202 201
151 180 181 203 202
152 181 182 204 203
153 182 183 205 204
154 183 184 206 205
155 184 185 207 206
156 185 186 208 207
157 186 187 209 208
158 187 188 210 209
159 188 189 211 210
160 189 190 212 211
161 190 191 213 212

162 191 192 214 213
163 192 193 215 214
164 193 194 216 215
165 194 195 217 216
166 195 196 218 217
167 196 197 219 218
168 197 198 220 219
169 199 200 222 221
170 200 201 223 222
171 201 202 224 223
172 202 203 225 224
173 203 204 226 225
174 204 205 227 226
175 205 206 228 227
176 206 207 229 228
177 207 208 230 229
178 208 209 231 230
179 209 210 232 231
180 210 211 233 232
181 211 212 234 233
182 212 213 235 234
183 213 214 236 235
184 214 215 237 236
185 215 216 238 237
186 216 217 239 238
187 217 218 240 239
188 218 219 241 240
189 219 220 242 241
190 221 222 244 243
191 222 223 245 244
192 223 224 246 245
193 224 225 247 246
194 225 226 248 247
195 226 227 249 248
196 227 228 250 249
197 228 229 251 250
198 229 230 252 251
199 230 231 253 252
200 231 232 254 253
201 232 233 255 254
202 233 234 256 255
203 234 235 257 256
204 235 236 258 257
205 236 237 259 258
206 237 238 260 259
207 238 239 261 260
208 239 240 262 261
209 240 241 263 262
210 241 242 264 263

Appendix B: SCAN Frigate Panel Data File

312 250

```

1 60.947536 0.000000 0.000001
2 58.401402 -0.524530 0.000000
3 53.320099 -1.476002 0.000000
4 48.238800 -2.434710 0.000000
5 43.157501 -3.389315 0.000000
6 38.076199 -4.303891 0.000000
7 32.994900 -5.139366 0.000000
8 27.913601 -5.860807 0.000000
9 22.832302 -6.436203 0.000000
10 17.750999 -6.853822 0.000000
11 12.669701 -7.132783 0.000000
12 7.588402 -7.296432 0.000000
13 2.513199 -7.374531 0.000000
14 -2.568096 -7.399031 0.000000
15 -7.649399 -7.400450 0.000000
16 -12.730698 -7.374021 0.000000
17 -17.811996 -7.307408 0.000000
18 -22.893303 -7.194063 0.000000
19 -27.974602 -7.029663 0.000000
20 -33.055893 -6.821264 0.000000
21 -38.137207 -6.577001 0.000000
22 -43.218491 -6.303737 0.000001
23 -48.299797 -6.012887 0.000000
24 -53.375000 -5.705189 0.000000
25 -61.000000 -2.650257 0.000000
26 -60.984070 0.000000 0.000000
27 60.616665 0.000000 -0.555725
28 58.401402 -0.364310 -0.844978
29 53.320099 -1.109498 -1.003852
30 48.238800 -1.891655 -1.051826
31 43.157501 -2.703433 -1.099825
32 38.076199 -3.548300 -1.106274
33 32.994900 -4.368403 -1.108773
34 27.913601 -5.121401 -1.111272
35 22.832302 -5.768233 -1.113771
36 17.750999 -6.286264 -1.116270
37 12.669701 -6.678662 -1.118769
38 7.588402 -6.952518 -1.121268
39 2.513199 -7.122389 -1.123764
40 -2.568096 -7.205325 -1.126263
41 -7.649399 -7.218411 -1.128762
42 -12.730698 -7.165122 -1.131261
43 -17.811996 -7.040945 -1.133760
44 -22.893303 -6.856896 -1.100609
45 -27.974602 -6.604474 -1.063733
46 -33.055893 -6.291186 -1.026857
47 -38.137207 -5.981167 -0.923506
48 -43.218491 -5.728983 -0.714630
49 -48.299797 -5.549915 -0.462004
50 -53.375000 -5.454232 -0.260600
51 -61.000000 -2.495513 -0.085000
52 -60.981178 0.000000 -0.063992
53 60.272755 0.000000 -1.111451
54 58.401402 -0.228421 -1.689956
55 53.320099 -0.763709 -2.007704
56 48.238800 -1.332298 -2.103652
57 43.157501 -1.922484 -2.199650
58 38.076199 -2.601648 -2.212548
59 32.994900 -3.315800 -2.217546
60 27.913601 -4.033416 -2.222544
61 22.832302 -4.724860 -2.227542
62 17.750999 -5.356009 -2.232540
63 12.669701 -5.886914 -2.237538
64 7.588402 -6.284518 -2.242536
65 2.513199 -6.548412 -2.247528
66 -2.568096 -6.688030 -2.252526
67 -7.649399 -6.713046 -2.257524
68 -12.730698 -6.631817 -2.262522
69 -17.811996 -6.436563 -2.267520
70 -22.893303 -6.175168 -2.201218

```

```

71 -27.974602 -5.812051 -2.127466
72 -33.055893 -5.341232 -2.053714
73 -38.137207 -4.834467 -1.847012
74 -43.218491 -4.566773 -1.429260
75 -48.299797 -4.641788 -0.924008
76 -53.375000 -4.270584 -0.521200
77 -61.000000 -2.095455 -0.170000
78 -60.979813 0.000000 -0.127984
79 59.906570 0.000000 -1.667177
80 58.401402 -0.123587 -2.534934
81 53.320099 -0.443803 -3.011556
82 48.238800 -0.759269 -3.155478
83 43.157501 -1.041175 -3.299475
84 38.076199 -1.427769 -3.318822
85 32.994900 -1.876867 -3.326319
86 27.913601 -2.389941 -3.333816
87 22.832302 -2.977795 -3.341313
88 17.750999 -3.616584 -3.348810
89 12.669701 -4.225645 -3.356307
90 7.588402 -4.727971 -3.363804
91 2.513199 -5.092036 -3.371292
92 -2.568096 -5.301293 -3.378789
93 -7.649399 -5.342615 -3.386286
94 -12.730698 -5.234574 -3.393783
95 -17.811996 -4.941694 -3.401280
96 -22.893303 -4.623424 -3.301827
97 -27.974602 -4.131893 -3.191199
98 -33.055893 -3.449829 -3.080571
99 -38.137207 -2.749531 -2.770518
100 -43.218491 -2.456336 -2.143890
101 -48.299797 -2.659938 -1.386012
102 -53.375000 -2.783313 -0.781800
103 -61.000000 -1.375002 -0.255000
104 -60.979912 0.000000 -0.191976
105 59.506714 0.000000 -2.222903
106 58.401402 -0.062945 -3.168668
107 53.320099 -0.216737 -3.764445
108 48.238800 -0.285331 -3.944348
109 43.157501 -0.296029 -4.124344
110 38.076199 -0.469634 -4.148528
111 32.994900 -0.603456 -4.157899
112 27.913601 -0.754897 -4.167270
113 22.832302 -0.944231 -4.176641
114 17.750999 -1.165309 -4.186012
115 12.669701 -1.368239 -4.195384
116 7.588402 -1.507736 -4.204755
117 2.513199 -1.585675 -4.214115
118 -2.568096 -1.619489 -4.223486
119 -7.649399 -1.624381 -4.232858
120 -12.730698 -1.579017 -4.242229
121 -17.811996 -1.470034 -4.251600
122 -22.893303 -1.593219 -4.127284
123 -27.974602 -1.820787 -3.988999
124 -33.055893 -1.319206 -3.850714
125 -38.137207 -0.864621 -3.463148
126 -43.218491 -0.647852 -2.679862
127 -48.299797 -0.664984 -1.732515
128 -53.375000 -0.833728 -0.977250
129 -61.000000 -0.318747 -0.318750
130 -60.980003 0.000000 -0.255968
131 59.053799 0.000000 -2.778629
132 58.401402 0.000000 -3.379912
133 53.320099 0.000000 -4.015408
134 48.238800 0.000000 -4.207304
135 43.157501 0.000000 -4.399300
136 38.076199 0.000000 -4.425096
137 32.994900 0.000000 -4.435092
138 27.913601 0.000000 -4.445088
139 22.832302 0.000000 -4.455084
140 17.750999 0.000000 -4.465080
141 12.669701 0.000000 -4.475076

```

```

142 7.588402 0.000000 -4.485072
143 2.513199 0.000000 -4.495056
144 -2.568096 0.000000 -4.505052
145 -7.649399 0.000000 -4.515048
146 -12.730698 0.000000 -4.525044
147 -17.811996 0.000000 -4.535040
148 -22.893303 0.000000 -4.402436
149 -27.974602 0.000000 -4.254932
150 -33.055893 0.000000 -4.107428
151 -38.137207 0.000000 -3.694024
152 -43.218491 0.000000 -2.858520
153 -48.299797 0.000000 -1.848016
154 -53.375000 0.000000 -1.042400
155 -61.000000 0.000000 -0.340000
156 -60.980003 0.000000 -0.319960
157 60.947536 0.000000 0.000001
158 58.401402 0.524530 0.000000
159 53.320099 1.476002 0.000000
160 48.238800 2.434710 0.000000
161 43.157501 3.389315 0.000000
162 38.076199 4.303891 0.000000
163 32.994900 5.139366 0.000000
164 27.913601 5.860807 0.000000
165 22.832302 6.436203 0.000000
166 17.750999 6.853822 0.000000
167 12.669701 7.132783 0.000000
168 7.588402 7.296432 0.000000
169 2.513199 7.374531 0.000000
170 -2.568096 7.399031 0.000000
171 -7.649399 7.400450 0.000000
172 -12.730698 7.374021 0.000000
173 -17.811996 7.307408 0.000000
174 -22.893303 7.194063 0.000000
175 -27.974602 7.029663 0.000000
176 -33.055893 6.821264 0.000000
177 -38.137207 6.577001 0.000000
178 -43.218491 6.303737 0.000001
179 -48.299797 6.012887 0.000000
180 -53.375000 5.705189 0.000000
181 -61.000000 2.650257 0.000000
182 -60.984070 0.000000 0.000000
183 60.616665 0.000000 -0.555725
184 58.401402 0.364310 -0.844978
185 53.320099 1.109498 -1.003852
186 48.238800 1.891655 -1.051826
187 43.157501 2.703433 -1.099825
188 38.076199 3.548300 -1.106274
189 32.994900 4.368403 -1.108773
190 27.913601 5.121401 -1.111272
191 22.832302 5.768233 -1.113771
192 17.750999 6.286264 -1.116270
193 12.669701 6.678662 -1.118769
194 7.588402 6.952518 -1.121268
195 2.513199 7.122389 -1.123764
196 -2.568096 7.205325 -1.126263
197 -7.649399 7.218411 -1.128762
198 -12.730698 7.165122 -1.131261
199 -17.811996 7.040945 -1.133760
200 -22.893303 6.856896 -1.100609
201 -27.974602 6.604474 -1.063733
202 -33.055893 6.291186 -1.026857
203 -38.137207 5.981167 -0.923506
204 -43.218491 5.728983 -0.714630
205 -48.299797 5.549915 -0.462004
206 -53.375000 5.454232 -0.260600
207 -61.000000 2.495513 -0.085000
208 -60.981178 0.000000 -0.063992
209 60.272755 0.000000 -1.111451
210 58.401402 0.228421 -1.689956
211 53.320099 0.763709 -2.007704
212 48.238800 1.332298 -2.103652

```

213 43.157501 1.922484 -2.199650
 214 38.076199 2.601648 -2.212548
 215 32.994900 3.315800 -2.217546
 216 27.913601 4.033416 -2.222544
 217 22.832302 4.724860 -2.227542
 218 17.750999 5.356009 -2.232540
 219 12.669701 5.886914 -2.237538
 220 7.588402 6.284518 -2.242536
 221 2.513199 6.548412 -2.247528
 222 -2.568096 6.688030 -2.252526
 223 -7.649399 6.713046 -2.257524
 224 -12.730698 6.631817 -2.262522
 225 -17.811996 6.436563 -2.267520
 226 -22.893303 6.175168 -2.201218
 227 -27.974602 5.812051 -2.127466
 228 -33.055893 5.341232 -2.053714
 229 -38.137207 4.834467 -1.847012
 230 -43.218491 4.566773 -1.429260
 231 -48.299797 4.641788 -0.924008
 232 -53.375000 4.270584 -0.521200
 233 -61.000000 2.095455 -0.170000
 234 -60.979813 0.000000 -0.127984
 235 59.906570 0.000000 -1.667177
 236 58.401402 0.123587 -2.534934
 237 53.320099 0.443803 -3.011556
 238 48.238800 0.759269 -3.155478
 239 43.157501 1.041175 -3.299475
 240 38.076199 1.427769 -3.318822
 241 32.994900 1.876867 -3.326319
 242 27.913601 2.389941 -3.333816
 243 22.832302 2.977795 -3.341313
 244 17.750999 3.616584 -3.348810
 245 12.669701 4.225645 -3.356307
 246 7.588402 4.727971 -3.363804
 247 2.513199 5.092036 -3.371292
 248 -2.568096 5.301293 -3.378789
 249 -7.649399 5.342615 -3.386286
 250 -12.730698 5.234574 -3.393783
 251 -17.811996 4.941694 -3.401280
 252 -22.893303 4.623424 -3.301827
 253 -27.974602 4.131893 -3.191199
 254 -33.055893 3.449829 -3.080571
 255 -38.137207 2.749537 -2.770518
 256 -43.218491 2.456336 -2.143890
 257 -48.299797 2.659938 -1.386012
 258 -53.375000 2.783313 -0.781800
 259 -61.000000 1.375002 -0.255000
 260 -60.979912 0.000000 -0.191976
 261 59.506714 0.000000 -2.222903
 262 58.401402 0.062945 -3.168668
 263 53.320099 0.216737 -3.764445
 264 48.238800 0.285331 -3.944348
 265 43.157501 0.296029 -4.124344
 266 38.076199 0.469634 -4.148528
 267 32.994900 0.603456 -4.157899
 268 27.913601 0.754897 -4.167270
 269 22.832302 0.944231 -4.176641
 270 17.750999 1.165309 -4.186012
 271 12.669701 1.368239 -4.195384
 272 7.588402 1.507736 -4.204755
 273 2.513199 1.585675 -4.214115
 274 -2.568096 1.619489 -4.223486
 275 -7.649399 1.624381 -4.232858
 276 -12.730698 1.579017 -4.242229
 277 -17.811996 1.470034 -4.251600
 278 -22.893303 1.593219 -4.127284
 279 -27.974602 1.820787 -3.988999
 280 -33.055893 1.319206 -3.850714
 281 -38.137207 0.864621 -3.463148
 282 -43.218491 0.647952 -2.679862
 283 -48.299797 0.664984 -1.732515

```

284 -53.375000 0.833728 -0.977250
285 -61.000000 0.318747 -0.318750
286 -60.980003 0.000000 -0.255968
287 59.053799 0.000000 -2.778629
288 58.401402 0.000000 -3.379912
289 53.320099 0.000000 -4.015408
290 48.238800 0.000000 -4.207304
291 43.157501 0.000000 -4.399300
292 38.076199 0.000000 -4.425096
293 32.994900 0.000000 -4.435092
294 27.913601 0.000000 -4.445088
295 22.832302 0.000000 -4.455084
296 17.750999 0.000000 -4.465080
297 12.669701 0.000000 -4.475076
298 7.588402 0.000000 -4.485072
299 2.513199 0.000000 -4.495056
300 -2.568096 0.000000 -4.505052
301 -7.649399 0.000000 -4.515048
302 -12.730698 0.000000 -4.525044
303 -17.811996 0.000000 -4.535040
304 -22.893303 0.000000 -4.402436
305 -27.974602 0.000000 -4.254932
306 -33.055893 0.000000 -4.107428
307 -38.137207 0.000000 -3.694024
308 -43.218491 0.000000 -2.858520
309 -48.299797 0.000000 -1.848016
310 -53.375000 0.000000 -1.042400
311 -61.000000 0.000000 -0.340000
312 -60.980003 0.000000 -0.319960
1 1 27 28 2
2 2 28 29 3
3 3 29 30 4
4 4 30 31 5
5 5 31 32 6
6 6 32 33 7
7 7 33 34 8
8 8 34 35 9
9 9 35 36 10
10 10 36 37 11
11 11 37 38 12
12 12 38 39 13
13 13 39 40 14
14 14 40 41 15
15 15 41 42 16
16 16 42 43 17
17 17 43 44 18
18 18 44 45 19
19 19 45 46 20
20 20 46 47 21
21 21 47 48 22
22 22 48 49 23
23 23 49 50 24
24 24 50 51 25
25 25 51 52 26
26 27 53 54 28
27 28 54 55 29
28 29 55 56 30
29 30 56 57 31
30 31 57 58 32
31 32 58 59 33
32 33 59 60 34
33 34 60 61 35
34 35 61 62 36
35 36 62 63 37
36 37 63 64 38
37 38 64 65 39
38 39 65 66 40
39 40 66 67 41
40 41 67 68 42
41 42 68 69 43
42 43 69 70 44

```

43 44 70 71 45
44 45 71 72 46
45 46 72 73 47
46 47 73 74 48
47 48 74 75 49
48 49 75 76 50
49 50 76 77 51
50 51 77 78 52
51 53 79 80 54
52 54 80 81 55
53 55 81 82 56
54 56 82 83 57
55 57 83 84 58
56 58 84 85 59
57 59 85 86 60
58 60 86 87 61
59 61 87 88 62
60 62 88 89 63
61 63 89 90 64
62 64 90 91 65
63 65 91 92 66
64 66 92 93 67
65 67 93 94 68
66 68 94 95 69
67 69 95 96 70
68 70 96 97 71
69 71 97 98 72
70 72 98 99 73
71 73 99 100 74
72 74 100 101 75
73 75 101 102 76
74 76 102 103 77
75 77 103 104 78
76 79 105 106 80
77 80 106 107 81
78 81 107 108 82
79 82 108 109 83
80 83 109 110 84
81 84 110 111 85
82 85 111 112 86
83 86 112 113 87
84 87 113 114 88
85 88 114 115 89
86 89 115 116 90
87 90 116 117 91
88 91 117 118 92
89 92 118 119 93
90 93 119 120 94
91 94 120 121 95
92 95 121 122 96
93 96 122 123 97
94 97 123 124 98
95 98 124 125 99
96 99 125 126 100
97 100 126 127 101
98 101 127 128 102
99 102 128 129 103
100 103 129 130 104
101 105 131 132 106
102 106 132 133 107
103 107 133 134 108
104 108 134 135 109
105 109 135 136 110
106 110 136 137 111
107 111 137 138 112
108 112 138 139 113
109 113 139 140 114
110 114 140 141 115
111 115 141 142 116
112 116 142 143 117
113 117 143 144 118

114 118 144 145 119
115 119 145 146 120
116 120 146 147 121
117 121 147 148 122
118 122 148 149 123
119 123 149 150 124
120 124 150 151 125
121 125 151 152 126
122 126 152 153 127
123 127 153 154 128
124 128 154 155 129
125 129 155 156 130
126 157 158 184 183
127 158 159 185 184
128 159 160 186 185
129 160 161 187 186
130 161 162 188 187
131 162 163 189 188
132 163 164 190 189
133 164 165 191 190
134 165 166 192 191
135 166 167 193 192
136 167 168 194 193
137 168 169 195 194
138 169 170 196 195
139 170 171 197 196
140 171 172 198 197
141 172 173 199 198
142 173 174 200 199
143 174 175 201 200
144 175 176 202 201
145 176 177 203 202
146 177 178 204 203
147 178 179 205 204
148 179 180 206 205
149 180 181 207 206
150 181 182 208 207
151 183 184 210 209
152 184 185 211 210
153 185 186 212 211
154 186 187 213 212
155 187 188 214 213
156 188 189 215 214
157 189 190 216 215
158 190 191 217 216
159 191 192 218 217
160 192 193 219 218
161 193 194 220 219
162 194 195 221 220
163 195 196 222 221
164 196 197 223 222
165 197 198 224 223
166 198 199 225 224
167 199 200 226 225
168 200 201 227 226
169 201 202 228 227
170 202 203 229 228
171 203 204 230 229
172 204 205 231 230
173 205 206 232 231
174 206 207 233 232
175 207 208 234 233
176 209 210 236 235
177 210 211 237 236
178 211 212 238 237
179 212 213 239 238
180 213 214 240 239
181 214 215 241 240
182 215 216 242 241
183 216 217 243 242
184 217 218 244 243

185	218	219	245	244
186	219	220	246	245
187	220	221	247	246
188	221	222	248	247
189	222	223	249	248
190	223	224	250	249
191	224	225	251	250
192	225	226	252	251
193	226	227	253	252
194	227	228	254	253
195	228	229	255	254
196	229	230	256	255
197	230	231	257	256
198	231	232	258	257
199	232	233	259	258
200	233	234	260	259
201	235	236	262	261
202	236	237	263	262
203	237	238	264	263
204	238	239	265	264
205	239	240	266	265
206	240	241	267	266
207	241	242	268	267
208	242	243	269	268
209	243	244	270	269
210	244	245	271	270
211	245	246	272	271
212	246	247	273	272
213	247	248	274	273
214	248	249	275	274
215	249	250	276	275
216	250	251	277	276
217	251	252	278	277
218	252	253	279	278
219	253	254	280	279
220	254	255	281	280
221	255	256	282	281
222	256	257	283	282
223	257	258	284	283
224	258	259	285	284
225	259	260	286	285
226	261	262	288	287
227	262	263	289	288
228	263	264	290	289
229	264	265	291	290
230	265	266	292	291
231	266	267	293	292
232	267	268	294	293
233	268	269	295	294
234	269	270	296	295
235	270	271	297	296
236	271	272	298	297
237	272	273	299	298
238	273	274	300	299
239	274	275	301	300
240	275	276	302	301
241	276	277	303	302
242	277	278	304	303
243	278	279	305	304
244	279	280	306	305
245	280	281	307	306
246	281	282	308	307
247	282	283	309	308
248	283	284	310	309
249	284	285	311	310
250	285	286	312	311

Appendix C: Viscous Damping Data for ALSC

```

1      1      1      1      1
21    9      14
999.099976 1.13999999E-06
0.5    0.011
1      73.656    15.557    4.151    0.226
1      194.18    20.93     5.906    1.98
1      234.36    22.594    7.548    3.623
1      261.14    26.298    9.152    5.227
1      291.27    27.78     10.567   6.6422
1      334.8     28.89     11.52    7.585
1      344.84    29.817    12.077   8.152
1      354.89    30.45     12.266   8.34
1      368.28    30.51     12.425   8.5
1      374.976   30.633    12.425   8.5
1      374.976   30.633    12.425   8.5
1      374.976   30.57     12.425   8.5
1      351.54    29.63     12.425   8.5
1      344.844   28.336    12.425   8.5
1      321.408   26.298    12.425   8.5
1      294.624   23.335    12.425   8.495
1      264.492   21.854    12.3      8.375
1      251.1     16         12.28     8.355
1      214.272   12.04     12.26     8.335
1      194.184   7.408     12.07     8.523
1      85.374    0.11      11.51     7.575
4.151    76.     0.         0.         4.5
5.906    66.     0.         0.         9.
7.548    55.     0.         0.         9.
9.152    41.5    0.         0.42       9.
10.567   31.5    0.         1.52       9.0
11.51    25.     0.         2.62       9.0
12.077   18.     0.         3.00       9.
12.266   13.     0.         3.72       9.0
12.425   10.5    10.205     3.72       9.0
12.425   10.5    10.645     3.72       9.0
12.425   10.5    10.846     3.72       9.0
12.425   9.5     10.865     3.72       9.0
12.425   11.0    10.675     3.72       9.0
12.425   14.0    10.252     3.62       9.0
12.425   18.0    0.         2.85       9.0
12.42    20.0    0.         2.50       9.0
12.3      18.0    0.         2.3        9.0
12.28     15.0    0.         2.0        9.0
12.26     11.0    0.         1.9        9.0
12.07      0.01    0.         1.8        9.0
11.51      0.01    0.         0.0        4.5
0.         0.         0.         0.
0.         0.         0.566     0.
0.         0.         0.755     0.
0.         0.         0.86      0.
0.         0.         0.944     0.
0.         0.         0.90      0.
0.         0.         0.89      0.
0.         0.         0.89      0.
0.471      7.         0.83      0.
0.471      7.5        0.83      0.
0.471      7.719     0.83      0.
0.471      7.719     0.83      0.
0.471      7.6        0.83      0.
0.471      7.         0.85      0.
0.         0.         0.99      0.
0.         0.         1.15      0.
0.         0.         1.23      0.
0.         0.         1.90      0.
0.         0.         2.5        0.
0.         0.         3.02      0.
0.         0.         0.         0.
0.         3.925    5.4      0.         27.0
2      1.17
9.0
8.3

```

90.0
5.0
5.0
5.4
-9.0
8.3
-90.0
5.0
5.0
5.4

Appendix D: Viscous Damping Data for SCAN Frigate

```

1      1      1      1      1
25    9    15
999.099976 1.13999999E-06
0.8    0.026
1    14.3    4.95    2.251    0.196
1    55.17    11.26    2.975    0.92
1    51.78    11.90    3.775    1.72
1    57.35    12.55    4.789    2.744
1    62.53    13.16    5.665    3.61
1    72.88    13.68    6.095    4.04
1    73.68    14.10    6.230    4.175
1    76.87    14.47    6.385    4.33
1    80.45    14.68    6.555    4.50
1    82.84    14.783    6.555    4.50
1    82.85    14.783    6.555    4.50
1    82.85    14.783    6.555    4.50
1    80.05    14.783    6.555    4.50
1    77.26    14.65    6.555    4.50
1    76.86    14.37    6.555    4.50
1    70.10    13.84    6.555    4.50
1    67.30    13.00    6.555    4.50
1    66.51    11.84    6.555    4.50
1    60.14    10.47    6.555    4.50
1    53.37    8.84    6.555    4.50
1    51.97    7.00    6.555    4.50
1    47.75    5.05    6.315    4.26
1    43.41    3.00    6.105    4.05
1    42.59    1.16    5.505    3.45
1    15.00    0.01    2.065    0.01
2.251 45. 0. 0.98    3.81
2.975 43. 0. 1.38    6.35
3.775 43. 0. 1.78    5.08
4.789 43. 0. 2.18    5.08
5.665 43. 0. 2.58    5.08
6.095 40. 0. 2.98    5.08
6.230 35. 0. 3.38    5.08
6.385 30. 0. 3.78    5.08
6.555 28. 4.185    4.18    5.08
6.555 20. 4.385    4.59    5.08
6.555 20. 4.487    4.59    5.08
6.555 20. 4.72    4.59    5.08
6.555 13. 4.795    4.184    5.08
6.555 19. 4.475    3.784    5.08
6.555 26. 4.375    3.384    5.08
6.555 29. 0. 0.1    5.08
6.555 35. 0. 0.1    5.08
6.555 39. 0. 0.1    5.08
6.555 40. 0. 0.1    5.08
6.555 40. 0. 0.1    5.08
6.555 40. 0. 0.1    5.08
6.315 35. 0. 0.1    5.08
6.105 23. 0. 0.1    5.08
5.505 10. 0. 0.1    6.39
2.065 0.1 0. 0.1    3.85
0. 0. 0.23 0.
0. 0. 0.39 0.
0. 0. 1.25 0.
0. 0. 2.30 0.
0. 0. 1.85 0.
0. 0. 1.18 0.
0. 0. 1.95 0.
0. 0. 1.22 0.
0.484 4.4 1.22 0.
0.484 4.6 1.22 0.
0.484 4.8 1.33 0.
0.484 4.95 1.22 0.
0.484 5.15 1.22 0.
0.484 5.20 1.22 0.
0.484 5.25 1.45 0.
0. 0. 1.67 0.
0. 0. 1.82 0.

```

0.	0.	0.	0.		
0.	0.	0.	0.		
0.	0.	0.	0.		
0.	0.	0.	0.		
0.	0.	0.	0.		
0.	0.	0.	0.		
0.	0.	0.	0.		
0.	0.	0.	0.		
2.5	2.055	5.3	1.02	25.97	
9	1.17				
3.5	2.9	97.	0.5	0.5	2.0
-3.5	2.9	-97.	0.5	0.5	2.0
1.9	2.3	47.	0.5	0.5	2.0
-1.9	2.3	-47.	0.5	0.5	2.0
4.1	3.6	104.	1.0	1.0	3.3
-4.1	3.6	-104.	1.0	1.0	3.3
1.0	2.9	48.	1.0	1.0	3.4
-1.0	2.9	-48.	1.0	1.0	3.4
0.0	4.5	90.	4.95	4.95	1.16

Appendix E: Wave Input Data

3
5.0 12.4

Appendix F: The Output Sample of Run Set 4-1

SHIPINT Program Output Results

Date of Computation:

Dec. 6, 1999

Form of ship_a:

ALSC

panel file : alsc.panel

Ship_a geometrical principals:

L= 180.00(m.) B= 30.63(m.) T= 8.50(m.) Vol= 27535.00(m.^3) Cb= 0.59

Xg= -1.69(m.) Yg= 0.00(m.) Zg= 3.92(m.)

r144= 8.05(m.) r155= 45.00(m.) r166= 45.00(m.)

Control parameters in six degree of motion:

1. 1. 0. 0. 0. 1.

Form of ship_b:

SCAN

panel file : scan.panel

Ship_b geometrical principals:

L= 122.00(m.) B= 14.78(m.) T= 4.50(m.) Vol= 3925.54(m.^3) Cb= 0.48

Xg= 3.28(m.) Yg= 0.00(m.) Zg= 2.06(m.)

r144= 4.92(m.) r155= 30.50(m.) r166= 30.50(m.)

Control parameters in six degree of motion:

1. 1. 0. 0. 0. 1.

Separation distance:

Lateral gap= 30.00(m.) Dy= 52.705(m.) Dx= 0.00(m.)

ship speed: 0.000(m/s)

number of wave heading angles: 1

no. heading(Deg.)

1 180.

number of wave length to ship length ratios: 7

no. Lambda/Lb

1 0.25

2 0.50

3 0.75

4 1.00

5 1.25

6 1.50

7 2.00

control parameters for viscous damping and m-term: 1 1

nondimensional wave exciting forces on ship_a (Heading = 180.0 (Deg.)

no.	Lamda/La	f1	f2	f3	f4	f5	f6
1	0.16944	0.00435	0.02417	0.03000	0.00017	0.00510	0.00374
2	0.33889	0.00692	0.02330	0.03907	0.00031	0.00486	0.00342
3	0.50833	0.00884	0.02813	0.04536	0.00103	0.00417	0.01071
4	0.67778	0.01892	0.06136	0.05175	0.00084	0.03534	0.00723
5	0.84722	0.03016	0.05908	0.13172	0.00046	0.04767	0.00347
6	1.01667	0.03846	0.04377	0.16210	0.00030	0.05874	0.00215
7	1.35556	0.04674	0.02756	0.23938	0.00017	0.07220	0.00094

phase angle (Deg.) of wave exciting forces on ship_a: (rel to wave crest at ship_a CG)

no.	Lamda/La	pf1	pf2	pf3	pf4	pf5	pf6
1	0.169	72.517	45.253	-153.332	32.070	-4.196	33.980
2	0.339	-41.267	-77.642	65.324	153.839	-174.674	-117.434
3	0.508	177.201	-152.197	-112.247	-76.561	-83.446	-63.912

4	0.678	4.759	-116.624	50.562	7.596	-33.262	2.132
5	0.847	-26.752	-72.190	72.800	53.681	-50.469	15.109
6	1.017	-46.948	-51.340	60.180	81.162	-63.383	25.028
7	1.356	-68.177	-31.258	36.348	116.531	-75.080	27.964

nondimensional wave exciting forces on ship_b (Heading = 180.0 (Deg.))

no.	Lamda/Lb	f1	f2	f3	f4	f5	f6
1	0.25000	0.00624	0.04001	0.06078	0.00004	0.01024	0.00701
2	0.50000	0.00760	0.02333	0.07137	0.00020	0.01451	0.00044
3	0.75000	0.02333	0.02232	0.02057	0.00043	0.06369	0.00926
4	1.00000	0.03598	0.05165	0.26809	0.00068	0.09368	0.00933
5	1.25000	0.03641	0.05193	0.36730	0.00048	0.08494	0.00540
6	1.50000	0.03569	0.03874	0.38422	0.00033	0.08203	0.00351
7	2.00000	0.03246	0.02496	0.43588	0.00021	0.07667	0.00182

phase angle (Deg.) of wave exciting forces on ship_b: (rel to wave crest at ship_b CG)

no.	Lamda/Lb	pf1	pf2	pf3	pf4	pf5	pf6
1	0.250	8.798	-178.195	166.632	-84.254	-0.031	-179.140
2	0.500	78.201	-96.300	-172.638	-43.908	76.688	160.676
3	0.750	-74.563	38.442	47.397	156.783	-82.030	156.943
4	1.000	-68.791	75.804	17.564	-132.760	-61.675	-146.261
5	1.250	-76.275	121.836	32.804	-88.074	-61.967	-119.484
6	1.500	-81.346	141.231	29.771	-68.604	-64.615	-106.477
7	2.000	-87.797	155.889	20.760	-48.342	-64.550	-88.452

nondimensional transfer function: motion dispt. amplitudes on ship_a

Heading = 180.0 (Deg.)

no.	Lamda/La	y1/a	y2/a	y3/a	y4/ka	y5/ka	y6/ka
1	0.169	0.00000	0.00000	0.01014	0.00040	0.00132	0.00000
2	0.339	0.00000	0.00000	0.04159	0.01896	0.01947	0.00000
3	0.508	0.00000	0.00000	0.23734	0.05649	0.07191	0.00000
4	0.678	0.00000	0.00000	0.17975	0.04559	0.11370	0.00000
5	0.847	0.00000	0.00000	0.19954	0.05771	0.28412	0.00000
6	1.017	0.00000	0.00000	0.28016	0.05503	0.46127	0.00000
7	1.356	0.00000	0.00000	0.47732	0.08402	0.70705	0.00000

phase angle (Deg.) of motions of ship_a: (rel to wave crest at ship_a CG)

Heading = 180.0 (Deg.)

no.	Lamda/La	pm1	pm2	pm3	pm4	pm5	pm6
1	0.169	0.000	0.000	56.983	-109.334	178.104	0.000
2	0.339	0.000	0.000	-144.730	-26.587	32.447	0.000
3	0.508	0.000	0.000	148.378	155.990	-14.191	0.000
4	0.678	0.000	0.000	110.581	-106.630	-87.472	0.000
5	0.847	0.000	0.000	58.432	-58.669	-107.596	0.000
6	1.017	0.000	0.000	30.264	-14.823	-108.804	0.000
7	1.356	0.000	0.000	8.050	31.420	-103.777	0.000

nondimensional transfer function: motion dispt. amplitudes on ship_b

Heading = 180.0 (Deg.)

no.	Lamda/Lb	y1/a	y2/a	y3/a	y4/ka	y5/ka	y6/ka
1	0.250	0.00000	0.00000	0.13572	0.02126	0.02161	0.00000

2	0.500	0.00000	0.00000	0.26403	0.14992	0.08678	0.00000
3	0.750	0.00000	0.00000	0.13272	0.58785	0.24726	0.00000
4	1.000	0.00000	0.00000	0.48499	2.01714	0.46382	0.00000
5	1.250	0.00000	0.00000	0.61457	2.08053	0.58794	0.00000
6	1.500	0.00000	0.00000	0.68982	0.66711	0.70614	0.00000
7	2.000	0.00000	0.00000	0.77926	0.19465	0.87105	0.00000

phase angle(Deg.) of motions of ship_b:(rel to wave crest at ship_b CG)

Heading = 180.0 (Deg.)

no.	Lamda/Lb	pm1	pm2	pm3	pm4	pm5	pm6
1	0.250	0.000	0.000	47.120	63.098	-117.268	0.000
2	0.500	0.000	0.000	121.974	131.194	-2.132	0.000
3	0.750	0.000	0.000	20.926	0.910	-115.101	0.000
4	1.000	0.000	0.000	20.888	91.910	-108.434	0.000
5	1.250	0.000	0.000	16.127	-109.674	-110.070	0.000
6	1.500	0.000	0.000	12.254	-59.765	-110.770	0.000
7	2.000	0.000	0.000	6.422	-16.438	-107.459	0.000

nondimensional measurement forces on ship_a (Heading = 180.0 (Deg.)

no.	Lamda/La	f1	f2	f3	f4	f5	f6
1	0.16944	0.00550	0.01383	0.00000	0.00000	0.00000	0.00276
2	0.33889	0.00928	0.00791	0.00000	0.00000	0.00000	0.00244
3	0.50833	0.00515	0.01098	0.00000	0.00000	0.00000	0.00551
4	0.67778	0.00366	0.00748	0.00000	0.00000	0.00000	0.00243
5	0.84722	0.02113	0.00622	0.00000	0.00000	0.00000	0.00133
6	1.01667	0.04222	0.00274	0.00000	0.00000	0.00000	0.00065
7	1.35556	0.06444	0.00084	0.00000	0.00000	0.00000	0.00017

phase angle (Deg.) of measurement forces on ship_a:(rel to wave crest at ship_a CG)

no.	Lamda/La	pf1	pf2	pf3	pf4	pf5	pf6
1	0.169	100.766	77.549	0.000	0.000	0.000	74.016
2	0.339	-32.749	60.908	0.000	0.000	0.000	-129.008
3	0.509	177.692	127.798	0.000	0.000	0.000	16.646
4	0.678	7.721	-173.333	0.000	0.000	0.000	103.772
5	0.847	-80.944	-130.006	0.000	0.000	0.000	148.346
6	1.017	-89.639	-103.441	0.000	0.000	0.000	-175.730
7	1.356	-90.154	-86.847	0.000	0.000	0.000	-136.065

nondimensional measurement forces on ship_b (Heading = 180.0 (Deg.)

no.	Lamda/Lb	f1	f2	f3	f4	f5	f6
1	0.25000	0.00131	0.02428	0.00000	0.00000	0.00000	0.00804
2	0.50000	0.00956	0.01893	0.00000	0.00000	0.00000	0.00210
3	0.75000	0.02348	0.04296	0.00000	0.00000	0.00000	0.00440
4	1.00000	0.03847	0.02328	0.00000	0.00000	0.00000	0.00196
5	1.25000	0.04187	0.02007	0.00000	0.00000	0.00000	0.00429
6	1.50000	0.04385	0.01127	0.00000	0.00000	0.00000	0.00185
7	2.00000	0.04287	0.00412	0.00000	0.00000	0.00000	0.00064

phase angle (Deg.) of measurement forces on ship_b:(rel to wave crest at ship_b CG)

no.	Lamda/Lb	pf1	pf2	pf3	pf4	pf5	pf6
1	0.250	40.169	-155.968	0.000	0.000	0.000	-147.990

2	0.500	19.209	-166.942	0.000	0.000	0.000	-106.296
3	0.750	-108.443	7.436	0.000	0.000	0.000	179.303
4	1.000	-100.740	65.558	0.000	0.000	0.000	-164.787
5	1.250	-103.447	87.322	0.000	0.000	0.000	-91.905
6	1.500	-105.248	112.422	0.000	0.000	0.000	-46.712
7	2.000	-103.144	139.238	0.000	0.000	0.000	2.406

RMS displacements and accelerations of ship-a
 (Heading= 180.0(Deg.), Bretschneider Spectrum
 average period T1=12.4(sec), HS=5(m)

motion_mode j	Dj	Aj
1	0.0000(m)	0.0000(g)
2	0.0000(m)	0.0000(g)
3	0.2154(m)	0.0080(g)
4	0.1017(deg)	0.0548(deg/s^2)
5	0.5627(deg)	0.1874(deg/s^2)
6	0.0000(deg)	0.0000(deg/s^2)

RMS displacements and accelerations of ship-b
 (Heading= 180.0(Deg.), Bretschneider Spectrum
 average period T1=12.4(sec), HS=5(m)

motion_mode j	Dj	Aj
1	0.0000(m)	0.0000(g)
2	0.0000(m)	0.0000(g)
3	0.4512(m)	0.0174(g)
4	2.4056(deg)	1.1653(deg/s^2)
5	0.9468(deg)	0.3887(deg/s^2)
6	0.0000(deg)	0.0000(deg/s^2)

UNCLASSIFIED
 SECURITY CLASSIFICATION OF FORM
 (highest classification of Title, Abstract, Keywords)

DOCUMENT CONTROL DATA		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall document is classified)		
1 ORIGINATOR (the name and address of the organization preparing the document. Organizations for whom the document was prepared, e.g. Establishment sponsoring a contractor's report, or tasking agency, are entered in section 8.) Centre for Marine Vessel Development and Research, DalTech, Dalhousie University	2 SECURITY CLASSIFICATION (overall security classification of the document including special warning terms if applicable) UNCLASSIFIED	
3 TITLE (the complete document title as indicated on the title page. Its classification should be indicated by the appropriate abbreviation (S,C,R or U) in parentheses after the title) Numerical Seakeeping Predictions Including Interaction Effects between Two Ships		
4 AUTHORS (Last name, first name, middle initial. If military, show rank, e.g. Doe, Maj John E.) Li, L., He, Y.J. and Hsiung, C.C.		
5 DATE OF PUBLICATION (month and year of publication of document) April 2000	6a NO OF PAGES (total containing information Include Annexes, Appendices, etc) 102	6b NO. OF REFS (total cited in document) 3
7 DESCRIPTIVE NOTES (the category of the document, e.g. technical report, technical note or memorandum. If appropriate, enter the type of report, e.g. interim, progress, summary, annual or final. Give the inclusive dates when a specific reporting period is covered) CONTRACTOR REPORT		
8 SPONSORING ACTIVITY (the name of the department project office or laboratory sponsoring the research and development. Include address) Defence Research Establishment Atlantic PO Box 1012 Dartmouth, NS, Canada B2Y 3Z7		
9a PROJECT OR GRANT NO (if appropriate, the applicable research and development project or grant number under which the document was written. Please specify whether project or grant) Project 1gb22	9b. CONTRACT NO (if appropriate, the applicable number under which the document was written) W7707-8-6038/001	
10a ORIGINATOR'S DOCUMENT NUMBER (the official document number by which the document is identified by the originating activity. This number must be unique to this document.) 	10b OTHER DOCUMENT NOS (Any other numbers which may be assigned this document either by the originator or by the sponsor.) DREA CR 2000-050	
11 DOCUMENT AVAILABILITY (any limitations on further dissemination of the document, other than those imposed by security classification) (☒) Unlimited distribution () Defence departments and defence contractors; further distribution only as approved () Defence departments and Canadian defence contractors; further distribution only as approved () Government departments and agencies; further distribution only as approved () Defence departments; further distribution only as approved () Other (please specify).		
12 DOCUMENT ANNOUNCEMENT (any limitation to the bibliographic announcement of this document. This will normally correspond to the Document Availability (11). However, where further distribution (beyond the audience specified in (11)) is possible, a wider announcement audience may be selected) Unlimited		

UNCLASSIFIED
 SECURITY CLASSIFICATION OF FORM

UNCLASSIFIED
 SECURITY CLASSIFICATION OF FORM
 (highest classification of Title, Abstract, Keywords)

13. **ABSTRACT** (a brief and factual summary of the document. It may also appear elsewhere in the body of the document itself. It is highly desirable that the abstract of classified documents be unclassified. Each paragraph of the abstract shall begin with an indication of the security classification of the information in the paragraph (unless the document itself is unclassified) represented as (S), (C), (R), or (U). It is not necessary to include here abstracts in both official languages unless the text is bilingual)

A modified version of the SHIPINT program, SHIPINT2, has been developed to compute the restraining forces and motions of the two ship interaction problem in accordance with prescribed captive model test conditions. The coupled motions are computed using a three-dimensional panel method with zero forward speed Green's function and a simple forward speed correction. With this method, the field points and source points are distributed on the wetted surface of two ships (ship-a and ship-b). The unsteady hydrodynamic forces, wave exciting forces and coupled motion amplitudes are computed based on the two ships interacting. Two ship double-body flow is used to determine the steady flow disturbance potential and velocity distribution. In this computation, the m-term computation is performed by the integral equation method based on the double body flow of two ships interacting. Alternatively, with the uniform flow assumption, the approximate m-terms can also be used in this study. Schmitke's method is applied to compute the viscous roll damping coefficients for ship-a and ship-b separately. The viscous interaction between the two ships is neglected. Spectral analyses for irregular waves are also carried out for ship-a and ship-b.

Calculations have been carried out in regular waves with heading angles of 120, 150, and 180 degrees for two forward speeds of 12 knots and 0 knots. Also considered is a lateral separation distance of 52.705 m, and a longitudinal separation distance $d_x/L_{ALSC} = 0.25$. Ship motions in irregular waves, using the Bretschneider spectrum for Sea State 6 ($H_s = 5.0$ m, $T_p = 12.4$ s), have also been computed.

14. **KEYWORDS, DESCRIPTORS or IDENTIFIERS** (technically meaningful terms or short phrases that characterize a document and could be helpful in cataloguing the document. They should be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location may also be included. If possible keywords should be selected from a published thesaurus e.g. Thesaurus of Engineering and Scientific Terms (TEST) and that thesaurus-identified. If it not possible to select indexing terms which are Unclassified, the classification of each should be indicated as with the title)

seakeeping
 replenishment at sea
 restraining forces
 hydrodynamic interaction
 frequency domain
 ship motions

UNCLASSIFIED
 SECURITY CLASSIFICATION OF FORM

The Defence Research
and Development Branch
provides Science and
Technology leadership
in the advancement and
maintenance of Canada's
defence capabilities.

Leader en sciences et
technologie de la défense,
la Direction de la recherche
et du développement pour
la défense contribue
à maintenir et à
accroître les compétences
du Canada dans
ce domaine.

#514934

