

REPORT DOCUMENTATION PAGE			Form Approved OMB NO. 0704-0188		
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA, 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 03-03-2016		2. REPORT TYPE Final Report		3. DATES COVERED (From - To) 20-Jun-2014 - 19-Mar-2015	
4. TITLE AND SUBTITLE Final Report: Localization of Gunfire from Multiple Shooters (ARO Research Topic 5.2, Information Processing & Fusion; STIR Program)			5a. CONTRACT NUMBER W911NF-14-1-0270		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHORS Richard J. Kozick			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAMES AND ADDRESSES Bucknell University Bucknell University 1 Dent Drive Lewisburg, PA 17837 -2005			8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSOR/MONITOR'S ACRONYM(S) ARO		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S) 65977-CS-II.2		
12. DISTRIBUTION AVAILABILITY STATEMENT Approved for Public Release; Distribution Unlimited					
13. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.					
14. ABSTRACT Soldier-wearable gunfire detection systems (SW-GDS) are important for situational awareness because they provide an estimate of the shooter's location and the trajectory of the bullet. Individual SW-GDS units provide an estimate of the range and bearing to the shooter for each shot, as well as "raw" data that includes time-of-arrival (TOA) and direction-of-arrival (DOA) of the muzzle blast (MB) produced by the weapon and the shock wave (SW) produced by the supersonic bullet. The localization accuracy is improved with data fusion between networked SW-GDS sensor units. We study models for bullet deceleration and develop efficient localization algorithms that					
15. SUBJECT TERMS gunfire localization, time of arrival, angle of arrival, muzzle blast, shock wave, bullet deceleration, fusion					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	15. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Richard Kozick
a. REPORT UU	b. ABSTRACT UU	c. THIS PAGE UU			19b. TELEPHONE NUMBER 570-577-1129

Report Title

Final Report: Localization of Gunfire from Multiple Shooters (ARO Research Topic 5.2, Information Processing & Fusion; STIR Program)

ABSTRACT

Soldier-wearable gunfire detection systems (SW-GDS) are important for situational awareness because they provide an estimate of the shooter's location and the trajectory of the bullet. Individual SW-GDS units provide an estimate of the range and bearing to the shooter for each shot, as well as "raw" data that includes time-of-arrival (TOA) and direction-of-arrival (DOA) of the muzzle blast (MB) produced by the weapon and the shock wave (SW) produced by the supersonic bullet. The localization accuracy is improved with data fusion between networked SW-GDS sensor units. We study models for bullet deceleration and develop efficient localization algorithms that explicitly incorporate the deceleration models in the data fusion. Localization algorithms are developed for individual SW-GDS units and fusion of networked SW-GDS units. A statistical analysis of mismatch between the assumed model and actual deceleration is performed, and the localization algorithms are tested with simulations and measured data. The deceleration models and localization algorithms are described in detail in a technical report.

Enter List of papers submitted or published that acknowledge ARO support from the start of the project to the date of this printing. List the papers, including journal references, in the following categories:

(a) Papers published in peer-reviewed journals (N/A for none)

Received

Paper

TOTAL:

Number of Papers published in peer-reviewed journals:

(b) Papers published in non-peer-reviewed journals (N/A for none)

Received

Paper

TOTAL:

Number of Papers published in non peer-reviewed journals:

(c) Presentations

Number of Presentations: 0.00

Non Peer-Reviewed Conference Proceeding publications (other than abstracts):

Received Paper

TOTAL:

Number of Non Peer-Reviewed Conference Proceeding publications (other than abstracts):

Peer-Reviewed Conference Proceeding publications (other than abstracts):

Received Paper

TOTAL:

Number of Peer-Reviewed Conference Proceeding publications (other than abstracts):

(d) Manuscripts

Received Paper

TOTAL:

Number of Manuscripts:

Books

Received Book

TOTAL:

Received Book Chapter

TOTAL:

Patents Submitted

Patents Awarded

Awards

Graduate Students

<u>NAME</u>	<u>PERCENT_SUPPORTED</u>
FTE Equivalent:	
Total Number:	

Names of Post Doctorates

<u>NAME</u>	<u>PERCENT_SUPPORTED</u>
FTE Equivalent:	
Total Number:	

Names of Faculty Supported

<u>NAME</u>	<u>PERCENT SUPPORTED</u>	National Academy Member
Richard J. Kozick	0.20	
FTE Equivalent:	0.20	
Total Number:	1	

Names of Under Graduate students supported

<u>NAME</u>	<u>PERCENT SUPPORTED</u>
FTE Equivalent:	
Total Number:	

Student Metrics

This section only applies to graduating undergraduates supported by this agreement in this reporting period

The number of undergraduates funded by this agreement who graduated during this period: 0.00

The number of undergraduates funded by this agreement who graduated during this period with a degree in science, mathematics, engineering, or technology fields:..... 0.00

The number of undergraduates funded by your agreement who graduated during this period and will continue to pursue a graduate or Ph.D. degree in science, mathematics, engineering, or technology fields:..... 0.00

Number of graduating undergraduates who achieved a 3.5 GPA to 4.0 (4.0 max scale):..... 0.00

Number of graduating undergraduates funded by a DoD funded Center of Excellence grant for Education, Research and Engineering:..... 0.00

The number of undergraduates funded by your agreement who graduated during this period and intend to work for the Department of Defense 0.00

The number of undergraduates funded by your agreement who graduated during this period and will receive scholarships or fellowships for further studies in science, mathematics, engineering or technology fields:..... 0.00

Names of Personnel receiving masters degrees

<u>NAME</u>
Total Number:

Names of personnel receiving PHDs

<u>NAME</u>
Total Number:

Names of other research staff

<u>NAME</u>	<u>PERCENT SUPPORTED</u>
FTE Equivalent:	
Total Number:	

Sub Contractors (DD882)

Inventions (DD882)

Scientific Progress

A survey of several bullet deceleration models is presented.

For each deceleration model, mathematical expressions are developed that relate the soldier-wearable gunfire detection system (SW-GDS) position and the shooter's position to the measured acoustic data, consisting of time-of-arrival (TOA) and direction-of-arrival (DOA) of the muzzle blast (MB) produced by the weapon and the shock wave (SW) produced by the supersonic bullet. These expressions form the basis for shooter localization algorithms.

In order to exploit SW data for shooter localization, it is necessary to determine the "SW detach range", which is the location along the bullet's trajectory at which the SW begins to propagate to the sensor. The SW detach range depends on the bullet deceleration model. We develop efficient algorithms for finding the SW detach range, consisting of closed-form expressions for some deceleration models, and rapidly-converging iterative algorithms for the other deceleration models.

The bullet deceleration model assumed in the localization algorithm may be different than the actual deceleration of the bullet. A statistical analysis of the fusion algorithm is performed to assess the effect of this mismatch in terms of bias and variance of the shooter location estimate.

The "drag force" (DF) bullet deceleration model is the most accurate, based on support from theory and experiments. For the DF model, we provide a complete shooter localization algorithm for individual SW-GDS units as well as a fusion algorithm for networked SW-GDS units.

The performance of the fusion algorithm for shooter localization is evaluated with simulations and field-measured data.

These items are described in detail in a separate document that is submitted as a Technical Report.

Technology Transfer