

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

1. REPORT DATE (DD-MM-YYYY) 01 June 2016		2. REPORT TYPE Technical Paper		3. DATES COVERED (From - To) 01 October 2013 – 30 September 2014	
4. TITLE AND SUBTITLE Annual Report 2014: High Fidelity Modeling of Field-Reversed Configuration (FRC) Thrusters				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Justin Koo				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER Q1AM	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQRS 1 Ara Drive Edwards AFB, CA 93524-7013				8. PERFORMING ORGANIZATION REPORT NO.	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQR 5 Pollux Drive Edwards AFB, CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-RQ-ED-TP-2016-081	
12. DISTRIBUTION / AVAILABILITY STATEMENT Distribution A: Approved for Public Release; Distribution Unlimited. PA Clearance #16201; Clearance Date 4/27/2016. The U.S. Government is joint author of the work and has the right to use, modify, reproduce, release, perform, display, or disclose the work.					
13. SUPPLEMENTARY NOTES Annual Report 2014 - Report Start Date: 10/01/2013 Report End Date: 09/30/2014					
14. ABSTRACT This report reviews our effort to develop an advanced multiscale and multifidelity Modeling & Simulation (M&S) capability targeted at the fundamental studies of the physical characteristics of Field Reversed Configuration (FRC) plasma for advanced space propulsion. This effort consists of numerical model development, physical model development, and systematic studies of the non-linear plasma dynamics and finite rate processes governing FRC formation, acceleration, stability and interaction with the environment.					
15. SUBJECT TERMS N/A					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			J. Koo
Unclassified	Unclassified	Unclassified	SAR	4	19b. TELEPHONE NO (include area code) N/A

Annual Report 2014
High Fidelity Modeling of Field-Reversed Configuration (FRC) Thrusters
 Report Start Date: 10/01/2013

Report End Date: 09/30/2014

Justin Koo, AFRL/RQRS

This report reviews our effort to develop an advanced multiscale and multifidelity Modeling & Simulation (M&S) capability targeted at the fundamental studies of the physical characteristics of Field Reversed Configuration (FRC) plasma for advanced space propulsion. This effort consists of numerical model development, physical model development, and systematic studies of the non-linear plasma dynamics and finite rate processes governing FRC formation, acceleration, stability and interaction with the environment.

The Field-Reversed Configuration (FRC), a type of closed-field plasmoid (CFP) is a self-organized magnetized plasma configuration in the shape of a highly compact toroid, characterized by the presence of closed magnetic field lines and a high ratio of toroidal to poloidal current. To date, a limited number of laboratory thrusters have demonstrated the feasibility of using FRCs for propulsion application. Two of the most advanced designs are based on the theta-pinch formation and the RMF formation mechanism, which forms the plasmoid through the induced electron current from a rotating magnetic field (RMF) as shown in Figure 1.




Figure 1. Schematic of RMF FRC thruster (left) and typical saddle coil geometry (right)

While the use of FRCs as a high efficiency/high thrust successor to the current generation of Electric Propulsion (EP) devices (HETs and Ion thrusters) holds great promise, especially as the foundation of a true hybrid chemical/electric propulsion capability, the need to optimize these devices for relatively low (1-10kW power levels) to make them relevant to modern satellites requires a much more comprehensive understanding of the fundamental physics of these devices. To achieve this understanding, it is necessary not only to construct a consistent hierarchy of plasma models describing the complex behavior of magnetized partially ionized plasmas, but also to develop an extensive suite of ancillary physics models (coil models for accurate evaluation of mutual inductance and Collisional-Radiative (CR) models for spectroscopic validation) to effectively study real FRC devices.

There are major phases of FRC thruster operation – pre-ionization, formation and translation. Each phase of FRC operation is associated with a set of technical challenges which in turn translate into several areas of focus of our research program. These include the field/plasma model, collisional physics, multiscale effects and the overall system complexity. During this period, we have focused largely on the formation phase of the FRC, both from a fully kinetic and also from a fluid perspective.

From the fully kinetic perspective, development has focused on the use of the numerical simulation of neutral entrainment in an FRC thruster with a neon propellant. A fully kinetic approach based on a Particle-In-Cell method of modeling plasmas and the Direct Simulation Monte Carlo method of modeling neutrals was applied. To perform the fully kinetic simulations, an implicit PIC code, Celeste3D, was extended to compute neutral transport and collision processes between neutral and charged particles. The collision models included all key elastic, collisional radiative, and reaction processes in neon.

The resulting two-dimensional modeling of the FRC neutral entrainment showed strong entrainment for neutral densities exceeding $5E18 \text{ m}^3$; with momentum transfer and thruster efficiency being non-linear functions of neutral density. The probability of neutral atom collision with the plasmoid was estimated at approximately 10%, with most of the collisions being charge exchange events. Electron impact ionization is not significant for a 5 eV plasmoid, but becomes a factor at 10 eV. For neutral gas injected in a 10% area of the chamber, the ion contribution to thrust was found to decrease by up to 30% due to the plasma-neutral momentum transfer when neutral density was increased to $2.5E19 \text{ m}^3$.

We have begun our fluid development by focusing on the development of a high order Multifluid (MF) method (based on the WarpX framework from the University of Washington) in order to more efficiently address the full timescale for FRC formation. This work has been greatly expedited through the hiring of two new employees, Dr. Eder Sousa (recent graduate of U. of Washington) and Dr. Artan Qerushi (formerly at Tri-Alpha). The initial work of these two hires has been focused on theoretical development efforts with further details presented in the Attachments section.

Attachments (These documents were presented outside of the reporting timeframe but represent work accomplished during the reporting period.)

- Brackbill, J., et al, "Numerical Analysis of Neutral Entrainment Effect on Field-Reversed Configuration Thruster Efficiency, Journal of Propulsion and Power, Vol 30, No. 6, Nov-Dec 2014.
- Qerushi, A, "Overview of FRC-Related Modeling (July 2014-Present)", RQ-West 6.1 Research Review (20 Jan 2015, Los Angeles, CA)
- Sousa, E, "The Discontinuous Galerkin Finite Element Method for Multi-fluid Plasma Modeling", RQ-West 6.1 Research Review (20 Jan 2015, Los Angeles, CA)