

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 31 August 2016		2. REPORT TYPE Briefing Charts		3. DATES COVERED (From - To) 31 August 2016 – 03 October 2016	
4. TITLE AND SUBTITLE Modeling Fluid-Structure Interaction in ANSYS Workbench				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Sam Dupas				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER Q0XZ	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQRM 4 Draco Drive Edwards AFB, CA 93524-7160				8. PERFORMING ORGANIZATION REPORT NO.	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RQR 5 Pollux Drive Edwards AFB, CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-RQ-ED-VG-2016-281	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for Public Release; Distribution Unlimited. The U.S. Government is joint author of the work and has the right to use, modify, reproduce, release, perform, display, or disclose the work.					
13. SUPPLEMENTARY NOTES For presentation at Intern Symposium IV (Internal); AFRL RQ-West, Edwards AFB, CA (31 August 2016) PA Case Number: #16480; Clearance Date: 10/3/2016 Prepared in collaboration with Sierra Lobo					
14. ABSTRACT Viewgraph/Briefing Charts					
15. SUBJECT TERMS N/A					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 18	19a. NAME OF RESPONSIBLE PERSON G. Trapp
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NO (include area code) N/A



Air Force Research Laboratory



Modeling Fluid- Structure Interaction in ANSYS Workbench

31 August 2016

Sam Dupas
AFRL/RQRM
Sierra Lobo, Inc.

Integrity ★ Service ★ Excellence






About Me



- **UCLA Aerospace Engineering '17**
 - Vishal Parikh Memorial Scholarship/AFRL Internship
- **UCLA Rocket Project**
 - Propulsion Chief Engineer '16-'17
 - Create a student-built hybrid rocket motor
- **AFRL/RQRM Aging & Surveillance (A&S) Group**





Outline




- Aging & Surveillance Overview
- Fluid-Structure Interaction (FSI)
- ANSYS Workbench Capabilities
 - Performing FSI Analysis in ANSYS Workbench
 - 1-Way FSI
 - 2-Way FSI
 - Automating FSI Analysis
- Conclusions & Future Work
- Acknowledgements



Aging & Surveillance Problem



- A&S attempts to figure out how an individual motor will behave after being stored for a period of time.
- Develop ways to gather data on individual motors.
- Model curing and aging of propellant, liner, and case, which all have changing mechanical properties.
- Model firing of motor to determine final behavior.
 - Goal was to use ANSYS Workbench to analyze fluid-structure interaction.
- Give a service life estimate for each individual motor, instead of a fleet wide SLE.







Fluid-Structure Interaction



- Fluid exerts loads on a solid structure, which then deforms.
 - Deformed solid changes the fluid flow characteristics.
- Situation can be modeled with various degrees of coupling between CFD and structural solvers.
 - CFD → Structural
 - CFD ↔ Structural
- In an A&S scenario, FSI is between combustion gas and remaining solid propellant.
 - Nonlinear viscoelasticity of materials makes simulation even more difficult.





ANSYS Workbench



- **Multiphysics application containing multiple solvers.**


- Fluid, Structural, Dynamics, Thermal, Electromagnetic

- **Steady state and transient simulations are possible.**

- **For FSI:**

- CFD Solver: Fluent
 - Structural Solver: ANSYS Mechanical

- **Important limitation is that data transfers are only supported for 3D simulations.**






1-Way Steady State FSI



- 2D axisymmetric geometry.
- Fluent adjusts the inlet mass flux using a user defined function (UDF).
 - $\dot{m}/A = \rho \times \dot{r} = \rho \times aP^n$
- Exporting and reimporting data allows workaround for 3D limitation.
- Solution is not coupled fully, lacks accuracy in situations with large deformations.
- 1-way data transfer does not support transient simulation.







2-Way Steady State FSI




- The fluid mesh is deformed along with the structure.
- Revolved version of 2D geometry.
- Force ramping was used to prevent excessive overshoot in solid.
 - Not valid for transient simulations.
- Max deformation was about 66% of a 1-way solution on the same geometry.
 - 9.3 mm vs 5.9 mm





Steady-State FSI Force Ramping






2-Way Transient FSI





- Overshoot issues were solved by making the time step very small (0.001 seconds).
 - Once transients die down the time step can be increased.
- Becomes useful when UDF's simulating actual motor behavior are integrated into fluid solution.
 - Transient ignition, nozzle erosion, and more.
- The propellant flap initially chokes the flow, then the flow becomes subsonic.
 - Important to avoid bore choking when designing actual motors.
- Results approach the steady state solution before breaking down from excessive deformation.





Transient FSI Results




Contours of Mach Number (Time=0.00000e+00) Aug 25, 2016
ANSYS Fluent Release 17.0 (3d, dp, pbns, dynamesh, sskw, transient)



Transient FSI Results



Maximum Displacement in Transient and Steady-State 2-Way FSI






Automating ANSYS



- ANSYS can read Python scripts with instructions on how to perform an analysis.
- Fluent & Mechanical are “Data-Integrated” applications.
 - “Native” apps like System Coupling allow for direct scripting.
 - Data-integrated apps must be sent commands in their respective scripting languages.
- Most important feature (available in both Workbench and Fluent) is ability to record journals/scripts.
 - An analyst can perform the analysis once by hand, and ANSYS will create a Python file that will replicate those actions.






Automated 1-Way FSI



- First attempt at automated analysis.
- Automatic Integrated New Technology Enableng Rapid Numerical Solutions (AutoINTERNs)
- Reads fluid and solid geometries, sets up and solves fluid problem, exports pressure to ANSYS Mechanical, and sets up structural analysis.
- Does not give a lot of flexibility in an analysis.





Automated 2-Way FSI



- **ANSYS Guided Process**
 - XML file combined with Python script.
 - HTML and images can also be added.
- **Creates a step by step process that a user can follow.**
 - Tasks like component/data linkage creation can still be automated.
 - Others like geometry creation/import can be left to the user.
- **Once coded, files are “compiled” into a single extension file that can be loaded on any ANSYS installation.**

Transient FSI Wizard

Geometry

FLUENT Meshing

FLUENT Journal File

Use Custom Journal?

FLUENT Setup

Set up FLUENT according to the instructions of a journal file. Opting not to use one will open FLUENT and allow you to set options manually.

Mechanical Model Setup

System Coupling Setup

Help

No wizard help is available



Conclusions & Future Work



Conclusions

- ANSYS Workbench provides an intuitive framework for coupled analysis.
 - Many steps can be automated, which simplifies complicated or repeated analyses.
 - 1-way coupling is generally not adequate for SRM simulation.
- ANSYS is exportable technology, which facilitates collaboration with foreign countries.
- Existing UDFs already work with Fluent, and need no modification.
- The requirement for 3D geometry increases computational load.

Future Work

- Improve long term stability of transient simulation.
- Integrate UDF's that better model transient motor behavior.
- Validate ANSYS Workbench solutions with test data.
- Add functionality to FSI Guided Process, such as images and help files.



Acknowledgements



Thanks to:

**Bill Harrigan and Geoffrey Trapp
Lt. Saif Ahmed**

And everyone else at:

RQRM

Sierra Lobo, Inc.

AFRL

UCLA