

AD/A-006 589

RESEARCH IN MICRO-TERMINAL DEVELOPMENT
AND NETWORK END-TO-END ERROR RECOVERY

Roland F. Bryan, et al

California University

Prepared for:

Advanced Research Projects Agency
Defense Supply Service

February 1975

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE

ARPA Order No: 2852

Program Code: 62706E

Grantee: The Regents of the
University of California

Effective Date: 1 September 1974

Expiration Date: 30 June 1975

Amount of Grant: \$124,962

Grant No: MDA903-75-G-2

Principal Investigator:
Roland F. Bryan (805)961-3933

Title: Research in Micro-Terminal
Development and Network
End-to-End Error Recovery

Date of Report: 27 February 1975

Period covered in Report:
October thru December 1974


083120

Sponsored by
Advanced Research Projects Agency
ARPA Order No. 2852

CSL-48

FIRST QUARTERLY TECHNICAL REPORT
10/1/74 - 12/31/74

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
U.S. Department of Commerce
Springfield VA 22151



This research was supported by the Advanced
Research Projects Agency of the Department
of Defense under Grant No. MDA903-75-G-2.



The views and conclusions contained in this document are those of the authors
and should not be interpreted as necessarily representing the official policies,
either expressed or implied, of the Advanced Research Projects Agency of the
U.S. Government.

AD A 006589

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)

University of California
Santa Barbara, California 93106

2a. REPORT SECURITY CLASSIFICATION

Unclassified

2b. GROUP

3. REPORT TITLE

RESEARCH IN MICRO-TERMINAL DEVELOPMENT AND NETWORK END-TO-END ERROR RECOVERY

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

First Quarterly Technical Report 10/1/74 - 12/31/74

5. AUTHOR(S) (Last name, first name, initial)

Roland F. Bryan
John J. McAfee

Paul E. Wells
Wm. R. Danielson

6. REPORT DATE

February 1975

7a. TOTAL NO. OF PAGES

13

7b. NO. OF REFS

0

8a. CONTRACT OR GRANT NO.

MDA903-75-G-2

b. PROJECT NO.

c. ARPA Order No: 2852

d. Program Code: 62706E

9a. ORIGINATOR'S REPORT NUMBER(S)

CSL-48

9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)

10. AVAILABILITY/LIMITATION NOTICES

Approved for public release; distribution unlimited.

11. SUPPLEMENTARY NOTES

This research is supported by the
Advanced Research Projects Agency.

12. SPONSORING MILITARY ACTIVITY

Department of the Army
Defense Supply Service-Washington
Room 1D245, The Pentagon
Washington, D.C. 20310

13. ABSTRACT

This report discusses the two tasks which are supported by the grant. They are presented as they were initially planned and as they have evolved over the first three months of the project.

In Task I, the Computer Systems Laboratory is to seek out the latest developments in miniature display, keyboard, storage, and micro-processors and incorporate these in the implementation of a highly portable computer terminal for individual use. Where devices do not exist to accomplish the task, the Laboratory is to direct and support research in the designated area. The proposed terminal will weigh less than 10 pounds, will have 8,000 words of computer storage and will equal certain minicomputers in performance. A small cassette will be added for auxiliary storage. The report discusses the progress toward realizing this goal.

In Task II, CSL is to investigate the requirements necessary for error-free, bi-directional communication between two terminals when the interconnection between terminals may not be under the control of the users themselves. For example when using a packet-switched commercial network. Processors to accomplish this task are being implemented and design specifications are being formulated.

DD FORM 1473
1 JAN 64

PRICES SUBJECT TO CHANGE

Unclassified
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Micro-Terminal						
Alpha/Numeric Terminal						
Portable Terminal						
Low Power Terminal						
End-to-End Error Checking						
Integrity of Communications						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

TABLE OF CONTENTS

	page
I. PROJECT GOALS	1
II. APPROACH	2
A. Task I	2
B. Task II	2
III. TASK I - PROGRESS TO DATE	3
A. Initial Specification	3
B. Additional Data	4
C. Guidelines	4
D. Present Configuration	5
Figure 1 - Organization	7
Figure 2 - Text Editor Features	8
IV. TASK II - PROGRESS TO DATE	9

FIRST QUARTERLY TECHNICAL REPORT

RESEARCH IN MICRO-TERMINAL DEVELOPMENT
AND NETWORK END-TO-END ERROR RECOVERY

I. PROJECT GOALS

The proposed research and development project, ending June 30, 1975, will include TASK I and TASK II with specific requirements as itemized below.

TASK I

Investigation of the requirements for, and the attributes of, a miniature "intelligent" terminal for use on a portable basis.

The development of design specifications for such a terminal, including references to commercially available component parts.

The implementation of a prototype terminal to establish the physical organization of a production terminal.

The fabrication of several field-test-units for evaluation.

A final report including recommendations for production units, fabrication documentation, and maintenance information.

TASK II

Investigation of the requirements and the application of end-to-end error checking and retransmission equipment for use on the Network.

Specification and implementation of a prototype pair of units for testing and demonstration. These units will probably contain programmable microprocessors and will be made to insure terminal-to-terminal integrity of the data being transmitted.

Consideration is to be given to a physical means for detection and correction of errors produced by the keyboard of the sending terminal and the printing mechanism in the receiving terminal.

II. APPROACH

A. Task I

A design team was organized and given the task of acquiring component parts for the terminal, from what is considered to be state-of-the-art equipment, and to implement the prototype.

The task was divided into four areas of investigation; the *processor*, the *display*, the *keyboard*, and *peripheral attachments*. The team was directed to pursue each area with vigor and to follow-up on every component which might fit within our restrictions on size and weight. The availability of selected components was to be determined and an implementation schedule was to be drawn up.

B. Task II

Researchers were assigned the task of implementing a pair of microprocessors with serial communication interfaces which would connect to standard terminal devices such as a Teletype and to the ARPANET by means of a TIP or Host. Programs within this processor pair are to transmit information from one unit to the other with full error recovery.

The two-man team which was assigned has experience with hardware and with Network protocol design.

III. TASK I - PROGRESS TO DATE

Charts showing availability of component parts are being drawn up. As our list of contacts widens we find near-term availability of the most appropriate components will be our major problem. The most useful Liquid Crystal Display, for example, may take from 1 to 2 years to get into production. Once our direction is established however, we believe that substitution of similar devices will allow the project to proceed.

The charts are not as yet complete but the design of the prototype is beginning to firm up. A realistic stop-gap machine with characteristics that will allow the change of individual elements as the preferred devices become available, is in the process of being specified.

The following paragraphs provide a view of the terminal specification as it was, and how it is evolving.

MICRO TERMINAL SPECIFICATION

A. Initial Specification

At the inception of the project we stated the terminal should have the following characteristics:

1. Portability - The terminal is to contain its own power supply, be readily carried by an individual, have the capability of being set up while seated at a small table such as in a commercial airplane.
2. Capability - The terminal must provide the user with text editing capability with as much versatility as can be built into the system. TECO-like command structure should be incorporated with those features that make the user's ability to deal with text and storage being emphasized. Storage must include the control programs, several pages of text for ready display, and magnetic tape storage for files and other information.
3. Display - The display should have a reasonable number of characters to represent a line of text and should have several lines displayed at one time. The user should be able to "scroll" through a page or more of text, both for review and for modification. The character set should contain standard symbols as well as regular alphanumeric presentation.
4. Peripherals - Attachments to the unit should include a magnetic tape cassette for storage and retrieval of files and a modem connection to allow data-set or acoustic coupler use.

B. Additional Data

Several events and factors have allowed us to narrow the range of decisions regarding implementation. These include:

1. Information from Bob Parker at USC-ISI regarding the acceptance and critique of his earlier portable terminal. To be acceptable to the user it must be less than 20 pounds in weight, it must have at least 40 characters in a line (not 32) so that it is more compatible with the line length used in TENEX, and it must have a keyboard which is large enough to allow typing by a person used to standard keyboards.
2. From our implementation of a TECO-like text editor for the IMLAC we found that the ability to scroll through a display of 4000 characters would make the terminal most useful, and that the text editor routines plus I/O modules should consume less than 4K bytes (8-bit).
3. Hughes Ground Systems Division has developed a special terminal for Forward Observer use which weights 16 pounds. They are projecting a reduction in weight to 9 pounds late in 1975. This special purpose terminal has fixed formatting and a minimal keyboard which would prohibit it for consideration as an intelligent terminal. However, it does have a transmitter, a 2 pound battery that will sustain it for 24 hours in intermittent operation, and their 9 pound version will incorporate either new low-power LEDs from H-P or the Hughes' developed Liquid Crystal display.

Information gained from these sources has helped in establishing the guidelines and the preliminary specifications for the prototype unit.

C. Guidelines

Size of the terminal will be primarily influenced by the display and the keyboard. The major factor in weight reduction is the amount of power required to operate the terminal.

With regard to size, it was our opinion that the unit should be no larger than a flat shoe box, possibly opening like a chess set. We believe that the size can be decreased when A/N Liquid Crystal displays become available.

Along with the size, we have set a weight limit of 10 pounds for the terminal, including the batteries to operate it. In considering the batteries that are presently available and the power requirements for memory, display, and tape cassette, we have established that it might be possible to operate with a

power consumption of 10 watts and we have placed this as our design goal. Our investigation of power sources is by no means complete but with a specially constructed power source, using rechargeable batteries available today, we can achieve more than 10 hours of continuous operation at somewhat over 10 watts. With our plans to reduce the duty cycle of major terminal components, this time can be extended.

D. Present Configuration

Figure 1 shows our present terminal organization. The power allotment for each of the major elements has been shown. Our choices for these elements are presently as follows:

1. Processor - RCA COSMAC or Intersil IM6100. The first has an inconvenient instruction set which might require tricky programming or cause inefficient utilization of program memory. The second looks like a PDP-8 (12 bit). Inselek and Intel project CMOS devices in 1975. These choices are made due to low power consumption. If the processor power allotment can be increased to 1 watt, we would choose a more capable N-MOS device such as the Motorola 6800 or Signetics 2650 PIP, either using only +5V.
2. Memory - Complementary Metal-Oxide Semiconductor (CMOS) memory chips have been designed specifically for low-power applications. CMOS is therefore especially useful in portable equipment. CMOS RAMs are available from a number of manufacturers (see list below).

Intersil	IM6523	256x1
Motorola	MCM14537	256x1
Inselek	INS4200S	256x1
AMI	S222	512x1

Additionally a number of 1024 bit CMOS RAMs have been announced.

Intel	5101	256x4
Intersil	IM6508	-
RCA	-	1024x1, 256x4

Intel has announced a new low power version of their 4096x1 NMOS Dynamic RAM (Part # P-2107 A8).


Both of the above technologies are consistent with the design objectives. Additional trade-off studies at the system level, 8K bytes, are required to make the best choice.

3. Display - Low power LED for the interim and liquid crystal ultimately. For 2 lines of 40 characters the LED will require 4.4 watts. The liquid crystals power consumption is <100 mwatts.

In the case of the displays, we believe that liquid crystal is the only type that will fulfill the final goal. It has low power, can present great amounts of information (with magnification), and future circuitry will contain not only the display but drivers.

However, availability ranges from 3 months for the most minimum alphanumeric display, to 2 years for a full page display in a 1"x1" package. Factors that will influence this lead-time will be the pressure of the marketplace to cause manufacturers such as Hughes, ITEK, PMS, and others to come out with these products sooner; or, if we are willing to spend the \$50,000 to \$100,000 in helping to accelerate the pace of this development.

4. Keyboard - Undecided.
5. Control Logic - CMOS.
6. Cassette - A survey of Digital Cassette Storage Systems was conducted to assay total capability in terms of power consumption, weight, and size. The MFE Unit is consistent with the design objectives. The unit consumes 3.4 W, weighs 1.5 lbs, and occupies approximately 40 in³.
7. Modem - RS-232 I/O circuitry.
8. Power Source - The results of preliminary studies indicated an energy requirement of approximately 100 W-Hr. A survey of battery manufacturers showed that this requirement can be satisfied with a rechargeable AG-ZN battery weighing approximately 3 pounds and occupying a volume of approximately 42 in³.
9. Programming - TECO-like (see Figure 2).



ELEMENT	POWER
PROCESSOR	- < 100 m watts (CMOS)
MEMORY (8K)	- 1.7 watts (?)
DISPLAY	- < 100 m watts (Liquid Crystal) - 4.4 watts (LED) *
KEYBOARD	- (?)
CONTROL (low)	- 200 m watts
CASSETTE	- 3.4 watts (only when operating)
MODEM	- (?)

* 2 UNITS OF 40 CHARACTERS

FIGURE 1 - ORGANIZATION

12-6-74

EDITING FEATURES

Character-at-a-time editor. All operations take place in relation to cursor.

CURSOR POSITIONING

1. Forward and backward, a character or line.
2. Search for string and position cursor after string (forward and backwards search?).
3. Jump to top and bottom of text.

INSERTION AND DELETION

1. Insert character(s) at cursor position.
2. Delete forward and backward, a character or line.

MISCELLANEOUS AND OPTIONAL

1. Replace command.
2. Zero buffer (clear all).
3. Block moves (probably not practical).
4. Repeat capability (do a command N times).

INPUT/OUTPUT

1. Depends on device. Either page mode or ?

FIGURE 2 - Text Editor Features

IV. TASK II - PROGRESS TO DATE

Two INTEL 8080 Processors, each with 8K memory, were procured in support of our earlier ARPA sponsored research. These units will be used as the processors to accomplish the goals of Task II.

Presently the processors and memory are separate units. They will not be functional until the design and implementation of memory and control interface hardware is completed. This design is proceeding at present.

The sequence toward implementation has the following stages:

1. System design of Processor and Memory interface.
2. Design of communications interface to accommodate at least two I/O ports.
3. Specification of reliable transmission software with details of interconnection through certain Hosts, TIPs, or direct.
4. Assembly of two systems, one for each end of the communication link.
5. Checkout, programming, and test of the end-to-end error recovery system.

Details of system organization will be presented in a subsequent report.