

A 019 928

NSWC/DL TH-3346

ROLL-RATE STABILIZATION OF A
MISSILE CONFIGURATION WITH WRAP-AROUND
FINS IN INCOMPRESSIBLE FLOW

by

PETER DANIELS

SAMUEL R. HARDY

Warfare Analysis Department

DECEMBER 1975

Approved for public release; distribution unlimited.

NAVAL SURFACE WEAPONS CENTER
Dahlgren Laboratory
Dahlgren, Virginia 22448

NSWC

Best Available Copy

**NAVAL SURFACE WEAPONS CENTER
DAHLGREN LABORATORY
Dahlgren, Virginia
22448**

D. M. Agnew, Jr., Capt., USN
OIC and Assistant Commander

L. A. Clayberg
Associate Technical Director

Best Available Copy

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TR-3346	2. GOVT ACCESSION NO. (14) NSWC/DL-TR-3346	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ROLL-RATE STABILIZATION OF A MISSILE CONFIGURATION WITH WRAP-AROUND FINS IN INCOMPRESSIBLE FLOW.	5. TYPE OF REPORT & PERIOD COVERED Final rept.	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Peter/Daniels Samuel R. Hardy	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center Dahlgren Laboratory Dahlgren, Virginia 22448	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS (12) 12 p.	
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Surface Weapons Center Dahlgren Laboratory Dahlgren, Virginia 22448	12. REPORT DATE (11) December 1975	13. NUMBER OF PAGES 13
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) subsonic wind tunnel wrap-around fin		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report contains the results of a subsonic wind tunnel test conducted to study the steady-state roll-rate characteristics of various wrap-around fin (WAF) missile configurations at angles of attack from 0 to 90°. The tests show that fin slots combined with wing tip fences and roll tabs eliminate the excessive roll-rate characteristics exhibited by WAF configurations at all angles of attack. dega.		

DD FORM 1473
1 JAN 73EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-66011

UNCLASSIFIED

391598
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWORD

The results of a study to eliminate the excessive roll rates at high angles of attack exhibited by missile configurations with wrap-around fin stabilizers are presented. The purpose of this study was to experimentally determine a method of roll-rate stabilization for this type of configuration to be used as an air-launched weapon.

This work was performed under the Index Exploratory Development Program sponsored by the Director of Naval Laboratories.

This report was reviewed by H. P. Caster, Head, Exterior Ballistics Division.

Released by:

R. A. Niemann

R. A. NIEMANN
Head, Warfare Analysis Department

ACCESSION	121
NTIS	
DTIC	
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	

CONTENTS

	<u>Page</u>
FOREWORD	i
INTRODUCTION	1
WIND TUNNEL TESTS	1
DISCUSSION OF RESULTS	2
CONCLUSIONS	7
COMMENT	8
REFERENCES	8
DISTRIBUTION	

INTRODUCTION

This work was undertaken as an initial phase of a research program to determine the potential of wrap-around fins (WAFs) as stabilizers for air-launched weapons. As a result of a previous investigation concerned with rocket flight dynamics,¹ it appeared that WAF configurations of proper design may avoid roll resonance and roll-yaw coupling, thus alleviating two problems plaguing current general-purpose bombs. However, a problem that is characteristic of WAF missile configurations is high roll rate at high angles of attack. The elimination of high roll rates is an important factor in controlling Magnus instability of air-launched weapons, particularly bombs.²⁻⁴

The purpose of this study was to determine if a fin modification could be found for WAF configurations that would provide roll-rate stabilization at all angles of attack.

WIND TUNNEL TESTS

Free-rolling tests were conducted in the 28- by 40-in. subsonic wind tunnel located at Edgewood Arsenal.⁵ The test specimen consisted of a free-rolling model with an ogival nose and a cylindrical afterbody, sting-mounted on ball bearings. The model was designed so that various fin configurations could be easily interchanged. A schematic of the basic configuration with fins extended (open) is presented in Figure 1. Steady-state roll rates were measured with a magnetic tachometer for angles of attack from 0 to 90°.




Figure 1. Schematic of Wind Tunnel Model (Basic Configuration)

DISCUSSION OF RESULTS

The basic WAF configuration was tested, and a plot of the reduced frequency ($Pd/2V$) versus the model angle of attack (α) is shown in Figure 2.

where

P = steady-state roll rate, rad/sec

d = reference diameter, 0.133 ft.

V = velocity of free stream, ft/sec

α = total angle of attack, °

This configuration exhibited large negative steady-state roll rates at high angles of attack and a small positive, steady-state roll rate at zero angle of attack. The bar indicates a region of roll lock-in, e.g., where the motion, if stopped, will remain stopped.

A straight fin configuration with the same planform as the basic WAF configuration was also tested (see Figure 2). As expected, the configuration exhibited roll speed-up in both the positive and negative directions.² The unsymmetrical character of the roll rates exhibited by this configuration is probably due to strut interference. Interference is inferred since models with longer sting-to-strut distances exhibit more-symmetrical roll characteristics.

It had previously been shown that fin slots eliminated roll speed-up of straight finned missiles.^{2,3} Consequently, fin slots were tested on the basic WAF configuration in the hope that the roll rates at high angles of attack would be reduced. The fin slot, centrally located, had an area of about 30 percent of the total fin area. The slot reduced roll rates at high angles of attack approximately 50 percent. Data for the slotted wraparound fin are presented in Figure 2.

At this point, it was obvious that an additional modification to the fin was required in order to provide roll-rate stabilization.

Since WAF configurations are not symmetrical in crossflow (see Figure 3), it was expected that a part of the high-angle-of-attack roll rate might be produced by differential drag. Consequently, fin fences might tend to equalize the drag differential between retreating and advancing fins. Figure 4 shows the effects of fin fences on the basic WAF configuration without slots. With fences at the fin tips, the roll rate is reversed except at very high angles of attack where the configuration can roll in either direction.




Figure 2. Steady-State Roll Rate vs Angle of Attack




Figure 3. Wrap-Around Fins in Crossflow

An inboard movement of the fence (Figure 4) gives the WAF configuration the characteristics of a straight-fin configuration; e.g., the missile rolls equally well in both directions at high angles of attack.

Using a combination of slots and fences, the WAF configuration was then roll-rate-stabilized, as shown in Figure 5. The addition of a roll tab provided the required driving torque. The dimensions of the final roll-stabilized configuration using slots, fences, and roll tabs are given in Figure 6. It should be noted that further refinement of the slot geometry and fence location was not attempted.




Figure 4. Steady-State Roll Rate vs Angle of Attack for Wrap-Around Fin Configuration With Outboard Fences




Figure 5. Steady-State Roll Rate vs Angle of Attack for Wrap-Around Fin Configuration




Figure 6. Roll Stabilized Wrap-Around Fin Configuration With Slot, 10° Roll Tab, and Outboard Fence 0.08 In. From Fin Tip

CONCLUSIONS

The following conclusions are made based on the results of this study:

1. In incompressible flow, a missile configuration with wrap-around fins can be roll-rate-stabilized using fences and slots.
2. Roll rates of the basic WAF configuration at high angles of attack are probably due to vortices shed from the fins and the differential drag of the fins in crossflow.

Surprisingly, the fence position can cause the basic WAF configuration to behave like its straight fin counterpart, probably by equalizing the drag in crossflow. The slots eliminate the roll rates caused by vortex shedding on the wrap-around fins. Thus, the combination of fences and slots eliminates the large roll rates exhibited by WAF missile configurations at high angles of attack.

COMMENT

The method of roll-rate stabilization presented in this report for wrap-around-fin configurations is relatively simple and practical. Consequently, additional high-speed tests are strongly recommended.

REFERENCES

1. F. L. Stevens, T. J. On, and T. A. Clare, *Wraparound Versus Cruciform Fins: Effects on Rocket Flight Performance*, AIAA Paper, No. 74-777, August 1974.
2. J. D. Nicolaides, *Missile Flight and Astrodynamics*, TN 100-A, 1959-1961, Bureau of Naval Weapons, Washington, D. C.
3. P. Daniels, *A Study of the Nonlinear Rolling Motion of a Four-Finned Missiles*, *Journal of Spacecraft and Rockets*, Vol. 7, No. 4, April 1970, pp. 510-512.
4. P. Daniels, *Fin Slots Versus Roll Lock-in and Roll Speed-up*, *Journal of Spacecraft and Rockets*, Vol. 4, No. 3, March 1967, pp. 410-412.
5. A. Flatau, *Facilities and Capabilities of Aerodynamic Group Research Laboratories*, EASP 100-79 of June 1970, Edgewood Arsenal, Edgewood, Maryland.

DISTRIBUTION

Commander
Naval Air Systems Command
Washington, D. C. 20361

Attn: AIR-320

(3)

AIR-5323

AIR-350

AIR-5301

(4)

AIR-532

Commander
Naval Sea Systems Command
Washington, D. C. 20360

Attn: SEA-3513

Commander
Naval Surface Weapons Center
White Oak Laboratory
Silver Spring, Maryland 20910
Attn: Dr. Leon Schindel
Frank J. Regan
S. Hastings
Technical Library

Commander
Naval Ship Research and Development Center
Washington, D. C. 20007

Attn: S. Gottlieb

Dr. Harvey Chaplin

George S. Pick

James Nichols

Martin Cook

Technical Library

Commander
Naval Weapons Center
China Lake, California 93555

Attn: Dr. W. Haseltine

R. F. Meeker

R. Demarco

R. E. Smith

Technical Library

Commanding Officer
Edgewood Arsenal
Edgewood Arsenal, Maryland 21010
Attn: A. Flatau
M. Miller
Technical Library

Commanding General
Ballistic Research Laboratory
Aberdeen Proving Ground, Maryland 21005
Attn: Dr. C. H. Murphy
L. MacAllister
Technical Library

Commanding General
Picatinny Arsenal
Dover, New Jersey 07801
Attn: A. Loeb
R. Kline
Technical Library

AFATL, RTD
Eglin Air Force Base, Florida 32542
Attn: Dr. G. B. Findley
Carol Butler
E. Sears
Technical Library

Arnold Engineering Development Center
Tullahoma, Tennessee 37388
Attn: James Uselton
Technical Library

NASA/Ames Research Center (Mail Stop 227-8)
Moffet Field, California 94035
Attn: Leland H. Jorgenson

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314

(12)

Defense Printing Service
Washington Navy Yard
Washington, D. C. 20374

Library of Congress
Washington, D. C. 20540
Attn: Gift and Exchange Division

(4)

Local:

DD

DF

DG

DK

DK-20

DK-21 (15)

DX-21 (2)

DX-222 (6)

DX-40

DX-43 (Elliott)