

AD-A020 818

CONCRETE DOOR. PROOF TEST FOR AIR BLAST

Anton Rinnan

Norwegian Defence Construction Service
Oslo, Norway

May 1975

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE

KEEP UP TO DATE

Between the time you ordered this report—which is only one of the hundreds of thousands in the NTIS information collection available to you—and the time you are reading this message, several new reports relevant to your interests probably have entered the collection.

Subscribe to the **Weekly Government Abstracts** series that will bring you summaries of new reports as soon as they are received by NTIS from the originators of the research. The WGA's are an NTIS weekly newsletter service covering the most recent research findings in 25 areas of industrial, technological, and sociological interest— invaluable information for executives and professionals who must keep up to date.

The executive and professional information service provided by NTIS in the **Weekly Government Abstracts** newsletters will give you thorough and comprehensive coverage of government-conducted or sponsored re-

search activities. And you'll get this important information within two weeks of the time it's released by originating agencies.

WGA newsletters are computer produced and electronically photocomposed to slash the time gap between the release of a report and its availability. You can learn about technical innovations immediately—and use them in the most meaningful and productive ways possible for your organization. Please request NTIS-PR-205/PCW for more information.

The weekly newsletter series will keep you current. But *learn what you have missed in the past* by ordering a computer NTISearch of all the research reports in your area of interest, dating as far back as 1964, if you wish. Please request NTIS-PR-186/PCN for more information.

WRITE: Managing Editor
5285 Port Royal Road
Springfield, VA 22161

Keep Up To Date With SRIM

SRIM (Selected Research in Microfiche) provides you with regular, automatic distribution of the complete texts of NTIS research reports *only* in the subject areas you select. SRIM covers almost all Government research reports by subject area and/or the originating Federal or local government agency. You may subscribe by any category or subcategory of our WGA (**Weekly Government Abstracts**) or **Government Reports Announcements and Index** categories, or to the reports issued by a particular agency such as the Department of Defense, Federal Energy Administration, or Environmental Protection Agency. Other options that will give you greater selectivity are available on request.

The cost of SRIM service is only 45¢ domestic (60¢ foreign) for each complete

microfiche report. Your SRIM service begins as soon as your order is received and processed and you will receive biweekly shipments thereafter. If you wish, your service will be backdated to furnish you microfiche of reports issued earlier.

Because of contractual arrangements with several Special Technology Groups, not all NTIS reports are distributed in the SRIM program. You will receive a notice in your microfiche shipments identifying the exceptionally priced reports not available through SRIM.

A deposit account with NTIS is required before this service can be initiated. If you have specific questions concerning this service, please call (703) 451-1558, or write NTIS, attention SRIM Product Manager.

This information product distributed by

NTIS

U.S. DEPARTMENT OF COMMERCE
National Technical Information Service
5285 Port Royal Road
Springfield, Virginia 22161

ADA020818

FORTIFIKATORISK

NOTAT NR. 105 / 75

Concrete door. Proof test for air blast

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
US Department of Commerce
Springfield, VA. 22151

DDC
RECEIVED
FEB 23 1976
D

Concrete door. Proof test for air blast

FORSVARETS BYGNINGSTJENESTE

DISTRIBUTION STATEMENT A


Approved for public release;

NORWEGIAN DEFENCE CONSTRUCTION SERVICE
Office of Test and Development

Fortifikatorisk notat nr 105/75

Concrete door. Proof test for air blast.

by
Anton Rinnan



May 1975

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

SUMMARY

1.68 1.25 3560 psi
A reinforced door 140 x 220 cm, concrete quality 250 kg/cm², designed by "Fortifikasjon A/S" was tested with gradually increasing air blast until max load according to the latest consideration of the NATO. AC/258 Storage Sub-Group [Head wall of acceptor igloo facing back wall of donor igloo at a scaled distance 0,8 Q^{1/3}]

	NATO AC/258	Test
Pressure	14 bar (<i>proposed</i>)	14 bar
Positive duration [t=1·Q ^{1/3}]	40 ms [Q=64 tonn]	90 ms [Q=729 tonn]
Positive impulse [i=2·Q ^{1/3}]	80 bar.ms [Q=64 tonn]	240 bar.ms [Q=17500 tonn]

After the test which totaled 10 shots the

- max plastic deformation of the door was 2 cm, and the only visible damage was a small crack in the concrete.
- Full protection would have been afforded to the interior of a magazine or shelter.

C O N T E N T S

	Page
SUMMARY .	1
1. Introduction	3
2. Test arrangement	3
3. Measurements	3
3.1. Location of the measuring points	4
4. Results	5
5. Discussion of the results	5
5.1. Pressure measurements	5
5.2. Strain measurements	6
5.3. Deflection measurements	6
5.4. Visual observations	6
6. Conclusions	7
Fig 2 a.	Sketch of tunnel
Fig 3 a.	Measuring chain
Fig 3.1.a.	Location of measuring points
Table 4.a.	Pressure, strain and deflection results
Table 4.b.	Plastic deformation results
Table 4.c.	Natural vibration period (20-30 ms)
Fig 5.2.a.	Strain versus pressure
Fig 5.2.b.	Strain versus impulse
Fig 5.4.	Pictures
Appendix 1.	Pressure, strain and deflection recordings
Appendix 2.	Drawing. Concrete door
Appendix 3.	Drawing. Tunnel

1. Introduction.

The object of the test was to load a door according to drawing in appendix 2 with a side on air blast according to the latest consideration of the NATO AC/258 Storage Sub-Group (Head wall of accantor igloo facing back wall of donor igloo at a scaled distance of $0,8 \cdot Q^{1/3}$, (m, kg^{1/3}))

Pressure	14 bar
Positive duration [t=1·Q ^{1/3}]	40 ms
Positive impulse [i=2·Q ^{1/3}]	80 bar.ms

As may be seen the duration and impulse is determined by the amount of net explosives in the donor igloo. In the test was also another door and a polycarbonat window with higher priority than the concrete door. The charge weights in the first 9 shots were therefore chosen with respect to these two objects.

2. Test arrangement.

The test was carried out in the NDCS's test tunnel at Raufoss in March 1975. The tunnel has a cross section of about 4 m², and the door was placed horizontally. Fig 2.a and appendix 3 show the arrangement in detail.

The charges were detonated at a distance 14 m from measuring point 2 and 17,5 m from measuring point 4 close to the door.

In table 4.a the charge weights are listed.

3. Measurements.

The measuring chain is presented in fig 3.a and the measuring points in fig 3.1.a. During each shot the following quantities were measured:

- Pressure-time history.

Only one and partly two pressure transducers operated satisfactorily during shot 6-10. There is however, good correspondence between these two. The pressure-time history is also known from previous tests.

- Strain of the door.
- Deflection of the door

Both the deflection - and strain gauges were fastened to a thin steel plate on the on the rear side of the door. The plate was necessary for the casting of the test door, but normally it will not be a part of the door-scaffolding will be removed after casting. For the test door, therefore, strain- and deflection are measured for the plate and not for the concrete. For shot 6-9 the plate is supposed to indicate the response of the concrete, but during shot 10 the plate loosened from the concrete and therefore the measurements has no value.

After shot 10 the door was controlled for plastic deformations. A metal ruler, supported at the door frame, was placed across the door in its longitudinal direction. See table 4.b.

3.1. Location of the measuring points.

Fig 3.1.a and 2.a show the location of the measuring points.

- The pressure-transducers (mp 1-8 fig 2.a) was placed in the same horizontal plane as the floor. Only mp 2 and 4 operated satisfactorily during shot 6-10.

- 5
- The strain-gauges mp 17, 18 and 19 were mounted on a steel plate on the rear side of the door. The strain was measured normal to the longitudinal direction of the door.
 - The deflection gauges mp 15 and 16 were mounted in the steel plate on the rear side of the door and fixed to the concrete floor below.
 - The controll points for plastic deformation are shown with results in table 4.b.

4. Results.

Table 4.a gives pressure, strain and dynamic deflection from each shot, and appendix 1 presents the recordings from each shot and measuring point. Table 4.b gives the plastic deformation after shot 10. This can also be seen from the pictures in fig 5.4. Table 4.a indicates that the natural vibration period of the door is 20-30 ms. There is not enough suitable recordings to determine the vibration period more accurately.

5. Discussion of the results.

5.1. Pressure measurements.

Only the pressure transducers in mp 2 and partly in mp 4 are expected to give a fairly correct pressure time history ($\pm 20\%$). There is usually a larger scatter in positive duration and impulse than in pressure, between different measuring points. Therefore, the uncertainty of positive duration and impulse is estimated to be $\pm 30\%$.

- The recordings from no 4 show a pressure peak short after the arrival of the shock front. This is the reflected shock front from the concrete door. The reading of the max pressure is done on the first shock and not on the reflected shock.
- The calculation of the positive impulse is done by a rude fitting of simple geometric figures to the recordings. The accuracy of the calculations is estimated to $\pm 30\%$.

5.2. Strain measurements.

In fig 5.2.a and 5.2.b strain is plotted versus side on pressure and impulse, respectively. Since the plate loosened from the concrete during shot 10, the last point on the curves may be wrong. The max strain was recorded approximated 10 ms after the door started to deflect.

5.3. Deflection measurements.

There is very little information to get from the deflection measurements except that for a load of 0,85 bar and 11 bar.ms the max deflection is 2 mm which is not very much. Unfortunately, the gauges was not in operation during shot 9 and in shot 10 the plate loosened as already mentioned.

5.4. Visual observations.

The only visible damage of the door was a max 2 cm deflection and a crack along its longitudinal direction. See fig 5.4.a. The fact that the steelplate loosened is not important since it will normally be removed after casting.

6. Conclusions.

The door withstood the following load:


Pressure	14 bar
Positive duration	90 ms
Positive impulse	240 bar.ms

with a max deformation of 2 cm.


Full protection would have been afforded to the interior of a magazin or shelter.

The door is considered to be designed for the load considered by the NATO AC/258- Storage Sub-Group for the head wall of an accentor igloo facing the back of an accentor igloo at a scaled distance of $0,8 \cdot Q^{1/3} \text{ (m, kg}^{1/3})$


8.



9.




Sketch of tunnel. Not in scale.



The measuring chain.

Fig 3.1.a.



X Deflection gauge
□ Strain gauge

Table 4.a.


Shot no	6	7	8	9	10
Charge weight (kg)	1,0	1,5	3,0	30	100
2.0					
Pressure (bar)	0,35	0,56	0,85	4	13
Duration (ms)	17	22	39	80	103
Impulse (bar.ms)	3	6	11	80	240
4.					
Pressure (bar)			0,96		14,5
Duration (ms)			43		80
Impulse (bar.ms)			14,5		230
15. Deflection (mm)	< 2	< 2	2	-	> 25
16. Deflection (mm)	-	< 2	2	-	> 25
17. Strain (μ s)	< 50	< 50	40	280	1000
18. Strain (μ s)	< 50	< 50	50	530	720
19. Strain (μ s)	< 50	< 50	40	160	1700

Nu

1) Numbers indicates measuring point.

Plastic deformation after shot 10.

The ruler placed across the door in its length direction and supported on the door frame.




MP	1	2	3	4	5	6	7	8	9	10	11
Deformation (cm)	0,5	0,8	0,7	0,6	1,2	1	1,2	1,7	1,0	1,2	1,9


12	13	14	15
1,2	1,8	2,5	1,2

Natural vibration period.

Shot no	8	9
MP 15	32 ms	
16	32 ms	
17		25 ms
18		
19		21 ms

Natural vibration period \approx 20-30 ms.








Plate 1.
The reinforcement
of the door.




Plate 2.
Detail of the
locking mechanism.



Plate 3. The door before the test.




Plate 4. The door after the test.




Plate 5. Permanent deformation
after the test.





Plate 6.
Crack in the concrete
after the test.




20








2.









Shot 8
mp 15



Shot 8
mp 16




Shot 8
mp 19



Shot 8
mp 18




Shot 8
mp 17






Shot 9
mp 2

bar


6
4
2








Shot 10
mp 15




30.

Shot 10
mp 16




Shot 10, 1200
mp 17 μ strain




31.

Shot 10
mp 18 μ strain



shot 10
P 19



32.

SUMMARY

A reinforced door 140 x 220 cm, concrete quality 250 kg/cm², designed by "Fortifikasjon A/S" was tested with gradually increasing air blast until max load according to the latest consideration of the NATO. AC/258 Storage Sub-Group [Head wall of acceptor igloo facing back wall of donor igloo at a scaled distance 0,8 Q^{1/2}]

	NATO AC/258	Test
Pressure	14 bar (proposed)	14 bar
Positive duration $\bar{t}=1 \cdot Q^{1/2}$	40 ms [Q=64 tonn]	90 ms [Q=729 tonn]
Positive impulse $i=2 \cdot Q^{1/2}$	80 bar.ms [Q=64 tonn]	240 bar.ms [Q=17500 tonn]

After the test which totaled 10 shots the

- max plastic deformation of the door was 2 cm, and the only visible damage was a small crack in the concrete.
- Full protection would have been afforded to the interior of a magazine or shelter.

XEROX COPY