



Calhoun: The NPS Institutional Archive
DSpace Repository

Theses and Dissertations

Thesis and Dissertation Collection

1976-03

Relative robustness of several CEP estimators

Chen, Tzu-ming

<http://hdl.handle.net/10945/17926>

Downloaded from NPS Archive: Calhoun



Calhoun is a project of the Dudley Knox Library at NPS, furthering the precepts and goals of open government and government transparency. All information contained herein has been approved for release by the NPS Public Affairs Officer.

Dudley Knox Library / Naval Postgraduate School
411 Dyer Road / 1 University Circle
Monterey, California USA 93943

<http://www.nps.edu/library>

RELATIVE ROBUSTNESS
OF SEVERAL CEP ESTIMATORS

Tzu Ming Chen

NAVAL POSTGRADUATE SCHOOL
Monterey, California



THESIS

RELATIVE ROBUSTNESS
OF SEVERAL CEP ESTIMATORS

by

Tzu Ming Chen

March 1976

Thesis Advisor:

D. R. Barr

Approved for public release; distribution unlimited.

T173108

| REPORT DOCUMENTATION PAGE | | READ INSTRUCTIONS BEFORE COMPLETING FORM | |
|--|-----------------------|--|--|
| 1. REPORT NUMBER | 2. GOVT ACCESSION NO. | 3. RECIPIENT'S CATALOG NUMBER | |
| 4. TITLE (and Subtitle) Relative Robustness of Several CEP Estimators | | 5. TYPE OF REPORT & PERIOD COVERED Master's Thesis; March 1976 | |
| 7. AUTHOR(s) Tzu Ming Chen | | 6. PERFORMING ORG. REPORT NUMBER | |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940 | | 8. CONTRACT OR GRANT NUMBER(s) | |
| 11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940 | | 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS | |
| 14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) | | 12. REPORT DATE March 1976 | |
| | | 13. NUMBER OF PAGES 43 | |
| | | 15. SECURITY CLASS. (of this report) Unclassified | |
| | | 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE | |
| 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. | | | |
| 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) | | | |
| 18. SUPPLEMENTARY NOTES | | | |
| 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) CEP Estimators Circular Error Probable Maximum Likelihood Estimation Rayleigh Distribution Power distribution | | | |
| 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This thesis presents a discussion of the problems involved in estimation of Circular Error Probable (CEP). Several estimators are compared through simulation, under two models; the power model and the Rayleigh model. Several measures of effectiveness are calculated for each of the competing estimators. It is found that maximum likelihood estimation based on the power distribution performs well for "heavy tailed" | | | |

(20. ABSTRACT Continued)

distributions; the Rayleigh unbiased estimator performs well for most other situations.

• • •

Relative Robustness
of Several CEP Estimators

by

Tzu Ming Chen
Lieutenant, Chinese Navy
B.S., Chung Cheng Institute of Technology, 1970

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN OPERATIONS RESEARCH

from the
NAVAL POSTGRADUATE SCHOOL
March 1976

ABSTRACT

This thesis presents a discussion of the problems involved in estimation of Circular Error Probable (CEP). Several estimators are compared through simulation, under two models; the power model and the Rayleigh model. Several measures of effectiveness are calculated for each of the competing estimators. It is found that maximum likelihood estimation based on the power distribution performs well for "heavy tailed" distributions; the Rayleigh unbiased estimator performs well for most other situations.

TABLE OF CONTENTS

| | | |
|------|---|----|
| I. | INTRODUCTION ----- | 7 |
| II. | MAXIMUM LIKELIHOOD ESTIMATION BASED ON THE POWER DISTRIBUTION MODEL ----- | 10 |
| | A. MATHEMATICAL FORMULATION ----- | 10 |
| | B. NUMERICAL SOLUTIONS: NEWTON'S METHOD ----- | 12 |
| III. | MAXIMUM LIKELIHOOD ESTIMATION BASED ON THE RAYLEIGH DISTRIBUTION MODEL ----- | 15 |
| IV. | NONPARAMETRIC ESTIMATION: THE SAMPLE MEDIAN ---- | 19 |
| V. | SIMULATION METHODOLOGY ----- | 23 |
| VI. | SIMULATION RESULTS ----- | 27 |
| VII. | CONCLUSIONS ----- | 37 |
| | APPENDIX ----- | 38 |
| | BIBLIOGRAPHY ----- | 42 |
| | INITIAL DISTRIBUTION LIST ----- | 43 |

ACKNOWLEDGMENT

I would like to express my appreciation and indebtedness to Professor Barr for his continued patience, encouragement. Without his guidance and his reviews of the manuscript, this dissertation would certainly not have been possible.

I would also like to express special thanks to Felicia for her painstaking assistance in typing the rough drafts.

I. INTRODUCTION

Evaluation of a weapons system is frequently an expensive and time consuming task. Only relatively few tests may be allowed because of the high cost of testing. It is possible that a good weapon system could be rejected because of inefficient utilization of the small amount of data available. Hence, efficient use of the limited data is required to reduce this risk.

Several authors have considered the measurement of weapon delivery accuracy using Circular Error Probable (CEP). This measure of accuracy is defined to be the radius of a circle centered at the target which on the average contains fifty percent of impact points, that is, the median radial miss distance. A functional relationship between CEP and the distribution parameters is given by the following integral:

$$F(\text{CEP}) = \int_0^{\text{CEP}} f(r) dr = 0.5 ,$$

where $f(r)$ is the probability density of radial miss distance.

Various parametric models for the distribution of impact points about the target have been used in connection with such estimations. A discussion of these models is given by Jordan [1]. But, deficiencies in the models have been

noted. Specifically, they tend to provide poor fit to the "upper tail" of the radial distributions. That is, they provide less than satisfactory explanation of impacts observed far from the target. A commonly used model is the "Rayleigh model", in which impacts in the target plane are assumed to be distributed as the unbiased circular normal distribution. One might anticipate that Rayleigh-based CEP estimators might not perform adequately with a large proportion of actual test data. Several potential competitors to Rayleigh CEP estimators were therefore developed for comparison.

Barr and Jordan [2] developed and proposed the power distribution model which is based on an infinite mixture of Rayleigh radial miss distance distributions. This distribution has properties compatible with the interpretation of σ in the underlying Rayleigh distribution model; they suggested the use of maximum likelihood estimates of the parameters of the power distribution which in turn provide a maximum likelihood estimate (MLE) of CEP.

The jackknife is a technique which was proposed by Quenouille [10] for reducing bias in estimation problems. We tried the jackknife procedure to estimate CEP under the Rayleigh model.

The sample median was also used to estimate CEP. Since CEP is defined as the median radial miss distance, a natural estimator for CEP is the sample median.

To measure the performance of the estimators, a variety of data sets from known distributions, such as uniform, Rayleigh, power and Weibull were generated by simulation. Samples from the known distributions were generated to test the capability of the estimators to handle widely disparate situations.

II. MAXIMUM LIKELIHOOD ESTIMATION BASED ON THE POWER DISTRIBUTION

Barr and Jordan [1], [2] have given a discussion of CEP accuracy measurement under a power distribution model. They showed that estimating the parameters of the power distribution by the method of moments may not be adequate; moreover it is possible only when the ratio of the squared sample mean and variance \bar{r}^2/s_r^2 does not exceed $\pi/4 - \pi$. Consequently, they suggested use of the maximum likelihood (M.L.) method.

Analytically closed expressions for the M.L. estimators cannot be obtained, the solution of normal equations yielding the parameter estimates requires numerical techniques. In this section we examine a numerical method to obtain the M.L. estimates of the parameters of the power distribution, which in turn provide a M.L. estimate of CEP. These estimation procedures require use of a computer.

A. MATHEMATICAL FORMULATION

The probability density function of the radial miss distance R having a power distribution with parameters κ and ζ is

$$f_R(r; \kappa, \zeta) = \frac{2\kappa r}{\zeta} \left(\frac{\zeta}{\zeta + r^2} \right)^{\kappa+1} ; \quad r \geq 0, \kappa, \zeta > 0$$

A C.D.F. for radial miss distance is

$$F_R(r; \kappa, \zeta) = 1 - \left(\frac{\zeta}{\zeta + r^2} \right)^\kappa ; \quad r \geq 0, \quad \kappa, \zeta > 0 \quad (1)$$

The CEP is given by

$$\text{CEP} = F_R^{-1}\left(\frac{1}{2}\right) = \left[(2^{\frac{1}{\kappa}} - 1) \zeta \right]^{\frac{1}{2}}$$

Because radial miss distance is always non-negative, one can equivalently consider squared radial miss distance. In the case of the power model, this leads to some notational simplification. Let Y denote the squared miss distance R^2 . Then from (1),

$$F_Y(y) = 1 - \left(1 + \frac{y}{\zeta} \right)^{-\kappa} ; \quad y \geq 0, \quad \kappa, \zeta > 0 \quad (2)$$

$$f_Y(y) = \frac{\kappa}{\zeta} \left(1 + \frac{y}{\zeta} \right)^{-\kappa-1} ; \quad y \geq 0, \quad \kappa, \zeta > 0$$

Here ζ and κ are parameters to be estimated from observed impact data. The relationship between CEP and these parameters is

$$\text{CEP}^2 = F_Y^{-1}\left(\frac{1}{2}\right) = \left[(2^{\frac{1}{\kappa}} - 1) \zeta \right]$$

The method of maximum likelihood is based upon the likelihood function $\phi(y)$ which is defined as the joint density function of a sample of size n ; i.e.,

$$\phi(y) = \prod_{i=1}^n f_Y(y_i) = \frac{\kappa^n}{\zeta^n} \prod_{i=1}^n \left(1 + \frac{y_i}{\zeta}\right)^{-\kappa-1}$$

Since it is easier to deal with sums rather than products when maximizing, $\phi(y)$ is transformed into

$$\begin{aligned} L(y) &= \log \phi(y) \\ &= n \log \kappa + n \log \zeta - (\kappa+1) \sum_{i=1}^n \log(\zeta + y_i) \end{aligned}$$

There is no loss of generality here because the maximum of a positive function occurs at the same point as the maximum of the logarithm of the function. The normal equations are then

$$m(\kappa, \zeta) = \frac{\partial L(y)}{\partial \kappa} = \frac{n}{\kappa} + n \log \zeta - \sum_{i=1}^n \log(\zeta + y_i) = 0$$

and

$$g(\kappa, \zeta) = \frac{\partial L(y)}{\partial \zeta} = \frac{n\kappa}{\zeta} - (\kappa+1) \sum_{i=1}^n \frac{1}{\zeta + y_i} = 0$$

The solution of $m(\hat{\kappa}, \hat{\zeta}) = 0$ and $g(\hat{\kappa}, \hat{\zeta}) = 0$ gives the parameter M.L. estimators $\hat{\kappa}$, $\hat{\zeta}$. As mentioned before, in the present case, this requires numerical techniques.

B. NUMERICAL SOLUTIONS: NEWTON'S METHOD

This method is a Newton's iteration technique and the concept and procedure are discussed in [3]. Newton's method provides a statistical criterion for stopping the iterations.

The pure form of Newton's method is given by the following iteration scheme:

$$\hat{X}_{j+1} = \hat{X}_j - [F(\hat{X}_j)]^{-1} \nabla f(\hat{X}_j)^T$$

where

$$X_j = [\hat{\kappa}_j, \hat{\zeta}_j], \quad f(X_j) = \left[\frac{\partial L(y)}{\partial \hat{\kappa}}, \frac{\partial L(y)}{\partial \hat{\zeta}} \right].$$

First we compute

$$\frac{\partial L(y)}{\partial \hat{\kappa}} = \frac{n}{\hat{\kappa}} + n \log \hat{\zeta} - \sum_{i=1}^n \log (\hat{\zeta} + y_i)$$

$$\frac{\partial L(y)}{\partial \hat{\zeta}} = \frac{n\hat{\kappa}}{\hat{\zeta}} - (\hat{\kappa}+1) \sum_{i=1}^n \frac{1}{\hat{\zeta} + y_i}$$

$$\frac{\partial^2 L(y)}{\partial \hat{\kappa}^2} = \frac{-n}{\hat{\kappa}^2}$$

$$\frac{\partial^2 L(y)}{\partial \hat{\kappa} \partial \hat{\zeta}} = \frac{n}{\hat{\zeta}} - \sum_{i=1}^n \frac{1}{\hat{\zeta} + y_i}$$

$$\frac{\partial^2 L(y)}{\partial \hat{\zeta}^2} = \frac{-n\hat{\kappa}}{\hat{\zeta}^2} + (\hat{\kappa}+1) \sum_{i=1}^n \frac{1}{(\hat{\zeta} + y_i)^2}.$$

Let

$$D = \frac{\partial^2 L(y)}{\partial \hat{\kappa}^2} \cdot \frac{\partial^2 L(y)}{\partial \hat{\zeta}^2} - \left(\frac{\partial^2 L(y)}{\partial \hat{\kappa} \partial \hat{\zeta}} \right)^2$$

If D were identically equal to zero, this method would not be applicable. Now take

$$F^{-1}(\hat{X}) = \frac{\begin{array}{cc} \frac{\partial^2 L(y)}{\partial \hat{\zeta}^2} & - \frac{\partial^2 L(y)}{\partial \hat{\kappa} \partial \hat{\zeta}} \\ - \frac{\partial^2 L(y)}{\partial \hat{\kappa} \partial \hat{\zeta}} & \frac{\partial^2 L(y)}{\partial \hat{\kappa}^2} \end{array}}{D} .$$

In order to develop the termination criterion, consider the statistic for (for reference see [4])

$$B = \nabla f(\hat{X}_j) F^{-1}(\hat{X}_j) \nabla f(\hat{X}_j)^{-1}$$

B is asymptotically a Chi-square r. v. with 2 degrees of freedom, therefore it might be reasonable to continue the iteration until the statistic B becomes less than the 100α percentile point of the chi-square distribution with two degrees of freedom, $\chi^2(\alpha)$.

III. MAXIMUM LIKELIHOOD ESTIMATION BASED ON THE RAYELIGH DISTRIBUTION MODEL

Suppose impacts, measured in a suitable plane, have range (X) and deflection (Y) components of impact that are jointly uncorrected bivariate normal distributed with mean at the target and common unknown variance σ^2 in both directions. That is, for the present development, it will be assumed that the joint density of miss distances about the target is given by

$$f(x,y) = (2\pi\sigma^2)^{-1} e^{-(x^2+y^2)/2\sigma^2}, \quad -\infty < x,y < \infty.$$

It is easy to derive the density of radial miss distance. Let $R = (X+Y)^{1/2}$ and transform to polar coordinates to obtain

$$\begin{aligned} F_R(r) = P[R \leq r] &= \frac{1}{2\pi\sigma^2} \int_0^{2\pi} \int_0^r R e^{-\frac{R^2}{2\sigma^2}} dR d\theta \\ &= 1 - e^{-\frac{r^2}{2\sigma^2}}; \quad r \geq 0, \quad \sigma^2 > 0. \end{aligned}$$

This distribution of the radial miss distance is referred to as either the radial normal distribution or the Rayleigh distribution.

Then the density function of the radial miss distance, $f_R(r)$ is

$$f_R(r) = \frac{r}{\sigma^2} e^{-\frac{r^2}{2\sigma^2}} ; r \geq 0, \sigma^2 > 0 .$$

To find the relationship between CEP and σ , we calculate

$$\text{CEP} = F_R^{-1}\left(\frac{1}{2}\right) = \sqrt{2 \ln 2} \sigma \approx 1.1774 \sigma ,$$

which is a well known relation. Hence, if we want to estimate CEP with this model, first we might estimate the population standard deviation. The maximum likelihood estimator for σ is easily found to be

$$\hat{\sigma} = \left(\frac{1}{2n} \sum_{i=1}^n r_i^2 \right)^{\frac{1}{2}} ,$$

where r_1, \dots, r_n is the sample of observed radial miss distances. This estimator has a slight bias, however. An adjusted unbiased estimator for CEP is

$$\hat{\text{CEP}} = 1.1774 \left(\sqrt{n} \frac{\Gamma(n)}{\Gamma\left(\frac{1}{2}(2n+1)\right)} \right) \hat{\sigma}, \quad (3)$$

where the quantity in parenthesis is an unbiasing factor for $\hat{\sigma}$. It has been shown by Chapman and Robbins [6] that $\text{CEP} = 1.1848 \hat{\sigma}$ for sample size 20 is a best estimator of CEP under the normality and other assumptions stated above. However other estimators, while not as efficient as the best estimator, may have more robustness under variations in the assumed distribution of radial miss distance.

The term "jackknife" has been used by Miller [9] and Quenouille [10] to describe a method of modifying a biased estimator to bring it closer to an unbiased condition. From (3) we see the M.L. CEP estimator has a bias term of order $\frac{1}{\sqrt{n}}$. We are thus led to try to examine the jackknife method to reduce this bias in the estimator. Brillinger[7] has provided a discussion of the asymptotic properties of estimators obtained with the jackknife method when it is applied to M.L.E's.

The jackknife procedure is based on dividing the data into groups, obtaining estimates from combinations of the groups, and then averaging these estimates. We apply this to our problem, as follows. The maximum likelihood estimator for $\hat{\sigma}^2$ is

$$\hat{\sigma}^2 = \frac{1}{2n} \sum_{j=1}^n r_j^2$$

Divide these data into m groups, where r_1, \dots, r_n is the sample of n observed radial miss distances and the size of each subgroup is k. First estimate the parameter $\hat{\sigma}^2$ based on all data

$$\hat{\sigma}_o^2 = \frac{1}{2n} \sum_{j=1}^n r_j^2 ;$$

next estimate $\hat{\sigma}^2$ based on all data except those in the i^{th} group

$$\hat{\sigma}_{-i}^2 = \frac{1}{2n} \sum_{j \neq i}^n r_j^2 \quad ; \quad i = 1, 2, \dots, m.$$

Then compute the pseudo values

$$\hat{\sigma}_i^2 = m\hat{\sigma}_0^2 - (m-1)\hat{\sigma}_{-i}^2 \quad ; \quad i = 1, 2, \dots, m.$$

Finally, compute the average of the pseudo values,

$$\bar{\hat{\sigma}}^2 = \frac{\sum_{i=1}^m \hat{\sigma}_i^2}{m}$$

and estimate the CEP by

$$\hat{\text{CEP}} = \sqrt{2 \ln 2 \bar{\hat{\sigma}}^2}$$

IV. THE SAMPLE MEDIAN

Since CEP is defined as the median radial miss distance, a natural estimator for CEP is the sample median (m). By definition; the median is the 50th percentile of the distribution, i.e.,

$$P(R \leq m) \geq 0.50 \quad \text{and} \quad P(R \geq m) \geq .50$$

Since $F(\text{CEP}) = 0.50$ and R is assumed to have a continuous distribution,

$$\hat{\text{CEP}} = m = F^{-1}\left(\frac{1}{2}\right)$$

Suppose that the n radial miss distance observations of the sample are arranged in order of magnitude, $r_{(1)}$, $r_{(2)}$, ..., $r_{(n)}$. We shall consider only the estimates of the population median defined as follows:

- (a) If the sample size is odd, and $n = 2p+1$, the median (m) is taken as the $(p+1)$ th value.
- (b) If the sample size is even, and $n = 2p$, the median (m) is taken as the midpoint between the p th and $(p+1)$ th values or

$$\frac{1}{2}(r_{(p)} + r_{(p+1)}) .$$

The distribution of the median will tend to be symmetrical, and should be very nearly normal in almost all populations. The distribution of the median in the case of small samples from a normal population, whether the sample size is odd or even, will tend to be normal [Hoji [11]]. The normal form is approached very rapidly. The value of the standard deviations of the median for n even and n odd approach the same limit,

$$\sigma_m = \sqrt{\frac{\pi}{2}} \cdot \tilde{\sigma} / n = 1.25331 \tilde{\sigma} / \sqrt{n}$$

where $\tilde{\sigma}$ is the standard deviation in the population sampled.

We use the order statistics to examine the sample median under the Rayleigh distribution model (see Inselmann [12]), and find its bias and variance so as to enable one to make a comparison with other estimates. If n is even, the distribution of sample median is given by the following:

$$g(r_{(0.5n)}) = \{n! / (n - [0.5n])! ([0.5n] - 1)!\} f(r) F(r_{[0.5n]})^{[0.5n] - 1} \\ \cdot [1 - F(r_{[0.5n]})]^{n - [0.5n]} .$$

For convenience we let $a = 0.5n$, and

$$C = n! / (n - [0.5n])! ([0.5n] - 1)! = (2a)! / a! (a - 1)!$$

so the sample median is r_a . Then we may write the distribution of sample median under the Rayleigh distribution model,

$$\begin{aligned}
 g(r_a) &= c \left[\frac{r}{\sigma} \exp\left(-\frac{r^2}{2\sigma^2}\right) \right] \left[1 - \exp\left(-\frac{r^2}{2\sigma^2}\right) \right]^{a-1} \left[\exp\left(-\frac{r^2}{2\sigma^2}\right) \right]^a \\
 &= c \frac{r}{\sigma^2} \left[\exp\left(-\frac{r^2(a+1)}{2\sigma^2}\right) \right] \left[1 - \exp\left(-\frac{r^2}{2\sigma^2}\right) \right]^{a-1}
 \end{aligned}$$

We will now consider computation of the mean of r_a ,

$$\begin{aligned}
 E(r_a) &= c \int_0^{\infty} \frac{r^2}{\sigma^2} \left[\exp\left(-\frac{r^2(a+1)}{2\sigma^2}\right) \right] \left[1 - \exp\left(-\frac{r^2}{2\sigma^2}\right) \right]^{a-1} dr \\
 &= c \int_0^{\infty} \frac{r^2}{\sigma^2} \left[\exp\left(-\frac{r^2(a+1)}{2\sigma^2}\right) \right] \sum_{K=0}^{a-1} (-1)^K \binom{a-1}{K} \left[\exp\left(-\frac{r^2}{2\sigma^2}\right) \right]^K dr \\
 &= c \sum_{K=0}^{a-1} (-1)^K \binom{a-1}{K} \int_0^{\infty} \frac{r^2}{\sigma^2} \exp\left(-\frac{r^2(a+1+K)}{2\sigma^2}\right) dr
 \end{aligned}$$

and make the following transformation

$$y = r^2(a+1+K)/2\sigma^2 ,$$

$$r = \sigma \sqrt{2y/(a+1+K)} ,$$

$$dy = [r(a+1+K)/\sigma^2] dr .$$

To obtain,

$$\begin{aligned}
 E(r_a) &= c\sigma\sqrt{2} \sum_{K=0}^{a-1} (-1)^K \binom{a-1}{K} / (a+1+K)^{\frac{3}{2}} \int_0^{\infty} \sqrt{y} e^{-y} dy \\
 &= c\sigma\Gamma\left(\frac{3}{2}\right) \cdot \sqrt{2} \cdot \sum_{K=0}^{a-1} \frac{(-1)^K \binom{a-1}{K}}{(a+1+K)^{3/2}} .
 \end{aligned}$$

We can adjust the bias term and using the same transformation as above we may now find the second moment

$$\begin{aligned}
 E(r_a^2) &= c \int_0^{\infty} \frac{r^3}{\sigma^2} \exp\left(-\frac{r^2(a+1)}{2\sigma^2}\right) \sum_{K=0}^{a-1} (-1)^K \binom{a-1}{K} \left[\exp\left(-\frac{r^2}{2\sigma^2}\right)\right]^K dr \\
 &= 2c\sigma^2 \sum_{K=0}^{a-1} \frac{(-1)^K \binom{a-1}{K}}{(a+1+K)^2} .
 \end{aligned}$$

The variances of this sample median can now be computed using the well-known formula

$$\text{Var}(r_a) = E(r_a^2) - [E(r_a)]^2 .$$

V. SIMULATION METHODOLOGY

The previous sections have been concerned with a development of different estimators for the median of the distribution of radial miss distances obtained under a set of fixed impact conditions. An analytical comparison is difficult to perform for these estimators, so computer simulation was used. This section summarizes the different models and estimators discussed in the previous sections, and includes an analysis of the results obtained from simulations. Although the sample problems do not represent actual weapon test results, an attempt has been made to generate data from a wide variety of "realistic" distributions. Therefore this simulation analysis should show relationships between our estimators of CEP, and indicate their relative robustness, and hence potential for use in a variety of applications. The alternative estimators are as follows:

- $\hat{\text{CEP}}$ 1: maximum likelihood unbiased Rayleigh estimator
- $\hat{\text{CEP}}$ 2: maximum likelihood Jackknife Rayleigh estimator,
with subgroup sample size $k = 1$
- $\hat{\text{CEP}}$ 3: maximum likelihood power estimator under Newton's
method
- $\hat{\text{CEP}}$ 4: sample median estimator

For the purpose of our simulation comparison of these four CEP estimators, we generated samples of radial miss distances (or, in some cases, squared radial miss distance)

from several parent distributions: Rayleigh, uniform, power and Weibull distributions. Throughout, we assumed a sample size of 20 impact observations. The method of generation was by C.D.F. inversion of generated uniform (0,1) values. For each parent distribution (hereafter called a "case") we replicated estimation of CEP's 500 times. Summaries of the sample distributions of 500 values of 5 CEP's were developed.

Eight cases were considered; in each, parameter values were used which gave a true CEP of 100. The cases are as follows (U is a uniform (0,1) random variable throughout):

Case I. (Rayleigh distribution)

$$F_R^2(y) = 1 - e^{-y/2\sigma^2} \quad \text{with } \sigma^2 = 10^4/2\ln 2$$

$$CEP = \sqrt{2 \ln 2} \sigma$$

$$\text{Generated value: } Y = -2\sigma^2 \ln U = -14426.95 \ln U$$

Case II. (Uniform distribution)

$$F_R(y) = \frac{1}{200} y \quad , \quad \text{with } y \in (0,200).$$

$$CEP = 100$$

$$\text{Generated value } Y = 200 U .$$

Case III. (Power distribution)

$$F_R^2(y) = 1 - \left(1 + \frac{y}{\zeta}\right)^{-\kappa}; \quad y \geq 0, \quad \zeta, \kappa > 0$$

with $\kappa = 1$ and $\zeta = 10^4$

$$CEP = \left[\zeta \left(2^{\frac{1}{\kappa}} - 1\right)\right]^{\frac{1}{2}}$$

$$\text{Generated value } Y = \left(U^{-\frac{1}{\kappa}} - 1\right)\zeta = 10^4 \left(\frac{1}{U} - 1\right)$$

Case IV. (Translated Rayleigh distribution)

$$F_R^2(y) = 1 - e^{-(y-100)/2\sigma^2}$$

where $2\sigma^2 = 14282.6809$

$$CEP = \left[100 + 2\sigma^2 \ln 2\right]^{\frac{1}{2}}$$

$$\text{Generated value } Y = -2\sigma^2 \ln U + 100$$

Cases V-VIII. (Weibull distributions)

$$F_R^2(y) = 1 - e^{-\frac{y}{v}^w}$$

$$CEP = \left(v \ln 2\right)^{\frac{1}{2w}}$$

Generated value Y in the table below

Four sets of parameters (w,v) were selected to give CEP = 100 and to provide distributions with varying upper tail thickness. One case (with w = 1) gives an exponential distribution with mean v, and this corresponds to the Rayleigh case. Case I above may be considered also as a Weibull case. The parameter pairs used, in order of increasing upper tail size, are given in the following table.

| Case | w | v | $Y = (-v \ln U)^{\frac{1}{w}}$ |
|------|-----|-------------------|--|
| V | 2 | $10^8 / \ln 2$ | $Y = (-144260504.1 \ln U)^{\frac{1}{2}}$ |
| VI | 1.5 | $10^6 / \ln 2$ | $Y = (-1442695.04 \ln U)^{\frac{2}{3}}$ |
| I | 1.0 | $10^4 / \ln 2$ | $Y = -4426.95 \ln U$ |
| VII | .5 | $10^2 / \ln 2$ | $Y = (-144.27 \ln U)^2$ |
| VIII | .1 | $10^{.4} / \ln 2$ | $Y = (-3.623886 \ln U)^{10}$ |

VI. SIMULATION RESULTS

As mentioned above, we tested four CEP estimators from eight different cases. Major comparison measures include bias, variance and mean square error. Others are included in the tables that follow.

CASE I. RAYLEIGH DISTRIBUTION

$$Y = - 14426.95 \ln U$$

| MOE | $\hat{C}EP\ 1^*$ | $\hat{C}EP\ 2$ | $\hat{C}EP\ 3$ | $\hat{C}EP\ 4$ |
|--------------|------------------|----------------|----------------|----------------|
| MEAN | 99.93 | 99.94 | 95.96 | 107 |
| STD DEV | 11.66 | 11.68 | 12.22 | 38.8 |
| MSE | 136.03 | 136.37 | 165.77 | 1549 |
| GED MEAN | 99.25 | 99.25 | 95.17 | 100 |
| VARIANCE | 136.03 | 137.37 | 149.45 | 1500 |
| COEFF VAR | 0.12 | 0.12 | 0.13 | 0.36 |
| SKEWNESS | 0.15 | 0.14 | 0.049 | 0.35 |
| KURTOSIS | 0.10 | 0.085 | 0.307 | 0.34 |
| RANGE | 71.38 | 70.87 | 83.60 | 252 |
| MINIMUM | 67.25 | 67.29 | 53.74 | 17.7 |
| .10 QUANTILE | 84.82 | 84.80 | 80.99 | 58.4 |
| .25 | 92.12 | 92.09 | 87.67 | 82.5 |
| .50 | 99.63 | 99.63 | 95.96 | 105 |
| .75 | 107.49 | 107.34 | 104.00 | 132 |
| .90 | 114.83 | 114.83 | 111.32 | 156 |
| MAXIMUM | 138.63 | 138.16 | 137.34 | 269 |

- * $\hat{C}EP\ 1$: maximum likelihood unbiased Rayleigh estimator.
- $\hat{C}EP\ 2$: maximum likelihood Jackknife Rayleigh estimator, with subgroup sample size $k = 1$.
- $\hat{C}EP\ 3$: maximum likelihood power estimator under Newton's Second method.
- $\hat{C}EP\ 4$: sample median estimator.

CASE II. UNIFORM DISTRIBUTION

$$Y = (200 U)^2$$

| | $\hat{C\acute{E}P}$ 1 | $\hat{C\acute{E}P}$ 2 | $\hat{C\acute{E}P}$ 3 | $\hat{C\acute{E}P}$ 4 |
|--------------|-----------------------|-----------------------|-----------------------|-----------------------|
| MOE | | | | |
| MEAN | 98.61 | 96.52 | 91.24 | 102 |
| STD DEV | 9.87 | 9.73 | 17.08 | 41.7 |
| MSE | 109.32 | 107.03 | 368.63 | 1744.0 |
| GED MEAN | 96.09 | 96.01 | * | 91.5 |
| VARIANCE | 97.83 | 94.92 | 291.89 | 1740 |
| COEFF VAR | 0.10 | 0.10 | 0.19 | 0.40 |
| SKEWNESS | - 0.21 | - 0.20 | - 1.83 | 0.005 |
| KURTOSIS | 0.61 | 0.60 | 5.54 | - 0.56 |
| RANGE | 67.28 | 66.35 | 125.60 | 191 |
| MINIMUM | 59.52 | 59.97 | 0.0 | 3.75 |
| .10 QUANTILE | 84.19 | 84.25 | 72.1 | 45.7 |
| .25 | 90.10 | 90.13 | 85.30 | 742 |
| .50 | 96.84 | 96.74 | 94.26 | 102 |
| .75 | 102.96 | 102.75 | 101.52 | 132 |
| .90 | 108.66 | 108.40 | 107.62 | 158 |
| MAXIMUM | 126.80 | 126.32 | 125.60 | 194 |

* some $\hat{C\acute{E}P} = 0.0$

CASE III. POWER DISTRIBUTION

$$Y = 10^4 \cdot \left(\frac{1}{U} - 1 \right)$$

| MOE | $\hat{C}EP\ 1$ | $\hat{C}EP\ 2$ | $\hat{C}EP\ 3$ | $\hat{C}EP\ 4$ |
|--------------|----------------|----------------|----------------|----------------|
| MEAN | 209.61 | 229.33 | 100.71 | 113 |
| STD DEV | 190.15 | 257.90 | 21.07 | 46.0 |
| MSE | 2460 | 83000 | 444.36 | 2279 |
| GED MEAN | 177.76 | 185.62 | 98.60 | 103 |
| VARIANCE | 3615.71 | 66515.7 | 443.86 | 2110 |
| COEF VAR | 0.90 | 1.12 | 0.21 | 0.40 |
| SKEWNESS | 6.39 | 7.32 | 0.84 | 0.76 |
| KURTOSIS | 57.54 | 72.76 | 2.05 | 1.48 |
| RANGE | 2264.4 | 3220.29 | 158.52 | 337 |
| MINIMUM | 74.59 | 75.08 | 48.32 | 17.2 |
| .10 QUANTILE | 108.29 | 108.79 | 76.88 | 57.1 |
| .25 | 126.07 | 127.96 | 86.19 | 82.5 |
| .50 | 161.63 | 166.20 | 99.25 | 107 |
| .75 | 220.09 | 228.03 | 112.71 | 140 |
| .90 | 331.77 | 364.51 | 124.77 | 172 |
| MAXIMUM | 2339.01 | 3295.38 | 206.84 | 354 |

CASE IV. TRANSLATED RAYLEIGH DISTRIBUTION

$$Y = - 14282.6809 \ln U + 100$$

| MOE | $\hat{C\acute{E}P}$ 1 | $\hat{C\acute{E}P}$ 2 | $\hat{C\acute{E}P}$ 3 | $\hat{C\acute{E}P}$ 4 |
|--------------|-----------------------|-----------------------|-----------------------|-----------------------|
| MEAN | 99.79 | 99.79 | 95.85 | 108 |
| STD DEV | 11.56 | 11.58 | 12.64 | 38.3 |
| MSE | 133.74 | 134.09 | 176.96 | 1524 |
| GED MEAN | 99.12 | 99.11 | 94.78 | 100 |
| VARIANCE | 133.70 | 134.05 | 159.74 | 1460 |
| COEF VAR | 0.12 | 0.12 | 0.13 | 0.35 |
| SKEWNESS | 0.15 | 0.15 | - 0.56 | 0.36 |
| KURTOSIS | 0.10 | 0.08 | 4.59 | 0.34 |
| RANGE | 70.75 | 70.25 | 135.40 | 248 |
| MINIMUM | 67.44 | 67.46 | 7.73 | 20.4 |
| .10 QUANTILE | 84.81 | 84.78 | 81.18 | 59.0 |
| .25 | 92.04 | 92.00 | 87.60 | 82.7 |
| .50 | 99.48 | 99.48 | 96.18 | 105 |
| .75 | 107.28 | 107.12 | 103.97 | 132 |
| .90 | 114.56 | 114.59 | 110.99 | 156 |
| MAXIMUM | 138.19 | 137.71 | 143.13 | 268 |

CASE V. WEIBULL DISTRIBUTION $w = 2$

$$Y = (-144260504.1 \ln U)^{\frac{1}{2}}$$

| DE | $\hat{C\acute{E}P} 1$ | $\hat{C\acute{E}P} 2$ | $\hat{C\acute{E}P} 3$ | $\hat{C\acute{E}P} 4$ |
|-------------|-----------------------|-----------------------|-----------------------|-----------------------|
| MEAN | 86.18 | 85.80 | 84.25 | 100 |
| STD DEV | 5.23 | 5.19 | 11.47 | 19.6 |
| MODE | 218.34 | 228.61 | 379.57 | 382.00 |
| STD MEAN | 86.03 | 85.64 | | 98.1 |
| VARIANCE | 27.35 | 26.97 | 131.51 | 382 |
| COEF VAR | 0.06 | 0.06 | 0.14 | 0.20 |
| SKEWNESS | 0.029 | 0.028 | - 5.47 | - 0.24 |
| KURTOSIS | 0.28 | 0.27 | 38.40 | 0.17 |
| RANGE | 32.67 | 32.46 | 112.79 | 121 |
| MINIMUM | 71.49 | 71.14 | 0.0 | 420 |
| 10 QUANTILE | 79.37 | 79.04 | 78.33 | 74.2 |
| 25 | 82.87 | 82.52 | 81.89 | 88.5 |
| 50 | 86.29 | 85.89 | 85.42 | 100.0 |
| 75 | 89.50 | 90.12 | 88.69 | 113 |
| 90 | 92.50 | 92.07 | 91.56 | 124 |
| MAXIMUM | 104.16 | 103.61 | 112.79 | 163 |

CASE VI. WEIBULL DISTRIBUTION $w = 1.5$

$$Y = (-1442695.04 \ln U)^{\frac{2}{3}}$$

| | $\hat{C\acute{E}P} 1$ | $\hat{C\acute{E}P} 2$ | $\hat{C\acute{E}P} 3$ | $\hat{C\acute{E}P} 4$ |
|--------------|-----------------------|-----------------------|-----------------------|-----------------------|
| MOE | | | | |
| MEAN | 89.58 | 89.28 | 87.51 | 102 |
| STD DEV | 7.07 | 7.04 | 12.85 | 25.7 |
| MSE | 158.65 | 164.46 | 321.29 | 664 |
| GED MEAN | 89.30 | 89.00 | | 98.4 |
| VARIANCE | 50.07 | 49.54 | 165.09 | 660 |
| COEF VAR | 0.08 | 0.08 | 0.148 | - 0.25 |
| SKEWNESS | 0.07 | 0.07 | - 4.27 | - 0.04 |
| KURTOSIS | 0.22 | 0.21 | 27.91 | 0.11 |
| RANGE | 44.55 | 44.26 | 125.57 | 161 |
| MINIMUM | 69.36 | 69.10 | 0.0 | 31.5 |
| .10 QUANTILE | 80.27 | 79.99 | 78.95 | 67.6 |
| .25 | 85.39 | 85.12 | 83.80 | 86.4 |
| .50 | 89.59 | 89.25 | 88.60 | 101 |
| .75 | 94.37 | 94.07 | 93.44 | 120 |
| .90 | 98.31 | 98.00 | 97.48 | 133 |
| MAXIMUM | 113.91 | 113.37 | 125.57 | 193 |

CASE VII. WEIBULL DISTRIBUTION $w = .5$

$$Y = (-144.27 \ln U)^2$$

| MOE | $\hat{C}EP\ 1$ | $\hat{C}EP\ 2$ | $\hat{C}EP\ 3$ | $\hat{C}EP\ 4$ |
|--------------|----------------|----------------|----------------|----------------|
| MEAN | 166.57 | 170.05 | 87.45 | 146 |
| STD DEV | 42.61 | 44.99 | 31.55 | 99.2 |
| MSE | 6246.94 | 6930.96 | 1153.15 | 11956 |
| GED MEAN | 161.26 | 164.32 | 81.72 | 113 |
| VARIANCE | 1815.38 | 2023.96 | 995.65 | 9840 |
| COEF VAR | 0.26 | 0.26 | 0.36 | 0.68 |
| SKEWNESS | 0.62 | 0.70 | 0.76 | 1.39 |
| KURTOSIS | 0.53 | 0.76 | 1.48 | 3.26 |
| RANGE | 250.79 | 258.53 | 218.72 | 746 |
| MINIMUM | 75.81 | 78.48 | 18.67 | 3.24 |
| .10 QUANTILE | 116.20 | 117.74 | 49.30 | 41.2 |
| .25 | 135.54 | 137.27 | 66.56 | 75.8 |
| .50 | 163.59 | 165.51 | 84.41 | 126 |
| .75 | 191.58 | 196.45 | 105.80 | 194 |
| .90 | 220.85 | 227.60 | 127.69 | 282 |
| MAXIMUM | 326.60 | 337.01 | 237.40 | 750 |

CASE VIII. WEIBULL DISTRIBUTION $w = .1$

$$Y = (-3.623886 \ln U)^{10}$$

| | $\hat{C}\hat{E}\hat{P}$ 1 | $\hat{C}\hat{E}\hat{P}$ 2 | $\hat{C}\hat{E}\hat{P}$ 3 | $\hat{C}\hat{E}\hat{P}$ 4 |
|--------------|---------------------------|---------------------------|---------------------------|---------------------------|
| MOE | | | | |
| MEAN | $2.6 \cdot 10^5$ | $3.6 \cdot 10^5$ | 131.06 | $5.1 \cdot 10^4$ |
| STD DEV | $7.8 \cdot 10^5$ | $1.1 \cdot 10^6$ | 335.02 | $2.8 \cdot 10^5$ |
| MSE | $6.7 \cdot 10^{11}$ | $1.4 \cdot 10^{12}$ | $1.13 \cdot 10^5$ | $8.2 \cdot 10^{10}$ |
| GED MEAN | $6.0 \cdot 10^4$ | $7.4 \cdot 10^4$ | 85.89 | 674 |
| VARIANCE | $6.0 \cdot 10^{11}$ | $1.3 \cdot 10^{12}$ | $1.1 \cdot 10^5$ | $7.9 \cdot 10^{10}$ |
| COEF VAR | 2.97 | 3.14 | 2.56 | 5.43 |
| SKEWNESS | 7.95 | 8.38 | 14.16 | 14.4 |
| KURTOSIS | 81.28 | 89.17 | 232.51 | 255 |
| RANGE | $9.8 \cdot 10$ | $1.4 \cdot 10^7$ | 6214.98 | $5.4 \cdot 10^6$ |
| MINIMUM | 461.12 | 476.59 | 5.65 | $7.2 \cdot 10^6$ |
| .10 QUANTILE | 6859.66 | 7661.19 | 30.28 | 4.41 |
| .25 | $1.8 \cdot 10^4$ | $2.2 \cdot 10^4$ | 54.43 | 77.0 |
| .50 | $5.9 \cdot 10^4$ | $7.4 \cdot 10^4$ | 93.37 | 1070 |
| .75 | $1.7 \cdot 10^5$ | $2.2 \cdot 10^5$ | 140.28 | 9280 |
| .90 | $5.6 \cdot 10^5$ | $7.3 \cdot 10^5$ | 195.25 | $8.3 \cdot 10^4$ |
| MAXIMUM | $9.8 \cdot 10^6$ | $1.4 \cdot 10^7$ | 6220.63 | $5.4 \cdot 10^6$ |

COMPARISON OF ESTIMATORS

USING MEAN SQUARED ERROR AS A CRITERION:

$$MSE[\hat{C\acute{E}P}] = \hat{\sigma}_{\hat{C\acute{E}P}} + [E(\hat{C\acute{E}P}) - C\acute{E}P]^2$$

| CASE NO. | DISTRIBUTION | $\hat{C\acute{E}P}$ 1 | $\hat{C\acute{E}P}$ 2 | $\hat{C\acute{E}P}$ 3 | $\hat{C\acute{E}P}$ 4 |
|----------|-----------------|-----------------------|-----------------------|-----------------------|-----------------------|
| I | RAYLEIGH | 136 | 136 | 165 | 1549 |
| II | UNIFORM | 109 | 107 | 368 | 1744 |
| III | POWER | 2460 | 83,000 | 444 | 2279 |
| IV | TRANSLATED RAY. | 134 | 134 | 177 | 1524 |
| V | WEIBULL w = 2. | 218 | 228 | 379 | 382 |
| VI | WEIBULL w = 1.5 | 158 | 164 | 321 | 664 |
| VII | WEIBULL w = .5 | 6246 | 6930 | 1153 | 11956 |
| VIII | WEIBULL w = .1 | $6.77 \cdot 10^{11}$ | $6.78 \cdot 10^{11}$ | $1.13 \cdot 10^5$ | $8.17 \cdot 10^{10}$ |

VII. CONCLUSION

In general, we found the maximum likelihood power estimator $\hat{C\acute{E}P 3}$ is better than moment method power estimator, in that it does not have the limitations and exists for all parent distributions we considered. Using minimum mean squared error as a criterion, the estimators based on the power model have inferior performance in the "shallow tailed" cases, but were best in the heavy tailed cases, this is especially true for the $w = .1$ Weibull case, in which it has less bias than its competitors and has relatively small variance.

We found the Rayleigh based CEP estimators ($\hat{C\acute{E}P 1}$) to be possibly the best overall, especially for the shallow tailed cases. The maximum likelihood jackknife Rayleigh estimator ($\hat{C\acute{E}P 2}$) had no better performance than the unbiased Rayleigh estimator.

The value of the sample median estimator ($\hat{C\acute{E}P 4}$) can be found for small samples with such rapidity that in certain cases the time saved may compensate for the accuracy lost.

In practice, when analysts find several impact points comparatively far away from target, they should choose maximum likelihood power estimator ($\hat{C\acute{E}P 3}$). Otherwise they could choose Rayleigh based CEP estimator ($\hat{C\acute{E}P 1}$).

APPENDIX 1: MAXIMUM LIKELIHOOD POWER ESTIMATOR

```

DIMENSION Y(200),S(2001),A(2001)
DIMENSION CEP(500)
CALL QVFLOW
ISEED=470723
READ (5,100) AO,SO
READ (5,200) NS,ISTOP,S(1),A(1)
SN=FLOAT(NS)
FA=-1.0/AO
KS=500
DC 1 KI=1, KS

C
C
GENERATE POWER SQUARE DEVIATE
DC 5 N=1, NS
Y(N)=0.0
CALL RANDOM (ISEED,U,1)
Y(N)=SO*(U**FA-1.0)
5 CONTINUE

C
C
SOLVE NONLINEAR EQUATION UNDER NEWTON'S SECOND METHOD
DO 10 I=1, ISTOP
ITERS=I
A(I+1)=0.0
S(I+1)=0.0
CALL BF (S(I),Y,NS,B)
CALL CF (S(I),Y,NS,C)
CALL DF (S(I),Y,NS,D)
E=ALOG(S(I))
UX=SN/A(I)+SN*E-B
VX=SN*A(I)/S(I)-(A(I)+1.0)*D
WX=-SN/(A(I)**2)
XX=SN/S(I)-D
ZX=-SN*A(I)/(S(I)**2)+(A(I)+1.0)*C
DET=WX*ZX-XX**2

C
C
CHECK THE DETERMINATION
IF (DET.EQ.0.0) GO TO 99
UU=ZX*UX-XX*VX
VV=WX*VX-XX*UX

C
C
WHETHER TO STOP THE ITERATION
CHI=-(UX*UU+VX*VV)/DET
IF (CHI.LE.0.040) GO TO 88
A(I+1)=A(I)-UU/DET
S(I+1)=S(I)-VV/DET
IF (S(I+1).GT.0.0) GO TO 10
S(I+1)=S(I)/2.0
10 CONTINUE
88 AOUT=A(ITERS)
SOUT=S(ITERS)

C
C
ESTIMATE CEP
AK=2**((1.0/AOUT)-1.0)
CEP(KI)=(SOUT*AK)**0.5
WRITE (6,400) SOUT,AOUT,ITERS,CEP(KI)
1 CONTINUE
CALL HISTG (CEP,KS,0)
99 STOP
END

SUBROUTINE RF (S,Y,NS,B)
DIMENSION Y(200)
B=0.0
DC 30 N=1, NS
B=B+ALOG(S+Y(N))
30 CCNTINUE

```

```
RETURN  
END
```

```
SUBROUTINE CF (S,Y,NS,C)  
DIMENSION Y(200)  
C=0.0  
DO 40 N=1,NS  
C=C+1.0/(S+Y(N))**2  
40 CONTINUE  
RETURN  
END
```

```
SUBROUTINE DF (S,Y,NS,D)  
DIMENSION Y(200)  
D=0.0  
DO 50 N=1,NS  
D=D+1.0/(S+Y(N))  
50 CONTINUE  
RETURN  
END
```

APPENDIX 2: RAYLEIGH UNBIASED AND JACKKNIFE ESTIMATOR

```

DIMENSION Y(50,50),SP(50),PSE(50),CEP(500)
DIMENSION RAY(500)
C
C GENERATE RAYLEIGH DEVIATE
CALL OVFLOW
ISEED=470723
C
C READ IN ORIGINAL POP. PARAMETER VO , TOTAL SAMPLE SIZE
C NS, SUBGROUP SAMPLE SIZE KS
READ (5,100) VO,NS,KS
CPC=1.17741002*SQRT(VO)
MS=NS/KS
SM=FLOAT(MS)
SN=FLOAT(NS)
SK=FLOAT(KS)
WRITE (6,200) VO,CPC,NS,MS,KS
KE=500
DO 1 KRE=1,KE
DO 5 M=1,MS
DO 5 K=1,KS
Y(M,K)=0.0
CALL RANDJM (ISEED,U,1)
Y(M,K)=10000.0*(1.0/U-1.0)
5 CONTINUE
C
C ESTIMATE THE PARAMETER BASED ON ALL DATA
T=0.0
DO 10 M=1,MS
DO 10 K=1,KS
T=T+Y(M,K)
10 CONTINUE
TM=SQRT(T/(SN*2.0))
C
C MAXIMUM LIKELIHOOD UNBIASED ESTIMATOR
RAY(KRE)=1.1848*TM
C
C ESTIMATE THE PARAMETER BASED ON ALL DATA EXCEPT THOSE
C IN THE ITH GROUP
DO 20 M=1,MS
S=0.0
DO 25 I=1,MS
IF (I.EQ.M) GO TO 25
DO 26 K=1,KS
S=S+Y(I,K)
26 CONTINUE
25 CONTINUE
SP(M)=SQRT(S/((SN-SK)*2.0))
20 CONTINUE
C
C COMPUTE THE MS PSEUDO VALUES
DO 40 M=1,MS
PSE(M)=SM*TM-(SM-1.0)*SP(M)
40 CONTINUE
C
C ESTIMATE JACKKNIFE PARAMETER
ACK=0.0
DO 45 M=1,MS
ACK=ACK+PSE(M)
45 CONTINUE
VJACK=ACK/SM
SCK=0.0
C
C COMPUTER THE CONFIDENCE INTERVAL
DO 50 I=1,MS
SCK=SCK+(PSE(I)-VJACK)**2
50 CONTINUE

```

```
SVJA=SCK/(SM*(SM-1.0))
UPE=VJACK-2.0*SQRT(SVJA)
PLB=VJACK+2.0*SQRT(SVJA)
```

C
C

```
ESTIMATE CEP FROM JACKKNIFE PARAMETER
CEP(KRE)=1.1774*VJACK
WRITE (6,300) VJACK,UPB,PLB,CEP(KRE)
1 CONTINUE
CALL HISTG (RAY,KE,0)
CALL HISTG (CEP,KE,0)
STOP
END
```

BIBLIOGRAPHY

1. Jordan, M.F., "Methods and Models for Estimating the Accuracy of Air-To-Surface Weapon Delivery," M.S. Thesis, Naval Postgraduate School, Monterey, CA., September, 1973.
2. Barr, D.R. and Jordan, M.F., "A Power Distribution Model for Weapon Accuracy", Technical Report, Naval Postgraduate School, Monterey, CA., January, 1974.
3. Luenberger, D.G., Introduction to Linear and Nonlinear Programming, Addison-Wesley, Inc., 1973.
4. Kendall, M.G., and Stuart, A., The Advanced Theory of Statistics, Volume 2, Hafner, Co., New York, 1961.
5. Moranda, P.B., "Comparison of Estimates of Circular Probable Error", JASA, 54, p. 794-800, 1959.
6. Chapman, D.G., and Robbins, H., "Minimum Variance Estimation Without Regularity Assumption", Annals of Mathematical Statistics, 22 (1951).
7. Brillinger, D.R., "The Asymptotic Behavior of Tukey's General Method of Setting Approx. Confidence Limits (The Jackknife) When Applied to Maximum Likelihood Estimates", Review of the Inter. Stat. Inst., v. 32:3, 1964.
8. Ravenis, J.V., "Estimating Weibull-Distribution Parameters", Electro-Technology, March, 1964.
9. Miller, R.G., "Jackknifing Variance", The Annals of Math. Statistics, 39, No. 2, p. 567-582, 1968.
10. Quenouille, M.H., "Notes On Bias In Estimation", Biometrika, 43, 1956.
11. Hojo, T., "Distribution of the Median, Quartiles and Interquartile Distance in Samples From A Normal Population", Biometrika, Vol. 23 (1931), pp. 315-36.
12. Inselman, E.H., "Circular Distribution Estimation", Operations Research, V. 15, P. 161-165, Jan. 1967.

INITIAL DISTRIBUTION LIST

| | No. Copies |
|--|------------|
| 1. Defense Documentation Center Cameron Station Alexandria, Virginia 22314 | 2 |
| 2. Library Code 0212 Naval Postgraduate School Monterey, CA., 93940 | 2 |
| 3. Assoc. Professor Donald Barr Department of Operations Research and Administrative Sciences Naval Postgraduate School Monterey, CA., 93940 | 1 |
| 4. Department of Operations Research and Administrative Sciences Naval Postgraduate School Monterey, CA., 93940 | 1 |
| 5. Assoc. Professor Rex Shudde Department of Operations Research and Administrative Sciences Naval Postgraduate School Monterey, CA., 93940 | 1 |
| 6. Lieutenant Tzu-Ming Chen Chinese Navy Headquarters, Military Assistance Advisory Group Republic of China APO San Francisco 96263 | 1 |

thesC4125

Relative robustness of several CEP estim



3 2768 001 02390 6

DUDLEY KNOX LIBRARY