

AD-A025 503

AD A 025503

AD

USADAC TECHNICAL LIBRARY



5 0712 01016820 0

EDGEWOOD ARSENAL CONTRACTOR REPORT

EM-CR-76030

Report No. 3

ESTIMATING EXTERNAL BLAST LOADS FROM SUPPRESSIVE STRUCTURES

by
E. D. Esparza

TECHNICAL
LIBRARY

November 1975

SOUTHWEST RESEARCH INSTITUTE
Post Office Drawer 28510, 8500 Culebra Road
San Antonio, Texas 78284

Contract No. DAAA15-75-C-0083



DEPARTMENT OF THE ARMY
Headquarters, Edgewood Arsenal
Aberdeen Proving Ground, Maryland 21010



Approved for public release; distribution unlimited

Disclaimer

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.


UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER EM-CR-76030	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ESTIMATING EXTERNAL BLAST LOADS FROM SUPPRESSIVE STRUCTURES		5. TYPE OF REPORT & PERIOD COVERED Technical Report Sept. 1974 to July 1975
		6. PERFORMING ORG. REPORT NUMBER No. 3
7. AUTHOR(s) E. D. Esparza		8. CONTRACT OR GRANT NUMBER(s) DAA-15-75-C-0083
9. PERFORMING ORGANIZATION NAME AND ADDRESSES Southwest Research Institute P. O. Drawer 28510 San Antonio, Texas 78284		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS PA, A 5751264
11. CONTROLLING OFFICE NAME AND ADDRESS Commander, Edgewood Arsenal Attn: SAREA-PR-W Aberdeen Proving Ground, Maryland 21010		12. REPORT DATE November 1975
		13. NUMBER OF PAGES 16
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Commander, Edgewood Arsenal Attn: SAREA-MT-H Aberdeen Proving Ground, MD 21010 (CPO Mr. Bruce W. Jezek, 671-2661)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Suppressive shields Blast scaling External blast Effective vent areas Blast attenuation		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report describes methods for predicting blast overpressure outside suppressive structures. Prediction curves are in scaled form. Data are compared to free-field data for large high-explosive detonations on the ground.		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

SUMMARY

This report describes methods for predicting blast overpressures outside suppressive structures of various sizes with a variety of vented panel configurations. The prediction curves are presented in scaled form, based on a previously developed model law. Free-field data are compared to scaled data from large high explosive detonations on the ground. Results are tentative because of continuing experimental work which may modify the curve fits given in the report.

PREFACE

The investigation described in this report was authorized under PA, A 4932, Project 5751264. The work was performed at Southwest Research Institute under Contract DAAA15-75-C-0083.

The use of trade names in this report does not constitute an official endorsement or approval of the use of such commercial hardware or software. This report may not be cited for the purposes of advertisement.

The information in this document has been cleared for release to the general public.

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	6
I. INTRODUCTION	7
II. ANALYSIS	7
III. RESULTS	11
IV. DISCUSSION AND CONCLUSIONS	14
REFERENCES	16

LIST OF ILLUSTRATIONS

Figure		Page
1	Definition of α for a Layer of Angles	9
2	Definition of α for Louvres	10
3	Curve Fit to Blast Pressures Outside NSTL Structures	12
4	Curve Fit to NSTL Free Field Blast Pressures	13
5	Curve Fit to NSTL, Snowball and Flat Top Free Field Blast Pressures	16

ESTIMATING EXTERNAL BLAST LOADS FROM SUPPRESSIVE STRUCTURES

I. INTRODUCTION

Suppressive structures are intended to attenuate the blast waves transmitted through their walls to levels which will minimize damage to other nearby structures or injury to nearby personnel. Accordingly, most of the past and planned tests of suppressive structures include measurements of the blast fields over a range of distances from their outer surfaces. Such data have usually been compared to blast pressures measured from the same blast sources without the suppressive structure, or to compiled data on air blast. The data from many different experiments can be scaled, however, and placed on a common basis to extend the range of prediction of blast attenuation for structures of different size, attenuating panel design, or explosive charge weight. In this report, we develop prediction equations for side-on blast overpressures outside suppressive structures with a variety of panel designs, based on a blast scaling law.

The work reported here was conducted for Edgewood Arsenal under Contract DAAA15-75-C-0083 as a part of the suppressive structures program.

II. ANALYSIS

The methodology for developing equations to estimate the side-on overpressure at a location outside of a suppressive structure is presented in Reference 1. However, since some of the parameters used to determine an expression for side-on pressure have subsequently been slightly redefined, an abbreviated analysis will be presented here.

The free-field relationship for side-on overpressure P_s is given by the Hopkinson-Cranz scaling law for geometrically similar sources at sea-level ambient atmospheric conditions as

$$P_s = f \left(\frac{R}{W^{1/3}} \right) \quad (\text{free field}) \quad (1)$$

Using a similar analysis to derive a functional expression for the side-on overpressures outside of a suppressive structure, we have

$$P_s = f_1 \left(\frac{R}{W^{1/3}}, \frac{X}{R}, \alpha_e \right) \quad (2)$$

where

$$P_s = \text{side-on pressure (psi)}$$

$$Z = R/W^{1/3} \text{ (ft/lb}_m^{1/3}\text{)}$$

R — distance from charge (ft)
 W — charge weight (lb)
 X — characteristic length of structure (ft)

For square walls, X = side dimension

For rectangular walls, X = square root of wall area

α_e — effective vent area ratio (-)

$L = R/X$ (-)

To compute α_e for N -layered, multiwalled structures, we have assumed that

$$\frac{1}{\alpha_e} = \sum_{i=1}^N \frac{1}{\alpha_i} \quad (3)$$

This relationship has at the moment no theoretical proof. However, it does reach the appropriate limits for small and large number of plates, and provides a relative measure of venting for a variety of panel configurations. For each vented member in a panel, α is defined as

$$\alpha_i = \left(\frac{\text{Vent Area}}{\text{Wall Area}} \right)_i, \frac{A_{V_i}}{A_W}, \dots \quad (4)$$


For perforated plates, the meaning of Equation (4) is obvious; however, for angles and louvres, the definition is less obvious. Figures 1 and 2 show the present definition of α for these two members.

Now that all the parameters in Equation (2) have been defined, this equation is assumed to have the form


$$P_s = A (Z)^{N_1} \left(\frac{X}{R} \right)^{N_2} (\alpha_e)^{N_3} \quad (5)$$

which will allow least-squares fitting to experimental data. Taking logarithms of both sides, a least-squares curve fit can be developed using the experimental data and stating that

$$\begin{bmatrix} 1.0, \ln Z, \ln \frac{X}{R}, \ln \alpha_e \end{bmatrix} \begin{bmatrix} \ln A \\ N_1 \\ N_2 \\ N_3 \end{bmatrix} = [\ln P_s] \quad (6)$$



SECTION A - A




$$A_{\text{vent}} = J \lambda g, \quad J = \text{NUMBER OF OPENINGS}$$

$$A_{\text{wall}} = LM$$

$$\alpha = \frac{A_{\text{vent}}}{A_{\text{wall}}}$$

FIGURE 1. DEFINITION OF α FOR A LAYER OF ANGLES



$$A_{vent} = K a_v, \quad K = \text{NUMBER OF LOUVRES}$$

$$A_{wall} = LM$$

$$\alpha = \frac{A_{vent}}{2 A_{wall}}$$

FIGURE 2. DEFINITION OF α FOR LOUVRES

or, substituting matrix notation,

$$[L] [N] = [P] \quad (7)$$

A least-squares curve fit results for the N matrix (N_1, N_2 , and N_3) when

$$[N] = [L^T L]^{-1} [L^T] [P] \quad (8)$$

III. RESULTS

Before any curve fitting was done, all the original NSTL data used to derive the previous expression P_s (see Reference 1) was rechecked to make sure that it was on a common base. Particular attention was given to computing α_e and X . However, because in several cases panel drawings were not available, the vent areas for each panel member were taken to be those which were stated in the texts of References 2, 3, and 4. The resulting equation from curve fitting the experimental data from these reports is

$$P_s = 677.5 \frac{L^{0.485} \alpha_e^{0.537}}{Z^{1.84}} \quad (9)$$

Figure 3 is a plot of Equation (9) versus the experimental data points used to compose this plot. This equation appears to curve fit the test results very well. The estimate of the standard deviation, S , for the experimental data about the line equals $\pm 20\%$ which is only slightly worse than the spread obtained for similar free-field data. *Because this is a curve fit to test data, Equation (9) should only be used when input conditions fall within variations in the individual pi terms.* The variations in the test results were:

$$\begin{aligned} 0.55 &\leq L \leq 3.09 \\ 0.025 &\leq \alpha_e \leq 0.60 \\ 4.29 \text{ ft/lb}_m^{1/3} &\leq Z \leq 15.5 \text{ ft/lb}_m^{1/3} \end{aligned}$$

Taking the free-field side-on pressure data from the same three references and curve-fitting using the same procedure over a similar range of Z as for the suppressive structure pressure data, the resulting equation is

$$P_s = \frac{962.3}{Z^{2.057}} \quad (10)$$

Figure 4 compares Equation (10) and the data points. This equation appears to curve fit the test results excellently with an S of $\pm 13\%$ which, as would be expected, is slightly better than the fit for the suppressive structure blast field. Naturally, Equation (10) should only be applied whenever Z varies as follows:

$$4.29 \text{ ft/lb}^{1/3} \leq Z \leq 15.9 \text{ ft/lb}_m^{1/3}$$




FIGURE 3. CURVE FIT TO BLAST PRESSURES
OUTSIDE NSTL STRUCTURES




FIGURE 4. CURVE FIT TO NSTL FREE FIELD BLAST PRESSURES

It is interesting to see how additional free-field data points from tests using charge weights which are orders of magnitude larger than those used to generate the NSTL data, will affect the curve fit. Using data from four different large-scale field tests^{5, 6} which fall within the same range of Z used previously results in

$$P_s = \frac{1089.2}{Z^{2.098}} \quad (11)$$

Figure 5 compares this equation with all the data points used and shows an excellent fit with an S of $\pm 13\%$.

Comparing Equations (10) and (11), one can see that they are almost identical. As a matter of fact the side-on pressure predicted by these equations would differ by a maximum of only 6.2% at a Z of 4.29 ft/lb_m^{1/3}. This difference decreases to an insignificant 1% at the upper limit of Z (15.9 ft/lb_m^{1/3}).

IV. DISCUSSION AND CONCLUSIONS

It must be emphasized again that in using the empirical equations in this report, the limits given for the individual π terms must be satisfied. *If large extrapolations are attempted beyond these limits, gross errors will certainly occur in estimating P_s .* For example, as a blast wave propagates to great distances from its source, it travels at essentially the speed of sound and, assuming homogeneous, still air, the pressure in the front would decrease as the inverse of the distance R (or as a function of $1/Z$).⁷ However, for the data range used here to obtain the free-field equations, the pressure is decreasing approximately as the inverse of the distance squared.

Work in measurement of blast pressures outside suppressive structures is continuing apace, and the results presented here will certainly be updated and extended in coming months. In particular, sufficient data for side-on impulse should soon be available to establish fits similar to those given here for side-on overpressure, and data will be available for other panel configurations such as interlocked I-beams. The equations and curves presented here must therefore be considered as interim ones, to be supplemented or supplanted as later data becomes available.

REFERENCES

1. W. E. Baker, P. S. Westine, P. A. Cox and E. D. Esparza, Southwest Research Institute, San Antonio, Texas, Technical Report No. 1. Contract No. DAAD05-74-C-0751, Analysis and Preliminary Design of a Suppressive Structure for a Melt Loading Operation, March 1974.




FIGURE 5. CURVE FIT TO NSTL, SNOWBALL AND FLAT TOP FREE FIELD BLAST PRESSURES

2. Report EA-FR-2B02, Final Report Application of Suppressive Structure Concepts to Chemical Agent Munition Demilitarization System (CAMDS), July 27, 1973.
3. A. H. Lasseigne, Report EA-FR-4C04. Static and Blast Pressure Investigation for the Chemical Agent Munition Demilitarization System: Sub-Scale. November 30, 1973.
4. Report EA-4E33, 81 mm Suppressive Shielding Technical Data Package. January 1974.
5. R. E. Reisler, J. H. Keefer, and L. Giglio-Tos. BRL Memo Report No. 1818. Basic Air Blast Measurements from a 500-Ton TNT Detonation Project 1.1 Operation Snowball. Ballistic Research Laboratories, Aberdeen Proving Ground, Maryland, December 1966.
6. J. H. Keefer, R. E. Reisler, L. Giglio-Tos and R. C. Kellner, Report No. POR-3001. Ferris Wheel Series—Flat Top Event Air Blast Phenomena, Aberdeen Proving Ground, Maryland, October 1966.
7. W. E. Baker, *Explosions in Air*, Univ. of Texas Press, Austin, Texas, 1973.

DISTRIBUTION OF SUPPRESSIVE SHIELDING REPORTS

Addressee	No. of Copies
Commander Rocket Propulsion Laboratory Attn: Mr. M. Raleigh Edwards Air Force Base, CA 93523	1
Commander HQ, Armament Development Test Center Attn: DOM/Mr. S. Reither Eglin Air Force Base, FL 32542	1
Commander Hill Air Force Base Attn: MMNTR/Mr. Cummings Clearfield, UT 84406	1
Commander Norton Air Force Base Attn: AFISC-SEV/Mr. K. Collinsworth San Bernardino, CA 92409	1
Commander Air Force Civil Engineering Center Attn: AFCEC-DE/LTC Walkup Tyndall Air Force Base Panama City, FL 32401	1
Commander HQ Air Force Logistics Command Attn: MMWM/CPT D. Rideout IGYE/Mr. K. Shopher Wright-Patterson Air Force Base Dayton, OH 45433	1 ea
Commander Naval Ordnance Systems Command Attn: Code ORD 43B/Mr. A. Fernandes Washington, DC 20360	1
Commander Explosives Safety Attn: ADTC/SEV (Mr. Ron Allen) Eglin Air Force Base, FL 32542	1

Commander Bureau of Naval Weapons Attn: Code F121/Mr. H. Roylance Department of the Navy Washington, DC 20360	1
Commander Naval Ship Research & Development Center Attn: Code 1747/Mr. A. Wilner Bethesda, MD 20034	1
Commander Naval Explosive Ordnance Disposal Facility Attn: Code 501/Mr. L. Wolfson Indianhead, MD 20640	1
Commander Naval Ordnance Systems Command NAPEC Naval Ammunition Depot Attn: ORD-04M/B/X-5/Mr. L. Leonard Crane, IN 47522	1
Commander US Naval Surface Weapons Center Attn: Mr. J. Proctor Whiteoak, MD 20904	1
Chairman DOD Explosives Safety Board Attn: COL P. Kelly, Jr. Forrestal Building GB-270 Washington, DC 20314	5
Joint Army-Navy-Air Force Conventional Ammunition Production Coordinating Group USA Armament Command Attn: Mr. Edward Jordan Rock Island, IL 61201	5
HQDA (DAEN-MCC-I/Mr. L. Foley) Washington, DC 20314	1
HQDA (DAEN-MCE-D/Mr. R. Wight) Washington, DC 20314	1
Director USAMC Field Safety Activity Attn: AMXOS-TA/Mr. Olson Charlestown, IN 47111	1

Commander 1 ea
US Army Materiel Command
Attn: AMCCG
AMCRD/Dr. Kaufman
AMCSF/Mr. W. Queen
AMCPM-CS/COL Morris
5001 Eisenhower Ave.
Alexandria, VA 22333

Office of the Project Manager for 3
Munition Production Base Modernization
and Expansion
Attn: AMCPM-PBM-E/Mr. Dybacki
USA Materiel Command
Dover, NJ 07801

Commander 1 ea
US Army Armament Command
Attn: AMSAR-EN/Mr. Ambrosini
AMSAR-SC/Dr. C. Hudson
AMSAR-SF/Mr. J. Varcho
AMSAR-TM/Mr. Serlin, Mr. T. Fetter, Mr. S. Porter
AMSAR-MT/Mr. A. Madsen, Mr. G. Cowan, CPT Burnsteel
Rock Island Arsenal
Rock Island, IL 61201

Commander 1 ea
USAMC Ammunition Center
Attn: Mr. J. Byrd
AMXAC-DEM/Mr. Huddleston
Mr. Sumpterer
Savanna, IL 61074

Commander 1 ea
Frankford Arsenal
Attn: Mr. F. Fidel, Mr. E. Rempler
Bridge and Tacony Sts.
Philadelphia, PA 19137

Commander
Picatinny Arsenal
Attn: Mr. Saffian 3
Mr. J. Cannovan 1 ea
Mr. Hickerson
Mr. I. Forsten
Dover, NJ 07801

Commander
USA Test and Evaluation Command
Attn: AMSTE-NB
Aberdeen Proving Ground, MD 21005

1

Commander
Dugway Proving Ground
Attn: Dr. Rothenburg
Mr. P. Miller
Dugway, UT 84022

1 ea

Commander
Cornhusker Army Ammunition Plant
Grand Island, NE 68801

1

Commander
Indiana Army Ammunition Plant
Charleston, IN 47111

1

Commander
Iowa Army Ammunition Plant
Burlington, IA 52502

1

Commander
Joliet Army Ammunition Plant
Joliet, IL 60436

1

Commander
Kansas Army Ammunition Plant
Parsons, KS 67357

1

Commander
Longhorn Army Ammunition Plant
Marshall, TX 75671

1

Commander
Lone Star Army Ammunition Plant
Texarkana, TX 75502

1

Commander
Louisiana Army Ammunition Plant
Shreveport, LA 71102

1

Commander
Milan Army Ammunition Plant
Milan, TN 38358

1

Commander
Radford Army Ammunition Plant
Radford, VA 24141

1

Commander Sunflower Army Ammunition Plant Lawrence, KS 66044	1
Commander Lake City Army Ammunition Plant Attn: Mr. John Jacobi Independence, MO 64056	1
Commander Ravenna Army Ammunition Plant Ravenna, OH 44266	1
Commander Pine Bluff Arsenal Pine Bluff, AR 71601	1
Director US Army Materiel Systems Analysis Activity Aberdeen Proving Ground, MD 21005	3
Director US Army Ballistics Research Laboratories Attn: Mr. R. Vitali Aberdeen Proving Ground, MD 21005	5
Division Engineer US Army Engineer Division, Huntsville Attn: HNDED-R/Mr. Dembo Mr. W. Char P.O. Box 1600, West Station Huntsville, AL 35807	1 ea
US Army Engineer Division Waterways Experimental Station P.O. Box 631 Vicksburg, MS 39180	1
Director USAMC Intern Training Center Attn: Dr. G. Chiang Red River Depot Texarkana, TX 75502	1
Dr. Robert D. Siewert NASA Lewis Laboratory 21000 Brook Park Rd Cleveland, OH 44135	1

Mr. George Pinkas Code 21-4 NASA Lewis Laboratory 21000 Brook Park Rd Cleveland, OH 44135	1
Mr. W. H. Jackson Deputy Manager for Engineering Atomic Energy Commission P.O. Box E Oak Ridge, TN 37830	1
Mr. Erskine Harton US Department of Transportation Washington, DC 20315	1
Dr. Jean Foster US Department of Transportation Washington, DC 20315	1
Mr. Frank Neff Mound Laboratory Monsanto Research Corp. Miamisburg, OH 45342	1
Ms. Trudy Prugh Mound Laboratory Monsanto Research Corp. Miamisburg, OH 45342	1
Commander Naval Weapons Laboratory Attn: Mr. F. Sanches Dahlgren, VA 22448	1
Dr. W. E. Baker Southwest Research Institute San Antonio, TX 78284	1
Division Engineer US Army Engineer Division, Fort Belvoir Fort Belvoir, VA 22060	1
Commander Naval Sea Systems Command Washington, DC 20315	1

Mr. Billings Brown 1
Hercules, Inc.
Box 98
Magna, UT 84044

Mr. John Komos 1
Defense Supply Agency
Cameron Station
Alexandria, VA 22030

Office of the Project Manager for Chemical 2
Demilitarization and Installation Restoration
Edgewood Arsenal
Aberdeen Proving Ground, MD 21010

Edgewood Arsenal
Technical Director
Attn: SAREA-TD-E 1
Foreign Intelligence Officer 1
Chief, Legal Office 1
Chief, Safety Office 1
CDR, US Army Technical Escort Center 1
Author's Copy, Manufacturing Technology Directorate 3
Aberdeen Proving Ground, MD 21010

Edgewood Arsenal
Director of Biomedical Laboratory
Attn: SAREA-BL-M 1
SAREA-BL-B 1
SAREA-BL-E 1
SAREA-BL-H 1
SAREA-BL-R 1
SAREA-BL-T 1
Aberdeen Proving Ground, MD 21010

Edgewood Arsenal
Director of Chemical Laboratory
Attn: SAREA-CL-C 1
SAREA-CL-P
Aberdeen Proving Ground, MD 21010

Edgewood Arsenal
Director of Development & Engineering
Attn: SAREA-DE-S 4
Aberdeen Proving Ground, MD 21010

Edgewood Arsenal
Director of Manufacturing Technology
Attn: SAREA-MT-TS
SAREA-MT-M
Aberdeen Proving Ground, MD 21010

2
1

Edgewood Arsenal
Director of Product Assurance
Attn: SAREA-PA-A
SAREA-PA-P
SAREA-PA-Q
Aberdeen Proving Ground, MD 21010

1
1
1

Edgewood Arsenal
Director of Technical Support
Attn: SAREA-TS-R
SAREA-TS-L
SAREA-TS-E
Aberdeen Proving Ground, MD 21010

2
3
1

Aberdeen Proving Ground
Record Copy
CDR, APG
Attn: STEAP-AD-R/RHA
APG-Edgewood Area, BLDG E5179
Aberdeen Proving Ground, MD 21005

1

Aberdeen Proving Ground
CDR, APG
Attn: STEAP-TL
APG, Aberdeen Area
Aberdeen Proving Ground, MD 21005

1

DEPARTMENT OF DEFENSE
Administrator
Defense Documentation Center
Attn: Accessions Division
Cameron Station
Alexandria, VA 22314

12

Commander
Edgewood Arsenal
Attn: SAREA-DM
Aberdeen Proving Ground, MD 21010

1

