

ADA 029180

AMRL-TR-76-3

12



WIND TUNNEL MEASUREMENTS OF VERTICAL ACTING LIMB FLAIL FORCES AND TORSO/ SEAT BACK FORCES IN AN ACES-II EJECTION SEAT

**PAYNE, INC.
1910 FOREST DRIVE
ANNAPOLIS, MARYLAND 21401**

JUNE 1973



Approved for public release; distribution unlimited

**AEROSPACE MEDICAL RESEARCH LABORATORY
AEROSPACE MEDICAL DIVISION
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433**

NOTICES

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Please do not request copies of this report from Aerospace Medical Research Laboratory. Additional copies may be purchased from:

National Technical Information Service
5285 Port Royal Road
Springfield, Virginia 22161

Federal Government agencies and their contractors registered with Defense Documentation Center should direct requests for copies of this report to:

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314

TECHNICAL REVIEW AND APPROVAL

AMRL-TR-76-3


This report has been reviewed by the Information Office (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER


HENNING E. VON GIERKE
Director
Biodynamics and Bionics Division
Aerospace Medical Research Laboratory

AIR FORCE - 20 AUGUST 76 - 100



REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AMRL-TR-76-3	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) WIND TUNNEL MEASUREMENTS OF VERTICAL ACTING LIMB FLAIL FORCES AND TORSO/SEAT BACK FORCES IN AN ACES-II EJECTION SEAT.		5. TYPE OF REPORT & PERIOD COVERED Final Report - Nov. 18, 1975 to March 31, 1976
6. AUTHOR(s) Fred W./Hawker Anthony J./Euler		7. PERFORMING ORG. REPORT NUMBER Working Paper, 148-7
8. PERFORMING ORGANIZATION NAME AND ADDRESS Payne, Inc. 1910 Forest Drive Annapolis, Maryland 21401		9. CONTRACT OR GRANT NUMBER(s) F33615-75-C- 5896
10. CONTROLLING OFFICE NAME AND ADDRESS Aerospace Medical Research Laboratory, Aerospace Medical Division, Air Force Systems Command, Wright-Patterson Air Force Base, Ohio 45433		11. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62202F 72310645
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Final rept. 18 Nov 75 - 31 Mar 76		13. REPORT DATE Jun 76
		14. NUMBER OF PAGES 27
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		16. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited 12 31p. 16 AF-7231 17 723106		
18. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
19. SUPPLEMENTARY NOTES		
20. KEY WORDS (Continue on reverse side if necessary and identify by block number) Aircraft Escape Systems Ejection Seats Flail Injury Aerodynamic Force Measurements		
21. ABSTRACT (Continue on reverse side if necessary and identify by block number) In the study of flail injury (References 4 and 5) it is important to know the magnitude of the forces tending to pull a crew member's limbs away from their "stowed" position, when he first ejects into the windblast. Earlier wind tunnel studies did not record the limb lift component force for the hands or feet. These forces, along with the drag force between the occupant and the seat, were measured in this investigation, for the range of pitch and yaw angles used in the previous investigations of other force components. The		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

277 770 LB

20. Abstract (Continued)

results and their implications are presented and discussed.

PREFACE

This report was prepared in partial fulfillment of Contract Number F33615-75-C-5096. The research was accomplished by Payne, Inc., 1910 Forest Drive, Annapolis, Maryland 21401. Peter R. Payne was the Principal Investigator.

The Air Force Technical Monitor was James W. Brinkley of the Impact Branch, Biodynamics and Bionics Division of the Aerospace Medical Research Laboratory. The work was performed in support of Project 7231, "Biodynamics of Aerospace Operation", Task 723106, "Impact Exposure Limits and Personnel Protection Criteria."

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	5
Test Facilities and Equipment	5
Local Force and Pressure Measurements	5
ACES-II Ejection Seat Modifications	5
Test Procedure	6
RESULTS AND DISCUSSION	15
Wind Tunnel Measurements of Limb and Torso Forces	15
Discussion of Seat and Occupant Ballistic Coefficients	15
CONCLUSIONS	26
REFERENCES	27

LIST OF FIGURES

<u>Figure No.</u>		<u>Page No.</u>
1	View of Right Ejection Handle and Strain-Gauged Beam for Measuring Vertical Hand Loads.	7
2	View of Foot Supports and Strain-Gauged Beam For Measuring Vertical Foot Loads.	8
3(a)	Front Elevation View of an ACES-II Ejection Seat "Liner."	9
3(b)	Side Elevation View of an ACES-II Ejection Seat "Liner."	10
4	Side View of ACES-II Ejection Seat Liner, With Helmet Attached.	11
5	Detail of Helmet Attachment to Liner.	12
6	Overall View of ACES-II Ejection Seat Showing Installation of Liner, Helmet, Ejection Handles and Foot Supports.	13
7	Schematic of Force Cell Locations and Critical Installation Dimensions.	14
8	Torso Force Area as a Function of Angle of Attack for the ACES-II Ejection Seat.	17
9	Pitching Moment Volume of the Torso Within the ACES-II Ejection Seat as a Function of Pitch Angle, About the Center of Gravity Defined for a 50% man in Figure 7.	18
10	Comparison of Seat Plus Occupant and Torso Plus Limb Drag Areas for ACES-II Ejection Seat.	19
11	Arm-Up Force Area as a Function of Angle of Attack For the ACES-II Ejection Seat (Yaw Angle, 0°).	20
12	Arm-Up Force Area as a Function of Angle of Attack For the ACES-II Ejection Seat (Yaw Angle, -15°).	21
13	Arm-Up Force Area as a Function of Angle of Attack of the ACES-II Ejection Seat (Yaw Angle, - 30°).	22
14	Leg-Lift Force Area as a Function of Angle of Attack For the ACES-II Ejection Seat (Yaw Angle, 0°).	23
15	Leg-Lift Force Area as a Function of Angle of Attack For the ACES-II Ejection Seat (Yaw Angle, -15°).	24

LIST OF FIGURES (Continued)

Figure No.

Page No.

16

Leg-Lift Force Area as a Function of Angle
of Attack for the ACES-II Ejection Seat
(Yaw Angle, -30°).

25

INTRODUCTION

In the study of flail injury (References 4 and 5) it is important to know the magnitude of the forces tending to pull a crew member's limbs away from their "stowed" position, when he first ejects into the windblast. The general background to the problem has been discussed by Payne (Reference 3) and some experimental measurements are reported in References 1, 2 and 3. Those measurements did not record the lift force on the hands or feet. They also did not measure the difference between the drag force on the torso and seat structure. An ACES-II ejection seat that had a large data base of wind tunnel tests with human subjects was therefore modified to measure these forces.

Test Facilities and Equipment

The University of Maryland subsonic wind tunnel is of the single return type with a rectangular working section 7.75 feet high by 11.04 feet wide. The tunnel is vented at the working section to ambient pressure, establishing the pressure reference datum. Dynamic pressure ($q = \frac{1}{2} \rho u^2$) at maximum tunnel operating speed is 135 lb/ft², corresponding to a speed of 337 ft/sec.

The tunnel is particularly suitable for tests with live subjects, since the test section accommodates a human figure, plus ejection seat, for less than 10% blockage and with adequate clearance above and below. The section is well lighted and has glass viewing panels on either side and above, so that the subject is under observation from the control room and additional vantage points. Details of the tunnel and the way in which it is used for limb flail tests may be found in References 1, 2, and 3.

Local Force and Pressure Measurements

The tunnel instrumentation provided 58 automated data channels, including ten galvanometer systems linear to 600 Hz. Eight of these channels were used to record limb and torso forces from strain-gauged beams mounted on the seat assembly. The measurements on these channels were automatically punched on IBM cards. Any six channels on this system could be switched to dynamic recording, linear to 150 Hz, when examination of transients in real time were required.

ACES-II Ejection Seat Modifications

The modifications to the existing ACES-II ejection seat were:

1. The ejection handles were positioned to accept strain-gauged beams to measure the lift force component (body axes) (Figure 1).

2. The feet supports were altered to accept strain-gauged beams to measure the lift force component (body axes). Figure 2.
3. A liner was constructed to fit within the ACES-II Seat and supported in such a manner that all the drag loads would be measured independently of the main ACES-II seat (body axes). Figures 3, 4, 5 and 6.

Test Procedure

These tests were run at a dynamic pressure of 20 pounds per square foot (129.7 ft/sec). The pitch angle is set and the tunnel balance automatically positions the subject at a given yaw angle. The prescribed forces are recorded digitally from the strain-gauged beams whose relative positions are shown in Figure 7.

All of the strain gauges were statically calibrated just prior to the test run. The Wheatstone bridge circuits were periodically shunted to see if there had been any damage to the circuits during the tests. Finally, all data was recorded as force areas, that being the measured force divided by the dynamic pressure ($C_f = F/q$).



FIGURE 1. VIEW OF RIGHT EJECTION HANDLE AND STRAIN-GAUGED BEAM FOR MEASURING VERTICAL HAND LOADS.




FIGURE 2. VIEW OF FOOT SUPPORTS AND STRAIN-GAUGED BEAM FOR MEASURING VERTICAL FOOT LOADS.




FIGURE 3(A). FRONT ELEVATION VIEW OF AN ACES-II EJECTION SEAT "LINER." THE DIMENSIONS ARE IN INCHES.




FIGURE 3(B). SIDE ELEVATION VIEW OF AN ACES-II EJECTION SEAT "LINER." THE DIMENSIONS ARE IN INCHES.




FIGURE 4. SIDE VIEW OF ACES-II EJECTION SEAT LINER, WITH HELMET ATTACHED.




FIGURE 5. DETAIL OF HELMET ATTACHMENT TO LINER.




FIGURE 6. OVERALL VIEW OF ACES-II EJECTION SEAT SHOWING INSTALLATION OF LINER, HELMET, EJECTION HANDLES AND FOOT SUPPORTS.

NOTES:

- 1) SEAT BACK ANGLE IS 13°
- 2) ANGLE θ IS MEASURED FROM THE HORIZONTAL
- 3) FORCE DESCRIPTION
 F_1 - TORSO
 F_2 - HEAD
 F_3, F_4 - (LEFT & RIGHT) SEAT SUPPORT
 F_5, F_6 - (LEFT & RIGHT) HAND
 F_7, F_8 - (LEFT & RIGHT) FOOT




FIGURE 7. SCHEMATIC OF FORCE CELL LOCATIONS AND CRITICAL INSTALLATION DIMENSIONS.

RESULTS AND DISCUSSION

Wind Tunnel Measurements of Limb and Torso Forces

The ACES-II seat was modified by installing a small "liner" seat pan and back, as shown in Figures 3 - 6, so that drag direction forces between the main seat and its occupant could be measured. Strain-gauged beams were also mounted to measure "hand-up" forces at the handles and "foot-up" forces on the footrests.

The seat was installed in the wind tunnel on Monday, August 11, and data collected using Fred W. Hawker as subject. Mr. Hawker is approximately 50 percentile, his statistics being

- Height: 5 ft 8 in
- Weight: 165 lbs
- Age : 27 years

The data is presented in Figures 8 - 16.

The torso drag and moment data are given in Figures 8 and 9. The drag data is added to the hand back and foot back data of Reference 1 and compared with the total seat plus occupant data of Reference 2 in Figure 10. About 80 percent of the total drag acts on the seat occupant at small trim angles, the ratio falling to about 50 percent at the high trim angles.

The moments of Figure 9 are not comparable with previously obtained total moment data because only forces in the drag direction were measured. Significant contributions could be made by the force distribution on the seat pan.

The "hand-up" forces are given in Figures 11 - 13 and the "foot-up" forces in Figures 14 - 16. The hand-up forces show a consistent decrease in magnitude with pitch angle. The maximum lift force occurs at approximately zero degrees angle of attack. The foot-up force shows an increase with angle of attack. These quantitative results confirm earlier observations by Major Ray Madson of the lifting effect on the legs at high angles of attack.

Discussion of Seat and Occupant Ballistic Coefficients

A_1 = occupant drag area

A_2 = seat drag area

$$m_1 \dot{u}_1 = A_1 \frac{1}{2} \rho u^2$$

$$m_2 \dot{u}_2 = A_2 \frac{1}{2} \rho u^2$$

$$\therefore \frac{\dot{u}_2}{\dot{u}_1} = \frac{\text{seat deceleration}}{\text{occupant deceleration}} = \frac{A_2 m_1}{A_1 m_2}$$

ACES-II seat weight 81 pounds, occupant weight 165 pounds

From Figure 10

$$\frac{A_1}{gm_1} = \frac{5.3}{165} = .032$$

$$\frac{A_2}{gm_2} = \frac{(6.6 - 5.3)}{81} = .016$$

$$\therefore \frac{\dot{u}_2}{\dot{u}_1} = \frac{.016}{.032} = \frac{1}{2}$$

Thus the occupant has, in this position, twice the deceleration potential of the seat. Doubling the seat drag area by adding 1.3 ft² would equalize the decelerations. A drag area greater than 1.3 ft² would result in a tension force between the man and seat.




FIGURE 8. TORSO FORCE AREA AS A FUNCTION OF ANGLE OF ATTACK FOR THE ACES-II EJECTION SEAT.




FIGURE 9. PITCHING MOMENT VOLUME OF THE TORSO WITHIN THE ACES-II EJECTION SEAT AS A FUNCTION OF PITCH ANGLE, ABOUT THE CENTER OF GRAVITY DEFINED FOR A 50% MAN IN FIGURE 7.




FIGURE 10. COMPARISON OF SEAT PLUS OCCUPANT AND TORSO PLUS LIMB DRAG AREAS FOR ACES-II EJECTION SEAT.




FIGURE 11. ARM-UP FORCE AREA AS A FUNCTION OF ANGLE OF ATTACK FOR THE ACES-II EJECTION SEAT (YAW ANGLE, 0°).




FIGURE 12. ARM-UP FORCE AREA AS A FUNCTION OF ANGLE OF ATTACK FOR THE ACES-II EJECTION SEAT (YAW ANGLE, -15°).




FIGURE 13. ARM-UP FORCE AREA AS A FUNCTION OF ANGLE OF ATTACK OF THE ACFS-II EJECTION SEAT (YAW ANGLE, -30°)




FIGURE 14. LEG-LIFT FORCE AREA AS A FUNCTION OF ANGLE OF ATTACK FOR THE ACES-II EJECTION SEAT (YAW ANGLE, 0°).




FIGURE 15. LEG-LIFT FORCE AREA AS A FUNCTION OF ANGLE OF ATTACK FOR THE ACES-II EJECTION SEAT (YAW ANGLE, -15°).




FIGURE 16. LEG-LIFT FORCE AREA AS A FUNCTION OF ANGLE OF ATTACK FOR THE ACES-II EJECTION SEAT (YAW ANGLE, -30°).

CONCLUSIONS

1. The occupant of the ACES-II ejection seat experiences about 80 percent of the total drag forces of the seat plus occupant, at small pitch angles. The percentage falls with increasing pitch angle.
2. Hand-up forces decrease with increasing pitch angle up to 60° pitch angle for the ACES-II ejection seat.
3. Feet-up forces increase with increasing pitch angle up to 60° pitch angle for the ACES-II ejection seat.
4. The difference in drag area between the occupant and seat in the tested configuration would cause a compressive force, thus hindering the separation of the occupant from the seat.

REFERENCES

1. Hawker, F. W. and Euler, A. J., Extended Measurements of Aerodynamic Stability and Limb Dislodgement Forces with the ACES-II Ejection Seat, AMRL-TR-75-15, Wright-Patterson Air Force Base, Ohio 45433, AD 14432, July 1975.
2. Payne, P. R., Hawker, F. W., and Euler, A. J., Stability and Limb Dislodgement Force Measurements with the F-105 and ACES-II Ejection Seats, AMRL-TR-75-8, Wright-Patterson Air Force Base, Ohio 45433, AD 15726, July 1975
3. Payne, P. R., Some Studies Relating to "Limb Flailing" After an Emergency Escape from an Aircraft, AMRL-TR-73-24, Wright-Patterson Air Force Base, Ohio 45433, AD 05699, December 1974.
4. Payne, P. R., On Pushing Back The Frontiers of Flail Injury. Paper Presented at NATO/AGARD Meeting in Toronto, Canada, May 1975.
5. Payne, P. R., USAF Experience of Flail Injury for Noncombat Ejections in the Period 1964-1970, AMRL-TR-72-111, Wright-Patterson Air Force Base, Ohio 45433, AD 921780L, May 1974.