

AD-A031 186

ARMY AVIATION TEST BOARD FORT RUCKER ALA  
PRODUCT IMPROVEMENT TEST OF THE FOREIGN OBJECT SCREEN FOR PARTI--ETC(U)  
JUN 69 J C KEY

F/G 21/5

UNCLASSIFIED

NL

| OF |  
AD  
A031186



END

DATE  
FILMED

11 - 76

AD AU 31186



DEPARTMENT OF THE ARMY  
UNITED STATES ARMY AVIATION TEST BOARD  
FORT RUCKER, ALABAMA 36360

1  
B.S.

STEBCG-TD

JUN 25 1969

SUBJECT: Final Report of Product Improvement Test of the Foreign Object Screen for Particle Separators on UH-1( ) and AH-1G Helicopters, USATECOM Project No. 4-6-0105-02

SEE DISTRIBUTION

11 25 Jun 69

12 5p.

9 Final rept. Jun 68 - Jun 69

DDC  
RECEIVED  
OCT 26 1976  
A

10 James C./Key

1. REFERENCES

a. Letter, AMSAV-EOT, Headquarters, US Army Aviation Materiel Command, 20 May 1968, subject: "Request for Test," with 1st Indorsement, AMSTE-BG, Headquarters, US Army Test and Evaluation Command, 18 June 1968.

b. Interim Report of Product-Improvement Test of Inlet Screen for UH-1( ) and AH-1G Particle Separator, US Army Aviation Test Board, 27 November 1968.

16 USATECOM-4-6-0105-02

2. BACKGROUND

UH-1( ) and AH-1G Helicopters have a particle separator installed that is designed to remove small particles from the engine inlet air. It does not remove, or protect against foreign object damage (FOD) caused by, larger objects such as nuts, bolts, Dzus fasteners, lockwire, etc. Because of the high rate of FOD to engines, the engine manufacturer developed an inlet screen for the separator. At the request of the US Army Aviation Systems Command (USAAVSCOM), the US Army Test and Evaluation Command, on 18 June 1968, directed the US Army Aviation Test Board (USAAVNTBD) to conduct a product-improvement test of the inlet screen (ref 1a). On 27 November 1968, an interim report was submitted to USAAVSCOM (ref 1b).

Approved for public release;  
distribution unlimited

2nd 44

1473  
036 500  
4B F

STEBG-TD

SUBJECT: Final Report of Product Improvement Test of the Foreign Object Screen for Particle Separators on UH-1( ) and AH-1G Helicopters, USATECOM Project No. 4-6-0105-02

### 3. OBJECTIVE

To determine suitability of the test inlet screen to prevent foreign objects from being ingested by T53 engines installed on UH-1( )/AH-1G Helicopters.

### 4. SCOPE AND METHOD

The USAAVNTBD conducted this product-improvement test at Fort Rucker, Alabama, and vicinity during the period June 1968 to June 1969. Both prototype and production (FSN 1560-167-8113) Foreign Object Screens were provided by USAAVSCOM and installed on UH-1B, UH-1H, UH-1M, and AH-1G Helicopters. These aircraft were flown on profiles established for the T53-L-13 product-improvement test (USATECOM Project No. 4-6-0150-05). Adequacy of the installation procedures was determined and man-hour requirements were recorded. The screens were inspected daily for damage. The engine compressors were visually inspected, as required by the other test.

### 5. SUMMARY OF RESULTS

a. Test hours accomplished on the inlet screens were:

<u>Helicopter</u>	<u>Serial No.</u>	<u>Hours</u>	<u>Reason for Removal</u>
UH-1B <sup>1</sup>	63-8659	346.5	Still in service.
UH-1H <sup>2</sup>	66-1093	1,458.5	Still in service.
UH-1H <sup>1</sup>	66-1094	556.4	Bottom right-hand forward corner of screen was torn. Equipment Performance Report KF-1 was submitted.
UH-1H <sup>2</sup>	66-1094	995.5	Still in service.

<sup>1</sup> Prototype model inlet screens.

<sup>2</sup> Production model inlet screens.



STEBG-TD

SUBJECT: Final Report of Product Improvement Test of the Foreign  
Object Screen for Particle Separators on UH-1( ) and  
AH-1G Helicopters, USATECOM Project No. 4-6-0105-02

7. CONCLUSION

The test inlet screen is suitable and desirable for installation on UH-1( )/AH-1G Helicopters to prevent foreign objects from being ingested by T53 engines.


8. RECOMMENDATIONS

a. All UH-1( )/AH-1G Helicopters be retrofitted with the production model Foreign Object Screen, Federal Stock Number 1560-167-8113.

b. Service use of production model screens be monitored to determine whether the frame bending problem reported in paragraph 5a recurs to the extent that product improvement is required.

FOR THE PRESIDENT:

1 Incl  
DD 1473

  
P. V. SCHUMAN  
Captain, AGC  
Adjutant

DISTRIBUTION:

Commanding General 10 copies  
US Army Aviation Systems Command  
ATTN: AMSAV-EOT  
P. O. Box 209, Main Office  
St Louis, Missouri 63166

Commanding General 2 copies  
US Army Test and Evaluation Command  
ATTN: AMSTE-BG  
Aberdeen Proving Ground, Maryland 21005

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION
US Army Aviation Test Board Fort Rucker, Alabama 36360		Unclassified
		2b. GROUP
3. REPORT TITLE		
PRODUCT IMPROVEMENT TEST OF THE FOREIGN OBJECT SCREEN FOR PARTICLE SEPARATORS ON UH-1( ) AND AH-1G HELICOPTERS		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
Final Report, June 1968 - June 1969		
5. AUTHOR(S) (Last name, first name, initial)		
KEY, JAMES C., DAC		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
June 1969	4	2
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
b. PROJECT NO.		
USATECOM Project No. 4-6-0105-02		
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.	Firing Code: 0	
10. AVAILABILITY/LIMITATION NOTICES		
<del>Each transmittal of this document outside the Department of Defense must have prior approval of US Army Aviation Systems Command.</del>		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY
		US Army Aviation Systems Command St. Louis, Missouri 63166
13. ABSTRACT		
<p>The US Army Aviation Test Board tested the Foreign Object Screen for Particle Separators to determine its suitability to prevent foreign objects from being ingested by T53 engines installed on UH-1( )/AH-1G Helicopters. From June 1968 to June 1969 at Fort Rucker, Alabama, five prototype and two production model screens were tested for totals of 3,184 and 2,454 hours, respectively. Two problems--a torn screen and a bent frame--were experienced on the prototype screens; no problems occurred with the production screens. There was no evidence of major foreign object damage to any engine with the inlet screen installed during the entire 5,638 test hours. It was concluded that the test inlet screen is suitable and desirable for installation on UH-1( )/AH-1G Helicopters to prevent foreign objects from being ingested by T53 engines. It was recommended that T53 engines installed on all UH-1( )/AH-1G Helicopters be retrofitted with the production model Foreign Object Screen (FSN 1560-167-8113) and that service use of production model screens be monitored to determine whether the frame bending problem recurs to the extent that product improvement is required.</p>		

DD FORM 1 JAN 64 1473

INCLOSURE

Unclassified

Security Classification

KEY WORDS				
LINK A	LINK B	LINK C	ROLE	WT
Foreign Object Screen				
T53 engines				
UH-1(/AH-1G Helicopters				
Particle Separators				
Foreign object damage				

INSTRUCTIONS

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_"
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_"
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_"

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on the report. Enter last name, first name, middle initial, or initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).