

AD/A035871

ESD ACCEP

DRI Call 86015

Copy No. 1 2

Project Report

ETS-6

L. G. Taff

The Handling and Uses of the SAO Catalog

5 November 1976

Prepared for the Department of the Air Force
under Electronic Systems Division Contract F19628-76-C-0002 by

Lincoln Laboratory

MASSACHUSETTS INSTITUTE OF TECHNOLOGY

LEXINGTON, MASSACHUSETTS



Approved for public release; distribution unlimited.

AD/A035871

The work reported in this document was performed at Lincoln Laboratory, a center for research operated by Massachusetts Institute of Technology, with the support of the Department of the Air Force under Contract F19628-76-C-0002.

This report may be reproduced to satisfy needs of U.S. Government agencies.

The views and conclusions contained in this document are those of the contractor and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the United States Government.

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER

A handwritten signature in dark ink, reading "Raymond L. Loiselle". The signature is written in a cursive style with a large, stylized initial 'R'.

Raymond L. Loiselle, Lt. Col., USAF
Chief, ESD Lincoln Laboratory Project Office

MASSACHUSETTS INSTITUTE OF TECHNOLOGY
LINCOLN LABORATORY

THE HANDLING AND USES OF THE SAO CATALOG

L. G. TAFF

Group 94

PROJECT REPORT ETS-6

5 NOVEMBER 1976

Approved for public release; distribution unlimited.

LEXINGTON

MASSACHUSETTS

ABSTRACT

The complete and rigorous update procedures applied to the 1950.0 epoch SAO Catalog are described. The corrections included are the terms of elliptic aberration, precession, proper motion, and foreshortening (e.g., parallax and radial velocity terms). The uses of the updated catalog are schematically described for the local reduction of artificial satellite positions. Finally, an annotated FORTRAN program is included.

I. INTRODUCTION

This report describes the sequence of computations performed to update the Smithsonian Astrophysical Observatory Catalog (SAO³; hereinafter the SAOC) from epoch 1950.0 to the present. We also schematically describe the use of a current version of the SAOC in reducing artificial satellite positions and photometry. The reader should be familiar with Taff⁴. Also, Taff (in press)⁵ discusses photometric reductions. Finally, the reader should be aware that the errors discussed in § VIII of Taff⁴ are reduced by a factor of two when proper treatment of the e-terms is included.

Sections III and IV detail the update calculations performed on the SAOC and Section V describes the astrometric information contained in the 1975.0 master and subsequent yearly tapes.

II. DESCRIPTION OF THE SAOC

The SAO, in response to the needs of the space age, constructed a non-fundamental, astrometric, compilation catalog with the following goals:

(1) the star density would be at least four stars per square degree, (2) the 1970.0 positions would have a root mean square error of $\leq 1''$, and (3) the catalog would be on the FK4 system. The physical existence of the SAOC and reference to Haramundanis¹ and Scott and Smith² indicate that these goals have been met.

The catalog contains entries for 258,997 stars. For astrometric purposes the most important aspects of the SAOC are its success in meeting the above goals and its availability in machine readable form. For our purposes the most important datum for each star consists of position (α = right ascension, δ = declination) and proper motions (μ = proper motion in right ascension, μ' = proper motion in declination). This information is in a barycentric solar system coordinate system for the equator and equinox of 1950.0. The reader is referred to the Introduction of the SAOC. However, he should be aware that the σ_{1950} column is totally incorrect and although the wrong equations appear on p. xiii for σ_{μ} and $\sigma_{\mu'}$, the correct formulas were used in their computation.

III. ELLIPTIC ABERRATION

The position (e.g., α , δ) of a star, referred to a mean equator and equinox of date, is referred to as a mean position. It differs from the true position (at that time in that coordinate system) by the effects of nutation. However, because the eccentricity of the earth's orbit is small and hand computation laborious, it has been traditional to leave in those observational effects due solely to the ellipticity of the earth's orbit in the just defined mean place. Catalogs contain mean places of stars. Let $[\alpha_0(t'), \delta_0(t')]$ be the just defined mean place at epoch t' as found in a catalog. Then the real (i.e., intrinsic) position $[\alpha(t'), \delta(t')]$ is obtained by setting

$$\alpha(t') = \alpha_0(t') - \Delta\alpha(t'), \quad (1a)$$

$$\delta(t') = \delta_0(t') - \Delta\delta(t'). \quad (1b)$$

The e-term corrections are given by

$$\Delta\alpha(t') = c\Delta C + d\Delta D, \quad (2a)$$

$$\Delta\delta(t') = c'\Delta C + d'\Delta D, \quad (2b)$$

where the Besselian star constants c , d , c' , d' are given by

$$c = \cos\alpha_0(t')\sec\delta_0(t'), \quad d = \sin\alpha_0(t')\sec\delta_0(t'), \quad (3a)$$

$$c' = \tan\epsilon(t')\cos\delta_0(t') - \sin\alpha_0(t')\sin\delta_0(t'),$$

$$d' = \cos\alpha_0(t')\sin\delta_0(t'), \quad (3b)$$

where ϵ is the true obliquity of the ecliptic at $t = t'$. The quantities ΔC and ΔD are computed from ϵ , the constant of aberration $\kappa (= 20''.4958)$, the eccentricity of the earth's orbit e , and the longitude of the earth's perihelion ω . Thus,

$$\Delta C = e(t')\kappa \cos \omega(t') \cos \epsilon(t') \quad (4a)$$

$$\Delta D = e(t')\kappa \sin \omega(t'), \quad (4b)$$

where

$$e = 0.01675104 - 4.18 \times 10^{-5}T - 1.26 \times 10^{-7}T^2, \quad (5a)$$

$$\epsilon = 23^{\circ}27'8''.26 - 46''.845T - 0''.0059T^2 + 0''.00181T^3, \quad (5b)$$

$$\omega = 101^{\circ}13'15''.0 + 6189''.03T + 1''.63T^2 + 0''.012T^3, \quad (5c)$$

and T is the number of tropical centuries elapsed since 1900.0.

From Eqs. (5) it is clear that e , ϵ , and ω vary very slowly and that $e\kappa$ is a small number. Hence, these corrections are generally minute. In fact, it can be shown that if $t' = 1950.0$, $t'' = 1975.0$ then the absolute value of the maximum errors in $\alpha(t'')$ and $\delta(t'')$ due to neglect of the e -terms are $2''.11 \times 10^{-3} \sec^2 \delta(t')$ and $0''.97 \times 10^{-3} \sec \delta(t')$. The errors are linear in $t'' - t'$.

However, as is the case with most approximations used in spherical astronomy, the neglect of the e -terms produces an effect in right ascension that systematically increases with declination. Therefore, since these right ascensions are necessarily of poorer accuracy than those at lower declinations, the first

step in updating the SAOC is to apply Eqs. (1). The second step is discussed below (§ IV). The third step is to add back in $\Delta\alpha(t'')$, $\Delta\delta(t'')$.

IV. PRECESSION AND PROPER MOTION

Using $\alpha(t')$ and $\delta(t')$ [along with $\mu(t')$ and $\mu'(t')$] as input, the power series method of Taff⁴ was then applied from $t' = 1950.0$ to $t'' = 1975.0$. The complete details are in § III of that report. The Appendix contains an annotated listing of a thoroughly tested FORTRAN program to perform all of the computations discussed herein.

While only minor typographical errors have been discovered in Taff⁴, the algebraic reduction which yielded Eqs. (14a, b) is sufficiently complicated that the unsimplified versions are used in the program.

V. THE LINCOLN 1975.0 YEARLY VERSIONS OF THE SAOC

After a complete reduction had been performed to 1975.0 a new SAOC tape was constructed at Lincoln. It contains for epoch 1975, α , δ , μ , μ' , $d\alpha/dt$, $0.5d^2\alpha/dt^2$, $d\delta/dt$, $0.5d^2\delta/dt^2$, $d\mu/dt$, and $d\mu'/dt$. In addition, depending on $\delta(t')$ (relative to $\pm 80^\circ$), either 1950.0 $0.5d^2\alpha/dt^2$, $0.5d^2\delta/dt^2$, $d\mu/dt$, and $d\mu'/dt$ or the same quantities at 1970.0. The tape has been resorted into 10° wide declination bands with right ascension increasing in each band.

For each year the 1975.0 tape is updated (on or about 1 July) to provide positions and proper motions whose epoch is that of nearest Besselian solar year. This update is performed using Eqs. (18, 19) or (20, 21) of Taff⁴.

VI. USES OF THE SAOC

The primary use of the SAOC is in the precise reduction of artificial satellite positions and photometry. For this purpose an interactive graphics display program exists. The operator (or computer) enters the right ascension and declination of interest, the size of the surrounding area to be displayed (up to 5°), and either the star density per square degree (with the brightest stars used first) or a magnitude limit. The program then generates a display of the appropriate star field including differing intensities for the stars. The position of the telescope and the satellite in question are also indicated. As the real time pointing system provides information on telescope motion, it is a simple task to continually update the display, look backward in time, or look forward in time. A local calibration procedure will be used to simultaneously reduce the position and photometry of the satellite.

APPENDIX: LISTING OF FORTRAN PROGRAM

Following this text is a complete listing of the two subroutines used to update the SAOC. In particular the epochs 1950.0, 1975.0, and 1977.0 appear explicitly in the program (e.g., within DO loops #1, #2; above statement #4; the IF statement below statement #5; at statement #6; at statement #14; and below statement #15). Quantities such as R(I), RA, ALP refer to right ascension; D(I), DEC, DEL refer to declination; MU, MUA refer to proper motion in right ascension; MUP, MUD refer to proper motion in declination; DA, EA to $d\alpha/dt$, etc. Trigonometric functions of an angle are usually prefixed, thus CO is the cosine of omega, TD the tangent of declination, etc. With close reference to Eqs. (7-21) of Taff⁴ the reader should have no difficulty following the program.

```

      SUBROUTINE UPDATE(R(1),D(1),MU(1),MUP(1),R(6),D(6),MU(6),MUP(6))
C   RIGOROUS PRECESSION & PROPER MOTION UPDATE/POWER SERIES METHOD
C   INPUT ARE VARIABLES AT INDEX 1, OUTPUT ARE VARIABLES AT INDEX 6
C   PRECISION NEEDED IS 10.**(-9) FOR ALL OPERATIONS
      IMPLICIT DOUBLE PRECISION (A-H,M-Z)
      DOUBLE PRECISION KAP
      INTEGER HK,DEG,MINT,MINA
      DIMENSION R(6),UA(6),UA2(6),U(6),DD(6),D2D(6),MU(6),DMU(6),MUP(6),
      *DMUP(6),M(6),MP(6),N(6),NP(6),TE(2),DECL(2),VELD(2),PHOT(11)
      COMMON /DERIV/UA75,D2A50,D2A75,DU75,D2D50,D2D75,DMU50,DMU75,
      * DMUP50,DMUP75
      COMMON/DAT/PI2,PI,TP1,T,FT,TWT
C   SET UP CONSTANTS
      DATA KAP,CUB,IP,IM/2.0495801,1.02269D-4,,'-','/'
      PI=3.141592653600
      PI2=5.0-1*PI
      TPI=PI+PI
      CRA=PI/4.3204
      CDEC=PI/6.4805
      P112=PI/1.201
      P1180=PI/1.802
      US=1.00/6.01
      TWT=2.01/3.00
      FT=4.00/3.00
      UMAX=8.001*P1180
C   IF PARALLAX AND RADIAL VELOCITY UNKNOWN SET THEM EQUAL TO ZERO
      PAR=0.00
      VR=0.00
C   SET UP PRECESSION CONSTANTS
      DO 1 I=1,6
      T=5.0-1+5.0-2*(1-1)
      M(I)=CRA*(3.0/233/02+T*(1.8630D-1+T*8.0-6))
      MP(I)=CRA*(1.8630D-1+T*1.60-5)
      N(I)=CDEC*(2.00468503-T*(8.533D-1+T*3.7D-4))
1    NP(I)=-CDEC*(8.533D-1+T*7.4D-4)
      MPP=CRA*1.60-5
      NPP=-CDEC*7.4D-4
C   SET UP ELLIPTIC ABERRATION CONSTANTS
      DO 2 I=1,2
      T=5.0-1+2.5D-1*(1-1)
      OME=P1180*(1.0102+US*(1.301+US*(1.501+T*(6.18903D3+T*(1.63D0+T*1.2
      *U-2))))))
      CO=DCOS(OME)
      SO=DSIN(OME)
      EPS=P1180*(2.301+US*(2.701+US*(8.26D0-T*(4.684501+T*(5.90-3-T*1.61
      *U-3))))))
      CE=DCOS(EPS)
      TE(I)=DTAN(EPS)
      ECC=1.675104D-2-T*(4.18D-5+T*1.26D-7)
      VELC(I)=CDEC*KAP*ECC*CO*CE
2    VELD(I)=CDEC*KAP*ECC*SO
C   INPUT IS      RA AND DEC IN RADIAN; MU,MUP IN RAD/CENT; PAR IN SECONDS
C   OF ARC, VR IN KM/SEC
C   DETERMINE DECLINATION RANGE
      L=5
      IF(ABS(U(1)).GT.UMAX) L=1
C   ADJUST RA AND DEC FOR E-TERMS
      SR=DSIN(R(1))
      CR=DCOS(R(1))

```

```

      SU=USIN(U(1))
      CU=UCOS(U(1))
      K(1)=R(1)-(CR*UELC(1)+SR*DELU(1))/CD
      U(1)=U(1)-((TE(1)*CD-SR*SD)*UELC(1)+CR*SD*DELD(1))
      T=5.0-2*L
C INITIALIZE COUNTER
      K=1
C CALCULATE DRA/UT,U2RA/DT**2,U3RA/DT**3,DDEC/UT,D2DEC/UT**2,D3DEC/UT**3
C ,DMU/UT,D2MU/UT**2,DMUP/UT, AND U2MUP/DT**2 AT 1950.0
      4 SR=USIN(R(K))
      CR=UCOS(R(K))
      TU=DTAN(U(K))
      SEC2=1.00+TU*TU
      S2U=USIN(2.00*U(K))
      C2U=UCOS(2.00*U(K))
      PR=M(K)+N(K)*SR*TU
      PU=N(K)*CR
      UA(K)=PR+MU(K)
      UU(K)=PU+MUP(K)
      UPR=MP(K)+NP(K)*SR*TU+N(K)*DA(K)*CR*TU+N(K)*DD(K)*SR*SEC2
      UPU=NP(K)*CR-N(K)*DA(K)*SR
      U2A(K)=5.0-1*(MP(K)+NP(K)*SR*TU+N(K)*(DA(K)+MU(K))*CR*TU+N(K)*(DU(
      *K)+MUP(K))*SR*SEC2+2.00*MU(K)*MUP(K)*TD-2.00*MU(K)*CON*PAR*VR)
      U2U(K)=5.0-1*(NP(K)*CR-N(K)*DA(K)+MU(K))*SR-5.0-1*MU(K)*MU(K)*S2U
      *2.00*MUP(K)*CON*PAR*VR)
      UMU(K)=N(K)*MU(K)*CR*TU+N(K)*MUP(K)*SR*SEC2+2.00*MU(K)*MUP(K)*TD-2
      *0.00*MU(K)*CON*PAR*VR
      UMUP(K)=-N(K)*MU(K)*SR-5.0-1*MU(K)*MU(K)*S2U-2.00*MUP(K)*CON*PAR*V
      *K
      U3A=MPP+NPP*SR*TU+NP(K)*UA(K)*CR*TU+NP(K)*UU(K)*SR*SEC2+NP(K)*(PR+
      *2.00*MU(K))*CR*TU+N(K)*(UPR+2.00*DMU(K))*CR*TU-N(K)*(PR+2.00*MU(K)
      %)*UA(K)*SR*TD+N(K)*(PR+2.00*MU(K))*DD(K)*CR*SEC2+2.00*UMU(K)*MUP(K
      a)*TU+2.00*MU(K)*DMUP(K)*TU+2.00*MU(K)*MUP(K)*UD(K)*SEC2+NP(K)*(PD+
      #2.00*MUP(K))*SR*SEC2+N(K)*(DPU+2.00*DMUP(K))*SR*SEC2+N(K)*(PD+2.00
      $*MUP(K))*UA(K)*CR*SEC2+2.00*N(K)*(PD+2.00*MUP(K))*SR*TD*SEC2*UU(K)
      U3U=MPP*CR-NP(K)*UA(K)*SR-NP(K)*(PR+2.00*DMU(K))*SR-N(K)*(UPR+2.00
      *DMU(K))*SR-N(K)*(PR+2.00*MU(K))*DA(K)*CR-MU(K)*DMU(K)*S2U-MU(K)*M
      %U(K)*DU(K)*C2U
      U2MU=MU(K)*NP(K)*CR*TU+MUP(K)*NP(K)*SR*SEC2+N(K)*(MU(K)*UD(K)+MUP(
      *K)*DA(K))*CR*SEC2+N(K)*(2.00*MUP(K)*DD(K)*SEC2-MU(K)*DA(K))*SR*TU-
      %2.00*SU*SU*MU(K)**3+N(K)*N(K)*MU(K)*(CR*CR*TD*TU-SR*SR*SEC2)+N(K)*
      aN(K)*MUP(K)*SR*CR*TU*SEC2+4.00*N(K)*MU(K)*MUP(K)*CR*TD*TU+N(K)*(2.
      #00*MUP(K)*MUP(K)*SEC2-3.00*MU(K)*MU(K))*SR*TU+4.00*MU(K)*MUP(K)*MU
      $P(K)*TD*TU+2.00*MU(K)*MUP(K)*DD(K)*SEC2
      U2MUP=-MU(K)+NP(K)*SR-N(K)*MU(K)*DA(K)*CR-N(K)*N(K)*MUP(K)*SR*SR*S
      *EC2-N(K)*N(K)*MU(K)*SR*CR*TU-2.00*N(K)*MU(K)*MU(K)*CR*SD*SU-4.00*N
      %(K)*MU(K)*MUP(K)*SR*TD-MU(K)*MU(K)*(DU(K)+2.00*(MUP(K)-PU)*SU*SD)
C OBTAIN ESTIMATES FOR RA,UEC,MU,MUP AT 1950.0+T
      5 RA=P(K)+T*(UA(K)+1*(U2A(K)+T*U3A/6.00))
      UEC=U(K)+T*(DU(K)+T*(U2U(K)+T*U3U/6.00))
      MUA=MU(K)+T*(UMU(K)+5.0-1*T*U2MU)
      MUU=MUP(K)+T*(UMUP(K)+5.0-1*T*U2MUP)
      SR=USIN(RA)
      CR=UCOS(RA)
      TU=DTAN(UEC)
      SEC2=1.00+TU*TU
      S2U=USIN(2.00*UEC)
C IF T=0.25 DONE
      IF(L.EJ.5) GO TO 14
C T=0.05: USING 1955.0,1960.0, ETC. ESTIMATES FOR RA,UEC,MU, AND MUP RE-

```



```

C CALCULATE D2RA/DT**2, D2DEC/DT**2, DMU/DT, AND DMUP/DT
  PR=M(K+1)+N(K+1)*SR*TD
  PU=N(K+1)*CR
  E2A=5.0-1*(MP(K+1)+NP(K+1)*SR*TD+ N(K+1)*(PR+2.00*MUA)*CR*TD+N(K+1)
  )*(PU+2.00*MUD)*SR*SEC2+2.00*MUA*MUD*TD-2.00*MUA*CON*PAR*VR)
  E2U=5.0-1*(NP(K+1)*CR- N(K+1)*(PR+2.00*MUA)*SR-5.0-1*MUA*MUA*S2D-2
  *.00*MUD*CON*PAR*VR)
  UMUA=N(K+1)*MUA*CR*TD+N(K+1)*MUD*SR*SEC2+2.00*MUA*MUD*TD-2.00*MUD*
  *CON*PAR*VR
  UMUD=-N(K+1)*MUA*SR-5.0-1*MUA*MUA*S2D-2.00*MUD*CON*PAR*VR
C GET 1955.0, 1960.0, ETC. RA, DEC, MU, AND MUP
  R(K+1)=R(K)+T*(UA(K)+T*(U2A(K)+TWT*T*(E2A-O2A(K))))
  U(K+1)=U(K)+T*(UD(K)+T*(U2D(K)+TWT*T*(E2U-O2U(K))))
  MU(K+1)=MU(K)+T*(DMU(K)+1.01*T*(OMUA-UMU(K)))
  MUP(K+1)=MUP(K)+T*(DMUP(K)+1.01*T*(OMUD-DMUP(K)))
C INCREMENT COUNTER
  K=K+1
C DONE?
  6 IF(K.EQ.6) GO TO 7
C NOT DONE, REPEAT UPDATE CYCLE
  GO TO 4
C PRECESSION AND PROPER MOTION UPDATE IS NOW DONE, UNDO E-TERMS
  7 SR=DSIN(R(6))
  CR=DCOS(R(6))
  SU=DSIN(U(6))
  CU=DCOS(U(6))
  R(6)=R(6)+(CR*UEL(2)+SR*OELU(2))/CO
  U(6)=U(6)+((TE(2)*CU-SR*SU)*UEL(2)+CR*SD*UEL(2))
C CALCULATE D2RA/DT**2, D2DEC/DT**2, DMU/DT, AND DMUP/DT AT 1975.0 FOR USE
  C IN YEARLY UPDATE PROGRAM (TOYR)
  SR=DSIN(R(K))
  CR=DCOS(R(K))
  TU=DTAN(U(K))
  SEC2=1.00+TU*TU
  S2U=DSIN(2.00*U(K))
  PR=M(K)+N(K)*SR*TD
  PU=N(K)*CR
  UA(K)=PR+MU(K)
  UD(K)=PU+MUP(K)
  U2A(K)=5.0-1*(MP(K)+NP(K)*SR*TD+N(K)*(OA(K)+MU(K))*CR*TD+N(K)*(OU(
  *K)+MUP(K))*SR*SEC2+2.00*MU(K)*MUP(K)*TD-2.00*MU(K)*CON*PAR*VR)
  U2U(K)=5.0-1*(NP(K)*CR-N(K)*(OA(K)+MU(K))*SR-5.0-1*MU(K)*MU(K)*S2D
  *-2.00*MUP(K)*CON*PAR*VR)
  UMU(K)=N(K)*MU(K)*CR*TD+N(K)*MUP(K)*SR*SEC2+2.00*MU(K)*MUP(K)*TD-2
  *.00*MU(K)*CON*PAR*VR
  UMUP(K)=-N(K)*MU(K)*SR-5.0-1*MU(K)*MU(K)*S2D-2.00*MUP(K)*CON*PAR*V
  *R
C CHECK FOR OVER THE POLES OR AROUND THE VERNAL EQUINOX
  IF(DABS(U(6)).LT.PI/2) GO TO 11
  R(6)=R(6)+PI
  IF(D(6)) 8,8,9
  8 U(6)=-U(6)-PI
  GO TO 10
  9 U(6)=PI-U(6)
  10 IF(R(6).GE.TPI) R(6)=R(6)-TPI
  IF(R(6).LT.0.00) R(6)=R(6)+TPI
C OUTPUT
  11 RA=R(6)/PI12
  HR=RA
  RA=6.01*(RA-HR)

```

```

MINT=RA
RA=6.01*(RA-MINT)
UEC=UABS(U(6))/PI180
UEG=UEC
UEC=6.01*(UEC-UEG)
MINA=UEC
UEC=6.01*(UEC-MINA)
MUA=MU(6)/CRA
MUD=MUP(6)/CUEC
IS=IP
IF(U(6).LT.0.00) IS=IM
WRITE(3,12) HR,MINT,RA,MUA,IS,DEG,MINA,DEC,MUD
12 FORMAT(1X,2I3,F8.3,2X,F8.3,5X,A1,I2,I3,F7.2,2X,F7.2)
GO TO 15
C USING 1975.0 ESTIMATES FOR RA,DEC,MU, AND MUP RECALCULATE U2RA/DT**2,
C U2UEC/DT**2,UMU/DT, AND UMUP/DT
14 K=5
PR=M(K+1)+N(K+1)*SR*TD
PU=N(K+1)*CR
E2A=5.0-1*(NP(K+1)+NP(K+1)*SR*TD+ N(K+1)*(PR+2.00*MUA)*CR*TD+N(K+1)
*)*(PU+2.00*MUD)*SR*SEC2+2.00*MUA*MUD*TD-2.00*MUA*CON*PAR*VR)
E2U=5.0-1*(NP(K+1)*CR- N(K+1)*(PR+2.00*MUA)*SR-5.0-1*MUA*MUA*S2D-2
*.00*MUD*CON*PAR*VR)
UMUA=N(K+1)*MUA*CR*TD+N(K+1)*MUD*SR*SEC2+2.00*MUA*MUD*TD-2.00*MUD*
*CON*PAR*VR
UMUD=-N(K+1)*MUA*SR-5.0-1*MUA*MUA*S2D-2.00*MUD*CON*PAR*VR
C GET 1975.0 RA,UEC,MU, AND MUP
K(6)=K(1)+1*(UA(1)+1*(U2A(1)+FT*T*(E2A-D2A(1))))
U(6)=U(1)+T*(UD(1)+T*(D2U(1)+FT*T*(E2U-D2U(1))))
MU(6)=MU(1)+T*(UMU(1)+2.00*T*(DMUA-DMU(1)))
MUP(6)=MUP(1)+T*(UMUP(1)+2.00*T*(DMUD-DMUP(1)))
C SET COUNTER TO END
A=6
GO TO 6
15 CONTINUE
C TOYR SECTION
C HERE UPDATES 1975.0 TO 1977.0
T=2.0-2
UA75=UA(6)
U2A75=U2A(6)
UD75=UD(6)
U2U75=U2U(6)
UMU75=UMU(6)
UMUP75=UMUP(6)
L=6-L
U2A50=U2A(L)
U2U50=U2U(L)
UMU50=UMU(L)
UMUP50=UMUP(L)
CALL TOYR(R(6),U(6),MU(6),MUP(6),RA,DEC,MUA,MUD,L)
C OUTPUT
ALP=RA/PI12
HR=ALP
ALP=6.01*(ALP-HR)
MINT=ALP
ALP=6.01*(ALP-MINT)
UEL=UABS(UEC)/PI180
UEG=UEL
DEL=6.01*(UEL-UEG)
MINA=UEL

```

```

      DEL=6.01*(DEL-MINA)
      MUA=MUA/CRA
      MUD=MUD/CUEC
      IS=IP
      IF(DEC.LT.0.00) IS=IM
      WRITE(3,12) HR,MINT,ALP,MUA,IS,DEG,MINA,DEL,MUD
16 CONTINUE
      CALL EXIT
      END

```

```

      SUBROUTINE TOYR(ALP,DEL,MUA,MUD,RA,DEC,MU,MUP,L)
      IMPLICIT DOUBLE PRECISION (A-H,M-Z)
      COMMON /DERIV/UA75,U2A50,U2A75,U075,U2D50,U2D75,DMU50,DMU75,
      * DMUP50,DMUP75
      COMMON/DAT/PI2,PI,TPI,T,FI,TWT
C INPUT IS ALP,DEL IN RAD; MUA,MUD IN RAD/CENT; T IN CENT
C OUTPUT IS RA,DEC,MU,MUP IN SAME UNITS
C L IS HIGH DECLINATION FLAG
      IF(L.EQ.5) GO TO 1
      RA=ALP+T*(UA75+T*(U2A75+T*T*(U2A75-U2A50)))
      DEC=DEL+T*(U075+T*(U2D75+T*T*(U2D75-U2D50)))
      MU=MUA+T*(DMU75+2.*T*(DMU75-DMU50))
      MUP=MUD+T*(DMUP75+2.*T*(DMUP75-DMUP50))
      GO TO 2
1  RA=ALP+T*(UA75+T*(U2A75+TWT*T*(U2A75-U2A50)))
   DEC=DEL+T*(U075+T*(U2D75+TWT*T*(U2D75-U2D50)))
   MU=MUA+T*(DMU75+10.*T*(DMU75-DMU50))
   MUP=MUD+T*(DMUP75+10.*T*(DMUP75-DMUP50))
C CHECK FOR OVER THE POLES OR AROUND THE VERNAL EQUINOX
2  IF(ABS(DEC).LT.PI2) GO TO 5
   RA=RA+PI
   IF(DEC) 3,3,4
3  DEC=-DEC-PI
   GO TO 5
4  DEC=PI-DEC
5  IF(RA.GE.TPI) RA=RA-TPI
   IF(RA.LT.0.D0) RA=RA+TPI
   RETURN
   END

```

REFERENCES

1. K. Haramundanis, *Astron. J.* 72, 558 (1967).
2. F. P. Scott and C. Smith, "Conference on Photographic Astrometric Technique," H. Eichorn, Editor, NASA CR-1825, Washington, D.C. (1971), p. 167.
3. Smithsonian Astrophysical Observatory (Staff of), Star Catalog (Publications of the Smithsonian Institute No. 4562, Washington, D.C., 1966).
4. L. G. Taff, "The Handling of Star Catalogs: The Transformations of Positions and Proper Motions," Technical Note 1976-12, Lincoln Laboratory, M.I.T. (17 February 1976).
5. L. G. Taff, "Photometric Reductions: Theory and Practice," Technical Note 1976-35, Lincoln Laboratory, M.I.T. (17 December 1976).

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ESD-TR-76-318	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) The Handling and Uses of the SAO Catalog		5. TYPE OF REPORT & PERIOD COVERED Project Report
		6. PERFORMING ORG. REPORT NUMBER Project Report ETS-6
7. AUTHOR(s) Laurence G. Taff		8. CONTRACT OR GRANT NUMBER(s) F19628-76-C-0002
9. PERFORMING ORGANIZATION NAME AND ADDRESS Lincoln Laboratory, M.I.T. P. O. Box 73 Lexington, MA 02173		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Element No. 63428 F Project No. 2128
11. CONTROLLING OFFICE NAME AND ADDRESS Air Force Systems Command, USAF Andrews AFB Washington, DC 20331		12. REPORT DATE 5 November 1976
		13. NUMBER OF PAGES 22
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Electronic Systems Division Hanscom AFB Bedford, MA 01731		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES None		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) artificial satellites space object identification satellite observation		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The complete and rigorous update procedures applied to the 1950.0 epoch SAO Catalog are described. The corrections included are the terms of elliptic aberration, precession, proper motion, and foreshortening (e.g., parallax and radial velocity terms). The uses of the updated catalog are schematically described for the local reduction of artificial satellite positions. Finally, an annotated FORTRAN program is included.		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

