

AD-A037 936


ARMY ELECTRONICS COMMAND WHITE SANDS MISSILE RANGE N--ETC F/G 4/2  
03702A HONEST JOHN MISSILE NUMBER 1548, ROUND NUMBER 654 AML (1--ETC(U)  
NOV 76

UNCLASSIFIED

DR-931

NL

1 of 1  
ADA037936



END

DATE  
FILMED  
4-77

AD A 037936

12  
B.S.

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

DR-931  
November 1976

AD

METEOROLOGICAL DATA REPORT

03702A HONEST JOHN  
MISSILE NO. 1548, ROUND NO. 654 AML  
(15 November 1976)

BY

WSMR METEOROLOGICAL TEAM

DDC  
RECEIVED  
APR 8 1977  
RECEIVED  
A

ATMOSPHERIC SCIENCES LABORATORY  
WHITE SANDS MISSILE RANGE, NEW MEXICO

AD No.  
DDC FILE COPY

ECOM

UNITED STATES ARMY ELECTRONICS COMMAND

**DISPOSITION INSTRUCTIONS**

Destroy this report when it is no longer needed. Do not return to the originator.

**DISCLAIMER**

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER DR-931	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) 03702A HONEST JOHN MISSILE NO. 1548, ROUND NO. 654 AML (15 November 1976). <i>Number</i>		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) WSMR Meteorological <del>Team</del> data rept.		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS		8. CONTRACT OR GRANT NUMBER(s) DA Task 1T665702D127-02
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Electronics Command Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1702
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) US Army Electronics Command Ft. Monmouth, New Jersey		12. REPORT DATE November 1976
		13. NUMBER OF PAGES 19
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  1. Ballistics 2. Meteorology 3. Wind		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  Meteorological data gathered for the launching of 03702A Honest John, Missile Number 1548, Round Number 654 AML, are presented in tabular form.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

400 844

LB

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

REPORT DOCUMENTATION PAGE	
1. AGENCY USE ONLY (Leave blank)	
2. GOVERNMENT ACQUISITION REPORT NUMBER	
3. REPORT NUMBER	
4. TITLE AND SUBTITLE	
5. AUTHOR	
6. PERFORMING ORGANIZATION REPORT NUMBER	
7. AUTHOR(S)	
8. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	
9. PERFORMING ORGANIZATION REPORT NUMBER	
10. PROGRAM ELEMENT, PROJECT, TASK NUMBER AND REPORT NUMBER	
11. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
12. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
13. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
14. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
15. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
16. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
17. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
18. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
19. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
20. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
21. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
22. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
23. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
24. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
25. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
26. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
27. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
28. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
29. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
30. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
31. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
32. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
33. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
34. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
35. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
36. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
37. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
38. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
39. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
40. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
41. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
42. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
43. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
44. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
45. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
46. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
47. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
48. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
49. DISTRIBUTION STATEMENT (See Instructions for Reporting)	
50. DISTRIBUTION STATEMENT (See Instructions for Reporting)	

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

CONTENTS

	PAGE
INTRODUCTION -----	1
DISCUSSION -----	1
TABLES	
I. Surface Observations Taken at CP-7 -----	1
II. Surface Observations Taken at Stallion -----	2
III. Anemometer-Measured Wind Speed and Direction, Pole No. 1 -----	3
IV. Pilot-Balloon-Measured Wind Data, Release No. 1 at 1330 MST -----	5
V. Pilot-Balloon-Measured Wind Data, Release No. 1 at 1359 MST -----	6
VI. Pilot-Balloon-Measured Wind Data, Release No. 1 at 1415 MST -----	7
VII. Stallion Significant Level Data (Release Time: 1400 MST) -----	8
VIII. Stallion Upper Air Data (Release Time: 1400 MST) -----	9
IX. Stallion Mandatory Levels (Release Time: 1400 MST) -----	12

## INTRODUCTION

03702A Honest John, Missile Number 1548, Round Number 654 AML, was launched from CP-7, White Sands Missile Range (WSMR), New Mexico, at 1400 HRS MST, 15 November 1976. The scheduled launch time was 1400 HRS MST.

## DISCUSSION

Meteorological data were recorded and reduced by the WSMR Meteorological Team, Atmospheric Sciences Laboratory (ASL), WSMR, New Mexico. The data are presented in the following tabulations.

ELEVATION	4,694.0	FEET/MSL
PRESSURE	855.5	MBS
TEMPERATURE	11.6	°C
RELATIVE HUMIDITY	38	%
DEW POINT	-2.2	°C
DENSITY	1,042.0	GM/M <sup>3</sup>
WIND SPEED	08	MPH
WIND DIRECTION	160	DEGREES
CLOUD COVER	6	Cu

TABLE I. SURFACE OBSERVATIONS TAKEN AT CP-7,  
1400 HRS MST/15 NOVEMBER 1976.

ELEVATION	4,941.24	FEET/MSL
PRESSURE	847.7	MBS
TEMPERATURE	11.2	°C
RELATIVE HUMIDITY	39	%
DEW POINT	-2.1	°C
DENSITY	1,034.0	GM/M <sup>3</sup>
WIND SPEED	013	MPH
WIND DIRECTION	140	DEGREES
CLOUD COVER	.2	Cu

TABLE II. SURFACE OBSERVATIONS TAKEN AT STALLION SITE,  
1400 HRS MST/15 NOVEMBER 1976.

T-TIME (MIN-SEC)	SPEED (MPH)	DIR DEG	T-TIME (MIN-SEC)	SPEED (MPH)	DIR DEG	T-TIME (MIN-SEC)	SPEED (MPH)	DIR DEG
-5.00	12.0	120	-0 9.5	17.0	151	-0 0.50	11.0	151
-4.30	12.0	112	-0 9.0		150	-0 0.25	14.0	151
-4.00	14.0	123	-0 8.5			0 0.00	14.0	151
-3.30	15.0	112	-0 8.0			+0 0.25	15.0	152
-3.00	17.0	108	-0 7.5	17.0		+0 0.50		152
-2.30	16.0	117	-0 7.0	16.0		+0 0.75		152
-2.00	17.0	099	-0 6.5	16.0	150	+0 1.00		152
-1.45	12.0	132	-0 6.0	16.0	153	+0 1.25		153
-1.30	14.0	117	-0 5.5	16.0	154	+0 1.50		153
-1.15	14.0	144	-0 5.0	15.0	153	+0 1.75		153
-0.60	13.0	143	-0 4.5	15.0	151	+0 2.00		153
-0.55	15.0	155	-0 4.0	11.0	152	+0 2.25		155
-0.50	12.0	150	-0 3.5	10.0	153	+0 2.50		
-0.45	17.0	163	-0 3.0	9.0	155	+0 2.75		
-0.40	16.0	153	-0 2.5	8.0		+0 3.00		
-0.35	16.0	156	-0 2.0	7.0		+0 3.25		
-0.30	18.0	156	-0 1.75	7.0		+0 3.50		
-0.25	18.0	154	-0 1.50	7.0		+0 3.75		
-2.20	18.0	158	-0 1.25	8.0		+0 4.00	15.0	
-0.15	17.0	153	-0 1.00	10.0	155	+0 4.25	16.0	
-0.10	17.0	155	-0 0.75	10.0	151	+0 4.50	16.0	155

TABLE III. ANEMOMETER-MEASURED WIND SPEED AND DIRECTION, POLE NO. 1  
03702A HONEST JOHN, MISSILE NO. 1548, ROUND NO. 654 AML  
LAUNCHED FROM CP-7, 1400 MST/15 NOVEMBER 1976

WSTM COORDINATES: X = 406,477 Y = 693,532

NOTE: WIND DIRECTION DATA ARE REFERENCED TO THE FIRING AZIMUTH 168.5°.

T-TIME (MIN-SEC)	SPEED (MPH)	DIR DEG	T-TIME (MIN-SEC)	SPEED (MPH)	DIR DEG	T-TIME (MIN-SEC)	SPEED (MPH)	DIR DEG
+0 4.75	16.0	155	+0 10.00	15.0	153	+0 20.50	20.0	150
+0 5.00		153	+0 10.50	15.0	155	+0 21.00	20.0	153
+0 5.25		152	+0 11.00	16.0	155	+0 21.50	19.0	153
+0 5.50		152	+0 11.50	16.0	155	+0 22.00		151
+0 5.75		152	+0 12.00	17.0	156	+0 22.50		152
+0 6.00		152	+0 12.50	17.0	154	+0 23.00		148
+0 6.25		153	+0 13.00	18.0	153	+0 23.50	19.0	142
+0 6.50	16.0	153	+0 13.50	19.0	152	+0 24.00	20.0	141
+0 6.75	15.0	155	+0 14.00	20.0	152	+0 24.50		146
+0 7.00			+0 14.50		153	+0 25.00		147
+0 7.25			+0 15.00		154	+0 25.50		147
+0 7.50			+0 15.50		153	+0 26.00		147
+0 7.75			+0 16.00		151	+0 26.50		148
+0 8.00			+0 16.50		151	+0 27.00		
+0 8.25			+0 17.00		151	+0 27.50		
+0 8.50			+0 17.50		154	+0 28.00		
+0 8.75			+0 18.00		156	+0 28.50	20.0	
+0 9.00		155	+0 18.50		158	+0 29.00	19.0	148
+0 9.25		154	+0 19.00		156	+0 29.50	19.0	146
+0 9.50		154	+0 19.50		150	+0 30.00	19.0	146
+0 9.75	15.0	152	+0 20.00	20.0	147			

TABLE III. (CONT)

NOTE: WIND DIRECTION DATA ARE REFERENCED TO THE FIRING AZIMUTH 168.5°.

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (KTS)
SUR	151.5	12.0
500	161.5	7.0
1000	183.5	6.0
1500	243.5	10.0
2000	182.5	14.0
2500	198.5	11.5
3000	193.5	12.0
3500	207.5	13.0
4000	215.5	8.5
4500	218.5	10.5
5000	225.5	12.0
5500	241.5	12.0
6000	234.5	12.0
6500	231.5	14.0
7000	231.5	16.0
7500	233.5	15.0
8000	232.5	12.5

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA, RELEASE NO. 1  
RELEASED FROM CP-17, AT 1330 MST/15 NOVEMBER 1976  
03702A HONEST JOHN, MISSILE NO. 1548, ROUND NO. 654 AML

PIBAL RELEASE POINT WSTM COORDINATES:

X = 413,576.24      Y = 665,015.33      Z = 4,746.53

APPROXIMATELY: 7 1/2 MILES SOUTH OF LAUNCHER.

NOTE: WIND DIRECTION DATA ARE REFERENCED TO THE FIRING AZIMUTH 168.5°.

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
SUR	140	13.0
100	147	
200	153	
300	160	
400	167	13.0
500	174	10.0
600	180	10.0
700	187	10.0
800	183	13.0
900	176	
1000	178	
1100	180	
1200	182	13.0
1300	183	14.0
1400	185	14.0
1500	186	14.0

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
1600	187	15.0
1700	188	16.0
1800	189	16.0
1900	191	16.0
2000	195	15.0
2100	199	15.0
2200	202	14.0
2300	205	14.0
2400	208	14.0
2500	211	14.0
2600	214	13.0
2700	217	12.0
2800	220	12.0
2900	220	13.0
3000	218	13.0

TABLE V. PILOT-BALLOON-MEASURED WIND DATA, RELEASE NO. 1  
RELEASED FROM CP-7, AT 1359 MST/15 NOVEMBER 1976  
03702A HONEST JOHN, MISSILE NO. 1548, ROUND NO. 654 AML

PIBAL RELEASE POINT WSTM COORDINATES:

X = 406,122.94    Y = 693,918.11    Z = 4,844.64

APPROXIMATELY: 100 YARDS NORTHEAST OF LAUNCHER.

NOTE: WIND DIRECTION DATA ARE REFERENCED TO THE FIRING AZIMUTH 168.5°.

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
SUR	160	8.0
500	140	15.0
1000	155	13.0
1500	160	16.0
2000	170	11.0
2500	180	13.0
3000	190	16.0
3500	210	18.0
4000	220	19.0
4500	230	20.0
5000	220	17.0
5500	200	16.0
6000	210	15.0

TABLE VI. PILOT-BALLOON-MEASURED WIND DATA, RELEASE NO. 1  
 RELEASED FROM AFSWC, AT 1415 MST/15 NOVEMBER 1976  
 03702A HONEST JOHN, MISSILE NO. 1548, ROUND NO. 654 AML

PIBAL RELEASE POINT WSTM COORDINATES:

X = 418,568.33      Y = 644,753.98      Z = 4,701.76

APPROXIMATELY: 10 MILES SOUTH SOUTHEAST OF LAUNCHER.

NOTE: WIND DIRECTION DATA ARE REFERENCED TO THE FIRING AZIMUTH 168.5°.

WSTM SITE COORDINATES  
 403783.00 FEET E  
 701402.00 FEET N

SIGNIFICANT LEVEL DATA  
 3200040271  
 STATION

STATION ALTITUDE 4040.00 FEET MSL  
 15 NOV. 75 1400 HRS MST  
 ASCENSION NC. 271

TABLE VII

PRESSURE MILLIBARS	GEOMETRIC ALTITUDE MSL FEET	TEMPERATURE		REL. HUM. PERCENT
		AIR DEGREES	DEWPOINT CENTIGRADE	
947.4	4940.0	11.2	-1.5	41.0
875.0	5342.1	8.0	-2.1	44.0
783.8	7047.4	3.2	-4.3	58.0
700.0	10010.1	-5.1	-7.4	84.0
588.6	10434.2	-5.3	-8.5	78.0
542.8	12196.7	-9.5	-15.8	60.0
600.0	13022.4	-14.3	-20.0	62.0
587.2	14467.8	-14.8	-31.2	23.0
558.2	15726.4	-15.3	-25.3	16.0
500.0	18475.2	-21.9	-40.8	10.0
400.0	23551.4	-24.3	-48.5	21.0
300.0	30137.3	-46.9		
275.0	36356.4	-52.9		

BEST AVAILABLE COPY

UPPER AIR DATA  
 3200040271  
 STATION  
 TABLE VIII

WSTM SITE COORDINATES  
 402783.00 FEET E  
 701403.00 FEET N

STATION ALTITUDE 4940.00 FEET MSL  
 15 NCV. 7F  
 ASCENSION NO. 771  
 1400 HRS MST

GEO METRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
4940.0	847.4	11.2	-1.5	41.0	1075.6	657.7	230.0	8.5	1.000256
5000.0	845.5	10.8	-1.8	41.4	1074.9	657.2	330.6	9.0	1.000256
5500.0	820.7	7.9	-3.2	45.3	1028.6	653.9	335.5	9.4	1.000252
6700.0	814.8	6.4	-3.4	49.4	1013.2	652.1	339.9	10.0	1.000249
6500.0	799.8	4.9	-3.8	53.5	1000.0	650.3	343.8	10.5	1.000245
7000.0	785.1	3.3	-4.2	57.6	997.0	648.5	347.3	11.1	1.000242
7500.0	770.3	1.6	-4.6	62.0	977.4	646.8	3.6	10.4	1.000239
8000.0	755.7	.5	-5.0	65.4	960.0	645.2	21.7	10.4	1.000235
8500.0	741.5	-.9	-5.5	70.8	946.7	643.5	27.5	10.5	1.000232
9000.0	727.5	-2.3	-6.1	75.1	937.7	641.8	51.0	12.1	1.000228
9500.0	713.7	-3.7	-6.7	79.5	920.9	640.2	55.8	12.0	1.000224
10000.0	700.3	-5.1	-7.4	83.9	908.3	638.5	60.4	11.8	1.000221
10500.0	686.8	-6.6	-8.0	88.2	892.3	636.0	52.3	12.6	1.000215
11000.0	673.6	-8.1	-8.8	92.5	879.1	636.5	41.5	14.2	1.000210
11500.0	660.5	-9.6	-10.8	97.1	866.2	635.0	30.6	15.1	1.000205
12000.0	647.8	-11.1	-12.0	101.5	853.4	633.5	18.3	15.7	1.000200
12500.0	635.1	-12.6	-14.9	104.4	841.0	631.9	10.5	16.1	1.000197
13000.0	622.5	-14.1	-16.5	108.9	828.9	630.2	6.3	15.9	1.000193
13500.0	610.4	-15.6	-17.7	113.5	817.0	628.5	6.7	16.4	1.000190
14000.0	598.3	-17.1	-18.9	118.0	804.9	626.9	9.7	17.4	1.000186
14500.0	586.4	-18.6	-21.1	122.8	790.8	626.3	12.1	17.5	1.000179
15000.0	574.8	-20.1	-21.3	127.8	775.5	626.0	14.4	17.3	1.000175
15500.0	563.3	-21.6	-22.8	133.0	760.6	625.7	18.4	17.2	1.000171
16000.0	552.0	-23.1	-24.5	138.5	747.0	624.8	22.6	17.2	1.000168
16500.0	540.9	-24.6	-26.9	144.0	736.0	623.3	28.9	17.9	1.000165
17000.0	529.9	-26.1	-30.0	150.0	724.0	621.8	33.6	18.6	1.000163
17500.0	519.2	-27.6	-32.8	156.0	713.4	620.3	30.8	18.2	1.000160
18000.0	508.8	-29.1	-34.5	162.0	702.4	618.8	27.4	17.6	1.000158
18500.0	499.4	-30.6	-38.9	168.0	691.5	617.3	21.3	17.5	1.000155
19000.0	488.0	-32.1	-40.0	174.0	680.2	615.9	16.6	17.5	1.000152
19500.0	477.0	-33.6	-41.6	180.0	668.2	614.5	16.6	17.5	1.000152

BEST AVAILABLE COPY

# BEST AVAILABLE COPY

UPPER AIR DATA  
 STATION ALTITUDE 4940.00 FEET MSL  
 15 NOV. 76  
 ASCENSION NC. 271  
 3200040271  
 STALLION  
 WSTM SITE COORDINATES  
 403783.00 FEET E  
 701402.00 FEET N

TABLE VIII (CONT)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNKTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES(TN)	SPEED KNKTS	
19500.0	477.7	-24.4	17.0	669.1	614.4	17.3	19.6	1.000150
20000.0	467.7	-25.6	17.5	658.2	613.0	18.6	21.2	1.000147
20500.0	457.9	-26.8	18.0	647.4	611.5	21.9	22.4	1.000145
21000.0	448.3	-28.0	18.4	636.5	610.0	24.0	23.7	1.000143
21500.0	438.9	-29.1	18.9	626.6	608.6	23.9	24.7	1.000140
22000.0	429.7	-30.3	19.4	616.4	607.1	21.7	25.8	1.000138
22500.0	420.7	-31.6	19.9	606.4	605.6	17.9	27.0	1.000136
23000.0	411.9	-32.7	20.3	596.6	604.2	17.3	27.2	1.000133
23500.0	403.3	-33.8	20.8	587.0	602.7	17.7	26.9	1.000131
24000.0	394.5	-34.9	20.0**	576.8	601.3	19.4	27.4	1.000129
24500.0	385.8	-35.9	18.4**	566.4	600.1	21.0	28.2	1.000127
25000.0	377.3	-36.9	16.7**	556.2	598.9	22.2	30.9	1.000124
25500.0	369.0	-37.8	15.1**	546.2	597.6	23.1	33.4	1.000122
26000.0	360.8	-38.8	13.5**	536.4	596.4	23.5	36.0	1.000120
26500.0	352.9	-39.8	11.8**	526.8	595.1	23.7	38.4	1.000117
27000.0	345.1	-40.8	10.2**	517.3	593.9	23.6	40.0	1.000115
27500.0	337.5	-41.7	8.6**	508.0	592.6	23.2	41.5	1.000113
28000.0	330.0	-42.7	7.0**	499.9	591.4	22.5	42.5	1.000111
28500.0	322.7	-43.7	5.3**	490.0	590.1	22.1	43.5	1.000109
29000.0	315.6	-44.7	3.7**	481.2	588.9	21.9	44.4	1.000107
29500.0	308.7	-45.7	2.1**	472.6	587.6	21.1	43.7	1.000105
30000.0	301.8	-46.6	.4**	464.2	586.3	19.7	41.4	1.000103
30500.0	295.0	-47.3		455.0	585.4	17.5	38.7	1.000101
31000.0	288.2	-47.9		445.7	584.7	14.4	35.6	1.000099
31500.0	281.6	-48.5		436.6	584.0	14.6	36.4	1.000097
32000.0	275.1	-49.0		427.7	583.2	14.9	37.2	1.000095
32500.0	268.8	-49.6		418.9	582.5	15.2	37.8	1.000093
33000.0	262.6	-50.2		410.4	581.7	15.1	34.0	1.000091
33500.0	256.6	-50.8		402.0	581.0	14.4	30.5	1.000089
34000.0	250.7	-51.3		393.8	580.2	12.1	27.5	1.000088

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 4994.00 FEET MSL  
 15 NOV. 76 1000 HRS MST  
 ASCENSION NC. 271

UPPER AIR DATA  
 3200040271  
 STATION

WSTM SITE COORDINATES  
 403783.00 FEET E  
 701403.00 FEET N

TABLE VIII (CONT)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DIRECTION DEGREES(TN)	WIND SPEED KNOTS	INDEX OF REFRACTION
34500.0	205.0	-51.0		785.7	579.5			1.000086
35000.0	220.7	-52.5		777.8	576.7			1.000084

STATION ALTITUDE 4900.00 FEET MSL  
 15 NOV. 76 1400 HRS MST  
 ASCENSION NO. 271

MANDATORY LEVELS  
 3200040271  
 STATION  
 TABLE IX

WSTM SITE COORDINATES  
 403783.00 FEET E  
 701403.00 FEET N

PRESSURE MILLIBARS	GEOPOTENTIAL FEET	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	WIND DATA	
				DIRECTION DEGREES (T)	SPEED KNOTS
800.0	6494.	4.5	53.	343.8	10.5
750.0	8207.	-0.0	68.	29.5	10.5
700.0	10004.	-5.1	84.	60.5	11.8
650.0	11905.	-8.8	83.	20.3	15.5
600.0	13020.	-14.3	81.	5.3	17.3
550.0	16078.	-16.2	16.	23.8	17.3
500.0	18906.	-21.9	16.	22.3	17.6
450.0	20921.	-27.8	18.	24.0	23.6
400.0	23661.	-34.2	21.	18.3	27.0
350.0	26689.	-40.1	11.**	23.6	39.1
300.0	30091.	-46.9		19.3	40.8
250.0	34015.	-51.4		11.8	27.1

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.