

AD-A039 148


GEORGIA INST OF TECH ATLANTA SCHOOL OF ENGINEERING S--ETC F/G 20/11  
THE EFFECT OF INITIAL IMPERFECTIONS ON OPTIMAL STIFFENED CYLIND--ETC(U)  
FEB 77 G J SIMITSES, I SHEINMAN AF-AFOSR-2655-74

UNCLASSIFIED

AFOSR-TR-77-0639

NL

1 of 2  
ADA  
039148



AFOSR - TR - 77 - 0639

AFOSR-TR-77-

ADA 039148

**THE EFFECT OF INITIAL IMPERFECTIONS ON  
OPTIMAL STIFFENED CYLINDERS UNDER AXIAL COMPRESSION**

**George J. Simitzes  
and  
Izhak Sheinman**



**School of Engineering Science and Mechanics  
Georgia Institute of Technology  
Atlanta, Georgia 30332**

**February 1977**

**DDC  
RECEIVED  
MAY 10 1977  
D**

**DDC FILE COPY**

Approved for public release; distribution unlimited.

Qualified requestors may obtain additional copies from the Defense Documentation Center, all others should apply to the National Technical Information Service.

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)  
NOTICE OF TRANSMITTAL TO DDC  
This technical report has been reviewed and is approved for public release IAW AFR 190-12 (7b).  
Distribution is unlimited.  
A. D. BLOSE  
Technical Information Officer



THE EFFECT OF INITIAL IMPERFECTIONS ON  
OPTIMAL STIFFENED CYLINDERS UNDER AXIAL COMPRESSION\*

by

George J. Simitses<sup>+</sup> and Izhak Sheinman<sup>++</sup>

\*This work was supported by the United States Air Force Office of Scientific Research under Grant AFOSR-74-2655.

<sup>+</sup>Professor, School of Engineering Science and Mechanics, Georgia Institute of Technology.

<sup>++</sup>Postdoctoral Fellow, School of Engineering Science and Mechanics, Georgia Institute of Technology.

Qualified requestors may obtain additional copies from the Defense Documentation Center, all others should apply to the National Technical Information Service.

Conditions of Reproduction

Reproduction, translation, publication, use and disposal in whole or in part by or for the United States Government is permitted.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER 18 AFOSR-TR-77-0639	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) 6 THE EFFECT OF INITIAL IMPERFECTIONS ON OPTIMAL STIFFENED CYLINDERS UNDER AXIAL COMPRESSION		5. TYPE OF REPORT & PERIOD COVERED INTERIM	
7. AUTHOR(s) 10 GEORGE J. SIMITSES IZHAK SHEINMAN		6. PERFORMING ORG. REPORT NUMBER	
9. PERFORMING ORGANIZATION NAME AND ADDRESS GEORGIA INSTITUTE OF TECHNOLOGY SCHOOL OF ENGINEERING SCIENCE & MECHANICS 225 N Ave, Atlanta, GA 30332		8. CONTRACT OR GRANT NUMBER(s) AFOSR 74-2655 15 AF-AFOSR-2655-74	
11. CONTROLLING OFFICE NAME AND ADDRESS AIR FORCE OFFICE OF SCIENTIFIC RESEARCH/NA BLDG 410 BOLLING AIR FORCE BASE, D C 20332		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 2307B1 61102F	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 16 2307 17 B1		12. REPORT DATE Feb 77	
		13. NUMBER OF PAGES 113 12 115P	
		15. SECURITY CLASS. (of this report) UNCLASSIFIED	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) IMPERFECTION SENSITIVITY OPTIMAL DESIGN NONLINEAR STABILITY ANALYSIS GENERAL INSTABILITY			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report deals with the effect of initial imperfections on optimal stiffened cylinders under axial compression. A nonlinear stability methodology is developed for analyzing such system in the presence of small initial imperfections. This methodology is then employed to assess the effectiveness of stiffened cylinders optimized on the basis of linear stability analysis. This research was performed under Grant AFOSR 74-2655 during the period 1 Feb 76 through 31 Jan 77.			

#### ABSTRACT

The buckling analysis of imperfect, thin, circular, cylindrical, stiffened shell under uniform axial compression, for various boundary conditions is first investigated. A methodology is presented for predicting critical conditions for such configurations. This methodology is based on the smeared technique and the von Kármán-Donnell nonlinear kinematic relations in the presence of geometric imperfections. The computational procedure employs a Fourier series type of separated solution and through the Galerkin procedure the field equations are reduced to a system of ordinary differential equations. These equations are solved by the finite difference scheme. Numerical results for numerous stiffened and unstiffened configurations are presented.

Then the effect of initial geometric imperfections on the optimal stiffened circular cylindrical shell under uniform axial compression is assessed. The imperfection sensitivity of geometries corresponding to values of the design variables surrounding the optimal configuration is investigated for two design configurations. A design methodology is proposed through which one may arrive at the minimum weight configuration in the presence of geometric imperfections of predetermined maximum amplitude and of a shape that yields the greatest reduction in the linear theory buckling load.

TABLE OF CONTENTS

	Page Number
NOTATIONS	
Chapter	
I.    INTRODUCTION	1
II.   MATHEMATICAL FORMULATION OF THE NONLINEAR BUCKLING ANALYSIS	5
III.  SOLUTION METHODOLOGY: NONLINEAR BUCKLING ANALYSIS	16
IV.   APPLICATION AND DISCUSSION	29
V.    CONCLUSIONS BASED ON THE NONLINEAR BUCKLING ANALYSIS	40
VI.   IMPERFECTION SENSITIVITY OF OPTIMAL CYLINDERS;	42
1. Design Examples	
2. Discussion of Results	
VII.  RECOMMENDED DESIGN PROCEDURE FOR AXIALLY LOADED IMPERFECT STIFFENED CYLINDERS	52
Appendices	
A.    BUCKLING OF IMPERFECT STIFFENED CYLINDERS UNDER COMBINED AXIAL COMPRESSION AND PRESSURE	55
B.    COMPUTER PROGRAM	60
Bibliography	106

## NOTATIONS

A	Area
$A_x, A_y$	Stringer and ring cross-sectional area
D	Flexural stiffness of the skin
E	Young's modulus of elasticity
$E_{xx_p}$	Extensional stiffness of the skin
$e_x, e_y$	Stringer and ring eccentricities (positive inward)
e	Unit end shortening
F	Stress function
$f_i$	Fourier coefficient of stress function
$I_{xc}, I_{yc}$	Stringer-and ring moment of inertia about their centroidal axes
K	Number of terms in truncated Fourier Series
$l_x, l_y$	Stringer and ring spacings
l	Mesh point
L	Total length of the shell
$M_{xx}, M_{yy}, M_{xy}$	Moment resultants
m	Number of axial half waves
$N_{xx}, N_{yy}, N_{xy}$	Stress resultants
$\bar{N}_{xx}$	Applied compressive load
$N_{x_{cl}}$	Classical buckling load
$N_{x_{cr}}$	Critical load (limit point)
n	Number of circumferential full waves

NP	Number of points in axial direction
$Q^*$	Effective transverse shear
R	Radius of the cylinder
t	Skin thickness
$U_T$	Total Potential
u,v	In-plane displacements
w	Radial displacement (positive inward)
$w^0$	Radial geometric imperfection
x,y,z	Coordinate system
Z	Batdorf curvature parameter [ $= L^2(1-\nu^2)^{1/2}/R.t$ ]
z	Unknowns vector
$\epsilon_{xx}, \epsilon_{yy}, \epsilon_{xy}$	Reference surface strains
$\kappa_{xx}, \kappa_{yy}, \kappa_{xy}$	Reference surface changes in curvature and torsion
$\lambda_{xx}, \lambda_{yy}$	Smeared extensional stiffnesses of stringers and rings
$\nu$	Poisson's ratio
$\rho_{xx}, \rho_{yy}$	Smeared flexural stiffnesses of stringers and rings
$\Delta$	Interval size between mesh point
$( )' = [ ]_{,x}$	Derivative with respect to x

## CHAPTER I

### INTRODUCTION

Stability of thin circular cylindrical shells (with or without stiffening), because of its importance, has enjoyed tremendous attention for the past seventy years. Although a complete understanding of all the details of the phenomena involved has not yet been reached, it has been well established that the discrepancy between classical theoretical predictions and experimental results lies primarily in the fact that the system is sensitive to geometric imperfections, the presence of which is unavoidable.

The imperfection sensitivity of the system was initially established through strict postbuckling analyses of the perfect geometry system. In addition, it was explained that, the load carrying capacity of such systems is directly related to the lowest load corresponding to postbuckling states of equilibrium. The first theoretical investigation of this type was reported by von Kármán and Tsien<sup>1</sup> in 1941. The investigators calculated postbuckling equilibrium states, for an unstiffened, axially compressed, thin, circular cylindrical shell, corresponding to loads far below the classical critical load. The calculations were based on a number of simplifying assumptions the most important being the neglect of the effect of the boundary conditions. Many subsequent investigators<sup>2-4</sup> attempted to improve the calculations of von Kármán and Tsien in order to find the smallest postbuckling equilibrium load. This search came to an end when Hoff, Madsen and Mayers<sup>5</sup> found in their calculations that the

minimal postbuckling load tended towards zero with improved functional representation (taking more and more terms in the series) for the solution to the governing equations and with diminishing thickness. In addition, Madsen and Hoff<sup>6</sup> repeated the investigation by employing more accurate kinematic relations than those of Donnell. The difference between these results and the previous ones was insignificant. Furthermore, Koiter<sup>7</sup> has shown that the von Kármán-Donnell equations are also applicable to problems with arbitrarily large displacements, when the function describing the radial displacement is taken to be the curvature function defined in his paper.

Koiter<sup>8</sup> was the first to question the use of the minimal postbuckling equilibrium load as a measure of the load carrying capacity of the configuration. Instead, he proposes to find the critical load (limit point) of the imperfect system. Koiter's work is the first attempt to the buckling analysis of an imperfect shell, but his method is limited to the neighborhood of the classical load and therefore to small imperfections of certain spatial form. This approach has been adopted by many investigators including Hutchinson and Amazigo<sup>9</sup> who treated the stringer or ring stiffened thin cylindrical shell. Excellent reviews on the subject may be found in the works of Hoff<sup>10</sup>, and Hutchinson and Koiter<sup>11</sup>.

Many of the postbuckling analyses that are based on Koiter's proposition (see Ref. 11) disregard the effect of end conditions by assuming that the cylinder length is extremely large. A systematic experimental investigation dealing with cylinders of various lengths (Ref. 12) revealed that

the postbuckling behavior is strongly influenced by the cylinder length. Narasinhham and Hoff<sup>13,14</sup> analyzed an unstiffened, thin, circular, cylindrical, imperfect shell of finite length under uniform axial compression. They solve the nonlinear equations by employing a separated series solution for the dependent variables, each term of which contains a function of  $x$  multiplied by a cosine term in  $y$  (Fourier). Thus the equations are reduced to a system of ordinary differential equations, which in turn are solved by the finite difference scheme. Although the equations are developed for arbitrary terms of Fourier series, the solution is restricted to just one term for the displacement function. A similar procedure, but one that employs the "shooting method" (Ref. 15) instead of the finite difference technique, is employed by Arbocz and Sechler<sup>16</sup> in their investigation of the buckling behavior of axially compressed imperfect cylindrical shells.

With the exception of the work of Ref. 9, there is virtually no reported investigation on the buckling behavior of imperfect stiffened configurations. The first part of the report presents a methodology for analyzing the buckling of a uniformly compressed, stiffened (rings and stringers), thin, circular, cylindrical imperfect shells of finite length and various boundary conditions. The analysis employs the von Kármán-Donnell large displacement equations and the smeared technique. The solution procedure is similar to that of Ref. 13 but the limitations on the spatial character of the imperfection has been relaxed considerably. Results have been produced for special case geometries that have been reported in the open literature (bench marks) and for new configurations

of the stiffened type in both directions.

The latter part of the present report applies this method to the investigation of the effect of initial geometric imperfections on the optimal (linear theory) stiffened cylinder configuration under uniform axial compression.

## CHAPTER II

### MATHEMATICAL FORMULATION OF THE NONLINEAR BUCKLING ANALYSIS

By employing the von Kármán-Donnell kinematic equations for geometrically imperfect  $[w^0(x,y)]$  thin cylindrical shells one can easily derive the compatibility and transverse equilibrium equations in terms of the radial displacement  $w$  and the stress function  $F$ , as well as the expressions for the total potential and the "unit end shortening". The procedure employed is similar to that outlined in Ref. 13 for unstiffened, imperfect thin cylindrical shells.

Consider a geometrically imperfect stiffened cylinder under uniform axial compression. Let  $w^0(x,y)$  denote the deviation of the shell mid-surface (taken to be the reference surface) from the corresponding perfectly cylindrical one. Let  $u, v$ , and  $w$  denote the displacements of material points on the reference surface (see Fig. 1).

The kinematic relations, first proposed by Donnell<sup>17</sup> are given below

$$\begin{aligned}
 \epsilon_{xx} &= u_{,x} + \frac{1}{2}(w_{,x}^2 + 2w_{,x}w_{,x}^0) \\
 \epsilon_{yy} &= v_{,y} - w/R + \frac{1}{2}(w_{,y}^2 + 2w_{,y}w_{,y}^0) \\
 \gamma_{xy} &= 2\epsilon_{xy} = u_{,y} + v_{,x} + w_{,x}w_{,y} + w_{,y}w_{,x}^0 + w_{,x}w_{,y}^0 \\
 \kappa_{xx} &= w_{,xx}; \quad \kappa_{yy} = w_{,yy}; \quad \kappa_{xy} = w_{,xy}
 \end{aligned}
 \tag{1}$$

The stress and moment resultants to strains and changes in curvature and torsion are taken from Ref. 18. They were derived by employing the smeared technique.

$$\begin{aligned}
N_{xx} &= E_{xx_p} [(1+\lambda_{xx})\epsilon_{xx} + \nu\epsilon_{yy} - e_x \lambda_{xx} \kappa_{xx}] \\
N_{yy} &= E_{xx_p} [\nu\epsilon_{xx} + (1+\lambda_{yy})\epsilon_{yy} - e_y \lambda_{yy} \kappa_{yy}] \\
N_{xy} &= E_{xx_p} [1-\nu)\epsilon_{xy}] \\
M_{xx} &= D \left\{ (1+\rho_{xx}) + \frac{12}{t^2} e_x^2 \lambda_{xx} \right\} \kappa_{xx} + \nu \kappa_{yy} - \frac{12}{t^2} e_x \lambda_{xx} \epsilon_{xx} \\
M_{yy} &= D \left\{ \nu \kappa_{xx} + \left[ (1+\rho_{yy}) + \frac{12}{t^2} e_y^2 \lambda_{yy} \right] \kappa_{yy} - \frac{12}{t^2} e_y \lambda_{yy} \epsilon_{yy} \right\} \\
M_{xy} &= D(1-\nu) \kappa_{xy}
\end{aligned} \tag{2}$$

where

$$\begin{aligned}
E_{xx_p} &= Et/(1-\nu^2); \quad D = Et^3/12(1-\nu^2); \quad \lambda_{xx} = A_x(1-\nu^2)/t\ell_x \\
\lambda_{yy} &= A_y(1-\nu^2)/t\ell_y; \quad \rho_{xx} = EI_{xc}/D\ell_x; \quad \text{and } \rho_{yy} = EI_{yc}/D\ell_y.
\end{aligned}$$

From Eqs. (2) one may derive the following expressions for the reference surface strains

$$\begin{aligned}
\epsilon_{xx} &= a_1 N_{xx} + a_2 N_{yy} + a_3 \kappa_{xx} + a_4 \kappa_{yy} \\
\epsilon_{yy} &= a_2 N_{xx} + b_2 N_{yy} + b_3 \kappa_{xx} + b_4 \kappa_{yy} \\
\epsilon_{xy} &= \frac{1}{2} \gamma_{xy} = N_{xy}/(1-\nu)E_{xx_p}
\end{aligned} \tag{3}$$

where

$$\begin{aligned}
a_1 &= (1+\lambda_{yy})/\alpha E_{xx_p}; \quad a_2 = -\nu/\alpha E_{xx_p}; \quad a_3 = (1+\lambda_{yy})e_x \lambda_{xx}/\alpha \\
a_4 &= -\nu e_y \lambda_{yy}/\alpha; \quad b_2 = (1+\lambda_{xx})\alpha E_{xx_p}; \quad b_3 = -\nu e_x \lambda_{xx}/\alpha
\end{aligned} \tag{4}$$

$$b_4 = (1+\lambda_{xx})e_y \lambda_{yy} / \alpha; \quad \alpha = [1+\lambda_{xx})(1+\lambda_{yy}) - v^2]$$

By employing the principle of the stationary value of the total potential one can derive the following equilibrium equations

$$N_{xx,x} + N_{xy,y} = 0$$

$$N_{xy,x} + N_{yy,y} = 0$$

$$M_{xx,xx} + 2M_{xy,xy} + M_{yy,yy} = \frac{N_{yy}}{R} + [N_{yy}(w_{,y} + w_{,y}^0)],_y + [N_{xy}(w_{,x} + w_{,x}^0)],_y \\ + [N_{xx}(w_{,x} + w_{,x}^0)],_x + [N_{xy}(w_{,y} + w_{,y}^0)],_x$$

By introducing the Airy stress function, as  $N_{xx} = -\bar{N}_{xx} + F_{,yy}$ ,  $N_{yy} = F_{,xx}$  and  $N_{xy} = -F_{,xy}$  where  $\bar{N}_{xx}$  is the level of the applied uniform axial compression, the first two of Eqs. (5) are identically satisfied.

Next, by eliminating  $u$  and  $v$  from the first three of Eqs. (1), employing Eqs. (3), the Airy stress function and the last three of Eqs. (1) one can derive the compatibility equation in terms of the Airy stress function,  $F$  and the radial displacement,  $w$ . If one expresses the third of Eq. (5) in terms of  $F$  and  $w$ , the governing equations consist of two coupled partial differential equations in  $F$  and  $w$ . These are:

#### Equilibrium

$$DL_h[w] - L_q[F] - F_{,xx}/R + \bar{N}_{xx}(w_{,xx} + w_{,xx}^0) - L[F, w + w^0] = 0 \quad (6)$$

#### Compatibility

$$L_d[F] + L_q[w] + \frac{1}{2}L[w, w + 2w^0] + w_{,xx}/R = 0 \quad (7)$$

where  $L_d$ ,  $L_h$ , and  $L_q$  are differential operators defined by  $L_g$ ,




Fig. 1. Geometry and Sign Convention

$$L_g[s] = g_{11}s_{,xxxx} + 2g_{12}s_{,xxyy} + g_{22}s_{,yyyy} \quad (8a)$$

with

$$d_{11} = (1+\lambda_{xx})/\alpha E_{xxp}$$

$$d_{12} = [(1+\lambda_{xx})(1+\lambda_{yy}) - \nu]/\alpha(1-\nu)E_{xxp} \quad (9a)$$

$$d_{22} = (1+\lambda_{yy})/\alpha E_{xxp}$$

$$h_{11} = 1 + \rho_{xx} + \frac{12}{t^2} \cdot \frac{e^{2\lambda_{xx}}(1 + \lambda_{yy} - \nu^2)}{\alpha}$$

$$h_{12} = 1 + \frac{12}{t^2} \frac{\nu e_x e_y \lambda_{xx} \lambda_{yy}}{\alpha} \quad (9b)$$

$$h_{22} = 1 + \rho_{yy} + \frac{12}{t^2} \frac{e^{2\lambda_{yy}}(1 + \lambda_{xx} - \nu^2)}{\alpha}$$

$$q_{11} = -\nu e_x \lambda_{xx}/\alpha$$

$$q_{12} = [(1 + \lambda_{yy})e_x \lambda_{xx} + (1 + \lambda_{xx})e_y \lambda_{yy}]/(2\alpha) \quad (9c)$$

$$q_{22} = -\nu e_y \lambda_{yy}/\alpha$$

and L is a differential operator defined by

$$L[S,T] = S_{,xx}T_{,yy} - 2S_{,xy}T_{,xy} + S_{,yy}T_{,xx} \quad (8b)$$

The total potential expression, in terms of the Airy stress function and the radial displacement, is given below

$$U_T = \frac{1}{2E_{xxp}} \int_A (\beta_1 F_{,yy}^2 + \beta_2 F_{,xx}^2 + \beta_3 F_{,xx} F_{,yy} + \beta_4 F_{,xy}^2) dA$$

$$\begin{aligned}
& + \frac{D}{2} \int_A (\alpha_1 w_{,yy}^2 + \alpha_2 w_{,xx}^2 + \alpha_3 w_{,xx} w_{,yy} + \alpha_4 w_{,xy}^2) dA \\
& - \frac{\bar{N}_{xx}}{2E_{xxp}} \int_A (2\beta_1 F_{,yy} + \beta_3 F_{,xx}) dA + \frac{\beta_1}{E_{xxp}} \pi RL \bar{N}_{xx}^2 - \bar{N}_{xx} 2\pi RL e_{AV}
\end{aligned} \tag{10}$$

where  $e_{AV}$  (average end shortening) is given by

$$e_{AV} = - \int_A u_{,x} dA / 2\pi RL$$

and

$$\begin{aligned}
\beta_1 &= d_{22} E_{xxp}; \quad \beta_2 = d_{11} E_{xxp}; \quad \beta_3 = -2\nu/\alpha; \quad \beta_4 = 2/(1-\nu) \\
\alpha_1 &= h_{22}; \quad \alpha_2 = h_{11}; \quad \alpha_3 = 2\sqrt{1 + \frac{12}{t^2} \frac{e_x e_y \lambda_{xx} \lambda_{yy}}{\alpha}}; \quad \alpha_4 = 2(1-\nu)
\end{aligned} \tag{11}$$

Similarly, the expressions for the average end shortening and "unit end shortening" at  $y = 0$  are given by

$$\begin{aligned}
e_{AV} &= a_1 \bar{N}_{xx} - \frac{1}{2\pi RL} \int_0^{2\pi R} \int_0^L [a_1 F_{,yy} + a_2 F_{,xx} + a_3 w_{,xx} + a_4 w_{,yy} \\
&\quad - \frac{1}{2} w_{,x} (w_{,x} + 2w_{,x}^o)] dx dy
\end{aligned} \tag{12a}$$

$$\begin{aligned}
e &= a_1 \bar{N}_{xx} - \frac{1}{L} \int_0^L [a_1 F_{,yy} + a_2 F_{,xx} + a_3 w_{,xx} + a_4 w_{,yy} \\
&\quad - \frac{1}{2} w_{,x} (w_{,x} + 2w_{,x}^o)]_{y=0} dx
\end{aligned} \tag{12b}$$

Note that  $e$  measures the amount of end shortening per unit of cylinder length,  $L$ . The associated boundary conditions are either kinematic or natural (but not both) except for the direction associated with the length

of the cylinder (x) in which case the displacement component u is free and the stress resultant  $N_{xx}$  must equal to the applied stress resultant,  $-\bar{N}_{xx}$ . Thus at a boundary characterized by  $x = 0$  or  $x = L$  the boundary conditions are:

<u>Either</u>	<u>or</u>
<u>in-plane</u>	
$N_{xx} = F_{,yy} - \bar{N}_{xx} = -\bar{N}_{xx}$	$u = \text{constant}$
$N_{xy} = 0$	$v = 0$

transverse

$M_{xx} = 0$	$w_{,x} = 0$
$Q_x^* = 0$	$w = 0$

The expressions for the moment resultant,  $M_{xx}$ , and the effective transverse shear,  $Q_x^*$ , are

$$\begin{aligned}
 M_{xx} &= \gamma_1 w_{,xx} + \gamma_2 w_{,yy} + \gamma_3 (F_{,yy} - \bar{N}_{xx}) + \gamma_4 F_{,xx} \\
 Q_x^* &= (F_{,yy} - \bar{N}_{xx})(w_{,x} + w_{,x}^0) + F_{,xy}(w_{,y} + w_{,y}^0) - M_{xx,x} - 2M_{xy,y}
 \end{aligned}
 \tag{14}$$

where

$$\gamma_1 = Dh_{11}; \quad \gamma_2 = D \frac{\alpha_3}{2}; \quad \gamma_3 = -\alpha_3; \quad \gamma_4 = -b_3$$

The general computer program is written for the following end conditions (SSi, CCI, FFi,  $i = 1, 2, 3, 4$ )

$$SS: w = M_{xx} = 0$$

$$CC: w = w_{,x} = 0$$

$$FF: Q_x^* = M_{xx} = 0$$

$$1. F_{,xy} = F_{,yy} = 0$$

$$2. F_{,xy} = 0; u = C$$

$$3. v = F_{,yy} = 0 \quad (15)$$

$$4. v = 0, u = C$$

where C is a constant.

The conditions in u and v can be expressed in terms of w and F as in Ref. 14. For example, the condition  $u = C$  in SS -2 can be replaced by a condition expressed solely in terms of w,  $w^0$ , F and their gradients. This is accomplished by the following procedure:

This boundary condition, SS=2, at  $x = 0$  or  $L$  given  $w = 0; F_{,xy} = 0, M_{xx} = 0$  and  $u = C$ . The first two are in terms of w and F. The third one,  $M_{xx} = 0$ , from the first of Eqs. (14) is expressed in terms of w, F, and their gradients. For the last one, one notes that [see Eqs. (1) and (3)]

$$\epsilon_{xy} = \frac{1}{2} [u_{,y} + v_{,x} + w_{,x}w_{,y} + w_{,y}w^0_{,x} + w_{,x}w^0_{,y}] = -F_{,xy}/(1-\nu)E_{xx} \quad (16)$$

since  $F_{,xy} = 0, w_{,y} = 0$  because  $w(0,y) = 0$ , and  $u_{,y} = 0$  because  $u(0,y) = C$ , Eq. (16) becomes

$$v_{,x} + w_{,x}w^0_{,y} = 0 \quad (17)$$

Similarly, from Eqs. (1) and (3) one may write

$$\begin{aligned} \epsilon_{yy} &= v_{,y} + \frac{1}{2}[w_{,y}(w_{,y} + 2w^0_{,y})] - \frac{w}{R} \\ &= a_2 N_{xx} + b_2 N_{yy} + b_3 k_{xx} + b_4 k_{yy} \end{aligned} \quad (18)$$

This equation, Eq. (18), is valid at any point along the shell, there-

fore differentiation with respect to x does not violate its validity. If this is done and if the N's and k's are expressed in terms of w, F, and their gradients, one may write

$$v_{,yx} + \frac{1}{2} [w_{,xy} (w_{,y} + 2w_{,y}^0) + w_{,y} (w_{,xy} + 2w_{,xy}^0)] - \frac{w_{,x}}{R} \quad (19)$$

$$= a_2 F_{,yyx} + b_2 F_{,xxx} + b_3 w_{,xxx} + b_4 w_{,yyx}$$

Evaluation of Eq. (19) at  $x = 0$  or  $L$ , and use of the fact that  $w_{,y}(0,y) = 0$  yields

$$v_{,yx} + w_{,xy} w_{,y}^0 - w_{,x}/R = a_2 F_{,yyx} + b_2 F_{,xxy} + b_3 w_{,xxx} + b_4 w_{,yyx} \quad (20)$$

Differentiation of Eq. (17) with respect to y, yields

$$v_{,xy} + w_{,xy} w_{,y}^0 + w_{,x} w_{,xy}^0 = 0 \quad (21)$$

Substitution of Eq. (21) into Eq. (20) yields a boundary condition equivalent to  $u = C$ , or

$$b_2 F_{,xxx} + b_3 w_{,xxx} + b_4 w_{,yyx} + w_{,x} \left( \frac{1}{R} + w_{,yy}^0 \right) = 0 \quad (22)$$

Similar steps may be followed to express all possible boundary conditions in terms of w, F, and their gradients. In order to save space only the final expression for all possible boundary conditions, Eqs. (15), are given below, which have been incorporated into the computer program (see Appendix B)

$$\underline{\text{SS-1}} \quad w = \gamma_1 w_{,xx} + \gamma_4 F_{,xx} = F_{,xy} = F_{,yy} = 0$$

$$\underline{\text{SS-2}} \quad w = \gamma_1 w_{,xx} + \gamma_3 (F_{,yy} - \bar{N}_{xx}) + \gamma_4 F_{,xx} = F_{,xy} = 0$$

$$b_2 F_{,xxx} + b_3 w_{,xxx} + b_4 w_{,yyx} + w_{,x} \left( \frac{1}{R} + w_{,yy}^0 \right) = 0$$

$$\underline{\text{SS-3}} \quad w = \gamma_1 w_{,xx} + \gamma_4 F_{,xx} = F_{,yy} = b_2 F_{,xx} + b_3 w_{,xx} = 0$$

$$\underline{\text{SS-4}} \quad w = \gamma_1 w_{,xx} + \gamma_3 (F_{,yy} - \bar{N}_{xx}) + \gamma_4 F_{,xx} = a_2 (F_{,yy} - \bar{N}_{xx}) + b_2 F_{,xx} \\ + b_3 w_{,xx} = 0$$

$$\left[ a_2 + \frac{2}{(1-\nu)E_{xxp}} \right] F_{,xyy} + b_2 F_{,xxx} + b_3 w_{,xxx} + b_4 w_{,xyy} \\ + w_{,x} \left( \frac{1}{R} + w_{,yy}^0 \right) = 0 \quad (23a)$$

$$\underline{\text{CC-1}} \quad w = w_{,x} = F_{,xy} = F_{,yy} = 0$$

$$\underline{\text{CC-2}} \quad w = w_{,x} = F_{,xy} = 0 \quad b_2 F_{,xxx} + b_3 w_{,xxx} = 0$$

$$\underline{\text{CC-3}} \quad w = w_{,x} = F_{,yy} = 0 \quad b_2 F_{,xx} + b_3 w_{,xx} = 0$$

$$\underline{\text{CC-4}} \quad w = w_{,x} = a_2 \left( F_{,yy} - \bar{N}_{xx} \right) + b_2 F_{,xx} + b_3 w_{,xx} = 0$$

$$\left[ a_2 + \frac{2}{(1-\nu)E_{xxp}} \right] F_{,yyx} + b_2 F_{,xxx} + b_3 w_{,xxx} = 0 \quad (23b)$$

Similarly the FF-1 condition and the symmetry and antisymmetry conditions at  $x = L/2$  are

$$\underline{\text{FF-1}} \quad \gamma_1 w_{,xx} + \gamma_2 w_{,yy} + \gamma_4 F_{,xx} = F_{,yy} = F_{,xy} = 0$$

$$\gamma_4 F_{,xxx} + \gamma_1 w_{,xxx} + \left[ \gamma_2 + 2D(1-\nu) \right] w_{,xyy} + \bar{N}_{xx} (w_{,x} - w_{,x}^0) = 0 \quad (23c)$$

$$\underline{\text{Symmetry}} \quad (w_{,x} = Q^* = N_{xy} = u = 0)$$

$$w_{,x} = \gamma_1 w_{,xxx} + \gamma_4 F_{,xxx} - (F_{,yy} - \bar{N}_{xx}) w_{,x}^0 = 0$$

$$F_{,xy} = b_2 F_{,xxx} + b_3 w_{,xxx} + w_{,x}^0 w_{,yy} = 0$$

(23d)

Antisymmetry ( $w = M_{xx} = v = F_{,yy} = 0$ )

$$w = \gamma_1 w_{,xx} + \gamma_4 F_{,xx} = 0$$

$$F_{,yy} = b_2 F_{,xx} + b_3 w_{,xx} = 0$$

The problem, as formulated herein, is to find the limit point which represents the buckling load for the imperfect configuration. This implies to solve the field equations, Eqs. (6) and (7), subject to the proper boundary conditions for a given imperfection and level of the applied load (small initially),  $-\bar{N}_{xx}$ , and thus obtain the corresponding amount of "unit end shortening", Eq. (12b). By plotting  $\bar{N}_{xx}$  versus  $e$  one can obtain the limit point (theoretically).

### CHAPTER III

#### SOLUTION METHODOLOGY; NONLINEAR BUCKLING ANALYSIS

By employing the von Kármán-Donnell kinematic relations the field equations consist of two coupled, nonlinear, partial differential equations in terms of the transverse displacement,  $w$ , and the Airy stress function,  $F$ . The procedure employed herein for accomplishing a solution is basically similar to that of Refs. 13 and 14. The system of partial differential equations is reduced to a system of ordinary differential equations by using a separated solution (Fourier series) of the following form (see Refs. 13 and 14).

$$\begin{aligned}w(x,y) &= \sum_{i=0}^K W_i(x) \cos \frac{iny}{R} \\F(x,y) &= \sum_{i=0}^{2K} f_i(x) \cos \frac{iny}{R} \\w^0(x,y) &= \sum_{i=0}^K W_i^0(x) \cos \frac{iny}{R}\end{aligned} \tag{24}$$

Note that  $W_i^0(x)$  denotes the known coefficient of the  $i$ th component of the geometric imperfection, and  $n$  is the parameter associated with the number of full waves around the circumference.

By substituting Eqs. (24) into Eq. (7), employing trigonometric identities of double Fourier series as in Ref. 19 involving products and the orthogonality of the trigonometric functions, the compatibility equation becomes

for  $i = 0$

$$f''_0 = \frac{1}{d_{11}} \left[ -q_{11} W''_0 - W^0/R + \frac{n^2}{4R^2} \sum_{j=1}^K j^2 (W_j + 2W_j^0) W_j \right] \quad (25a)$$

for  $i = 1, 2, \dots, 2K$

$$\begin{aligned} & d_{11} f''''_i - 2 \left( \frac{in}{R} \right)^2 d_{12} f''_i + \left( \frac{in}{R} \right)^4 d_{22} f_i \\ & + \delta_i \left[ q_{11} W''''_i - 2 \left( \frac{in}{R} \right)^2 q_{12} W''_i + \left( \frac{in}{R} \right)^4 q_{22} W_i + W''_i/R \right] \\ & - \frac{n^2}{4R^2} \sum_{j=0}^K \left\{ (i+j)^2 \delta_{i+j} (W_{i+j} + 2W_{i+j}^0) \right. \\ & + (2 - \eta_{j-i}^2) (i-j)^2 \delta_{|i-j|} (W_{|i-j|} + 2W_{|i-j|}^0) \left. \right\} W_j'' \\ & + \left[ \delta_{i+j} (W_{i+j}'' + 2W_{i+j}^{0''}) + (2 - \eta_{j-i}^2) \delta_{|i-j|} (W_{|i-j|}'' + 2W_{|i-j|}^{0''}) \right] j^2 W_j \\ & + 2 \left[ (i+j) \delta_{i+j} (W'_{i+j} + 2W_{i+j}^{0'}) - \eta_{i-j} |i-j| \delta_{|i-j|} (W'_{|i-j|} + 2W_{|i-j|}^{0'}) \right] j W_j' \left. \right\} = 0 \end{aligned} \quad (25b)$$

where

$$\delta_\ell = \begin{cases} 0 & \ell > K \\ 1 & \ell \leq K \end{cases} \quad \eta_\ell = \begin{cases} -1 & \ell < 0 \\ 0 & \ell = 0 \\ 1 & \ell > 0 \end{cases}$$

and

$$(\ )' = \frac{d}{dx} .$$

Next, if Eqs. (24) are substituted into the equilibrium equation, Eq. (6),

and the Galerkin procedure is employed ( $\cos \frac{iny}{R}$  is the weighting function  $i = 1, 2, \dots, K$ ), the vanishing of the  $(K+1)$  Galerkin integrals leads to the following system of  $(K+1)$  ordinary differential equations

for  $i = 0$

$$\begin{aligned}
 W_0'''' [Dh_{11} + q_{11}^2 / d_{11}] + W_0'' [2q_{11} / R \cdot d_{11}] + W_0 [1/R^2 \cdot d_{11}] + \bar{N}_{xx} (W'' + W_0^0) \\
 - \frac{n^2}{4R^2} \sum_{j=1}^K j^2 \left\{ \frac{q_{11}}{d_{11}} [(W_j + 2W_j^0)W_j'' + (W_j'' + 2W_j^{0''})W_j] \right. \\
 + 2(W_j' + 2W_j^{0'})W_j' + \frac{1}{Rd_{11}} [(W_j + 2W_j^0)W_j] - 2[(W_j + W_j^0)f_j'' \\
 \left. + (W_j'' + W_j^{0''})f_j + 2(W_j' + W_j^{0'})f_j'] \right\} = 0 \quad (26a)
 \end{aligned}$$

for  $i = 1, 2, \dots, K$

$$\begin{aligned}
 D \left[ h_{11} W_i'''' - 2 \left( \frac{in}{R} \right)^2 h_{12} W_i'' + \left( \frac{in}{R} \right)^4 h_{22} W_i \right] \\
 - \left[ q_{11} f_i'''' - 2 \left( \frac{in}{R} \right)^2 q_{12} f_i'' + \left( \frac{in}{R} \right)^4 q_{22} f_i + f_i'' / R \right] \\
 + \bar{N}_{xx} (W_i'' + W_i^{0''}) - W_i'' \left[ \frac{q_{11}}{d_{11}} \left( \frac{in}{R} \right)^2 \right] (W_i + W_i^0) - W_0 \left[ \frac{1}{Rd_{11}} \left( \frac{in}{R} \right)^2 (W_i \right. \right. \\
 \left. \left. + W_i^0) + \frac{n^4}{4R^4} \frac{i^2}{d_{11}} (W_i + W_i^0) \sum_{j=1}^K j^2 (W_j + 2W_j^0) W_j \right. \right. \\
 \left. \left. + \frac{n^2}{2R^2} \sum_{j=1}^{2K} \left\{ [(i+j)^2 \delta_{i+j} (W_{i+j} + W_{i+j}^0) \right. \right. \right.
 \end{aligned}$$

$$\begin{aligned}
& + (2 - \eta_{j-i}^2) (i-j)^2 \delta_{|i-j|} (W_{|i-j|} + W_{|i-j|}^0) f_j'' \\
& + [\delta_{i+j} (W_{i+j}'' + W_{i+j}^{0''}) + (2 - \eta_{j-i}^2) \delta_{|i-j|} (W_{|i-j|}'' + W_{|i-j|}^{0''})] j^2 f_j \\
& + 2[ (i+j) \delta_{i+j} (W_{i+j}' + W_{i+j}^{0'}) \\
& - \eta_{i-j} |i-j| \delta_{|i-j|} (W_{|i-j|}' + W_{|i-j|}^{0'})] j f_j' \} = 0 \quad (26b)
\end{aligned}$$

For a given value of the applied load,  $\bar{N}_{xx}$ , and imperfection, Eqs. (25) and (26) represent a system of  $(3K + 2)$  coupled nonlinear differential equations in  $(3K + 2)$  unknowns,  $f_i$   $i = 0, 1, 2, \dots, 2K$  and  $W_i$   $i = 0, 1, 2, \dots, K$ . These equations denote equilibrium and compatibility conditions. Similarly, the expressions for the total potential,  $U_T$ , average end shortening,  $e_{AV}$ , and "unit end shortening",  $e$ , become

$$\begin{aligned}
U_T = nR \int_0^L & \left\langle \frac{1}{E_{xxp}} \left\{ \frac{\beta_2}{d_{11}^2} \left[ -\frac{W_0}{R} - q_{11} W_0'' + \frac{n^2}{4R^2} \sum_{j=1}^K i^2 (W_i + 2W_i^0) W_i \right]^2 \right. \right. \\
& + \frac{1}{2} \sum_{i=1}^{2K} \left[ \beta_1 \left( \frac{in}{R} \right)^4 f_i^2 + \beta_2 f_i''^2 - \beta_3 \left( \frac{in}{R} \right)^2 f_i'' f_i + \beta_4 \left( \frac{in}{R} \right)^2 f_i'^2 \right] \\
& \left. + D \left\{ \alpha_2 W_0''^2 + \frac{1}{2} \sum_{i=1}^K \left[ \alpha_1 \left( \frac{in}{R} \right)^4 W_i^2 + W_i''^2 - \alpha_3 \left( \frac{in}{R} \right)^2 W_i' W_i + \alpha_4 \left( \frac{in}{R} \right)^2 W_i'^2 \right] \right\} \right\rangle
\end{aligned}$$

$$\begin{aligned}
& - \frac{\bar{N}_{xx} \beta_3}{d_{11} E_{xxp}} \left[ - \frac{W_o}{R} - q_{11} W_o'' + \frac{n^2}{4R^2} \sum_{i=1}^K i^2 (W_i + 2W_i^o) W_i \right] dx \\
& + \frac{\beta_1 \pi R L}{E_{xxp}} \bar{N}_{xx}^2 - \bar{N}_{xx} 2\pi R L e_{AV}
\end{aligned} \tag{27}$$

$$\begin{aligned}
e_{AV} = & a_1 \bar{N}_{xx} + \frac{1}{L} \int_0^L \left\{ \frac{a_2}{d_{11}} \left[ \frac{W_o}{R} + q_{11} W_o'' - \frac{n^2}{4R^2} \sum_{i=1}^K i^2 (W_i + 2W_i^o) W_i \right] \right. \\
& \left. - a_3 W_o'' + \frac{1}{2} W_o' (W_o' + W_o^{o'}) + \frac{1}{4} \sum_{i=1}^K W_i' (W_i' + W_i^{o'}) \right\} dx
\end{aligned} \tag{28a}$$

$$\begin{aligned}
e = & a_1 \bar{N}_{xx} + \frac{1}{L} \int_0^L \left\{ \frac{a_2}{d_{11}} \left[ \frac{W_o}{R} + q_{11} W_o'' - \frac{n^2}{4R^2} \sum_{i=1}^K i^2 (W_i + 2W_i^o) W_i \right] \right. \\
& + \sum_{i=1}^{2K} \left[ a_1 \left( \frac{i n}{R} \right)^2 f_i - a_2 f_i'' \right] - a_3 \sum_{i=0}^K W_i'' + a_4 \sum_{i=1}^K \left( \frac{i n}{R} \right)^2 W_i \\
& \left. + \frac{1}{2} \left[ \sum_{i=0}^K W_i' \right] \sum_{i=0}^K (W_i' + 2W_i^{o'}) \right\} dx
\end{aligned} \tag{28b}$$

Finally, the appropriate boundary conditions are expressed in terms of  $W_i$ ,  $W_i^o$ , and  $f_i$ . Note that, because of the character of the nonlinear differential field equations, Eqs. (6) and (7), by setting  $n = 0$  one obtains the linearized version of equilibrium and compatibility. Furthermore, it is easily seen from Eqs. (24) that  $n = 1$  includes the axisymmetric mode since the summation on  $i$  starts from zero. In addition, it is seen from the Fourier series representation of the imperfection that this

expression is suitable for the case when the imperfection is of the same shape as the buckling mode, as well as for any arbitrary symmetric (with respect to y) imperfection shape. In this latter case, in order to obtain a solution it is necessary to let  $n = 1$  (in the series representation for  $W^0$ ) and take  $K$  large enough for an accurate representation of the imperfection and for achieving a convergent solution. By employing Eq. (24) the expressions for the various boundary, symmetry and antisymmetry conditions become, Eqs. (23),

$$\underline{\text{SS-1}} \quad W_0 = W_0'' = 0$$

$$W_i = \gamma_1 W_i'' + \gamma_4 f_i'' = 0 \quad i = 1, 2, \dots, K$$

$$f_i' = f_i = 0 \quad i = 1, 2, \dots, 2K$$

$$\underline{\text{SS-2}} \quad W_0 = W_0'' - \gamma_3 \bar{N}_{xx} = 0$$

$$W_i = \gamma_1 W_i'' - \gamma_3 \left[ \bar{N}_{xx} + \left( \frac{in}{R} \right)^2 f_i \right] + \gamma_4 f_i'' = 0 \quad i = 1, 2, \dots, K$$

$$f_i' = 0 \quad i = 1, 2, \dots, 2K$$

$$b_2 f_i''' + b_3 W_i''' - \left( \frac{in}{R} \right)^2 b_4 W_i' + \frac{1}{R} W_i'$$

$$- \frac{n^2}{2R^2} \sum_{j=0}^K \left[ (i+j)^2 W_{i+j}^0 + (1 - \eta_{j-i}^2 + \eta_i) (i-j)^2 W_{|i-j|}^0 \right] W_j' = 0 \quad (29a)$$

$$i = 1, 2, \dots, 2K$$

$$\underline{\text{SS-3}} \quad W_0 = W_0'' = 0$$

$$W_i = \gamma_1 W_i'' + \gamma_4 f_i'' = 0 \quad i = 1, 2, \dots, K$$

$$f_i = b_2 f_i'' + b_3 W_i'' = 0 \quad i = 1, 2, \dots, 2K$$

SS-4

$$W_0 = W_0'' = 0$$

$$W_i = \gamma_1 W_i'' - \gamma_3 \left[ \left( \frac{in}{R} \right)^2 f_i + \bar{N}_{xx} \right] + \gamma_4 f_i'' = 0 \quad i = 1, 2, \dots, K$$

$$-a_2 \left[ \bar{N}_{xx} + \left( \frac{in}{R} \right)^2 f_i \right] + b_2 f_i'' + b_3 W_i'' = 0 \quad ; \quad i = 1, 2, \dots, 2K$$

$$- \left[ a_2 + 2/(1-\nu) E_{xxp} \right] \left( \frac{in}{R} \right)^2 f_i + b_2 f_i'' + b_3 W_i'' - b_4 \left( \frac{in}{R} \right)^2 W_i' + \frac{1}{R} W_i'$$

$$- \frac{n^2}{2R^2} \sum_{j=0}^K \left[ (i+j)^2 W_{i+j}^0 + (1 - \eta_{j-1}^2 + \eta_i) W_{|i-j|}^0 \right] W_j' = 0$$

$$i = 1, 2, \dots, 2K$$

CC-1

$$W_i = W_i' = 0 \quad , \quad i = 0, 1, 2, \dots, K$$

$$f_i' = f_i = 0 \quad , \quad i = 1, 2, \dots, 2K$$

CC-2

$$W_i = W_i' = 0 \quad , \quad i = 0, 1, 2, \dots, K$$

$$f_i' = b_2 f_i''' + b_3 W_i''' = 0 \quad , \quad i = 1, 2, \dots, 2K$$

(29b)

CC-3

$$W_i = W_i' = 0 \quad , \quad i = 0, 1, \dots, K$$

$$f_i = b_2 f_i'' + b_3 W_i'' = 0 \quad , \quad i = 1, 2, \dots, 2K$$

CC-4

$$W_i = W_i' = 0 \quad , \quad i = 0, 1, 2, \dots, K$$

$$- a_2 \left[ \bar{N}_{xx} + \left( \frac{in}{R} \right)^2 f_i \right] + b_2 f_i'' + b_3 W_i'' = 0 \quad , \quad i = 1, 2, \dots, 2K$$

$$- \left[ a_2 + 2/(1-\nu) E_{xxp} \right] \left( \frac{in}{R} \right)^2 f_i' + b_2 f_i''' + b_3 W_i''' = 0 \quad ,$$

$$i = 1, 2, \dots, 2K$$

$$\text{FF-1} \quad W_o'' \left[ \gamma_1 - \gamma_4 q_{11}/d_{11} \right] - W_o \gamma_4 / R d_{11} + \frac{\gamma_4 n^2}{4R^2 d_{11}} \sum_{j=1}^K j^2 (W_j + 2W_j^o) W_j = 0$$

$$W_o''' \left[ \gamma_1 - \gamma_4 q_{11}/d_{11} \right] + W_o' \left[ \bar{N}_{xx} - \gamma_4 / R d_{11} \right] + \bar{N}_{xx} W_o' =$$

$$+ \frac{\gamma_4 n^2}{4R^2 d_{11}} \sum_{j=1}^K j^2 \left[ (W_j + 2W_j^o) W_j' + (W_j' + 2W_j^{o'}) W_j \right] = 0$$

$$\gamma_1 W_i'' - \left( \frac{in}{R} \right)^2 \gamma_2 W_i + \gamma_4 f_i'' = 0 \quad , \quad i = 1, 2, \dots, K \quad (29c)$$

$$\gamma_4 f_i''' + \gamma_1 W_i''' - \left[ \gamma_2 + 2D(1-\nu) \right] \left( \frac{in}{R} \right)^2 W_j' + \bar{N}_{xx} (W_i' + W_i^{o'}) = 0$$

$$i = 1, 2, \dots, K$$

$$f_i' = f_i = 0 \quad , \quad i = 1, 2, \dots, 2K$$

$$\text{Symmetry} \quad W_o' = 0$$

$$W_o''' (\gamma_1 - \gamma_4 q_{11}/d_{11}) + \frac{\gamma_4 n^2}{4R^2 d_{11}} \sum_{j=1}^K j^2 (W_i + 2W_j^o) W_j'$$

$$+ (W_j' + 2W_j^{o'})W_j] + \frac{n^2}{2R^2} \sum_{j=1}^{2K} [\delta_{i+j}W_{i+j}^{o'} + (1-\eta_{j-1}^2 + \eta_i)W_{|i-j|}^{o'} \delta_{|i-j|}]^2 f_j = 0$$

$$W_i' = \gamma_1 W_i''' + \gamma_4 f_i''' + \frac{n^2}{2R^2} \sum_{j=1}^{2K} [\delta_{i+j}W_{i+j}^{o'} + (1 - \eta_{j-i}^2 + \eta_i) \delta_{|i-j|}W_{|i-j|}^{o'}] j f_i = 0$$

$i = 1, 2, \dots, K$  (29d)

$$f_i' = b_2 f_i''' + b_3 W_i''' - \frac{n^2}{2R^2} \sum_{j=1}^K [W_{i+j}^{o'} + (1 - \eta_{j-i}^2 + \eta_i)W_{|i-j|}^{o'}] j^2 W_j = 0$$

$i = 1, 2, \dots, 2K$

Antisymmetry: same as SS-3 (29e)

The solution procedure employed is described below.

A generalization of Newton's method (Refs. 20 and 21), applicable to differential equations, is employed to reduce the nonlinear field equations, Eqs. (25) and (26), and appropriate boundary conditions to a sequence of linear systems. In this method, the iteration equations are derived by assuming that the solution is achieved by a small correction to an approximate solution (initially taken as the linear solution). These small corrections are obtained through the solution of the linearized (with respect to the corrections) differential equations.

The linearized differential equations are written in matrix form as follows:

Field equations

$$[R] \{Z''\} + [S] \{Z'\} + [T] \{Z\} = \{g\} \quad (30)$$

Boundary Conditions

$$[\bar{S}] \{Z'\} + [\bar{T}] \{Z\} = \{\bar{g}\} \quad (31)$$

where  $\{Z\}$  is the vector of the  $6K + 2$  unknowns.

$$\{Z\}^T = \{W_0, W_1, \dots, W_K, f_1, f_2, \dots, f_{2K}, W''_0, W''_1, \dots, W''_K, f''_1, f''_2, \dots, f''_{2K}\} \quad (32)$$

Note that  $f_0$  has been eliminated in a manner similar to that of Refs. 13 and 14.

These ordinary differential equations are cast into the form of finite difference equations, and the system of ordinary equations, Eqs. (30) and (31), are changed into a system of linear algebraic equations. The usual central difference formula is used at all mesh points, i.e.

$$Z'_\ell = (Z_{\ell+1} - Z_{\ell-1})/2\Delta \quad (33)$$

$$Z''_\ell = (Z_{\ell-1} - 2Z_\ell + Z_{\ell+1})/\Delta^2$$

Note that the second derivatives in  $W_i$  and  $f_i$  are taken as independent elements of the vector of the unknowns, therefore the second of Eqs. (33) applied only to fourth derivatives of  $W_i$  and  $f_i$ . By using one fictitious point on each side of the cylinder ends one obtains a system of  $(6K + 2) \times (NP + 2)$  difference equations ( $NP$  - number of mesh points).

These equations are:

$$\begin{aligned} [\bar{C}_1] \{Z_0\} + [\bar{B}_1] \{Z_1\} + [\bar{A}_1] \{Z_2\} &= \bar{g}_1 \\ [C_\ell] \{Z_{\ell-1}\} + [B_\ell] \{Z_\ell\} + [A_\ell] \{Z_{\ell+1}\} &= g_\ell; \quad \ell = 1, 2, \dots, NP \\ [\bar{C}_{NP}] \{Z_{NP-1}\} + [\bar{B}_{NP}] \{Z_{NP}\} + [\bar{A}_{NP}] \{Z_{NP+1}\} &= \bar{g}_{NP} \end{aligned} \quad (34)$$



This system is solved by the special algorithm which is reported in Ref. 22.

When the load parameter is at a limit point a unique solution does not exist (the system becomes singular) and thus the solution does not converge. Therefore, the solution procedure goes as follows: first, the system of equations is solved for a small level of the applied load (say 20% of the classical buckling load), then a multiple of this solution is used for a small increase in the load parameter until the process fails to converge. The load level at which the solution fails to converge is taken to be the critical load. Note that, when approaching the limit load, if the increment in the load value is large enough so as to place the systems at equilibrium far beyond the limit point, the system in some cases, does converge. In this case, since the interest is in the limit point value only, one can check the sign of the determinant of the coefficients of the unknown vector. If the sign changes, by taking a large increment in the load level, one must decrease the increment and proceed with the solution. Large increments are used in the procedure in order to save computer time. Because of the use of large increments and since, in some cases, the solution converged at both consecutive steps the criterion of the change in the determinant sign is employed to establish the existence of a critical point within the range of these consecutive steps. At each level of the load for which the system is solved, the value of the number of full circumferential waves is needed. Different values of  $n$  are used to obtain a solution, and the one that minimizes the total potential, Eq. (27), is taken as the correct one (see Refs. 13 and 14). Numerical integration is used to find the total potential.

The number of  $n$  values to be tried at every increment of the load is small, since the circumferential mode does not vary significantly with small increases in the load,  $\bar{N}_{xx}$ . The end shortenings at each level of the applied load are also computed through numerical integration.

## Chapter IV

### APPLICATIONS AND DISCUSSION

The mathematical formulation and the method of solution for the buckling analysis of imperfect, thin, circular, stiffened cylindrical shells under uniform axial compression is presented in Chapters II and III. The methodology is demonstrated through a number of illustrative examples. Numerical solutions are obtained by employing the Georgia Tech high speed digital computer CDC-CYBER 70, Model 74-28. A general program is written (see Appendix B) which includes the following desirable features: (a) it is applicable to stiffened (in either or both directions) geometries as well as unstiffened; (b) it accomodates all possible boundary conditions (SS,CC,FF, etc.), and it can easily be modified to accomodate elastic end restraints; (c) the number of Fourier terms ( $K$ ) can be as large as desired. The same holds true for the number of points (NP) in the finite difference scheme; (d) the geometric imperfection can be axisymmetric as well as an arbitrary symmetric (w.r.t.  $y$ ) one. The program can easily be modified to include other destabilizing loading conditions such as pressure and torsion.

Although the program is highly dimensional because of the number of Fourier terms, number of points and number of required iterations, the solution is obtained with reasonable CPU time. For example, by using  $K = 1$  (one-term) and 65 points (536 unknowns) it requires four seconds to complete one iteration; for the same but  $K = 2$  it requires 15 seconds. For a convergent solution to be obtained at low levels of the applied load two iterations are sufficient. At load levels approaching the limit

point six iterations are needed (convergence: percent difference  $< 10^{-4}$ ).

The numerical results for all the illustrative examples are presented in tabular form in Table 1. A number of these examples are taken from the open literature in order to check the present solution. In addition, new results are generated and the discussion of both is given below. In this table, for each example considered, the buckling load (see columns of  $\bar{N}_{xx_{cr}}$  and  $\bar{N}_{xx_{cr}}/N_{xx_{cl}}$ ) is bracketed between two numbers (denoting the desired accuracy). The first number denotes the highest level of the load for which a convergent solution is obtained and the second number a level higher than the limit point (according to criterion discussed herein). In all examples, the imperfection is taken to be symmetric with respect to  $x = L/2$  and therefore the response is taken to be symmetric. Thus only half of the cylinder is analyzed by employing the appropriate symmetric conditions at  $x = L/2$ . The examples can broadly be classified in one of the following four categories: (a) unstiffened (Examples 1-5); (b) stringer-stiffened (Examples 6-9); (c) ring-stiffened (Examples 10 and 11); and (d) ring- and stringer-stiffened (Examples 12-21). In each of the four categories, at least one case was calculated for two different truncated Fourier series ( $K = 1$  and  $K = 2$ ) and for two different number of points ( $NP = 35$  and  $NP = 65$ ) in order to check the effect of these two parameters on the convergence of the solution.

(a) Unstiffened (Examples 1-5). This geometry is taken from Ref. 16. Only Example 3 is reported in Ref. 16 and the results are in very good agreement. Examples 1, 2, 4 and 5 are considered in order to assess the effect of boundary conditions for this type of an imperfection (see Table

1). It is seen from the results that the effect of in-plane boundary conditions is significant for the simply supported case and insignificant for the clamped case. In Example 2, because of the  $u = C$  in-plane boundary condition, the criterion used for finding  $\bar{N}_{xx_{cr}}$  is that the determinant (see Chapter 3) goes to zero. It can be seen from Fig. 2 that as the sign of the determinant changes the radial mode of deformation changes. The calculations for this case were based on  $K = 1$  and 65 grid points in the axial direction (for half the cylinder length).

(b) Stringer-stiffened (Examples 6-9). The geometry for these examples is taken from Ref. 9 and referred to, in it, as heavy stringers. The present results are in very good agreement with those of Ref. 9. Examples 6 and 7 correspond to  $Z = 95.4$  with external stringers and the imperfection shape is virtually axisymmetric in Example 6, and symmetric in Example 7. The axisymmetric imperfection yields greater reduction than the symmetric one. Note that, for this case, the perfect geometry buckles axisymmetrically. Examples 8 and 9 correspond to  $Z = 394$  with external and internal stringers respectively and an imperfection which is primarily axisymmetric. From these examples one can conclude (as in Ref. 9) that imperfection sensitivity is greatly affected by the curvature parameter  $Z$ , and that externally stiffened configurations are much more sensitive to geometric imperfections than internally stiffened ones. These cases were analyzed with 35 and 65 grid points in the axial direction for half the cylinder length. From these computations one can see (for a typical case, see Tables 2 and 3), that the critical load and the response  $(w, F)$  for each  $n$  are almost the same regardless of the number

of points.

(c) Ring-stiffened (Examples 10 and 11). This geometry is also taken from Ref. 9, and it corresponds to light ring-stiffened cylinders with  $Z = 394$  and external and internal positioning of the rings respectively. Although the numerical results of the present analysis are in good agreement with those of Ref. 9, the conclusion concerning the effect of ring positioning on the sensitivity is reversed. According to the present results internal rings make the overall configuration more sensitive than external rings.

(d) Ring and stringer stiffened (Examples 12-21). These examples are chosen to demonstrate the methodology for ring and stringer stiffened configuration. In addition, the geometries were chosen in such a way that some comparison can be given with stiffened configurations of the only stringer or ring stiffened type. These examples correspond to a geometry for which  $Z = 95.4$ ,  $(e_x/t) = \pm 6$ ,  $(e_y/t) = \pm 3$ ,  $\bar{\lambda}_{xx} = 0.455$ ,  $\bar{\rho}_x = 100$ , and  $\bar{\rho}_y = 20$  (see Table 1). The imperfection shape is taken to be similar to the buckling mode and the imperfection amplitude is varied from half to four times the thickness of the skin. The reader is reminded that the analysis is based on the smeared technique. According to Ref. 9 this configuration without rings is highly sensitive to geometric imperfections when the stringers are positioned on the outside and virtually insensitive for inside positioning of the stringers. The present results (see Table 1) indicate that with the presence of rings the sensitivity is reduced for external stiffeners and aggravated (increased) for internal stiffeners. Examples 12-16 correspond to external stiffening, while

examples 17-21 to internal stiffening. The configuration is checked for a primarily axisymmetric imperfection (examples 12 and 17) as well as symmetric imperfections (remaining examples). The effect of the imperfection amplitude is checked for symmetric imperfections and both external and internal stiffening. This effect is shown graphically on Fig. 3. Fig. 4 shows the plots of load versus "unit and shortening" for three amplitudes of the symmetric imperfection and external stiffeners. Table 2, which corresponds to example 14 but is typical for all examples considered, depicts in tabular form the computational procedure required to arrive at the final results shown in Table 1. From this table one can see that the minimum total potential corresponds to  $n = 4$ . For this  $n$  value, all results are the same for  $NP = 35$  and  $NP = 65$ . In addition, when  $K = 1$  and  $K = 2$ , the critical load differs by 4% or less. Table 3 presents a comparison of response (radial displacement and stress function amplitudes) and critical loads for different  $K$  values (number of Fourier terms) and two different values of  $NP$  (number of grid points).

Table 1: Final Results for Imperfect Unstiffened and Stiffened Cylindrical Shell.

Case	Geometric parameters				Boundary Condition	linear buckling load perfect cylinder		Imperfection $w^0(x,y)$	Nonlinear limit point imperfect cylinder		
	$\tau$	$\frac{e_x}{t}$	$\frac{e_y}{t}$	$\frac{e_z}{t}$		$N_{x_{cl}}$	$n$		$N_{x_{cr}}$	$N_{x_{cr}}/N_{x_{cl}}$	$n$
1	0.004	0	0	0	SS1	14.48*		$-0.5t \cos \frac{2\pi x}{L} + 0.05t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	12.50 ± 14.50	0.860 ± 1.000	12
2	0.004	0	0	0	SS2	14.48*		$-0.5t \cos \frac{2\pi x}{L} + 0.05t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	14.00 ± 16.00	0.967 ± 1.105	15
3	0.004	0	0	0	SS3	25.42		$-0.5t \cos \frac{2\pi x}{L} + 0.05t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	16.50 ± 16.56	0.649 ± 0.651	13
4	0.004	0	0	0	CC1	25.42		$-0.5t \cos \frac{2\pi x}{L} + 0.05t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	16.88 ± 17.00	0.664 ± 0.669	13
5	0.004	0	0	0	CC3	25.42		$-0.5t \cos \frac{2\pi x}{L} + 0.05t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	16.88 ± 17.00	0.664 ± 0.669	13
6	0.04	-15	0	1.82	SS3	123300	0	$2t \sin \frac{\pi x}{L} + 0.2t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	73000 ± 78000	0.592 ± 0.632	7
7	0.04	-15	0	1.82	SS3	123300	0	$2t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	101450 ± 111450	0.823 ± 0.903	1
8	8.175	0.04	-15	0	SS3	58480	5	$2t \sin \frac{\pi x}{L} + 0.2t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	19000 ± 20000	0.325 ± 0.341	12
9	8.175	0.04	-15	0	SS3	24810	3	$2t \sin \frac{\pi x}{L} + 0.2t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	24000 ± 25000	0.967 ± 1.007	3
10	8.125	0.04	0	-3	SS3	3140	2	$0.6t \sin \frac{\pi x}{L} + 0.06t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	1700 ± 1800	0.541 ± 0.573	2
11	8.125	0.04	0	3	SS3	2713	5	$0.6t \sin \frac{\pi x}{L} + 0.06t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	1600 ± 1725	0.589 ± 0.635	2
12	4	0.04	-6	-3	SS3	35220	4	$0.5t \sin \frac{\pi x}{L} + 0.05t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	26500 ± 28000	0.752 ± 0.795	4
13	4	0.04	-6	3	SS3	35220	4	$0.5t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	25000 ± 26500	0.710 ± 0.752	4
14	4	0.04	-6	3	SS3	35220	4	$1.0t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	20500 ± 22000	0.582 ± 0.625	4
15	4	0.04	-6	3	SS3	35220	4	$2.0t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	16000 ± 16750	0.454 ± 0.476	4
16	4	0.04	-6	3	SS3	35220	4	$4.0t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	13000 ± 13500	0.369 ± 0.383	4
17	4	0.04	6	3	SS3	19790	4	$0.5t \sin \frac{\pi x}{L} + 0.05t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	17000 ± 17500	0.859 ± 0.884	4
18	4	0.04	6	3	SS3	19790	4	$0.5t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	17000 ± 17500	0.859 ± 0.884	4
19	4	0.04	6	3	SS3	19790	4	$1.0t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	15250 ± 15630	0.771 ± 0.790	4
20	4	0.04	6	3	SS3	19790	4	$2.0t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	13750 ± 14500	0.695 ± 0.733	4
21	4	0.04	6	3	SS3	19790	4	$4.0t \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$	11200 ± 11400	0.566 ± 0.576	3

\*Estimated as 0.57  $N_{x_{cl}}$  (for SS3) [Ref. 14].

Table 2. Computations for Estimating  $n$  and  $\bar{N}_{xx_{cr}}$   
(Example 14).

$\bar{N}_{xx}$	$\frac{\bar{N}_{xx}}{N_{x_{cl}}}$	$n$	$k$	Points NP	Total Potential	"end shortening"	No. of Iterations	CPU TIME (SEC)
19000	0.54	3	1	35	-10777.	0.021870	3	9
22000	0.62	3	1	35	-14499.	0.025424	4	11
23500	0.67	3	1	35	-16590.	0.027394	4	12
25000	0.71	3	1	35	over limit point			
13000	0.37	4	1	35	- 5028.	0.015124	3	9
16000	0.45	4	1	35	- 7628.	0.018620	3	9
19000	0.54	4	1	35	-10785.	0.022161	4	11
22000	0.62	4	1	35	-14534.	0.026189	6	20
22750	0.65	4	1	35	over limit point			
19000	0.54	4	1	65	-10784.	0.022160	4	19
22000	0.62	4	1	65	-14534.	0.026188	6	33
22750	0.65	4	1	65	over limit point			
19000	0.54	4	2	65	-10789.	0.022232	4	70
20500	0.58	4	2	65	-12590.	0.024197	5	90
22000	0.62	4	2	65	over limit point			
19000	0.54	5	1	35	-10745.	0.022248	4	11
22000	0.62	5	1	35	-14443.	0.025847	4	11
22750	0.65	5	1	35	-15459.	0.026813	5	15
23500	0.67	5	1	35	over limit point			
22000	0.62	6	1	35	-14362.	0.025764	4	11
22000	0.62	7	1	35	-14318.	0.025762	3	9
22000	0.62	12	1	35	-14267.	0.025758	2	7

Table 3. Effect of Number of Fourier Terms and Grid Points on the Response Amplitudes.  
 $w^0(x,y) = b_2 \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$

$\delta_2/t$	K	No. of Points	Examples	$\frac{N_{x_{cr}}}{N_{x_{cl}}}$	$w_0$	$w_1$	$w_2$	$f_1$	$f_2$	$f_3$	$f_4$		
1.0	1	35	14 ↓	0.539	0.009172	0.052284	--	2246.40	-77.13	--	--		
1.0	1	65		0.539	0.009167	0.052270	--	2245.88	-77.12	--	--		
1.0	2	65		0.539	0.009894	0.055149	0.0035991	2306.74	-39.86	-4.55	-0.45		
1.0	1	35		0.625	0.024436	0.096853	--	3976.12	-191.04	--	--		
1.0	1	65		0.625	0.024401	0.096768	--	3973.14	-190.83	--	--		
1.0	2	65		0.582	0.015810	0.074324	0.0058296	3018.11	-60.28	-8.86	-0.12		
1.0	2	65		0.625	over limit point	over limit point	} → 3% Difference						
1.0	1	65		0.646	over limit point	over limit point	} → 3% Difference						
2.0	1	35	15 ↓	0.454	0.026022	0.086314	--	3405.72	-236.92	--	--		
2.0	1	65		0.454	0.026005	0.086281	--	3404.66	-236.86	--	--		
2.0	2	65		0.454	0.034229	0.105602	0.0114593	3699.64	-194.83	-28.22	-0.4501		
2.0	1	35		0.497	over limit point	over limit point	} → 4% Difference						
2.0	1	65		0.497	over limit point	over limit point	} → 4% Difference						
2.0	2	65		0.476	over limit point	over limit point	} → 4% Difference						
4.0	1	35		16 ↓	0.369	0.113547	0.201740	--	4794.98	-1166.29	--	--	
4.0	2	65			0.369	0.132664	0.230965	0.21715	3549.32	-1342.51	-109.53	-1.37	
4.0	1	35	0.383		over limit point	over limit point	} → 4% Difference						
4.0	2	65	0.383		over limit point	over limit point	} → 4% Difference						
1.0	1	35	19 ↓		0.771	0.036821	0.164462	--	1483.81	-447.37	--	--	
1.0	2	65			0.771	0.036716	0.164500	0.002221	1409.59	-461.42	-5.957	-0.0159	
1.0	1	35			0.790	over limit point	over limit point	} → 4% Difference					
1.0	2	65			0.790	over limit point	over limit point	} → 4% Difference					




Fig. 2. Radial Displacement along  $y = 0$  (Example 2).




Fig. 3. Effect of Amplitude of Symmetric Imperfection on the Critical Load (Examples 13-16 and 18-21).




Fig. 4. Load versus "unit end shortening"  
(Examples 13-15).

## Chapter V

### CONCLUSIONS BASED ON THE NONLINEAR BUCKLING ANALYSIS

A methodology for the buckling analysis of imperfect, thin, circular, cylindrical, stiffened shells under uniform axial compression and for various end conditions is presented and demonstrated through a number of examples. On the basis of the results reported herein very few, if any, general conclusions can be drawn. Among these one may list the following:

- (1) It seems that the imperfection sensitivity of generally stiffened configurations strongly depends on the curvature parameter.
- (2) From the examples considered, it appears that configurations with external stiffening are more imperfection sensitive than configurations with internal stiffening.
- (3) The few examples considered seem to support the contention that the most severe shape of imperfection is that which resembles the buckling mode.
- (4) The curve that demonstrates the effect of the imperfection amplitude on the critical load seems to be approaching a finite asymptote (see Fig. 3).
- (5) The presence of both stringers and rings in a configuration alters the conclusions regarding the effects of positioning of the stiffeners and of the curvature parameter on the imperfection sensitivity of a configuration with either strings or rings only. The limited generated data suggests a nonlinear coupling of the individual effects.
- (6) In general one should not expect the wave number,  $n$ , corresponding to the limit point for an imperfect cylinder, to be the same as the one

predicted by the linear analysis of the corresponding perfect geometry. This difference, though, seems to be minimized when the configuration is stiffened in both directions (see Table 1; Examples 12-21).

## Chapter VI

### IMPERFECTION SENSITIVITY OF OPTIMAL CYLINDERS

The formulation of minimum weight design or optimization of stiffened cylinders under destabilizing loads is based on classical (linear) buckling analyses (see References 18 and 23 and references therein). A knockdown factor is used to account for the fact that such geometries are sensitive to geometric imperfections. Such formulation and design procedure is fully described and demonstrated through a number of examples in References 18 and 23.

The precise statement of the problem considered in the above two references (in its most general form) is as follows: Given an internally stiffened thin circular, cylindrical shell of specified material, radius, and length, find the size, shape, and spacings of the stiffeners, and the thickness of the skin such that the resulting configuration can safely carry a given axial compressive load with minimum weight. Since this configuration is sensitive to geometric imperfections, a true solution can be accomplished by incorporating, in the design procedure, a nonlinear buckling analysis (of geometrically imperfect cylinders - as described in Chapters II and III). This task is formidable and it will probably require an unreasonably large amount of computer time.

The reasonable alternate to the above approach is to follow the design procedure employed in References 18 and 23, establish the optimum point in the design space and then perform an imperfection sensitivity analysis (nonlinear buckling analysis) on the optimum point as well as the surrounding design space in order to establish what effect the

different design variables have on the knockdown factor. The design space that needs to be investigated, for a given amplitude of the imperfection (the shape can either be considered the same for all design points, or it can be taken to be as one that leads to the largest reduction in load - see Chapter IV), should be established a priori by employing the following criterion: if for a given problem the optimum weight is 500 lbs., as one moves away from this optimum geometry (variations in the design variables) the weight increases; in addition, it is well accepted that stiffened cylinders are not as sensitive as unstiffened ones (on the basis of available experimental data); therefore, if for a given imperfection the critical load is 60% of the corresponding perfect geometry critical load, (knockdown factor = .6), then the design space in which comparison studies are made should be such that its boundary weight is no larger than, say 50%, of the optimum weight; this way one can find out if whatever is gained by being at an optimum point (on the basis of linear buckling analysis) is not lost because of large variations in the knockdown factor as one moves away from the optimum design point. The only question in this procedure is whether one needs to use one value of the load and one knockdown factor in the linear optimization procedure or several in order to establish how the optimum design point moves in the design space with small variations (10-15%) in the  $\bar{N}_{xx}$  value used in References 18 and 23. This question is dealt with in the section entitled "Recommended Design Procedure."

## 1. Design Examples

This alternate approach is employed herein and it is applied to the following two design cases of References 18 and 23.

Case 1. R = 95.5 in., L = 291 in.,  $\bar{N}_{xx} = 800$  lb/in.,  
(Ref. 18) E =  $10.5 \times 10^6$  psi;  $\rho = 0.101$  lbs/in.<sup>3</sup>,  $\nu = 0.33$ ,  
 $\delta = 0.0442$  in. (imperfection amplitude)  
RSRR (rectangular stringers and rings)  
MG = 0.02 in. (minimum gage constraint)  
Boundary Conditions SS3.

Case 2. R = 85 in., L = 100 in.,  $\bar{N}_{xx} = 2700$  lbs/in.,  
(Ref. 23) E = 10.5 psi,  $\rho = 0.101$  lbs/in.<sup>3</sup>,  $\nu = 0.33$   
 $\delta = 0.1$  in., RSRR (rectangular stringer and rings),  
TSRR (T stringers and rectangular rings with  
 $C_x = 1.079$  and 1.135)  
MG = 0.05 in., Boundary Conditions SS3.

In both cases the imperfection amplitude is almost twice the skin thickness of the optimum geometry. Both cases are checked for an axisymmetric and for a symmetric shape of the imperfection. The results for the latter shape are reported herein, because they yield the greatest sensitivity. This shape is given by

$$w^0(x,y) = \delta \sin \frac{m\pi x}{L} \cos \frac{n\pi y}{R} .$$

Case 1 corresponds to a geometry with rectangular stringers and rings (RSRR) and the optimum design geometry is reported in References 18.

Case 2 corresponds to a geometry with tee stringers and rectangular rings

(optimum stiffener shapes) with various flange width to web height ratios ( $k_x = 0.65, C_x = 1.212$ ;  $k_x = 0.45, C_x = 1.135$ ;  $k_x = 0.30, C_x = 1.079$ ) including the limiting case of  $k_x = 0$  and  $C_x = 1.000$  which corresponds to rectangular stringers. The corresponding geometries are reported in Table 6 of Reference 23.

The results are presented in tabular form and are discussed below.

## 2. Discussion of Results

Case 1. The important results associated with the investigation of Case 1 are presented in Table 4. The minimum weight configuration obtained in Reference 18 is labeled as point 2 on this table. The knockdown factor for this point is found to be 0.9125 and the shape of the imperfection that yields the greatest reduction corresponds to the perfect geometry buckling mode, i.e.,  $m = 17$  and  $n = 9$ . Because of this, the imperfection for all design points in the neighborhood of the optimum is taken to be  $0.0442 \sin \frac{17\pi y}{L} \cos \frac{\pi y}{R}$ , and  $n$  for each point is a free parameter and evaluated such that it yields the most reduction from the classical buckling load. Points 1, 3, and 4 correspond to the optimal geometries for spanning values of the curvature parameter  $Z$ . Note that as  $Z$  decreases the knockdown factor decreases, which means that the thicker the shell the bigger the imperfection sensitivity. By comparing the weights and the knockdown factors for these four points, it can easily be concluded that point 2 geometry is better than the geometry corresponding to points 3 and 4. The only question exists with point 1 geometry since it is less sensitive than that of point 2. But, since the weight of point

1 geometry is heavier than that of point 2 by 5.5% while the knockdown factor is only higher by 2.8%, one might still conclude that the optimal geometry (point 2) is the best even in the presence of imperfection sensitivity. At this point the authors would like to point out that these conclusions do not suffer by keeping  $m = 17$  in the imperfection shape, because points 3 and 4, only, might be affected by letting  $m$  be a free parameter, in which case the knockdown factor for these points might become smaller.

Once the effect of the curvature parameter is established, the investigators considered the effect of the other design parameters, such as extensional and bending stiffnesses ( $\alpha_x, \alpha_y, \lambda_{xx}, \lambda_{yy}$ ). For the  $Z$  value that corresponds to the optimal geometry (point 2) the design space surrounding the optimal point is investigated (in the presence of imperfections) and the comparison of the weights and knockdown factors (points 2a, 2b, 2c, 2d, 2e and 2) supports the conclusion that point 2 yields the minimum weight design even when imperfections are present. In this comparison it is also observed that small variations in all other design parameters, except the curvature parameter  $Z$ , have a very small effect on the knockdown factor. A similar investigation of the surrounding design space of point 1 ( $Z = 41,850$ ) yields the same conclusion (these results are not reported herein).

Case 2. The results of the investigation for this case are reported in Table 5. The imperfections are taken as A)  $w^0 = 0.1 \sin \frac{5\pi x}{L} \cos \frac{\pi y}{R}$  and B)  $w^0 = 0.1 \sin \frac{\pi x}{L} \cos \frac{\pi y}{R}$ . The optimal geometry corresponds to tee stringers and rectangular rings and is labeled as point 1 in Table 5 (see

Table 6 of Ref. 23). Two shapes for the imperfection are considered, one denoted by  $0.1 \sin \frac{5\pi x}{L} \cos \frac{ny}{R}$  and the other by  $0.1 \sin \frac{m\pi x}{L} \cos \frac{ny}{R}$ , where  $m$  in the second is taken to be the classical buckling mode number of half sine waves in the axial direction and  $n$  (in both cases) corresponds to the number of full waves in the circumferential direction that yields the smallest buckling load (in the presence of the imperfection). The imperfection amplitude in both cases is twice the thickness of the optimum geometry. Point 2 corresponds to the optimum geometry at a lower  $Z$  value. For both points (1 and 2) the geometry corresponds to tee stringers and rectangular rings (TSRR). Point 3 employs rectangular stiffeners and corresponds to the optimum geometry for this construction and the same  $Z$  as point 1. Points 1a through 1g correspond to the same construction (TSRR) and  $Z$  value as point 1 but different values of the remaining design parameters  $(\bar{\alpha}_x, \bar{\alpha}_y, \lambda_{xx}, \lambda_{yy}, C_x)$ . Finally, points 3a through 3e correspond to the same construction (RSRR) and  $Z$  value as point 3 but different values of the remaining design parameters.

Optimal geometries corresponding to higher  $Z$  values than point 1; are checked, but since the knockdown factor for these geometries is smaller than that of point 1, the results are not presented herein. This conclusion is the same as that of Case 1.

In making the comparison studies the smallest of the knockdown factors is considered.

In comparing points 1 and 2, the results are inconclusive because the difference in knockdown factors and that of the corresponding weights are approximately the same. This might be interpreted as both geometries

being very close to the optimum for this construction.

A comparison of the data for points 1a-1g with those of point 1 suggests that point 1f might yield a lighter configuration than that of point 1. The reason for this conclusion is based on the observation that the geometry of point 1f is heavier than that of point 1 by 1% while it is less sensitive by approximately 15%.

A similar comparison among the RSRR geometries shows that point 3 geometry is indeed the best geometry (same conclusion as in Case 1).

Finally, a comparison between the two different constructions suggests that the best of either corresponds to an acceptable design. The only thing in favor of the RSRR construction is that, if cost of manufacturing is taken under consideration (additional constraint), then this construction is superior.

Note that in both cases the results of the linear optimization procedure, corresponding to only one value of  $\bar{N}_{xx}$ , are employed. This may cast some doubt to the validity of the conclusion and for this reason an improved design methodology is suggested in the next chapter.

Table 4. Effect of Imperfections on the Optimal Geometry (CASE 1).

$$[w^0(x,y) = 0.0442 \sin \frac{17\pi x}{L} \cos \frac{\pi y}{R}]$$

Point	1	2	3	4	2a	2b	2c	2d	2e
W, lbs.	801	755	760	790	770	789	832	809	792
h, in.	0.02	0.0221052	0.024	0.028	0.0221052	0.0221052	0.0221052	0.0221052	0.0221052
$\bar{\alpha}_x$	21	20	18	15	20	20	20	20	25
$\bar{\alpha}_y$	120	95	85	65	90	85	75	80	55
$\lambda_{xx}$	0.8690	0.6319	0.5276	0.3962	0.6384	0.6578	0.7227	0.6904	0.5711
$\lambda_{yy}$	0.2636	0.2049	0.1833	0.1391	0.2325	0.2546	0.2885	0.2686	0.3493
$\rho_{xx}$	383.23	252.79	170.95	89.15	255.37	263.14	239.09	276.16	356.93
$\rho_{yy}$	3796.40	1848.86	1324.27	587.82	1883.17	1839.20	1522.76	1718.85	1056.60
$e_x$	0.220	0.232	0.228	0.224	0.232	0.232	0.232	0.232	0.287
$e_y$	1.210	1.061	1.032	0.924	1.005	0.951	0.840	0.895	0.619
Z	41850	37870	34880	29894	37870	37870	37870	37870	37870
$N_{x_{cf}}$	800	800	800	800	800	800	300	800	800
$n$	17	17	18	19	17	17	17	17	14
$n$	8	9	10	11	9	9	10	10	10
$N_{x_{cr}}$	755	730	720	695	730	725	735	735	735
$n$	8	9	10	11	9	9	10	10	10
$N_{x_{cr}}/N_{x_{cf}}$	0.9438	0.9125	0.9000	0.8690	0.9125	0.9062	0.9187	0.9187	0.9187

\*The  $\rho$ 's and  $e$ 's can be found from the  $\alpha$ 's and  $\lambda$ 's (see Ref. 18).

Table 5. Effect of Imperfections on the Optimal Geometry (CASE 2).

$$\left[ A; w^0 = 0.1 \sin \frac{5\pi x}{L} \cos \frac{\pi y}{L} \cdot B; w^0 = 0.1 \sin \frac{3\pi x}{L} \cos \frac{\pi y}{L} \right]$$

Point	TS 1	TS 2	TS 3	TS 1a	TS 1b	TS 1c	TS 1d	TS 1e
W, lb.	473	491	486	499	474	484	488	500
h, in.	0.0500	0.0550	0.05	0.05	0.05	0.05	0.05	0.05
$\bar{\alpha}_x$	16	11	12	15	15	17	13	12
$\bar{\alpha}_y$	35	45	60	40	35	35	40	45
$\lambda_{xx}$	0.5386	0.3310	0.4608	0.6629	0.4940	0.5990	0.4525	0.4508
$\lambda_{yy}$	0.1351	0.2128	0.2309	0.0961	0.1804	0.1105	0.2685	0.3119
$\rho_{xx}$ *	137.88	40.04	66.35	149.14	111.14	173.11	76.47	64.91
$\rho_{yy}$	165.45	430.88	831.17	153.74	220.95	135.38	429.66	631.50
$e_x$	0.457	0.354	0.325	0.429	0.429	0.483	0.376	0.349
$e_y$	0.900	1.265	1.525	1.025	0.900	0.900	1.025	1.150
$c_x$	1.079	1.079	1.0	1.079	1.079	1.079	1.079	1.079
Z	2221	2020	2221	2221	2221	2221	2221	2221
Perfect	$N_{x_{cl}}$	2700	2700	2700	2700	2700	2700	2700
	m	4	6	6	4	4	3	5
	n	9	8	7	9	9	9	8
Imp. A	$N_{x_{cr}}$	2215	2175	2275	2215	2175	2306	2145
	n	9	8	7	9	9	9	8
	$\frac{N_{x_{cr}}}{2700}$	0.8204	0.8055	0.8426	0.8204	0.8055	0.8541	0.7944
Imp. B	$N_{x_{cr}}$	2085	2207	2306	2085	2060	2045	2145
	n	9	8	7	9	9	8	8
	$\frac{N_{x_{cr}}}{2700}$	0.7722	0.8174	0.8541	0.7722	0.7630	0.7574	0.7944

Point	TS 1f	TS 1g	RS 4a	RS 4b	RS 4c	RS 4d	RS 4e
W, lb.	482	478	490	488	502	500	408
h, in.	0.05	0.05	0.05	0.05	0.05	0.05	0.05
$\bar{\alpha}_x$	12	12	15	17	12	16	13
$\bar{\alpha}_y$	50	45	45	40	55	35	40
$\lambda_{xx}$	0.4305	0.4406	0.6419	0.6396	0.4329	0.6297	0.4997
$\lambda_{yy}$	0.2736	0.2497	0.0866	0.0581	0.3349	0.1320	0.2876
$\rho_{xx}$ ] *	61.99	63.45	144.42	184.85	62.33	161.20	84.46
$\rho_{yy}$ ]	683.88	505.68	175.28	134.50	1.013.13	161.66	460.14
$e_x$ ]	0.349	0.365	0.400	0.450	0.325	0.425	0.350
$e_y$ ]	1.275	1.150	1.150	1.025	1.400	0.900	1.025
$C_x$	1.079	1.135	1.0	1.0	1.0	1.0	1.0
Z	2221	2221	2221	2221	2221	2221	2221
Perfect	$N_{x_{cl}}$	2700	2700	2700	2700	2700	2700
	m	6	5	4	3	6	4
	n	8	8	9	9	7	9
Imp. A	$N_{x_{cr}}$	2245	2175	2195	2270	2295	2215
	n	8	8	9	10	7	9
	$\frac{N_{x_{cr}}}{2700}$	0.8315	0.8055	0.8130	0.8407	0.8500	0.8204
Imp. B	$N_{x_{cr}}$	2290	2175	2075	2045	2290	2175
	n	8	8	9	8	7	9
	$\frac{N_{x_{cr}}}{2700}$	0.8481	0.8055	0.7685	0.7574	0.8481	0.7722

\* The  $\rho$ 's and  $e$ 's can be found from the  $\bar{\alpha}$ 's,  $\lambda$ 's and  $C_x$ 's. (see Ref. 23).

## Chapter VII

### RECOMMENDED DESIGN PROCEDURE FOR AXIALLY LOADED IMPERFECT STIFFENED CYLINDERS

As is seen from the discussion of the results of the two design cases considered, there are no general trends and conclusions that can be applied to all design problems. In addition, the entire study (presented herein) and the resulting conclusions, as far as the position of the optimum design (including the effect of geometric imperfection) in the design space is concerned, are based on the following conjecture: as the applied load  $\bar{N}_{xx}$  (including a knockdown factor - used in the linear optimization procedure of References 18 and 23) experiences small changes the corresponding linear optimum point shifts smoothly and by small amounts in the design space. For example, if for a given problem the value of  $\bar{N}_{xx}$  changes from 800 to 880 (10% increase) the corresponding optimum design is expected to change from  $Z = 35,000$ ,  $\bar{\alpha}_x = 20$ ,  $\bar{\alpha}_y = 90$ ,  $\lambda_{xx} = 0.64$  and  $\lambda_{yy} = 0.20$  to  $Z = 35,000 + \Delta Z$ ,  $\bar{\alpha}_x = 20 + \Delta\bar{\alpha}_x$ , etc. where the deltas denote changes of less than 10% from the previous values. To further clarify this point and its implications consider the Case I design.

First of all, the optimum (linear optimization) design is characterized by (point 2 of Table 4)  $h = 0.0221$  in.,  $\bar{\alpha}_x = 20$ ,  $\bar{\alpha}_y = 95$ ,  $\bar{\lambda}_{xx} = 0.6319$  and  $\lambda_{yy} = 0.2049$  with a weight equal to 755 lbs. The value of the applied load used is 800 lbs/in. Since, at this geometry, the knockdown factor is 0.9125, then the shell is in reality, designed to carry safely, with minimum weight, a load of 730 lbs/in. ( $\bar{N}_{xx} = [730/\text{knockdown factor}] = 800$ ).

Realizing that the knockdown factor is not known apriori and observing that this factor depends on the particular point in the design space, then different values of  $\bar{N}_{xx}$  must be considered in the entire optimization procedure, before one is able to zero in to the final optimum design point.

Because of this, the following procedure is suggested in order to achieve the minimum weight design for a given applied load (for the sake of argument, say 1000 lbs/in.) in the presence of geometric imperfections.

- a) Specify the maximum allowable amplitude of the geometric imperfection.
- b) Guess the value for the knockdown factor (say 0.8 for the ensuing discussion).
- c) Employ the design procedure of References 18 and 23 with  $\bar{N}_{xx} = (1000/0.8 = 1250)$ , and find the minimum weight design point  $(W, \bar{\alpha}_x, \bar{\alpha}_y, \lambda_{xx}$  and  $\lambda_{yy})$ .
- d) If the actual knockdown factor is within 10% from the guessed value of 0.8, then perform comparison studies as outlined herein.
- e) Repeat steps c) and d) for values of  $\bar{N}_{xx}$  equal to  $1000/(0.72)$  and  $1000/(0.88)$ . An examination of the three comparison studies will yield the optimum configuration within any desired (reasonable) accuracy.
- f) If the actual knockdown factor differs by more than 10% from the guessed value (say 20% lower), then repeat step c) for values of  $\bar{N}_{xx}$  equal to  $1000/(0.55)$ ,  $1000/(0.65)$ , and  $1000/(0.80)$  and perform the comparison studies as mentioned in step e).

By following the above procedure, the designer is assured of arriving at a

minimum weight design, which can carry safely a uniform axial compression of 1000 lbs/in.

## Appendix A

### BUCKLING OF IMPERFECT STIFFENED CYLINDERS UNDER COMBINED AXIAL COMPRESSION AND PRESSURE

The buckling analysis of geometrically imperfect, stiffened, thin, circular, cylindrical shells under uniform axial compression has been presented in Chapters II-IV. The purpose of this Appendix is to show the extension of the analysis for the load cases of hydrostatic pressure, lateral pressure, and combined uniform axial compression with lateral pressure.

Most of the investigations, reported in the open literature which deal with buckling of imperfect configurations, are for uniform axial compression and isotropic, constant thickness geometries. Hutchinson and Amazigo<sup>9</sup> investigated the buckling of imperfect stiffened cylinders (stringer and ring stiffened only) under hydrostatic pressure. There is no reported investigation for stringer and ring stiffened geometries.

The self-equilibrated lateral load  $p(x,y)$  [positive inward] is expanded in terms of Fourier series

$$p(x,y) = \sum_{i=0}^K \bar{p}_i(x) \cos \frac{iny}{R} \quad (A-1)$$

Then all equations in the body of the report must be changed appropriately to reflect the inclusion of this load. For example, the term  $-\bar{p}_0(x)$  must be added to Eq. (26a), the term  $-\bar{p}_i(x)$  to Eq. (26b), and the following term must be added to the total potential expression, Eq. (27).

$$-\pi R \int_0^L \left[ 2\bar{p}_0(x) W_0(x) + \sum_{i=1}^K \bar{p}_i(x) W_i(x) \right] dx$$

The related computer program (Appendix B) includes these changes.

A number of illustrative examples are considered and the results are presented in tabular form (see Table A-1) for uniform pressure only. For all examples, the boundary conditions are taken to be the classical simply supported ones, SS3. The program, though, is written for all types of lateral (clamped, simply supported, free, etc.) as well as in-plane boundary conditions. Some of the examples considered serve as bench marks for the developed methodology and computer program. In addition, new results are reported. For all cases, two types of geometric imperfection are considered which are characterized by  $\xi = 1$  and  $\xi = 2$ . These are:

$$\xi = 1 \quad w^0(x,y) = t \sin \frac{m\pi x}{L} + 0.1t \sin \frac{m\pi x}{L} \cos \frac{ny}{R} \quad (A-2)$$

$$\xi = 2 \quad w^0(x,y) = t \sin \frac{m\pi x}{L} \cos \frac{ny}{R} \quad (A-3)$$

Note that the imperfection characterized by Eq. (A-2) virtually denotes an axisymmetric type of imperfection, while the one characterized by Eq. (A-3) denotes a symmetric type of imperfection. In both cases the amplitude is approximately one skin thickness. The values of m and n that correspond to the most sensitive geometry are reported in Table A-1.

The examples reported have the following common geometry

$$\begin{aligned} L &= 4''; \quad R = 4''; \quad t = 0.04'' \\ \nu &= 0.3; \quad E = 10.5 \times 10^6 \text{ psi}; \quad Z = 95.3 \end{aligned} \quad (A-4)$$

Note that examples 1 and 2 correspond to internal ring stiffening only, examples 3 and 4 to internal stringer stiffening only, examples 5, 6, 8-11 to internal ring and stringer stiffening, and example 7 to external ring and stringer stiffening. In addition, the loading for all the examples is lateral pressure for examples 1, 3, and 5, hydrostatic pressure for examples 2, 4, 6, and 7, axial compression for example 8, and combined loading for examples 9-11 (internal pressure of half and one atmosphere respectively for examples 9 and 10, and external pressure of one atmosphere for example 11).

Examples 2 and 4 are taken from Ref. 9 and the results are in very good agreement.

Among the important observations, on the basis of the generated data, one may list the following:

- 1) For pressure loading the ring only stiffened cylinder is sensitive to geometric imperfections while the stringer only stiffened cylinder is not. This observation is true for lateral pressure ( $\bar{N}_{xx} = 0$ ; examples 1 and 3) as well as hydrostatic pressure ( $\bar{N}_{xx} = pR/2$ ; examples 2 and 4). Furthermore, the presence of the axial load in the case of hydrostatic pressure (compare results of examples 1 to 2 and 3 to 4) aggravates the imperfection sensitivity.
- 2) When stiffening in both directions is used the configuration is still sensitive but not as sensitive as the ring only configuration (compare the results of examples 5 to 1 and 6 to 2).
- 3) It is concluded, in Ref. 9, that positioning the rings on the outside (rings only configuration) makes the shell more sensitive

to geometric imperfections as compared to internal positioning of the rings. This observation is also true for stringer and ring stiffened cylinders (compare the results of example 7 to 6).

- 4) For stiffened cylinders (both rings and stringers) under uniform axial compression with or without lateral pressure the presence of internal or external pressure of up to one atmosphere does not have an appreciable effect on the final results. Linear theory predicts minimal effect, in the right direction (examples 8-11) (negative  $p$  implies internal pressure) and nonlinear theory shows that, for the same imperfection, the sensitivity is not affected by the presence of the small internal or external pressure.
- 5) The buckled shape in the circumferential direction ( $n$ ) is virtually the same for the nonlinear theory in the presence of geometric imperfections, as it is for the perfect geometry linear theory.


Finally, note that all results are derived for one value of the curvature parameter  $Z$  and two stiffener geometries; therefore, no generality should be attached to the above observations. If one is interested in performing extensive parametric studies in order to draw general conclusions the present computer program is very efficient (Appendix B).


Table A-1. Buckling Results of Imperfect Stiffened Cylinders

Example Number	Loading	Geometry						Classical (Linear) Solution				Imperfection Parameter			Nonlinear Solution		
		$\lambda_{xx}$	$\lambda_{yy}$	$e_x/t$	$e_y/t$	$\rho_x$	$\rho_y$	$N_{xx,cr}$	P cr	n	m	$\xi$	$N_{xx,cr}$	P cr	$\frac{N_{xx,cr}}{\text{Classical}}$	n	
1	$\bar{N}_{xx} = 0, P$	0	0.91	0	6	0	100	0	4827	3	1	1	0	3800 - 4000	0.787 - 0.829	3	
2	$\bar{N}_{xx} = \frac{PR}{2}, P$	0	0.91	0	6	0	100	2619	1309	4	6	1	1500 - 1600	750 - 800	0.573 - 0.611	3	
3	$\bar{N}_{xx} = 0, P$	0.91	0	6	0	100	0	0	399	13	1	1	0	550 - 600	1.378 - 1.504	22	
4	$\bar{N}_{xx} = \frac{PR}{2}, P$	0.91	0	6	0	100	0	776	388	13	1	1	900 - 1000	450 - 500	1.160 - 1.290	17	
5	$\bar{N}_{xx} = 0, P$	0.91	0.91	6	6	100	100	0	7060	4	1	2	0	6000 - 6500	0.850 - 0.920	4	
6	$\bar{N}_{xx} = \frac{PR}{2}, P$	0.91	0.91	6	6	100	100	9686	4843	3	1	2	8500 - 9000	4250 - 4500	0.878 - 0.929	3	
7	$\bar{N}_{xx} = \frac{PR}{2}, P$	0.91	0.91	-6	-6	100	100	16200	8100	4	1	2	9000 - 10000	4500 - 5000	0.555 - 0.617	4	
8	$P = 0, \bar{N}_{xx}$	0.91	0.455	6	3	100	20	19790	0	4	1	2	15250 - 15630	0	0.771 - 0.790	4	
9	$P = -7.2, \bar{N}_{xx}$	0.91	0.455	6	3	100	20	19830	-7.2	4	1	2	15000 - 15500	-7.2	0.756 - 0.782	4	
10	$P = -14.4, \bar{N}_{xx}$	0.91	0.455	6	3	100	20	19880	-14.4	4	1	2	15000 - 15500	-14.4	0.755 - 0.780	4	
11	$P = 14.4, \bar{N}_{xx}$	0.91	0.455	6	3	100	20	19690	14.4	4	1	2	15000 - 15500	14.4	0.762 - 0.787	4	

APPENDIX B  
COMPUTER PROGRAM

# I. BLOCK DIAGRAM





## COMMON CARDS

1) Common/CINTG/NEQPOT, MI (500)

NEQPOT - Number of points in axial direction  
MI (500) - The order of Eq. I, MI(I) [according to Ref. 22]

2) COMMON/BOUND/LS1, LSN

Definition of boundary condition at the first point (LS1),  
and at the last point (LSN) of the shell.

3) COMMON/FIDFR/DELTA, AL1, GA1, AL2, BT2, GA2.

Coefficients of finite difference form,  $\Delta$ ,  $\alpha^1 = -1/2\Delta$ ,  
 $\gamma^1 = 1/2\Delta$ ,  $\alpha^2 = \gamma^2 = 1/\Delta^2$ ,  $\beta^2 = -2/\Delta^2$ .

4) COMMON/FOURIR/KFOUR, KG, K4, K3, K2, K1.

Fourier series limit ( $K=KFOUR$ ) and parameters  
dependent on  $K$ .

5) COMMON/GEOM/RR, DD, H<sub>11</sub>, H<sub>12</sub>, H<sub>22</sub>, Q<sub>11</sub>, Q<sub>12</sub>, Q<sub>22</sub>, D<sub>11</sub>, D<sub>12</sub>, D<sub>22</sub>

Shell geometric parameters;  $R, D, h_{ij}, q_{ij}, d_{ij}$  [Eqs. (9)].

6) COMMON/FACTOR/C1, C2, . . . . . C12.


Coefficients which are dependent on circumferential wave number.

7) COMMON/FACT2/DL1-DL4, DA1-DA4, DB2, DB3, DB4, XNI, Exxp.

Coefficients  $\gamma_1, \gamma_2, \gamma_3, \gamma_4, a_1, a_2, a_3, a_4, b_2, b_3, b_4, v, Exxp$ .

- 8) COMMON/CDISK/I21(501),I22(501)  
Direct access data set 21 and 22.
- 9) COMMON/FACT3/DLS,XL,XH.  
parameter,  $XL=L$ ,  $XH=t$ .
- 10) COMMON/PRES1/WM(200,5),ETM(200,5),WMP(200,5)  
The vector of previous solution  $W_m$ ,  $W_m''$ , and  $W_m'$   
at point  $\underline{l}$  for Fourier term  $\underline{i}$ .
- 11) COMMON/PRES2/WZ(200,5),WZP(200,5),WZPP(200,5)  
Imperfection mode  $W^0$ ,  $W^0'$ ,  $W^0''$  at point  $\underline{l}$   
for Fourier term  $\underline{i}$ .
- 12) COMMON/PRES3/FM(200,8),XFM(200,8),FMP(200,8)  
The vector of previous solution  $f_m$ ,  $f_m''$ , and  $f_m'$   
at point  $\underline{l}$  for Fourier term  $\underline{i}$ .
- 13) COMMON/XXLOAD/XPRES  
XPRES - hydrostatic pressure.

## II. FLOW CHART FOR DATA PREPARATION



A1

(cont'd)  
LPRINT 0 = minimum printout ; 1 = maximum printout  
LMOD 0 = does not print modes ; 1 = prints modes  
IDDET 0 = does not calculate determinant  
1 : calculates determinant and prints it.  
AP (12K+4, 12K+4), BP (12K+4, 12K+4), CP (12K+4, 12K+4)  
PR (12K+4, 12K+4), GP (12K+4, 1), XP (12K+4, 1), T1 (12K+4), C (12K+4),  
MT (12K+4), V1 ((12K+4) \* (12K+4)).  
COMMON/PRES1/WM (NEQPOT, K+1), ETA (NEQPOT, K+1), WMP (NEQPOT, K+1).  
COMMON/PRES2/WZ (NEQPOT, K+1), WZP (NEQPOT, K+1), WZPP (NEQPOT, K+1).  
COMMON/PRES3/FM (NEQPOT, 2K), XFM (NEQPOT, 2K), FMP (NEQPOT, 2K).

RR, XL, XH, ELAS, XNI 6E12.4

RR : Radius of the cylinder  
XL : Length of the cylinder  
XH : Thickness of the cylinder  
ELAS : Modulus of Elasticity  
XNI : Poisson's ratio.

A2

A2

XLAMD, YLAMD, EX, EY, RHOX, RHOY

6E12.4

$$XLAMD = \lambda_{xx} = (1-\nu^2)A_x / t l_x$$

$$YLAMD = \lambda_{yy} = (1-\nu^2)A_y / t l_y$$

EX = stringer eccentricity parameter (positive inward)

EY = Ring eccentricity parameter (positive inward)

$$RHOX = \rho_{xx} = EI_{xc} / D l_x$$

$$RHOY = \rho_{yy} = EI_{yc} / D l_y$$

The user must write subroutine IMPERF for the definition of the imperfection and the derivatives.

$$WZ(I, J) = W^0 \quad (\text{positive inward})$$

$$WZP(I, J) = W^{0'}$$

$$WZPP(I, J) = W^{0''}$$

I = 1, NEQPOT mesh point

J = 1, KFOUR+1 for all Fourier terms

Note that since  $W^0 = \sum_{i=0}^K W_i^0(x) \cos \frac{i\pi y}{R}$

then

J=1 for i=0, and J=KFOUR+1 for i=KFOUR

A3

A3

DLND, XNXX, XPRES, DNXP, ACCUR, RI

GE12.4

DLND=1 For fixed lateral pressure  $p$  find  $N_{xcr}$ .

DLND=2 For fixed axial compression  $\bar{N}_{xx}$ , find  $p_{cr}$ .

DLND=3 Axial load and pressure are related by the factor XNXX ( $N_x = XNXX * XPRES$ )

XNXX For DLND=1 is the initial axial load  
For DLND=2 is the fixed axial load.  
For DLND=3 is the factor that relates  $N_{xx}$  and  $p$  (positive XNXX = compression).

XPRES For DLND=1 is the fixed pressure  
For DLND=2,3 is the initial pressure  
(positive inward)

DNXP For DLND=1 is the increment in axial load  
For DLND=2,3 is the increment in pressure

ACCUR The required load accuracy in percent


RI Maximum number of load points

$$* N_x = XNXX + RI * DNXP \text{ (for DLND=1)}$$

$$p = XPRES + RI * DNXP \text{ (for DLND=2,3)}$$

A4

A4



INON

1016

INON = 1

The initial solution for the nonlinear system comes from the linear solution

INON = 2

The initial solution for the nonlinear system (XNXX + DNXP or XPRES + DNXP) is the solution at the previous load level (i.e. XNXX or XPRES).

(It is desirable to take INON = 1.)

A5

A5

NNN, LNNN, ILNW

10I6

NNN - The circumferential wave number,  $n$ . The program finds the limit point for this  $n$ .

LNNN=0: The program does which  $n$  gives the minimum potential energy.

LNNN=1 The program finds the limit point for NNN, and calculates the total potential for values surrounding NNN at load levels lower than limit point (NNN).


LNNN=2 The program calculates the total potential only for the given load XNXX. In this case set XNXX close to the estimated limit point.

ILNW  $\leq$  10 Ten is the maximum number of  $n$ -values for which the program calculates the total potential in order to find the minimum (and corresponding  $n$ ).

For example, if  $n=5$  and ILNW=2 the program calculates the total potential for  $n=5; 6$ .

If  $U_T(n=6) < U_T(n=5)$  then it calculates  $U_T$  for  $n=7$ , if not for  $n=4$ .

A6



III. COMPUTER PROGRAM

```

PROGRAM MAIN(INPUT,OUTPUT,TAPE5=INPUT,TAPE6=OUTPUT,TAPE2),TAPE21
1,TAPE22)
C POST BUCKLING OF STIFFENED CYLINDRICAL SHELLS UNDER UNIFORM AXIAL
C COMPRESSION (NONLINEAR THEORY)
COMMON/CINTG/NEQPOT,MI(500)
COMMON/BOUND/LS1,LSN
COMMON/FIDFR/DELTA,AL1,GA1,AL2,BT2,GA2
COMMON/FOURIR/KFCUR,K6,K4,K3,K2,K1
COMMON/GEOM/RR,DC,H11,H12,H22,Q11,Q12,G22,U11,U12,D22
COMMON/FACTCR/C1,C2,C3,C4,C5,C6,C7,C8,C9,C10,C11,C12
COMMON/FACT2/DL1,DL2,DL3,DL4,DA1,DA2,DA3,DA4,DB2,DE3,DB4,XNI,EXXP
COMMON/CDISK/I21(501),I22(501)
COMMON/FACT3/DL5,XL,XH
COMMON/PRES1/WM(200,5),ETM(200,5),WMP(200,5)
COMMON/PRES2/WZ(200,5),WZP(200,5),WZPP(200,5)
COMMON/PRES3/FM(200,8),XFM(200,8),FMP(200,8)
COMMON/XXLOAD/XPRES
DIMENSION WWM(5),FFM(8)
DIMENSION TI(10)
DIMENSION WF(2,5),XWF(2,5),FF(2,8),XFF(2,8)
DIMENSION AP(52,52),BP(52,52),CP(52,52),PR(52,52),GP(52,1)
DIMENSION XF(52,1),T1(52),CC(52),MT(52),V1(2704)
C 2704=52*52
DIMENSION WCON(20,5),FCON(20,8)
C ALL THE CARDS WITH SIGN ** IN COLUMNS 73,74 DEPEND ON NUMBER
C OF FCINTS AND KFOUR
EQUIVALENCE (AP(1,1),V1(1))
CALL CFENMS(21,I21,501,0)
CALL CFENMS(22,I22,501,0)
ECCNV=0.000001
MAXN=52
MAX2=MAXN*MAXN
NRHS=1
NJ=200
NW=5
NF=8
C NJ,NW,NF - FOR DIMENSION -- NJ=MAXIMUM POINTS IN AXIAL DIRECTION
C NW= MAXIMUM KFOUR+1 , NF= MAXIMUM 2*KFOUR , MAXN=12*KFOUR+4
C IN ORDER TO INCREASE THE CAPABILITY OF THE PROGRAM FOR MANY POINTS IN AXIAL
C DIRECTION AND HIGHER LIMIT OF FCURIER SERIES THE USER HAS TO CHANGE
C ALL THE CARDS WITH THE SIGN ** IN COLUMNS 73 AND 74
1111 WRITE(6,20)
READ(5,10)(TI(I),I=1,9)
WRITE(6,60)
WRITE(6,10)(TI(I),I=1,9)
READ(5,100)NEQPOT,KFOUR,LS1,LSN,LPRINT,LMOD,IDCET
IF(LPRINT.EG.1)LMCC=1
READ(5,200)RR,XL,XH,ELAS,XNI
READ(5,200)XLAMD,YLAMC,EXX,EYY,RHOX,RHOY
EX=-EXX
EY=-EYY
*****
CALL COEFF(EX,EY,XLAMC,YLAMC,RHOX,RHOY,ELAS)
*****
WRITE(6,300)NEQPOT,KFOUR,LS1,LSN
WRITE(6,400)RR,XL,XH,ELAS,XNI,DD,EXXP
WRITE(6,573)XLAMD,YLAMC,EXX,EYY,RHOX,RHOY

```

2

```

C *****
  CALL IMPERF
C *****
  WRITE(6,508)
  DO 85 IK=1,K1
  LK=IK-1
  WRITE(6,510) LK
  WRITE(6,520)
  XX=0.
  DO 85 I1=1,NEQPOT
  WRITE(6,509) I1,XX,WZ(I1,IK),WZF(I1,IK),WZPP(I1,IK)
  XX=XX+DELTA
85 CONTINUE
  IF (LPRINT.NE.1) GO TO 39
  WRITE(6,500) DELTA,AL1,GA1,AL2,BT2,GA2
  WRITE(6,501) H11,H12,H22,Q11,Q12,Q22
  WRITE(6,502) D11,D12,D22,DB2,DB3,DB4
  WRITE(6,503) DL1,DL2,DL3,DL4,CL5
  WRITE(6,504) DA1,CA2,DA3,DA4
39 CONTINUE
  DO 63 I1=1,NEQPOT
  DO 64 J1=1,K1
  WM(I1,J1)=0.
  ETM(I1,J1)=0.
  WMP(I1,J1)=0.
64 CONTINUE
  DO 65 J1=1,K2
  FM(I1,J1)=0.
  XFM(I1,J1)=0.
  FMP(I1,J1)=0.
65 CONTINUE
63 CONTINUE
  READ(5,230) DLND,XNXX,XPRES,DNXX,ACCUR,R11
  IRR=R11
  IF (IRR.EQ.0.) IRR=1
  IDLND=DLND
  CNX=DNXX
  XPRES=XPRES
  XFNX=XNXX
C XFNX=AXIAL COMPRESSION, XPRES=HYDROSTATIC PRESSURE, XNX=EITHER XFNX
C OR XPRES ACCORDING TO IDLND
  GO TO (71,72,73),IDLND
71 WRITE(6,511) XPRES,XFNX,DNX,ACCUR
  XNX=XNXX
  XN11=XNXX
  GO TO 74
72 WRITE(6,512) XFNX,XPRES,DNX,ACCUR
  XNX=XFREE
  XN11=XPRES
  GO TO 74
73 WRITE(6,513) XNXX,XPRES,DNX,ACCUR
  TLMGX=XNXX
  XFNX=TLMGX*XPRES
  XNX=XFREE
  XN11=XPRES
74 TLMGX=1.0, XNX
  TLMGX=1.0, XNXX

```

3

```

      READ(5,100)NNN,LNNN,ILNW
      NWAVE=NNN
C *****
      CALL CCEFNN(NWAVE)
C *****
      WRITE(6,505)NNN
      IF(LPRINT.NE.1) GO TO 49
      WRITE(6,506)C1,C2,C3,C4,C5,C6
      WRITE(6,507)C7,C8,C9,C10,C11,C12
49 CONTINUE
      ILR=0
      LICON=1
      IPOTT=0
      CALL SECOND(TIM1)
      WRITE(6,793)TIM1
      TIM2=TIM1
      TIM4=TIM2
      IINN=0
555 LN=1
      IF(IDLND.EQ.1)XFNX=XNX
      IF(IDLND.EQ.2.OR.IDLND.EQ.3)XPRES=XNX
      IF(IDLND.EQ.3)XFNX=TLMDX*XPRES
      IDET=ICDET
      CALL FCTERS(IDET,NRHS,MAXN,AP,BP,CP,GP,PR,XP,CC,MT,T1,V1,MAX2,
1 IXPM,DETM,XFNX,LN,NJ,NK,NF)
      IF(LPRINT.NE.1) GO TO 101
      CALL SECOND(TIM3)
      TIM1=TIM3-TIM2
      TIM2=TIM3
      TIM4=TIM3
      WRITE(6,201)NWAVE,XFNX,XPRES,TIM1
101 CALL TRANSF(WF,XWF,FF,XFF,NW,NF,2,T1,MAXN,1,LPRINT)
444 IDET=ICDET
      IF(IDLND.EQ.1)XFNX=XNX
      IF(IDLND.EQ.2.OR.IDLND.EQ.3)XPRES=XNX
      IF(IDLND.EQ.3)XFNX=TLMDX*XPRES
      IMAX=1
      WMAX=0.
      ITER=0
      DO 102 J1=1,K1
102 WMAX=WMAX+WM(1,J1)
      DO 103 I1=2,NEQPCT
      WMM=0.
      DO 104 J1=1,K1
104 WMM=WMM+WM(I1,J1)
      IF(ABS(WMM).LE.AES(WMAX)) GO TO 103
      WMAX=WMM
      IMAX=I1
103 CONTINUE
      JWMAX=1
      WWM(1)=WM(IMAX,1)
      AWWW=WWM(1)
      IF(K1.EQ.1) GO TO 1051
      DO 105 J1=2,K1
      WWM(J1)=WM(IMAX,J1)
      IF(ABS(WWM(J1)).LE.ABS(AWWW)) GO TO 105
      AWWW=WWM(J1)

```

4

```

    JWMAX=J1
105 CONTINUE
1051 JFMAX=1
    FFM(1)=FM(IMAX,1)
    AFFM=FFM(1)
    IF(K2.EQ.1) GO TO 333
    DO 106 J1=2,K2
    FFM(J1)=FM(IMAX,J1)
    IF(ABS(FFM(J1)).LE.ABS(AFFM)) GO TO 106
    AFFM=FFM(J1)
    JFMAX=J1
106 CONTINUE
333 LN=2
    ITER=ITER+1
    IF(ITER.LE.10) GO TO 113
    WRITE(6,114)ITER
    GO TO 9999
113 CALL FCTERS(IDET,NRHS,MAXN,AP,BP,CP,GP,PR,XP,CC,MT,T1,V1,MAX2,
1IXPM,DETM,XFNX,LN,NJ,NW,NF)
    IF(LPRINT.NE.1) GO TO 111
    CALL SECOND(TIM3)
    TIM1=TIM3-TIM2
    TIM2=TIM3
    WRITE(6,112)ITER,NWAVE,XFNX,XPRES,TIM1
111 CALL TRANSF(WF,XWF,FF,XFF,NW,NF,2,T1,MAXN,1,LPRINT)
    DO 115 J1=1,K1
    IF(WM(IMAX,J1).NE.0.) GO TO 57
    WCCN(ITER,J1)=0.
    GO TO 115
57 CONTINUE
    WCCN(ITER,J1)=ABS((WM(IMAX,J1)-WWM(J1))/WM(IMAX,J1))
115 CONTINUE
    WCH=WCCN(ITER,JWMAX)
    IWH=JWMAX
    DO 116 J1=1,K2
    IF(FM(IMAX,J1).NE.0.) GO TO 58
    FCCN(ITER,J1)=0.
    GO TO 116
58 CONTINUE
    FCCN(ITER,J1)=ABS((FM(IMAX,J1)-FFM(J1))/FM(IMAX,J1))
116 CONTINUE
    FCH=FCCN(ITER,JFMAX)
    IFH=JFMAX
    IF(LPRINT.NE.1) GO TO 117
    WRITE(6,118)ITER,WCH,FCH
    WRITE(6,119)(J1,WCCN(ITER,J1),J1=1,K1)
    WRITE(6,119)(J1,FCCN(ITER,J1),J1=1,K2)
117 IF(WCH.GT.ECCNV) GO TO 194
    IF(FCH.GT.ECCNV) GO TO 194
    GO TO 195
194 IF(ITER.LE.2) GO TO 196
    IF(WCCN(ITER,IWH).GT.WCON(ITER-1,IWH)) GO TO 197
    IF(FCCN(ITER,IFH).GT.FCON(ITER-1,IFH)) GO TO 197
    GO TO 196
197 IF(XNX.NE.XN11) GO TO 198
    WRITE(6,991)XNX
    GO TO 9999

```

5

```

196 DO 131 J1=1,K1
131 WWM(J1)=WM(IMAX,J1)
   DO 132 J1=1,K2
132 FFM(J1)=FM(IMAX,J1)
   GO TO 333
195 IF(IDLND.EQ.1)XFNX=XNX
   IF(IDLND.EQ.2.OR.IDLND.EQ.3)XFRES=XNX
   IF(IDLND.EQ.3)XFNX=TLMOX*XPRES
   CALL FCTSN(PCT,STRY,STRA,1,1,1,XFNX)
   CALL SECOND(TIM3)
   TIM1=TIM3-TIM4
   TIM2=TIM3
   TIM4=TIM3
   WRITE(6,241)XFNX,XPRES,NWAVE,ITER,TIM1
   WRITE(6,242)POT,STRY,STRA
   IF(IDET.EQ.1) WRITE(6,243)DETM,IXPM
   IF(LMCD.NE.1) GO TO 476
   CALL TRANSF(WF,XWF,FF,XFF,NW,NF,2,T1,MAXN,2,3)
476 CONTINUE
   IF(LNNM.EQ.2.AND.LICON.NE.10) GO TO 566
   IF(LICCN.NE.10) GO TO 629
   ILR=1
   GO TO 777
629 XNX1=XNX
   IINN=IINN+1
   IF(IINN.LE.IRR)GO TO 721
   WRITE(6,722)IINN
   GO TO 9999
721 CONTINUE
   XNX=XNX+DNX
   IF(TXNX.GT.XNX) GO TO 244
   DNX=DNX/2.
   XNX=XNX-DNX
   ADN=DNX*100./XNX
   IINN=IINN-1
   IF(ADN.GT.ACCUR) GO TO 244
   XNX=XNX1
   GO TO 819
244 IF(INCN.EQ.1) GO TO 555
   REWIND 20
   WRITE(20)((WM(I1,J1),J1=1,K1),I1=1,NEQPOT),((ETM(I1,J1),J1=1,K1)
1,I1=1,NEQPOT),((WMP(I1,J1),J1=1,K1),I1=1,NEQPOT),((FM(I1,J1)
2,J1=1,K2),I1=1,NEQPOT),((XFM(I1,J1),J1=1,K2),I1=1,NEQPOT),
3((FMP(I1,J1),J1=1,K2),I1=1,NEQPOT)
   GO TO 444
198 IF(LICCN.NE.10) GO TO 429
   ILR=0
   GO TO 777
429 IF(LNNM.EQ.3) GO TO 249
   IPOTT=IPOTT+1
   IF(IPOTT.GT.1) GO TO 249
   POTT=PCT
   FXNX=XNX-DNX
249 ADN=DNX*100./XNX
   WRITE(6,545)NWAVE,XNX
   TXNX=XNX
   XNX=XNX-DNX

```

```

IINN=0
IF (ADM.LE.ACCUR) GO TO 819
DNX=DNX/2.
XNX=XNX+DNX
IF (INCN.EQ.1) GO TO 555
REWIND 20
READ(20) ((WM(I1,J1),J1=1,K1),I1=1,NEQPOT),((ETM(I1,J1),J1=1,K1)
1,I1=1,NEQPOT),((WMF(I1,J1),J1=1,K1),I1=1,NEQPOT),((FM(I1,J1)
2,J1=1,K2),I1=1,NEQPOT),((XFM(I1,J1),J1=1,K2),I1=1,NEQPOT),
2((FMP(I1,J1),J1=1,K2),I1=1,NEQPOT)
GO TO 444
819 IF (IDLND.EQ.1) XFNX=XNX
IF (IDLND.EQ.2.OR.IDLND.EQ.3) XPRES=XNX
IF (IDLND.EQ.3) XFNX=TLMDX*XPRES
WRITE (6,785) NWAVE, XFNX, XPRES, POT, STRY, STRA
L CALCULATION OF CRITICAL WAVE NUMBER
566 WRITE (6,20)
IF (LNAN.EQ.0) GO TO 9999
WRITE (6,584)
ILR=1
NWPRIN=NWAVE
NWAVE=NWAVE+1
IF (LNAN.EQ.2) POTT=POT
POTMIN=POTT
NMIN=NNN
INWAVE=0
ISTOP=0
I9=0
PCT=PCTT
777 IF (IDLND.EQ.1) XFNX=XNX
IF (IDLND.EQ.2.OR.IDLND.EQ.3) XPRES=XNX
IF (IDLND.EQ.3) XFNX=TLMDX*XPRES
IF (ILF.EQ.1) GO TO 778
WRITE (6,582) NWAVE, XFNX, XPRES
GO TO 9999
778 INWAVE=INWAVE+1
IINN=0
IF (LNAN.EQ.2) PXNX=XNX
XNX=PXNX
LIGON=10
IF (INWAVE.EQ.1) GO TO 391
NWPRIN=NWAVE
IF (I9.EQ.1) GO TO 694
IF (PCTMIN.LE.PCT) GO TO 139
POTMIN=POT
NMIN=NWAVE
NWAVE=NWAVE+1
GO TO 391
139 IF (NWAVE.LE.NNN+1) GO TO 549
ISTOP=1
GO TO 185
549 I9=I9+1
IF (I9.GT.1) GO TO 694
NWAVE=NNN-1
GO TO 391
694 IF (PCTMIN.LE.PCT) GO TO 695
POTMIN=POT

```

7

```

NMIN=NWAVE
NWAVE=NWAVE-1
GO TO 391
695 ISTOP=1
GO TO 185
391 CALL CCEFNN(NWAVE)
CALL SECOND(TIM2)
185 WRITE(6,581)NWFRIN,PXNX,POT,TIM2
IF(NWAVE.LE.0) GO TO 9999
IF(ISTOP.NE.1) GO TO 798
WRITE(6,789)XNX,FOTMIN,NMIN
GO TO 9999
798 IF(INWAVE.GT.ILNK) GO TO 9999
GO TO 555
9999 READ(5,100)LCNTN
IF(LCNTN.EQ.1) GO TO 1111
23 FORMAT(1H1)
10 FORMAT(1H0,9A8)
60 FORMAT(//25H BEGINNING OF NEXT CASE ///)
100 FORMAT(10I6)
200 FORMAT(6E12.4)
300 FORMAT(//,2X,"NO. OF POINTS=",I8,2X,"KFOUR=",I8,2X,"BOUND.CON OF
1POINT 1=",I8,2X,"BOUND.CON OF POINT NEG POT=",I8)
400 FORMAT(//,2X,"F=",E12.4,2X,"XL=",E12.4,2X,"XH=",E12.4,2X,
1"ELAS=",E12.4,2X,"XNI=",E12.4,2X,"UD=",E12.4,2X,"EXXP=",E12.4)
508 FORMAT(//,2X,"THE IMPERFECTION FORM IN AXIAL DIRECTION IS"/)
510 FORMAT(//,2X,"THE IMPERFECTION FOR CIRCUMFERENTIAL WAVE ",I6/)
520 FORMAT(//,4X,"POINT",9X,"LENGTH",12X,"WZ",14X,"WZP",13X,"WZPP"/)
509 FORMAT(I10,4E16.6)
500 FORMAT(//,2X,"DELTA=",E12.4,2X,"AL1=",E12.4,2X,"GA1=",E12.4,2X,
1"AL2=",E12.4,2X,"BT2=",E12.4,2X,"GA2=",E12.4)
501 FORMAT(//,2X,"H11=",E12.4,2X,"H12=",E12.4,2X,"H22=",E12.4,2X,
1"Q11=",E12.4,2X,"Q12=",E12.4,2X,"Q22=",E12.4)
502 FORMAT(//,2X,"D11=",E12.4,2X,"D12=",E12.4,2X,"D22=",E12.4,2X,
1"DB2=",E12.4,2X,"DE3=",E12.4,2X,"DE4=",E12.4)
503 FORMAT(//,2X,"DL1=",E12.4,2X,"DL2=",E12.4,2X,"DL3=",E12.4,2X,
1"DL4=",E12.4,2X,"DL5=",E12.4)
504 FORMAT(//,2X,"DA1=",E12.4,2X,"DA2=",E12.4,2X,"DA3=",E12.4,2X,
1"DA4=",E12.4)
511 FORMAT(//,2X,"FOR FIXED PRESSURE OF ",E12.4,2X,"THE INITIAL AXIAL
1LOAD IS ",E12.4,2X,"THE INCREMENT OF AXIAL LOAD IS ",E12.4/
12X,"AND THE ACCURACY (PERCENT) OF THE AXIAL LOAD IS ",E12.4)
512 FORMAT(//,2X,"FOR FIXED AXIAL LOAD OF ",E12.4,2X,"THE INITIAL HYDR
10STATIC PRESSURE IS",E12.4/2X,"THE INCREMENT OF THE HYDROSTATIC PR
2ESSURE IS",E12.4,2X,"AND THE ACCURACY (PERCENT) OF THE HYDROSTATIC
3 PRESSURE IS",E12.4)
505 FORMAT(//,2X,"THE CIRCUMFERENTIAL WAVE NUMBER=",I6)
506 FORMAT(//,2X,"C1=",E12.4,2X,"C2=",E12.4,2X,"C3=",E12.4,2X,
1"C4=",E12.4,2X,"C5=",E12.4,2X,"C6=",E12.4)
507 FORMAT(//,2X,"C7=",E12.4,2X,"C8=",E12.4,2X,"C9=",E12.4,2X,
1"C10=",E12.4,2X,"C11=",E12.4,2X,"C12=",E12.4)
793 FORMAT(//,2X,"ELAPSED TIME=",E12.4,2X,"SECONDS"/)
201 FORMAT(//,2X,"INITIAL SOLUTION (FROM LINEAR). FOR N=",I8,2X,"NX="
1,E12.4,2X,"F=",E12.4/2X,"TIME COMPUTATION =",E12.4,2X,"SECONDS"/
22X,"=====
3=====")
114 FORMAT(//,2X,"END OF THIS CASE BECAUSE ITER GREATER THAN ",I8)

```



```
SUBROUTINE IMPERF
COMMON/FOURIR/KFCUR,K6,K4,K3,K2,K1
COMMON/CINTG/NEQPOT,MI(500)
COMMON/FACT3/DL5,XL,XH
COMMON/FILFR/DELTA,AL1,GA1,AL2,BT2,GA2
COMMON/PRES2/WZ(200,5),WZP(200,5),WZPP(200,5)
DV=1.
PI=4.*ATAN(DV)
AC=1.0*XH
A1=PI*7./4.
XX=0.
DO 10 I1=1,NEQPOT
WZ(I1,2)=-AC*SIN(A1*XX)
WZP(I1,2)=-AC*A1*CCS(A1*XX)
WZPP(I1,2)=AC*A1*A1*SIN(A1*XX)
WZ(I1,1)=0.
WZP(I1,1)=0.
WZPP(I1,1)=0.
IF(K1.LE.2)GO TO 50
DO 11 J1=3,K1
WZ(I1,J1)=0.
WZP(I1,J1)=0.
WZPP(I1,J1)=0.
11 CONTINUE
50 CONTINUE
XX=XX+DELTA
10 CONTINUE
RETURN
END
```

10

```

SUBROUTINE TRANSF(WF,XWF,FF,XFF,NW,NF,NRF,T1,MAXN,IDER,IPRR)
COMMON/PRES1/WM(200,5),ETM(200,5),WMP(200,5)
COMMON/PRES3/FM(200,8),XFM(200,8),FMP(200,8)
COMMON/FIDFR/DELTA,AL1,GA1,AL2,BT2,GA2
COMMON/CDISK/I21(501),I22(501)
COMMON/CINTG/NEQPOT,MI(500)
COMMON/FOURIR/KFCUR,K6,K4,K3,K2,K1
DIMENSION WF(NRF,NW),XWF(NRF,NW),FF(NRF,NF),XFF(NRF,NF),T1(MAXN)
IF(IPRR.EQ.3) GO TO 278
DO 10 I1=1,NEQPOT
NL=MI(I1)
CALL READMS(22,T1,NL,I1)
IF(I1.NE.1) GO TO 175
DO 11 J1=1,K1
WF(1,J1)=T1(J1)
WM(I1,J1)=T1(J1+K6)
XWF(1,J1)=T1(J1+K3-1)
ETM(I1,J1)=T1(J1+K3+K6-1)
11 CONTINUE
DO 12 J1=1,K2
FF(1,J1)=T1(J1+K1)
FM(I1,J1)=T1(J1+K1+K6)
XFF(1,J1)=T1(J1+K4)
XFM(I1,J1)=T1(J1+K4+K6)
12 CONTINUE
GO TO 10
175 DO 13 J1=1,K1
WM(I1,J1)=T1(J1)
ETM(I1,J1)=T1(J1+K3-1)
13 CONTINUE
DO 14 J1=1,K2
FM(I1,J1)=T1(J1+K1)
XFM(I1,J1)=T1(J1+K4)
14 CONTINUE
IF(I1.NE.NEQPOT) GO TO 10
DO 15 J1=1,K1
WF(2,J1)=T1(J1+K6)
XWF(2,J1)=T1(J1+K3+K6-1)
15 CONTINUE
DO 16 J1=1,K2
FF(2,J1)=T1(J1+K1+K6)
XFF(2,J1)=T1(J1+K4+K6)
16 CONTINUE
10 CONTINUE
IF(IDER.NE.1) GO TO 275
NEQP=NEQPOT-1
DO 20 I1=2,NEQP
DO 21 J1=1,K1
WMP(I1,J1)=AL1*WM(I1-1,J1)+GA1*WM(I1+1,J1)
21 CONTINUE
DO 22 J1=1,K2
FMP(I1,J1)=AL1*FM(I1-1,J1)+GA1*FM(I1+1,J1)
22 CONTINUE
20 CONTINUE
DO 23 J1=1,K1
WMP(1,J1)=AL1*WF(1,J1)+GA1*WM(2,J1)
WMP(NEQPOT,J1)=AL1*WM(NEQP,J1)+GA1*WF(2,J1)

```

```

23 CONTINUE
DO 24 J1=1,K2
FMP(1,J1)=AL1*FF(1,J1)+GA1*FM(2,J1)
FMP(NEQPOT,J1)=AL1*FM(NEQP,J1)+GA1*FF(2,J1)
24 CONTINUE
275 IF(IPRR.NE.1)RETURN
278 CONTINUE
J1=0
WRITE(6,400)J1
WRITE(6,500)
XX=0.
WRITE(6,600)WF(1,1),XWF(1,1)
DO 48 I1=1,NEQPOT
WRITE(6,509)I1,XX,WM(I1,1),WMP(I1,1),ETM(I1,1)
XX=XX+DELTA
48 CONTINUE
WRITE(6,600)WF(2,1),XWF(2,1)
DO 49 J1=1,KFOUR
WRITE(6,400)J1
WRITE(6,500)
WRITE(6,700)WF(1,J1+1),XWF(1,J1+1),FF(1,J1),XFF(1,J1)
DO 51 I1=1,NEQPOT
WRITE(6,609)I1,WM(I1,J1+1),WMP(I1,J1+1),ETM(I1,J1+1),FM(I1,J1),
1FMP(I1,J1),XFM(I1,J1)
51 CONTINUE
WRITE(6,700)WF(2,J1+1),XWF(2,J1+1),FF(2,J1),XFF(2,J1)
49 CONTINUE
DO 52 J1=K1,K2
WRITE(6,400)J1
WRITE(6,500)
WRITE(6,800)FF(1,J1),XFF(1,J1)
DO 53 I1=1,NEQPOT
WRITE(6,709)I1,FM(I1,J1),FMP(I1,J1),XFM(I1,J1)
53 CONTINUE
WRITE(6,800)FF(2,J1),XFF(2,J1)
52 CONTINUE
400 FORMAT(//,2X,"INTERMIDIAT RESULTS FOR KFOUR=",I8/2X,"*****
1*****")
500 FORMAT(//,2X,"POINT",4X,"LENGTH",10X,"W",14X,"WP",13X,"WPP",
112X,"F",14X,"FF",13X,"FPP"/2X,"*****
2*****
3*****")
509 FORMAT(I8,E12.4,3E15.6)
600 FORMAT(//20H FICTIVE POINT E15.6,15X,E15.6//)
609 FOFMAT(I8,12X,6E15.6)
700 FORMAT(//20H FICTIVE POINT E15.6,15X,2E15.6,15X,E15.6//)
800 FORMAT(//65H FICTIVE POINT
1 E15.6,15X,E15.6//)
709 FORMAT(I8,57X,3E15.6)
RETURN
END

```

12

```

SUBROUTINE ABCG(IEG,M1,CF,BF,AF,GF,NRHS,XNXX,LN,NJ,NW,NF)
COMMON/CINTG/NEQPOT,MI(500)
COMMON/BCOND/LS1,LSN
COMMON/FIDFR/DELTA,AL1,GA1,AL2,BT2,GA2
COMMON/FOLPIR/KFCUF,K6,K4,K3,K2,K1
DIMENSION AF(M1,M1),BF(M1,M1),CF(M1,M1),GF(M1,NRHS)
C  NEQPOT=NPOINT (EXCLUDING FICTIVES POINTS)
C  LS1  -KIND OF BOUNDARY CONDITIONS OF POINT 1
C  LSN  -KIND OF BOUNDARY CONDITIONS OF POINT NP
C  NW   - MAXIMUM K+1 FOR DIMENSION WM(NJ,NW)
C  NF   - MAXIMUM 2*K FOR DIMENSION FM(NJ,NF)
      IF(IEG.GT.1) GO TO 10
      CALL RSTG(BF,CF,AF,GF,1,XNXX,M1,NJ,NW,NF,LN,NRHS)
      DO 2 I1=1,K6
      CF(I1+K6,NRHS)=GF(I1,NRHS)
      DO 2 J1=1,K6
      BF(I1+K6,J1)=AL2*BF(I1,J1)+AL1*CF(I1,J1)
      BF(I1+K6,J1+K6)=BT2*BF(I1,J1)+AF(I1,J1)
      BF(I1,J1+K6)=GA2*BF(I1,J1)+GA1*CF(I1,J1)
2     CONTINUE
      CALL ECUNDR(AF,CF,GF,1,XNXX,LS1,M1,NJ,NW,NF,LN,NRHS)
      DO 3 I1=1,K6
      DO 3 J1=1,K6
      BF(I1,J1)=AL1*AF(I1,J1)
      AF(I1+K6,J1)=BF(I1,J1+K6)
      BF(I1,J1+K6)=CF(I1,J1)
      AF(I1,J1)=GA1*AF(I1,J1)
3     CONTINUE
      RETURN
10  IF(IEG.GT.2) GO TO 20
      CALL RSTG(AF,CF,BF,GF,2,XNXX,M1,NJ,NW,NF,LN,NRHS)
      DO 4 I1=1,K6
      DO 4 J1=1,K6
      BF(I1,J1)=BF(I1,J1)+BT2*AF(I1,J1)
      CF(I1,J1+K6)=AL2*AF(I1,J1)+AL1*CF(I1,J1)
      AF(I1,J1)=GA2*AF(I1,J1)+GA1*CF(I1,J1)
      CF(I1,J1)=0.
4     CONTINUE
      RETURN
20  IF(IEG.GE.NEQPOT-1) GO TO 30
      JP=IEG
      CALL RSTG(AF,CF,BF,GF,JP,XNXX,M1,NJ,NW,NF,LN,NRHS)
      DO 5 I1=1,K6
      DO 5 J1=1,K6
      BF(I1,J1)=BF(I1,J1)+BT2*AF(I1,J1)
      TEMP=GA2*AF(I1,J1)+GA1*CF(I1,J1)
      CF(I1,J1)=AL2*AF(I1,J1)+AL1*CF(I1,J1)
      AF(I1,J1)=TEMP
5     CONTINUE
      RETURN
30  IF(IEG.EQ.NEQPOT) GO TO 40
      JP=IEG
      CALL RSTG(AF,CF,BF,GF,JP,XNXX,M1,NJ,NW,NF,LN,NRHS)
      DO 6 I1=1,K6
      DO 6 J1=1,K6
      BF(I1,J1)=BF(I1,J1)+BT2*AF(I1,J1)
      TEMP=GA2*AF(I1,J1)+GA1*CF(I1,J1)

```

13

```

CF(I1,J1)=AL2*AF(I1,J1)+AL1*CF(I1,J1)
AF(I1,J1)=TEMP
AF(I1,J1+K6)=C.
6 CONTINUE
RETURN
40 JP=IEG
CALL RSTG(AF,CF,BF,GF,JP,XNXX,M1,NJ,NW,NF,LN,NRHS)
DO 7 I1=1,K6
CF(I1+K6,NRHS)=GF(I1,NRHS)
DO 7 J1=1,K6
BF(I1,J1)=BF(I1,J1)+BT2*AF(I1,J1)
BF(I1,J1+K6)=GA2*AF(I1,J1)+GA1*CF(I1,J1)
BF(I1+K6,J1)=AL2*AF(I1,J1)+AL1*CF(I1,J1)
7 CONTINUE
CALL BCUNDR(CF,AF,GF,JP,XNXX,LSN,M1,NJ,NW,NF,LN,NRHS)
DO 8 I1=1,K6
TEMP=GF(I1,NRHS)
CF(I1,NRHS)=GF(I1+K6,NRHS)
CF(I1+K6,NRHS)=TEMP
DO 8 J1=1,K6
BF(I1+K6,J1+K6)=GA1*CF(I1,J1)
CF(I1+K6,J1)=AL1*CF(I1,J1)
CF(I1,J1)=BF(I1+K6,J1)
BF(I1+K6,J1)=AF(I1,J1)
8 CONTINUE
RETURN
END

```

```
FUNCTION ALB(I,J,L,B,JP,N2,N3,N4,LL)
C   N4=1 FOR   E(JP,I+J) OR B(JP,I-J)
C   N4=2 FOR B(JP,J)
C   LL=1 FOR W   LL=2 FOR F
COMMON/FOURIR/KFCUP,K6,K4,K3,K2,K1
DIMENSION B(N2,N3)
IF(L.GT.3) GO TO 10
I1=I+J
I2=I1
GO TO 20
10 I1=IAES(I-J)
I2=I1
20 IF(N4.EQ.1) GO TO 120
I2=J
GO TO 100
120 IF(I1.LE.KFOUR) GO TO 100
ALB=0.
RETURN
100 IF(L.LE.3) GO TO 110
ETA=1.
IF(I.EQ.J) ETA=0.
110 GO TO(11,12,13,14,15,16),L
11 R1=I1**2
GO TO 17
12 R1=J**2
GO TO 17
13 R1=2.*I1*J
GO TO 17
14 R1=(2.-ETA)*I1**2
GO TO 17
15 R1=(2.-ETA)*J**2
GO TO 17
16 IF(I-J.LT.0) ETA=-1.
R1=-2.*ETA*J*I1
17 IF(LL.EQ.1) I2=I2+1
ALB=R1*B(JP,I2)
RETURN
END
```

```

SUBROUTINE RSTG(R,S,T,G,JP,XNXX,M1,NJ,NW,NF,LN,NRHS)
C LN=1 FOR LINEAR LN=2 FOR NONLINEAR
C NJ MAXIMUM POINTS IN MERIDIONAL DIRECTION
C NW MAXIMUM KFOUR+1 NF= MAXIMUM 2.*KFOUR
C XNXX AXIAL COMPRESSION LOAD JP= THE POINT IN MERIDIONAL DIRECTION
COMMON/FOURIR/KFCUR,K6,K4,K3,K2,K1
COMMON/GEOM/RR,DD,H11,H12,H22,Q11,G12,G22,D11,D12,D22
COMMON/FACTR/C1,C2,C3,C4,C5,C6,C7,C8,C9,C10,C11,C12
COMMON/PRES1/WM(200,5),ETM(200,5),WMP(200,5)
COMMON/PRES2/WZ(200,5),WZF(200,5),WZPP(200,5)
COMMON/PRES3/FM(200,8),XFM(200,8),FMP(200,8)
COMMON/XXLOAD/XPRES
DIMENSION R(M1,M1),S(M1,M1),T(M1,M1),G(M1,NRHS)
C K6=6*KFOUR+2
C K4=4*KFOUR+2
C K3=3*KFOUR+2
C K2=2*KFOUR
C K1=KFOUR+1
C C9=(NFW/RR)**2
C C1=DD*H11
C C2=2.*DD*H12*C9
C C3=2.*G12*C9
C C4=DD*H22*C9**2
C C5=Q11/D11*C9
C C6=1./(RR*D11)*C9
C C7=C9**2/(2.*C11)
C C8=Q22*C9**2
C C10=C9/2.
C C11=2.*C9*D12
C C12=C22*C9**2
DO 1 I1=1,K6
G(I1,NRHS)=0.
DO 1 J1=1,K6
R(I1,J1)=0.
S(I1,J1)=0.
T(I1,J1)=0.
1 CONTINUE
J1=0
DO 2 I1=K3,K6
T(I1,I1)=1.
J1=J1+1
R(I1,J1)=-1.
2 CONTINUE
C EQUILIBRIUM EQUATION FOR I=C
R(1,K3)=DD*H11+Q11**2/D11
T(1,K3)=2.*Q11/(RR*D11)+XNXX
T(1,1)=1./(RR**2*D11)
G(1,NRHS)=-XNXX*WZFP(JP,1)
G(1,NRHS)=G(1,NRHS)+XPRES
DO 6 J=1,KFOUR
IS=J**2
M=J+1
T(1,K3+J)=T(1,K3+J)-C5/2.*IS*WZ(JP,M)
S(1,J+1)=S(1,J+1)-C5*IS*WZF(JP,M)
T(1,J+1)=T(1,J+1)-IS/2.*(C5*WZFP(JP,M)+C6*WZ(JP,M))
T(1,K4+J)=T(1,K4+J)+C10*IS*WZ(JP,M)
T(1,K1+J)=T(1,K1+J)+C10*IS*WZFP(JP,M)

```

AD-A039 148

GEORGIA INST OF TECH ATLANTA SCHOOL OF ENGINEERING S--ETC F/G 20/11  
THE EFFECT OF INITIAL IMPERFECTIONS ON OPTIMAL STIFFENED CYLIND--ETC(U)  
FEB 77 G J SIMITSES, I SHEINMAN AF-AFOSR-2655-74

UNCLASSIFIED

AFOSR-TR-77-0639

NL

2 of 2  
ADA  
039148



END

DATE  
FILMED  
\* 5-77

```

S(1,K1+J)=S(1,K1+J)+2.*C10*IS*WZP(JP,M)
IF(LN.EQ.1) GO TC 6
T(1,K3+J)=T(1,K3+J)-C5/2.*IS*WM(JP,M)+C10*IS*FM(JP,J)
T(1,J+1)=T(1,J+1)-IS/2.*(C5*ETM(JP,M)+C6*WM(JP,M))
1 +C10*IS*XFM(JP,J)
S(1,J+1)=S(1,J+1)-C5*IS*WMP(JP,M)+2.*C10*IS*FMP(JP,J)
T(1,K4+J)=T(1,K4+J)+C10*IS*WM(JP,M)
T(1,K1+J)=T(1,K1+J)+C10*IS*ETM(JP,M)
S(1,K1+J)=S(1,K1+J)+2.*C10*IS*WMP(JP,M)
G(1,NRHS)=G(1,NRHS)-C5/2.*IS*(WM(JP,M)*ETM(JP,M)+WMP(JP,M)**2)
1 -C6/4.*IS*(WM(JP,M)**2)+C10*IS*(WM(JP,M)*XFM(JP,J)+ETM(JP,M)*
2FM(JP,J)+2.*WMP(JP,M)*FMP(JP,J))
6 CONTINUE
C EQUILIBRIUM EQUATIONS FOR I=1,2,,,,,,KFOUR
DO 3 I1=2,K1
I=I1-1
IS=I**2
IS2=IS**2
T(I1,1)=-C6*IS*WZ(JP,I1)
T(I1,K3)=-C5*IS*WZ(JP,I1)
T(I1,I1)=C4*IS2
T(I1,I1+K1-1)=-C8*IS2
T(I1,I1+K3-1)=-C2*IS+XNXX
T(I1,I1+K4-1)=C3*IS-1./RR
R(I1,I1+K3-1)=C1
R(I1,I1+K4-1)=-Q11
E1=C7*IS*WZ(JP,I1)
G(I1,NRHS)=-XNXX*WZPP(JP,I1)
IF(LN.EQ.1) GO TC 60
T(I1,1)=T(I1,1)-C6*IS*WM(JP,I1)
T(I1,K3)=T(I1,K3)-C5*IS*WM(JP,I1)
T(I1,I1)=T(I1,I1)-IS*(C5*ETM(JP,1)+C6*WM(JP,1))
E1=C7*IS*(WM(JP,I1)+WZ(JP,I1))
E2=C7/2.*IS
E3=E2*WM(JP,I1)
G(I1,NRHS)=G(I1,NRHS)-C5*IS*ETM(JP,1)*WM(JP,I1)
1 -C6*IS*WM(JP,1)*WM(JP,I1)
60 DO 4 J=1,KFCLR
JS=J**2
M=J+1
T(I1,J+1)=T(I1,J+1)+E1*JS*WZ(JP,M)
IF(LN.EQ.1) GO TC 4
T(I1,J+1)=T(I1,J+1)+E1*JS*WM(JP,M)
T(I1,I1)=T(I1,I1)+E2*JS*WM(JP,M)*(WM(JP,M)+2.*WZ(JP,M))
G(I1,NRHS)=G(I1,NRHS)+E1/2.*JS*WM(JP,M)**2+E3*JS*WM(JP,M)
1*(WM(JP,M)+2.*WZ(JP,M))
4 CONTINUE
DO 5 J=1,K2
T(I1,K4+J)=T(I1,K4+J)+C10*(ALB(I,J,1,WZ,JP,NJ,NW,1,1)+
1ALB(I,J,4,WZ,JP,NJ,NW,1,1))
T(I1,K1+J)=T(I1,K1+J)+C10*(ALB(I,J,2,WZPP,JP,NJ,NW,1,1)+
1ALB(I,J,5,WZPP,JP,NJ,NW,1,1))
S(I1,K1+J)=S(I1,K1+J)+C10*(ALB(I,J,3,WZP,JP,NJ,NW,1,1)+
1ALB(I,J,6,WZP,JP,NJ,NW,1,1))
IF(LN.EQ.1) GO TO 5
T(I1,K4+J)=T(I1,K4+J)+C10*(ALB(I,J,1,WZ,JP,NJ,NW,1,1)+
1ALB(I,J,4,WZ,JP,NJ,NW,1,1))

```

```

T(I1,K1+J)=T(I1,K1+J)+C10*(ALB(I,J,2,ETM,JP,NJ,NW,1,1)+
1 ALB(I,J,5,ETM,JP,NJ,NW,1,1))
S(I1,K1+J)=S(I1,K1+J)+C10*(ALB(I,J,3,WMP,JP,NJ,NW,1,1)+
1 ALB(I,J,6,WMP,JP,NJ,NW,1,1))
G(I1,NRHS)=G(I1,NRHS)+C10*((ALB(I,J,1,WM,JP,NJ,NW,1,1)+
1 ALB(I,J,4,WM,JP,NJ,NW,1,1))*XFM(JP,J)+(ALB(I,J,2,ETM,JP,NJ,NW,
21,1)+ALB(I,J,5,ETM,JP,NJ,NW,1,1))*FM(JP,J)+(ALB(I,J,3,WMP,JP,NJ,
3 NW,1,1)+ALB(I,J,6,WMP,JP,NJ,NW,1,1))*FMP(JP,J))
IJ1=I+J
IF(IJ1.GT.KFCUR) GO TO 80
T(I1,IJ1+1)=T(I1,IJ1+1)+C10*(ALB(I,J,1,XFM,JP,NJ,NF,2,2))
T(I1,K3+IJ1)=T(I1,K3+IJ1)+C10*ALB(I,J,2,FM,JP,NJ,NF,2,2)
S(I1,IJ1+1)=S(I1,IJ1+1)+C10*ALB(I,J,3,FMP,JP,NJ,NF,2,2)
80 IJ2=IAES(I-J)
IF(IJ2.GT.KFCUR) GO TO 5
T(I1,IJ2+1)=T(I1,IJ2+1)+C10*ALB(I,J,4,XFM,JP,NJ,NF,2,2)
T(I1,K3+IJ2)=T(I1,K3+IJ2)+C10*ALB(I,J,5,FM,JP,NJ,NF,2,2)
S(I1,IJ2+1)=S(I1,IJ2+1)+C10*ALB(I,J,6,FMP,JP,NJ,NF,2,2)
5 CONTINUE
3 CONTINUE
C COMPATIBILITY EQUATIONS FOR I=1,2,,,,,2KFOUR
E1=C10/2.
I2=K1+1
I3=I2+K2-1
DO 7 I1=I2,I3
I=I1-K1
IS=I**2
R(I1,I1+K4-K1)=D11
T(I1,I1+K4-K1)=-IS*C11
T(I1,I1)=IS**2*C12
IF(I.GT.KFOUR) GO TO 82
R(I1,I1+K3-K1)=Q11
T(I1,I1+K3-K1)=-IS*C3+1./RR
T(I1,I1-K1+1)=IS**2*C8
82 DO 9 J1=1,K1
J=J1-1
T(I1,J1+K3-1)=T(I1,J1+K3-1)-C10*(ALB(I,J,1,WZ,JP,NJ,NW,1,1)+
1ALB(I,J,4,WZ,JP,NJ,NW,1,1))
T(I1,J1)=T(I1,J1)-C10*(ALB(I,J,2,WZPP,JP,NJ,NW,1,1)+
1 ALB(I,J,5,WZPP,JP,NJ,NW,1,1))
S(I1,J1)=S(I1,J1)-C10*(ALB(I,J,3,WZP,JP,NJ,NW,1,1)+
1 ALB(I,J,6,WZP,JP,NJ,NW,1,1))
IF(LN.EQ.1) GO TO 9
T(I1,J1+K3-1)=T(I1,J1+K3-1)-E1*(ALB(I,J,1,WM,JP,NJ,NW,1,1)+
1 ALB(I,J,4,WM,JP,NJ,NW,1,1))
T(I1,J1)=T(I1,J1)-E1*(ALB(I,J,2,ETM,JP,NJ,NW,1,1)+
1 ALB(I,J,5,ETM,JP,NJ,NW,1,1))
S(I1,J1)=S(I1,J1)-E1*(ALB(I,J,3,WMP,JP,NJ,NW,1,1)+
1 ALB(I,J,6,WMP,JP,NJ,NW,1,1))
G(I1,NRHS)=G(I1,NRHS)-E1*((ALB(I,J,1,WM,JP,NJ,NW,1,1)
1+ALB(I,J,4,WM,JP,NJ,
2NW,1,1))*ETM(JP,J1)+(ALB(I,J,2,ETM,JP,NJ,NW,1,1)+ALB(I,J,5,ETM,
3JP,NJ,NW,1,1))*WM(JP,J1)+(ALB(I,J,3,WMP,JP,NJ,NW,1,1)+ALB(I,J,6,
4WMP,JP,NJ,NW,1,1))*WMP(JP,J1))
IJ1=I+J
IF(IJ1.GT.KFCUR) GO TO 83
T(I1,IJ1+1)=T(I1,IJ1+1)-E1*(ALB(I,J,1,ETM,JP,NJ,NW,2,1))

```

18

```
T(I1,K3+IJ1)=T(I1,K3+IJ1)-E1*(ALB(I,J,2,WM,JP,NJ,NW,2,1))
S(I1,IJ1+1)=S(I1,IJ1+1)-E1*ALB(I,J,3,WMP,JP,NJ,NW,2,1)
83 IJ2=IAES(I-J)
   IF(IJ2.GT.KFCUR) GO TO 9
   T(I1,IJ2+1)=T(I1,IJ2+1)-E1*ALB(I,J,4,ETM,JP,NJ,NW,2,1)
   T(I1,K3+IJ2)=T(I1,K3+IJ2)-E1*ALB(I,J,5,WM,JP,NJ,NW,2,1)
   S(I1,IJ2+1)=S(I1,IJ2+1)-E1*ALB(I,J,6,WMP,JP,NJ,NW,2,1)
9  CONTINUE
7  CONTINUE
   RETURN
   END
```

19

```

SUBROUTINE BCUNDR(BS,BT,BG,IN,XNXX,LS,M1,NJ,NW,NF,LN,NRHS)
COMMON/FOURIR/KFCUR,K6,K4,K3,K2,K1
COMMON/PRES1/WM(200,5),ETM(200,5),WMP(200,5)
COMMON/PRES2/WZ(200,5),WZP(200,5),WZPP(200,5)
COMMON/PRES3/FM(200,8),XFM(200,8),FMP(200,8)
COMMON/GEOM/RR,DC,H11,H12,H22,Q11,Q12,Q22,D11,D12,D22
COMMON/FACT12/DL1,DL2,DL3,DL4,DA1,DA2,DA3,DA4,DB2,DB3,DB4,XNI,EXXP
COMMON/FACTOR/C1,C2,C3,C4,C5,C6,C7,C8,C9,C10,C11,C12
DIMENSION BS(M1,M1),BT(M1,M1),BG(M1,NRHS)
C   BCUNDRARY CONDITIONS  BS*Z;+BT*Z=3G
C   LS=1 FOR SS1  W=MX=NXY=NX=0.
C   LS=2 FOR SS2  W=MX=NXY=U=0.
C   LS=3 FOR SS3  W=MX=V=NX=0.
C   LS=4 FOR SS4  W=MX=V=U=0.
C   LS=5 FOR CC1  W=W,X=NXY=NX=0.
C   LS=6 FOR CC2  W=W,X=NXY=U=0.
C   LS=7 FOR CC3  W=W,X=V=NX=0.
C   LS=8 FOR CC4  W=W,X=V=U=0.
C   LS=9 FOR FREE EDGE  NX=NXY=QX=MX=0.
C   LS=10 FOR SYMMETRY  NXY=QX=W,X=U=0.
C   LS=11 FOR ANTISYMMETRY  NX=MX=W=V=0.
C   DALFA=(1.+XLAMD)*(1.+YLAMD)-XNI**2
C   DL1=DD*(1.+PHOX+EX**2*XLAMD*(1.+YLAMD-XNI**2)*12./(XH**2*DALFA))
C   DL2=LD*XNI*(1.+EX*EY*YLAMD*XLAMD*12./(XH**2*DALFA))
C   DL3=EX*XLAMD*(1.+YLAMD)/DALFA
C   DL4=-XNI*EX*XLAMD/DALFA
C   DA1=(1.+YLAMD)/(DALFA*EXXP)
C   DA2=-XNI/(DALFA*EXXP)
C   DA3=-(1.+YLAMD)*EX*XLAMD/DALFA
C   DA4=XNI*EY*YLAMD/DALFA
C   DE2=(1.+XLAMD)/(DALFA*EXXP)
C   DE3=XNI*EX*XLAMD/DALFA
C   DE4=-(1.+XLAMD)*EY*YLAMD/DALFA
C   K6=6*KFOUR+2
C   K4=4*KFCUR+2
C   K3=3*KFCUR+2
C   K2=2*KFCUR
C   K1=KFOUR+1
C   IF(LS.EQ.11)LS=3
C   DO 1 I1=1,K6
C   BG(I1,NRHS)=0.
C   DO 1 J1=1,K6
C   BS(I1,J1)=0.
C   BT(I1,J1)=0.
1 CONTINUE
C   IF(LS.EQ.10) GO TO 888
C   IF(LS.GT.8) GO TO 100
C   DO 2 I1=1,K1
2 BT(I1,I1)=1.
C   IF(LS.LE.4.CF.LS.GT.8) GO TO 100
888 J=0
C   DO 3 I1=K3,K4
C   J=J+1
3 BS(I1,J)=1.
100 IF(LS.GT.4) GO TO 200
C   ET(K3,K3)=1.
C   K31=K3+1

```

```

CO 4 I1=K31,K4
BT(I1,I1)=DL1
BT(I1,I1+K4-K3)=DL4
IF(LS.EQ.1.CF.LS.EG.3) GO TO 4
I=I1-K3
BT(I1,I1+K1-K3)=BT(I1,I1+K1-K3)-I**2*C9*DL3
4 CONTINUE
200 IF(LS.NE.1) GO TO 300
E1=DL4/D11*C10
ES(1,K3)=DL1-DL4/D11*Q11
DO 5 J1=1,KFCUR
JS=J1**2
ES(1,J1+1)=ES(1,J1+1)+E1*JS*WZ(IN,J1+1)
BT(1,J1+1)=BT(1,J1+1)+E1*JS*WZP(IN,J1+1)
ET(1,K1+J1)=ET(1,K1+J1)+C10*JS*WZP(IN,J1+1)
IF(LN.EQ.1) GO TO 5
ES(1,J1+1)=ES(1,J1+1)+E1*JS*WM(IN,J1+1)
ET(1,J1+1)=ET(1,J1+1)+E1*JS*WMP(IN,J1+1)
EG(1,NRHS)=EG(1,NRHS)+E1*JS*WM(IN,J1+1)*WMP(IN,J1+1)
5 CONTINUE
CO 12 I1=2,K1
I=I1-1
BS(I1,I1+K3-1)=BS(I1,I1+K3-1)+DL1
ES(I1,I1+K4-1)=BS(I1,I1+K4-1)+DL4
CO 12 J1=1,K2
BT(I1,K1+J1)=BT(I1,K1+J1)+C10*(ALB(I,J1,2,WZP,IN,NJ,NW,1,1)+
1 ALB(I,J1,5,WZP,IN,NJ,NW,1,1))
12 CONTINUE
300 IF(LS.NE.9) GO TO 400
E1=DL4/D11*Q11
BT(1,K3)=DL1-E1
BS(K3,K3)=DL1-E1
E1=DL4/(D11*RR)
ET(1,1)=-E1
ES(K3,1)=XNXX-E1
BG(K3,NRHS)=-XNXX*WZP(IN,1)
E1=DL4/D11*C10
DO 6 J1=1,KFCUR
JS=J1**2
ET(1,J1+1)=ET(1,J1+1)+E1*JS*WZ(IN,J1+1)
BT(K3,J1+1)=BT(K3,J1+1)+E1*JS*WZP(IN,J1+1)
BS(K3,J1+1)=BS(K3,J1+1)+E1*JS*WZ(IN,J1+1)
IF(LN.EQ.1) GO TO 6
ET(1,J1+1)=ET(1,J1+1)+E1*JS*WM(IN,J1+1)
EG(1,NRHS)=EG(1,NRHS)+E1/2.*JS*WM(IN,J1+1)**2
BT(K3,J1+1)=BT(K3,J1+1)+E1*JS*WMP(IN,J1+1)
BS(K3,J1+1)=BS(K3,J1+1)+E1*JS*WM(IN,J1+1)
BG(K3,NRHS)=BG(K3,NRHS)+E1*JS*WM(IN,J1+1)*WMP(IN,J1+1)
6 CONTINUE
DO 13 I1=2,K1
I=I1-1
IS=I**2
BT(I1,I1+K3-1)=DL1
BT(I1,I1)=-IS*C9*DL2
BT(I1,I1+K4-1)=DL4
BS(I1+K3-1,I1+K4-1)=DL4
BS(I1+K3-1,I1+K3-1)=DL1

```

21

```

BS(I1+K3-1,I1)=-IS*C9*(DL2+2.*CD*(1.-XNI))+XNXX
BG(I1+K3-1,NRHS)=-XNXX*WZF(IN,I1)
13 CCNTINUE
400 I2=K1+1
I3=I2+K2-1
I4=K3-1
DO 7 I1=I2,I3
I=I1-K1
IS=I**2
GO TO (21,22,23,24,21,26,27,28,21,30),LS
21 BS(I1,K1+I)=1.
BT(I1+I4,K1+I)=1.
GO TO 7
22 BS(I1,K1+I)=1.
BS(I1+I4,K4+I)=DB2
DO 8 J1=1,K1
J=J1-1
BS(I1+I4,J1)=BS(I1+I4,J1)-C10*(ALB(I,J,1,WZ,IN,NJ,NW,1,1)+
1ALB(I,J,4,WZ,IN,NJ,NW,1,1))
8 CONTINUE
IF(I.GT.KFOUR) GO TO 7
BS(I1+I4,K3+I)=BS(I1+I4,K3+I)+DB3
BS(I1+I4,I+1)=BS(I1+I4,I+1)-IS*C9*DB4+1./RR
GO TO 7
23 BT(I1,K1+I)=1.
BT(I1+I4,K4+I)=DB2
IF(I.GT.KFOUR) GO TO 7
BT(I1+I4,K3+I)=DB3
GO TO 7
24 BT(I1,K1+I)=-IS*C9*DA2
BT(I1,K4+I)=DB2
BS(I1+I4,K1+I)=-IS*C9*(DA2+2./((1.-XNI)*EXXP))
BS(I1+I4,K4+I)=DB2
DO 9 J1=1,K1
J=J1-1
BS(I1+I4,J1)=BS(I1+I4,J1)-C10*(ALB(I,J,1,WZ,IN,NJ,NW,1,1)+
1ALB(I,J,4,WZ,IN,NJ,NW,1,1))
9 CONTINUE
IF(I.GT.KFOUR) GO TO 7
BT(I1,K3+I)=DB3
BS(I1+I4,K3+I)=DB3
BS(I1+I4,I+1)=BS(I1+I4,I+1)-IS*C9*DB4+1./RR
GO TO 7
26 BS(I1,K1+I)=1.
BS(I1+I4,K4+I)=DB2
IF(I.GT.KFOUR) GO TO 7
BS(I1+I4,K3+I)=DB3
GO TO 7
27 BT(I1,K1+I)=1.
BT(I1+I4,K4+I)=DB2
IF(I.GT.KFOUR) GO TO 7
BT(I1+I4,K3+I)=DB3
GO TO 7
28 BT(I1,K1+I)=-IS*C9*DA2
BT(I1,K4+I)=DB2
BS(I1+I4,K1+I)=-IS*C9*(DA2+2./((1.-XNI)*EXXP))
BS(I1+I4,K4+I)=DB2

```

```
IF(I.GT.KFOUR) GC TO 7
BT(I1,K3+I)=EB3
BS(I1+I4,K3+I)=DB3
GO TO 7
30 BS(I1,K1+I)=1.
   BS(I1+I4,K4+I)=DE2
   DO 14 J1=1,KFOUR
   BT(I1+I4,J1+1)=BT(I1+I4,J1+1)-C19*(ALB(I,J1,2,WZP,IN,NJ,NW,1,1)+
1ALB(I,J1,5,WZP,IN,NJ,NW,1,1))
14 CONTINUE
   BS(I1+I4,K3+I)=BS(I1+I4,K3+I)+DB3
7 CONTINUE
RETURN
END
```

23

```

SUBROUTINE INVERT(NA,A,C,N,NM1,NM2,DET,IXP,IDEI)
DIMENSION A(NM1,NM1),C(NM2),M(NM2)
DET=1.
IXP=0
NN=NA
IF(NN.NE.1) GO TO 303
DET=A(1,1)
A(1,1)=1./A(1,1)
GO TO 304
303 DO 90 I=1,NN
90 M(I)=-I
DO 140 II=1,NN
D=0.00
DO 112 K=1,NN
IF(M(K)) 103,100,112
100 DO 110 L=1,NN
IF(M(L)) 103,103,110
103 IF(ABS(D)-ABS(A(K,L)))105,105,110
105 LD=L
KD=K
D=A(K,L)
BIGA=D
110 CONTINUE
112 CONTINUE
IF(D.EC.0.0) GO TO 170
GO TO 188
170 WRITE(6,502)
STOP
502 FORMAT(/,5X,"DETERMINANT=(")
188 NEMP=-M(LD)
M(LD)=M(KD)
M(KD)=NEMP
DO 114 I=1,NN
C(I)=A(I,LD)
A(I,LD)=A(I,KD)
114 A(I,KD)=0.00
A(KD,KD)=1.00
DO 115 J=1,NN
115 A(KD,J)=A(KD,J)/D
DO 135 I=1,NN
IF(I.EC.KD) GO TO 135
DO 134 J=1,NN
TEMP=C(I)*A(KD,J)
134 A(I,J)=A(I,J)-TEMP
135 CONTINUE
IF(IDEI.NE.1) GO TO 140
DET=DET*BIGA
IF(KD.NE.LD)DET=-DET
529 IF(ABS(DET).LT.1.E+10) GO TO 630
DET=DET/1.E+10
IXP=IXP+10
GO TO 629
630 IF(ABS(DET).GT.1.E-10) GO TO 140
DET=DET*1.E+10
IXP=IXP-10
140 CONTINUE
DO 200 I=1,NN

```

```
L=C  
150 L=L+1  
IF(M(L)-I) 150,160,150  
160 M(L)=M(I)  
M(I)=I  
DO 200 J=1,NN  
TEMP=A(L,J)  
A(L,J)=A(I,J)  
200 A(I,J)=TEMP  
304 RETURN  
END
```

25

```
SUBROUTINE YMY(N1,A,B,C,N2,L1,L2,L3,T)
DIMENSION A(L1,L2),B(L1,L1),C(L1,L2),T(L3)
IF(N2.EQ.1) GO TO 100
DO 11 I=1,N1
DO 10 J=1,N2
TEMP=0.
DO 20 K=1,N1
20 TEMP=TEMP+B(I,K)*C(K,J)
10 T(J)=TEMP
DO 30 J=1,N2
30 A(I,J)=T(J)
11 CONTINUE
RETURN
100 DO 111 I=1,N1
TEMP=0.
DO 120 K=1,N1
120 TEMP=TEMP+B(I,K)*C(K,1)
111 T(I)=TEMP
DO 130 I=1,N1
130 A(I,1)=T(I)
RETURN
END
```

```
SUBROUTINE YSYMY (N2,N1,A,B,C,D,N3,L1,L2,L3,L4,T)
DIMENSION A(L1,L3),B(L1,L3),C(L1,L2),D(L2,L3),T(L4)
  IF(N3.EQ.1) GO TO 100
  DO 11 I=1,N1
  DO 10 J=1,N3
  TEMP=C.
  DO 20 K=1,N2
  20 TEMP=TEMP+C(I,K)*D(K,J)
  10 T(J)=B(I,J)-TEMP
  DO 30 J=1,N3
  30 A(I,J)=T(J)
  11 CONTINUE
  RETURN
100 DO 111 I=1,N1
  TEMP=C.
  DO 120 K=1,N2
  120 TEMP=TEMP+C(I,K)*D(K,1)
  111 T(I)=B(I,1)-TEMP
  DO 130 I=1,N1
  130 A(I,1)=T(I)
  RETURN
  END
```

27

```

SUBROUTINE POTERS(IDET, NRHS, MAXN, AP, BP, CP, GP, PR, XP, C, MT, T1,
1 V1, MAX2, IXFM, DETM, XNXX, LN, NJ, NW, NF)
C MAX2=MAXN*MAXN
COMMON/CINTG/NEQPOT, MI(500)
COMMON/COISK/I21(501), I22(501)
DIMENSION AP(MAXN, MAXN), BP(MAXN, MAXN), CP(MAXN, MAXN)
DIMENSION PR(MAXN, MAXN), GP(MAXN, NRHS), XP(MAXN, NRHS)
DIMENSION T1(MAXN), C(MAXN), MT(MAXN), V1(MAX2)
C EQUIVALENCE (AP(1,1), V1(1))
IXFM=0
DETM=1.
DO 100 I=1, NEQPOT
CALL AECG(I, MAXN, CP, BP, AP, GP, NRHS, XNXX, LN, NJ, NW, NF)
N=MI(I)
IF(I.EQ.1) GO TO 888
NMIN1=MI(I-1)
888 IF(I.EQ.NEQPOT) GO TO 999
NPLUS1=MI(I+1)
999 CONTINUE
IF(I.EQ.1) GO TO 12
CALL YSYMY(NMIN1, N, BP, EP, CP, PR, N, MAXN, MAXN, MAXN, MAXN, T1)
12 CALL INVERT(N, BP, C, MT, MAXN, MAXN, DET, IXF, IDET)
IF(IDET.NE.1) GO TO 640
DETM=DET*DETM
IXFM=IXF+IXFM
IF(ABS(DETM).LT.1.E+10) GO TO 630
DETM=DETM/1.E+10
IXFM=IXFM+10
GO TO 640
630 IF(ABS(DETM).GT.1.E-10) GO TO 640
DETM=DETM*1.E+10
IXFM=IXFM-10
640 CONTINUE
IF(I.EQ.NEQPOT) GO TO 102
CALL YFY(N, PR, BP, AP, NPLUS1, MAXN, MAXN, MAXN, T1)
CALL XWRITE(21, PR, N, NPLUS1, MAXN, MAXN, I, MAX2, V1)
102 IF(I.EQ.1) GO TO 32
CALL YSYMY(NMIN1, N, XP, GP, CP, XP, NRHS, MAXN, MAXN, NRHS, MAXN, T1)
CALL YFY(N, XP, BP, XP, NRHS, MAXN, NRHS, MAXN, T1)
GO TO 42
32 CALL YFY(N, XP, BP, GP, NRHS, MAXN, NRHS, MAXN, T1)
42 CALL XWRITE(22, XP, N, NRHS, MAXN, NRHS, I, MAXN, T1)
100 CONTINUE
NEQPOT=NEQPOT-1
DO 200 K=1, NEQPOT
NK=NEQPOT-K
NMIN1=MI(NK)
N=MI(NK+1)
CALL XREAD(21, PR, NMIN1, N, MAXN, MAXN, NK, MAX2, V1)
CALL XREAD(22, GP, NMIN1, NRHS, MAXN, NRHS, NK, MAXN, T1)
CALL YSYMY(N, NMIN1, XP, GP, PR, XP, NRHS, MAXN, MAXN, NRHS, MAXN, T1)
CALL XWRITE(22, XP, NMIN1, NRHS, MAXN, NRHS, NK, MAXN, T1)
200 CONTINUE
RETURN
END

```

```
SUBROUTINE XREAD(ND,A,L1,L2,M1,M2,IND,M3,VV)
COMMON/CDISK/I21(501),I22(501)
DIMENSION A(M1,M2),VV(M3)
C RECORD IND OF DIRECT ACCESS DATA SET ND IS READ AND ALLOCATED
C BY ROWS INTO L1*L2 PORTION OF MATRIX A
  L3=L1*L2
  CALL READMS(ND,VV,L3,IND)
  KL=0
  DO 10 NROW=1,L1
  DO 10 NCOL=1,L2
  KL=KL+1
  A(NROW,NCOL)=VV(KL)
10 CONTINUE
RETURN
END
```

29

```
SUBROUTINE XWRITE(ND,A,L1,L2,M1,M2,IND,M3,VV)
COMMON/CDISK/I21(501),I22(501)
DIMENSION A(M1,M2),VV(M3)
C L1*L2 PORTION OF MATRIX A IS WRITTEN BY ROWS ON DIRECT ACCESS
C DATA SET ND IN RECORD INC
  KL=0
  DO 10 NROW=1,L1
    DO 10 NCOL=1,L2
      KL=KL+1
      VV(KL)=A(NROW,NCOL)
10 CONTINUE
  CALL WRITMS(ND,VV,KL,IND,-1)
  RETURN
  END
```

30

```

SUBROUTINE POTSN(FCT,STRY,STRA,IP,ISY,ISA,XNXX)
C   FCT   - POTENTIAL ENERGY
C   STRY  - UNIT END SHORTENING FOR Y=0.
C   STRA  - AVERAGE UNIT END SHORTENING
C   IF=1  FOR CALCULATE POT
C   ISY=1  FOR CALCULATE STRY
C   ISA=1  FOR CALCULATE STRA
COMMON/FOURIR/KFCUR,K6,K4,K3,K2,K1
COMMON/GEOM/RR,DC,H11,H12,H22,G11,G12,G22,D11,D12,D22
COMMON/PRES1/WM(200,5),ETM(200,5),WMP(200,5)
COMMON/PRES2/WZ(200,5),WZP(200,5),WZPP(200,5)
COMMON/PRES3/FM(200,8),XFM(200,8),FMP(200,8)
COMMON/FACTR/C1,C2,C3,C4,C5,C6,C7,C8,C9,C10,C11,C12
COMMON/FACT2/DL1,DL2,DL3,DL4,DA1,DA2,DA3,DA4,DE2,DB3,DB4,XNI,EXXP
COMMON/FACT3/CL5,XL,XH
COMMON/CINTG/NEQPOT,MI(500)
COMMON/FIDFR/DELTA,AL1,GA1,AL2,BT2,GA2
COMMON/XXLOAD/XPRES
CE1=C10/2.
CE2=C9**2/2.
CE3=C9/((1.-XNI)*EXXP)
CE4=C9*DD*(1.-XNI)
POT=0.
STRY=0.
STRA=0.
DO 10 I1=1,NEGPOT
E7=1.
IF(I1.EQ.1.OR.I1.EQ.NEGPOT)E7=0.5
E1=-C11*ETM(I1,1)-1./RR*WM(I1,1)
E2=0.
DO 11 J1=1,KFOUR
JS=J1**2
E2=JS*WM(I1,J1+1)*(WM(I1,J1+1)+2.*WZ(I1,J1+1))+E2
11 CONTINUE
E1=E1+CE1*E2
IF(IF.NE.1) GO TO 100
PE1=DE2/D11**2*E1**2+DL1*ETM(I1,1)**2-XNXX*WMP(I1,1)*(WMP(I1,1)+
12.*WZP(I1,1))
PE1=PE1-2.*XPRES*WM(I1,1)
100 E1=E1*DA2/D11+DA3*ETM(I1,1)
IF(ISY.NE.1) GO TO 110
PSY=E1
110 IF(ISA.NE.1) GO TO 120
PSA=E1-WMP(I1,1)*(WMP(I1,1)+2.*WZP(I1,1))/2.
120 IF(ISY.NE.1) GO TO 130
E1=0.
DO 18 J1=1,K1
DO 18 J2=1,K1
E1=WMP(I1,J1)*(WMP(I1,J2)+2.*WZP(I1,J2))+E1
18 CONTINUE
PSY=PSY-E1/2.
E1=0.
E2=0.
DO 14 J1=1,KFOUR
JS=J1**2
E1=ETM(I1,J1+1)+E1
E2=E2+JS*WM(I1,J1+1)

```

```

12 CONTINUE
   PSY=PSY+DA3*E1-DA4*C9*E2
   E1=0.
   E2=0.
   DO 13 J1=1,K2
     JS=J1**2
     E1=E1+XFM(I1,J1)
     E2=E2+JS*FM(I1,J1)
13 CONTINUE
   PSY=PSY+DA2*E1-DA1*C9*E2
   STRY=STRY+PSY*E7
130 IF(ISA.NE.1) GO TO 140
   E1=0.
     DO 14 J1=1,KFOUR
14 E1=E1+WMP(I1,J1+1)*(WMP(I1,J1+1)+2.*WZF(I1,J1+1))
     PSA=PSA-E1/4.
     STRA=STRA+PSA*E7
140 IF(IP.NE.1) GO TO 10
   E1=0.
   E2=0.
   E3=0.
   E4=0.
   E5=0.
   DO 15 J1=1,KFOUR
     JS=J1**2
     JS2=JS**2
     E1=E1+WMP(I1,J1+1)*(WMP(I1,J1+1)+2.*WZF(I1,J1+1))
     E2=E2+JS2*WM(I1,J1+1)**2
     E3=E3+JS*WMP(I1,J1+1)**2
     E4=E4+ETM(I1,J1+1)**2
     E5=E5+JS*WM(I1,J1+1)*ETM(I1,J1+1)
15 CCNTINUE
   PE1=PE1-XNXX*E1/2.+CE2*DL9*E2+CE4*E3+DL1*E4/2.-C9*DL2*E5
   E1=0.
   E2=0.
   E3=0.
   E4=0.
   DO 16 J1=1,K2
     JS=J1**2
     JS2=JS**2
     E1=JS2*FM(I1,J1)**2+E1
     E2=E2+JS*FMP(I1,J1)**2
     E3=E3+XFM(I1,J1)**2
     E4=E4+JS*FM(I1,J1)*XFM(I1,J1)
16 CONTINUE
   PE1=PE1+CE2*DA1*E1+CE3*E2+DB2*E3/2.-DA2*C9*E4
   POT=POT+PE1*E7
10 CONTINUE
   IF(IP.NE.1) GO TO 150
   POT=POT*3.14159*RR*DELTA
150 IF(ISY.NE.1) GO TO 160
   STRY=DA1*XNXX-STRY/XL
160 IF(ISA.NE.1) GO TO 170
   STRA=DA1*XNXX-STRA/XL
170 CONTINUE
   RETURN
   END

```

```

SUBROUTINE CCEFF (EX,EY,XLAMD,YLAMD,RHOX,RHOY,ELAS)
COMMON/GEOM/RR,DC,H11,H12,H22,Q11,Q12,Q22,D11,D12,D22
COMMON/FACT2/DL1,DL2,DL3,DL4,LA1,CA2,DA3,DA4,DE2,DB3,DE4,XNI,EXXP
COMMON/CINTG/NEQPOT,MI(500)
COMMON/FIDFR/DLTA,AL1,GA1,AL2,BT2,GA2
COMMON/FOURIR/KFCUR,K6,K4,K3,K2,K1
COMMON/FACT3/DL5,XL,XH
K6=6*KFOUR+2
K4=4*KFOUR+2
K3=3*KFOUR+2
K2=2*KFOUR
K1=KFCUR+1
XN2=XNI**2
XH2=XH**2
DALFA=(1.+XLAMD)*(1.+YLAMD)-XN2
DD=ELAS*XH**3/(12.*(1.-XN2))
EXXP=ELAS*XH/(1.-XN2)
H11=1.+RHCX+12.*EX**2*XLAMD*(1.+YLAMD-XN2)/(XH2*DALFA)
H22=1.+RHCY+12.*EY**2*YLAMD*(1.+XLAMD-XN2)/(XH2*DALFA)
H12=1.+12.*XNI*EX*EY*XLAMD*YLAMD/(XH2*DALFA)
Q11=XNI*EX*XLAMD/DALFA
Q22=XNI*EY*YLAMD/DALFA
Q12=-0.5*((1.+YLAMD)*EX*XLAMD+(1.+XLAMD)*EY*YLAMD)/DALFA
D11=(1.+XLAMD)/(DALFA*EXXP)
D22=(1.+YLAMD)/(DALFA*EXXP)
D12=((1.+XLAMD)*(1.+YLAMD)-XNI)/(DALFA*EXXP*(1.-XNI))
LL1=DD*H11
DL2=DD*XNI*(1.+(EX*EY*XLAMD*YLAMD*12.)/(XH2*DALFA))
DL3=EX*XLAMD*(1.+YLAMD)/DALFA
DL4=-XNI*EX*XLAMD/DALFA
DL5=DD*H22
DA1=(1.+YLAMD)/(DALFA*EXXP)
DA2=-XNI/(DALFA*EXXP)
DA3=-(1.+YLAMD)*EX*XLAMD/DALFA
DA4=XNI*EY*YLAMD/DALFA
DB2=(1.+XLAMD)/(DALFA*EXXP)
DB3=XNI*EX*XLAMD/DALFA
DB4=-(1.+XLAMD)*EY*YLAMD/DALFA
MI(1)=2*K6
MI(NEQPOT)=2*K6
NEQ1=NEQPOT-1
DO 10 I1=2,NEQ1
MI(I1)=K6
1? CONTINUE
DELTA=XL/(NEQPOT-1)
AL1=-1./(2.*DELTA)
GA1=1./(2.*DELTA)
AL2=1./(DELTA**2)
BT2=-2./DELTA**2
GA2=1./DELTA**2
RETURN
END

```

33

```
SUBROUTINE CCEFNM(NNN)
COMMON/GEOM/RR,DD,H11,H12,H22,Q11,Q12,Q22,D11,D12,D22
COMMON/FACTOR/C1,C2,C3,C4,C5,C6,C7,C8,C9,C10,C11,C12
C9=(NNN/RR)**2
C1=DD*H11
C2=2.*D0*H12*C9
C3=2.*C12*C9
C4=DD*H22*C9**2
C5=Q11/D11*C9
C6=1./(RR*D11)*C9
C7=C9**2/(2.*D11)
C8=Q22*C9**2
C10=C9/2.
C11=2.*C9*D12
C12=D22*C9**2
RETURN
END
```

#### BIBLIOGRAPHY

1. Von Kármán, T. H., Tsien, H. S., "The Buckling of Thin Cylindrical Shells under Axial Compression", J. Aero. Sci., Vol. 8, 1941, pp. 303-312.
2. Michielsen, H. F., "The Behavior of Thin Cylindrical Shells after Buckling under Axial Compression", J. Aero. Sci., Vol. 15, 1948, pp. 738-744.
3. Kempner, J., "Postbuckling Behavior of Axially Compressed Circular Cylindrical Shells", J. Aero. Sci., Vol. 17, 1954, pp. 329-342.
4. Almroth, B. O., "Postbuckling Behavior of Axially Compressed Circular Cylinders", AIAA J., Vol. 1, No. 3, 1963, pp. 630-633.
5. Hoff, N. J., Madson, W. R., and Mayers, J., "The Postbuckling Equilibrium of Axially Compressed Circular Cylindrical Shells", AIAA J., Vol. 4, No. 1, 1966, pp. 126-133.
6. Madson, W. A. and Hoff, N. J., "The Snap-through and Postbuckling Equilibrium Behavior of Circular Cylindrical Shells under Axial Load", SUDAER No. 227, Stanford University, 1965.
7. Koiter, W. T., "On the Nonlinear Theory of Thin Elastic Shells", Koninklijke Nederlandse Akademie Van Wetenschappen, Vol. 69, No. 1, 1966, pp. 1-54.
8. Koiter, W. T., "On the Stability of Elastic Equilibrium", Thesis, Polytechnic Institute at Delft, H. J. Paris, Amsterdam, 1945 (in Dutch).
9. Hutchinson, J. W., and Amazigo, J. C., "Imperfection Sensitivity of Eccentrically Stiffened Cylindrical Shells", AIAA J., Vol. 5, No. 3, 1967, pp. 392-401.
10. Hoff, N. J., "The Perplexing Behavior of Thin Circular Cylindrical Shells in Axial Compression", Israel Journal of Technology, Vol. 4, No. 1, 1966, pp. 1-28.
11. Hutchinson, J. W., and Koiter, W. T., "Postbuckling Theory", Applied Mechanics Reviews, Vol. 13, 1970, pp. 1353-1366.
12. Thielemann, W. F., and Esslinger, M. E., "On the Postbuckling Behavior of Thin Walled Axially Compressed Circular Cylinder of Finite Length", Proc. 70th Anniv. Symp. on the Theory of Shells to Honor Lloyd Hamilton Donnell, edited by D. Muster, Univ. of Houston, Houston, Texas, 1967, pp. 433-479.
13. Narasimhan, K. Y., and Hoff, N. J., "Snapping of Imperfect Thin-Walled Circular Cylindrical Shells of Finite Length", J. Appl. Mech., Vol. 93, No. 1, 1971, pp. 162-171.

14. Narasimhan, K. Y. and Hoff, N. J., "Calculation of the Load Carrying Capacity of Initially Slightly Imperfect Thin Walled Circular Cylindrical Shells of Finite Length", SUDAER No. 329, Stanford University, Dec. 1967.
15. Keller, H., Numerical Method for Two Point Boundary-Value Problems, Blaisdell Publishing Co., Waltham, Mass. 1968.
16. Arboz, J. and Sechler, E. E., "On the Buckling of Axially Compressed Imperfect Cylindrical Shells", J. of Applied Mech., Vol. 41, No. 3, Trans. ASME, Vol. 96, Series E, Sept. 1974, pp. 737-743.
17. Donnell, L. H., "A New Theory for the Buckling of Thin Cylinder Under Axial Compression and Bending", Transactions of the ASME, Vol. 56, No. 11, 1934, p. 795.
18. Simitzes, G. J. and Ungbhakorn, V., "Minimum Weight Design of Stiffened Cylinders under Axial Compression", AIAA J., Vol. 13, No. 6, 1975, pp. 750-755.
19. Sheinman, I., and Tene, Y., "Buckling in Segmented Shells of Revolution Subjected to Symmetric and Antisymmetric Loads", AIAA J., Vol. 12, No. 1, 1974, pp. 15-20.
20. Thurston, G. A., "Newton's Method Applied to Problems in Nonlinear Mechanics", J. Appl. Mech., Vol. 32, No. 2, 1965, pp. 383-388.
21. Thurston, G. A., and Freeland, M. A., "Buckling Imperfect Cylinders under Axial Compression", NASA CR-541, July 1966.
22. Tene, Y., Epstein, M. and Sheinman, I., "A Generalization of Potter's Method", Computers Structures, Vol. 4, 1974, pp. 1099-1103.
23. Simitzes, G. J., and Ungbhakorn, V., "Weight Optimization of Stiffened Cylinders Under Axial Compression", Computers and Structures, Vol. 5, 1975, pp. 305-314.