

AD-A039 682

LEHIGH UNIV BETHLEHEM PA CENTER FOR THE APPLICATION--ETC F/6 20/11
ON THE SPEED OF PROPAGATION OF WAVES IN A DEFORMED ELASTIC MATE--ETC(U)
APR 77 K N SAWYERS, R S RIVLIN

N00014-76-C-0235


UNCLASSIFIED

CAM-100-27

NL

OF /
ADA
039682





NATIONAL BUREAU OF STANDARDS
MICROCOPY RESOLUTION TEST CHART

AD A 039682

AD NO. DDC FILE COPY




**Lehigh
University**

12
NY

ON THE SPEED OF PROPAGATION OF WAVES IN
A DEFORMED ELASTIC MATERIAL

by

K.N. SAWYERS and R.S. RIVLIN



TECHNICAL REPORT NO.

CAM-100-27

April 1977

OFFICE OF NAVAL RESEARCH CONTRACT NO. N00014-76-C-0235

**Center for the
Application of
Mathematics
(CAM)**

see 1473

On the Speed of Propagation of Waves
in a Deformed Elastic Material

by

K.N. Sawyers and R.S. Rivlin
Center for the Application of Mathematics
Lehigh University, Bethlehem, Pa.

ABSTRACT

The secular equation is obtained for small amplitude waves propagated in an arbitrary direction in a body of incompressible isotropic elastic material subjected to a pure homogeneous deformation. Conditions are obtained that the wave speeds be real.

ACCESSION for		
NTIS	White Section	☒
DDC	Buff Section	☐
UNANNOUNCED		☐
JUSTIFICATION		
BY		
DISTRIBUTION AVAILABILITY CODES		
Dist.	Avail.	Special
A		

1. Introduction

In a previous paper [1], we have considered the propagation of plane sinusoidal waves of infinitesimal amplitude in an incompressible isotropic elastic material which is subjected to an initial static pure homogeneous deformation. There the secular equation was obtained for waves propagated in an arbitrary direction in a principal plane of the pure homogeneous deformation. The requirement that the wave speeds be real for all such directions of propagation led to certain necessary and sufficient conditions on the form of the strain-energy function w . These conditions are expressed by equations (4.6) below with the notation of (3.13). The conditions $(4.6)_1$ were previously given by Baker and Ericksen [2], while the conditions $(4.6)_2$ were not, we believe, previously known.

In another paper [3], we conjectured that more stringent conditions on w than those in (4.6) might arise from the requirement that the wave speeds be real for arbitrary direction of propagation, not necessarily in a principal plane of the static pure homogeneous deformation. It is argued here (§5) that this is certainly not true in the case when two of the principal extension ratios are equal.

In the present paper we obtain the secular equation for waves propagated in an arbitrary direction in the deformed material. From it we easily obtain necessary and sufficient conditions that the wave speeds be real. However, these conditions involve not only the principal extension ratios and the derivatives of w with respect to the strain invariants,

but also the direction of wave propagation. We have not, so far, been able to obtain the necessary and sufficient conditions in a form which is independent of this direction for arbitrary strain-energy functions and arbitrary values of the principal extension ratios associated with the pure homogeneous deformation.

However, in §6, it is shown that for strain-energy functions of the Mooney-Rivlin type, the Baker-Ericksen conditions provide necessary and sufficient conditions for the velocities of waves propagated in an arbitrary direction to be real. Essentially the same result was previously obtained by Ericksen [4] in his study of the propagation of a second-order discontinuity in an incompressible isotropic elastic material.

Finally, in §7 it is shown that if w depends on only one of the two strain invariants i_1 and i_2 , defined in (2.4), then the restrictions expressed by equations (4.6) are necessary and sufficient that the wave speeds be real for arbitrary direction of propagation.

2. Basic equations

We consider a body of incompressible isotropic elastic material subjected to a pure homogeneous deformation with extension ratios $\lambda_1, \lambda_2, \lambda_3$ and principal directions parallel to the axes of a rectangular cartesian coordinate system x . In this deformation, a particle which initially has vector position ξ with respect to the origin of the system x moves to vector position X , where

$$\underline{X} = \underline{\Lambda} \underline{\xi}, \quad \underline{\Lambda} = \text{diag}(\lambda_1, \lambda_2, \lambda_3) \quad (2.1)$$

and

$$\det \underline{\Lambda} = \lambda_1 \lambda_2 \lambda_3 = 1. \quad (2.2)$$

We now assume that a plane sinusoidal wave of small amplitude propagates in the deformed material. With the usual complex notation, the vector displacement $\underline{u}$ may be written in the form

$$\underline{u} = \underline{U} \exp_1[\omega(\underline{S} \cdot \underline{X} - t)] , \quad (2.3)$$

where $\underline{U}$ is a constant vector, ω is the angular frequency of the wave, $\underline{S}$ is its complex slowness and $\underline{\ell}$ is a unit vector in the direction of propagation.

For an incompressible isotropic elastic material, subjected to a deformation in which a particle initially at $\underline{\xi}$ moves to $\underline{x}$ at time t , the strain-energy w , measured per unit volume, is expressible as a function of i_1 and i_2 , thus

$$w = w(i_1, i_2) , \quad (2.4)$$

where i_1 and i_2 are defined by

$$i_1 = \text{tr } \underline{c} , \quad i_2 = \frac{1}{2}[(\text{tr } \underline{c})^2 - \text{tr } \underline{c}^2] , \quad (2.5)$$

and $\underline{c} = \| c_{ij} \|$ is the Fingerstrain matrix, referred to the system x , defined by

$$c_{ij} = x_{i,\alpha} x_{j,\alpha} . \quad (2.6)$$

x_i and ξ_α are the components of $\underline{x}$ and $\underline{\xi}$ in the system x and $_{,\alpha}$ denotes differentiation with respect to ξ_α . Correspondingly, the Cauchy stress matrix $\underline{\sigma} = \| \sigma_{ij} \|$, referred to the system x , is given by

$$\underline{\sigma} = 2[(w_1 + i_1 w_2) \underline{c} - w_2 \underline{c}^2] - p \underline{\delta} , \quad (2.7)$$

where p is an arbitrary hydrostatic pressure, $\underline{\delta}$ is the unit matrix, and the notation

$$w_1 = \partial w / \partial i_1 , \quad w_2 = \partial w / \partial i_2 \quad (2.8)$$

is used. Since the material considered is incompressible, the deformation gradients $x_{i,\alpha}$ must satisfy the condition

$$\det |x_{i,\alpha}| = 1 . \quad (2.9)$$

We now assume that

$$\tilde{x} = \tilde{X} + \text{Re } \tilde{u} = \Lambda \tilde{\xi} + \text{Re } \tilde{u} , \quad (2.10)$$

where $\tilde{u}$ is given by (2.3) and is assumed to be sufficiently small so that we can linearize in it. We then obtain [1] from (2.7) and the equations of motion, the following equation

$$S^2(Q_{ij} - Q\delta_{ij})\ell_j = \rho U_i , \quad (2.11)$$

where Q is an arbitrary constant and Q_{ij} is defined by

$$Q_{ij} = R_{ijk}U_k , \quad (2.12)$$

with*

$$\begin{aligned} R_{ABC} = & 2\{[W_1 + (I_1 - \lambda_A^2 - \lambda_B^2)W_2](\lambda_A^2\ell_A\delta_{BC} + \lambda_B^2\ell_B\delta_{AC}) \\ & + 2\lambda_A^2\lambda_C^2\ell_C[W_2 + W_{11} + (2I_1 - \lambda_A^2 - \lambda_C^2)W_{12} \\ & + (I_1 - \lambda_A^2)(I_1 - \lambda_C^2)W_{22}]\delta_{AB}\} . \end{aligned} \quad (2.13)$$

In (2.13) the notation

$$\begin{aligned} I_1 &= i_1|_{\tilde{u}=0} , \quad I_2 = i_2|_{\tilde{u}=0} , \\ W_1 &= \frac{\partial W}{\partial I_1}|_{\tilde{u}=0} , \quad W_2 = \frac{\partial W}{\partial I_2}|_{\tilde{u}=0} , \\ W_{11} &= \frac{\partial^2 W}{\partial I_1^2}|_{\tilde{u}=0} , \quad \text{etc.} \end{aligned} \quad (2.14)$$

is used.

* The summation convention is not applied to upper case Latin subscripts.

In a similar manner, we obtain from (2.9), (2.10) and (2.3),

$$U_i \ell_i = 0 . \quad (2.15)$$

In the previous paper [1], we used (2.11) and (2.15) to obtain the secular equation for S in the particular case when the wave propagates in a principal plane of the pure homogeneous deformation, i.e. when either ℓ_1 , ℓ_2 , or ℓ_3 is zero. In the next section, we obtain the secular equation without this restriction.

3. The secular equation

We can eliminate Q from equation (2.11) by multiplying it throughout by $\epsilon_{mni} \ell_n$ where ϵ_{mni} is the alternating symbol. We then obtain

$$\epsilon_{mni} \sigma Q_{ij} \ell_n \ell_j = \epsilon_{mni} \ell_n U_i, \quad (3.1)$$

where we have introduced the notation

$$\sigma = S^2 / \rho. \quad (3.2)$$

Introducing (2.12) into (3.1), we obtain

$$\bar{R}_{mk} U_k = 0 \quad (3.3)$$

where

$$\bar{R}_{mk} = \epsilon_{mni} (\sigma R_{ijk} \ell_j - \delta_{ik}) \ell_n. \quad (3.4)$$

We note that the three equations represented by (3.3) are not linearly independent, since $\bar{R}_{mk} \ell_m$ is identically zero.

Taking $m = 1$ and 2 in (3.3), we have two equations

$$\bar{R}_{1k} U_k = 0, \quad \bar{R}_{2k} U_k = 0. \quad (3.5)$$

The necessary and sufficient condition for (3.5) and (2.15) to yield a non-trivial solution for U_k is

$$\varepsilon_{ijk} \bar{R}_{1j} \bar{R}_{2k} l_i = 0 . \quad (3.6)$$

With (3.4) this can be rewritten as

$$\bar{\alpha} \sigma^2 - \bar{\beta} \sigma + \bar{\gamma} = 0 , \quad (3.7)$$

where

$$\begin{aligned} \bar{\alpha} &= \varepsilon_{ijk} \varepsilon_{lmn} \varepsilon_{2rs} R_{npj} R_{sqk} l_p l_q l_m l_r l_i , \\ \bar{\beta} &= \varepsilon_{ijk} \varepsilon_{lmn} \varepsilon_{2rs} (R_{npj} l_p \delta_{sk} + R_{sqk} l_q \delta_{nj}) l_m l_r l_i , \\ \bar{\gamma} &= \varepsilon_{ijk} \varepsilon_{lmj} \varepsilon_{2rk} l_i l_m l_r . \end{aligned} \quad (3.8)$$

After some algebraic manipulation, we obtain

$$\begin{aligned} \bar{\alpha} &= l_3 \varepsilon_{ijk} l_i l_p l_q (l_1 R_{2pj} R_{3qk} + l_2 R_{3pj} R_{1qk} + l_3 R_{1pj} R_{2qk}) , \\ \bar{\beta} &= l_3 l_p (R_{kpk} - l_k l_r R_{kpr}) , \\ \bar{\gamma} &= l_3 . \end{aligned} \quad (3.9)$$

Introducing (3.9) into (3.7), we obtain, provided that^{*}
 $l_3 \neq 0$,

$$\alpha \sigma^2 - \beta \sigma + 1 = 0 , \quad (3.10)$$

* If $l_3 = 0$, we take $m = 2$ and 3 , or 3 and 1 , in (3.4) to obtain another pair of equations instead of (3.5). Then, by a similar procedure to that used above, we arrive at (3.10) with (3.12).

where

$$\alpha = \sum_{\substack{A,B,C, \\ P,Q}} \epsilon_{ABC} \ell_A \ell_P \ell_Q (\ell_1 R_{2PB} R_{3QC} + \ell_2 R_{3PB} R_{1QC} + \ell_3 R_{1PB} R_{2QC}) \quad (3.11)$$

$$\beta = \sum_{A,B,C} \ell_B (R_{ABA} - \ell_A \ell_C R_{ABC})$$

Now, introducing (2.13) into (3.11), we obtain

$$\begin{aligned} \alpha = & 4(\lambda_1^2 \ell_1^2 + \dots) \{ (\lambda_1^2 \ell_1^2 K_2 K_3 + \dots) \\ & + W_1 [\ell_2^2 \ell_3^2 (\lambda_2^2 - \lambda_3^2)^2 M_1 + \dots] \} \\ & + 4W_2 [\lambda_2^2 \lambda_3^2 \ell_2^2 \ell_3^2 (\lambda_2^2 - \lambda_3^2)^2 M_1 + \dots] \\ & - 16\ell_1^2 \ell_2^2 \ell_3^2 (\lambda_2^2 - \lambda_3^2)^2 (\lambda_3^2 - \lambda_1^2)^2 (\lambda_1^2 - \lambda_2^2)^2 (W_{12}^2 - W_{11} W_{22}) , \quad (3.12) \\ \beta = & 2\{ [K_1 (\lambda_2^2 \ell_2^2 + \lambda_3^2 \ell_3^2) + \dots] \\ & + [(\lambda_2^2 - \lambda_3^2)^2 \ell_2^2 \ell_3^2 M_1 + \dots] \} , \end{aligned}$$

where the dots denote terms obtained from those shown by cyclic permutation of the subscripts 1,2,3 on the λ 's, ℓ 's, K 's and M 's, and K_A and M_A are defined by

$$\begin{aligned} K_A &= W_1 + \lambda_A^2 W_2 , \\ M_A &= 2(W_{11} + 2\lambda_A^2 W_{12} + \lambda_A^4 W_{22}) . \end{aligned} \quad (3.13)$$

From (3.12) it follows, after somewhat lengthy algebraic manipulation, that

$$\begin{aligned}
 \beta^2 - 4\alpha = & 4W_2^2 \{ [\lambda_1^4 \ell_1^4 (\lambda_2^2 - \lambda_3^2)^2 + \dots] \\
 & + 2[\lambda_2^2 \lambda_3^2 \ell_2^2 \ell_3^2 (\lambda_1^2 - \lambda_2^2) (\lambda_1^2 - \lambda_3^2) + \dots] \} \\
 & + 8W_2 \{ [(\lambda_2^2 - \lambda_3^2)^2 \ell_2^2 \ell_3^2 M_1 \{ \lambda_2^2 (\lambda_1^2 - \lambda_3^2) (\ell_1^2 + \ell_2^2) \\
 & \quad + \lambda_3^2 (\lambda_1^2 - \lambda_2^2) (\ell_1^2 + \ell_3^2) \}] + \dots \} \\
 & + 4 \{ [(\lambda_2^2 - \lambda_3^2)^2 \ell_2^2 \ell_3^2 M_1 + \dots]^2 \\
 & + 16 \ell_1^2 \ell_2^2 \ell_3^2 (\lambda_2^2 - \lambda_3^2)^2 (\lambda_3^2 - \lambda_1^2)^2 (\lambda_1^2 - \lambda_2^2)^2 (W_{12}^2 - W_{11} W_{22}) \} \quad (3.14)
 \end{aligned}$$

It is of interest to note that $\beta^2 - 4\alpha$ is independent of W_1 .

The necessary and sufficient conditions for the secular equation (3.10) to yield two positive roots for σ , i.e. for S^2 , are

$$\alpha > 0, \quad \beta > 0, \quad \beta^2 \geq 4\alpha. \quad (3.15)$$

The remainder of this paper is concerned with the conditions which must be satisfied by w so that (3.15) shall be satisfied.

4. Propagation in a principal plane

If the direction of propagation of the wave lies in the principal plane normal to the 3-direction, so that $\underline{\ell} = (\ell_1, \ell_2, 0)$, then equations (3.12) can be written as

$$\begin{aligned}\alpha &= 4(\lambda_1^2 \ell_1^2 K_2 + \lambda_2^2 \ell_2^2 K_1) \{K_3 (\lambda_1^2 \ell_1^2 - \lambda_2^2 \ell_2^2)^2 \\ &\quad + \ell_1^2 \ell_2^2 (\lambda_1 + \lambda_2)^2 [K_3 + (\lambda_1 - \lambda_2)^2 M_3]\} , \\ \beta &= 2\{\lambda_1^2 \ell_1^2 K_2 + \lambda_2^2 \ell_2^2 K_1 + K_3 (\lambda_1^2 \ell_1^2 - \lambda_2^2 \ell_2^2)^2 \\ &\quad + \ell_1^2 \ell_2^2 (\lambda_1 + \lambda_2)^2 [K_3 + (\lambda_1 - \lambda_2)^2 M_3]\}\end{aligned}\tag{4.1}$$

and equation (3.14) can be written as

$$\begin{aligned}\beta^2 - 4\alpha &= 4\{W_2 [\lambda_1^2 \ell_1^2 (\lambda_3^2 - \lambda_2^2) + \lambda_2^2 \ell_2^2 (\lambda_3^2 - \lambda_1^2) \\ &\quad + \ell_1^2 \ell_2^2 (\lambda_1^2 - \lambda_2^2)^2 M_3]\}^2\end{aligned}\tag{4.2}$$

We note that the weak inequality (3.15)₃ is automatically satisfied.

Again, if the direction of propagation of the wave is a principal direction for the pure homogeneous deformation, say the direction (1,0,0), then equations (4.1) become

$$\alpha = 4\lambda_1^4 K_2 K_3 , \quad \beta = 2\lambda_1^2 (K_2 + K_3) .\tag{4.3}$$

Analogous expressions for α and β may be written in the cases when the direction of propagation is (0,1,0) and (0,0,1) and it is then seen that necessary conditions for $\alpha > 0$ and $\beta > 0$ are

$$K_A > 0 \quad (A = 1, 2, 3) .\tag{4.4}$$

These conditions are known as the Baker-Ericksen conditions [2].

Returning to $(4.1)_1$, we see that provided (4.4) is satisfied, the necessary and sufficient condition for $\alpha > 0$ is

$$K_3 + (\lambda_1 - \lambda_2)^2 M_3 > 0 . \quad (4.5)$$

If (4.4) and (4.5) are satisfied then, from $(4.1)_2$, $\beta > 0$. Analogous arguments based on the expressions for α and β obtained by taking $\underline{\ell} = (0, \ell_2, \ell_3)$ and $(\ell_1, 0, \ell_3)$ in (3.12), lead to the conclusion that the necessary and sufficient conditions for (3.15) to be satisfied for all $\underline{\ell}$ parallel to a principal plane are

$$K_A > 0 \quad \text{and} \quad (\lambda_B - \lambda_C)^2 M_A + K_A > 0 , \quad (4.6)$$

where A, B, C is a cyclic permutation of 1, 2, 3. This result was previously obtained by a slightly different path in [1].

It will now be shown that if the conditions (4.6) are satisfied by w , then $\beta > 0$ for all $\underline{\ell}$. To see this we rewrite $(3.12)_2$ in the form

$$\begin{aligned} \frac{1}{2}\beta = & [K_1 \{ (\lambda_2 \ell_2^2 - \lambda_3 \ell_3^2)^2 + \ell_1^2 (\lambda_2^2 \ell_2^2 + \lambda_3^2 \ell_3^2) \}] \\ & + [\dots] + [\dots] + b , \end{aligned} \quad (4.7)$$

where

$$\begin{aligned} b = & [(\lambda_2 + \lambda_3)^2 \ell_2^2 \ell_3^2 \{ (\lambda_2 - \lambda_3)^2 M_1 + K_1 \}] \\ & + [\dots] + [\dots] . \end{aligned} \quad (4.8)$$

5. Two principal extension ratios equal

In this section we will show that if two of the principal extension ratios are equal, then the conditions (4.6) imply that the conditions (3.15) are satisfied for arbitrary λ .

Let

$$\lambda_2 = \lambda_3 = \lambda, \quad \text{say.} \quad (5.1)$$

Then, from (2.2)

$$\lambda_1 = \lambda^{-2}, \quad (5.2)$$

and the inequalities (4.6) become

$$\begin{aligned} K_1 &> 0, \quad K > 0, \\ (\lambda^3 - 1)^2 M + \lambda^4 K &> 0, \end{aligned} \quad (5.3)$$

where, from (3.13),

$$\begin{aligned} K_1 &= W_1 + \lambda^{-4} W_2, \quad K = K_2 = K_3 = W_1 + \lambda^2 W_2, \\ M &= M_2 = M_3 = 2(W_{11} + 2\lambda^2 W_{12} + \lambda^4 W_{22}). \end{aligned} \quad (5.4)$$

With (5.4), we obtain from (3.12)

$$\begin{aligned}\alpha &= 4\lambda^{-12}\{\ell_1^2 K + \lambda^6(\ell_2^2 + \ell_3^2)K_1\}\{\lambda^4[\lambda^3(\ell_2^2 + \ell_3^2) - \ell_1^2]^2 K \\ &\quad + (\lambda^3 + 1)^2 \ell_1^2 (\ell_2^2 + \ell_3^2)[(\lambda^3 - 1)^2 M + \lambda^4 K]\} , \\ \beta &= 2\{(\ell_2^2 + \ell_3^2)[(K_1 + K)\lambda^2 + M\lambda^{-8}(\lambda^6 - 1)^2 \ell_1^2] \\ &\quad + 2K\lambda^{-4}\ell_1^2\} .\end{aligned}\tag{5.5}$$

It follows from (5.4) and (5.5) that

$$\beta^2 - 4\alpha = 4\lambda^{-16}(\lambda^6 - 1)^2(\ell_2^2 + \ell_3^2)^2[\lambda^6 W_2 + (\lambda^6 - 1)\ell_1^2 M]^2 .\tag{5.6}$$

It is evident that if the conditions (5.3) are satisfied, then the expressions for α, β and $\beta^2 - 4\alpha$ given in (5.5) and (5.6) satisfy (3.15).

This result, that if two of the principal extension ratios are equal, the conditions (4.6) imply (3.15) for arbitrary ℓ , is, of course, by no means unexpected. For the conditions (4.6) are the conditions that (3.15) be valid for all ℓ parallel to a principal plane. If two of the extension ratios are equal then any direction is parallel to a principal plane.

It should be noted that even if we restrict ourselves to underlying pure homogeneous deformations for which two of the principal extension ratios are equal, we cannot ensure that the velocities of wave propagation shall be real for all propagation directions by imposing restrictions on w beyond those implied by (5.3). For, we can choose a direction of propagation for which $\ell_1^2 = 1$ and obtain from (5.5)₂, $\beta = 4K\lambda^{-4}$, so

that the conditions $\beta > 0$ and $K > 0$ are identical. Again, by choosing $\ell_1 = 0$, $(5.5)_1$ becomes $\alpha = 4\lambda^4 K_1 K$, which, with $K > 0$ and the condition $\alpha > 0$, yields $K_1 > 0$. Finally, it is possible to choose a direction of propagation for which $\ell_1^2 = \lambda^3(\ell_2^2 + \ell_3^2)$, and it follows from $(5.5)_1$, with $K_1 > 0$ and $K > 0$, that $\alpha > 0$ only if $(5.3)_3$ is satisfied.

In a previous paper [3], Sawyers and Rivlin conjectured that the conditions (4.2), which are the necessary and sufficient conditions for the wave velocities to be real for directions of propagation parallel to a principal plane, might be replaced by the stronger conditions

$$K_A > 0, \quad (\lambda_A + \lambda_B)^2 M_C + K_C \geq 0, \quad (5.7)$$

where A,B,C is a cyclic permutation of 1,2,3, if we wish to ensure that the wave velocities be real for arbitrary directions of propagation. That this is not true, in general, is evidenced by the above discussion, and also from the results given in §7 below.

6. The Mooney-Rivlin material

We now consider a material for which the strain-energy function is given by

$$w = C_1(i_1 - 3) + C_2(i_2 - 3) \quad (6.1)$$

where C_1 and C_2 are constants. Then,

$$W_1 = C_1, \quad W_2 = C_2, \quad W_{11} = W_{22} = W_{12} = 0. \quad (6.2)$$

It follows from (3.13) that

$$K_A = C_1 + \lambda_A^2 C_2, \quad M_A = 0. \quad (6.3)$$

Then, from (3.12),

$$\begin{aligned} \alpha &= 4(\lambda_1^2 \lambda_1^2 + \dots) \{ \lambda_1^2 \lambda_1^2 K_2 K_3 + \dots \}, \\ \beta &= 2[K_1(\lambda_2^2 \lambda_2^2 + \lambda_3^2 \lambda_3^2) + \dots]. \end{aligned} \quad (6.4)$$

We shall assume that the underlying pure homogeneous deformation to which the body is subjected is such that the three principal extension ratios are all different^{*}. We may assume, without loss of generality, that $\lambda_1 > \lambda_2 > \lambda_3$. It follows from (6.4) and (6.3)₁ that

* If this is not the case, the analysis of the preceding section is applicable.

$$\begin{aligned} \beta^2 - 4\alpha = 4C_2^2 \{ & [\lambda_1^2 \ell_1^2 (\lambda_2^2 - \lambda_3^2) + \lambda_2^2 \ell_2^2 (\lambda_1^2 - \lambda_3^2) - \lambda_3^2 \ell_3^2 (\lambda_1^2 - \lambda_2^2)]^2 \\ & + 4\lambda_2^2 \lambda_3^2 \ell_2^2 \ell_3^2 (\lambda_1^2 - \lambda_2^2) (\lambda_1^2 - \lambda_3^2) \} . \end{aligned} \quad (6.5)$$

From (6.4) it follows that the conditions $\alpha > 0$, $\beta > 0$ are satisfied for all ℓ if and only if $K_A > 0$ ($A=1,2,3$) . It is, of course, evident from (6.5) that the condition $\beta^2 - 4\alpha \geq 0$ is automatically satisfied.

7. Two additional special cases

In this section we shall discuss the cases when w is a function of i_1 only or of i_2 only.

If w is independent of i_2 , so that

$$w = f(i_1) , \quad (7.1)$$

then equations (3.13) become

$$K_A = f' , \quad M_A = 2f'' \quad (A=1,2,3) , \quad (7.2)$$

where the prime denotes differentiation with respect to i_1 .

The conditions (4.6) then become

$$f' > 0 , \quad 2(\lambda_A - \lambda_B)^2 f'' + f' > 0 . \quad (7.3)$$

where $AB = 23, 31, 12$.

With (7.1) and (7.2), we obtain from (3.12)₁ and (3.14)

$$\begin{aligned} \alpha &= 4(\lambda_1^2 \lambda_1^2 + \dots) f' \{ (\lambda_1^2 \lambda_1^2 + \dots) f' \\ &\quad + 2f'' [(\lambda_2^2 - \lambda_3^2)^2 \lambda_2^2 \lambda_3^2 + \dots] \} , \\ \beta^2 - 4\alpha &= 16 [(\lambda_2^2 - \lambda_3^2)^2 \lambda_2^2 \lambda_3^2 + \dots]^2 (f'')^2 . \end{aligned} \quad (7.4)$$

It is evident that $\beta^2 - 4\alpha \geq 0$ for all forms of f .

We shall now show that $\alpha > 0$ for all functions f which satisfy (7.3). It is, of course, evident that the conditions (7.3) are satisfied for all functions f for which $f' > 0$ and $f'' \geq 0$ and, for all such functions, $\alpha > 0$. We accordingly consider only functions f for which $f' > 0$ and $f'' < 0$.

Let us assume* that $\lambda_1 > \lambda_2 > \lambda_3$. Then, the condition

$$2(\lambda_1 - \lambda_3)^2 f'' + f' > 0 \quad (7.5)$$

implies the remaining two conditions $(7.3)_2$. We may rewrite (7.5) as

$$2(\lambda_1 - \lambda_3)^2 f'' + f' = \varepsilon, \quad \varepsilon > 0. \quad (7.6)$$

Then, with $(7.6)_1$, equation $(7.4)_1$ becomes

$$\alpha = \frac{4(\lambda_1^2 \ell_1^2 + \dots)}{(\lambda_1 - \lambda_3)^2} f' \{ F f' + \varepsilon [(\lambda_2^2 - \lambda_3^2)^2 \ell_2^2 \ell_3^2 + \dots] \}, \quad (7.7)$$

where

$$F = (\lambda_1 - \lambda_3)^2 (\lambda_1^2 \ell_1^2 + \dots) - [(\lambda_2^2 - \lambda_3^2)^2 \ell_2^2 \ell_3^2 + \dots]. \quad (7.8)$$

We now show that $F \geq 0$. Since $\ell_2^2 = 1 - \ell_1^2 - \ell_3^2$, we can rewrite (7.8) as

$$\begin{aligned} F = & \lambda_2^2 (\lambda_1 - \lambda_3)^2 + (\lambda_1^2 - \lambda_2^2) [(\lambda_1 - \lambda_3)^2 - (\lambda_1^2 - \lambda_2^2)] \ell_1^2 \\ & - (\lambda_2^2 - \lambda_3^2) [(\lambda_1 - \lambda_3)^2 + (\lambda_2^2 - \lambda_3^2)] \ell_3^2 \\ & + [(\lambda_1^2 - \lambda_2^2) \ell_1^2 - (\lambda_2^2 - \lambda_3^2) \ell_3^2]^2. \end{aligned} \quad (7.9)$$

Regarding F as a function of ℓ_1^2 and ℓ_3^2 , we see that if F has a minimum, it occurs when $\partial F / \partial (\ell_1^2) = \partial F / \partial (\ell_3^2) = 0$, i.e. when

* The case when two of the λ 's are equal is covered in §5.

$$\begin{aligned} (\lambda_1^2 - \lambda_2^2)\ell_1^2 - (\lambda_2^2 - \lambda_3^2)\ell_3^2 &= -\frac{1}{2}[(\lambda_1 - \lambda_3)^2 - (\lambda_1^2 - \lambda_2^2)] , \\ (\lambda_1^2 - \lambda_2^2)\ell_1^2 - (\lambda_2^2 - \lambda_3^2)\ell_3^2 &= -\frac{1}{2}[(\lambda_1 - \lambda_3)^2 - (\lambda_3^2 - \lambda_2^2)] . \end{aligned} \quad (7.10)$$

Since $\lambda_1 > \lambda_3$, equations (7.10) evidently yield no solution for ℓ_1^2 and ℓ_3^2 and, accordingly, F cannot assume a minimum value.

We find, from (7.9) and the fact that $\underline{\ell}$ is a unit vector, that

$$\begin{aligned} F|_{\ell_1=0} &= (\lambda_1 - \lambda_3)^2 (\lambda_2 \ell_2^2 - \lambda_3 \ell_3^2)^2 \\ &\quad + (\lambda_2 + \lambda_3)^2 (\lambda_1 - \lambda_2) (\lambda_1 + \lambda_2 - 2\lambda_3) \ell_2^2 \ell_3^2 > 0 , \\ F|_{\ell_3=0} &= (\lambda_1 - \lambda_3)^2 (\lambda_1 \ell_1^2 - \lambda_2 \ell_2^2)^2 \\ &\quad + (\lambda_1 + \lambda_2)^2 (\lambda_2 - \lambda_3) (2\lambda_1 - \lambda_2 - \lambda_3) \ell_1^2 \ell_2^2 > 0 , \\ F|_{\ell_2=0} &= (\lambda_1 - \lambda_3)^2 (\lambda_1 \ell_1^2 - \lambda_3 \ell_3^2)^2 \geq 0 . \end{aligned} \quad (7.11)$$

We note that $F|_{\ell_2=0} = 0$ if and only if $\lambda_1 \ell_1^2 - \lambda_3 \ell_3^2 = 0$.

The domain in the ℓ_1^2, ℓ_3^2 plane for which $\underline{\ell}$ is a unit vector is the triangular domain bounded by the lines $\ell_1^2 = 0$, $\ell_3^2 = 0$ and $\ell_1^2 + \ell_3^2 = 1$. It follows from (7.11) that $F \geq 0$ on the boundary of this domain. If $F < 0$ at any point in the interior of the domain, it follows (see, for example, [5]) that it must assume a minimum value in the interior of the domain. However, we have seen that it does not assume such a minimum. Accordingly, $F \geq 0$ at all points of the closed domain, i.e. for all $\underline{\ell}$. It follows from (7.7) and (7.6) that $\alpha > 0$ for all $\underline{\ell}$ if w has the form (7.1) and the conditions (4.6) are satisfied.

We now turn to the case when w is independent of i_1 and write

$$w = g(i_2) \quad (7.12)$$

Then, the conditions (4.6) become

$$g' > 0, \quad 2(\lambda_A - \lambda_B)^2 \lambda_C^2 g'' + g' > 0, \quad (7.13)$$

where the prime now denotes differentiation with respect to i_2 . With (7.12) and (3.13), we obtain from (3.12)

$$\begin{aligned} \alpha &= 4g'(g'\phi_4 + 2g''\phi_3) \quad \beta = 4(g'\phi_2 + g''\phi_1), \\ \beta^2 - 4\alpha &= 16\{\phi_1^2(g'')^2 + 2(\phi_1\phi_2 - \phi_3)g'g'' + (\phi_2^2 - \phi_4)(g')^2\}, \end{aligned} \quad (7.14)$$

where

$$\begin{aligned} \phi_1 &= \lambda_1^4(\lambda_2^2 - \lambda_3^2)^2 \ell_2^2 \ell_3^2 + \dots, \\ \phi_2 &= \frac{1}{2}\{\lambda_1^2 \ell_1^2(\lambda_2^2 + \lambda_3^2) + \dots\}, \\ \phi_3 &= \lambda_1^2(\lambda_2^2 - \lambda_3^2)^2 \ell_2^2 \ell_3^2 + \dots, \\ \phi_4 &= \lambda_1^2 \ell_1^2 + \dots \end{aligned} \quad (7.15)$$

We may rewrite (7.14)₂ in the form

$$\begin{aligned} \beta^2 - 4\alpha &= 16\{[\phi_1 g'' + (\phi_2 - \frac{\phi_3}{\phi_1})g']^2 \\ &\quad + (\frac{g'}{\phi_1})^2(2\phi_1\phi_2\phi_3 - \phi_1^2\phi_4 - \phi_3^2)\}. \end{aligned} \quad (7.16)$$

After some lengthy calculation, we obtain

$$2\phi_1\phi_2\phi_3 - \phi_1^2\phi_4 - \phi_3^2 = \ell_1^2 \ell_2^2 \ell_3^2 (\lambda_2^2 - \lambda_3^2)^2 (\lambda_3^2 - \lambda_1^2)^2 (\lambda_1^2 - \lambda_2^2)^2 \geq 0. \quad (7.17)$$

Thus, the condition $\beta^2 - 4\alpha \geq 0$ is satisfied for all g .

It is evident that the conditions (7.13) are satisfied for all g for which $g' > 0$ and $g'' \geq 0$ and, $\alpha > 0$ for all such g . We accordingly consider only functions g for which $g' > 0$ and $g'' < 0$. Let us assume $\lambda_1 > \lambda_2 > \lambda_3$. Then, since, with (2.2),

$$\lambda_2^2(\lambda_1 - \lambda_3)^2 > \lambda_1^2(\lambda_2 - \lambda_3)^2, \quad \lambda_2^2(\lambda_1 - \lambda_3)^2 > \lambda_3^2(\lambda_1 - \lambda_2)^2, \quad (7.18)$$

it follows that the condition

$$2\lambda_2^2(\lambda_1 - \lambda_3)^2 g'' + g' > 0, \quad (7.19)$$

implies the remaining two conditions (7.13)₂.

The condition (7.19) may be rewritten as

$$2\lambda_2^2(\lambda_1 - \lambda_3)^2 g'' + g' = \epsilon, \quad \epsilon > 0. \quad (7.20)$$

From (7.20)₁ and (7.14)₁, we obtain

$$\alpha = \frac{4g'}{\lambda_2^2(\lambda_1 - \lambda_3)^2} (Gg' + \epsilon\phi_3), \quad (7.21)$$

where

$$G = \lambda_2^2(\lambda_1 - \lambda_3)^2\phi_4 - \phi_3. \quad (7.22)$$

Writing $\lambda_2^2 = 1 - \lambda_1^2 - \lambda_3^2$ in the expression (7.15) for ϕ_3 and ϕ_4 and regarding G as a function of λ_1^2 and λ_3^2 it follows that if G has a minimum, it occurs when

$$\begin{aligned}
 2\lambda_3^2(\lambda_1^2-\lambda_2^2)\ell_1^2 - (\lambda_1^2+\lambda_3^2)(\lambda_2^2-\lambda_3^2)\ell_3^2 \\
 = \lambda_3^2(\lambda_1^2-\lambda_2^2) - \lambda_2^2(\lambda_1-\lambda_3)^2, \\
 2\lambda_1^2(\lambda_3^2-\lambda_2^2)\ell_3^2 - (\lambda_1^2+\lambda_3^2)(\lambda_2^2-\lambda_1^2)\ell_1^2 \\
 = \lambda_1^2(\lambda_3^2-\lambda_2^2) - \lambda_2^2(\lambda_1-\lambda_3)^2,
 \end{aligned} \tag{7.23}$$

i.e. when

$$\begin{aligned}
 (\lambda_1^2-\lambda_3^2)(\lambda_1^2-\lambda_2^2)\ell_1^2 &= -\{\lambda_3^2(\lambda_1^2-\lambda_2^2) + 2\lambda_2\}, \\
 (\lambda_1^2-\lambda_3^2)(\lambda_2^2-\lambda_3^2)\ell_3^2 &= \lambda_1^2(\lambda_2^2-\lambda_3^2) - 2\lambda_2.
 \end{aligned} \tag{7.24}$$

Since $\lambda_1 > \lambda_2 > \lambda_3$, the value of ℓ_1^2 given by (7.24) is negative and accordingly, G does not possess a minimum value for real values of ℓ .

We find, from (7.22) and (7.15) and the fact that ℓ is a unit vector, that

$$\begin{aligned}
 G|_{\ell_1=0} &= (\lambda_1-\lambda_3)^2 \lambda_2^2 (\lambda_2 \ell_2^2 - \lambda_3 \ell_3^2)^2 \\
 &\quad + \lambda_3 (\lambda_1-\lambda_2) (\lambda_2+\lambda_3)^2 (2\lambda_1 \lambda_2 - \lambda_1 \lambda_3 - \lambda_2 \lambda_3) \ell_2^2 \ell_3^2 > 0, \\
 G|_{\ell_3=0} &= (\lambda_1-\lambda_3)^2 \lambda_2^2 (\lambda_1 \ell_1^2 - \lambda_2 \ell_2^2)^2 \\
 &\quad + \lambda_1 (\lambda_2-\lambda_3) (\lambda_1+\lambda_2)^2 (\lambda_1 \lambda_2 + \lambda_1 \lambda_3 - 2\lambda_2 \lambda_3) \ell_1^2 \ell_2^2 > 0, \\
 G|_{\ell_2=0} &= \lambda_2^2 (\lambda_1-\lambda_3)^2 (\lambda_1 \ell_1^2 - \lambda_3 \ell_3^2)^2 \geq 0.
 \end{aligned} \tag{7.25}$$

We note that $G|_{\ell_2=0} = 0$ if and only if $\lambda_1 \ell_1^2 = \lambda_3 \ell_3^2$.

By an argument similar to that used in showing that $F \geq 0$, it follows that $G \geq 0$ for all real ℓ and the value $G = 0$

is taken only when ℓ is perpendicular to the 2-direction. It then follows from (7.21) and (7.15), with (7.20), that $\alpha > 0$ for all ℓ if w has the form (7.12) and the conditions (4.6) are satisfied.

Acknowledgement. The results presented in this paper were obtained in the course of research sponsored by the Office of Naval Research under Contract No. N00014-76-C-0235 with Lehigh University.

References

- [1] K.N. Sawyers and R.S. Rivlin, Int. J. Solids Structures 9, 607 (1973)
- [2] M. Baker and J.L. Ericksen, J. Washington Acad. Sciences 44, 33 (1954)
- [3] K.N. Sawyers and R.S. Rivlin, Int. J. Solids Structures 10, 483 (1974)
- [4] J.L. Ericksen, J. Rational Mech. Anal. 2, 141 (1953)
- [5] D.V. Widder, Advanced Calculus, Prentice Hall: New York (1947).

PART 1 - GOVERNMENT

Administrative & Liaison
Activities

Chief of Naval Research
Department of the Navy
Arlington, Virginia. 22217
Attn: Code 439 (2)
471

Director
ONR Branch Office
495 Summer Street
Boston, Massachusetts 02210

Director
ONR Branch Office
219 S. Dearborn Street
Chicago, Illinois 60604

Director
Naval Research Laboratory
Attn: Library, Code 2029 (ONRL)
Washington, D.C. 20390 (6)

Commanding Officer
ONR Branch Office
207 West 24th Street
New York, New York 10011

Director
ONR Branch Office
1030 E. Green Street
Pasadena, California 91101

U.S. Naval Research Laboratory
Attn: Technical Information Div.
Washington, D.C. 20390 (6)

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314 (20)

Army

Commanding Officer
U.S. Army Research Office Durham
Attn: Mr. J.J. Murray
CRD-AA-IP, Box CM, Duke Station
Durham, North Carolina 27706

Commanding Officer
AMXMR-ATL
Attn: Mr. J. Bluhm
U.S. Army Materials Res. Agcy.
Watertown, Massachusetts 02172

Watervliet Arsenal
MAGGS Research Center
Watervliet, New York 12189
Attn: Director of Research

Redstone Scientific Info.Center
Chief, Document Section
U.S. Army Missile Command
Redstone Arsenal, Alabama 35809

Army R & D Center
Fort Belvoir, Virginia 22060

Technical Library
Aberdeen Proving Ground
Aberdeen, Maryland 21005

Navy

Commanding Officer & Director
Naval Ship Research & Develop-
ment Center
Washington, D.C. 20007
Attn: Code 042 (Tech.Lib.Br.)
700 (Struc.Mech.Lab.)
720
725
727

Naval Weapons Laboratory
Dahlgren, Virginia 22448

Naval Research Laboratory
Washington, D.C. 20390
Attn: Code 8400
8410
8430
8440
6300
6305
6380

Undersea Explosion Research Div.
Naval Ship R & D Center
Norfolk Naval Shipyard
Portsmouth, Virginia 23709
Attn: Dr. Schauer Code 780

Naval Ship R & D Center
Annapolis Division
Annapolis, Maryland 21402
Attn: Code A800, Mr.W.L. Williams

Technical Library
Naval Underwater Weapons Center
Pasadena Annex
3202 E. Foothill Blvd.
Pasadena, California 91107

U S. Naval Weapons Center
China Lake, California 93557
Attn: Code 4520 Mr.Ken Bischel

U.S. Naval Ordnance Laboratory
Mechanics Division
BFD 1, White Oak
Silver Spring, Maryland 20910

U.S. Naval Ordnance Laboratory
Attn: Mr. H.A. Perry, Jr.
Non-Metallic Materials Division
Silver Spring, Maryland 20910

Technical Director
U.S. Naval Undersea R & D Center
San Diego, California 92132

Supervisor of Shipbuilding
U.S. Navy
Newport News, Virginia 23607

Technical Director
Mare Island Naval Shipyard
Vallejo, California 94592

U.S. Naval Ordnance Station
Attn: Mr. Garet Bornstein
Research & Development Div.,
Indian Head, Maryland 20640

Chief of Naval Operations
Department of the Navy
Washington, D.C. 20350
Attn: Code OP-07T

Deep Submergence Systems
Naval Ship Systems Command
Code 39522, Dept. of the Navy
Washington, D.C. 20360
Attn: Chief Scientist.

Director
Naval Air Development Center
Johnsville
Warminster, Pa. 18974

Naval Air Systems Command
Dept. of the Navy
Washington, D.C. 20360
Attn: NAIR 320 Aero & Structures
5320 Structures
604 Tech. Library
52031F Materials

Naval Facilities Engng.Command
Dept. of the Navy
Washington, D.C. 20360
Attn: NFAC 03 Res. & Development
04 Engng. & Design
14114 Tech. Library

Naval Ship Systems Command
Dept. of the Navy
Washington, D.C. 20360
Attn: NSHIP 031 Ch.Sci. for R & D
0342 Ship Mats.& Structs.
2052 Tech. Library

Naval Ship Engineering Center
Prince George Plaza
Hyattsville, Maryland 20782
Attn: NSEC 6100 Ship Sys.Engr.&D.D.
6102C Computer-Aided Ship D.
6105 Ship Protection
6110 Ship Concept Design
6120 Hull Div.
6120D Hull Div.
6128 Surface Ship Struct.
6129 Submarine Struct.

Naval Ordnance Systems Command
Dept. of the Navy
Washington, D.C. 20360
Attn: NORD 03 Res. & Technology
035 Weapons Dynamics
9132 Tech. Library

Engineering Department
U.S. Naval Academy
Annapolis, Maryland. 21402.
Mr. Sidney Brown, Resident Rep.
Office of Naval Research
University of Pennsylvania
The Moore School of Elec. Engng.
200 South 33rd Street
Philadelphia, Pa. 19104.

Air Force

Commander WADD
Wright-Patterson Air Force Base
Dayton, Ohio. 45433
Attn: Code WWRMDD
AFFDL (FDDS)
Structures Division
AFLC (MCEEA)
Code WWRC
ARML (MAAM)

Commander
Chief, Applied Mechanics Group
U.S. Air Force Inst. of Tech.
Wright-Patterson Air Force Base
Dayton, Ohio. 45433

Chief, Civil Engng. Branch
WLRC, Research Division
Air Force Weapons Lab.
Kirtland AFB, New Mexico 87117

Air Force Office of Scientific Res.
1400 Wilson Blvd.
Arlington, Virginia 22209
Attn: Mechs. Div.

NASA

Structures Research Division
National Aeronautics & Space Admin.
Langley Research Center
Langley Station
Hampton, Virginia. 23365
Attn: Mr. R.R. Heldenfels, Chief

National Aeronautic & Space Admin.
Assoc. Administrator for Advanced
Research & Technology
Washington, D.C. 20546

Other Government Activities

Technical Director
Marine Corps. Dev. & Educ.
Command
Quantico, Virginia 22134

Director
National Bureau of Standards
Washington, D.C. 20234
Attn: Mr. B.L. Wilson, EM 219.

National Science Foundation
Engineering Division
Washington, D.C. 20550

Director, STBS
Defense Atomic Support Agency
Washington, D.C. 20350

Commander Field Command
Defense Atomic Support Agency
Sandia Base
Albuquerque, New Mexico 87115

Chief, Defense Atomic Supp. Agency
Blast & Shock Division
The Pentagon
Washington, D.C. 20301

Director Defense Research & Engng.
Technical Library, Room 3C-128
The Pentagon
Washington, D.C. 20301

Chief, Airframe & Equipment
FS-120
Office of Flight Standards
Federal Aviation Agency
Washington, D.C. 20553

Chief of Research & Development
Maritime Administration
Washington, D.C. 20235

Mr. Milton Shaw, Director
Div. of Reactor Dev. & Technology
Atomic Energy Commission
Germantown, Maryland. 20767

Ship Hull Research Committee
National Research Council
National Academy of Sciences
2101 Constitution Avenue
Washington, D.C. 20418
Attn: Mr. A.R. Lytle.

PART 2 - CONTRACTORS AND OTHER
TECHNICAL COLLABORATORS

Universities

Professor J.R. Rice
Division of Engineering
Brown University
Providence, Rhode Island 02912

Dr. J. Tinsley Oden
Dept. of Engng. Mechanics
University of Alabama
Huntsville, Alabama 35804

Professor R.S. Rivlin
Center for the Application of
Mathematics
Lehigh University
Bethlehem, Pa. 18015

Professor Julius Miklowitz
Div. of Eng g. & Appl. Science
California Institute of Tech.
Pasadena, California 91109

Professor George C. Sih
Department of Mechanics
Lehigh University
Bethlehem, Pa. 18015

Dr. Harold Liebowitz, Dean
School of Engng. & Appl. Sci.,
George Washington University
725, 23rd Street
Washington, D.C. 20006

Professor Eli Sternberg
Div. of Engng. & Appl. Sci.,
Cal. Institute of Technology
Pasadena, California 91109

Professor Burt Paul
University of Pennsylvania
Towne School of Civil and
Mechanical Engng.,
Room 113 Towne Building
220 South 33rd Street
Philadelphia, Pa. 19104

Professor S.B. Dong
University of California
Department of Mechanics
Los Angeles, California 90024

Professor Paul M. Naghdi
Div. of Appl. Mechanics
Etcheverry Hall
University of California
Berkeley, California 94720

Professor W. Nachbar
University of California
Dept. of Aerospace and Mech. Engng.
La Jolla, California 92037

Professor J. Baltrukonis
Mechanics Division
The Catholic University of America
Washington, D.C. 20017

Professor A.J. Durelli
Mechanics Division
The Catholic University of America
Washington, D.C. 20017

Professor H.H. Bleich
Dept. of Civil Engng.,
Columbia University
Amsterdam & 120th Street
New York, N.Y. 10027

Professor R.D. Mindlin
Department of Civil Engng.
Columbia University
S.W. Mudd Building
New York, N.Y. 10027

Professor A.M. Freudenthal
George Washington University
School of Engng. & Appl. Sci.,
Washington, D.C. 20006

Dean Bruno A. Boley
Technological Institute
Northwestern University
2145 Sheridan Road
Evanston, Illinois. 60201.

Professor P.G. Hodge
Department of Aerospace Engng.
& Mechanics, Univ. of Minnesota
Minneapolis, Minnesota. 55455.

Dr. D.C. Drucker
Dean of Engineering
University of Illinois
Urbana, Illinois 61801.

Professor N.M. Newmark
Dept. of Civil Engng.
University of Illinois
Urbana, Illinois. 61801

Professor James Mar
Mass. Institute of Tech.
Room 33-318
Dept. of Aerospace & Astro
77 Massachusetts Ave.
Cambridge, Mass. 02139

Library (Code 0384)
U.S. Naval Postgraduate School
Monterey, California. 93940

Dr. Francis Cozzarelli
Div. of Interdisciplinary
Studies and Research
School of Engineering
State University of N.Y.
Buffalo, New York. 14214

Professor R.A. Douglas
Dept. of Engng. Mechanics
North Carolina State Univ.,
Raleigh, North Carolina 27607.

Dr. George Herrmann
Stanford University
Dept. of Applied Mechanics
Stanford, California 94305

Professor J.D. Achenbach
Technological Institute
Northwestern University
Evanston, Illinois 60201

Director, Ordnance Research Lab.
Pennsylvania State University
P.O. Box 30
State College, Pa. 16801

Professor J. Kempner
Dept. of Aero., Engng., &
Applied Mechanics
Polytechnic Inst. of Brooklyn
333 Jay Street
Brooklyn, New York 11201

Professor J. Klosner
Polytechnic Inst. of Brooklyn
333 Jay Street
Brooklyn, New York. 11201

Professor A.C. Eringen
Dept. of Aerospace & Mech. Sci.,
Princeton University
Princeton, New Jersey. 08540

Dr. S.L. Koh
School of Aero., Astro. & Engng.Sci.
Purdue University
Lafayette, Indiana. 47907

Professor R.A. Schapery
Civil Engineering Dept.
Texas A & M University
College Station, Texas. 77840

Professor E.H. Lee
Division of Engng. Mechanics
Stanford University
Stanford, California. 94305

Dr. Nicholas J. Hoff
Dept. of Aero. & Astro.,
Stanford University
Stanford, California 94305

Professor Max Anliker
Dept. of Aero. & Astro.
Stanford University
Stanford, California 94305

Professor Chi-Chang Chao
Div. of Engng. Mechanics
Stanford University
Stanford, California 94305

Professor H.W. Liu
Dept. of Chem. Engng. & Metal.
Syracuse University
Syracuse, New York 13210

Professor S. Bodner
Technion R & D Foundation
Haifa, Israel

Dr. S. Dhawan, Director
Indian Institute of Science
Bangalore, India

Professor Tsuyoshi Hayashi
Department of Aeronautics
Faculty of Engineering
University of Tokyo
Bunkyo-Ku
Tokyo, Japan.

Professor J.E. Fitzgerald
Chairman, Dept. of Civil Eng.
University of Utah
Salt Lake City, Utah. 84112

Professor R.J.H. Bollard
Chairman, Aero. Engng. Dept.,
207 Guggenheim Hall
University of Washington
Seattle, Washington. 98105

Professor A.S. Kobayashi
Dept. of Mech. Engng.
University of Washington
Seattle, Washington 98105

Professor G.R. Irwin
Dept. of Mechanical Engng.
Lehigh University
Bethlehem, Pa. 18015

Dr. Daniel Frederick
Dept. of Engng. Mechanics
Virginia Polytechnic Inst.
Blacksburg, Virginia. 24061

Professor Lambert Tall
Lehigh University
Dept. of Civil Engng.
Bethlehem, Pa. 18015

Professor M.P. Wnuk
So. Dakota State University
Dept. of Mechanical Engng.
Brookings, South Dakota 57006

Professor Norman Jones
Mass. Institute of Tech.
Dept. of Naval Arch. & Mar. Engng.
Cambridge, Mass. 02139

Professor Pedro V. Marcal
Brown University
Division of Engineering
Providence, Rhode Island 02912

Professor Werner Goldsmith
Dept. of Mech. Engng.
Division of Appl. Mechanics
University of California
Berkeley, California. 94720

Professor R.B. Testa
Dept. of Civil Engng.
Columbia Univ., S.W. Mudd Bldg.
New York, N.Y. 10027,

Dr. Y. Weitsman
Dept. of Engng. Sciences
Tel-Aviv University
Ramat-Aviv, Tel-Aviv, Israel.

Professor W.D. Pilkey
Dept. of Aerospace Engng.
University of Virginia
Charlottesville, Virginia 22903

Professor W. Prager
Division of Engineering
Brown University
Providence, Rhode Island 02912

Industry & Research Institutes

Mr. Carl E. Hartbower
Dept. 4620, Bldg. 2019 A2
Aerojet-General Corp.
P.O. Box 1947
Sacramento, California. 95809

Library Services Department
Report Section, Bldg. 14-14
Argonne National Laboratory
9400 S. Cass Avenue
Argonne, Illinois. 60440

Dr. F.R. Schwarzl
Central Laboratory T.N.O.
Schoenmakerstraat 97
Delft, The Netherlands.

~~Dr. Wendt
Valley Forge Space Technology Cen.
General Electric Co.
Valley Forge, Pa. 10481~~ 11/2/73 ⁰⁸

Library Newport News Shipbuilding
& Dry Dock Company
Newport News, Virginia 23607

Director
Ship Research Institute
Ministry of Transportation
700, SHINKAWA, Mitaka
Tokyo, Japan.

Dr. H.N. Abramson
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas. 78206.

Dr. R.C. DeHart
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas. 78206

Mr. Roger Weiss
High Temp. Structures. & Mat'ls.
Applied Physics Lab.
8621 Georgia Avenue
Silver Spring, Maryland. 20910

Mr. E.C. Francis, Head
Mech. Props. Eval.
United Technology Center
Sunnyvale, California. 94088

Mr. C.N. Robinson
Atlantic Research Corp.
Shirley Highway at Edsall Road
Alexandria, Virginia. 22314

Mr. P.C. Durup
Aeromechanics Dept. 74-43
Lockheed-California Co.
Burbank, California. 91503

Mr. D. Wilson
Litton Systems, Inc.
AMTD, Dept. 400
El Segundo
9920 W. Jefferson Blvd.
Culver City, California. 90230.

Dr. Kevin J. Forsberg, Head
Solid Mechanics
Orgn. 52-20, Bldg. 205
Lockheed Palo Alto Research Lab.
Palo Alto, California. 94302.

Dr. E.M.Q. Roren
Head, Research Department
Det Norske Veritas
Post Box 6060
Oslo, Norway.

Dr. Andrew F. Conn
Hydronautics, Inc.,
Pindell School Road
Howard County
Laurel, Maryland. 20810.

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Center for the Application of Mathematics Lehigh University		2a. REPORT SECURITY CLASSIFICATION Unclassified	
3. REPORT TITLE (6) On the Speed of Propagation of Waves in a Deformed Elastic Material.		2b. GROUP	
4. DESCRIPTIVE NOTES (Type of report and, inclusive dates) Unclassified Technical Report April 1977			
5. AUTHOR(S) (First name, middle initial, last name) (10) K.N. Sawyers and R.S. Rivlin (9) Technical rept.			
6. REPORT DATE (11) April 1977 (12) 38p.		7a. TOTAL NO. OF PAGES 26	7b. NO. OF REFS 5
8a. CONTRACT OR GRANT NO. (15) N00014-76-C-0235		9a. ORIGINATOR'S REPORT NUMBER(S) (4) CAM-100-27	
b. PROJECT NO.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. DISTRIBUTION STATEMENT Distribution of this document is unlimited			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Office of Naval Research Arlington, Va.	
13. ABSTRACT The secular equation is obtained for small amplitude waves propagated in an arbitrary direction in a body of incompressible isotropic elastic material subjected to a pure homogeneous deformation. Conditions are obtained that the wave speeds be real.			

403812 B

DD FORM 1 NOV 65 1473

(PAGE 1)

S/N 0101-807-6811

Unclassified

Security Classification

A-1

Unclassified

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
material stability, finite deformation, real wave speeds						

DD FORM 1 NOV 66 1473 (BACK)

S/N 0101-807-6821

Unclassified

Security Classification

A-31409

Industry & Research Institutes

Mr. W.K. Bills, Jr.,
Dept. 4722, Bldg. 0525
Aerojet-General Corporation
P.O. Box 1947
Sacramento, California. 95809

Dr. Paul J. Blatz
Shock Hydrodynamics, Inc.
15010 Ventura Boulevard
Sherman Oaks,
Los Angeles, California. 91403.

Mr. Ross H. Petty
Technical Library
Allegany Ballistics Lab.
Hercules Powder Company
P.O. Box 210
Cumberland, Maryland. 21501

Mr. R.F. Landel
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, California. 91103

Mr. Harry Leeming
Director, Research & Engng.
Lockheed Propulsion Company
P.O. Box 111
Redlands, California. 92374

Solid Rocket Division
Rocketdyne
P.O. Box 548
McGregor, Texas. 76657

Dr. Thor L. Smith
IBM Research Labs.,
Monterey & Cottle Roads
San Jose, California. 95114

Hercules, Inc., Bacchus Works
S.C. Browning
Magna, Utah. 84044

Dr. Norman Fishman
Stanford Research Institute
Propulsion Sciences Division
Menlo Park, California. 94025.

McDonnell-Douglas Corp.
Douglas Aircraft Company Div.
R.V. Mellette, A2-260
3000 Ocean Park Blvd.
Santa Monica, California. 90406.

Hercules, Inc.,
Bacchus Works
James H. Thacher
Magna, Utah. 84044.

PART - 3

A Supplement List for Reports
Relating to the Mechanical Behavior
of Viscoelastic Materials.

Army

Army Missile Command
Redstone Arsenal, Alabama 35809
Attn: AMSMI-RKP Mr. T.H. Duerr

Ballistic Research Laboratories
Aberdeen Proving Grounds
Aberdeen, Maryland. 21005
Attn: Dr. Alex S. Elder
Mr. H.P. Gay

Picatinny Arsenal
Dover, New Jersey. 07801
Attn: Mr. Ben Lehman

Navy

Chief of Naval Research
Department of the Navy
Arlington, Virginia. 22217
Attn: Code 472

U.S. Naval Weapons Center
China Lake, California 93557
Attn: Code 6058 Dr.A. Adicoff

Naval Air Systems Command
Department of the Navy
Washington, D.C. 20360
Attn: NAIR Code 330 Propulsion
5367 Rocket Components

Naval Ordnance Systems Command
Department of the Navy
Washington, D.C. 20360
Attn: NORD Code 0331 Prop. & Propellants

Air Force

Commander
Rocket Propulsion Laboratory
Edwards AFB, California 93523
Attn: RPMC Dr. F.N. Kelley
MKPB Mr. N. Walker

Mr. J.D. Ray, Chief
Plastics & Composites Branch
Nonmetallic Mat'ls Division
Air Force Mat'ls Laboratory
Wright-Patterson AFB, Ohio 45433

NASA

National Aeronautics & Space Admin.
Code RPS (R.W. Ziem)
Washington, D.C. 20546

Universities

Professor F.R. Eirich
Polytechnic Inst. of Brooklyn
333 Jay Street
Brooklyn, New York. 11201

~~Professor A.V. Tobolsky
Dept. of Chemistry
Princeton University
Princeton, New Jersey. 08540~~ 2/7/74
CB

Dr. Rodney D. Andrews
Themis Project Director
Dept. of Chemistry and
Chemical Engineering
Stevens Institute of Technology
Hoboken, New Jersey. 07030

Professor F. Wagner
Solid Rocket Struct. Integrity Ctr.,
Dept. of Mechanical Engng.
University of Utah
Salt Lake City, Utah. 84112

Dr. M.L. Williams
Dean of Engineering
University of Utah

Salt Lake City, Utah. 84112.

California Inst. of Technology
Attn: Security Officer
(for Prof. W.G. Knauss)
1201 East California Blvd.
Pasadena, California. 91109.

University of California
College of Engineering
Professor K.S. Pister
Berkeley, California. 94720.