

AD-A042 814

PENNSYLVANIA STATE UNIV UNIVERSITY PARK APPLIED RESE--ETC F/G 20/1
SOUND TRANSMISSION IN THE 48-INCH WATER TUNNEL FOR A RANGE OF T--ETC(U)
MAY 77 D E THOMPSON N00017-73-C-1418
TM-77-175 NL

UNCLASSIFIED

1 of 1
ADA042814



END
DATE
FILMED
9-77
DDC



ADA 042814

12

J

6

SOUND TRANSMISSION IN THE 48-INCH WATER TUNNEL FOR A RANGE OF TOTAL AIR CONTENT, PRESSURE, AND VELOCITY,

10

D. E./Thompson

12

14p.

9

Technical Memorandum,

File No. 77-175

18 May 1977

Contract No. N00017-73-C-1418

14

TM-77-175

11

15

Copy No. 32

The Pennsylvania State University
APPLIED RESEARCH LABORATORY
Post Office Box 30
State College, PA 16801

NAVY DEPARTMENT
NAVAL SEA SYSTEMS COMMAND

DDC
RECEIVED
AUG 12 1977
RECEIVED
B

AD No. —

DDC FILE COPY

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED

1473
391007

1B

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TM 77-175	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SOUND TRANSMISSION IN THE 48-INCH WATER TUNNEL FOR A RANGE OF TOTAL AIR CONTENT, PRESSURE, AND VELOCITY		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) D. E. Thompson		8. CONTRACT OR GRANT NUMBER(s) N00017-73-C-1418
9. PERFORMING ORGANIZATION NAME AND ADDRESS Applied Research Laboratory P. O. Box 30 State College, PA 16801		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Sea Systems Command Washington, DC 20362		12. REPORT DATE 18 May 1977
		13. NUMBER OF PAGES 9
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release. Distribution unlimited. Per NAVSEA - July 22, 1977.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) sound transmission pressure attenuation velocity bubbles water air content		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) It is well known that the presence of small bubbles in water can cause attenuation of transmitted sound. An experiment was performed in the 48-inch diameter water tunnel test section to determine the effects of total air content, test section pressure, and velocity on the transmission of sound. It was shown that there is negligible attenuation of sound for typical ranges of the variables considered.		

File No. 77-175
18 May 1977
DET:tms
Total Pages: 9
Total Figures: 3

APPLIED RESEARCH LABORATORY

Internal Memorandum

To: B. R. Parkin, R. E. Henderson, J. W. Holl, F. E. Smith, G. C. Lauchle
M. L. Billet, F. S. Archibald, ARL Files (4), Water Tunnel Files

From: D. E. Thompson

Subject: Sound Transmission in the 48-inch Water Tunnel for a Range of
Total Air Content, Pressure, and Velocity

References: See Page 6

Abstract: It is well known that the presence of small bubbles in water can cause attenuation of transmitted sound. An experiment was performed in the 48-inch diameter water tunnel test section to determine the effects of total air content, test section pressure, and velocity on the transmission of sound. It was shown that there is negligible attenuation of sound for typical ranges of the variables considered.

Acknowledgement: This work was performed under contract with the Naval Sea Systems Command, Code 0371.

ACCESSION for		
NTIS	White Section	<input checked="" type="checkbox"/>
DDC	Buff Section	<input type="checkbox"/>
UNANNOUNCED		<input type="checkbox"/>
JUSTIFICATION		
BY		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	AVAIL.	and/or SPECIAL
A		

Table of Contents

	<u>Page No.</u>
List of Figures	3
Introduction.	4
Test Facility and Apparatus	4
Data Acquisition and Reduction.	4
Descriptions of the Tests	5
Results and Conclusions	5
Future Experiments.	5
References	6

List of Figures

<u>Figure No.</u>	<u>Title</u>	<u>Page No.</u>
1	Schematic of Test Facility and Hydrophones	7
2	Block Diagram of Data Acquisition and Analysis System	8
3	Spread of the Received Sound Level versus Frequency	9

Introduction

Hydrodynamic noise sources have become the subject of increasing experimentation in the various water tunnels at The Applied Research Laboratory in recent years. It is expected that such work will continue at at least the same level of effort in the future. The present memorandum considers determining an important acoustic characteristic of the 48-inch water tunnel.

It is well known that the presence of small bubbles in water will cause attenuation of sound transmitted through it. The amount of attenuation and the frequency at which attenuation occurs is a function of the bubble size distribution, static pressure, density of water, etc., References 1 and 2.

In any water tunnel there is a certain amount and size distribution of free air in the water. If the amount and distribution of free air are known, then techniques exist for estimating the acoustic attenuation due to free air, Reference 2. At the present time, no accurate technique for determining the free air exists at the Fluids Engineering Department. The attenuation of sound has, therefore, been measured directly under typical operating conditions in the 48-inch diameter water tunnel. The effects of total air content, and test section velocity and pressure on the sound transmitted in the test section were measured. The ranges of the considered variables are typical of those encountered in tests involving the measurement of hydrodynamic noise.

Test Facility and Apparatus

Tests were conducted in the test section of the 48-inch diameter water tunnel. The test section is 14 feet long. There are three plexiglass windows on each side of the test section. A water filled tank, external to the test section, spans its length on one side of the test section. A reflecting hydrophone is suspended in the tank and serves as a receiving hydrophone.

A piston hydrophone was mounted in the center of one plexiglass window in the test section, opposite the receiver and served as the sound source. Figure 1 shows this arrangement. For the tests conducted, the sound source and receiver were positioned directly across from each other.

The flow velocity in the test section can be varied from 0 to approximately 60 fps. The pressure in the test section can be varied from approximately 6 to 40 psia. The total gas content can be reduced to approximately 2 ppm.

Data Acquisition and Reduction

A block diagram of the data acquisition and reduction system is shown in Figure 2. The received hydrophone signal was amplified and then transmitted to the real time analyzer. The spectrum of the received signal was obtained for the frequency range 0 to 50 kHz which is the upper limit of the Spectral Dynamics 301-C analyzer. The bandwidth for this frequency range is 150 Hz.

Description of the Tests

The piston hydrophone sound source was excited with white noise by a General Radio model 1390B white noise generator for each test conducted.

Measurements of the spectra of the transmitted sound were made for various flow conditions. The test section velocities considered were 0, 20, 30, 40, and 50 fps. For each of these velocities, the test section pressures considered were 18.2, 9.1, and 6.6 psia. For each combination of velocity and pressure, the total air contents considered were 3.2, and 9.1 ppm on a mole basis. This is a sufficient range of total air contents and pressures to span the conditions at which tests are normally conducted at ARL.

Results and Conclusions

The results of these measurements are shown in Figure 3. This figure shows the spread of the spectra of the sound transmitted through the test section for all test conditions considered. The maximum spread is 2.8 dB at the lower frequencies. This amount of deviation can be ascribed to measurement errors alone and not to any effects of total air content, pressure, or velocity on the transmitted sound. The conclusion is that in the frequency range 0 to 50 kHz, for the range of variables considered insignificant attenuation of sound in the ARL/PSU 48-inch water tunnel.

Future Experiments

Two experiments designed to extend and/or amplify the current results are planned.

The first experiment will employ a laser nuclei counter to measure the bubble size distribution which exists in the water tunnel test section under typical test conditions. The development of the necessary instrumentation and techniques for a useful system are currently underway.

The second experiment will employ a system of high frequency hydrophones, 50 kHz to 300 kHz, to determine the sound attenuation, in that frequency range, in a manner similar to that described in the present memorandum. Mounting systems for the high frequency hydrophones are being designed at the present time.

References

1. Killen, J. M. and J. F. Ripken, "A Water Tunnel Air Content Meter," Report No. 70, St. Anthony Falls Hydraulic Laboratory, University of Minnesota, Minneapolis, Minnesota, February 1964.
2. Brockett, T., "Computational Method for Determination of Bubble Distributions in Liquids," DTNSRDC Report No. 2798, April 1969.




Figure No. 1 Schematic of Test Facility and Hydrophones




Figure No. 2 Block Diagram of Data Acquisition and Analysis System

18 May 1977
DET:tms




Figure No. 3 Spread of the Received Sound Level
versus Frequency

DISTRIBUTION LIST FOR UNCLASSIFIED TM 77-175, by D. E. Thompson dated
18 May 1977

Commander
Naval Sea Systems Command
Department of the Navy
Washington, DC 20362
Attn: Library
Code NSEA-09G32
(Copy Nos. 1 and 2)

Naval Sea Systems Command
Attn: A. L. Palazzolo
Code NSEA-031
(Copy No. 3)

Naval Sea Systems Command
Attn: C. G. McGuigan
Code NSEA-03133
(Copy No. 4)

Naval Sea Systems Command
Attn: L. Benen
Code NSEA-0322
(Copy No. 5)

Naval Sea Systems Command
Attn: E. J. McKinney
Code NSEA-03421
(Copy No. 6)

Naval Sea Systems Command
Attn: E. G. Liszka
Code NSEA-03421
(Copy No. 7)

Naval Sea Systems Command
Attn: G. Sorkin
Code NSEA-035
(Copy No. 8)

Naval Sea Systems Command
Attn: T. E. Peirce
Code NSEA-0351
(Copy No. 9)

Naval Sea Systems Command
Attn: J. G. Juergens
Code NSEA-037
(Copy No. 10)

Naval Sea Systems Command
Attn: A. R. Paladino
Code NSEA-0372
(Copy No. 11)

Commander
Naval Ship Engineering Center
Prince Georges Center
Hyattsville, MD 20782
Attn: R. J. Cauley
Code NSEC-6140B
(Copy No. 12)

Commanding Officer
Naval Underwater Systems Center
Newport, RI 02840
Attn: R. Nadolink
Code SB323
(Copy No. 13)

Naval Underwater Systems Center
Attn: R. Trainor
Code SB323
(Copy No. 14)

Naval Underwater Systems Center
Attn: F. White
Code SB332
(Copy No. 15)

Naval Underwater Systems Center
Attn: Library
Code LA15
(Code No. 16)

Commanding Officer
Naval Undersea Center
San Diego, CA 92132
Attn: J. W. Hoyt
Code 2501
(Copy No. 17)

Naval Undersea Center
Attn: A. G. Fabula
Code 5002
(Copy No. 18)

Commanding Officer & Director
David W. Taylor Naval Ship R&D Center
Department of the Navy
Bethesda, MD 20084
Attn: W. B. Morgan
Code 154
(Copy No. 19)

DISTRIBUTION LIST FOR TM 77-175 (con't)

David W. Taylor Naval Ship R&D Center
Attn: R. Cumming
Code 1544
(Copy No. 20)

David W. Taylor Naval Ship R&D Center
Attn: J. McCarthy
Code 1552
(Copy No. 21)

David W. Taylor Naval Ship R&D Center
Attn: T. Brockett
Code 1544
(Copy No. 22)

David W. Taylor Naval Ship R&D Center
Attn: M. Sevik
Code 19
(Copy No. 23)

David W. Taylor Naval Ship R&D Center
Attn: W. Blake
Code 1942
(Copy No. 24)

David W. Taylor Naval Ship R&D Center
Attn: T. C. Mathews
Code 1942
(Copy No. 25)

David W. Taylor Naval Ship R&D Center
Attn: Tech. Info. Lib.
Code 522.1
(Copy No. 26)

Defense Documentation Center
5010 Duke Street
Cameron Station
Alexandria, VA 22314
(Copy Nos. 27-39)

GTWT
The Pennsylvania State University
APPLIED RESEARCH LABORATORY
P. O. Box 30
State College, PA 16801
(Copy No. 40)