

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TR-3615	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER (9)
4. TITLE (and Subtitle) SUBSONIC WIND TUNNEL TESTS OF A CANARD-CONTROL MISSILE CONFIGURATION IN PURE ROLLING MOTION.		5. TYPE OF REPORT & PERIOD COVERED Continuing Technical Report 1 July 1975-31 October 1976
7. AUTHOR(s) Samuel R. Hardy		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center Dahlgren Laboratory (DK-21) Dahlgren, VA 22448		8. CONTRACT OR GRANT NUMBER(s) (15) (17)
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Air Systems Command Washington, DC 20360		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62332N F32323 WF32323201 DK04AA102 E32310 WF32300000
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) (14) NSWG/DL-TR-3615		12. REPORT DATE June 1977
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		13. NUMBER OF PAGES 87
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
18. SUPPLEMENTARY NOTES		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Subsonic wind tunnel tests Canard-control missile		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The description and run log of subsonic wind tunnel tests on a canard-control missile in pure rolling motion are presented. Test data for the body plus canard plus tail configuration (with 0-deg deflections) of the canard-control missile are shown. The nonlinear second-order differential equation of motion used in the "global" nonlinear least-squares analysis of the test data is discussed. Nonlinear aerodynamic coefficients extracted from the test data are presented and discussed. The results for the body plus canard plus		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

20. (Continued)

→ tail configuration with 0-deg deflections showed that the linear roll damping moment coefficient increases slightly with the angle of attack up to about 20 deg, as predicted. However, at 30 deg the coefficient decreases significantly. ↗

S/N 0102- LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWORD

This technical report documents wind tunnel tests and preliminary data analyses which were conducted from 1 July 1975 to 31 October 1976, under a program to investigate the rolling motion of cruciform canard-control missiles at moderate angles of attack.

This work was supported by Mr. W. C. Volz of the Naval Air Systems Command (AIR-320C) under AIRTASK A03W-350D/004B-6F32-300-000.

The Army Air Mobility Research and Development Laboratory, Moffet Field, California, provided testing facilities and personnel for the wind tunnel tests.

Timely, successful completion of the tests was due to Ms. G. A. Laub, test engineer, and the other staff members of the Army Air Mobility Research and Development Laboratory. Critical repairs to the test equipment were made by members of the NASA, Ames Research Laboratory staff. Photographic support was provided by W. A. Shipman, Naval Surface Weapons Center, Dahlgren Laboratory (NSWC/DL), Photographic Laboratory, Dahlgren, Virginia.

Mr. R. E. Meeker, Naval Weapons Center (NWC), China Lake, California, provided valuable consultation and advice during the tests.

This report was reviewed for technical accuracy and approved by Mr. Frank Stevens, Aeromechanics Branch, Dr. Frankie G. Moore, Head, Aeromechanics Branch, and Mr. Herman Caster, Head, Exterior Ballistics Division of the Warfare Analysis Department.

Released by:

Ralph A. Niemann
RALPH A. NIEMANN, Head
Warfare Analysis Department

ACCESSION for

FIS White Section ☒

Black Section ☐

RECORDED

INDEXED

FILED

MAY 1968

FBI - NEW YORK

A

TABLE OF CONTENTS

	<u>Page</u>
FOREWORD.....	i
LIST OF ILLUSTRATIONS.....	iii
LIST OF TABLES.....	v
INTRODUCTION.....	1
EQUATION OF MOTION.....	1
CONFIGURATIONS AND TEST CONDITIONS.....	8
DISCUSSION OF WIND TUNNEL DATA.....	13
ROLL MOMENT COEFFICIENT EXTRACTION.....	21
DISCUSSION OF RESULTS.....	22
SUMMARY AND FUTURE PLANS.....	32
REFERENCES.....	32
APPENDIXES:	
A. RUN LOG FOR SUBSONIC FREE-ROLLING WIND TUNNEL TESTS OF CANARD-CONTROL MISSILE.....	A-1
B. NOMENCLATURE.....	B-1
DISTRIBUTION	

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	Characteristic Rolling Motion of a Cruciform-Finned (Body Plus Tail) Missile.....	2
2	Roll Damping Moment Coefficient in the Roll "Speed-Up" Region.....	5
3	Canard-Control Missile Configuration Dimensions (Body Plus Canard Plus Tail).....	8
4	Nomenclature and Sign Conventions for Canard and Tail Deflections.....	10
5	Wind Tunnel Model in Army Air Mobility Research and Development Laboratory's 7 x 10 ft Wind Tunnel.....	11
6	Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 0-deg Angle of Attack.....	14
7	Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 5-deg Angle of Attack.....	15
8	Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 10-deg Angle of Attack.....	16
9	Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 15-deg Angle of Attack.....	17
10	Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 20-deg Angle of Attack.....	18
11	Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 25-deg Angle of Attack.....	19
12	Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 30-deg Angle of Attack.....	20

LIST OF ILLUSTRATIONS (Continued)

<u>Figure</u>		<u>Page</u>
13	Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 0-deg Angle of Attack.....	23
14	Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 5-deg Angle of Attack.....	24
15	Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 10-deg Angle of Attack.....	25
16	Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 15-deg Angle of Attack.....	26
17	Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 20-deg Angle of Attack.....	27
18	Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 25-deg Angle of Attack.....	28
19	Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 30-deg Angle of Attack.....	29
20	Comparison of Predicted and Experimental Linear Roll Damping Moment Coefficients for Body Plus Canards Plus Tail Configuration With 0-deg Deflections.....	30
21	Experimental Fin Cant Moment Coefficients for Body Plus Canard Plus Tail Configuration With 0-deg Deflections..	31
22	Experimental Induced Static Roll Moment Coefficients for Body Plus Canard Plus Tail Configuration With 0-deg Deflections.....	31

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Aerodynamic Roll Moment Coefficient Correlation.....	6
2	Configuration Fin Deflections.....	9
A-1	Run Log for Subsonic Free-Rolling Wind Tunnel Test of Canard-Control Missile.....	A-1

INTRODUCTION

The work presented herein is part of a joint program with the Naval Weapons Center (NWC), China Lake, California, to improve the methods of predicting the rolling motion of non-roll-controlled guided missiles. Improved prediction of rolling motion may simplify guidance systems and provide some further insight into the roll characteristics of canard-control missiles that fly at high angles of attack.

The specific objective of the Naval Surface Weapons Center (NSWC) in this program is to experimentally determine dynamic roll moment coefficients (roll damping) of a cruciform, canard-control missile airframe. The experimental data are to be used by NWC to evaluate NWC-sponsored prediction techniques of roll damping characteristics of cruciform, canard-control missiles. The experimental data will serve as a data base for comparison with "theory."

NSWC had previously developed the analysis tools needed to extract static and dynamic roll moment coefficients as a function of angle of attack from experimental angular roll data. A "global" nonlinear least-squares fitting procedure was developed to extract nonlinear roll moment coefficients from single-degree-of-freedom rolling motion data. The equation of motion used in the procedure was developed for cruciform-finned (body plus tail) missile configurations. The fitting procedure and the equation of motion were used successfully to extract nonlinear roll coefficients of cruciform-finned and wrap-around-finned missile configurations. It seemed logical to extend the fitting procedures to more complex configurations such as the canard-control configuration, even though the equation of motion was not specifically developed for guided-missile configurations.

NSWC was tasked to conduct wind tunnel tests and analyze part of the test data in Fiscal Years 76 and TQ. Only the test data for the body plus canard plus tail configuration (with 0-deg deflections) were analyzed during the past year. This technical report summarizes the work performed in Fiscal Years 76 and TQ.

EQUATION OF MOTION

The "global" nonlinear least-squares fitting procedure used to extract the nonlinear roll moment coefficients requires a second-order nonlinear differential equation of motion which contains adequate coefficients to describe the roll characteristics of the test configuration in order to fit the observed data. To the writer's knowledge, there has been no complete formulation of a pure rolling equation of motion for a canard-control missile at high angles of attack. Therefore, it was

decided to use the equation of motion developed for the cruciform body plus tail configuration (Reference 1). This previously developed equation was thought to be adequate for canard-control configurations which have 90-deg roll symmetry. It was assumed that the body plus canard plus tail configuration with 0-deg deflections would exhibit rolling motion characteristics similar to cruciform body plus tail configurations.

The basic characteristics of free rolling motion of cruciform body plus tail were described by Nicolaides in References 2 and 3. The basic characteristics, "linear" rolling motion, roll "slow-down," roll "lock-in," roll "break-out," and roll "speed-up" occur as the missile's angle of attack increases from 0 to 90 deg. Figure 1 shows the roll characteristics as a function of angle of attack for a typical cruciform-finned missile with fin cant at low subsonic speeds. In this wind tunnel case, the missile has only a roll degree-of-freedom. Therefore,

$$p = \dot{\gamma}$$

where γ is the roll orientation.




Figure 1. Characteristic Rolling Motion of a Cruciform-Finned (Body Plus Tail) Missile

The "linear" rolling motion occurs at small angles of attack. The steady-state roll rate is invariant with changes in the angle of attack in the "linear" region. The magnitude of the steady-state spin rate is proportional to the fin cant and the roll damping is considered to be a linear function of spin rate at low spin rates near the steady-state spin rate. However, at very high spin rates, the damping may be a nonlinear function of spin rate. The classical equation of rolling motion at a particular angle of attack in the "linear" region is:

$$\frac{I_{x_p} \dot{p}}{Q S d} = C_{l_{\delta}}(\alpha) \delta + C_{l_p}(\alpha) \frac{p d}{2V} \quad (1)$$

Equation (1) is considered adequate to describe the rolling motion in the "linear" region at low spin rates.

As the angle of attack is increased from the "linear" region where the steady-state roll rate is independent of the angle of attack, the steady-state spin rate decreases. The "slow-down" in the steady-state spin rate is caused because the ratio of the fin cant moment to the roll damping moment is decreased. The decrease in this ratio may be due to a loss in fin cant moment effectiveness due to the angle of attack or an increase in the roll damping moment due to the angle of attack or both. The classical equation of rolling motion, Equation (1), is still adequate to describe the rolling motion at angles of attack in the roll "slow-down" region. As mentioned before, at high spin rates the damping may be a nonlinear function of spin rate.

As the angle of attack increases from the roll "slow-down" region, roll "lock-in" occurs. Roll "lock-in" is characterized by oscillatory rolling motion about a roll trim angle. The amplitude of the oscillatory motion is less than ± 45 deg from the roll trim angle. The amplitude may damp at the lower angles of attack in the "lock-in" region. At higher angles of attack within the "lock-in" region, the amplitude of roll oscillations may be constant. Depending upon the initial roll conditions, a missile with fin cant at a particular angle of attack within the "lock-in" region may exhibit a non-zero, steady-state spin rate as well as "lock-in." Nicolaides showed in Reference 3 that the induced rolling moment, which varies as a function of missile angle of attack and roll orientation, causes the oscillatory rolling motion. The induced roll moment coefficient for a cruciform missile at a particular angle of attack was defined as:

$$C_{l(\gamma)} = C_{l(4\gamma)}(\alpha) \sin 4\gamma. \quad (2)$$

However, Daniels in Reference 4 found that the induced roll moment coefficient was better described by the Fourier sine series;

$$C_{\ell}(\gamma) = \sum_{k=1}^{\infty} C_{\ell}(4k\gamma)(\alpha) \sin 4k\gamma. \quad (3)$$

Equation (3) with higher-order terms was adequate to describe the induced rolling moment at angles of attack from 0 deg up to 90 deg. The amplitude of the induced roll moment generally increases with the angle of attack. For "lock-in" to occur, the induced roll moment must balance the fin cant moment. The roll angle at which this balance occurs is the roll trim angle. The roll trim angle varies with the angle of attack because of variation in the induced rolling moment and the fin cant moment. In the "lock-in" region the roll oscillations are dynamically stable; however, as the angle of attack is increased, the roll oscillation becomes unstable and the amplitude of the oscillations grows about a roll trim angle until the missile "breaks-out" and rolls at a steady-state rate. The region where the oscillations are dynamically unstable and the steady-state rates are high is referred to as roll "speed-up." Figure 1 shows that at low angles of attack within the roll "speed-up" region, roll "break-out" occurs only in the spin direction of the fin cant. At higher angles of attack, the roll "break-out" occurs in both the positive and negative spin directions; however, the roll "speed-up" steady-state rates are higher in the direction of the fin cant. If a missile does not have fin cant, then the missile "breaks-out" in both positive and negative directions at the same angle of attack and the steady-state roll rates in the roll "speed-up" region are equal. Daniels showed in Reference 4 that the motion in the roll "speed-up" region could be explained by using a roll damping torque that is a cubic function of spin rate. Figure 2 shows that undamping (positive damping) occurs at spin rates less than the steady-state spin rate so the missile "breaks-out" and "speeds-up" to the steady-state spin rate. If the missile is forced to spin at rates above the steady-state rate where the roll damping is negative, then the missile will slow down to the steady-state spin rate. Daniels (Reference 4) assumed that the damping coefficient at a particular angle of attack could be expressed as a Taylor series whose coefficients depend on the odd powers of spin rate;

$$C_{\ell}(p) = \sum_j C_{\ell j}(\alpha) \left(\frac{pd}{2V} \right)^j, \quad (4)$$

where $j = 1, 3, 5, \dots, \infty$.

Using superposition of forces (Reference 3), the fin cant moment, Fourier series for the induced moment, and the Taylor series for roll damping are combined into a more general differential equation,

$$\frac{\dot{\gamma} I_x}{Q S d} = C_{l_\delta}(\alpha) \delta + \sum_{jk} C_{l_{\dot{\gamma}_{jk}}}(\alpha) \dot{\gamma}_{jk}^j \sin(4k\gamma + 1/2j\pi). \quad (5) *$$




Figure 2. Roll Damping Moment Coefficient in the Roll "Speed-Up" Region

Equation (5) describes the rolling motion of a cruciform-finned missile at angles of attack from 0 through 90 deg. It is important to note that true steady-state spin rates exist only at 0 deg or very small angles of attack where the induced moment is negligible. At higher angles of attack, the roll rates approach quasi-steady-state roll rates because the induced roll moment is periodic.

Cohen and Clare in Reference 1 modified Equation (5) so that it could be incorporated into a computer program which uses the "global" nonlinear least-squares procedures to extract roll moment coefficients.

* Equation (5) is due to Dr. C. J. Cohen, Research Associate for the Warfare Analysis Department, Naval Surface Weapons Center, Dahlgren Laboratory, Dahlgren, Virginia.

Cohen, Clare, and Stevens in Reference 5 then modified the differential equation to include mass and/or aerodynamic asymmetry terms. The modified equation became:

$$\ddot{\gamma} = Q \sum_{j=0}^J \left(\frac{\dot{\gamma} d}{2V} \right)^j \sum_{k=0}^K (C_{jk} \cos 4k\gamma + S_{jk} \sin 4k\gamma) \quad (6)$$

$$+ C_{ac} \cos \gamma + C_{as} \sin \gamma$$

$$\gamma(0) = \gamma_0 \quad \dot{\gamma}(0) = \dot{\gamma}_0$$

The correspondence between the aerodynamic coefficients in Equation (6) (C_{jk} and S_{jk}) and more conventional nomenclature used in Equation (5) is shown in Table 1.

Table 1. Aerodynamic Roll Moment Coefficient Correlation*

Coefficient		Description
Conventional Nomenclature	Computer Program Nomenclature	
$C_{l_{\delta}}$	C_{00}	Fin cant roll moment coefficient
$C_{l_{\delta(4\gamma)}}$	C_{01}	Variation of fin cant moment Coefficient with roll angle
$C_{l_{\delta(8\gamma)}}$	C_{02}	
$C_{l_{\delta(12\gamma)}}$	C_{03}	
$\vdots$	$\vdots$	
$C_{l_{\delta(4K\gamma)}}$	C_{0K}	

*All coefficients are a function of the missile's angle of attack.

Table 1. Aerodynamics Roll Moment Coefficient
Correlation* (Continued)

Coefficient		Description
Conventional Nomenclature	Computer Program Nomenclature	
C_{ℓ_p}	C_{10}	Linear roll damping moment coefficient
$C_{\ell_p^2}$	C_{20}	Quadratic roll damping moment coefficient
$C_{\ell_p^3}$	C_{30}	Cubic roll damping moment coefficient
$\vdots$	$\vdots$	
$C_{\ell_p^j}$	C_{j0}	j^{th} order roll damping moment coefficient
$C_{\ell_p(4\gamma)}$	C_{11}	Variation of linear roll damping Moment coefficient with roll Angle
$C_{\ell_p(8\gamma)}$	C_{12}	
$C_{\ell_p(12\gamma)}$	C_{13}	
$\vdots$	$\vdots$	
$C_{\ell_p(4k\gamma)}$	C_{1K}	
$C_{\ell(4\gamma)}$	S_{01}	Induced rolling moment coefficients
$C_{\ell(8\gamma)}$	S_{02}	
$C_{\ell(12\gamma)}$	S_{03}	
$\vdots$	$\vdots$	
$C_{\ell(4K\gamma)}$	S_{0K}	
	C_{ac}	Roll asymmetry coefficients (Combinations of aerodynamic and mass asymmetry constants)
	C_{as}	

*All coefficients are a function of the missile's angle of attack.

CONFIGURATIONS AND TEST CONDITIONS

Figure 3 shows a sketch of the basic missile configuration used in this test. This configuration was recommended by NWC.

The three-inch model used in this test had canards and tail fins with planar cross sections and rounded leading edges. The model was designed so that body build-up configurations (body plus canards, body plus tail, and body plus canard plus tail) could be tested. The body build-up configurations were tested to determine the contribution of the canards, tails, and canard-tail interference to the roll damping torque. The individual canards were adjusted to fixed deflection angles during testing. Five different canard deflection patterns were selected to approximate missile canard deflections during different maneuvers. The patterns chosen included 0-deg deflection and deflections to provide roll torque, pitch control, roll torque with pitch, and off-axis pitch control. Two sets of tail fins provided 0- and 5-deg fin cant roll torque. Table 2 gives the canard and tail fin deflection used on each of the 17 body build-up configurations. Figure 3 shows the canard-control missile configuration dimensions. The nomenclature and sign convention for the canard and tail deflections is shown in Figure 4. The model was mounted on a free-rolling air bearing which had negligible friction eliminating bearing friction force in the analysis of the test data.




Figure 3. Canard-Control Missile Configuration Dimensions
(Body Plus Canard Plus Tail)

Table 2. Configuration Fin Deflections

Configuration	Deflections (deg)							
	Canards				Tail			
	C1	C2	C3	C4	T1	T2	T3	T4
Body plus Tail	-	-	-	-	0	0	0	0
	-	-	-	-	5	5	5	5
Body plus Canard								
Zero Deflection	0	0	0	0	-	-	-	-
(Differential								
Canard Cant)	10	0	10	0	-	-	-	-
(Pitch Control								
with Differential								
Canard Cant)	10	15	10	-15	-	-	-	-
(Pitch Control								
Only)	0	15	0	-15	-	-	-	-
(Off-Axis Pitch								
Control)	15	15	-15	-15	-	-	-	-
Body plus Canard								
plus Tail	0	0	0	0	0	0	0	0
	10	0	10	0	0	0	0	0
	10	15	10	-15	0	0	0	0
	0	15	0	-15	0	0	0	0
	15	15	-15	-15	0	0	0	0
	0	0	0	0	5	5	5	5
	10	0	10	0	5	5	5	5
	10	15	10	-15	5	5	5	5
	0	15	0	-15	5	5	5	5
	15	15	-15	-15	5	5	5	5




Figure 4. Nomenclature and Sign Conventions for Canard and Tail Deflections

The tests were conducted in the 7 x 10 ft low-speed wind tunnel of the Army Air Mobility Research and Development Laboratory, Moffet Field, California. The air bearing that supported the model was mounted on a general purpose sting. Although the sting was capable of providing combinations of pitch, yaw, and roll angles, the sting was programmed to provide only yaw in the horizontal plane. The yaw angle is the total angle of attack; therefore, no distinction is made between them. Each configuration was tested at angles of attack from 0 through 30 deg in 5-deg increments. The angle of attack was fixed during each data run.

The rolling motion of the model was recorded using a high-speed movie camera. The camera was equipped with a timing generator which provided precise timing marks on the film records at the rate of ten marks per second. The lens of the camera was mounted on a flexible fiber optics cable so that the centerline of the lens could be mounted closer to the model's axis of rotation. The fiber optics cable also allowed the camera to be moved further downstream from the model. The trailing edges of the canards and tail fins were coded so that the roll orientation of the model could be determined from the movie film. The film provided roll orientation versus time data. The lens and movie camera were mounted on the sting so that they moved in pure yaw, always pointing parallel to the model's roll axis. A photograph of the test equipment is shown in Figure 5.




Figure 5. Wind Tunnel Model in Army Air Mobility Research and Development Laboratory's 7 x 10 ft Wind Tunnel

To obtain proper rolling motion, the initial conditions of the missile must be controlled. A solenoid-actuated pin at the base of the missile locked the missile at a fixed roll angle until the wind tunnel test conditions had stabilized. At the beginning of a test run, the pin was pulled, unlocking the model to roll freely. In other runs, the missile was spun-up to a high spin rate at the beginning of the test. An external jet of air was created by a nozzle on the end of a long pressurized pipe. The pipe, referred to as a wand, was used to position the air jet so that it blew against the model's fins spinning the model up. When the model reached adequate spin rates, the wand was withdrawn from the flow field in the wind tunnel, thus, beginning the run. The wand was used (with the air jet cut off) to manipulate the model to find roll "lock-in" phenomena.

The wind tunnel was operated at a dynamic pressure (Q) of approximately 15 psf (718.2 Pa) due to the load limitations of the air bearing. The nominal velocity of the tests was about 113 ft/s (34.44 m/s). The exact flow conditions in the tunnel at the time of each data run were recorded by an auxiliary computer.

The initial conditions of each run depended on the configuration and the type of motion the configuration exhibited at the particular angle of attack of the run. Configurations with tail fin cant and/or canard cant that exhibited steady-state roll rates used the solenoid pin to hold the model at $\gamma_0 = 0$ -deg roll orientation until the tunnel was stabilized at the test conditions. Then the camera was turned on and the pin was pulled. The camera photographed the missile as it spun-up to a steady-state rate. If oscillatory motion was observed, then various roll orientations were used as initial conditions to explore the rolling motion for dual modes, "lock-in," and roll oscillations. Roll oscillations were needed to extract the induced roll moment coefficients. If a configuration did not exhibit a steady-state roll rate, then the model was spun-up using the air jet on the wand. When the tunnel was running at test conditions and the model was spun-up to an adequate rate, the wand was withdrawn from the wind tunnel just before the camera was turned on. The camera was not stopped until the motion of the missile stopped or the motion reached a quasi-steady-state rate.

Appendix A contains a run log for the wind tunnel test. The log includes configuration canard and tail deflections, tunnel flow conditions, angle of attack, initial conditions, and remarks about the rolling motion of configuration for each run.

DISCUSSION OF WIND TUNNEL DATA

The results of the wind tunnel tests included approximately 350 data runs that were recorded by high-speed movie film and a run log documenting test conditions for these runs. Repeat runs were conducted and are included in the 350 runs. The film data were reduced to roll orientation versus frame number by digitizing the roll angle on each frame. Timing marks were also read so that the frame number could be converted into time. Because of funding limitations, only seven data runs were digitized and analyzed. The body plus canard plus tail configuration with 0-deg control deflections was selected for analysis because it is a complete, simple, symmetric configuration which is more amenable to theoretical analysis. Figures 6 through 12 show the roll orientation versus frame number for the configuration, covering the angle-of-attack range from 0 to 30 deg. The roll orientation angle is shown on a scale from 0 to 360 deg to produce a useful size graph.

Since this configuration did not possess intentional fin cant, the missile was spun-up and then allowed to damp at each angle of attack. At angles of attack 0 and 5 deg, the missile damped to a small steady-state rate due to some unintentional asymmetry which produced a small roll torque. The consistent decay of spin rate to a small steady-state spin rate is predicted by linear theory (Equation (1)). At angles of attack from 10 to 25 deg, the missile's spin rate decays until the missile exhibits damped roll oscillation about a roll trim angle (lock-in). The fluctuation in the spin rate every 90 deg and the preferred roll orientation indicate the presence of the induced roll moment. The motion is similar to the rolling motion that the cruciform body-tail missile exhibited in the "lock-in" region. The frequency of the roll oscillations indicates that the induced roll moment increases with increasing angles of attack. At a 30-deg angle of attack, the missile spin rate decays until oscillatory motion begins; however, the oscillatory motion does not damp. This motion is neither roll "lock-in" nor "speed-up." Similar motion was observed and documented for the cruciform body-tail missile in Reference 6. Thus, it appears that the motion of the body plus canard plus tail configuration with 0-deg deflection is similar to the motion exhibited by a cruciform body plus tail configuration. For this reason, Equation (6) was used as the equation of motion for the canard missile configuration in the procedure to extract the nonlinear roll moment coefficients.




Figure 6. Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 0-deg Angle of Attack




Figure 7. Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 5-deg Angle of Attack




Figure 8. Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 10-deg Angle of Attack




Figure 9. Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 15-deg Angle of Attack




Figure 10. Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 20-deg Angle of Attack




Figure 11. Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 25-deg Angle of Attack




Figure 12. Observed Roll Angle Versus Frame Number for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 30-deg Angle of Attack

ROLL MOMENT COEFFICIENT EXTRACTION

The "global" nonlinear least-squares procedure fits the roll equation of motion (Equation (6)) to segmented observed rolling motion data. The fitting process requires the variation of the sum of the squares of the residuals (between observed and computed roll angles) with respect to perturbed coefficients to vanish. The coefficients are incremented in an iterative fashion until the sum of the squares of the residuals converge. The observed data was divided into segments. The segment size was made as large as possible, but small enough to allow convergence during both "local" and "global" fitting. Equation (6) is fit "locally" to each of the observed data segments using constant best estimate roll moment coefficients to determine initial conditions (roll angle and roll rate) for that segment. The initial conditions are determined for each segment independent of the other segments. All of the observed data segments are fit "globally" to obtain a new set of roll moment coefficients and new initial conditions for each segment. Discontinuities or jumps occur in the computed roll rate and roll angle between the segments. The jumps are needed because the sum of the square of the residuals may become too large for convergence when the data is fit over a long time period. The large residuals may be due to truncation of the equation of motion, unmodeled turbulence, or other unmodeled transients in the wind tunnel. The jump in roll angle and roll rate due to independent initial conditions of a segment allow a restart of the motion in regions where the rolling motion is sensitive to accumulated error of roll angle and roll rate. Estimates of the fin cant moment coefficient, linear roll damping, and induced roll moment coefficient were used to begin the fitting process. Estimates of the initial roll angle and roll rate for each segment were estimated from the observed data. Once a fit was obtained, additional coefficients were included until all of the desired coefficients were obtained or until the fitting procedure would not converge. Then the segments were made as long as possible while allowing convergence. Large segments were desired so that the inaccuracy in the aerodynamic coefficients due to the jumps in the segments' initial condition would be minimized. These techniques were applied to each data run until a set of roll moment coefficients were obtained at each angle of attack.

The method and equations employed in the "global" nonlinear least-squares fitting procedure are contained in detail in References 1 and 5. Description of the computer program utilizing the fitting technique to extract the roll moment coefficients is presented in Reference 7.

DISCUSSION OF RESULTS

Five aerodynamic coefficients were considered in fitting the seven data runs of the body plus canard plus tail configuration with 0-deg deflections. The coefficients included fin cant, linear damping, induced roll moment, and the roll asymmetry terms. Two additional higher order, induced roll moment coefficients were extracted from the run at 30-deg angle of attack because of the oscillatory data in that run. Five coefficients were thought to be adequate to describe the motion exhibited in the data runs. Higher order roll damping coefficients were not extracted since these coefficients are usually determined from roll "speed-up" data. Figures 13 through 19 show comparison plots of the observed and computed roll angle data for the seven angles of attack. Comparison of Figures 6 through 12 and Figures 13 through 19, respectively, shows the correlation between frame number and time. The computed curves were calculated using the extracted coefficients. The small lines drawn normal to the computed curves indicate segment locations. The plots show that there is good agreement between the observed and computed roll angles considering the small number of segments used. In Figure 14, a portion of data is missing due to a camera malfunction; however, the results are not significantly affected since the data were segmented around the gap in the data. Better fits could have been obtained in Figures 17 and 18 by adding higher order induced and damping terms (e.g., S_{02} , S_{03} , C_{11} , C_{12}).

Figure 20 presents a comparison plot of the extracted and predicted linear roll damping coefficients as functions of angle of attack. The predicted roll damping coefficient values were taken from Reference 8. The experimental and predicted values compare favorably at all angles of attack except 30 deg. A decrease in roll damping would be expected since the roll damping of a cruciform body plus tail missile becomes positive in the roll "speed-up" region. The roll "speed-up" region may begin at a 45-deg angle of attack in some cruciform body plus tail configurations. Amplitudes of the oscillatory motion in Figure 19, also, indicate that the damping is nearly zero.

RUN 262 - GAMMA VERSUS TIME

× OBSERVED (EVERY 4TH PT PLOTTED)
 - COMPUTED




Figure 13. Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 0-deg Angle of Attack

RUN 263 - GAMMA VERSUS TIME




Figure 14. Comparison of Observed and Computed
 Roll Angles for Body Plus Canard
 Plus Tail Configuration With 0-deg
 Deflections at 5-deg Angle of Attack

RUN 264 - GAMMA VERSUS TIME




Figure 15. Comparison of Observed and Computed
 Roll Angles for Body Plus Canard
 Plus Tail Configuration With 0-deg
 Deflections at 10-deg Angle of Attack

RUN 265 - GAMMA VERSUS TIME




Figure 16. Comparison of Observed and Computed
 Roll Angles for Body Plus Canard
 Plus Tail Configuration With 0-deg
 Deflections at 15-deg Angle of Attack

RUN 266 - GAMMA VERSUS TIME




Figure 17. Comparison of Observed and Computed
 Roll Angles for Body Plus Canard
 Plus Tail Configuration With 0-deg
 Deflections at 20-deg Angle of Attack

RUN 267 - GAMMA VERSUS TIME




Figure 18. Comparison of Observed and Computed Roll Angles for Body Plus Canard Plus Tail Configuration With 0-deg Deflections at 25-deg Angle of Attack

RUN 268 - GAMMA VERSUS TIME

X OBSERVED (EVERY 4TH PT PLOTTED)
 — COMPUTED




Figure 19. Comparison of Observed and Computed
 Roll Angles for Body Plus Canard
 Plus Tail Configuration With 0-deg
 Deflections at 30-deg Angle of Attack




Figure 20. Comparison of Predicted and Experimental Linear Roll Damping Moment Coefficients for Body Plus Canards Plus Tail Configuration With 0-deg Deflections

The extracted fin cant moment coefficient versus angle of attack is shown in Figure 21. These results appear reasonable at angles of attack from 0 through 15 deg because a small positive roll torque was observed. The results obtained for the fin cant coefficient ($C_{\ell \delta}$) at higher angles of attack were unexpected and no explanation is presented for these results.

Figure 22 shows that the induced roll moment coefficient ($C_{\ell(4\gamma)}$) generally increases with the angle of attack. An error is present in the data point at a 0-deg angle of attack. The induced roll moment should be 0 at 0-deg angle of attack. The absence of 0-deg oscillatory type motion in the observed data at 0-deg angle of attack (shown in Figure 13) indicates that the induced roll moment is zero. The error may have occurred because there was no oscillatory data. The small negative value for the induced roll moment coefficient at a 5-deg angle of attack is expected since the cruciform body plus tail configuration in Reference 3 exhibited similar small negative values at small angles of attack.




Figure 21. Experimental Fin Cant Moment Coefficients for Body Plus Canard Plus Tail Configuration with 0-deg Deflections




Figure 22. Experimental Induced Static Roll Moment Coefficients for Body Plus Canard Plus Tail Configuration with 0-deg Deflections

SUMMARY AND FUTURE PLANS

Subsonic free-rolling wind tunnel tests have been conducted on 17 canard missile configurations. Wind tunnel data have been reduced to roll angle versus frame number for seven data runs of the body plus canard plus tail configuration with 0-deg deflections. At least five basic coefficients were extracted from the seven data runs. The extracted coefficient results were provided to NWC. The results for the body plus canard plus tail configuration with 0-deg deflections showed that the linear roll damping moment coefficient (C_{l_p}) increases slightly with angle of attack up to about 20 deg, as predicted. However, at 30 deg, the coefficient decreases significantly. The induced static roll moment ($C_{l(4\gamma)}$) was slightly negative at 5-deg angle of attack and increased positively with increasing angle of attack through 30 deg as expected.

In future work, body plus tail and body plus canard configurations with 0 deg deflections will be analyzed to determine canard, tail, and canard/tail interference contributions to the roll damping of a complete canard missile configuration. In addition, the body plus canard plus tail configuration with 15-deg pitch control deflections will be analyzed to determine the effect of a large pitch deflection on the missile's roll damping.

REFERENCES

1. Cohen, C. J. and T. A. Clare, Analysis of the Rolling Motion of Finned Missiles at Large Angles of Attack, NWL Technical Report TR-2671, Naval Weapons Laboratory, Dahlgren, VA, February 1972.
2. Nicolaidis, J. D., An Hypothesis for Catastrophic Yaw, Bureau of Ordnance, U.S. Navy, TN-18, 1955.
3. Nicolaidis, J. D., Missile Flight and Astrodynamics, Bureau of Naval Weapons, TN-100A, 1961.
4. Daniels, P., A Study of the Nonlinear Rolling Motion of a Four-Finned Missile, Journal of Spacecraft and Rockets, Volume 7, No. 4, April 1970.
5. Cohen, C. J., T. A. Clare, and F. L. Stevens, Analysis of the Nonlinear Rolling Motion of Finned Missiles, AIAA Paper No. 72-980, Palo Alto, CA, 1972.

REFERENCES (Continued)

6. Stevens, F. L., Subsonic Wind Tunnel Tests of the Basic Finner Missile in Pure Rolling Motion, NWL Technical Note TN-K-4/72, Naval Weapons Laboratory, Dahlgren, VA, February 1972.
7. Reynolds, J. H., ROMOF a CDC 6700 Computer Program for Fitting Rolling Motion Data of Cruciform-Finned Missiles, NWL Technical Note TN-K-42/76, Naval Weapon Laboratory, Dahlgren, VA, July 1973.
8. Meeker, R. E., Estimation of the Damping in Roll of a Canard Cruciform Missile in Incompressible Flow, NWC Technical Note 4063-251, Naval Weapons Center, China Lake, CA, January 1976.

APPENDIX A

RUN LOG FOR SUBSONIC FREE-ROLLING WIND TUNNEL TEST OF
CANARD-CONTROL MISSILE

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile

EXPERIMENTAL CANARD - CONTROL MISSILE											
RUN NO.	CONFIGURATION				Q (PSF)	TEMP. ° (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)						SPUN-UP	PIN-PULL ANGLE (DEG)	
	δC_1 δC_2	δC_3 δC_4	δT_1 δT_2	δT_3 δT_4							
0	-	-	0	0	0	-	-	-	-		Model has asymmetry Zero Frame
1	-	-	0	0	0	15.16	522.9	113.19	2124.2	Spun-Up Wand	Air Bearing P = 40 PSI Wand Pressure = 200 PSI
2	-	-	0	0	0	15.16	523.3	113.23	2124.2	"	
3	-	-	0	0	0	14.97	523.6	112.54	2124.4	"	Weak Lock-in Begins
4	-	-	0	0	0	15.47	523.6	114.42	2123.9	"	Lock-in
5	-	-	0	0	0	15.08	524.0	113.01	2124.3	"	Lock-in
6	-	-	0	0	0	15.16	524.0	113.30	2124.2	"	Lock-in Strong
7	-	-	0	0	0	15.18	528.1	113.86	2122.7	+15	Pin Pull
8	-	-	0	0	0	15.14	528.4	113.75	2122.8	+30	
9	-	-	0	0	0	14.66	528.8	111.95	2123.2	+15	Few Oscillations
10	-	-	0	0	0	15.01	528.8	113.28	2122.9	+30	Few Oscillations Poor
11	-	-	0	0	0	14.93	528.4	112.95	2123.0	7.5	3 Few Oscillations Poor

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE											
RUN NO.	CONFIGURATION				Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)						SPUN-UP	PIN-PULL ANGLE (DEG)	
	δ_{C1} δ_{C2}	δ_{C3} δ_{C4}	δ_{T1} δ_{T2}	δ_{T3} δ_{T4}							
12	-	-	+5	+5	15.08	527.7	113.46	2122.9		Pin-Pull 0	SWITCHED TO CANTED FINS 420 r.p.m. Steady-State
13	-	-	+5	+5	15.08	526.7	113.35	2122.9		0	420 r.p.m. Steady-State
14	-	-	+5	+5	14.87	526.0	112.47	2123.0		0	0 - Steady-State r.p.m.
15	-	-	+5	+5	15.10	526.0	113.35	2122.9		0	"
16	-	-	+5	+5	15.12	526.0	113.42	2122.8		0	"
17	-	-	+5	+5	15.10	525.8	113.32	2122.8		0	"
18	-	-	+5	+5	15.08	525.8	113.25	2122.8		0	Steady-State Rate Mode Dual Mode
19	-	-	+5	+5	15.03	525.0	112.94	2122.9		52.5	Good Oscillations Lock-in Mode
20	-	-	+5	+5	15.26	516.4	112.99	2118.4		75.0	3 Oscillation to Steady-State Rate
21	-	-	0	0	15.04	519.8	112.57	2118.6		0	Switch to 0° Tail Fins Lock-in Large Amplitude Damping
22	-	-	0	0	8.24	521.2	83.31	2125.7		45	Bad 0 Set

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)	δ_{C1}	δ_{C2}	δ_{C3}	δ_{C4}	δ_{T1}	δ_{T2}	δ_{T3}	δ_{T4}	SPUN-UP	PIN-PULL ANGLE (DEG)	
23	-	-	-	-	-	-	-	-	-	-	-	45	Lock-in-Large Amplitude Build-up
					30.0	15.03	522.2	112.76	2118.6				
24	0	0	0	0	-	-	-	-	-	-	-		Tail Fins Off - Switch to Canards
					0°	14.99	526.4	113.06	2118.7		Spun-Up Wand		Wand Pressure = 150 PSI Damping
25	0	0	0	0	-	-	-	-	-	-	-		"
					5°	15.26	526.4	114.08	2118.4		Spun-Up Wand		
26	0	0	0	0	-	-	-	-	-	-	-		Shut Down - Main Generator
					10°	15.20	526.7	114.07	2112.1		Spun-Up Wand		Wand Pressure = 150 PSI
27	0	0	0	0	-	-	-	-	-	-	-		Lock-in at 15°
					15°	14.99	527.0	113.30	2112.3		Spun-Up Wand		
28	0	0	0	0	-	-	-	-	-	-	-		
					20°	14.83	527.7	112.79	2112.5		Spun-Up Wand		
29	0	0	0	0	-	-	-	-	-	-	-		
					25°	15.08	527.7	113.74	2112.2		Spun-Up Wand		
30	0	0	0	0	-	-	-	-	-	-	-		Possible Lock-in at 0° and 45°
					30°	15.28	528.1	114.51	2112.0		Spun-Up Wand		
31	0	0	0	0	-	-	-	-	-	-	-		Pin-Pull 37.5
					30°	15.28	532.7	115.01	2112.1				5 small oscillations at 0° Lock-in
32	0	0	0	0	-	-	-	-	-	-	-		Pin-Pull 45 + 180 = 225° Small Oscillations at 45°
					30°	14.97	532.9	113.86	2112.4			45 225.0	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSEA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	δ_{C1}	δ_{C2}	δ_{C3}	δ_{C4}									δ_{T1}
33	0	0	0	0	-	-	533.6	115.24	2107.1		37.5	Small Oscillations at 45°	
34	0	0	0	0	-	-	533.9	115.86	2107.0		22.5	Small Oscillations at 0° Vertical Lock-in	
35	0	0	0	0	-	-	534.3	114.73	2107.2		180+22.5 202.5	Small Oscillations at 0° Vertical Lock-in	
36	0	0	0	0	-	-	534.3	114.80	2107.2		30	Small Oscillations at 45°	
37	0	0	0	0	-	-	533.6	113.99	2107.4		0	Small Oscillations at 45°	
38	0	0	0	0	-	-	533.2	113.95	2107.5		0	Small Oscillations at 45°	
										Changed Two Canard		Angles - δ_{C1} and δ_{C3}	
39	+10	0	+10	0	-	-		114.98	2107.1		Pin-Pull 0	0 to Steady-State r.p.m. Steady-State 440 r.p.m.	
40	+10	0	+10	0	-	-		113.10	2107.6		Pin-Pull 0	0 to Steady-State r.p.m.	
41	+10	0	+10	0	-	-		115.08	2107.1		Pin-Pull 0	0 to Steady-State r.p.m.	
42	+10	0	+10	0	-	-		113.57	2107.4		Pin-Pull 0	0 to Steady-State r.p.m. Weak Lock-in or None	
43	+10	0	+10	0	-	-		113.69	2107.4		90	0 to Steady-State r.p.m.	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)	δC1	δC2	δC3	δC4	δT1	δT2	δT3	δT4	PIN-PULL ANGLE (DEG)		
44	+10	0	0	0	0	0	-	-	-	-	0	Small Amplitude Lock-in at -45°	Lock-in every 180°
45	+10	0	0	0	0	0	-	-	-	-	15	Large Amplitude Lock-in at -20°	
46	+10	0	0	0	0	0	-	-	-	-	Pin-Pull 90	0 to Steady-State r.p.m. No Oscillations	
47	+10	0	0	0	0	0	-	-	-	-	Pin-Pull 45	Small Oscillations to Lock-in at 0° and then +45°	
48	+10	0	0	0	0	0	-	-	-	-	Pin-Pull 15	Small Oscillations to Lock-in at 0° (Lock-in Location every 180°)	
49	+10	0	0	0	0	0	-	-	-	-	Pin-Pull 90	0 to Steady-State r.p.m.	
50	+10	0	0	0	0	0	-	-	-	-	Pin-Pull 30	Q not exact Small Oscillations to Lock-in at 0°	
51	+10	0	0	0	0	0	-	-	-	-	Pin-Pull -60	Small Oscillations to Lock-in at -45°	
											Change Canards to Pitch Up Control (+15)		
52	+10	+10	-15	-	-	-	-	-	-	-	Pin-Pull 0	0 to Steady-State r.p.m.	
53	+10	+10	-15	-	-	-	-	-	-	-	0	0 to Steady-State r.p.m.	
54	+10	+10	-15	-	-	-	-	-	-	-	0	0 to Steady-State r.p.m. One Light Off	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL.. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	6 C1	6 C2	6 C3	6 C4									6 T1
55	+10	+15	+10	-15	-	-	14.95	522.6	112.68	2112.3		0	0 to Steady-State r.p.m.
56	+10	+15	+10	-15	-	-	15.04	522.6	113.14	2108.8		0	0 to Steady-State r.p.m. Small Oscillation to Steady-State r.p.m.
57	+10	+15	+10	-15	-	-	14.93	522.9	112.73	2108.9		0	Small Oscillation to Lock-in about -45° Location (only position of lock-in)
58	+10	+15	+10	-15	-	-	15.01	523.3	113.06	2108.8		0 + 180 180	0 to Steady-State r.p.m.
59	+10	+15	+10	-15	-	-	15.03	523.6	113.18	2108.7		30	Large Oscillations to Lock-in at -45° (only position)
60	+10	+15	+10	-15	-	-	15.08	524.0	113.43	2108.7		0 + 180 180	0 to Steady-State r.p.m.
61	+10	+15	+10	-15	-	-	15.08	524.0	113.43	2108.7		30	Large Oscillations to Lock-in at -45° (only position)
62	+10	+15	+10	-15	-	-	14.91	525.0	112.88	2108.9		0 + 180 180	0 to Steady-State r.p.m.
63	+10	+15	+10	-15	-	-	15.04	525.7	113.47	2108.7		30	Large Oscillations to Lock-in at -45° position
64	+10	+15	+10	-15	-	-	14.91	526.4	113.03	2108.9		-52.5+180 127.5 +225	One or two oscillations to Lock-in at -45°
65	0	0	0	0	0	0	15.03	527.0	113.54	2108.8	Change Canards to		Zero Roll Torque
	+15	-15	-	-	-	-					Spun-Up Wand		No driving asymmetry

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD		TAIL							SPUN-UP	PIN-PULL ANGLE (DEG)		
	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)									
	δ_{C1} δ_{C2} δ_{C3} δ_{C4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}											
66	0 +15 -15 0	- - - -	- - - -	- - - -	5°	14.81	527.4	112.77	2109.0	Spun-Up Wand		No Lock-in	
67	0 +15 -15 0	- - - -	- - - -	- - - -	10°	15.16	527.0	114.06	2108.6	Spun-Up Wand			
68	0 +15 -15 0	- - - -	- - - -	- - - -	15°	14.99	527.4	113.43	2108.8	Spun-Up Wand		Piece of Tape Loose	
69	0 +15 -15 0	- - - -	- - - -	- - - -	20°	15.20	528.1	114.32	2108.6	Spun-Up Wand			
70	0 +15 -15 0	- - - -	- - - -	- - - -	25°	15.16	528.1	114.17	2108.6	Spun-Up Wand		Loose Tape	
71	0 +15 -15 0	- - - -	- - - -	- - - -	30°	14.97	528.1	113.44	2108.8	Spun-Up Wand			
72	0 +15 -15 0	- - - -	- - - -	- - - -	30°	15.39	527.7	115.01	2108.4		Pin-Pull -60.0	Small or no Oscillations to Lock-in at -60°	
73	0 +15 -15 0	- - - -	- - - -	- - - -	30°	15.43	527.0	115.07	2108.4		Pin-Pull 30	2 Oscillations to Lock-in at -60°	
74	0 +15 -15 0	- - - -	- - - -	- - - -	30°	15.06	526.7	113.65	2108.7		Pin-Pull +120	Large Oscillations to Lock-in 3 Oscillations	
75	0 +15 -15 0	- - - -	- - - -	- - - -	25°	15.30	526.4	114.49	2108.5		-30+180 150	Both Lock- ins covered Rotate to Lock-in	
76	0 +15 -15 0	- - - -	- - - -	- - - -	25°	15.55	526.0	115.39	2108.2		30	3 Oscillations to Lock-in	
77	0 +15 -15 0	- - - -	- - - -	- - - -	20°	15.06	513.3	112.10	2112.2		Pin-Pull 30	5 Large Oscillations to Lock-in at 270°	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD		TAIL							SPUN-UP	PIN-PULL ANGLE (DEG)		
	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)									
	δ_{C1}	δ_{C2}	δ_{C3}	δ_{C4}	δ_{T1}	δ_{T2}	δ_{T3}	δ_{T4}					
78	0	0	-15	-15	-	-	-	-	15.08	514.0	112.25	2112.3	180° - 60° 2 Oscillations to Lock-in at 90°
79	0	+15	-15	-15	-	-	-	-	15.12	514.3	112.43	2112.2	180° - 60° 3 Oscillations to Lock-in at 90°
80	0	+15	-15	-15	-	-	-	-	15.12	515.4	112.55	2112.2	Only one Lock-in Position 3 Oscillations to Lock-in at 300°
													Change Canards to Off Axis Control Pitch
81	+15	-15	-15	-15	-	-	-	-	15.01	516.7	112.26	2112.3	Spun-Up
82	+15	-15	-15	-15	-	-	-	-	14.76	517.0	111.34	2112.7	Spun-Up
83	+15	-15	-15	-15	-	-	-	-	15.20	517.8	113.10	2112.1	Spun-Up
84	+15	-15	-15	-15	-	-	-	-	14.99	517.4	112.26	2112.4	Spun-Up Lock-in one Position
85	+15	-15	-15	-15	-	-	-	-	15.20	518.1	113.13	2112.1	Spun-Up Lock-in one Position at 270°
86	+15	-15	-15	-15	-	-	-	-	15.31	518.1	113.57	2112.0	Spun-Up Lock-in at 90° and 270° both
87	+15	-15	-15	-15	-	-	-	-	15.08	518.1	112.70	2112.2	Spun-Up Lock-in at 300°, 160° and 90° (computer print wrong angle of ϵ)
88	+15	-15	-15	-15	-	-	-	-	14.99	518.4	112.37	2112.4	Pin-Pull 120° 2 Oscillations to Lock-in at 160°

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE														
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. ° (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS		
	CANARD		TAIL							SPUN-UP	PIN-PULL ANGLE (DEG)			
	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)										
	δ_{C1} δ_{C2} δ_{C3} δ_{C4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}												
89	+15 -15 -15 -15	- - - -			30°	15.04	519.0	112.65	2112.3		Pin-Pull 180	2 Oscillations to Lock-in at 200°		
90	+15 -15 -15 -15	- - - -			30°	15.06	519.1	112.74	2112.3		Pin-Pull 30	4 Oscillations to Lock-in at 200°		
91	+15 -15 -15 -15	- - - -			30°	15.16	521.5	113.44	2109.3		Pin-Pull -45	2 Oscillations to Lock-in at 270°		
92	+15 -15 -15 -15	- - - -			25°	15.16	521.9	113.51	2108.1		Pin-Pull 120	4 Oscillations to Lock-in at 200° (only lock-in)		
93	+15 -15 -15 -15	- - - -			20°	14.93	522.2	112.68	2108.2		Pin-Pull 0	2 Oscillations to Lock-in at 200°		
94	+15 -15 -15 -15	- - - -			15°	14.74	522.1	111.93	2108.3		0			
										Add Tail Fins and Canards				
95	0 0 0 0	0 0 0 0			0°	14.85	523.3	112.51	2107.6		Spun-Up Wand	Wand Pressure = 200 PSI		
96	0 0 0 0	0 0 0 0			5°	15.03	523.3	113.18	2107.3		Spun-Up Wand			
97	0 0 0 0	0 0 0 0			10°	14.89	523.6	112.70	2107.5		Spun-Up Wand			
98	0 0 0 0	0 0 0 0			15°	14.89	523.6	112.70	2107.5		Spun-Up Wand			
99	0 0 0 0	0 0 0 0			20°	15.26	523.3	114.05	2107.1		Spun-Up Wand			

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE												
RUN NO.	CONFIGURATION				Q (PSF)	TEMP. ° (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)		SPIN-UP					PIN-PULL ANGLE (DEG)			
		δ C1 δ C2	δ C3 δ C4							δ T1 δ T2		δ T3 δ T4
100	0	0	0	0	25°	15.10	522.9	113.43	2107.4	Spun-Up Wand		
101	0	0	0	0	30°	15.10	523.3	113.46	2107.4	Spun-Up Wand		
102	0	0	0	0	30°	15.12	522.6	113.50	2106.0	Pin-Pull -45	Small Oscillations, About -45° Lock-In. Lock-in every 90°	
103	0	0	0	0	30°	15.35	523.3	114.45	2105.6	Pin-Pull 0	Large Oscillations about -45° Lock-in	
104	0	0	0	0	25°	15.03	523.3	113.21	2106.0	0	"	
105	0	0	0	0	20°	15.10	522.6	113.43	2105.8	0	"	
106	0	0	0	0	15°	15.18	522.9	113.76	2105.8	0	"	
107	0	0	0	0	10°	15.30	522.9	114.19	2105.6	0	One Oscillation to Lock-in at +45°	
108	0	0	0	0	10°	15.06	522.9	113.32	2105.9	15	Two Oscillations to Lock-in at 45°	
										Change Canard to δ = +10 Roll Cant		
109	+10	+10	0	0	0°	15.08	522.6	113.36	2105.9	0	0 to Steady-State r.p.m. = 120 r.p.m.	
110	+10	+10	0	0	5°	15.03	522.2	113.12	2105.3	0	0 to Steady-State	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)	δ_{C1}	δ_{C2}	δ_{C3}	δ_{C4}	δ_{T1}	δ_{T2}	δ_{T3}	δ_{T4}	SPUN-UP	PIN-PULL ANGLE (DEG)	
111	+10	0	0	0	0	0	0	0	0	0	0	0	0 to Steady State Lock-in Weak (pin-pull didn't work)
112	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	No Steady-State rate. 2 Lock-in positions (at 120° and -60°)
113	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	No Steady-State rate. 2 Lock-in positions (at 120° and -60°)
114	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Steady-State rate (Slow) Lock-in at -45° 4 positions (every 90°)
115	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Lock-in at -45° 4 positions (every 90°)
116	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Steady-State Rate Large Oscillations damped to lock-in at 135° (4 positions of lock-in both case 180° symmetric)
117	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Large Oscillations damped to Lock-in at 225°
118	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	0 to Steady-State r.p.m.
119	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Large damped oscillations to Lock-in at 135°
120	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Only three Oscillations to Lock-in at 225°. Steady-State r.p.m.
121	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Large damped oscillations to lock-in at +45°. Steady-State r.p.m.
122	+10	0	0	0	0	0	0	0	0	0	Spun-Up	0	Only 2 Lock-in positions at -50° and 120° No Steady-State r.p.m. Large damped oscillations

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSI)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	δ_{C1}	δ_{C2}	δ_{C3}	δ_{C4}									δ_{T1}
123	+10	+10	0	0	0	15°	14.78	514.7	111.24	2109.8	180 + 30 30	Wrong Pin-Pull at 216° (Lock-in present)	
124	+10	+10	0	0	0	15°	15.04	514.7	112.26	2109.3	30	Lock-in at 210° weak. Large oscillations damped to lock-in at -60°	
Bearing filters changed.													
125	+10	+10	-15	0	0	0°	14.87	559.0	116.28	2111.0	0	0 to steady-state r.p.m. repeat run power on timing 0 to steady-state r.p.m. light off.	
126	+10	+10	-15	0	0	5°	15.24	560.8	117.89	2110.6	0		
127	+10	+10	-15	0	0	10°	15.06	561.8	117.32	2110.8	0		
128	+10	+10	-15	0	0	0°	14.99	524.1	113.02	2110.9	0	0 to steady-state r.p.m.	
129	+10	+10	-15	0	0	5°	15.33	524.0	114.32	2110.6	0	0 to steady-state r.p.m. Bearing Bad	
130	+10	+10	-15	0	0	5°	14.93	522.2	112.61	2110.9	0	0 to steady-state r.p.m.	
131	+10	+10	-15	0	0	10°	15.24	522.9	113.84	2110.6	0	0 to steady-state r.p.m.	
132	+10	+10	-15	0	0	15°	15.18	523.0	113.64	2110.6	0	Lock-in at 135° Large oscillations damped	
133	+10	+10	-15	0	0	15°	15.10	522.9	113.33	2110.8	-15	Large oscillations damped to lock-in at -45°	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD		TAIL							SPUN-UP	PIN-FULL ANGLE (DEG)		
	δ C1 δ C2	δ C3 δ C4	δ T1 δ T2	δ T3 δ T4									
134	+10 +15	+10 -15	0 0	0 0	20°	15.10	522.6	113.30	2110.8		-15	Large oscillations damping to lock-in at -45°	
135	+10 +15	+10 -15	0 0	0 0	20°	15.20	522.6	113.66	2110.7		0	Large oscillations damping to lock-in at -45°	
136	+10 +15	+10 -15	0 0	0 0	20°	14.99	522.2	112.82	2110.9		+30	Large oscillations damping to lock-in at 135°	
137	+10 +15	+10 -15	0 0	0 0	25°	14.93	521.9	112.57	2110.9		0	Large oscillations damping to lock-in at -45°	
138	+10 +15	+10 -15	0 0	0 0	25°	15.20	521.2	113.51	2110.6		+15	Large oscillations damping to lock-in at +45°	
139	+10 +15	+10 -15	0 0	0 0	25°	14.99	520.9	112.66	2111.6		120	Large oscillations damping to lock-in at 135°	
140	+10 +15	+10 -15	0 0	0 0	25°	15.18	520.2	113.31	2111.4		210	Large oscillations to lock-in at 225°	
141	+10 +15	+10 -15	0 0	0 0	30°	14.70	519.8	111.44	2111.9		0	Large oscillations to lock-in at -45°	
BAD BEARING													
142	+10 +15	+10 -15	0 0	0 0	30°	14.99	507.9	111.00	2120.8		+15	Large oscillations to lock-in at +45°	
143	+10 +15	+10 -15	0 0	0 0	30°	15.10	508.8	111.53	2120.7		180 - 60 120	Large oscillations to lock-in at +135° then Steady-State r.p.m.	
144	+10 +15	+10 -15	0 0	0 0	30°	14.74	509.5	110.24	2121.1		210	Large oscillations to lock-in at -45°	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE												
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)	
	δ_{C1}	δ_{C2}	δ_{C3}	δ_{C4}								
145	+10	+10	-15	0	0	14.99	510.2	111.25	2120.8	Spun-Up		Damped to lock-in
146	+10	+10	-15	0	0	14.93	511.2	111.15	2120.8	Spun-Up		Damped to steady-state r.p.m.
147	+10	+10	-15	0	0	14.99	512.3	111.48	2120.8	Spun-Up		Damped to lock-in
148	+10	+10	-15	0	0	15.06	513.3	111.88	2120.8	Spun-Up		Damped to lock-in
149	+10	+10	-15	0	0	15.10	514.5	112.16	2120.7	Spun-Up		Damped to steady-state r.p.m.
150	+10	+10	-15	0	0	15.18	515.4	112.54	2120.6	Spun-Up		Damped to steady-state r.p.m.
151	+10	+10	-15	0	0	15.37	516.4	113.37	2120.4	Spun-Up		Damped to steady-state r.p.m.
										CHANGE CANARD TO	PITCH DEFLECTION ONLY	
152	0	0	-15	0	0	15.01	517.4	112.11	2120.8	Spun-Up		No roll at 0°
153	0	0	-15	0	0	15.20	518.8	112.98	2120.6	Spun-Up		Damped to a lock-in with pitch fins vertical at 270°
154	0	0	-15	0	0	15.03	523.3	112.83	2120.1	Spun-Up		Lock-in present Damped to lock-in
155	0	0	-15	0	0	15.16	524.3	113.45	2120.0	Spun-Up		Lock-in at -45°, 135°, 225° Damped to lock-in

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. ° (° R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	δ C1 δ C2	δ C3 δ C4	δ T1 δ T2	δ T3 δ T4									
156	0	0	-15	0	0	20°	15.06	525.0	113.16	2120.1		Lock-in at -45, +45, 135, 225° Damped to lock-in	
157	0	0	0	0	0								
157	+15	-15	0	0	0	25°	15.10	525.0	113.31	2120.0		Lock-in at -45, +45, 135, 225° Damped to lock-in	
158	0	0	0	0	0								
158	+15	-15	0	0	0	30°	15.10	525.0	113.31	2120.0		Lock-in at -45, +45, 135, 225° Damped to lock-in	
159	0	0	0	0	0								
159	+15	-15	0	0	0	30°	14.93	525.2	112.68	2120.2		Large oscillations to lock-in at 225° Did not damp	
160	0	0	0	0	0								
160	+15	-15	0	0	0	30°	15.22	525.0	113.75	2119.9		Undamped oscillations about lock-in at +45°	
161	0	0	0	0	0								
161	+15	-15	0	0	0	30°	15.20	525.3	113.71	2119.9		Undamped oscillations about lock-in at 135°	
162	0	0	0	0	0								
162	+15	-15	0	0	0	30°	15.28	525.4	114.01	2119.9		Undamped oscillations about lock-in at -45°	
163	0	0	0	0	0								
163	+15	-15	0	0	0	25°	15.18	525.7	113.68	2119.9		Damped oscillations to lock-in at -45°	
164	0	0	0	0	0								
164	+15	-15	0	0	0	25°	15.08	525.7	113.31	2120.0		Damped to lock-in at +45°	
165	0	0	0	0	0								
165	+15	-15	0	0	0	25°	15.14	526.0	113.57	2120.1		Damped to lock-in at 135°	
166	0	0	0	0	0								
166	+15	-15	0	0	0	25°	15.31	526.4	114.26	2119.8		Damped to lock-in at 225°	
167	0	0	0	0	0								
167	+15	-15	0	0	0	20°	15.35	526.4	114.40	2119.7		Damped to lock-in at -45°	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)		SPUN-UP						PIN-PULL ANGLE (DEG)			
		δ_{C1} δ_{C2} δ_{C3} δ_{C4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}										
168	0 +15 -15 0	0 0 0 0	0 0 0 0	20°	15.14	526.7	113.68	2118.5			30	Damped to lock-in at 135°	
169	0 +15 -15 0	0 0 0 0	0 0 0 0	20°	15.04	526.7	113.32	2118.7			210	Damped to lock-in at 225°	
170	0 +15 -15 0	0 0 0 0	0 0 0 0	15°	15.14	526.7	113.68	2118.5			0	Damp oscillations to lock-in at 135°	
171	0 +15 -15 0	0 0 0 0	0 0 0 0	15°	15.20	526.7	113.90	2118.4			-30	Damped small oscillations (2) to lock-in at -45°	
172	0 +15 -15 0	0 0 0 0	0 0 0 0	15°	14.91	527.0	112.84	2118.8			210	Damped small oscillations (2) to lock-in at 225°	
173	0 +15 -15 0	0 0 0 0	0 0 0 0	10°	14.99	526.7	113.10	2118.6			0	Damped large oscillations to lock-in at 90°	
											CHANGE CANARD		
174	+15 -15 0 0	0 0 0 0	0 0 0 0	0°	14.93	525.4	112.74	2118.7		Spun-Up		Small roll rates positive and negative	
175	+15 -15 0 0	0 0 0 0	0 0 0 0	5°	15.12	525.7	113.50	2118.6		Spun-Up		Damped to lock-in at 90°	
176	+15 -15 0 0	0 0 0 0	0 0 0 0	10°	14.87	525.3	112.51	2118.7		Spun-Up		Damped to lock-in at (+45° only)	
177	+15 -15 0 0	0 0 0 0	0 0 0 0	15°	15.12	525.0	113.43	2118.4		Spun-Up		Damped to lock-in at (+45° only)	
178	+15 -15 0 0	0 0 0 0	0 0 0 0	20°	15.39	525.0	114.44	2118.2		Spun-Up		Damped to lock-in at -30, +45, +135, +225	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE														
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS		
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)	SPUN-UP	PIN-PULL ANGLE (DEG)										
	δC_1	δC_2	δC_3	δC_4	δT_1	δT_2	δT_3	δT_4						
179	+15	-15	0	0	0	0	0	0	25°	15.10	523.6	113.20	2118.6	Damped to lock-in +45°, 135° lock-in at -45°, 225°
180	+15	-15	0	0	0	0	0	0	30°	15.03	524.0	112.95	2118.6	Damped to lock-in +45°, 135° lock-in at -45°, 225°
181	+15	-15	0	0	0	0	0	0	30°	15.12	523.6	113.27	2118.5	Damped to lock-in at 135°
182	+15	-15	0	0	0	0	0	0	30°	14.97	523.3	112.65	2118.7	Damped to lock-in at 225°
183	+15	-15	0	0	0	0	0	0	30°	15.14	523.3	113.31	2118.4	Damped to lock-in at +45°
184	+15	-15	0	0	0	0	0	0	30°	15.22	522.9	113.56	2118.4	Damped to lock-in at -45°
185	+15	-15	0	0	0	0	0	0	25°	14.97	522.7	112.59	2118.7	Damped to lock-in at -45°
186	+15	-15	0	0	0	0	0	0	25°	14.79	522.6	111.92	2118.8	Damped in 3 oscillations to lock-in at 225°
187	+15	-15	0	0	0	0	0	0	25°	14.93	521.9	112.38	2117.9	Damped to lock-in at +45°
188	+15	-15	0	0	0	0	0	0	25°	14.81	521.5	111.90	2118.2	Damp to lock-in at 135°
189	+15	-15	0	0	0	0	0	0	20°	14.87	521.5	112.12	2118.0	Damped to lock-in at -45°
190	+15	-15	0	0	0	0	0	0	20°	15.16	521.2	113.18	2117.7	Damped to lock-in at +45°

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	δC1 δC2	δC3 δC4	δT1 δT2	δT3 δT4									
191	+15	-15	0	0	0	20°	514.7	112.93	2119.0		120	Small damped and undamped to lock-in to 135°	
192	+15	-15	0	0	0	20°	515.4	112.21	2119.3		210	Small damped oscillations to lock-in at 225°	
193	+15	-15	0	0	0	15°	515.7	111.24	2119.6		0	Damps with small oscillation to lock-in at +45°	
194	+15	-15	0	0	0	15°	516.4	111.75	2119.3		180	Damps with small oscillation to lock-in at +45°	
195	+15	-15	0	0	0	10°	516.7	112.22	2119.3		180	Damps with many large oscillations to lock-in at +45°	
196	+15	-15	0	0	0	10°	517.4	113.02	2119.1		180	Lights off on 195. Repeat of 195	
197	+15	-15	0	0	0	5°	518.1	112.87	2119.2		0	Damps with many large oscillations to lock-in at +45°	
198	+15	-15	0	0	0	5°	518.8	113.10	2119.1		180	Damps with many large oscillations to lock-in at +45°	
										CHANGE TO 5	CANTED TAIL FINS		
199	+15	-15	5	5	5	0°	519.1	112.84	2119.2		0	0 to steady-state r.p.m.	
200	+15	-15	5	5	5	5°	520.2	112.08	2119.5		0	0 to steady-state r.p.m.	
201	+15	-15	5	5	5	10°	520.9	113.17	2119.2		0	0 to steady-state r.p.m.	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)								SPUN-UP	PIN-PULL ANGLE (DEG)		
		δC_1 δC_2	δC_3 δC_4	δT_1 δT_2									δT_3 δT_4
202	+15 -15	-15 5	5 5	5 5	15°	15.01	520.5	112.48	2119.4		0	0 to steady-state r.p.m.	
203	+15 -15	-15 5	5 5	5 5	20°	15.04	520.9	112.63	2120.8		0	0 to steady-state r.p.m.	
204	+15 -15	-15 5	5 5	5 5	25°	15.20	520.9	113.21	2120.6		0	0 to steady-state r.p.m.	
205	+15 -15	-15 5	5 5	5 5	30°	15.06	520.5	112.66	2120.8		0	0 to steady-state r.p.m. Lock-in -45, +45, 225°	
206	+15 -15	-15 5	5 5	5 5	30° forgot label	15.12	520.5	112.88	2120.7		-30	Damped oscillations to lock-in at -45°	
207	+15 -15	-15 5	5 5	5 5	30° forgot label	15.28	520.9	113.50	2120.6		+30	0 to steady-state r.p.m. there is lock-in about +45°	
208	+15 -15	-15 5	5 5	5 5	30°	15.35	521.1	113.81	2120.4		210	Large undamped oscillations about lock-in at 225°	
209	+15 -15	-15 5	5 5	5 5	25°	15.22	522.2	113.43	2120.6		-30	Large undamped oscillations about -45° lock-in	
210	+15 -15	-15 5	5 5	5 5	25°	15.08	523.3	113.03	2120.8		+30	0 to steady-state r.p.m.	
211	+15 -15	-15 5	5 5	5 5	30°	15.10	523.6	113.14	2120.7		120	0 to steady-state r.p.m.	
212	+15 -15	-15 5	5 5	5 5	25°	15.14	524.0	113.34	2120.0		210	0 to steady-state r.p.m. Lock-in noted using wand at 225°	
213	+15 -15	-15 5	5 5	5 5	20°	15.10	524.6	113.27	2120.0		-30	0 to steady-state r.p.m.	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE															
RUN NO.	CONFIGURATION								Q (PSF)	TEMP. ° (R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD				TAIL								SPUN-UP	PIN-PULL ANGLE (DEG)	
	δ _{C1}	δ _{C2}	δ _{C3}	δ _{C4}	δ _{T1}	δ _{T2}	δ _{T3}	δ _{T4}							
													CHANGE CANARD	PITCH ON AXIS CONTROL DEFLECTION	
214	0	0	+15	-15	5	5	5	5	15.18	525.6	113.72	2117.8		0	0 to steady-state r.p.m.
215	0	0	+15	-15	5	5	5	5	15.18	526.7	113.84	2117.9		0	0 to steady-state r.p.m.
216	0	0	+15	-15	5	5	5	5	15.08	527.4	113.59	2116.5		0	0 to steady-state r.p.m.
217	0	0	+15	-15	5	5	5	5	14.70	527.0	112.09	2116.9		0	0 to steady-state r.p.m.
218	0	0	+15	-15	5	5	5	5	15.16	527.4	113.88	2116.4		0	0 to steady-state r.p.m.
219	0	0	+15	-15	5	5	5	5	15.12	527.7	113.78	2116.5		0	0 to steady-state r.p.m.
220	0	0	+15	-15	5	5	5	5	15.14	527.0	113.77	2116.5		0	0 to steady-state r.p.m.
221	0	0	+15	-15	5	5	5	5	14.95	527.4	113.08	2116.7		-30	Damped to lock-in at -45°
222	0	0	+15	-15	5	5	5	5	15.16	527.4	113.88	2116.4		+30	0 to steady-state r.p.m. (Lock-in noted with wand at +45°)
223	0	0	+15	-15	5	5	5	5	15.12	527.2	113.71	2116.5		120	0 to steady-state r.p.m.
224	0	0	+15	-15	5	5	5	5	15.06	527.0	113.48	2116.5		135	Undamped from 135° lock-in to steady-state r.p.m. (small oscillations to large)

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE												
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD		TAIL							SPUN-UP	PIN-FULL ANGLE (DEG)	
	DEFLECTION (DEG)		DEFLECTION (DEG)									
	δ_{C1} δ_{C2} δ_{C3} δ_{C4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}								
225	0 +15 -15 5	0 -15 5 5	0 -15 5 5	0 -15 5 5	30°	15.31	527.0	114.43	2116.3		210	0 to steady-state r.p.m. (Lock-in noted at 225° with wand)
226	0 +15 -15 5	0 -15 5 5	0 -15 5 5	0 -15 5 5	25°	15.12	526.4	113.63	2116.5		-30	Damped to lock-in at -45°
227	0 +15 -15 5	0 -15 5 5	0 -15 5 5	0 -15 5 5	25°	15.08	526.7	113.52	2116.6		135	0 to steady-state r.p.m. (Lock-in at -45, +80, 225°) 0 to steady-state r.p.m.
228	0 +15 -15 5	0 -15 5 5	0 -15 5 5	0 -15 5 5	25°	15.10	527.0	113.63	2116.4		210	0 to steady-state r.p.m.
											CHANGED CANARD	
229	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	0°	15.06	526.0	113.39	2115.8		0	0 to steady-state 100 fps
230	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	5°	15.04	526.0	113.32	2115.9		0	0 to steady-state 100 fps
731	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	0°	15.06	525.3	113.32	2115.7		0	Changed camera speed to 200 fps 0 to steady-state r.p.m.
232	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	5°	15.14	524.6	113.53	2115.7		0	0 to steady-state r.p.m.
233	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	10°	15.20	525.3	113.83	2115.6		0	0 to steady-state r.p.m.
234	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	15°	14.93	525.3	112.81	2115.9		0	0 to steady-state r.p.m.
235	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	+10 +15 -15 5	20°	15.14	525.3	113.61	2115.7		0	0 to steady-state r.p.m.

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	I (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	δC1	δC2	δC3	δC4									δT1
	+10	+10	-15	5	5	25°	15.14	524.0	113.46	2115.6		0	0 to steady-state r.p.m.
236	+10	+10	-15	5	5								Lock-in at -45, 135, 225° using wand.
237	+10	+10	-15	5	5	30°	15.08	524.0	113.24	2115.8		0	0 to steady-state r.p.m.
238	+10	+10	-15	5	5								Small oscillations to lock-in at -45°
239	+10	+10	-15	5	5	30°	15.16	523.6	113.49	2115.7			Small oscillations to lock-in at 135°
240	+10	+10	-15	5	5								0 to steady-state r.p.m.
	+10	+10	-15	5	5	30°	14.91	523.6	112.55	2116.0		216	Lock-in at -45° using wand.
	+10	+10	-15	5	5								Damped small lock-in at -45°
241	+10	+10	-15	5	5	25°	15.08	522.5	113.08	2115.7		-30	No lock-in at 20°
													CHANGE CANARD NO PITCH
	+10	+10	5	5	5								
242	0	0	0	5	5	0°	15.39	521.5	114.14	2115.5		0	0 to steady-state r.p.m.
243	+10	+10	5	5	5								
	0	0	0	5	5	5°	15.10	521.9	113.09	2115.8			0 to steady-state r.p.m.
244	+10	+10	5	5	5								
	0	0	0	5	5	10°	15.16	521.5	113.27	2115.7			0 to steady-state r.p.m.
245	+10	+10	5	5	5								
	0	0	0	5	5	15°	15.03	510.9	111.60	2115.8		0	0 to steady-state rate
246	+10	+10	5	5	5								
	0	0	0	5	5	20°	14.89	511.6	111.17	2116.0		0	0 to steady-state rate

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD -- CONTROL MISSILE													
RUN NO.	CONFIGURATION						Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD		TAIL		YAW ANGLE (DEG)	SPUN-UP					PIN-PULL ANGLE (DEG)		
	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)									
	δ _{C1}	δ _{C2}	δ _{C3}	δ _{C4}	δ _{T1}	δ _{T2}	δ _{T3}						
247	+10	+10	0	0	5	5	5	15.24	512.3	112.55	2115.6	0	0 to steady-state rate
248	+10	+10	0	0	5	5	5	15.28	512.6	112.73	2115.6	0	
249	+10	+10	0	0	5	5	5	15.31	513.3	112.95	2115.5	-30	Lock-in at 4 positions. Wind Small oscillations damped -45°
250	+10	+10	0	0	5	5	5	15.26	514.0	112.81	2115.6	210	Symmetric configuration 0 to steady-state rate
251	+10	+10	0	0	5	5	5	15.01	515.4	112.02	2115.8	-30	Lock-in -45 and 135 wind Small oscillations or none.
252	+10	+10	0	0	5	5	5	15.04	515.4	112.16	2115.8	-15	0 to steady-state rate
												CHANGE CANARD	
253	0	0	0	0	5	5	5	15.08	515.0	112.27	2115.7	0	0 to steady-state rate
254	0	0	0	0	5	5	5	15.14	516.2	112.61	2115.7	0	0 to steady-state rate
255	0	0	0	0	5	5	5	15.03	516.4	112.20	2115.9	0	0 to steady-state rate
256	0	0	0	0	5	5	5	14.97	516.7	112.02	2115.9	0	0 to steady-state rate
257	0	0	0	0	5	5	5	15.26	516.7	113.11	2115.6	0	0 to steady-state rate

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE											
RUN NO.	CONFIGURATION				Q (PSF)	TEMP. (° F)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)						SPUN-UP	PIN-PULL ANGLE (DEG)	
	δ_{C1} δ_{C2} δ_{C3} δ_{C4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}	δ_{T1} δ_{T2} δ_{T3} δ_{T4}								
258	0	0	0	5	5	15.06	517.4	112.46	2115.8	0	0 to steady-state rate
259	0	0	0	5	5	14.95	517.4	112.02	2115.9	-22.5	0 to steady-state rate
260	0	0	0	5	5	15.08	518.1	112.61	2115.8	-22.5	8 oscillations to lock-in at -45°
261	-	-	0	0	0	15.12	519.0	112.85	2115.8	Spun-Up	CHANGE TO TAIL WITH 0° CANT
262	0	0	0	0	0	15.04	526.2	113.38	2114.4	Spun-Up	REPLACED REAR CARBON BEARING
263	0	0	0	0	0	15.12	525.7	113.61	2114.4	Spun-Up	
264	0	0	0	0	0	14.93	525.0	112.80	2114.6	Spun-Up	Weak lock-in noted at -45°
265	0	0	0	0	0	14.89	525.0	112.66	2114.6	Spun-Up	Lock-in noted
266	0	0	0	0	0	15.06	525.0	113.32	2114.4	Spun-Up	Lock-in noted
267	0	0	0	0	0	15.10	525.0	113.46	2114.3	Spun-Up	Lock-in noted

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE															
RUN NO.	CONFIGURATION								Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)				YAW ANGLE (DEG)	SPUN-UP					PIN-PULL ANGLE (DEG)		
	6 C1	6 C2	6 C3	6 T1	6 T2	6 T3								6 T4	
268	0	0	0	0	0	0	0	30°	15.12	524.6	113.50	2114.4	Spun-Up	Lock-in noted	
269	0	0	0	5	5	5	5	0°	15.06	524.0	113.21	2114.4	Pin-Pull	CHANGED TAIL CANT	
	0	0	0	5	5	5	5	5°	15.22	524.0	113.79	2114.2	0	0 to steady-state rate	
270	0	0	0	5	5	5	5	10°	14.97	522.9	112.73	2114.5	0	0 to steady-state rate	
	0	0	0	5	5	5	5	15°	14.93	523.3	112.62	2114.5	0	0 to steady-state rate	
271	0	0	0	5	5	5	5	20°	14.91	523.3	112.55	2114.6	0	0 to steady-state rate	
	0	0	0	5	5	5	5	25°	15.14	522.9	113.38	2114.3	0	0 to steady-state rate	
272	0	0	0	5	5	5	5	30°	15.39	522.9	114.32	2114.1	0	0 to steady-state rate	
273	0	0	0	5	5	5	5	0°	15.01	521.5	112.75	2113.7	0	CHANGED CANARD ANGLES	
	+15	-15	-15	5	5	5	5	5°	15.18	521.9	113.44	2113.6	0		
274	0	0	0	5	5	5	5	5°	15.22	524.0	113.79	2114.2	0	0 to steady-state rate	
	+15	-15	-15	5	5	5	5	10°	14.97	522.9	112.73	2114.5	0	0 to steady-state rate	
275	0	0	0	5	5	5	5	15°	14.93	523.3	112.62	2114.5	0	0 to steady-state rate	
	+15	-15	-15	5	5	5	5	20°	14.91	523.3	112.55	2114.6	0	0 to steady-state rate	
276	0	0	0	5	5	5	5	25°	15.14	522.9	113.38	2114.3	0	0 to steady-state rate	
	+15	-15	-15	5	5	5	5	30°	15.39	522.9	114.32	2114.1	0	0 to steady-state rate	
277	0	0	0	5	5	5	5	0°	15.01	521.5	112.75	2113.7	0	CHANGED CANARD ANGLES	
	+15	-15	-15	5	5	5	5	5°	15.18	521.9	113.44	2113.6	0		

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	δ_{C1} δ_{C2}	δ_{C3} δ_{C4}	δ_{T1} δ_{T2}	δ_{T3} δ_{T4}									
278	0	0	5	5	10°	15.14	508.5	111.40	2129.9		0	0 to steady-state rate	
279	0	0	5	5	15°	14.91	509.5	110.65	130.1		0	0 to steady-state rate	
280	0	0	5	5	20°	15.10	509.8	111.41	2129.9		0	0 to steady-state rate	
281	0	0	5	5	25°	15.28	510.5	112.13	2129.7		0	0 to steady-state rate	
282	0	0	5	5	30°	15.03	511.2	111.27	2130.0		0		
											CHANGE TAIL FINS 0° CANT		
283	0	0	0	0	0°	14.95	512.3	111.10	2130.0	Spun-Up		Two titles	
284	0	0	0	0	5°	15.01	512.9	111.38	2130.0	Spun-Up		Damps	
285	0	0	0	0	10°	15.20	513.3	112.14	2129.8	Spun-Up		Damps	
286	0	0	0	0	15°	15.08	513.6	111.75	2129.9	Spun-Up		Damps to lock-in	
287	0	0	0	0	20°	15.12	514.0	111.93	2129.9	Spun-Up		Damps to lock-in	
288	0	0	0	0	25°	15.04	514.3	111.68	2129.9	Spun-Up		Damps to lock-in	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE											
RUN NO.	CONFIGURATION				Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD		TAIL						PIN-PULL ANGLE (DEG)	SPUN-UP	
	DEFLECTION (DEG)		DEFLECTION (DEG)								
	δ _{C1} δ _{C2} δ _{C3} δ _{C4}	δ _{T1} δ _{T2} δ _{T3} δ _{T4}	YAW ANGLE (DEG)								
289	0	0	0	0	15.01	517.1	111.83	2130.0	Spun-Up		Damps to lock-in
										CHANGE CANARD	
290	+10	+10	0	0	15.22	518.8	112.81	2129.8		Pin-Pull 0	0 to steady-state rate
291	+10	+10	0	0	14.91	519.8	111.76	2130.1			0 to steady-state rate
292	+10	+10	0	0	15.08	520.9	112.53	2129.9			0 to steady-state rate
293	+10	+10	0	0	15.22	521.2	113.07	2129.8			Forgot to set printout Damped to lock-in at +90°
294	+10	+10	0	0	14.97	522.2	112.24	2130.1	Spun-Up		Damped to lock-in at +45°
295	+10	+10	0	0	14.93	522.9	112.17	2130.1	Spun-Up		Damped to lock-in at 135°
296	+10	+10	0	0	15.20	523.3	113.22	2129.8	Spun-Up		Damped to steady-state r.p.m.
297	+10	+10	0	0	14.99	523.6	112.46	2130.0	Spun-Up		Damped to steady-state r.p.m.
298	+10	+10	0	0	0.00	521.0	0.00	2145.1		Pin-Pull 0	Damped to lock-in at -45° Forgot to punch printer
299	+10	+10	0	0	14.93	524.0	112.50	2130.1		Pin-Pull 0	Damped to lock-in at +45°

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD		TAIL							SPUN-UP	PIN-PULL ANGLE (DEG)		
	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)	DEFLECTION (DEG)									
	δ_{C1} +10	δ_{C2} +15	δ_{T1} 0	δ_{T2} 0									
300	+10	+15	-15	0	0	25°	15.04	525.0	112.83	2129.9	0	Damped to lock-in at +45°	
												CHANGE TO 5° CANT TAIL	
301	+10	+10	5	5	5	0°	15.04	526.0	112.94	2130.0	0	0 to steady-state rate	
302	+10	+10	-15	5	5	5°	15.26	526.4	113.78	2129.8	0	0 to steady-state rate 200 fps 10 cycles per second omitted	
303	+10	+10	-15	5	5	10°	15.16	526.7	113.45	2129.8	0	0 to steady-state rate	
304	+10	+10	-15	5	5	15°	15.04	527.0	113.05	2130.0	0	0 to steady-state rate	
305	+10	+10	-15	5	5	20°	14.91	527.7	112.61	2130.1	0	0 to steady-state rate	
306	+10	+10	-15	5	5	25°	14.95	527.7	112.76	2130.1	0	0 to steady-state rate	
307	+10	+10	-15	5	5	30°	15.04	530.5	113.42	2130.0	0	0 to steady-state rate	
												CHANGE CANARDS TO OFF AXIS PITCH	
308	+15	-15	5	5	5	0°	14.87	532.6	113.13	2124.5	0	0 to steady-state	
309	+15	-15	5	5	5	5°	15.26	532.9	114.63	2124.1	0	0 to steady-state	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	C (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)		
	δC_1 δC_2	δC_3 δC_4	δT_1 δT_2	δT_3 δT_4									
310	+15	-15	5	5	10°	15.01	533.5	113.74	2124.3		0	0 to steady-state	
311	+15	-15	5	5	15°	14.95	533.6	113.53	2124.4		0	0 to steady-state	
312	+15	-15	5	5	20°	15.08	532.9	113.97	2124.3		0	0 to steady-state	
313	+15	-15	5	5	25°	14.93	533.7	113.47	2124.5		0		
314	+15	-15	5	5	30°	15.01	534.3	113.83	2124.4		0		
											CHANGE TO 0° CANT TAIL		
315	+15	-15	0	0	0°	14.85	534.0	113.21	2124.5	Spun-Up			
316	+15	-15	0	0	5°	15.12	534.6	114.30	2124.2	Spun-Up		Damps to lock-in at +45°	
317	+15	-15	0	0	10°	15.06	534.6	114.09	2124.3	Spun-Up		Damps to lock-in at +45°	
318	+15	-15	0	0	15°	14.97	534.3	113.68	2124.4	Spun-Up			
319	+15	-15	0	0	20°	15.10	534.6	114.23	2124.3	Spun-Up		Damps to lock-in at +45°	
320	+15	-15	0	0	25°	15.10	535.0	114.27	2124.2	Spun-Up		Damps to lock-in at +135°	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)								SPUN-UP	PIN-PULL ANGLE (DEG)		
		δ_{C1}	δ_{C3}	δ_{T1}									δ_{T3}
	δ_{C2}	δ_{C4}	δ_{T2}	δ_{T4}									
321	+15	-15	0	0	30°	19.12	535.0	114.34	2124.2	Spun-Up		Damps to lock-in at 225°	
											CHANGE CANARD REMOVE CONTROL DEFLECTION		
322	+10	+10	0	0	0°	15.28	534.3	114.91	2121.9	Pin-Pull	0	0 to steady-state rate	
323	+10	+10	0	0	5°	15.24	535.0	114.84	2122.0		0	0 to steady-state rate	
324	+10	+10	0	0	10°	14.93	535.0	113.66	2122.3		0	0 to steady-state rate	
325	+10	+10	0	0	15°	15.01	533.6	113.81	2122.2		0	Damping to lock-in at -45°	
326	+10	+10	0	0	20°	15.16	534.3	114.47	2122.1		0	Damping to lock-in at -45°	
327	+10	+10	0	0	25°	15.08	534.6	114.21	2122.2		0	Damping to lock-in at +45°	
328	+10	+10	0	0	30°	15.24	534.6	114.80	2122.0		0	0 to steady-state rate	
329	+10	+10	0	0	30°	15.12	534.6	114.36	2122.1	Spun-Up		Damps to steady-state rate	
330	+10	+10	0	0	25°	15.30	534.3	114.98	2121.9	Spun-Up		Damps to steady-state rate	
331	+10	+10	0	0	20°	15.31	534.5	115.12	2120.5	Spun-Up		Damps to lock-in at +135°	

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE												
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS
	CANARD DEFLECTION (DEG)		TAIL DEFLECTION (DEG)							SPUN-UP	PIN-PULL ANGLE (DEG)	
	δC_1 δC_2	δC_3 δC_4	δT_1 δT_2	δT_3 δT_4								
332	+10	0	0	0	0	15°	15.31	534.4	115.11	2120.5	Spun-Up	Damps to steady-state rate
333	+10	+10	5	5	5	0°	15.14	534.3	114.44	2120.6	Pin-Pull	CHANGED TO 5° TAIL CANT
334	+10	+10	5	5	5	5°	15.16	534.3	114.51	2120.6		0 to steady-state rate
335	+10	+10	5	5	5	10°	14.87	533.5	113.32	2121.0		0 to steady-state rate
336	+10	+10	5	5	5	15°	15.20	533.6	114.58	2120.6		0 to steady-state rate
337	+10	+10	5	5	5	20°	15.10	533.2	114.18	2120.7		0 to steady-state rate
338	+10	+10	5	5	5	25°	15.06	532.8	113.99	2120.7		0 to steady-state rate
339	+10	+10	5	5	5	30°	14.97	532.8	113.62	2120.9		0 to steady-state rate
340	-	-	5	5	5	0°	15.04	517.1	112.39	2114.4		REMOVED CANARD FINS
341	-	-	5	5	5	5°	14.91	517.4	111.92	2114.6		0 to steady-state rate

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE													
RUN NO.	CONFIGURATION				YAW ANGLE (DEG)	Q (PSF)	TEMP. (°R)	VEL. (FPS)	P (PSFA)	INITIAL CONDITIONS		REMARKS	
	CANARD DEFLECTION (DEG)	TAIL DEFLECTION (DEG)	SPUN-UP	PIN-PULL ANGLE (DEG)									
342	-	-	-	-	5	5	15.10	518.4	112.75	2114.4	0		
343	-	-	-	-	5	5	15.04	518.8	112.57	2114.4	0		
344	-	-	-	-	5	5	15.03	519.5	112.58	2114.4	0		
345	-	-	-	-	5	5	15.08	519.8	112.83	2114.3	0		
346	-	-	-	-	5	5	15.04	520.2	112.72	2114.4	0		
	-	-	-	-	-	-					CHANGE TAIL CANT TO 0°		
347	-	-	-	0	0	0	14.93	520.5	112.32	2114.5	Spun-Up		
348	-	-	-	0	0	0	15.06	520.9	112.87	2114.4	Spun-Up		
349	-	-	-	0	0	0	15.06	521.2	112.91	2114.4	Spun-Up	No lock-in at 10°	
350	-	-	-	0	0	0	15.14	521.5	113.24	2114.3	Spun-Up	Weak lock-in at 10°	
351	-	-	-	0	0	0	15.10	522.2	113.16	2114.4	Spun-Up		
352	-	-	-	0	0	0	14.99	522.9	112.80	2114.5	Spun-Up		

Table A-1. Run Log for Subsonic Free-Rolling Wind Tunnel
Test of Canard-Control Missile (Continued)

EXPERIMENTAL CANARD - CONTROL MISSILE															
RUN NO.	CONFIGURATION								Q (PSF)	TEMP. ° (°R)	VEL. (FPS)	P (PSIA)	INITIAL CONDITIONS		REMARKS
	CANARD				TAIL								SPUN-UP	PIN-PULL ANGLE (DEG)	
	DEFLECTION (DEG)				DEFLECTION (DEG)										
	δ_{C1}	δ_{C2}	δ_{C3}	δ_{C4}	δ_{T1}	δ_{T2}	δ_{T3}	δ_{T4}							
353	-	-	-	-	0	0	0	0	14.97	523.3	112.77	2114.5	Spun-Up		
354	-	-	-	-	0	0	0	0	15.10	524.0	113.35	2114.3	Pin-Pull 0		
355	-	-	-	-	0	0	0	0	15.20	524.0	113.71	2114.3	0		
	-	-	-	-	-	-	-	-					CHANGED TO 5° TAIL CANT		
356	-	-	-	-	5	5	5	5	15.08	526.0	113.50	2114.4		Undamps with many oscillations to steady- state	
357	-	-	-	-	5	5	5	5	15.22	528.2	114.25	2114.3		0 to steady-state rate	
358	-	-	-	-	5	5	5	5	15.04	529.0	113.67	2114.5		4 undamped oscillations to steady-state	
359	-	-	-	-	5	5	5	5	15.10	531.2	114.13	2114.4	Spun-Up	Turbine	
	-	-	-	-	-	-	-	-						END OF TEST	
	-	-	-	-	-	-	-	-							
	-	-	-	-	-	-	-	-							
	-	-	-	-	-	-	-	-							
	-	-	-	-	-	-	-	-							
	-	-	-	-	-	-	-	-							

APPENDIX B
NOMENCLATURE

NOMENCLATURE

C_{ac}, C_{as}	Roll asymmetry coefficients, defined in Equation (6)
C_{jk}	Roll moment coefficients, defined in Equation (6) (see Table 1)
C_{ljk}	Roll moment coefficients, defined in Equation (5)
C_l	Roll moment coefficient (l/QSd)
$C_l(p)$	Roll moment coefficient variation with missile spin rate
C_{lp}	Linear roll damping moment coefficient
C_{lpj}	j^{th} order roll damping moment coefficient, defined in Equation (4)
$C_{lp}(4Y)$	Variation of roll damping moment coefficient with roll angle for a four-finned missile (see Table 1)
$C_{lp}(4KY)$	K^{th} order variation of roll damping moment coefficient with roll angle for a four-finned missile (see Table 1)
$C_{l\delta}$	Fin cant roll moment coefficient
$C_{l\delta}(4Y)$	Variation of fin cant moment with roll angle for a four-finned missile (see Table 1)
$C_{l\delta}(4KY)$	K^{th} order variation of fin cant moment with roll angle for a four-finned missile (see Table 1)
$C_l(Y)$	Roll moment coefficient variation with roll angle
$C_l(4Y)$	Induced rolling moment coefficient for a four-finned missile
$C_l(4KY)$	K^{th} order induced rolling moment coefficient for a four-finned missile, defined in Equation (3) (see Table 1)
d	Missile reference diameter
I_x	Missile axial moment of inertia
p	Missile spin rate, $p = \dot{\gamma}$
Q	Dynamic pressure
S	Missile reference area

S_{jk}	Roll moment coefficient, defined in Equation (6) (see Table 1)
V	Free-stream velocity
α	Angle of attack
γ	Roll orientation angle, measured between reference fin No. 1 and normal component of missile velocity vector
γ_0	Initial roll orientation angle
δ	Fin cant angle
δ_{C1}	Canard deflection angles, defined in Figure 4
δ_{C2}	
δ_{C3}	
δ_{C4}	
δ_{T1}	Tail fin deflection (cant) angles, defined in Figure 4
δ_{T2}	
δ_{T3}	
δ_{T4}	

DISTRIBUTION

Commander
Naval Air Systems Command
Washington, DC 20360
ATTN: AIR-320, Mr. Bill Volz
AIR-320, Dr. H. Mueller
Technical Library

(2)

Commander
Naval Weapons Center
China Lake, CA 93555
ATTN: Code 4063, Mr. Ray Van Aken
Code 4063, Mr. R. E. Meeker
Code 4063, Mr. R. M. Rogers
Technical Library

Army Air Mobility Research and Development Laboratory
Ames Directorate
NASA, Ames Research Center
Moffett Field, CA 94035
ATTN: F. Lazzeroni (Mail Stop N216)
G. Laub (Mail Stop N216)

Commander
Naval Sea Systems Command
Washington, DC 20360
ATTN: SEA-03, Mr. Lionel Pasiuk
Technical Library

(2)

Commander
Naval Material Command
Washington, DC 20360
ATTN: Mr. Sid Jacobson (MAT-032)
Dr. John Huth
Technical Library

(2)

Commander
Pacific Missile Test Center
Point Mugu, CA 93041
ATTN: Mr. Joe Rom
Technical Library

(2)

DISTRIBUTION (Continued)

Commander
Naval Ship Research and Development Center
Washington, DC 20007
ATTN: S. Gottlieb
Martin Cook
Technical Library

Chief of Naval Research
Department of the Navy
Washington, DC 20360
ATTN: Technical Library (2)

Commander
Pacific Missile Test Center
U.S. Naval Missile Center
Point Mugu, CA 93041
ATTN: Technical Library (2)

Director
Naval Strategic Systems Projects Office (PM-1)
Department of the Navy
Washington, DC 20360
ATTN: Technical Library (2)

Superintendent
U.S. Naval Academy
Annapolis, MD 21402
ATTN: Head, Weapons Department
Head, Science Department
Technical Library (2)

Superintendent
U.S. Naval Postgraduate School
Monterey, CA 95076
ATTN: Head, Mechanical Engineering Department
Head, Department of Aeronautics
Technical Library (2)

Officer in Charge
U.S. Naval Scientific and Technical Intelligence Center
U.S. Naval Observatory
Washington, DC 20360
ATTN: Technical Library (2)

DISTRIBUTION (Continued)

Commander
Naval Weapons Center
Corona Laboratories
Corona, CA 91720
ATTN: Technical Library (2)

Office of Naval Research
Pentagon
Washington, DC 20350
ATTN: Dr. R. J. Lundegard
Mr. Dave Seigel
Dr. Bob Whitehead
Mr. Mort Cooper
Mr. Ralph Cooper
Technical Library (2)

Officer in Charge
Carderock Laboratory
Naval Ship Research and Development Center
Bethesda, MD 20034
ATTN: Technical Library (2)

Deputy Chief of Naval Operations
(Development)
The Pentagon
Washington, DC 20350
ATTN: Technical Library (2)

Commanding Officer
Naval Air Development Center
Warminster, PA 18974
ATTN: Technical Library (2)

Commanding Officer
Naval Air Engineering Center
Aeronautical Structures Department
Lakehurst, NJ 19112
ATTN: Technical Library (2)

DISTRIBUTION (Continued)

Commanding Officer
Naval Ordnance Station
Indian Head, MD 20640
ATTN: Technical Library (2)

Commandant of the Marine Corps
Headquarters, Marine Corps
Washington, DC 20380
ATTN: Technical Library (2)

Director, Development Center
Marine Corps Development and Education Command
Quantico, VA 22134

Chief of S and R Division
Development Center
Marine Corps Development and Education Command
Quantico, VA 22134

Chief of Air Operations Division
Development Center
Marine Corps Development and Education Command
Quantico, VA 22134

Chief of Ground Operations Division
Development Center
Marine Corps Development and Education Command
Quantico, VA 22134

Marine Corps Liaison Officer
Field Artillery Board
Fort Sill, OK 73503
ATTN: Technical Library (2)

Commanding General
Ballistic Research Laboratory
Aberdeen Proving Ground, MD 21005
ATTN: Dr. C. H. Murphy
Mr. L. McAllister
Dr. A. Platou
Mr. B. McCoy
Technical Library (2)

DISTRIBUTION (Continued)

Commanding General
Picatinny Arsenal
Dover, NJ 07801
ATTN: Mr. A. Loeb
Mr. Mertz
M. Cline
Technical Library (2)

Commanding General
U.S. Army Missile Command
Redstone Arsenal, AL 35809
ATTN: Mr. Ray Deep (DRSMI)
Dr. D. J. Spring (DRSMI)
Technical Library (2)

Commanding General
U.S. Army Material Command AMCRD-TP
Washington, DC 20315
ATTN: Technical Library (2)

Office of Chief of Research and Development
Washington, DC 20310
ATTN: Technical Library (2)

Commanding Officer
Army Chemical Center
Edgewood, MD 21040
ATTN: Technical Library (2)

Commanding General
Frankford Arsenal
Philadelphia, PA 19104
ATTN: Mr. W. Gadomski
Technical Library (2)

Commanding Officer
Harry Diamond Laboratories
Washington, DC 20013
ATTN: Technical Library (2)

Commanding Officer of U.S. Army Combat Development Command
Field Artillery Agency
Fort Sill, OK 73503
ATTN: Technical Library (2)

DISTRIBUTION (Continued)

President of U.S. Army Field Artillery Board
Fort Sill, OK 73503
ATTN: Technical Library

(2)

Aeronautical Research Laboratory
Wright-Patterson Air Force Base
Dayton, OH 45433
ATTN: Technical Library

(2)

Aeronautical System Division
USAF
Wright-Patterson Air Force Base
Dayton, OH 45433
ATTN: Technical Library

(2)

AF Office of Scientific Research
Washington, DC 20330
ATTN: Technical Library

(2)

Arnold Engineering Development Center
USAF

Tullahoma, TN 37389
ATTN: Mr. J. Uselton
Mr. L. M. Jenke
Mr. W. B. Baker, Jr.
Technical Library

(3)

Headquarters, USAF
Systems Command
Andrews Air Force Base, MD 20331
ATTN: Technical Library

(2)

Headquarters, USAF
Washington, DC 20330
ATTN: Technical Library

(2)

Flight Research Center
Edwards Air Force Base, CA 93523
ATTN: Technical Library

(2)

Air Force Rocket Propulsion Laboratory (AFSC)
Department of the Air Force
Edwards, CA 93523
ATTN: Major Washburn

DISTRIBUTION (Continued)

U.S. Air Force Systems Command Regional Offices
c/o Department of the Navy
Washington, DC 20360
ATTN: Technical Library (2)

AFATL (ADLRA), (DLGC)
Eglin Air Force Base, FL 32542
ATTN: Dr. Daniel
Mr. C. Butler
Mr. C. Matthews
Mr. K. Cobb
Mr. E. Sears
Technical Library (2)

USAF Academy
Colorado Springs, CO 80912
ATTN: Technical Library (2)

Wright Air Development Center/AFFDL
Wright-Patterson Air Force Base, OH 45433
ATTN: Mr. E. Flinn (FGC)
Dr. G. Kurylowich (FGC)
Technical Library (2)

Applied Physics Laboratory
The John Hopkins University
8621 Georgia Avenue
Silver Spring, MD 20910
ATTN: Dr. L. L. Cronvich
Mr. Edward T. Marley
Dr. Gordon Dugger
Technical Library (2)

Advanced Research Projects Agency
Department of Defense
Washington, DC 20305
ATTN: Technical Library (2)

Director
Defense Research and Engineering
Department of Defense
Washington, DC 20305
ATTN: Technical Library (2)

DISTRIBUTION (Continued)

George C. Marshal Flight Center
Huntsville, AL 35804
ATTN: Technical Library (2)

NASA Goddard Space Center
Greenbelt, MD 20771
ATTN: Technical Library (2)

NASA Lewis Research Center
Cleveland, OH 44101
ATTN: Technical Library (2)

NASA
Washington, DC 20546
ATTN: Technical Library (2)

NASA Ames Research Center
Moffett Field, CA 94035
ATTN: Mr. Vic Peterson
Mr. John Rakich
Technical Library (2)

NASA Langley Research Center
Langley Station
Hampton, VA 23365
ATTN: Mr. Bud Bobbitt
Mr. Jerry South
Mr. Leroy Spearman
Mr. C. M. Jackson, Jr.
Mr. W. C. Sawyer
Technical Library (2)

Virginia Polytechnic Institute and State University
Department of Aerospace Engineering
Blackburg, Virginia 24060
ATTN: Prof. J. A. Schetz
Technical Library (2)

Stanford Research Institute
Menlo Park, CA 94025
ATTN: Dr. Milton Van Dyke
Technical Library (2)

DISTRIBUTION (Continued)

Raytheon Company
Spencer Laboratory
Burlington, MA 01803
ATTN: Steve Pealsing
Box SL 7162

North Carolina State University
Department of Mechanical and Aerospace Engineering
Box 5246
Raleigh, NC 27607
ATTN: Prof. F. R. DeJarnette
Technical Library (2)

The University of Tennessee Space Institute
Tullahoma, TN 37388
ATTN: Dr. J. M. Wu
Technical Library (2)

Director Defense Research and Engineering
Department of Defense
Washington, DC 20301
ATTN: Bartley Osborne, R&AT Office

Dr. Jim Zerikos
McDonnell Douglas Astronautics Company (West)
5301 Bolsa Avenue
Huntington Beach, CA 92647
Mall Station 13-2

Mr. B. H. Shirley
Lockheed Missiles & Space Co., Inc.
P. O. Box 1103, W. Street
Huntsville, AL 35807

Dr. Lars E. Erisson
Lockheed Missiles & Space Co., Inc.
Department 81-10, Bldg. 154
Sunnyvale, CA 94088

Nielsen Engineering and Research, Inc.
510 Clyde Avenue
Mountain View, CA 94043

DISTRIBUTION (Continued)

Mr. V. L. Pianta
Senior Project Engineer
P. O. Box 1201
San Jose, CA 95108

Defense Documentation Center
Cameron Station
Alexandria, VA 22314

(12)

Library of Congress
Washington, DC 20390
ATTN: Gift and Exchange Division

(4)

Defense Printing Service
Washington Navy Yard
Washington, DC 20374

Califronia Polytechnic Institute
Aeronautical Engineering Department
San Luis Obispo, CA 93407
ATTN: Dr. John D. Nicolaidis

Local:

DG

DG-04

DG-44

DK

DK-01

DK-20

DK-21 (10)

DK-50

DN

DN-80

DX-21 (2)

DX-222 (6)

DX-40

DX-43 (Shea)

WA

WA-20 (Mr. B. Piper)

WA-20 (Mr. G. Graff)

WA-30

WA-40

WA-40 (Mr. S. Hastings)

WA-40 (Dr. J. Goeller)

DISTRIBUTION (Continued)

Local:

WA-40 (Dr. N. Sheetz)
WA-40 (Dr. J. Solomon)
WA-40 (Mr. F. Baltakis)
WA-41 (F. J. Regan)
WA-42 (M. V. Krumins)
WA-50
WR
WX-40