

AD-A045 839

HARRY DIAMOND LABS ADELPHI MD
SOURCE-REGION EMP COUPLING RELATED TESTS: RECTANGULAR GEOMETRY, (U)
SEP 77 J F DIETZ, G MERKEL, D J SPOHN
HDL-TM-77-23

F/G 20/3

UNCLASSIFIED

NL

1 of 1
ADA045839



END
DATE
FILMED
11-77
DDC

AD A 045839

DDC
REFERENCE
NOV 2 1977
B

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER HDL-TM-77-23	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Source-Region EMP Coupling related Tests: Rectangular Geometry		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) John F. W. Dietz George/Merkel Daniel J. Spohn		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783		8. CONTRACT OR GRANT NUMBER(s) DNA Subtask: R99QAXEB088
11. CONTROLLING OFFICE NAME AND ADDRESS Director Defense Nuclear Agency Washington, DC 20305		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Ele: 62704H
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE Sept 1977
15. SECURITY CLASS. (of this report) Unclassified		13. NUMBER OF PAGES 33
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES This work was funded by the Defense Nuclear Agency under Subtask R99QAXEB088, Work Unit 51, Tactical Source Region Coupling and Simulation Feasibility. MIPR: 75545 HDL Project: E055E3		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Electromagnetic pulse Source-region EMP Simulation AURORA tests		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report describes a series of source-region EMP experiments, which were conducted at the Defense Nuclear Agency's AURORA Flash X-Ray Facility. Measured data are compared with pretest calculations of the predicted responses of simple rectangular gamma-thick and gamma-thin structures that were exposed to ionizing radiation. Predicted values of Compton current also are compared with		

DD FORM 1473 1 JAN 73 EDITION OF 1 NOV 68 IS OBSOLETE

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

163050

next page

ent

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

data obtained by using a Compton diode and Rogowski coils in collimated and uncollimated configurations.

ACCESSION for		
NTIS	Write Section	<input checked="" type="checkbox"/>
DDC	Buff Section	<input type="checkbox"/>
UNANNOUNCED		<input type="checkbox"/>
JUSTIFICATION		
BY		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	AVAIL	and/or SPECIAL
A		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

FOREWORD

This report describes the tests conducted at the AURORA Flash X-Ray Facility in support of the Tactical Environment Multiple Systems Evaluation Program funded jointly by the Defense Nuclear Agency and the U.S. Army Materiel Development and Readiness Command. The tests were conducted during early December 1975 by the authors and Leedy Ambrose of the Harry Diamond Laboratories. The experimenters thank the AURORA staff for their kind assistance during the tests.

CONTENTS

	<u>Page</u>
1. OBJECTIVES	7
2. TEST CONFIGURATION	7
3. PRETEST ANALYSIS AND CHECKOUT	10
3.1 Predictions	10
3.1.1 Quasi-static Model	11
3.1.1.1 γ -Thick Calculations	11
3.1.1.2 γ -Thin Calculations	15
3.1.2 Equivalent Circuit Model	16
3.1.3 Compton Diode	16
3.1.4 Rogowski Coil	16
3.1.5 Collimated Rogowski Coil	17
3.1.6 Collimated Dosimeter Experiments	17
3.2 Special Instrumentation	18
3.3 Posttest Checkout	19
4. TEST PROCEDURES	19
5. DATA REDUCTION	20
6. TEST RESULTS	20
6.1 Voltage Measurements: Compton Diode and Rogowski Coil	20
6.2 Current Measurements	24
6.3 Collimation Experiment	27
7. CONCLUSIONS	27
DISTRIBUTION	29

FIGURES

1 Primary test geometry	8
2 Cable arrangement between test cell and data taking room	9
3 Cathode follower circuit	18

FIGURES (CONT'D)

	<u>Page</u>
4 Compton current inside test chamber; dose rate = 4.01×10^9 rads (Si)/s	21
5 Compton current inside test chamber; dose rate = 3.82×10^9 rads (Si)/s	22
6 Compton current inside test chamber; dose rate = 4.06×10^9 rads (Si)/s	22
7 Compton current inside test chamber; dose rate = 4.94×10^9 rads (Si)/s	23
8 Compton current inside test chamber; dose rate = 4.64×10^9 rads (Si)/s	23
9 Current coupled to γ -thin inner box; dose = 497 rads (Si) . . .	25
10 Current coupled to γ -thick inner box; dose = 520 rads (Si) . .	25
11 Current coupled to γ -thick inner box; dose = 567 rads (Si) . .	26

TABLES

I Shot Schedule	19
II Experimental and Theoretical Values of Peak Compton Current .	24
III Experimental and Theoretical Values of Peak Current Coupled to Inner Box	26

1. OBJECTIVES

The test described in this report was performed in support of the Tactical Environment Multiple Systems Evaluation Program (TEMSEP), a program at the Harry Diamond Laboratories (HDL) directed toward the analysis and testing of the vulnerability of tactical military systems to the effects of electromagnetic pulse (EMP) when exposed to nearby nuclear detonations.

The purpose was primarily to test the effectiveness of the instrumentation to be used in a more extensive source-region EMP simulation-related AURORA test planned for March 1976. In the event that the instruments failed to perform adequately, necessary modifications could be completed before the start of the March test.

The most important instrument to be evaluated was a cathode follower amplifier to be utilized as a matching element in an attempt to make high impedance voltage measurements in the environment of the Defense Nuclear Agency's AURORA Flash X-Ray Facility at HDL. This amplifier was to be evaluated during an attempt to measure the voltage generated between a conducting body and a conducting enclosure within which it was suspended.

Another instrument to be evaluated was a newly constructed Compton diode sensor which was to be utilized to measure Compton current densities. The output of this instrument was to be correlated with results obtained with thermoluminescent dosimeters (TLD's) and Rogowski coils.

A secondary objective of these experiments concerned the investigation of the source distribution of the AURORA radiation, by using collimated TLD's and a collimated Rogowski coil. In addition, the experiments tested equivalent circuit models for source-region coupling, such as that developed by Conrad Longmire of Mission Research Corp.¹ and presently being extended at HDL by Monti Wilson. Since the test configuration being utilized to evaluate the cathode follower amplifier was amenable to equivalent circuit analysis, the short-circuit current was to be measured during some shots.

2. TEST CONFIGURATION

The primary test geometry consisted of a box 6 × 6 × 6 in. (15.2 × 15.2 × 15.2 cm) constructed of 1/4-in. (0.6-cm) aluminum, suspended on nylon rope in a 26-in. (66-cm) square conducting upper chamber of a two-chamber radio frequency interference (RFI) shielded box. The inner aluminum box, located in the center of the upper

¹C. L. Longmire, *Direct Interaction Effects in EMP*, Mission Research Corp. LANC-N-12 (November 1973).

chamber, was connected with a thin wire to a BNC feed-through connector to the lower chamber where the cathode followers were located. The cathode follower was connected to a cable running to the data room, where the cable was ultimately terminated (fig. 1). The two chambers were separated by a 1-in. (2.5-cm) aluminum partition. The suspended 6-in. (15.2-cm) aluminum box was employed in two modes: one with the box empty so that it was thin with respect to the absorption range of the γ radiation and another with the box filled with lead so that it was thick compared with the absorption range of the radiation. The outer RFI enclosure was of double-wall galvanized sheet metal construction with separate RFI gasketed entry ports in the two chambers and a cable port in the lower chamber. The upper chamber was exposed directly to the radiation, but the lower chamber was shielded on the exterior, with 4 in. (10.2 cm) of lead adjacent to the front and the two sides, and on the interior, with 2 in. (5.1 cm) of lead adjacent to the top, the sides, and the bottom.




Figure 1. Primary test geometry.

placed on the center axis of the AURORA test cell with the front of the chamber located at the 700-rad total dose line. The chamber was elevated so that the center of the inner aluminum box was at the axis of the γ radiation (approximately 70 in.--1.8 m--from the floor). The Compton diode and Rogowski coils were placed on a wooden cart approximately 6 ft (1.82 m) from the experimental chamber and approximately 70 in. (1.8 m) from the floor, at the 500-rad total dose

The data cables extended through the data cable port down through a 4-in. (10.2-cm) thick lead chimney through the floor and along trenches covered with 2 in. (5.1 cm) of steel to the data room wall. In addition, the cables were wrapped with two layers of RFI zip tubing terminated on one end at the inner and the outer layers of the experimental chamber and on the other end at the test cell wall (fig. 2). Also, two BNC and two type "N" feed-through connectors were placed in the side of the lower chamber to be used with the externally placed Rogowski coils and the Compton diode. Two gas ports were installed in the upper chamber: one in the side near the bottom and one on the top.

The experimental chamber was




Figure 2. Cable arrangement between test cell and data-taking room. (The 78-Ω double-balanced line is used for the Rogowski coil measurements. The cathode followers and the Compton diode feed the coaxial lines.

line, but not on the axis of the radiation. These sensors were connected to the lower chamber with exposed cable (no zip tube). The collimated dosimeter experiment consisted of seven TLD's, three located at the ends of holes drilled through 2 in. (5.1 cm) of lead, three at the ends of holes drilled through 4 in. (10.2 cm) of lead, and one with no collimation. The experiment was located near the Compton diode. The axes of the collimating holes were oriented along radii to the focus of the radiation source (the hot spot). The entire experimental setup was backed with 2-in. (5.1-cm) lead bricks to shield the dosimeters from scattered radiation.

These measurements were made during the test series: short-circuit current from the inner box to the outer box, open-circuit voltage between the inner and the outer boxes, magnetic fields and Compton currents inside the upper chamber, and Compton current outside the experimental chamber. Total dose measurements were made at various locations inside and outside the experimental chamber, as well as at the peripheral Compton diode and Rogowski coil locations.

A variety of sensors was employed in obtaining the data. The short-circuit current was measured on the wire extending from the aluminum box to the outer chamber wall by using an Adams Electronic Corp. (ADELCO) current probe placed inside the lower chamber. This probe was connected to VE-20072 twisted shielded twin-axial cable running to the data room, where it connected through a balun transformer to an RG-213 coaxial cable. This cable led to the user rack and then to the oscilloscope, where it was terminated in 50Ω . The magnetic fields inside the upper chamber were measured by using Moebius loop \dot{B} sensors. The sensor output was carried to the oscilloscope through cabling similar to that used for the current probes. The Compton currents inside the upper chamber (specifically, in front of and behind the floating aluminum box) were measured by using Rogowski coils, which are very similar to the ADELCO current probe, but somewhat larger. Consequently, the cable assembly was the same as that used for the current probes and magnetic field sensors.

The voltage measurements were made by using Tektronix voltage probes (P6006 and P6015) feeding cathode follower amplifiers (gain of approximately 0.7). The cathode follower drove the low impedance cable without loading the high impedance input. In most tests, the drive cable was $50\text{-}\Omega$, RG-223 coaxial cable, which was patched to the user rack and then to the oscilloscope, where it was terminated in 50Ω . In one test, in an attempt to lower the noise level on the cable, the cathode follower drove a $72\text{-}\Omega$ twin-axial cable with baluns at both ends.

The noise levels induced on representative cables also were noted. The noise was measured by recording the induced signal with the sensor disconnected or short-circuited, but with the cable remaining in its normal configuration.

The total dose was measured during each shot at strategic locations in and around the experimental chamber by using TLD's furnished by AURORA. High dose-->50 rads (Si)--or low dose--<50 rads (Si)--TLD's were used where appropriate.

3. PRETEST ANALYSIS AND CHECKOUT

3.1 Predictions

Prior to the test, a series of calculations was performed to predict the response of the various instruments and the test set to the radiation environment. These calculations served as a basis upon which to judge the experimental data, as well as an indication as to the expected signal level for setting the oscilloscope. The calculations addressed the basic concentric box test set response by using a quasi-static model and an equivalent circuit model. The Compton diode,

the collimated Rogowski coil, and the Rogowski coil sensors were treated with simple coupling models.

3.1.1 Quasi-static Model

3.1.1.1 γ -Thick Calculations

Voltage.--Because of the relatively slow rise time of the AURORA radiation pulse, it was assumed that calculations of voltages generated between the inner and the outer boxes and of the current generated on the inner box could be treated quasi-statically. Since pretest calculations were done merely to produce rough estimates of oscilloscope voltage settings, a simple static model was developed to generate voltage and current predictions.

If the region between the boxes is a perfect vacuum with no conductivity, the voltage generated between the inner and the outer boxes is equal to

$$V = Q/C , \quad (1)$$

where Q is the total charge deposited and C is the capacitance of the boxes. Since the total charge deposited is equal to the time integral of the intercepted current, if the inner box is γ -thick and the outer box is γ -thin, the total charge deposited on the inner box is given by

$$q = \int_0^T [J(t) \cdot A] dt ,$$

where T is the width of the radiation pulse, J is the Compton current density at the front of the inner box, and A is the area of the front face of the box. Since the Compton current density generated in air is equal¹ to

$$J = -2 \times 10^{-8} \dot{\gamma} , \quad (2)$$

where $\dot{\gamma}$ is the dose rate, the total charge deposited is given by

$$q = 2 \times 10^{-8} D_{\gamma} A , \quad (3)$$

¹C. L. Longmire, *Direct Interaction Effects in EMP*, Mission Research Corp. LANC-N-12 (November 1973).

where D_γ is the total radiation dose in rads (Si). The peak voltage generated between the boxes, then, is given by

$$V_p = 2 \times 10^{-8} D_\gamma A/C . \quad (4)$$

It was assumed that the capacitance of the two boxes was approximately equal to the capacitance of two concentric spheres, each having a surface area equal to the surface area of one of the boxes. Since the two boxes were cubes of edge length 6 and 26 in. (15.2 and 66 cm), spheres of equal surface area would have radii of 0.105 and 0.457 m, respectively.

The capacitance of a sphere within a sphere is equal² to

$$C = 4\pi\epsilon_0 \frac{r_1 r_2}{r_2 - r_1} , \quad (5)$$

where ϵ_0 is the permittivity of free space and r_1 and r_2 are the radii of the spheres. Thus, the capacitance of the boxes, assuming that they are spheres with the above-mentioned radii, is equal to 15.2 pF.

The boxes were to be placed so that the dose on the front of the inner box would be 500 rads (Si). With $D = 500$ rads (Si), $A = 0.023 \text{ m}^2$, and $C = 1.52 \times 10^{-11} \text{ F}$, equation (4) yielded a peak voltage of 15.4 kV.

Because the region between the cylinders was to be filled with 1 atm of SF_6 or with 1 atm of dry air, it was necessary to modify this result. Since the electron attachment rate of SF_6 is very large, it was assumed that the conductivity of the region between the boxes would be small, so that the voltage calculated above would not be reduced significantly. It was estimated that the peak voltage generated would be 7 to 8 kV.

When the region between the boxes is filled with air, the voltage generated between the inner and the outer boxes is reduced because some charge flows through the ionized, conducting air between the boxes. The peak voltage generated is then

$$V_p = \frac{1}{C} (q - q_L) , \quad (6)$$

²W. P. Smythe, *Static and Dynamic Electricity*, McGraw-Hill Book Co., Inc., New York (1968), 27.

where q is the total charge deposited on the inner box and q_L is the leakage charge.

The leakage charge is given by

$$Q_L = \int_0^T \sigma E dt, \quad (7)$$

where σ is the air conductivity in the region between the cylinders and E is the electric field in this region. If the electric field between the boxes is approximately equal to V/d , where V is the voltage generated between the boxes and d is the distance between the boxes,

$$q_L = \frac{1}{d} \int_0^T \sigma V dt.$$

The ionization rate, Q , in ion pairs per cubic meter second produced in the region between the boxes is equal to*

$$Q = 2.25 \times 10^{15} \dot{\gamma},$$

and the peak number density of electrons (N_{ep}) produced in this region is given by

$$N_{ep} = Q/\alpha_e,$$

where α_e is the electron attachment rate in air. Since it can be assumed that most of the conductivity in the region between the boxes is due to electrons, the peak conductivity (σ_p) in mhos per meter in this region is equal to

$$\sigma_p = 1.6 \times 10^{-19} N_{ep} \mu_e,$$

*C. L. Longmire, *A Simple Analysis of the Blue Cylinder Experiments*, Mission Research Corp. AURORA EMP Memorandum 3 (October 1975).

where μ_e is the electron mobility. If the electron attachment rate is equal to $8 \times 10^7 \text{ s}^{-1}$ and the electron mobility is $0.6 \text{ m}^2/\text{V s}$, the peak conductivity is equal to

$$\sigma_p = 2.73 \times 10^{-12} \dot{\gamma}.$$

If the average conductivity can be approximated by $\sigma_p/2$, and if the average voltage can be approximated by $V_p/2$, then equation (7) becomes

$$q_L = 6.8 \times 10^{-13} D_\gamma V_p / d.$$

When this equation and equation (3) are substituted into equation (6), the result is the following equation for the peak voltage:

$$V_p = 2 \times 10^{-8} A - 6.8 \times 10^{-13} V_p / d D_\gamma / C.$$

Solving for V_p yields

$$V_p = \frac{2 \times 10^{-8} A d D_\gamma}{C d + 6.8 \times 10^{-13} D_\gamma}. \quad (8)$$

The peak voltage generated at the 500-rad (Si) location would then be 170 V.

In this and in all subsequent calculations, any boundary layer effects have been neglected.

Current.--When the inner box is γ -thick, the short-circuit current flowing between the inner and the outer boxes should equal the Compton current intercepted by the inner box. Thus, the current would be given by

$$I = JA, \quad (9)$$

where J is calculated from equation (2). At the 500-rad (Si) location, the current should be 1.6 A.

In this and all subsequent calculations of coupled current, electromagnetic coupling effects have been neglected.

3.1.1.2 γ -Thin Calculations

Voltage.--Since the side plates of the aluminum inner box are 6 in. (15.2 cm) long and the density of aluminum is 2.7 g/cm³, the projected mass per unit area of these plates is 41 g/cm². Since this value is neither small nor large compared with 30 g/cm², which is a typical energy absorption mass for γ rays,³ these plates are neither truly γ -thin nor γ -thick. Thus, the rate of charge collection of each of these plates is given by¹

$$\frac{dq}{dt} = \frac{2 \times 10^{-8}}{m_{\gamma}} \int \rho \bar{\gamma} dV_{pl} ,$$

where $m_{\gamma} = 300 \text{ kg/m}^2$, ρ is the density of the plates in kilograms per cubic meter, $\bar{\gamma}$ is the γ flux over all directions, and V_{pl} is the volume of the plates. Consider the radiation beam to be approximately in one direction, and let the flux be $\bar{\gamma}_f$ at the front of the plate, then¹

$$\frac{dq}{dt} = \frac{2 \times 10^{-8} A_{pl} \rho \bar{\gamma}_f}{m_{\gamma}} \int_0^{\ell} \exp(-\rho x/m_{\gamma}) dx ,$$

where A_{pl} is the cross-sectional area of each plate, ℓ is the length of each plate, and x is the distance. Integration yields

$$dq/dt = 2 \times 10^{-8} A_{pl} \bar{\gamma}_f \left[1 - \exp(-\rho \ell/m_{\gamma}) \right] . \quad (10)$$

The total charge deposited during the radiation pulse on each plate is then given by

$$q = 2 \times 10^{-8} A_{pl} D_{\gamma f} \left[1 - \exp(-\rho \ell/m_{\gamma}) \right] . \quad (11)$$

Since the front and the back^o plates of the box are γ -thin, the total charge collected by each is given by

$$q = 2 \times 10^{-8} M D_{\gamma} / m_{\gamma} , \quad (12)$$

¹C. L. Longmire, *Direct Interaction Effects in EMP*, Mission Research Corp. LANC-N-12 (November 1973).

³R. D. Evans, *The Atomic Nucleus*, McGraw-Hill Book Co., Inc., New York (1955), 715.

where M is the mass of each plate. If the total dose at the front of the box were 500 rads (Si), the total charge collected by the box would be 5.5×10^{-8} C. If the region between the boxes were a vacuum, the peak voltage generated would be 280 V. If the region between the boxes were filled with SF₆, about 150 V would be generated. If the region were filled with air, at most a few volts would be generated.

Current.--When the inner box is not filled with lead, the short-circuit current must be calculated by using equation (10) and the derivative of equation (12). At the 500-rad (Si) location, the short-circuit current should be 0.38 A.

3.1.2 Equivalent Circuit Model

An equivalent circuit model is being developed by HDL for calculating coupling in a radiation environment. Prior to the test, some preliminary predictions of the test geometry response were made, but subsequently it was discovered that the circuit employed was not completely adequate for that application. Consequently, those pretest predictions, which were erroneous, are not discussed here.

3.1.3 Compton Diode

The current collected by the Compton diode should be equal to

$$I = J_d A_{c1} , \quad (13)$$

where J_d is the Compton current density at the front of the diode, and A_{c1} is the exposed area of the collector. If the Compton diode were placed at a location where the total dose would be 500 rads (Si), and if the effective AURORA pulse width were 145 ns, then, from equation (2), the Compton current density at this location should be approximately 69 A/m². If the diameter of the collector were 2.5 in. (6.4 cm), then the current collected would be 0.22 A. If a 50-Ω cable were attached to the output of the Compton diode, the output voltage would be given by

$$V = IR_o ,$$

where R_o is equal to 50 Ω. Thus, the measured voltage would be 11 V.

3.1.4 Rogowski Coil

The current measured by a Rogowski coil is given by

$$I = J_c A_c , \quad (14)$$

where J_C is the Compton current density at the coil, and A_C is the effective area of the coil. If the diameter of the coil were 1.875 in. (4.76 cm), and if the coil were exposed to the same radiation environment as the Compton diode mentioned above, the collected current would be equal to 0.123 A. If the transfer impedance of the coil were equal to 2.4Ω , then the output voltage would be 0.295 V.

3.1.5 Collimated Rogowski Coil

If the radiation incident on the Rogowski coil were collimated with a lead collimator, then the effective area of the Rogowski coil used in equation (14) would be reduced to the area of the collimator. If the collimator had a circular hole of 1-in. (2.54-cm) diameter, and if the Compton current density at the sensor were 69 A/m^2 , then, from equation (14), the collected current would be 0.035 A, and the output voltage would be 0.084 V.

3.1.6 Collimated Dosimeter Experiments

Although it may sometimes be assumed so, the AURORA flash x-ray machine is not a point source of radiation. A more reasonable assumption is that it is a disk source of some effective area. To determine this area, an experiment was designed using TLD's placed in holes drilled through various thicknesses of lead bricks. By measuring the dose and dose rates at the same distance from the source employing 0, 2, and 4 in. (0, 5.1, and 10.2 cm) of collimation, then the effective area of the source can be calculated directly by geometrical considerations. This calculation is based on the assumptions that no γ -radiation scattering takes place in the collimating tube and that no radiation traverses the lead directly. In reality, neither of these assumptions is valid, but possibly somewhat reasonable for the purposes at hand. To determine the effective area of the AURORA source, it was assumed that the radiation emanates uniformly from a disk of some radius at the test chamber wall. For an uncollimated dosimeter, the measured dose is the sum of the contributions from the entire disk. But, if the dosimeter is placed behind some collimation, the dose is contributed only from a portion of the disk, depending on the distance and length of collimation involved. The area of the source can be calculated from the expression

$$A_s = (r_{\text{contributing}})^2 \pi D_u / D_c ,$$

where

A_s = effective area of source,
 $r_{\text{contributing}}$ = radius of disk contributing to dosimeter,
 D_u = uncollimated dose measurement,
 D_c = collimated dose measurement.

3.2 Special Instrumentation

A cathode follower circuit was employed as an impedance matching network to drive the low impedance ($50\ \Omega$) cable while making a high impedance ($10\ \text{M}\Omega$) measurement so that signals sufficiently above noise levels remained. The cathode follower was selected because of the high input impedance ($1\ \text{M}\Omega$) and low output impedance ($50\ \Omega$) coupled with a gain of 0.7. In addition, the cathode follower (of tube rather than solid state design) was expected to operate in a radiation environment. The circuit for the cathode followers employed for this test is given in figure 3. Initial check-out of the breadboard circuit indicated that the dynamic range of the cathode follower could be expected to be from about +10 to -3 V. The final assembled versions were checked out and indicated a dynamic range from +10 to -3 V and a bandwidth of 29 MHz




Figure 3. Cathode follower circuit.

operating in a nonradiation environment. In the final placement during the test, the cathode followers were shielded with lead so that they were exposed to a total dose of 0.5 rads (Si).

3.3 Posttest Checkout

After the test, all of the instrumentation and probes were checked by using standard signal sources to insure that calibration was maintained during the test.

4. TEST PROCEDURES

The test chamber was placed at a location 2.9 m from the front test cell wall on the axis of the radiation. In this position, the total dose predicted at the front of the test chamber was 700 rads (Si) (with the machine charged to 90 kV). The series of shots was conducted with the primary measurement and the absorber specified in table I.

TABLE I. SHOT SCHEDULE.

Shot Series	Configuration	Measurement
1	γ -thin	Current
2	γ -thin	Current
3	γ -thin	Voltage
4	γ -thick	Voltage
5	γ -thick	Current
6	γ -thick	Current
7	γ -thick	Voltage
8	γ -thin	Voltage
9	γ -thick	Voltage
10	γ -thick	Voltage
11	γ -thick	Voltage
12	γ -thin	Voltage
13	γ -thin	Voltage

Twenty-eight oscilloscope channels recorded the data; 12 channels were dedicated to the primary measurement (either current or voltage on the absorber), and 16 were used to monitor cable noise or to record data on the external sensors. In addition, during the first two shots, Rogowski coils (measuring Compton current) and Moebius loops (measuring magnetic field) were placed inside the upper chamber, and the data were recorded. During the remaining shots, though, the test chamber was free of sensors, with the exception of the thin wire

connecting the suspended absorber and the data-taking point at the wall separating the two chambers.

Prior to each shot, initial estimates of the peak signals were reviewed, and a series of data channels was dedicated to each measurement with amplitude setting bracketing the predicted signal level. In this way, there was reasonable assurance that at least one oscilloscope trace would provide meaningful data.

After each shot, the shot number was recorded on the oscilloscope pictures, and the pictures were placed in an album, along with sensor

information and amplitude and time settings. In addition, notes on the experimental setup were recorded.

5. DATA REDUCTION

Data obtained during AURORA tests consist of pictures of oscilloscope traces. Unfortunately, it is not a simple task to relate the pulses appearing on these pictures to the currents, fields, etc., which are being generated within or upon an experimental configuration placed within the AURORA test cell. Sensors such as current probes and Moebius loops have response functions and certain electronic limitations which must be taken into consideration when analyzing their output. Cables tend to reduce the signals passing through them, and this reduction is frequency dependent. Consequently, a frequency-dependent transfer function representing the characteristics of the sensor-cable-balun measuring system used at AURORA is measured with a network analyzer.

The following procedure is used to analyze the data taken during AURORA experiments: The oscilloscope pictures are digitized, and the digitized information is stored on a computer disk file. This information is read into a program which plots the data. The plot is compared with the oscilloscope picture, and any needed corrections are made to the digitized data. The digitized information is then read off the disk file by a computer code developed at HDL, which numerically transforms the digitized data into the frequency domain, multiplies the frequency domain representation by the appropriate transfer function, transforms this information back into the time domain, multiplies the result by the appropriate sensor response and conversion factors, and plots the resultant information. The plotted information represents the time histories of the actual fields, currents, etc., occurring at the sensor locations during the AURORA tests, not merely measured voltages. These plots are then compared with theoretical predictions of test results.

6. TEST RESULTS

6.1 Voltage Measurements, Compton Diode and Rogowski Coil

The voltage measurements with the cathode followers and the Compton current measurements with the Compton diode and with the collimated Rogowski coil were all unsuccessful. Despite the fact that the cathode followers were shielded with lead, the small amount of radiation which reached them produced transient radiation effects on electronics (TREE), which rendered them useless. The direct coupling to the coaxial cable used with the Compton diode was of the order of the

signals being measured, so that the measurements had no value. Also, the collimator used with the Rogowski coil reduced the signal so that it was lost in the cable noise.

The output of the Rogowski coils was processed by the computer code mentioned previously; the resultant plots of the Compton current time histories are shown in figures 4 to 8. Table II lists the peak Compton currents calculated from equation (2) and those obtained from the plots shown in figures 4 to 8. Sensor RC2 was used within the larger box, and sensor RC4 was used directly in the AURORA test cell.




Figure 4. Compton current inside test chamber; dose rate = 4.01×10^9 rads (Si)/s.




Figure 5. Compton current inside test chamber; dose rate = 3.82×10^9 rads (Si)/s.




Figure 6. Compton current inside test chamber; dose rate = 4.06×10^9 rads (Si)/s.




Figure 7. Compton current inside test chamber; dose rate = 4.94×10^9 rads (Si)/s.




Figure 8. Compton current inside test chamber; dose rate = 4.64×10^9 rads (Si)/s.

TABLE II. EXPERIMENTAL AND THEORETICAL VALUES OF PEAK COMPTON CURRENT.

$\dot{\gamma}$ ($\times 10^9$ rads (Si)/s)	Sensor	Peak Compton Current	
		Experimental (A/m ²)	Theoretical (A/m ²)
4.01	RC2	64	80
3.82	RC4	85	76
4.06	RC4	73	81
4.94	RC4	112	99
4.64	RC4	112	93

In all tests, the experimental results are within 20 percent of the predicted values. One cause of the discrepancy between experiment and theory may be that the effective area of a Rogowski coil is not known accurately. The ratio of the experimental results to the measured dose rate may vary somewhat because (1) the dosimetry data vary; (2) the Rogowski coils measure the total current (Compton plus conduction) passing through them and we were not able to remove the contribution of the conduction currents to the measured values; and (3) the Rogowski coils do not measure only totally axial currents, but respond to all currents passing through the center opening.

6.2 Current Measurements

Measurements of the current flowing from the free-floating inner box also were processed, and the resultant current time histories are plotted in figures 9 to 11. Table III compares the peak currents calculated from equation (9) or equations (10) and (12) with the peak currents obtained from the plots shown in figures 9 to 11. In all tests, the experimental results are in fairly good agreement with the theoretical predictions, although the experimental results are somewhat lower. Thus, the simple model used for the predictions of these currents seems quite adequate in making rough estimates of the coupled currents.

This agreement between the crude quasi-static calculation of the current and the measured current may appear trivial, but a calculation based on a simple equivalent circuit that neglects inductive couplings and yields a reasonable answer is useful in the estimation of tactical source-region coupling. A purely capacitive, quasi-static approach to the estimation of the measured current is valid probably because the wire between the absorber and the wall of the outer cubic chamber is essentially perpendicular to both the Compton current and the magnetic field resulting from the Compton current.




Figure 9. Current coupled to γ -thin inner box; dose = 497 rads (Si).




Figure 10. Current coupled to γ -thick inner box; dose = 520 rads (Si).




Figure 11. Current coupled to γ -thick inner box; dose = 567 rads (Si).

TABLE III. EXPERIMENTAL AND THEORETICAL VALUES OF PEAK CURRENT COUPLED TO INNER BOX.

Total radiation dose (rads (Si))	Type	Peak Coupled Current	
		Experimental (A)	Theoretical (A)
497	thin	0.28	0.32
520	thick	1.28	1.63
567	thick	1.26	1.82

An appreciable amount of magnetic energy is in the outer box, but the inductive coupling between the inner γ -thick absorber and the magnetic field is very small. Let us make a crude estimate of the magnetic energy in the outer container. The inductance, L , per unit length due to the partial flux linkages within a round wire can be shown to be

$$L = \mu_0 / 8\pi ,$$

where μ_0 is the permeability of free space. If we approximate the square outer box with a round box of equal area, the inductance of the Compton current passing through the box is given by

$$L = (\mu_0/8\pi l_b),$$

where l_b is the length of the box parallel to the Compton current. Let us now compare the magnitude of the capacitive energy between the concentric boxes and the magnetic energy in the outer box. That is, let us compare $CV^2/2$ with $LI^2/2$. The Compton current (I) through the box is $I = JA_0$, where A_0 is the area of the outer box.

We find that

$$CV^2/2 = 2.05 \times 10^{-7} \text{ MKS units ,}$$

$$LI^2/2 = 2.50 \times 10^{-6} \text{ MKS units .}$$

In other words, a significant amount of energy is stored in the magnetic field, but it is not coupled into the wire between the concentric boxes.

Even if the ability to separate inductive and capacitive interactions were a tool limited only to ideal, experimentally controllable geometries, this tool would greatly simplify the design and understanding of experiments. When considering lumped element equivalent circuits of a particular experimental configuration, it is much simpler to deal only with resistors and capacitors than with resistors, capacitors, inductors, and transformers. If the lumped parameters in our equivalent circuit were time varying and nonlinear, the above result would be of even greater significance.

6.3 Collimation Experiment

From the equations in section 3, the effective area of the AURORA source was calculated to be 2209 in.² (1.425 m²) resulting from the 2-in. (2.54-cm) collimation data and 1346 in.² (0.868 m²) resulting from the 4-in. (10.2-cm) collimation data. This calculation implies that the AURORA source can be approximated by a disk whose radius is about 20 to 26 in. (50.8 to 66 cm).

7. CONCLUSIONS

The cathode follower, which was to be used to make a high impedance voltage measurement in the AURORA radiation environment, was not

successful because of TREE on the voltage probe and the cathode follower. When the capacitance of the probe was not adequately compensated because of TREE, the signal was severely distorted. In addition, the dose rate measured at the cathode follower was sufficient to indicate that the instrument could be severely upset.

Therefore, it was concluded that a compensated high voltage probe should be constructed to function in the AURORA radiation environment. Further, it was decided that the March test plan should be modified to specify that a greater amount of lead shielding be placed around the cathode followers so that the dose rate would be sufficiently reduced below the expected upset level.

The Compton diode data indicated that the Compton current was not successfully being measured by the instrument. Because of the collimation problems, it was decided that this method of measuring Compton current should not be pursued in the March test.

Finally, for some configurations, a simple coupling model which considers only direct interaction effects might be sufficient to predict responses. One must be extremely careful, however, in implementing such a model.

DISTRIBUTION

DEFENSE DOCUMENTATION CENTER
CAMERON STATION, BUILDING 5
ALEXANDRIA, VA 22314
ATTN DDC-TCA (12 COPIES)

COMMANDER
USA RSCH & STD GP (EUR)
BOX 65
FPO NEW YORK 09510
ATTN LTC JAMES M. KENNEDY, JR.
CHIEF, PHYSICS & MATH BRANCH

COMMANDER
US ARMY MATERIEL DEVELOPMENT
& READINESS COMMAND
5001 EISENHOWER AVENUE
ALEXANDRIA, VA 22333
ATTN DRXAM-TL, HQ TECH LIBRARY

COMMANDER
US ARMY ARMAMENT MATERIEL
READINESS COMMAND
ROCK ISLAND ARSENAL
ROCK ISLAND, IL 61201
ATTN DRSAR-ASF, FUZE & MUNITIONS
SPT DIV

COMMANDER
USA MISSILE & MUNITIONS CENTER
& SCHOOL
REDSTONE ARSENAL, AL 35809
ATTN ATSK-CTD-F

COMMANDER IN CHIEF
US EUROPEAN COMMAND, JCS
APO NEW YORK 09128
ATTN TECHNICAL LIBRARY

DIRECTOR
DEFENSE ADVANCED RSCH PROJ AGENCY
ARCHITECT BUILDING
1400 WILSON BLVD.
ARLINGTON, VA 22209
ATTN TECHNICAL LIBRARY
ATTN AD/E&PS GEORGE H. HALMEIER

DIRECTOR
DEFENSE CIVIL PREPAREDNESS AGENCY
ASSISTANT DIRECTOR FOR RESEARCH
WASHINGTON, DC 20301
ATTN TS(AED)
ATTN RE(EO)
ATTN ADMIN OFFICER

DEFENSE COMMUNICATION ENGINEER CENTER
1860 WIEHLE AVENUE
RESTON, VA 22090
ATTN CODE R720, C. STANSBERRY
ATTN CODE R400
ATTN CODE R124C, TECH LIB

DIRECTOR
DEFENSE COMMUNICATIONS AGENCY
WASHINGTON, DC 20305
ATTN CODE 540.5
ATTN CCTC/C672 FRANKLIN D. MOORE
ATTN CODE 930, MONTE I. BURGETT, FR

DIRECTOR
DEFENSE NUCLEAR AGENCY
WASHINGTON, DC 20305
ATTN RATN
ATTN DDST
ATTN RAEV
ATTN TITL TECH LIBRARY
ATTN TISI ARCHIVES
ATTN STVL

DIRECTOR OF DEFENSE RESEARCH
& ENGINEERING
DEPARTMENT OF DEFENSE
WASHINGTON, DC 20301
ATTN DD/S&SS

COMMANDER
FIELD COMMAND
DEFENSE NUCLEAR AGENCY
KIRTLAND AFB, NM 87115
ATTN FCPR
ATTN FCSM-F3/CDR SMITH

DIRECTOR
INTERSERVICE NUCLEAR WEAPONS SCHOOL
KIRTLAND AFB, NM 87115
ATTN DOCUMENT CONTROL

DIRECTOR
JOINT STRATEGIC TARGET PLANNING
STAFF, JCS
OFFUTT AFB
OMAHA, NB 68113
ATTN STINFO LIBRARY
ATTN JSAS
ATTN JPST

CHIEF
LIVERMORE DIVISION, FIELD COMMAND DNA
LAWRENCE LIVERMORE LABORATORY
P.O. BOX 808
LIVERMORE, CA 94550
ATTN FCPRL

NATIONAL COMMUNICATIONS SYSTEM
OFFICE OF THE MANAGER
WASHINGTON, DC 20305
ATTN NCS-TS, CHARLES D. BODSON

DIRECTOR
NATIONAL SECURITY AGENCY
FT. GEORGE G. MEADE, MD 20755
ATTN O. O. VAN GUNTEN, R-425
ATTN TECHNICAL LIBRARY

OJCS/J-6
THE PENTAGON
WASHINGTON, DC 20301
ATTN J-6, ESD-2

DIRECTOR
BMD ADVANCED TECH CTR
HUNTSVILLE OFFICE
PO BOX 1500
HUNTSVILLE, AL 35807
ATTN TECH LIB

COMMANDER
BMD SYSTEM COMMAND
P.O. BOX 1500
HUNTSVILLE, AL 35807
ATTN TECHNICAL LIBRARY
ATTN BDMSC-TEN, NOAH J. HURST

DEP CHIEF OF STAFF FOR RSCH DEV & ACQ
DEPARTMENT OF THE ARMY
WASHINGTON, DC 20310
ATTN DAMA-CSM-N, LTC G. OGDEN

COMMANDER
PICATINNY ARSENAL
DOVER, NJ 07801
ATTN SARPA-MD-D-B, EDWARD J. ARBER
ATTN PAUL HARRIS
ATTN SARPA-ND-D-C-2
ATTN SARPA-ND-W
ATTN SARPA-ND-DA-4
ATTN TECHNICAL LIBRARY
ATTN HYMAN POSTERNAK

COMMANDER
TRASANA
WHITE SANDS MISSILE RANGE, NM 88002
ATTN ATAA-EAC, FRANCIS N. WINANS

COMMANDER
US ARMY ARMOR CENTER
FORT KNOX, KY 40121
ATTN TECHNICAL LIBRARY

CHIEF
US ARMY COMMUNICATIONS SYSTEMS AGENCY
FORT MONMOUTH, NJ 07703
ATTN SCCM-AD-SV (LIBRARY)

COMMANDER
US ARMY COMPUTER SYSTEMS COMMAND
FORT BELVOIR, VA 22060
ATTN TECHNICAL LIBRARY

COMMANDER
US ARMY ELECTRONICS COMMAND
FORT MONMOUTH, NJ 07703
ATTN DRSEL-CT-HDK, ABRAHAM E. COHEN
ATTN DRSEL-CE, T. PREIFFER
ATTN DRSEL-TL-MD, GERHART K. GAULE
ATTN DRSEL-GG-TD, W. R. WERK
ATTN DRSEL-TL-ENV, HANS A. BOMKE
ATTN DRSEL-TL-ME, M. W. POMERANTZ
ATTN DRSEL-TL-IR, ROBERT A. FREIBERG
ATTN DRSEL-WL-D
ATTN DRSEL-NL-D

DIRECTOR
US ARMY MATERIAL SYS ANALYSIS ACTIVITY
ABERDEEN PROVING GROUND, MD 21005
ATTN DRXSY-CC, D. R. BARTHEL
ATTN TECHNICAL LIBRARY

COMMANDER
US ARMY MISSILE COMMAND
REDSTONE ARSENAL
HUNTSVILLE, AL 35809
ATTN DRSMI-RGF, HUGH GREEN
ATTN DRCPM-LCEX, HOWARD H. HENRIKSEN
ATTN DRCPM-PE-EA, WALLACE O. WAGNER
ATTN DRSMI-RGD, VICTOR W. RUWE

COMMANDER
US ARMY MOBILITY EQUIPMENT R & D CENTER
FORT BELVOIR, VA 22060
ATTN STSFB-MW, JOHN W. BOND, JR.
ATTN TECHNICAL LIBRARY

DISTRIBUTION (Cont'd)

COMMANDER
US ARMY NUCLEAR AGENCY
7500 BACKLICK ROAD
BUILDING 2073
SPRINGFIELD, VA 22150
ATTN TECH LIB
ATTN ATCN-W, LTC LEONARD A. SLUGA
ATTN COL DEVERILL

COMMANDER
US ARMY SECURITY AGENCY
ARLINGTON HALL STATION
4000 ARLINGTON BLVD
ARLINGTON, VA 22212
ATTN TECHNICAL LIBRARY

COMMANDER
US ARMY TEST AND EVALUATION COMMAND
ABERDEEN PROVING GROUND, MD 21005
ATTN DRSTE-EL, R. I. KOLCHIN
ATTN DRSTE-NB, R. R. GALASSO
ATTN TECHNICAL LIBRARY

COMMANDER
US ARMY TRAINING AND DOCTRINE COMMAND
FORT MONROE, VA 23651
ATTN TECH LIBRARY

COMMANDER
WHITE SANDS MISSILE RANGE
WHITE SANDS MISSILE RANGE, NM 88002
ATTN TECHNICAL LIBRARY
ATTN STEWS-TE-AN/A DE LA PAZ
ATTN STEWS-TE-NT,
MR. MARVIN P. SQUIRES

CHIEF OF NAVAL OPERATIONS
NAVY DEPARTMENT
WASHINGTON, DC 20350
ATTN CODE 604C3, ROBERT PIACESI

CHIEF OF NAVAL RESEARCH
DEPARTMENT OF THE NAVY
ARLINGTON, VA 22217
ATTN TECHNICAL LIBRARY
ATTN CODE 464, R. GRACEN JOINER
ATTN CODE 427
ATTN CODE 464, THOMAS P. QUINN

COMMANDER
NAVAL AIR SYSTEMS COMMAND
HEADQUARTERS
WASHINGTON, DC 21360
ATTN TECH LIB
ATTN AIR-350F, LCDR HUGO HART

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
HEADQUARTERS
WASHINGTON, DC 20360
ATTN TECH LIB
ATTN PME-117-T
ATTN PME 117-21
ATTN PME117-215A, GUNTER BRUNHART

COMMANDER
NAVAL INTELLIGENCE SUPPORT CENTER
4301 SUITLAND ROAD, BLDG 5
WASHINGTON, DC 20390
ATTN TECHNICAL LIBRARY

COMMANDER
NAVAL OCEAN SYSTEMS CENTER
SAN DIEGO, CA 92152
ATTN CODE 2200 1, VERNE E. HILDEBRAND
ATTN CODE 3100, E. E. MCCOWN
ATTN CODE 2400, S. W. LICHTMAN
ATTN TECHNICAL LIBRARY

SUPERINTENDENT
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CA 93940
ATTN CODE 2124, TECH RPTS LIBRARIAN

DIRECTOR
NAVAL RESEARCH LABORATORY
WASHINGTON, DC 20375
ATTN CODE 6631, JAMES C. RITTER
ATTN CODE 7706, JAY P. BORIS
ATTN CODE 4004, EMANUAL L. BRANCATO
ATTN CODE 2600, TECH LIB
ATTN CODE 2627, DORIS R. FOLEN
ATTN CODE 7701, JACK D. BROWN

COMMANDER
NAVAL SEA SYSTEMS COMMAND
NAVY DEPARTMENT
WASHINGTON, DC 20362
ATTN SEA-9931, RILEY B. LANE

COMMANDER
NAVAL SURFACE WEAPONS CENTER
WHITE OAK, SILVER SPRING, MD 20910
ATTN CODE 431, EDWIN B. DEAN
ATTN CODE WA501, NAVY NUC PRGMS OFF
ATTN CODE 431, EDWIN R. RATHBURN
ATTN CODE WA50, JOHN H. MALLOY
ATTN CODE 223, L. LIBELLO
ATTN CODE WR43

COMMANDER
NAVAL SURFACE WEAPONS CENTER
DAHLGREN LABORATORY
DAHLGREN, VA 22448
ATTN TECHNICAL LIBRARY
ATTN CODE FUR, ROBERT A. AMADORI

COMMANDING OFFICER
NAVAL WEAPONS EVALUATION FACILITY
KIRTLAND AIR FORCE BASE
ALBUQUERQUE, NM 87117
ATTN LAWRENCE R. OLIVER
ATTN CODE ATG, MR. STANLEY

COMMANDING OFFICER
NAVAL WEAPONS SUPPORT CENTER
CRANE, IN 47522
ATTN CODE 7024, JAMES RAMSEY
ATTN TECHNICAL LIBRARY

DIRECTOR
STRATEGIC SYSTEMS PROJECT OFFICE
NAVY DEPARTMENT
WASHINGTON, DC 20376
ATTN SP2701, JOHN W. PITSENBERGER
ATTN NSP-2342, RICHARD L. COLEMAN
ATTN NSP-43, TECH LIB
ATTN NSP-230, DAVID GOLD

COMMANDER
ADCOM/XPB
ENT AFB, CO 80912
ATTN XPQDQ, MAJ G. KUCH
ATTN XPDQ

AF GEOPHYSICS LABORATORY, AFSC
HANSCOM AFB, MA 01731
ATTN J. EMERY CORMIER

AF OFFICE OF SCIENTIFIC RESEARCH
BOLLING AFB, DC 20332
ATTN NP

AF WEAPONS LABORATORY, AFSC
KIRTLAND AFB, NM 87117
ATTN NT, JOHN DARRAH
ATTN DYX, DONALD C. WUNSCH
ATTN SAT
ATTN ELA
ATTN ELC
ATTN NT, CARL E. BAUM
ATTN EL
ATTN SAS
ATTN SUL
ATTN ELA, J. P. CASTILLO
ATTN EL (LIBRARY)

AFTAC
PATRICK AFB, FL 32925
ATTN TECH LIB

HEADQUARTERS
AIR FORCE SYSTEMS COMMAND
ANDREWS AFB
WASHINGTON, DC 20331
ATTN TECHNICAL LIBRARY

COMMANDER
AIR UNIVERSITY
MAXWELL AFB, AL 36112
ATTN AUL/LSE-70-250

COMMANDER
ASD
WPAFB, OH 45433
ATTN ENFTV
ATTN ASD-YH-EX

HEADQUARTERS
ELECTRONIC SYSTEMS DIVISION/XR
HANSCOM AFB, MA 01731
ATTN XRT, LTC JOHN M. JASINSKI

HEADQUARTERS
ELECTRONIC SYSTEMS DIVISION/YS
HANSCOM AFB, MA 01731
ATTN YSEV

HEADQUARTERS
ELECTRONIC SYSTEMS DIVISION/YW
HANSCOM AFB, MA 01731
ATTN YWEI

HEADQUARTERS
ELECTRONIC SYSTEMS DIVISION, (AFSC)
HANSCOM AFB, MA 01731
ATTN TECHNICAL LIBRARY

COMMANDER
FOREIGN TECHNOLOGY DIVISION, AFSC
WRIGHT-PATTERSON AFB, OH 45433
ATTN NICD LIBRARY
ATTN ETRP

DISTRIBUTION (Cont'd)

HQ USAF/RD
WASHINGTON, DC 20330
ATTN RDQSM

COMMANDER
OGDEN AIR LOGISTICS CENTER
HILL AFB, UT 84401
ATTN TECH LIB
ATTN MMEWM, ROBERT JOFFS

SAMSO/DY
POST OFFICE BOX 92960
WORLDWAY POSTAL CENTER
LOS ANGELES, CA 90009
(TECHNOLOGY)
ATTN DYS, MAJ LARRY A. DARDA

SAMSO/MN
NORTON AFB, CA 92409
(MINUTEMAN)
ATTN MNH, MAJ M. BARAN
ATTN MNH, CAPT B. STEWART

SAMSO/SK
POST OFFICE BOX 92960
WORLDWAY POSTAL CENTER
LOS ANGELES, CA 90009
(SPACE COMM SYSTEMS)
ATTN SKF, PETER H. STADLER

COMMANDER IN CHIEF
STRATEGIC AIR COMMAND
OFFUTT AFB, NE 68113
ATTN NRI-STINFO LIBRARY
ATTN DEF, FRANK N. BOUSHA
ATTN XEFS, MAJ BRIAN STEPHAN

DIVISION OF MILITARY APPLICATION
US ENERGY RSCH & DEV ADMIN
WASHINGTON, DC 20545
ATTN TECHNICAL LIBRARY

EG&G, INC.
LOS ALAMOS DIVISION
PO BOX 809
LOS ALAMOS, NM 85544
ATTN TECH LIB

UNIVERSITY OF CALIFORNIA
LAWRENCE LIVERMORE LABORATORY
P.O. BOX 808
LIVERMORE, CA 94550
ATTN E. K. MILLER, L-156
ATTN FREDERICK R. KOVAR, L-31
ATTN HANS KRUGER, L-96
ATTN L-153, ROBERT A. ANDERSON
ATTN IELAND C. LOQUIST, L-154
ATTN TERRY R. DONICH, L-96
ATTN TECH INFO DEPT, L-3
ATTN WILLIAM J. HOGAN, L-531
ATTN DONALD J. MEEKER, L-545
ATTN LOUIS F. WOUTERS, L-48

LOS ALAMOS SCIENTIFIC LABORATORY
P.O. BOX 1663
LOS ALAMOS, NM 87545
ATTN REPORTS LIBRARY
ATTN ARTHUR FREED
ATTN RICHARD L. WAKEFIELD

SANDIA LABORATORIES
PO BOX 5800
ALBUQUERQUE, NM 87115
ATTN ORD 9353, R. L. PARKER
ATTN 3141 SANDIA RPT COLL
ATTN ELMER F. HARTMAN
ATTN GERALD W. BARR, 1114
ATTN DIV 5231, JAMES H. RENKEN

UNION CARBIDE CORPORATION
HOLIFIELD NATIONAL LABORATORY
P.O. BOX X
OAK RIDGE, TN 37830
ATTN PAUL R. BARNES
ATTN TECH LIBRARY

AEROSPACE CORPORATION
PO BOX 92957
LOS ANGELES, CA 90009
ATTN C. B. PEARLSTON
ATTN IRVING M. GARFUNKEL
ATTN JULIAN REINHEIMER
ATTN LIBRARY
ATTN S. P. BOWER
ATTN NORMAN D. STOCKWELL
ATTN BAL KRISHAN

BATTELLE MEMORIAL INSTITUTE
505 KING AVENUE
COLUMBUS, OH 43201
ATTN TECHNICAL LIBRARY

BDM CORPORATION, THE
7915 JONES BRANCH DRIVE
MCLEAN, VA 22101
ATTN T. H. NEIGHBORS
ATTN TECHNICAL LIBRARY

BDM CORPORATION, THE
PO BOX 9274
ALBUQUERQUE INTERNATIONAL
ALBUQUERQUE, NM 87119
ATTN TECH LIB

BOEING COMPANY, THE
PO BOX 3707
SEATTLE, WA 98124
ATTN HOWARD W. WICKLEIN, MS 17-11
ATTN D. E. ISBELL
ATTN DAVID DYE, MS 87-75
ATTN DAVID KEMLE
ATTN AEROSPACE LIBRARY

BOOZ-ALLEN AND HAMILTON, INC.
106 APPLE STREET
TINTON FALLS, NJ 07724
ATTN TECH LIB
ATTN R. J. CHRISNER

BROWN ENGINEERING COMPANY, INC.
CUMMINGS RESEARCH PARK
HUNTSVILLE, AL 35807
ATTN JOHN M. MCSWAIN, MS 18
ATTN TECH LIB, MS12, P. SHELTON

BURROUGHS CORPORATION
FEDERAL AND SPECIAL SYSTEMS GROUP
CENTRAL AVE AND ROUTE 252
PO BOX 517
PAOLI, PA 19301
ATTN ANGELO J. MAURIELLO
ATTN TECH LIB

CALSPAN CORPORATION
PO BOX 235
BUFFALO, NY 14221
ATTN TECH LIBRARY

CHARLES STARK DRAPER LABORATORY INC.
555 TECHNOLOGY SQUARE
CAMBRIDGE, MA 02139
ATTN TECH LIB
ATTN KENNETH FERTIG

COMPUTER SCIENCES CORPORATION
P.O. BOX 530
6565 ARLINGTON BLVD
FALLS CHURCH, VA 22046
ATTN TECH LIB

COMPUTER SCIENCES CORPORATION
201 LA VETA DRIVE, NE
ALBUQUERQUE, NM 87108
ATTN RICHARD H. DICKHAUT
ATTN ALVIN SCHIFF

CONTROL DATA CORPORATION
P.O. BOX 0
MINNEAPOLIS, MN 55440
ATTN JACK MEEHAN

CUTLER-HAMMER, INC.
AIL DIVISION
COMAC ROAD
DEER PARK, NY 11729
ATTN CENTRAL TECH FILES, ANN ANTHONY

DIKEWOOD INDUSTRIES, THE
1009 BRADBURY DRIVE, SE
UNIVERSITY RESEARCH PARK
ALBUQUERQUE, NM 87106
ATTN TECH LIB
ATTN L. WAYNE DAVIS
ATTN K. LEE

EG&G, INC.
ALBUQUERQUE DIVISION
PO BOX 10218
ALBUQUERQUE, NM 87114
ATTN TECHNICAL LIBRARY

ESL, INC.
495 JAVA DRIVE
SUNNYVALE, CA 94086
ATTN TECHNICAL LIBRARY

EXP AND MATH PHYSICS CONSULTANTS
P. O. BOX 66331
LOS ANGELES, CA 90066
ATTN THOMAS M. JORDAN

FORD AEROSPACE & COMMUNICATIONS OPERATIONS
FORD & JAMBOREE ROADS
NEWPORT BEACH, CA 92663
ATTN TECH INFO SECTION
ATTN KEN C. ATTINGER
ATTN E. R. PONCELET, JR.

GARRETT CORPORATION
PO BOX 92248, 9851 SEPULVEDA BLVD
LOS ANGELES, CA 90009
ATTN ROBT. WEIR, DEPT. 93-9
ATTN TECH LIB

DISTRIBUTION (Cont'd)

GENERAL ELECTRIC COMPANY
TEMPO-CENTER FOR ADVANCED STUDIES
816 STATE STREET (PO DRAWER QQ)
SANTA BARBARA, CA 93102
ATTN DASIAC
ATTN ROYDEN R. RUTHERFORD

GENERAL ELECTRIC COMPANY-TEMPO
ATTN: DASIAC
C/O DEFENSE NUCLEAR AGENCY
WASHINGTON, DC 20305
ATTN WILLIAM ALFONTE

GENERAL RESEARCH CORPORATION
P.O. BOX 3587
SANTA BARBARA, CA 93105
ATTN TECH INFO OFFICE
ATTN JOHN ISE, JR.

GEORGIA INSTITUTE OF TECHNOLOGY
GEORGIA TECH RESEARCH INSTITUTE
ATLANTA, GA 30332
ATTN R. CURRY

GTE SYLVANIA, INC.
ELECTRONICS SYSTEMS GRP-EASTERN DIV
77 A STREET
NEEDHAM, MA 02194
ATTN CHARLES A. THORNHILL, LIBRARIAN
ATTN LEONARD L. BLAISDELL
ATTN JAMES A. WALDON

GTE SYLVANIA, INC.
189 B STREET
NEEDHAM HEIGHTS, MA 02194
ATTN CHARLES H. RAMSBOTTOM
ATTN A S M DEPT, S. E. PERLMAN
ATTN DAVID P. FLOOD
ATTN COMM SYST DIV, EMIL P. MOTCHOK
ATTN HERBERT A. ULLMAN
ATTN H & V GROUP, MARIO A. NUREFORA

HARRIS CORPORATION
HARRIS SEMICONDUCTOR DIVISION
P.O. BOX 883
MELBOURNE, FL 32901
ATTN C. F. DAVIS, MS 17-220
ATTN WAYNE E. ABARE, MS 16-111
ATTN T. CLARK, MS 4040
ATTN TECH LIB
ATTN CHARLES DENTON, JR., MS 1-500

HONEYWELL INCORPORATED
AVIONICS DIVISION
13350 US HIGHWAY 19 NORTH
ST. PETERSBURG, FL 33733
ATTN TECHNICAL LIBRARY
ATTN HARRISON H. NOBLE, MS 725-5A

IIT RESEARCH INSTITUTE
10 WEST 35TH STREET
CHICAGO, IL 60616
ATTN TECHNICAL LIBRARY
ATTN IRVING N. MINDEL
ATTN JACK E. BRIDGES

INSTITUTE FOR DEFENSE ANALYSES
400 ARMY-NAVY DRIVE
ARLINGTON, VA 22202
ATTN IDA, LIBRARIAN, RUTH S. SMITH

IRT CORPORATION
P.O. BOX 81087
SAN DIEGO, CA 92138
ATTN R. L. MERTZ
ATTN TECHNICAL LIBRARY
ATTN MDC

JAYCOR
1401 CAMINO DEL MAR
DEL MAR, CA 92014
ATTN ERIC P. WENAAS
ATTN RALPH H. STAHL

JAYCOR
205 S WHITTING STREET, SUITE 500
ALEXANDRIA, VA 22304
ATTN CATHERINE TURESKO
ATTN ROBERT SULLIVAN

JOHNS HOPKINS UNIVERSITY
APPLIED PHYSICS LABORATORY
JOHNS HOPKINS ROAD
LAUREL, MD 20810
ATTN TECH LIB

KAMAN SCIENCES CORPORATION
P.O. BOX 7463
COLORADO SPRINGS, CO 80933
ATTN LIBRARY
ATTN J. R. CURRY
ATTN DONALD H. BRYCE
ATTN ALBERT P. BRIDGES
ATTN W. FOSTER RICH
ATTN WALTER E. WARE
ATTN JERRY I. LUBELL

LITTON SYSTEMS, INC.
AMECOM DIVISION
5115 CALVERT ROAD
COLLEGE PARK, MD 20740
ATTN TECH LIB

LOCKHEED MISSILES AND SPACE
COMPANY, INC.
P.O. BOX 504
SUNNYVALE, CA 94088
ATTN DEPT 85-85, SAMUEL I. TAIMUTY
ATTN G. F. HEATH, D/81-14
ATTN BENJAMIN T. KIMURA, DEPT 81-14,
ATTN PHILIP J. HART, DEPT 81-14
ATTN KEVIN MCCARTHY 0-85-71
ATTN EDWIN A. SMITH, DEPT 85-85
ATTN TECHNICAL LIBRARY
ATTN L-365 DEPT 81-20
ATTN ROSSI, DEPT 81-64

M.I.T. LINCOLN LABORATORY
P.O. BOX 73
LEXINGTON, MA 02173
ATTN LEONA LOUGHLIN, LIBRARIAN

MARTIN MARIETTA CORPORATION
DENVER DIVISION
PO BOX 179
DENVER, CO 80201
ATTN RESEARCH LIB, 6617, J. R. MCKEE
ATTN BEN T. GRAHAM, MS PO-454

MAXWELL LABORATORIES, INC.
9244 BALBOA AVENUE
SAN DIEGO, CA 92123
ATTN TECH LIB
ATTN VICTOR FARGO

MISSION RESEARCH CORPORATION
735 STATE STREET
SANTA BARBARA, CA 93101
ATTN TECH LIB
ATTN CONRAD L. LONGMIRE
ATTN WILLIAM C. HART
ATTN DANIEL F. HIGGINS

MISSION RESEARCH CORPORATION
P.O. BOX 8693, STATION C
ALBUQUERQUE, NM 87108
ATTN LARRY D. SCOTT
ATTN TECH LIB
ATTN DAVID E. MEREWETHER

MISSION RESEARCH CORPORATION-SAN DIEGO
P.O. BOX 1209
LA JOLLA, CA 92038
ATTN V. A. J. VAN LINT

MITRE CORPORATION, THE
P.O. BOX 208
BEDFORD, MA 01730
ATTN LIBRARY
ATTN THEODORE JARVIS
ATTN M. F. FITZGERALD

NORTHROP CORPORATION
ELECTRONIC DIVISION
1 RESEARCH PARK
PALOS VERDES PENINSULA, CA 90274
ATTN TECH LIB

NORTHROP CORPORATION
NORTHROP RESEARCH AND TECHNOLOGY CENTER
3401 WEST BROADWAY
HAWTHORNE, CA 92050
ATTN LIBRARY
ATTN DAVID N. POCOCK

NORTHROP CORPORATION
ELECTRONIC DIVISION
2301 WEST 120TH STREET
HAWTHORNE, CA 90250
ATTN VINCENT R. DEMARTINO
ATTN JOHN M. REYNOLDS

PHYSICS INTERNATIONAL COMPANY
2700 MERCED STREET
SAN LEANDRO, CA 94577
ATTN TECH LIB
ATTN JOHN H. HUNTINGTON

PULSAR ASSOCIATES, INC.
7911 HERSCHEL AVENUE
LA JOLLA, CA 92037
ATTN CARLETON H. JONES

R & D ASSOCIATES
PO BOX 9695
MARINA DEL REY, CA 90291
ATTN TECHNICAL LIBRARY
ATTN S. CLAY ROGERS
ATTN WILLIAM R. GRAHAM, JR.
ATTN LEONARD SCHLESSINGER
ATTN CHARLES MO
ATTN RICHARD R. SCHAEFER
ATTN WILLIAM J. KARZAS
ATTN GERARD K. SCHLEGEL

DISTRIBUTION (Cont'd)

RCA CORPORATION
 GOVERNMENT SYSTEMS DIVISION
 ASTRO ELECTRONICS
 PO BOX 800, LOCUST CORNER
 EAST WINDSOR TOWNSHIP
 PRINCETON, NJ 08540
 ATTN TECH LIB
 ATTN GEORGE J. BRUCKER

ROCKWELL INTERNATIONAL CORPORATION
 P.O. BOX 3105
 ANAHEIM, CA 92803
 ATTN N. J. RUDIE, FA53
 ATTN J. L. MONROE, DEPT 243-027, DIV 031
 ATTN L. APODACA, FA53
 ATTN K. F. HULL
 ATTN TECHNICAL LIBRARY
 ATTN JAMES E. BELL, HA10
 ATTN DONALD J. STEVENS, FA70

SCIENCE APPLICATIONS, INC.
 PO BOX 2351
 LA JOLLA, CA 92038
 ATTN TECHNICAL LIBRARY
 ATTN LEWIS M. LINSON
 ATTN R. PARKINSON

SCIENCE APPLICATIONS, INC.
 HUNTSVILLE DIVISION
 2109 W. CLINTON AVENUE
 SUITE 700
 HUNTSVILLE, AL 35805
 ATTN NOEL R. BYRN
 ATTN TECH LIB

SCIENCE APPLICATIONS, INC.
 PO BOX 3507
 ALBUQUERQUE, NM 87110
 ATTN RICHARD L. KNIGHT
 ATTN J. ROGER HILL

SCIENCE APPLICATIONS, INC.
 8400 WESTPARK DRIVE
 MCLEAN, VA 22101
 ATTN WILLIAM L. CHADSEY

SIMULATION PHYSICS, INC.
 P.O. BOX D
 BEDFORD, MA 01730
 ATTN JOHN R. UGLUM

STANFORD RESEARCH INSTITUTE
 3980 EL CAMINO REAL
 PALO ALTO, CA 94306
 ATTN MR. PHILIP DOLAN
 ATTN GEORGE CARPENTER
 ATTN ARTHUR LEE WHITSON
 ATTN MEL BERNSTEIN

SYSTEMS, SCIENCE AND SOFTWARE
 P.O. BOX 4803
 HAYWARD, CA 94540
 ATTN TECH LIB

SYSTEMS, SCIENCE AND SOFTWARE, INC.
 PO BOX 1620
 LA JOLLA, CA 92038
 ATTN TECHNICAL LIBRARY

TEXAS INSTRUMENTS, INC.
 P.O. BOX 6015
 DALLAS, TX 75222
 ATTN TECH LIB
 ATTN DONALD J. MANUS, MS 72

TRW DEFENSE & SPACE SYS GROUP
 ONE SPACE PARK
 REDONDO BEACH, CA 90278
 ATTN TECH INFO CENTER/S-1930
 ATTN ROBERT M. WEBB, MS R1-1150
 ATTN AARON H. NAREVSKY, R1-2144

TRW DEFENSE & SPACE SYS GROUP
 SAN BERNARDINO OPERATIONS
 PO BOX 1310
 SAN BERNARDINO, CA 92402
 ATTN F. B. FAY

VECTOR RESEARCH ASSOCIATES
 735 STATE STREET
 SANTA BARBARA, CA 93101
 ATTN W. A. RADASKY

HARRY DIAMOND LABORATORIES
 ATTN DANIEL, CHARLES D., JR., MG,
 COMMANDING GENERAL (ERADCOM)
 ATTN RAMSDEN, JOHN J., LTC, COMMANDER/
 FLYER, I.N./LANDIS, P.E./
 SOMMER, H./OSWALD, R. B.
 ATTN CARTER, W.W., DR., TECHNICAL
 DIRECTOR/MARCUS, S.M.
 ATTN KIMMEL, S., PAO
 ATTN CHIEF, 0021
 ATTN CHIEF, 0022
 ATTN CHIEF, LAB 100
 ATTN CHIEF, LAB 200
 ATTN CHIEF, LAB 300
 ATTN CHIEF, LAB 400
 ATTN CHIEF, LAB 500
 ATTN CHIEF, LAB 600
 ATTN CHIEF, DIV 700
 ATTN CHIEF, DIV 80
 ATTN CHIEF, LAB 900
 ATTN CHIEF, LAB 1000
 ATTN RECORD COPY, BR 041
 ATTN HDL LIBRARY (5 COPIES)
 ATTN CHAIRMAN, EDITORIAL COMMITTEE
 ATTN CHIEF, 047
 ATTN TECH REPORTS, 013
 ATTN PATENT LAW BRANCH, 071
 ATTN GIDEP OFFICE, 741
 ATTN LANHAM, C., 0021
 ATTN WONG, R., 1000
 ATTN GORNAK, G., 1020
 ATTN AGEY, F. J., 1000
 ATTN DANDO, J., 1040
 ATTN BELFUSS, J. W., 1010
 ATTN PFEFFER, R., 1010
 ATTN GRAY, R. F., 1000
 ATTN BOMBARDT, J., 1030
 ATTN SWETON, J. F., 1000
 ATTN WYATT, W. T., 1000
 ATTN WIMENITZ, F. N., 0024
 ATTN MILETTA, J. R., 1010
 ATTN TOMPKINS, J. E., 230
 ATTN ROSADO, J. A., 230
 ATTN MERKEL, G., 1030 (5 COPIES)
 ATTN SPOHN, D., 1030 (5 COPIES)

BEST AVAILABLE COPY