

AD-A046 491

ARMY AVIATION ENGINEERING FLIGHT ACTIVITY EDWARDS AF--ETC F/G 1/4
FLIGHT EVALUATION ROSEMOUNT LOW-RANGE ORTHOGONAL AIRSPEED SYSTE--ETC(U)
MAR 77 W Y ABBOTT, J R GUIN

UNCLASSIFIED

USAAEFA-75-17-3


NL

| OF |
AD
A046491



END
DATE
FILMED
12-77

DDC



AD A 0 46491



14 USAAEFA [REDACTED] -75-17-3

5

6

**FLIGHT EVALUATION
ROSEMOUNT LOW-RANGE ORTHOGONAL
AIRSPEED SYSTEM WITH 853G SENSOR.**

9 FINAL REPORT

10

WILLIAM Y. ABBOTT
PROJECT OFFICER/ENGINEER

JERRY R. GUIN
MAJ, FA
US ARMY
PROJECT PILOT

11 MARCH 1977

12 26p.

DDC
RECEIVED
NOV 16 1977
A

Approved for public release; distribution unlimited.

UNITED STATES ARMY AVIATION ENGINEERING FLIGHT ACTIVITY
EDWARDS AIR FORCE BASE, CALIFORNIA 93523

AD NO. _____
DDC FILE COPY

409 025

DISCLAIMER NOTICE

The findings of this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return it to the originator.

TRADE NAMES

The use of trade names in this report does not constitute an official endorsement or approval of the use of the commercial hardware and software.

ACCESSION FOR	
NTIS	White Section ☒
DDO	Buff Section ☐
UNANNOUNCED	☐
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODE	
Dist.	AVAIL. AND/OR SPECIM.
A	

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER USAAEFA PROJECT NO. 75-17-3	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) FLIGHT EVALUATION ROSEMOUNT LOW RANGE ORTHOGONAL AIRSPEED SYSTEM WITH 853G SENSOR		5. TYPE OF REPORT & PERIOD COVERED FINAL REPORT August 1976
7. AUTHOR(s) MAJOR JERRY R. GUIN WILLIAM Y. ABBOTT		6. PERFORMING ORG. REPORT NUMBER USAAEFA PROJECT NO. 75-17-3
9. PERFORMING ORGANIZATION NAME AND ADDRESS US ARMY AVIATION ENGINEERING FLIGHT ACTIVITY EDWARDS AIR FORCE BASE, CALIFORNIA 93523		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS US ARMY AVIATION ENGINEERING FLIGHT ACTIVITY EDWARDS AIR FORCE BASE, CALIFORNIA 93523		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE MARCH 1977
		13. NUMBER OF PAGES 27
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Rosemount low-range orthogonal airspeed system Model 853G sensor		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The Rosemount low range orthogonal airspeed system with a Model 853G sensor installed above the main rotor was evaluated by the United States Army Aviation Engineering Flight Activity at Edwards Air Force Base, California, in August 1976. The system repeatably measured airspeed in the direction of the relative wind. However, the system had excessive perturbations in the axis perpendicular to relative wind, which must be corrected prior to the system becoming operational.		

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	
Background	2
Test Objectives	2
Description	2
Test Scope	3
Test Methodology	3
RESULTS AND DISCUSSION	
General	4
System Performance in Forward and Rearward Flight	4
System Performance in Sideward Flight	4
Sideslip Effects	7
Cockpit Display	7
Reliability and Maintainability	7
Additional System Features	7
CONCLUSIONS	9
RECOMMENDATIONS	10
APPENDIXES	
A. References	11
B. System Description and Theory of Operation.	12
C. Test Instrumentation	18
D. Test Data	19
DISTRIBUTION	

INTRODUCTION

BACKGROUND

1. Standard aircraft pitot-static airspeed systems are inadequate for low forward airspeed (below 40 knots) sensing in helicopters, and are inoperable in crosswind or downwind flight conditions. The United States Army Aviation Engineering Flight Activity (USAAEFA) conducted tests on several low-speed omnidirectional systems during USAAEFA Project No. 71-30 (refs 1 through 6, app A). The United States Army Avionics Laboratory, Fort Monmouth, New Jersey, is currently developing a lightweight doppler navigation system (LDNS) which requires inputs from an airspeed system that will operate reliably in the low-speed nap-of-the-earth (NOE) flight regime. In May 1975, the United States Army Aviation Systems Command (AVSCOM) directed USAAEFA to evaluate two systems for the Avionics Laboratory (ref 7) and a test plan was prepared by USAAEFA (ref 8). Subsequently, the Avionics Laboratory requested that two additional systems be tested. One of those systems was the Rosemount low range orthogonal airspeed system with a Model 853G sensor.

TEST OBJECTIVES

2. The objective of this evaluation was to define the operating characteristics of the Rosemount low-airspeed system in an NOE flight environment for possible use with the LDNS. Specific objectives were to define:

- a. Airspeed range in which system is effective.
- b. Impact of flight direction on accuracy.
- c. Optimal display characteristics.

DESCRIPTION

3. The system tested was manufactured by Rosemount, Inc. of Minneapolis, Minnesota. It consisted of an airspeed and altitude sensor, an airspeed transducer, an altitude transducer, and an airspeed and direction indicator. A detailed description of the system is provided in appendix B.

4. The sensor is a hemispherically capped cylindrical tube approximately 3/4 inch in diameter and 15 inches long. It senses differential pressures in the longitudinal and lateral axes. It was mounted vertically on a stationary platform which was attached to a standpipe placed inside the hollow main rotor shaft. The installation

placed the sensor above the main rotor plane of rotation. The aircraft used in this evaluation was an NUH-1M helicopter, SN 63-8684. A detailed description of the aircraft is contained in the operator's manual (ref 9, app A).

TEST SCOPE

5. The Rosemount system was evaluated in August 1976 at Edwards Air Force Base, California. A total of 3 hours were flown, of which 1.8 hours were productive. Flight conditions were within the limitations imposed by the operator's manual and the safety-of-flight release (ref 10, app A). Testing was limited to 40 knots at various azimuths. Angle of attack effects were not investigated.

TEST METHODOLOGY

6. The Rosemount system was tested to 40 knots near the ground, using the calibrated pace vehicle technique. Wind speed and direction were measured and added vectorially to the pace vehicle readings to obtain aircraft true airspeed. The true airspeed was then converted to calibrated airspeed for a direct comparison with Rosemount airspeed outputs.

7. Previous testing on a similar Rosemount system (ref 5, app A) indicated that optimal results would be obtained by mounting the sensor on a relatively long (18 inches) adaptor above the main rotor mast. This was the only configuration evaluated during this test.

RESULTS AND DISCUSSION

GENERAL

8. The performance of the Rosemount system in all cardinal azimuths in the horizontal plane was similar. The system measured forward, rearward, and lateral airspeeds adequately in the direction of the relative wind, but showed undesirable perturbations in the axis perpendicular to the relative wind. The sensor was mounted above the main rotor throughout the evaluation. All tests were flown at approximately 7000 pounds gross weight, mid center of gravity, and main rotor speed of 324 rpm.

SYSTEM PERFORMANCE IN FORWARD AND REARWARD FLIGHT

9. The performance of the Rosemount system in forward and rearward flight is shown in figure 1, appendix D. The longitudinal airspeed output was essentially linear, steady, and repeatable throughout the range of the transducer capsule, ± 40 knots. Position error for the 50-foot skid height data was typically less than 4 knots, and could be nearly eliminated by a slight gain adjustment in the transducer output circuitry.

10. The lateral airspeed output of the system during forward and rearward flight was erratic, with random perturbations as great as 24 knots. This phenomenon was consistent throughout the test.

SYSTEM PERFORMANCE IN SIDEWARD FLIGHT

11. The system characteristics in sideward flight were similar to those during forward and rearward flight, as shown in figures 1 and 2, appendix D. The lateral airspeed output was essentially linear, steady, and repeatable throughout the range of the transducer capsule (± 40 knots). The lateral position error in sideward flight was typically less than 4 knots and could be nearly eliminated by a slight gain adjustment. Also, similar to longitudinal flight, the off-axis output (longitudinal in the case of lateral flight) displayed erratic behavior, which should be corrected.

12. The perturbations noted in the flight test data appear to occur when a high proportion of the flow is tangential to the pressure ports of a given axis. A time history of this phenomenon is shown in figure A. In response to inquiries by USAAEFA, Rosemount conducted additional wind tunnel tests on a system similar to the model tested by USAAEFA. Sample results are shown in figure B. Wind tunnel data of the off-axis perturbations show trends similar to flight test data, though of a much smaller magnitude. Viewing figures A and B together, it can be concluded that the greater tangential perturbations in the flight test data are caused by turbulence. The off-axis perturbations must be corrected before the





Figure A. Rosemount System Perturbations During Forward Flight.




Figure B. Rosemount System Perturbations During Wind Tunnel Testing.

system can be used either as part of a navigation system or as an engineering flight test reference. During the wind tunnel testing, Rosemount experimented with different diameters and lengths of tubing to vary the damping characteristics of the system. Some success was noted in the reduction of the perturbations and in the increase of off-axis accuracy.

SIDESLIP EFFECTS

13. The effects of sideslip on longitudinal and lateral system error are shown in figures 3 and 4, appendix D. Longitudinal errors for 10, 17, and 30 KCAS are typically 5 knots, which is consistent with the position error shown in figure 1. At small angles of sideslip, the longitudinal airspeed component showed no fluctuations. Larger angles of sideslip show the onset of the perturbation phenomenon noted in the off-axis during longitudinal and lateral flight. The lateral error data typically show considerable perturbation at small sideslips and greater stability with increasing sideslip.

COCKPIT DISPLAY

14. The indicator supplied with the system was the cross-pointer type (fig. 1, app B), and provided adequate qualitative information to the pilot as to the direction of the relative wind. The resolution of the indicator (approximately 1/8 inch/10 knots) was inadequate to easily obtain airspeed magnitude. A display showing the resultant airspeed should be incorporated.

RELIABILITY AND MAINTAINABILITY

15. The sensor operated reliably throughout the test. However, the small sensor ports could be subject to clogging during operational flight. The system should be tested in the field to evaluate performance degradation caused by debris, and to evaluate the sensor device capability.

16. A diaphragm in an airspeed transducer capsule ruptured before the first flight, and the pressure altitude and rate-of-climb elements of the system were inoperable during the test. No cause was determined for either failure.

ADDITIONAL SYSTEM FEATURES

17. The pressure altitude and rate-of-climb outputs were not tested; however, several features of the system should be noted. Airspeed is measured with the aircraft axes as a reference, and rate-of-climb is computed with the earth axis as a reference. If this system is to be used as a navigation input, the difference in

reference axes must be considered. Additionally, rate of climb is obtained by differentiating pressure altitude, and cannot be used directly as a vertical airspeed component because airspeed output in the horizontal plane is calibrated airspeed. If the Rosemount system is to be used in the LDNS, provisions should be made to convert the system airspeed outputs to true airspeed.

CONCLUSIONS

18. The Rosemount low-airspeed system with the sensor mounted above the main rotor repeatably measured airspeed in the direction of the relative wind to the limits tested (paras 9 and 11).
19. Excessive perturbation occurs in the system output for the axis perpendicular to the relative wind (para 12).
20. The cockpit indicator, while giving adequate relative wind direction information, did not have adequate resolution to easily determine resultant airspeed (para 14).

RECOMMENDATIONS

21. The perturbations and inaccuracies in the axis of tangential flow must be corrected (para 11).
22. A display should be added to the cockpit indicator showing the resultant airspeed (para 14).
23. Additional field testing should be conducted to evaluate performance degradation caused by debris and to evaluate the sensor device capability (para 15).
24. Provisions should be made for the system output to be in true airspeed for possible use with the LDNS (para 17).

APPENDIX A. REFERENCES

1. Final Report I, US Army Aviation Systems Test Activity (USAASTA), Project No. 71-30, *Flight Evaluation, Elliott Low-Airspeed System*, September 1972.
2. Final Report II, USAASTA, Project No. 71-30, *Flight Evaluation, Aeroflex True Airspeed Vector System, Low-Airspeed System*, March 1973.
3. Final Report III, USAASTA, Project No. 71-30, *Flight Evaluation, Pacer Systems, Inc., LORAS II Low-Airspeed System*, March 1974.
4. Final Report IV, USAASTA, Project No. 71-30, *Flight Evaluation, J-TEC Airspeed System, Low-Airspeed Sensor*, April 1974.
5. Final Report V, USAAEFA, Project No. 71-30, *Flight Evaluation, Rosemount Orthogonal Low-Airspeed System, Low-Airspeed Sensor*, November 1974.
6. Final Report VI, USAAEFA, Project No. 71-30, *Flight Evaluation, Elliott Dual-Axis Low-Airspeed System, LASSIE II, Low-Airspeed Sensor*, September 1975.
7. Letter, AVSCOM, AMSAV-EQI, 12 May 1975, subject: AVSCOM Test Request Number 75-17, *Flight Evaluation of Two Low-Airspeed Sensing Systems*.
8. Test Plan, USAAEFA, Project No. 75-17, *Flight Evaluation of Two Low-Airspeed Sensing Systems*, September 1975.
9. Technical Manual, TM 55-1520-220-10, *Operator's Manual, Army Model UH-1C/M*, November 1968 with changes 1 through 4.
10. Letter, AVSCOM, DRSAB-EQA, 6 May 1976, subject: *Safety-of-Flight Release for Rosemount Probe Installed on UH-1M*.

APPENDIX B. SYSTEM DESCRIPTION AND THEORY OF OPERATION

GENERAL

1. The Rosemount orthogonal airspeed system consists of a Model 853G orthogonal airspeed sensor, a Model 542AM-1 air data transducer, a Model 1241 barometer altitude transducer, and an indicator. The system components are shown in photo 1.

Sensor

2. The 853G airspeed sensor is a hemispherically capped cylindrical tube approximately 3/4 inch in diameter and 15 inches long, and is shown in detail in figure 1. In the test installation, the sensor was mounted vertically on an 18-inch adaptor atop a nonrotating platform above the main rotor hub, as illustrated in figure 2. The sensor has four sets of four pressure ports drilled into the surface of the tube, gaining access to the four chambers within the tube. Two sets of ports are aligned in the fore-aft direction, and two in the left-right direction. An additional set of ports is located below the orthogonal ports for sensing static pressure, which is used to determine pressure altitude and vertical velocity.

3. The sensor is heated for deicing and to vaporize surface and internal moisture. The heater uses 150 watts in still air and 275 watts in flight. Heaters are available to operate on either 28 VDC or 115 VAC.

Air Data Transducer

4. The function of the 542AM-1 transducer is to convert the differential pressure from the sensor to a voltage, which may be interpreted as airspeed by an indicator or other instrumentation. Inside the unit is a fore-aft capsule and a right-left capsule. Pressures from the sensor are input on opposite sides of the capsule, moving a sensing diaphragm stretched between fixed capacitor plates. The differential capacitance between the sensing diaphragm and the capacitor plates is converted electronically to a high-level DC voltage signal (linear with pressure) by signal conditioning circuitry. Rosemount currently makes three different capsules: ± 40 knots, ± 100 knots, and ± 120 knots. The system tested used a ± 40 -knot capsule for both axes.




Photo 1. Rosemount Orthogonal Airspeed System.




Figure 1. Model 853G Sensor.




Figure 2. Sensor Installation

5. Dynamic pressure (q) attributable to longitudinal and lateral velocity is proportional to the pressure differential along those axes.

$$q_x = A(P_1 - P_2) \quad (1)$$

$$q_y = A(P_4 - P_3) \quad (2)$$

Where:

A is a calibration constant

The relationship between dynamic pressure and calibrated airspeed is defined by the equation:

$$v_{cal} = \left\{ \frac{2\gamma}{\gamma-1} \left(\frac{P}{P_o} \right) \left[\left(\frac{q}{P_o} \right) + 1 \right]^{\frac{\gamma-1}{\gamma}} - 1 \right\}^{1/2} \quad (3)$$

Where:

γ = specific heat ratio of air ~ 1.4

P_o = standard-day, sea-level pressure

ρ_o = standard-day, sea-level density

This equation can be represented by the transfer function:

$$v_{cal} = K_1 + K_2 \left[q / (1 + K_3 q) \right]^{1/2} \quad (4)$$

Where:

K_n are constants required to make the equation valid

The error introduced by the use of this function rather than equation 3 is ± 0.0007 percent over the range of 10 to 150 knots.

6. The transfer function is applied to the DC voltage in a function module within the air data transducer unit. This allows the transducer output to be proportional to airspeed.

7. A temperature compensation circuit is also included in the transducer to eliminate errors caused by temperature variation.

8. Rosemount has also developed a transducer that will combine dynamic and static pressures with temperature and output longitudinal and lateral airspeeds in units of true airspeed. This would probably be more useful if the system is to be incorporated into a navigation system.

Barometer Altitude Transducer

9. The 1241 altitude transducer converts static pressure from the sensor to a voltage proportional to pressure altitude. The transfer function used is:

$$H_P = K_1 \left(\frac{1}{P_S} \right)^{K_2} \quad (5)$$

The transducer also has a module to differentiate the altitude signal to obtain rate of climb.

Cockpit Indicator

10. The cross-pointer indicator has a display in the form of concentric circles 10 knots apart with zero located at the geometric center. The horizontal pointer moves up with increasing forward airspeed; the vertical pointer moves in the direction of lateral aircraft motion. The intersection of the two pointers will show resultant vector airspeed. There is no indicator for pressure altitude or rate of climb.

APPENDIX C. TEST INSTRUMENTATION

1. The following parameters were recorded on board the test helicopter on magnetic tape and were displayed on the instrument panel.

- Time of day
- Engineer event
- Pilot event
- Run number
- Test boom altitude
- Test boom airspeed
- Radar altimeter
- Outside total temperature
- Angle of attack
- Angle of sideslip
- Rotor speed
- Pitch attitude
- Roll attitude
- Magnetic heading
- Fuel used counter
- Fuel temperature
- Rosemount longitudinal airspeed
- Rosemount lateral airspeed
- Rosemount pressure altitude¹
- Rosemount rate of climb¹

2. The following parameters were hand-recorded on the ground.

- Wind speed and direction
- Pace vehicle speed and direction
- Ambient temperature

¹Not displayed in the aircraft.

APPENDIX D. TEST DATA

INDEX

<u>Figure</u>	<u>Figure Number</u>
System Performance in Forward and Rearward Flight	1
System Performance in Sideward Flight	2
Sideslip Effects on Longitudinal Error	3
Sideslip Effects on Lateral Airspeed Error	4

FIGURE 1 **SYSTEM PERFORMANCE IN FORWARD AND REARWARD FLIGHT**

NAV-EN USA 2/N 65-0004

ROSEMOUNT ORTHOGONAL AIRSPEED SYSTEM MODEL 869

AVG GROSS HEIGHT (LB)	AVG CG LOCATION (IN)	AVG DENSITY ALTITUDE (FEET)	AVG OAT (DEG C)	AVG ROTOR SPEED (RPM)	AVG CT	AVG SHD HEIGHT (FEET)
7000.	131.9 (110)	3710.	24.0	324.	0.0039	50.

NOTES: 1) GROUND PACE VEHICLE METHOD
2) SYMBOLS DENOTE MEAN VALUES
3) VERTICAL LINES DENOTE RANGE
OF ROSEMOUNT DATA
4) SHADED SYMBOLS DENOTE
5 FOOT SHD HEIGHT




FIGURE 2 **SYSTEM PERFORMANCE IN SIDEWARD FLIGHT**

NUM-1H USA S/N 65-0334 ROSEBUNT ORTHODONAL AIRSPEED SYSTEM MODEL 059

AVG GROSS WEIGHT (LB)	AVG CD LOCATION (F8)	AVG DENSITY ALTITUDE (FEET)	AVG OAT (DEG C)	AVG ROTOR SPEED (RPM)	AVG CT	SKID HEIGHT (FEET)
6950.	131.7 (MID)	3900.	25.5	324.	0.0039	50.

NOTES: 1) GROUND PACE VEHICLE METHOD
2) SYMBOLS DENOTE MEAN VALUES
3) VERTICAL LINES DENOTE RANGE
OF ROSEBUNT DATA




FIGURE 3

SIDESLIP EFFECTS ON LONGITUDINAL AIRSPEED ERROR

UH-1H UH-1H S/N 69-0004

ROSEMOUNT ORTHOGONAL AIRSPEED SYSTEM MODEL 853

AVG GROSS WEIGHT (LB)	AVG CG LOCATION (IN)	AVG DENSITY ALTITUDE (FEET)	AVG OAT (DEG C)	AVG ROTOR SPEED (RPM)	AVG CT	SKID HEIGHT (FEET)
9900.	131.7 (MID)	3900.	28.0	524.	0.0038	50.

NOTES: 1) GROUND PACE VEHICLE METHOD
2) SYMBOLS DENOTE MEAN VALUES
3) VERTICAL LINES DENOTE RANGE
OF ROSEMOUNT DATA





FIGURE 4

SIDESLIP EFFECTS ON LATERAL AIRSPEED ERROR

NUM-11 USA 9/11 83-0004 ROSEHUNT ORTHOGONAL AIRSPEED SYSTEM MODEL 853

AVG GROSS WEIGHT (LB)	AVG CG LOCATION (IN)	AVG DENSITY ALTITUDE (FEET)	AVG OAT (DEG C)	AVG ROTOR SPEED (RPM)	AVG CT	AVG HMD HEIGHT (FEET)
8000.	131.7 (MID)	3800.	28.0	324.	0.0038	80.

NOTES: 1) GROUND PACE VEHICLE METHOD
2) SYMBOLS DENOTE MEAN VALUES
3) VERTICAL LINES DENOTE RANGE
OF ROSEHUNT DATA



DISTRIBUTION

Director of Defense Research and Engineering	2
Deputy Director of Test and Evaluation, OSD (OAD(SSST&E))	1
Assistant Secretary of the Army (R&D), Deputy for Aviation	1
Deputy Chief of Staff for Research, Development, and Acquisition (DAMA-WSA, DAMA-RA, DAMA-PPM-T)	4
US Army Materiel Development and Readiness Command (DRCPM-CO, DRCDE-DW-A, DRCSE-A, DRCQA)	8
US Army Aviation Research and Development Command (DRDAV-EQ)	12
US Army Training and Doctrine Command (ATCD-CM-C)	1
US Army Materiel Systems Analysis Activity (DRXSY-CM)	2
US Army Test and Evaluation Command (DRSTE-AV, USMC LNO)	3
US Army Electronics Command (AMSEL-VL-D)	1
US Army Forces Command (AFOP-AV)	1
US Army Armament Command (SARRI-LW)	2
US Army Missile Command (DRSMI-QT)	1
Hq US Army Air Mobility R&D Laboratory (DAVDL-D)	2
US Army Air Mobility R&D Laboratory (DAVDL-SR)	1
Ames Directorate, US Army Air Mobility R&D Laboratory (DAVDL-AM)	2
Eustis Directorate, US Army Air Mobility R&D Laboratory (DAVDL-EU-SY)	2
Langley Directorate, US Army Air Mobility R&D Laboratory (DAVDL-LA)	2
Lewis Directorate, US Army Air Mobility R&D Laboratory (DAVDL-LE-DD)	1
US Army Aeromedical Research Laboratory	1
US Army Avionics Laboratory	2
US Army Aviation Center (ATZQ-D-MT)	3
US Army Aviation School (ATZQ-AS, ATST-CTD-DPS)	3
US Army Aircraft Development Test Activity (PROV) (STEBG-CO-T, STEBG-PO, STEBG-MT)	5
US Army Agency for Aviation Safety (IGAR-TA, IGAR-Library)	2
US Army Maintenance Management Center (DRXMD-EA)	1
US Army Transportation School (ATSP-CD-MS)	1
US Army Logistics Management Center	1
US Army Foreign Science and Technology Center (AMXST-WS4)	1

US Military Academy	3
US Marine Corps Development and Education Command	2
US Naval Air Test Center	1
US Air Force Aeronautical Division (ASD-ENFTA)	1
US Air Force Flight Dynamics Laboratory (TST/Library)	1
US Air Force Flight Test Center (SSD/Technical Library, DOEE)	3
US Air Force Electronic Warfare Center (SURP)	1
Department of Transportation Library	1
US Army Bell Plant Activity (DAVBE-ES)	5
Bell Helicopter Textron	5
Rosemount, Inc.	5
AVCO Lycoming Division	5
Defense Documentation Center	12