

AD-A047 432


ARMY ELECTRONICS COMMAND FORT MONMOUTH N J
A PRELIMINARY ANALYSIS OF TWO SOUND RANGING ALGORITHMS. (U)
JUL 77 W MILLER, B ENGBOS
ECOM-5826

F/G 17/1

UNCLASSIFIED

NL

| OF |
AD
A047432



END
DATE
FILMED
1 - 78
DDC



(12) *sc*

AD

Reports Control Symbol
OSD-1366

RESEARCH AND DEVELOPMENT TECHNICAL REPORT
ECOM-5826

AD A 0 4 7 4 3 2

A PRELIMINARY ANALYSIS OF TWO SOUND RANGING ALGORITHMS

By

W. Miller
B. Engebos

DDC
RECEIVED
NOV 28 1977
F

AD No.
DDC FILE COPY

Atmospheric Sciences Laboratory

US Army Electronics Command
White Sands Missile Range, New Mexico 88002

July 1977

Approved for public release; distribution unlimited.

ECOM

UNITED STATES ARMY ELECTRONICS COMMAND - FORT MONMOUTH, NEW JERSEY 07703

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ECOM-5826 ✓	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A PRELIMINARY ANALYSIS OF TWO SOUND RANGING ALGORITHMS.	5. TYPE OF REPORT & PERIOD COVERED 9. Technical Report.	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) W./Miller B./Engebos	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Atmospheric Sciences Laboratory White Sands Missile Range, NM 88002 ✓	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS DA Task 1L1.61101.A91A	
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Electronics Command Fort Monmouth, NJ 07703 ✓	12. REPORT DATE Jul 77	13. NUMBER OF PAGES 41
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. ⑩/1L161101A91A		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) ①37 62①		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Sound ranging Acoustics Meteorological data Algorithms		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Two sound ranging algorithms are examined by observing their behavior in a basic controlled environment. The consistency of both is verified under a variety of meteorological regimes and a selection of arrival time accuracies. The advantages and shortcomings of each are discussed. In particular, possible compromise between timing accuracy and integrity of meteorological data is evidenced. Field applicability may prove feasible.		

D D C
PREPARED
NOV 28 1977
REGISTERED
F

GM

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

A large, empty rectangular box with a black border, intended for security classification information. The box is centered on the page and occupies most of the vertical space between the top and bottom text labels.

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

CONTENTS

	<u>Page</u>
INTRODUCTION	2
ACOUSTIC LOCATION PROGRAM 1 (ALP-1)	4
TEMPERATURE AND WIND EFFECTS FOR ALP-1	9
ALP-2 AND THE CORRECTIVE MODE	18
CONCLUSIONS	25
REFERENCES	32
BIBLIOGRAPHY	33

ACCESSION for

NTIS White Section
DOC Buff Section

UNANNOUNCED
JUSTIFICATION

BY _____

DISTRIBUTION/AVAILABILITY CODES

Dist. _____ or SF CIAL

A

RE: Classified reference, ECOM-5826
Document should remain for unlimited
distribution per Ms. Marie Richardson,
Army Atmospheric Sciences Lab.

INTRODUCTION

The traditional use by army artillery of a linear array of sound detection microphones in the solution of a variety of "sound ranging" problems [1] has focused attention on the predictable behavior characteristics of such a system. Of equal interest are the nature and extent of meteorological information necessary for solutions of a given reliability. A number of techniques exist or are under consideration which deal with these problems, and a bibliography of pertinent established or ongoing work is included at the close of this presentation.

At present, interest will be with a set of algorithms developed from [2]. In this work, Miller and Engebos present a mathematical structure within which the sound ranging problem is given a rigorous definition, and a solution is offered in context. The state of the propagating medium is reflected in the form of a quadrivariate function called an extended wave generating function. For the purposes at hand, a simple but revealing form is utilized [3] describing a circular or spherical sound wave propagating in a region of uniform temperature and subject to horizontal translation by a wind of fixed velocity.

The above-mentioned algorithms are simple in form and are structured in such a manner that system failure due to reliability or vulnerability may easily be addressed. No barrier is present to the consideration of more comprehensive wave generating functions; hence, more involved and realistic physical states for the atmosphere can be considered.

A series of three specialized algorithms have been constructed. These algorithms are programmed on the HP9830A computer and have been designated as Acoustic Location Programs one, two, and three (ALP-1, ALP-2, ALP-3). Of interest at present are ALP-1 and ALP-2. The program ALP-1 allows the consideration of a linear array of three or more acoustic microphones and requires the following as input: wind and temperature estimates, a family of wave front arrival times at the respective microphones, and a preliminary estimate of source location. Note that errors in temperature and wind and discrepancies in arrival times will appear as errors in source determination. On the other hand, if ALP-2 is utilized, experience has shown that for sufficient accuracy of arrival times, the initial source location estimate may be considerably in error, yet the true source is reproduced. This phenomenon will be discussed more explicitly in the text to follow.

The program ALP-2 is similar to ALP-1 in that it requires an identical input. It differs in that it is capable of operating in one of three correction modes. These three modes are a temperature correction mode, a wind correction mode, and a mode for correcting both wind and temperature simultaneously. As will be seen, these modes can permit considerable reduction in source location error, but generally require a level of accuracy in timing higher than ALP-1.

The program ALP-3 extends all previous results to three dimensions, and in some cases can produce drastic reductions in source location errors. However, a number of special considerations surface which require attention, and this aspect is felt to warrant a separate descriptive documentation. This documentation is currently in progress and should be available soon after the publication of the present work.

Numerical results are now available from more than two thousand exploratory runs of ALP-1 and ALP-2. These results have brought to light a number of properties of linear arrays which tend to validate the conjectures made by Lee [4] and have caused a considerable change in the authors' outlook toward the utility of the linear array. Current thinking based on latest numerical results plus additional analysis has indicated that a linear array of six acoustic microphones may possess certain favorable behavior characteristics if the proper computational algorithms are utilized. The greatest danger lies in the susceptibility of all methodology to timing estimation errors.

An examination of the behavior of ALP-1 and ALP-2 as sound ranging algorithms necessitated the development of a program which could supply a suitably precise data base for an exhaustive check on the consistency of the algorithms in question and under several conditions for accuracy of arrival times and meteorological states. This program was so constructed that if microphone locations and the state of wind and temperature are known, each source point chosen gives rise to a set of arrival times. This first model does not consider terrain influence, position, or time varying meteorological states, but for the special conditions mentioned previously, it produces arrival times of near nanosecond accuracy to a distance of 30 kilometers.

Since a primary purpose of this report is the documentation of some of the more important behavior characteristics of ALP-1 and ALP-2, a sufficiently inclusive number of sound sources is considered to indicate response to differing source locations. Since microphone positions are symmetrical, consideration of 30 sound sources is equivalent to the observation of 60 sources.

As will be seen, all algorithms considered exhibited a negligible error in source location under idealized conditions; for ALP-2, negligible error occurred also with considerable errors in temperature and wind estimates. However, all were in general degraded in performance as timing accuracy was degraded.

Without theoretical barriers, algorithms may now be constructed which can utilize a more thorough knowledge of the meteorological state and hence be more completely in rapport with a realistic physical environment. In this way, work may progress toward the eventual goal of developing a flexible sound ranging package for the Army.

ACOUSTIC LOCATION PROGRAM 1 (ALP-1)

At this point; the behavior of ALP-1 will be observed in an uncomplicated but revealing setting. This algorithm is the simplest of those to be considered. A local rectangular Cartesian coordinate system (X, Y, Z) will be assumed to supply all underlying coordinates in the situations to follow. The present analysis will be expository and directed toward identifying important features of the linear array without obscuration by an overabundance of mathematical embellishment. Results will be taken as the primary objective. Interested readers may consult [2] for mathematical details.

All events will be assumed to occur on the plane $Z = 0$; or in other words, the model will be two-dimensional. As will be seen, this closely parallels existing techniques and permits considerable interpretive analysis. Let (x_0, y_0) denote a source point of interest on the plane $Z = 0$, and for each j among $1, 2, \dots, 6$, let (x_j, y_j) be the coordinates of an acoustic microphone indexed by j . Assume, moreover, that there exists real constants a and b such that for all j , $y_j = ax_j + b$ with $y_0 \neq ax_0 + b$. This stipulates that the family $\{(x_j, y_j) \mid j = 1, 6\}$ form a linear array whose extension of baseline does not include (x_0, y_0) .

Within some region of interest, it will be assumed that a steady wind of components $(u, v) = \vec{u}$ is blowing, and that this region is of a constant temperature, say k degrees Kelvin. The speed of sound in this region will be assumed to be $c\sqrt{k}$ meters/second, where c is a constant of value 20.06.

The vector $\vec{x} = [(x_j - x_0), (y_j - y_0)]$ represents the distance between the sound source and acoustic microphone indexed by j in the above-mentioned array. It is not difficult to show that under these circumstances, a blast occurring at time t_0 and giving rise to a waveform propagating at a speed of $c\sqrt{k}$ meters/second, if subject to the wind \vec{u} , will result in a clean time break, t_j , at the j^{th} microphone defined by

$$t_j = t_0 + \frac{\sqrt{(\vec{u} \cdot \vec{x})^2 + (c^2k - |\vec{u}|^2)|\vec{x}_j|^2} - (\vec{u} \cdot \vec{x}_j)}{(c^2k - |\vec{u}|^2)}. \quad (1)$$

In expression (1), the usual conventions for dot product and magnitude of vectors are employed.


For the purposes of verifying the construction, operating characteristics, and effectiveness of ALP-1, ALP-2, and later ALP-3, and for controlled comparisons of techniques planned for a later date, a comprehensive configuration of 72 sound sources was chosen for examination. These were located at flanking angles of 0 to 75 degrees in 15-degree increments. Along each line segment so designated, sources were located at 5-kilometer increments from 5 to 30 kilometers. The expression (1) was utilized to supply timing information for a linear array located parallel to and 1 kilometer below the X-axis and symmetrically with the Y-axis. Microphones were given a uniform separation of 2 kilometers with the array centroid located at the point (0, -1000). The use of symmetry reduced the actual calculations to those in the first quadrant, and an illustration of this configuration is given in Figure 1. Here, microphones are designated by M. Sound sources are denoted by asterisks. This array will be used exclusively throughout the remainder of this report and should prove adequate for the purposes intended.

It should be stressed that the timing information derived from this array and used subsequently is based on physical assumptions concerning the environment and originates from programs distinct and separate from the algorithms to be tested.

The timing data were produced and tabulated through the use of the HP9830A minicomputer. These timing data are never rounded but always represent direct truncations. A primary consistency check of ALP-1 was performed under idealized meteorological conditions and with primary estimates 10% and 20% of range. When a 90-degree clockwise sequence of four source locations was utilized, the algorithm ALP-1 invariably converged to the true source point for flanking angles of 0 to 75 degrees. When estimates were chosen in a similar fashion for a 20% range error, results were similar (Fig. 2). In all cases indicated, convergence of ALP-1 was consistent and resulted in identical points.

As a next step, perfect meteorological information was utilized but timing accuracy was degraded to the nearest 0.1 millisecond. Results of such a degradation on chosen points of the array are given in Fig. 3. In Figs. 2 and 3, the deviations for the 5-kilometer range are purposely

SOURCE LOCATIONS UTILIZED IN THE EVALUATION OF ALP-1, ALP-2, AND ALP-3. SOURCE POINT POSITIONS ARE DESIGNATED BY ASTERISKS (*) AND MICROPHONE POSITIONS BY THE LETTER (M).




HORIZONTAL & VERTICAL SCALES 5.0 KILOMETERS.

FIGURE 1

DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 PRODUCED BY
 A 0.1 MILLISECOND TRUNCATION OF ARRIVAL TIMES. HORIZONTAL AND
 VERTICAL SCALES 5.0 KILOMETERS.

INDICATED DEPARTURES
 GIVEN IN METERS.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT
 RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.
 FIGURE 3

omitted for editorial reasons. In addition, these numbers are consistent in behavior with the remaining values and offer little additional information.

The timing accuracy which may be related to ideal field conditions is in the vicinity of 1 millisecond. Figure 4 gives the results of the location algorithm ALP-1 under the previously mentioned conditions, except that a truncation at the nearest millisecond is employed. The degradation from Figs. 2 and 3 is obvious but not unbearable. Figure 5 represents identical information, but expressed in the familiar format of percent of range. Effects of truncation error as a function of range and flanking angle are discernible, but individual truncation characteristics often tend to obscure these relations.

In Fig. 6, the effect of timing accuracy correct to the nearest 10 milliseconds is presented, and a greater loss in source point identification ability is evidenced. Figure 7 presents this data as percent of range to preserve this familiar context.


In the majority of cases observed, or presented in this report, the effects of degradation of timing accuracy are increasingly evident as either range increases or high flanking angles are encountered. This fact will occasionally be obscured by the behavior of truncation effects as they apply to individual times arising from the location of the sound source under consideration.

It is true that in practice many problems arise which are not considered at present. Signal attenuation, complex atmospheric conditions, terrain, errors in location of acoustic microphones, break point identification, and multiple arrival times all serve to degrade or hamper source point identification. However, as the more amenable problems are systematically dealt with and thoroughly understood, the way will be paved to the introduction of more precise and flexible algorithms.

TEMPERATURE AND WIND EFFECTS FOR ALP-1

When the effects of temperature variations are examined at the selection of points indicated in Fig. 1, an interesting phenomenon may be observed. The effect of unit increases and decreases in temperature does not result in equal and opposite source point location effects. This characteristic is evident when Figs. 8 and 9 are compared, and is solely the result of millisecond truncation of arrival times. Even more evident are similar consequences of a 10-millisecond truncation, as seen in Figs. 10 and 11. This characteristic, which could conceivably be interpreted as caused by refraction, is in reality due only to truncation of arrival times.


DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 PRODUCED BY
 A 1.0 MILLISECOND TRUNCATION OF ARRIVAL TIMES. HORIZONTAL AND
 VERTICAL SCALES 5.0 KILOMETERS.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT
 RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.

FIGURE 4


DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 EXPRESSED AS PERCENT OF RANGE. ARRIVAL TIMES ARE TRUNCATED AT THE NEAREST MILLISECOND. UNIFORM SCALE REPRESENTS 5.0 KILOMETERS.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.


FIGURE 5

DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 PRODUCED BY
 A 10 MILLISECOND TRUNCATION OF ARRIVAL TIMES. HORIZONTAL AND
 VERTICAL SCALES 5.0 KILOMETERS.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT
 RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.
 FIGURE 6


DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 EXPRESSED AS PERCENT OF RANGE. ARRIVAL TIMES ARE TRUNCATED AT THE NEAREST 10 MILLISECONDS. UNIFORM SCALE REPRESENTS 5.0 KILOMETERS.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.

FIGURE 7

DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 PRODUCED BY A 1.0 MILLISECOND TRUNCATION OF ARRIVAL TIMES AND +1.0 DEGREES KELVIN ERROR IN TEMPERATURE.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.

FIGURE 8


DEPARTURES OF SOURCE LOCATION ESTIMATES DERIVED FROM ALP-1 AND INCLUDING A 10 MILLISECOND TRUNCATION OF ARRIVAL TIMES. ALSO PRESENT IS A ± 1.0 DEGREES KELVIN ERROR IN TEMPERATURE.

	INDICATED DEPARTURES GIVEN IN METERS									
30	9.7	95.3								
	34.9	44.3	164.3							
20	1.6	73.7	19.1	332.7						
	48.2	22.6	74.9	52.0	86.1	210.3				
10	9.8	24.1	40.1	68.1	188.8	100.6	1358.7			
			57.8	217.1	828.9	1795.7				
			84.7	753.2						
			281.3							

NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.
FIGURE 10

DEPARTURES OF SOURCE LOCATION ESTIMATES DERIVED FROM ALP-1 AND INCLUDING A 10 MILLISECOND TRUNCATION OF ARRIVAL TIMES. ALSO PRESENT IS A -1.0 DEGREES KELVIN ERROR IN TEMPERATURE.

INDICATED DEPARTURES
GIVEN IN METERS



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.

FIGURE 11

True unit effects which utilize full possible timing accuracy are given in Fig. 12. These effects represent a unit variation in temperature in either a positive or negative sense, and are consistent. Note that respective locations in Fig. 12 are very nearly averages from Figs. 8 and 9 or from Figs. 10 and 11. A point which should be noted is that as flanking angles approach zero degrees, unit effects diminish considerably. Another method of viewing this condition which will prove pertinent is that temperature information occurs further and further to the right of the decimal point of the timing data as flanking angles decrease to 0 degrees. This point will also arise when ALP-2 is introduced.


In Fig. 13, effects due to a positively oriented unit wind parallel to the array baseline are displayed. Figure 14 offers identical information for a unit wind which is perpendicular to this baseline. Notice the drastic reduction in error magnitudes in Fig. 14. In fact, if Fig. 14 is compared with errors due to millisecond truncation (Fig. 4), it might be suspected that position estimates must be independent of winds perpendicular to array baseline. This fact is further verified by Fig. 15 which represents the effect of a vector sum of unit coordinate winds. It can be rigorously shown that such must always be the case in so far as the linear array is concerned. This fact will be of considerable importance in the construction of ALP-2.

ALP-2 AND THE CORRECTIVE MODE

The algorithm designated as ALP-2 is constructed to function optimally in the same physical environment as ALP-1 and is fabricated by way of [2], section 5. It is tailored to the linear array and requires a configuration of five or more acoustic microphones, as contrasted to the requirement of three or more microphones for ALP-1. On the positive side, the algorithm ALP-2 operates in a full corrective mode and will recover source point location even when subject to considerable errors in wind and temperature estimates, providing arrival times at the microphones under consideration are determined to sufficient accuracy. In fact, one may balance the required accuracy of arrival times against the necessary integrity of the meteorological data involved.

Examination with near exact data has indicated that with a preliminary estimate in error up to 20% of range, ALP-2 will function consistently to a range of 10 kilometers and a flanking angle of 75 degrees, or 12 kilometers with a flanking angle of 60 degrees. A more complete picture is presented if one examines those source locations as indicated in Fig. 16. Figure 17 presents the departures in estimates derived from ALP-1 and caused by a wind error of unit magnitude (meters/second) in the direction of positive x and y, together with a temperature error of +1.0° kelvin. This is with regards to respective source points from Fig. 16 in excess of 2 kilometers. The behavior of ALP-1 at the 2-kilometer range is


DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 PRODUCED BY
 A NANSECONDD TRUNCATION OF ARRIVAL TIMES AND 1.0 DEGREES
 KELVIN ERROR IN TEMPERATURE.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT
 RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.
 FIGURE 12

DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 PRODUCED BY A 1.0 MILLISECOND TRUNCATION OF ARRIVAL TIMES AND A WIND ERROR OF 1.0 METERS/SECOND PARALLEL TO ARRAY BASELINE.


INDICATED DEPARTURES
GIVEN IN METERS



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.
FIGURE 13


DEPARTURES OF SOURCE LOCATION ESTIMATES DERIVED FROM ALP-1 AND INCLUDING A MILLISECOND TRUNCATION OF ARRIVAL TIMES, PRESENT ALSO IS A 1.0 METERS/SECOND ERROR IN WIND PERPENDICULAR TO THE ARRAY BASELINE.

INDICATED DEPARTURES
GIVEN IN METERS




NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1. FIGURE 14

DEPARTURES OF SOURCE LOCATION ESTIMATES FROM ALP-1 PRODUCED BY
 A 1.0 MILLISECOND TRUNCATION OF ARRIVAL TIMES AND A WIND ERROR
 OF 1.4 METERS/SECOND 45 DEGREES OFF ARRAY BASELINE.



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT
 RESPECTIVE POSITIONS AS INDICATED IN FIGURE 1.
 FIGURE 15

SOURCE LOCATIONS UTILIZED IN THE EVALUATION OF ALP-2 AND ALP-3. SOURCE POINT POSITIONS ARE DESIGNATED BY ASTERISKS WITH MICROPHONE POSITIONS INDICATED BY THE LETTER M.




HORIZONTAL & VERTICAL SCALES 2.0 KILOMETERS.

FIGURE 16

DEPARTURES OF ALP-1 SOURCE LOCATION ESTIMATES DERIVED FROM ARRIVAL TIMES IN THE VICINITY OF 1.0 NANoseconds. INCLUDED ARE 1.0 M/SEC. ERRORS IN X & Y COMPONENTS OF WIND AND A 1.0 DEG. KELVIN ERROR IN TEMPERATURE.

INDICATED DEPARTURES GIVEN IN METERS



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT SELECTED POSITIONS FROM FIGURE 16.

FIGURE 17

omitted for editorial reasons, and departures are in all cases smallest at the 2-kilometer distance. Figure 18 yields similar information, except that all meteorological errors are five times as great. Figures 19 and 20 present departures of ALP-2 estimates from the true source points with errors identical to those encountered in Figs. 17 and 18, respectively. In all cases utilizing ALP-2, preliminary estimates in error 20% of range are employed. Points of convergence of ALP-2 have thus far always proved consistent except at the point defined by 75 degrees flanking angle and 12 kilometers range as indicated in Fig. 18. By constraining the preliminary estimate to lie within 5% of range, this figure is reduced to 3 centimeters.

A slight degradation in accuracy occurs with the larger meteorological errors; but in general, departures in Figs. 19 and 20 are similar and represent a considerable improvement in source point location over those values given for ALP-1 in Figs. 17 and 18. These figures, however, are intended only to demonstrate the potential information contained in arrival times and to serve as a consistency check on ALP-2.


More pertinent is the information gained by considering the results of truncation at the nearest millisecond. Behavior of ALP-2 under these circumstances is given in Figs. 21 and 22 to correspond with Figs. 19 and 20, respectively. The degradation in accuracy is apparent and conclusive, but it is still of interest to compare Figs. 17 and 21 as well as Figs. 18 and 22. In these latter cases, a sequence of dollar signs at a given position indicates that at least one guess vector at 20% of range distance from the true source point did not produce results identical to the others chosen. If instead, 5% of range is considered as an error-bound, negligible changes from those encountered in Fig. 22 are met. This indicates that in ALP-2, timing is considerably more important than accuracy of preliminary estimates. In all, the algorithm ALP-2 appears to exhibit some interest in the context of advancing technology. It must be recalled also that this mechanism is operating in an idealized physical situation. In field practice, a family of algorithms reflecting more complex environmental conditions could well prove of greater value.

CONCLUSIONS

The algorithms ALP-1 and ALP-2 have been examined in detail by considering their behavior at selected points and in a simple physical environment. Systems with truncated arrival times are considered as well. The theory under which the algorithms were constructed has been verified, and possible field application may prove feasible. It is recognized that all ALP algorithms have the disadvantage of requiring some form of preliminary source estimates, but these estimates may contain fairly large errors without undue problems if arrival times are reasonable. The problem of reducing station numbers may be easily handled by ALP-1 or ALP-2; but only


DEPARTURES OF ALP-1 SOURCE LOCATION ESTIMATES DERIVED FROM ARRIVAL TIMES IN THE VICINITY OF 1.0 NANSECONDS. INCLUDED ARE 5.0 M/SEC. ERRORS IN X & Y COMPONENTS OF WIND, AND A 5.0 DEG. KELVIN ERROR IN TEMPERATURE.

INDICATED DEPARTURES
GIVEN IN METERS



DEPARTURES OF ALP-2 SOURCE LOCATION ESTIMATES DERIVED FROM ARRIVAL TIMES IN THE VICINITY OF 1.0 NANoseconds. INCLUDED ARE 1.0 M/SEC. ERRORS IN X & Y COMPONENTS OF WIND, AND A 1.0 DEG. KELVIN ERROR IN TEMPERATURE.

INDICATED DEPARTURES
GIVEN IN METERS




NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT SELECTED POSITIONS FROM FIGURE 16.

FIGURE 19


DEPARTURES OF ALP-2 SOURCE LOCATION ESTIMATES DERIVED FROM ARRIVAL TIMES IN THE VICINITY OF 1.0 NANSECONDS. INCLUDED ARE 5.0 M/SEC. ERRORS IN X & Y COMPONENTS OF WIND, AND A 5.0 DEG. KELVIN ERROR IN TEMPERATURE.

INDICATED DEPARTURES
GIVEN IN METERS



NUMBERS INDICATE DEPARTURES OF SOURCE LOCATION ESTIMATES AT SELECTED POSITIONS FROM FIGURE 16.

FIGURE 20



one microphone may be lost in ALP-2, while ALP-1 permits loss of three. In addition, ALP-1 is independent of array construction, while ALP-2 requires a linear array of acoustic microphones for full correction.

A modification of ALP-2 is already written which will permit use of nonlinear arrays and will require five or more operative microphones for corrective mode. Unfortunately, this modification will not permit use of a linear array. General nonlinear arrays are being constructed, including random dispersions. From study of such arrays, a degree of "focusing" or optimizing may be possible.

REFERENCES

1. FM 6-122, Artillery Sound Ranging and Flash Ranging, 1964, Dept of Army, Washington, DC.
2. Miller, Walter B. and B. F. Engebos, 1976, A Mathematical Structure for Refinement of Sound Ranging Estimates, ECOM-5805, Atmospheric Sciences Laboratory (ASL), US Army Electronics Command, White Sands Missile Range (WSMR), NM.
3. Rachele, Henry, 1966, A Specialized Acoustic Array Solution, ASL, WSMR, NM, unpublished manuscript.
4. Lee, Robert P., 1972, Artillery Sound Ranging Computer Simulations, ECOM-5441, ASL, US Army Electronics Command, WSMR, NM.

BIBLIOGRAPHY

1. Denver Research Institute, 1956, "Study of Meteorological and Terrain Factors which Affect Sound Ranging - Final Report," University of Denver, Denver, CO (AD 139326).
2. Bellucci, Raymond, 1963, "Studies of Meteorological Techniques for Sound Ranging, Part 1," USAERDL Technical Report 2367, US Army Research and Development Laboratory, Fort Monmouth, NJ.
3. Bellucci, Raymond, 1966, "Studies of Meteorological Techniques for Sound Ranging, Report 11, Error Analysis," Technical Report ECOM-2703, Atmospheric Sciences Laboratory, US Army Electronics Command, Fort Monmouth, NJ.
4. Barichivich, Anthony, 1966, "Proposed New Meteorological Techniques for Sound Ranging, Report 111," Technical Report ECOM-2702, Atmospheric Sciences Laboratory, US Army Electronics Command, Fort Monmouth, NJ.
5. Lee, R. P., 1967, "A Probabilistic Model for Acoustic Sound Ranging," ECOM-5159, Atmospheric Sciences Laboratory, US Army Electronics Command, White Sands Missile Range, NM (AD 664117).
6. Lee, R. P., 1969, "A Dimensional Analysis of the Errors of Atmospheric Sound Ranging," ECOM-5236, Atmospheric Sciences Laboratory, US Army Electronics Command, White Sands Missile Range, NM (AD 686287).
7. Kennedy, W. B., et al., 1956, "Study of Meteorological and Terrain Factors which Affect Sound Ranging - Final Report," Denver Research Institute, University of Denver, Denver, CO.
8. Diamond, M. and R. P. Lee, 1965, "Long-Range Atmospheric Sound Propagation," J. Geophys. Res., Vol. 70, No. 22.

DISTRIBUTION LIST

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLB, Dr. G. E. Keller
Aberdeen Proving Ground, MD 21005

Air Force Weapons Laboratory
ATTN: Technical Library (SUL)
Kirtland AFB, NM 87117

Commander
Headquarters, Fort Huachuca
ATTN: Tech Ref Div
Fort Huachuca, AZ 85613

6585 TG/WE
Holloman AFB, NM 88330

Commandant
US Army Field Artillery School
ATTN: Morris Swett Tech Library
Fort Sill, OK 73503

Commandant
USAFAS
ATTN: ATSF-CD-MT (Mr. Farmer)
Fort Sill, OK 73503

Director
US Army Engr Waterways Exper Sta
ATTN: Library Branch
Vicksburg, MS 39180

Commander
US Army Electronics Command
ATTN: DRSEL-CT-S (Dr. Swingle)
Fort Monmouth, NJ 07703
03

CPT Hugh Albers, Exec Sec
Interdept Committee on Atmos Sci
Fed Council for Sci & Tech
National Sci Foundation
Washington, DC 20550

Inge Dirmhirn, Professor
Utah State University, UMC 48
Logan, UT 84322

HQDA (DAEN-RDM/Dr. De Percin)
Forrestal Bldg
Washington, DC 20314

Commander
US Army Aviation Center
ATTN: ATZQ-D-MA
Fort Rucker, AL 36362

CO, USA Foreign Sci & Tech Center
ATTN: DRXST-ISI
220 7th Street, NE
Charlottesville, VA 22901

Director
USAE Waterways Experiment Station
ATTN: Library
PO Box 631
Vicksburg, MS 39180

US Army Research Office
ATTN: DRXRO-IP
PO Box 12211
Research Triangle Park, NC 27709

Mr. William A. Main
USDA Forest Service
1407 S. Harrison Road
East Lansing, MI 48823

Library-R-51-Tech Reports
Environmental Research Labs
NOAA
Boulder, CO 80302

Commander
US Army Dugway Proving Ground
ATTN: MT-S
Dugway, UT 84022

HQ, ESD/DRI/S-22
Hanscom AFB
MA 01731

Head, Atmospheric Rsch Section
National Science Foundation
1800 G. Street, NW
Washington, DC 20550

Office, Asst Sec Army (R&D)
ATTN: Dep for Science & Tech
HQ, Department of the Army
Washington, DC 20310

Commander
US Army Satellite Comm Agc
ATTN: DRCPM-SC-3
Fort Monmouth, NJ 07703

Sylvania Elec Sys Western Div
ATTN: Technical Reports Library
PO Box 205
Mountain View, CA 94040

William Peterson
Research Association
Utah State University, UNC 48
Logan, UT 84322

Defense Communications Agency
Technical Library Center
Code 205
Washington, DC 20305

Dr. A. D. Belmont
Research Division
PO Box 1249
Control Data Corp
Minneapolis, MN 55440

Commander
US Army Electronics Command
ATTN: DRSEL-WL-D1
Fort Monmouth, NJ 07703

Commander
ATTN: DRSEL-VL-D
Fort Monmouth, NJ 07703

Meteorologist in Charge
Kwajalein Missile Range
PO Box 67
APO
San Francisco, CA 96555

The Library of Congress
ATTN: Exchange & Gift Div
Washington, DC 20540
2

US Army Liaison Office
MIT-Lincoln Lab, Library A-082
PO Box 73
Lexington, MA 02173

Dir National Security Agency
ATTN: TDL (C513)
Fort George G. Meade, MD 20755

Director, Systems R&D Service
Federal Aviation Administration
ATTN: ARD-54
2100 Second Street, SW
Washington, DC 20590

Commander
US Army Missile Command
ATTN: DRSMI-RRA, Bldg 7770
Redstone Arsenal, AL 35809

Dir of Dev & Engr
Defense Systems Div
ATTN: SAREA-DE-DDR
H. Tannenbaum
Edgewood Arsenal, APG, MD 21010

Naval Surface Weapons Center
Technical Library & Information
Services Division
White Oak, Silver Spring, MD
20910

Dr. Frank D. Eaton
PO Box 3038
Universtiy Station
Laramie, Wyoming 82071

Rome Air Development Center
ATTN: Documents Library
TILD (Bette Smith)
Griffiss Air Force Base, NY 13441

National Weather Service
National Meteorological Center
World Weather Bldg - 5200 Auth Rd
ATTN: Mr. Quiroz
Washington, DC 20233

USAFETAC/CB (Stop 825)
Scott AFB
IL 62225

Director
Defense Nuclear Agency
ATTN: Tech Library
Washington, DC 20305

Director
Development Center MCDEC
ATTN: Firepower Division
Quantico, VA 22134

Environmental Protection Agency
Meteorology Laboratory
Research Triangle Park, NC
27711

Commander
US Army Electronics Command
ATTN: DRSEL-GG-TD
Fort Monmouth, NJ 07703

Commander
US Army Ballistic Rsch Labs
ATTN: DRXBR-IB
APG, MD 21005

Dir, US Naval Research Lab
Code 5530
Washington, DC 20375

Mil Assistant for
Environmental Sciences
DAD (E & LS), 3D129
The Pentagon
Washington, DC 20301

The Environmental Rsch
Institute of MI
ATTN: IRIA Library
PO Box 618
Ann Arbor, MI 48107

Armament Dev & Test Center
ADTC (DLOSL)
Eglin AFB, Florida 32542

Range Commanders Council
ATTN: Mr. Hixon
PMTC Code 3252
Pacific Missile Test Center
Point Mugu, CA 93042

Commander
Eustis Directorate
US Army Air Mobility R&D Lab
ATTN: Technical Library
Fort Eustis, VA 23604

Commander
Frankford Arsenal
ATTN: SARFA-FCD-0, Bldg 201-2
Bridge & Tarcony Sts
Philadelphia, PA 19137

Director, Naval Oceanography and
Meteorology
National Space Technology Laboratories
Bay St Louis, MS 39529

Commander
US Army Electronics Command
ATTN: DRSEL-CT-S
Fort Monmouth, NJ 07703

Commander
USA Cold Regions Test Center
ATTN: STECR-OP-PM
APO Seattle 98733

Redstone Scientific Information Center
ATTN: DRDMI-TBD
US Army Missile Res & Dev Command
Redstone Arsenal, AL 35809

Commander
AFWL/WE
Kirtland AFB, NM 87117

Naval Surface Weapons Center
Code DT-22 (Ms. Greeley)
Dahlgren, VA 22448

Commander
Naval Ocean Systems Center
ATTN: Research Library
San Diego, CA 92152

Commander
US Army INSCOM
ATTN: IARDA-OS
Arlington Hall Station
Arlington, VA 22212

Commandant
US Army Field Artillery School
ATTN: ATSF-CF-R
Fort Sill, OK 73503

Commander and Director
US Army Engineer Topographic Labs
ETL-GS-AC
Fort Belvoir, VA 22060

Technical Processes Br-D823
NOAA, Lib & Info Serv Div
6009 Executive Blvd
Rockville, MD 20852

Commander
US Army Missile Research
and Development Command
ATTN: DRDMI-CGA, B. W. Fowler
Redstone Arsenal, AL 35809

Commanding Officer
US Army Armament Rsch & Dev Com
ATTN: DRDAR-TSS #59
Dover, NJ 07801

Air Force Cambridge Rsch Labs
ATTN: LCB (A. S. Carten, Jr.)
Hanscom AFB
Bedford, MA 01731

National Center for Atmos Res
NCAR Library
PO Box 3000
Boulder, CO 80307

Air Force Geophysics Laboratory
ATTN: LYD
Hanscom AFB
Bedford, MA 01731

Chief, Atmospheric Sciences Division
Code ES-81
NASA
Marshall Space Flight Center, AL 35812

Department of the Air Force
OL-C, 5WW
Fort Monroe, VA 23651

Commander
US Army Missile Rsch & Dev Com
ATTN: DRDMI-TR
Redstone Arsenal, AL 35809

Meteorology Laboratory
AFGL/LY
Hanscom AFB, MA 01731

Director CFD
US Army Field Artillery School
ATTN: Met Division
Fort Sill, OK 73503

Naval Weapons Center (Code 3173)
ATTN: Dr. A. Shlanta
China Lake, CA 93555

Director
Atmospheric Physics & Chem Lab
Code R31, NOAA
Department of Commerce
Boulder, CO 80302

Department of the Air Force
5 WW/DN
Langley AFB, VA 23665

Commander
US Army Intelligence Center and School
ATTN: ATSI-CD-MD
Fort Huachuca, AZ 85613

Dr. John L. Walsh
Code 4109
Navy Research Lab
Washington, DC 20375

Director
US Army Armament Rsch & Dev Com
Chemical Systems Laboratory
ATTN: DRDAR-CLJ-I
Aberdeen Proving Ground, MD 21010

R. B. Girardo
Bureau of Reclamation
E&R Center, Code 1220
Denver Federal Center, Bldg 67
Denver, CO 80225

Commander
US Army Missile Command
ATTN: DRDMI-TEM
Redstone Arsenal, AL 35809

Commander
US Army Tropic Test Center
ATTN: STETC-MO (Tech Library)
APO New York 09827

Commanding Officer
Naval Research Laboratory
Code 2627
Washington, DC 20375

Defense Documentation Center
ATTN: DDC-TCA
Cameron Station (Bldg 5)
Alexandria, Virginia 22314
12

Commander
US Army Test and Evaluation Command
ATTN: Technical Library
White Sands Missile Range, NM 88002

US Army Nuclear Agency
ATTN: MONA-WE
Fort Belvoir, VA 22060

Commander
US Army Proving Ground
ATTN: Technical Library
Bldg 2100
Yuma, AZ 85364

Office, Asst Sec Army (R&D)
ATTN: Dep for Science & Tech
HQ, Department of the Army
Washington, DC 20310

ATMOSPHERIC SCIENCES RESEARCH PAPERS

1. Lindberg, J.D., "An Improvement to a Method for Measuring the Absorption Coefficient of Atmospheric Dust and other Strongly Absorbing Powders," ECOM-5565, July 1975.
2. Avara, Elton, P., "Mesoscale Wind Shears Derived from Thermal Winds," ECOM-5566, July 1975.
3. Gomez, Richard B., and Joseph H. Pierluissi, "Incomplete Gamma Function Approximation for King's Strong-Line Transmittance Model," ECOM-5567, July 1975.
4. Blanco, A.J., and B.F. Engebos, "Ballistic Wind Weighting Functions for Tank Projectiles," ECOM-5568, August 1975.
5. Taylor, Fredrick J., Jack Smith, and Thomas H. Pries, "Crosswind Measurements through Pattern Recognition Techniques," ECOM-5569, July 1975.
6. Walters, D.L., "Crosswind Weighting Functions for Direct-Fire Projectiles," ECOM-5570, August 1975.
7. Duncan, Louis D., "An Improved Algorithm for the Iterated Minimal Information Solution for Remote Sounding of Temperature," ECOM-5571, August 1975.
8. Robbiani, Raymond L., "Tactical Field Demonstration of Mobile Weather Radar Set AN/TPS-41 at Fort Rucker, Alabama," ECOM-5572, August 1975.
9. Miers, B., G. Blackman, D. Langer, and N. Lorimier, "Analysis of SMS/GOES Film Data," ECOM-5573, September 1975.
10. Manquero, Carlos, Louis Duncan, and Rufus Bruce, "An Indication from Satellite Measurements of Atmospheric CO₂ Variability," ECOM-5574, September 1975.
11. Petracca, Carmine, and James D. Lindberg, "Installation and Operation of an Atmospheric Particulate Collector," ECOM-5575, September 1975.
12. Avara, Elton P., and George Alexander, "Empirical Investigation of Three Iterative Methods for Inverting the Radiative Transfer Equation," ECOM-5576, October 1975.
13. Alexander, George D., "A Digital Data Acquisition Interface for the SMS Direct Readout Ground Station — Concept and Preliminary Design," ECOM-5577, October 1975.
14. Cantor, Israel, "Enhancement of Point Source Thermal Radiation Under Clouds in a Nonattenuating Medium," ECOM-5578, October 1975.
15. Norton, Colburn, and Glenn Hoidale, "The Diurnal Variation of Mixing Height by Month over White Sands Missile Range, N.M.," ECOM-5579, November 1975.
16. Avara, Elton P., "On the Spectrum Analysis of Binary Data," ECOM-5580, November 1975.
17. Taylor, Fredrick J., Thomas H. Pries, and Chao-Huan Huang, "Optimal Wind Velocity Estimation," ECOM-5581, December 1975.
18. Avara, Elton P., "Some Effects of Autocorrelated and Cross-Correlated Noise on the Analysis of Variance," ECOM-5582, December 1975.
19. Gillespie, Patti S., R.L. Armstrong, and Kenneth O. White, "The Spectral Characteristics and Atmospheric CO₂ Absorption of the Ho³⁺:YLF Laser at 2.05 μ m," ECOM-5583, December 1975.
20. Novlan, David J. "An Empirical Method of Forecasting Thunderstorms for the White Sands Missile Range," ECOM-5584, February 1976.
21. Avara, Elton P., "Randomization Effects in Hypothesis Testing with Autocorrelated Noise," ECOM-5585, February 1976.
22. Watkins, Wendell R., "Improvements in Long Path Absorption Cell Measurement," ECOM-5586, March 1976.
23. Thomas, Joe, George D. Alexander, and Marvin Dubbin, "SATTEL — An Army Dedicated Meteorological Telemetry System," ECOM-5587, March 1976.
24. Kennedy, Bruce W., and Delbert Bynum, "Army User Test Program for the RDT&E-XM-75 Meteorological Rocket," ECOM-5588, April 1976.

25. Barnett, Kenneth M., "A Description of the Artillery Meteorological Comparisons at White Sands Missile Range, October 1974 - December 1974 ('PASS' - Prototype Artillery [Meteorological] Subsystem)," ECOM-5589, April 1976.
26. Miller, Walter B., "Preliminary Analysis of Fall-of-Shot From Project 'PASS'," ECOM-5590, April 1976.
27. Avara, Elton P., "Error Analysis of Minimum Information and Smith's Direct Methods for Inverting the Radiative Transfer Equation," ECOM-5591, April 1976.
28. Yee, Young P., James D. Horn, and George Alexander, "Synoptic Thermal Wind Calculations from Radiosonde Observations Over the Southwestern United States," ECOM-5592, May 1976.
29. Duncan, Louis D., and Mary Ann Seagraves, "Applications of Empirical Corrections to NOAA-4 VTPR Observations," ECOM-5593, May 1976.
30. Miers, Bruce T., and Steve Weaver, "Applications of Meteorological Satellite Data to Weather Sensitive Army Operations," ECOM-5594, May 1976.
31. Sharenow, Moses, "Redesign and Improvement of Balloon ML-566," ECOM-5595, June, 1976.
32. Hansen, Frank V., "The Depth of the Surface Boundary Layer," ECOM-5596, June 1976.
33. Pinnick, R.G., and E.B. Stenmark, "Response Calculations for a Commercial Light-Scattering Aerosol Counter," ECOM-5597, July 1976.
34. Mason, J., and G.B. Hoidale, "Visibility as an Estimator of Infrared Transmittance," ECOM-5598, July 1976.
35. Bruce, Rufus E., Louis D. Duncan, and Joseph H. Pierluissi, "Experimental Study of the Relationship Between Radiosonde Temperatures and Radiometric-Area Temperatures," ECOM-5599, August 1976.
36. Duncan, Louis D., "Stratospheric Wind Shear Computed from Satellite Thermal Sounder Measurements," ECOM-5800, September 1976.
37. Taylor, F., P. Mohan, P. Joseph and T. Pries, "An All Digital Automated Wind Measurement System," ECOM-5801, September 1976.
38. Bruce, Charles, "Development of Spectrophones for CW and Pulsed Radiation Sources," ECOM-5802, September 1976.
39. Duncan, Louis D., and Mary Ann Seagraves, "Another Method for Estimating Clear Column Radiances," ECOM-5803, October 1976.
40. Blanco, Abel J., and Larry E. Taylor, "Artillery Meteorological Analysis of Project Pass," ECOM-5804, October 1976.
41. Miller, Walter, and Bernard Engebos, "A Mathematical Structure for Refinement of Sound Ranging Estimates," ECOM-5805, November, 1976.
42. Gillespie, James B., and James D. Lindberg, "A Method to Obtain Diffuse Reflectance Measurements from 1.0 to 3.0 μ m Using a Cary 17I Spectrophotometer," ECOM-5806, November 1976.
43. Rubio, Roberto, and Robert O. Olsen, "A Study of the Effects of Temperature Variations on Radio Wave Absorption," ECOM-5807, November 1976.
44. Ballard, Harold N., "Temperature Measurements in the Stratosphere from Balloon-Borne Instrument Platforms, 1968-1975," ECOM-5808, December 1976.
45. Monahan, H.H., "An Approach to the Short-Range Prediction of Early Morning Radiation Fog," ECOM-5809, January 1977.
46. Engebos, Bernard Francis, "Introduction to Multiple State Multiple Action Decision Theory and Its Relation to Mixing Structures," ECOM-5810, January 1977.
47. Low, Richard D.H., "Effects of Cloud Particles on Remote Sensing from Space in the 10-Micrometer Infrared Region," ECOM-5811, January 1977.
48. Bonner, Robert S., and R. Newton, "Application of the AN/GVS-5 Laser Rangefinder to Cloud Base Height Measurements," ECOM-5812, February 1977.

49. Rubio, Roberto, "Lidar Detection of Subvisible Reentry Vehicle Erosive Atmospheric Material," ECOM-5813, March 1977.
50. Low, Richard D.H., and J.D. Horn, "Mesoscale Determination of Cloud-Top Height: Problems and Solutions," ECOM-5814, March 1977.
51. Duncan, Louis D., and Mary Ann Seagraves, "Evaluation of the NOAA-4 VTPR Thermal Winds for Nuclear Fallout Predictions," ECOM-5815, March 1977.
52. Randhawa, Jagir S., M. Izquierdo, Carlos McDonald and Zvi Salpeter, "Stratospheric Ozone Density as Measured by a Chemiluminescent Sensor During the Stratcom VI-A Flight," ECOM-5816, April 1977.
53. Rubio, Roberto, and Mike Izquierdo, "Measurements of Net Atmospheric Irradiance in the 0.7- to 2.8-Micrometer Infrared Region," ECOM-5817, May 1977.
54. Ballard, Harold N., Jose M. Serna, and Frank P. Hudson Consultant for Chemical Kinetics, "Calculation of Selected Atmospheric Composition Parameters for the Mid-Latitude, September Stratosphere," ECOM-5818, May 1977.
55. Mitchell, J.D., R.S. Sagar, and R.O. Olsen, "Positive Ions in the Middle Atmosphere During Sunrise Conditions," ECOM-5819, May 1977.
56. White, Kenneth O., Wendell R. Watkins, Stuart A. Schleusener, and Ronald L. Johnson, "Solid-State Laser Wavelength Identification Using a Reference Absorber," ECOM-5820, June 1977.
57. Watkins, Wendell R., and Richard G. Dixon, "Automation of Long-Path Absorption Cell Measurements," ECOM-5821, June 1977.
58. Taylor, S.E., J.M. Davis, and J.B. Mason, "Analysis of Observed Soil Skin Moisture Effects on Reflectance," ECOM-5822, June 1977.
59. Duncan, Louis D. and Mary Ann Seagraves, "Fallout Predictions Computed from Satellite Derived Winds," ECOM-5823, June 1977.
60. Snider, D.E., D.G. Murcray, F.H. Murcray, and W.J. Williams, "Investigation of High-Altitude Enhanced Infrared Background Emissions" (U), SECRET, ECOM-5824, June 1977.
61. Dubbin, Marvin H. and Dennis Hall, "Synchronous Meteorological Satellite Direct Readout Ground System Digital Video Electronics," ECOM-5525, June 1977.
62. Miller, W., and B. Engebos, "A Preliminary Analysis of Two Sound Ranging Algorithms," ECOM-5826, July 1977.