

AD-A052 753

WISCONSIN UNIV-MADISON DEPT OF INDUSTRIAL ENGINEERING

F/6 5/8

DYNAMICS OF THE EYE AND HEAD DURING MOVEMENT BETWEEN DISPLAYS: --ETC(U)

FEB 78 G H ROBINSON

N00014-75-C-0364

NL

UNCLASSIFIED

TR-78-2

1 OF 1
AD
A052753

END
DATE
FILMED
5-78

DDC

g

**DEPARTMENT OF
INDUSTRIAL ENGINEERING**

12

AD A 052753

AD No. _____
DDC FILE COPY



DDC
RECEIVED
APR 17 1978
D

**UNIVERSITY OF
WISCONSIN-MADISON**

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

ACCESSION for	
NTIS	Write Section ☒
DDO	Out Section ☐
UNANNOUNCED	☐
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

12

Human Systems Program

Dynamics of the Eye and Head During
Movement Between Displays: A
Qualitative and Quantitative
Guide for Designers

by

Gordon H. Robinson

~~1726-~~
January 1978

Tech Rep TR-78-2

*Department of Industrial Engineering
The University of Wisconsin-Madison*

Support for this research was provided by the
Engineering Psychology Programs, Office of Naval Research
Contract N00014-75-C-0364
Work Unit NR 197-028

Reproduction in whole or part permitted for any
purpose of the U.S. Government

DDC
RECEIVED
APR 17 1978
D

Approved for public release; distribution unlimited

unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TR-78-2	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) DYNAMICS OF THE EYE AND HEAD DURING MOVEMENT BETWEEN DISPLAYS: A QUALITATIVE AND QUANTITATIVE GUIDE FOR DESIGNERS.		5. TYPE OF REPORT & PERIOD COVERED Technical Report.
7. AUTHOR(s) Gordon H./Robinson		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Board of Regents of the University of Wisconsin System; 750 University Ave. Madison, Wisconsin 53706		8. CONTRACT OR GRANT NUMBER(s) N00014-75-C-0364
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Arlington, Virginia 22217		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 197-028 12/29p.
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of Naval Research Branch Office 536 S. Clark Street, Room 286 Chicago Chicago, Illinois 60605		12. REPORT DATE February 1, 1978 13. NUMBER OF PAGES 204/1 Feb 78
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		15. SECURITY CLASS. (of this report) unclassified
15a. DECLASSIFICATION/DOWNGRADING SCHEDULE		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Eye and head movement, display design		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The purpose of this paper is to provide a designer or systems analyst a guide to human performance limitations in vision when fixation must be redirected from one display to another. The focus is on large angular separation (greater than 20 degrees) and on tasks wherein speed is of importance. Patterns of eye and head movements are shown; as well as quantitative data on		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 68 IS OBSOLETE
S/N 0102-014-6601

unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

408 848

SM

unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

cont

saccades, periods of eye/head compensation, and head movement. Independent variables include inter-display angle, display visibility, operator's knowledge of display location, and some relevant characteristics of a possible task which must be interrupted for the refixation. Inter and intra subject variability is also presented.

unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

Dynamics of the Eye and Head During Movement Between Displays:
A Qualitative and Quantitative Guide for Designers

GORDON H. ROBINSON, Dept. of Industrial Engineering,
University of Wisconsin, Madison.

ABSTRACT

The purpose of this paper is to provide a designer or systems analyst a guide to human performance limitations in vision when fixation must be redirected from one display to another. The focus is on large angular separation (greater than 20 degrees) and on tasks wherein speed is of importance. Patterns of eye and head movements are shown; as well as quantitative data on saccades, periods of eye/head compensation, and head movement. Independent variables include inter-display angle, display visibility, operator's knowledge of display location, and some relevant characteristics of a possible task which must be interrupted for the refixation. Inter and intra subject variability is also presented.

INTRODUCTION AND SETTING

This paper describes the dynamics of the eye and head as vision is redirected from one fixation point to another. The purpose is to provide a qualitative framework and quantitative performance data that will assist a designer in predicting operator performance in tasks requiring such refixations. Common tasks include monitoring large instrument panels and controlling complex vehicles. The data here will probably be of most interest in "speeded" tasks, where fractions of a second may be important, and with those displays separated by larger angles (20 degrees or more). Perhaps the most universally appreciated example, in the US at least, would be the visual dynamics involved when driving an automobile and merging from an on-ramp onto a busy freeway. The time required here to move visual fixation from ahead, back to a possible traffic gap, and to return will often exceed the time gap to the vehicle ahead.

SCOPE

Each visual refixation involves a decision to leave the original display, programming the initial movements of the eye and possibly head, neural and muscular reaction times, the pattern of eye and head movements necessary to acquire the new display, and the subsequent processing of the new display. Many tasks, such as vehicle control, also require the rapid return of fixation to the first display, where it may provide information used in continuous control.

This paper will not concern itself with the decision to seek the second display nor the information processing that may go on after it has been acquired. It will be concerned with the total pattern of eye and head movements that follow such a decision and with visual acquisition of the second display. This decoupling of these three phases seems theoretically reasonable and has been demonstrated in the laboratory (Robinson, Koth, and Ringenbach, 1976).

The paper will also indicate, in as quantitative a manner as possible, the effects of common systems variables including display spacing and visibility, operator's prior knowledge of display location, and characteristics of the initial display which affect the dynamic pattern. An approximation of the range of individual differences and intra-person variability will be given, where known.

SOME RELEVANT FEATURES OF THE EYE

It is useful to have a rough model of the eye in mind when attempting to use the ideas and data to be presented. Some important features will be presented briefly. (Numerous books are available on the general anatomical and physiological features of the human eye if the reader wants a more complete picture.)

The important feature of the human eye is the relatively small angular region within which there is useful visual acuity. This property derives from the function and spatial distribution of the two photoreceptors found in the eye. The "cones," responsible for acuity (detail) and color perception are located as shown in figure 1.

The "rods" are distributed outside the dense cone area and are responsible for detection of peripheral displays of interest which may then be acquired by the cone region (fovea) for detailed perception.

The resulting central (foveal) angle through which practical processing can occur is related to target size, brightness, and contrast. Commonly presented acuity data can be misleading here in that it is reflective of minimal, threshold conditions and is difficult to relate to displays of size and visibility in common use. Figure 1 illustrates this issue, showing both an acuity function and illustrative data on readability of a common digital display. Note, for example, that this specific display would be correctly identified at greater than a 50 percent level up to 40 degrees from the fovea.

In most situations fixation is close to the item being processed, usually within 2 or 3 degrees. It must be anticipated, however, that if time is of importance the operator may process the visual data with a fixation point that can be as much as 10 degrees from a highly visible display. This discrepancy will assist in speeding return to the original display.

Visual redirection is accomplished by coordinated movements of the eyes and by movements of the head and body if necessary. Four control systems for eye movement have been identified, corresponding to: 1) rapid movement to acquire a new display--saccadic movement; 2) slower, pursuit movement to follow a moving display; 3) opposed movements of the two eyes to focus on objects at close range; and 4) compensatory movements of the eyes equal

and opposite to head movements to maintain stationary fixation for visual perception during head movement. (Discussion of dynamic properties of these four systems can be found in Robinson, D. A., 1968). Concern here will be with movements between stationary displays at approximately equal depths and therefore with the use of systems "1" and "4" only.

It is generally agreed that little if any visual processing occurs during a saccade, although the mechanism for this suppression is not yet clear. (Matin, 1974 provides a review and discussion of this issue.) Visual processing can and does take place during the eye/head compensation movements (Data and discussions of this issue appear in London, Nelson and Robinson, 1978 and in Bartz, 1978.)

Movement of the head, necessary for visual redirection beyond about 40 degrees, has not been studied extensively. Most eye movement research has fixed the head to allow more precise eye measurement. Care must be taken when applying these data in real-life situations where the head is free to move. The initial eye/head compensation patterns to be discussed in the Reaction Time section and occasionally reported overshoots of saccadic movements are both qualitatively different whether the head is free or not. In fact, it is reasonably easy to inhibit head movement by instruction and care must therefore be taken in laboratory measurements if they are to be extrapolated to normal, free head situations. (Bizzi, 1974 and Robinson, Koth, and Ringenbach, 1976 discuss eye/head coordination data.)

DYNAMIC PATTERNS OF EYE AND HEAD MOVEMENT

Two distinct time periods appear in the dynamic patterns of eye and head movement during wide angle refixation: 1) a reaction time (latency) between the command to refixate and the first movement of the eye and 2) an interval containing saccades, head movement, and eye/head compensatory movements leading to visual acquisition of the new display. Reaction time is affected by a number of variables and will be discussed in the following section. The qualitative movement pattern appears to be mainly related to three task variables: 1) angle of refixation, 2) new display's visibility, and 3) prior knowledge of the location of the new display. These three variables interact in ways related to limitations in peripheral vision, maximum extent of saccadic movements, and requirements for head movement. Figures 2, A through F, show illustrative qualitative changes related to these variables.

Fig 2A shows movement to a bright (clearly visible at initial location), certain location display at 30 degrees (from the initial display). One saccade of the correct extent is made, with no corresponding head movement. Since the original display is for a continuous control task it is returned to as rapidly as possible. Fig 2B shows the change that occurs with the same new display at 60 degrees. Head movement, with lower velocity and slightly delayed, is programmed along with the saccade. The new display is acquired only when the sum of the eye and head positions are at approximately 60 degrees. The length of the saccade in this illustration is typical of maximum lengths seen.

Fig 2C shows a 30 degree response with the displays spatial location (in the horizontal plane) unknown in advance (from among nine possible locations). There is no head movement and two distinct saccades occur, with a period of stationary fixation between them. In this case, even though the new display was bright enough to be seen easily from the original fixation point, prior uncertainty as to its location led to a less than adequate first saccade and a delay necessary to program and execute a second saccade of the correct amplitude. (The correct display was the only one lighted.)

Fig 2D shows movement to a 30 degree display that is both dim (cannot be detected at a 50 percent level at 30 degrees) and of uncertain location. Here, the lack of knowledge of the display's location, either from instructions or adequate brightness, led the operator to initiate head movement. (Many possible displays were beyond 40 degrees and thus would have required head movement.) A new phenomenon here is the occurrence of a period of "dynamic fixation," or eye/head compensation between the two saccades. During this period, of approximately 150 msec, the eye moves back toward center with a velocity precisely matching the corresponding head velocity and thus keeping fixation stationary. In this case fixation was on the 20 degree display, a possible display that was then rejected with the execution of the second saccade to the 30 degree, correct display. This response also illustrates eye/head compensation after display acquisition, during which the eye returns to its central position while the head assumes almost all of the angle

needed for display processing. This will occur more frequently if the display must be viewed for more than a few hundred milliseconds or if there is prior knowledge by the operator that the next display to be viewed is in another direction (not simply a return to the first as is illustrated here). Return of the eye to its central position is a rational control action since it provides maximum flexibility for subsequent saccadic movements.

Fig 2E shows a complex interposition of four saccades and three dynamic fixation (compensation) periods as a 60 degree display that is dim and of uncertain location is sought. Apparent fixations occur at the 20, 30, and 50 degree potential displays before the correct display is finally acquired.

Fig 2F shows the complexity that can occur if a dim display of uncertain location is at 90 degrees. Here there are seven fairly distinct saccades between six periods of dynamic fixation, including one decision to check a possible display location that had been bypassed by the initial saccade. This reversal decision also led to a temporary termination of head movement.

In all cases return to the original display was accomplished with one large saccade and appropriate head movement. The original display was comparatively bright and, of course, at a well-known location.

Figures 3 A and B show the systematic increase in both number of saccades and time for the total pattern of movements as a function of the three variables discussed above: 1) angle, 2) visibility (bright and dim), and 3) location certainty. (These data were taken

from Robinson and Rath, 1976.) The similarity in form of these two measures reflects the fact that the time taken by each saccade and its succeeding dynamic fixation period is relatively constant.

REACTION TIME OF THE EYE

Prior to recent work it was widely agreed that reaction time for the eye (occularmotor latency) ranged from 150 to 200 msec and was minimally affected by most task variables such as display angle or visibility. (Robinson, Koth and Ringenbach, 1976, provide a brief overview of this position, including possible effects of alcohol [slight increase] and information processing after re-fixation [no effect].)

Interest in a more valid simulation of vehicle control led the author to construct a paradigm wherein an ongoing, continuous control task must be interrupted for the visual redirection to the peripheral display. This paradigm would seem to have fair generality. In systems where the operator is not engaged in continuous control they are, most likely, engaged in something when the command to refixate is received. Subsequent data shows that "something" need be very little to substantially increase reaction time.

"Interrupting something" has both quantitative and qualitative effects on the processes between command and first saccadic eye movement. The quantitative results show that the "classical" 150 to 200 msec result is unlikely in realistic settings and appears

to be the result of a laboratory paradigm with the features:

1) simple, meaningless fixation light being extinguished as the command; 2) known location, clearly visible target; and 3) highly practiced, repetitive trials. In contrast, eye reaction times can reach 700 msec if an interrupted manual control task is felt to be more important than the peripheral display. Simply having the target appear randomly on the right or left--with the viewer knowing in advance which direction--can increase the reaction time to 350 msec. If the direction is not instructed in advance, and is presented symbolically as the command signal, the time will increase to approximately 500 msec. In neither of these cases is an ongoing task interrupted. If, on the other hand, there is an ongoing control task then the 350 msec will increase to 450 msec and the 500 will increase to 650 msec.

In summary, following a command to refixate the minimum delay is about 300 msec. Increases to 700 msec can result from combinations of directional uncertainty, symbolic as opposed to geometric (direct spatial) indicators of direction, and especially the existence and assumed importance of the ongoing or interrupted task. (This would not include the case where the operator might choose to delay refixation until satisfied with the status of ongoing control. Cases of this sort could be constructed wherein the operator might choose to wait 10 seconds--or 10 minutes!)

The qualitative change noted when a continuous task is interrupted is the occasional occurrence of a period of eye/head compensatory movement prior to the first saccade toward the new display.

This behavior is rational since it permits the slower head to begin movement toward the new display, while the eye moves in the opposite direction and maintains fixation on the original display. This initial compensatory period, when it occurs, delays the eventual onset of the first saccade by 100 to 200 msec. The angle through which the compensatory movement occurs is usually less than 15 degrees and often only 5 or 10 degrees. Recent data in the author's laboratory indicate that some people compensate with the new display on the right or left side, some on one side only, and some never compensate. This would seem, therefore, to represent a learned phenomenon, albeit at a non-conscious level. Whether operators could be trained to use this strategy is not clear.

(This same phenomenon has been observed in an automobile on the highway by Mourant and Grimson, 1977, who speculate that it may be a learned skill.) (A complete analysis of eye/head reaction time under these "realistic," engineering systems conditions is presented in Nelson, London and Robinson, 1978.)

It is appropriate to inquire as to the information processing relationship between the selection and programming functions for the eye and head going on during this reaction time and the processing of the display being interrupted. The question of overlap of these functions arises in relation to information processing theory and specifically to the limitations that may be imposed by the "single-channel" concept. No studies have yet directly examined this particular information processing issue. Two lines of evidence

from the author's laboratory are relevant: 1) the longer reaction times when an ongoing task is interrupted (discussed above) and 2) the lack of evidence of any important deterioration in the continuous control performance during this period. In this case, it is possible that the requisite eye/head programming decisions are simply "squeezed in" during fairly quiescent control intervals. Some overlap would be predicted from the current theoretical position in that programming a saccade is a highly practiced task. Highly practiced tasks require little decision or memory capacity and may overlap other tasks. (An excellent introduction to human information processing and skill, with a distinct bias toward application, can be found in Welford, 1976.)

CHARACTERISTICS OF SACCADDES

Saccades appear to represent a set of pre-programmed dynamic responses over which no effective control can be instituted once movement is initiated. Selection appears to consist only of a choice of the saccade's amplitude and direction but not of its velocity characteristics. For each individual a 20 degree saccade to the right will be remarkably stable in its average dynamic profile and will not be affected by any task variable outside those that might have major effects on all muscle systems. Referring to the range of variables illustrated in Fig 2, it is apparent that the individual saccades of the same extent are essentially the

same over all conditions examined. Similarly, other variables such as motivation or preceived task importance have little if any effect on saccadic properties.

Typical position and velocity profiles for 25 and 40 degree saccades are shown in Fig 4. (Possible mechanisms and control systems producing these patterns are discussed by Robinson, D. A., 1968; Westheimer, 1954 a and b; and Yarbus, 1967.)

The control mechanism is not linear, with the important non-linearity for our purposes being a limited maximum velocity for saccades over about 20 degrees. This velocity is approximately 550 deg/sec, with college age people varying between 500 and 600 deg/sec. An individual will vary from one saccade to the next with a standard deviation of about 200 deg/sec.

A smaller saccade of 10 degrees will have a maximum velocity of 300 to 400 deg/sec. The average velocity for a 550 deg/sec maximum is about 300 deg/sec. Therefore, a 20 degree saccade will take approximately 67 msec and one of 40 degrees roughly double that, or 135 msec.

For refixations up to about 20 degrees one saccade will usually be executed. Between 20 and 40 degrees either one, or two saccades may occur. If there are two they appear to be programmed in advance and little time (less than 25 msec) will occur between them. For refixations over 40 degrees one or two saccades will be made out to a maximum extent of about 45 degrees where further travel must await movement of the head.

DYNAMIC FIXATION PERIODS

When the display location is not known in advance, and is not sufficiently visible in the periphery, saccades may be made to the possible display locations. If there is no corresponding head movement, as in Fig 2C, the eye will simply remain stationary until a subsequent saccade can be executed. However, if head movement has been initiated, it is necessary for the eye to compensate for that continuing movement in order to hold a stationary fixation. These periods of dynamic fixation are shown in Fig 2 D, E and F.

Although the eye is capable of compensating for head velocities up to 300 deg/sec, head movement may be slower during conditions favoring dynamic fixation periods. Values of head (and thus eye) velocities are typically in the range of 50 to 100 deg/sec. These periods last for 150 to 200 msec.

Two processes occur simultaneously during dynamic fixation periods: 1) fixation is stabilized for visual processing, and 2) the eye returns towards its central position, thereby allowing further large saccades.

The 150-200 msec time is minimum for simple rejection of a clear non-display. If determination of the correctness of a display required complex discrimination or choice then these processes would require more time than the 150-200 msec minimum. It appears that whatever processing is taking place in discriminating and rejecting the non-display is occurring to a large extent in

parallel with the programming of the subsequent saccade; a situation similar to that noted above for the programming of the initial saccade (Reaction Time section).

HEAD MOVEMENT

Movement of the head may occur for any of three purposes:

- 1) the new display is located beyond the range of eye movement only (about 45 degrees);
- 2) the display to be processed will be retained, visually, for more than a fraction of a second; or
- 3) movement to other displays (not back to the point of beginning) is anticipated.

For the first purpose the head will usually begin its movement before the termination of the first saccade, indicating that both are programmed in advance. The delay of the head after the initial saccade will range from 0 to 50 msec. The initial eye/head compensation period discussed under "Reaction Time," above, is an exception. When this behavior occurs the head will move 100 to 200 msec before the first saccade.

Head movements for the second and third reasons noted above have not been studied but, in any event, their presence probably does not affect overall performance times.

Head movement may occur with displays as close as 20 degrees but will not be frequent until about 30 and 40 degrees. Head movement will occur in almost 100 percent of all refixations over 45 degrees.

Average head velocities are shown in Fig 5 as a function of the same variables presented in Figures 3, A and B: 1) angle, 2) visibility, and 3) location certainty (data from London, Nelson, and Robinson, 1978). Displays bright enough to be detected prior to initiation of movement, or displays of certain location yield a linear increase in velocity with target angle. (This same linearity was shown by Robinson, Roth and Ringenback [1976] for maximum head velocity, up to 100 degrees). In all probability the velocities after 100 degree inter-display angles will level off. D. A. Robinson (1968) reports maximum (possible) head velocities of 300 deg/sec.

Displays of uncertain location, and insufficiently visible to be seen until fixation is within a few degrees, will not show the increase in velocity with angle (curve "D, U" in Fig 5).

The relatively large inter-subject difference reported by Robinson, Koth and Ringenback (1976) for maximum head velocities do not appear for average head velocities, which show a standard deviation over college age subjects of about 30 deg/sec.

Variability (standard deviation) within subjects averages to about 25 deg/sec for the DC, BC, BU data and 16 deg/sec for the DU condition (reference to Figs. 2 and 3). (The concerns expressed by Robinson, Koth, and Ringenback (1976) over the unpredictability of head velocities may have been related to their use of maximum values and due to the small subject population in their second experiment.)

DIRECTION OF REQUIRED REFIXATION

Little evidence is available on performance changes in eye or head movements as a function of direction of movement. Almost all wide angle research has been in or very near the horizontal plane. Yarbus (1967) suggests that the shape of a saccade may change slightly as they are directed in angles off the horizontal but he does not note any velocity differences. Measurements in the author's laboratory have indicated no differences in the reaction time for saccadic movement for any angle from horizontal to vertical. The lack of comment on this issue can probably be taken as indicating little effect, at least for small vertical angles. Larger vertical angles would require quite different head movement than horizontal ones. Since the maximum head velocities seen for most refixations are well below the maximum attainable head velocity there is little reason to assume that head dynamic behavior off of the horizontal plane is importantly different from that seen on the horizontal plane.

REFERENCES

1. Bartz, A. E. Information transmission during eye movements. Human Factors. (to appear).
2. Bizzi, E. The coordination of eye-head movements. Scientific American, Oct. 1974, 23, 100-106.
3. London, R. M., Bice, K. C., and Robinson, G. H. Eye-Head Compensatory Movements Prior to Leaving One Display to Acquire Another. (to appear) 1978.
4. London, R. M., Nelson, C. L., and Robinson, G. H. Periods of Dynamic Fixation When Searching for a New Display at an Uncertain Location. (to appear) 1978.
5. Matin, E. Saccadic suppression: A review and an analysis. Psychological Bulletin, 1974, 81, 899-917.
6. Mourant, R. R. and Grimson, C. G. Predictive head-movements during automobile mirror-sampling. Perceptual and Motor Skills, 1977, 44, 283-286.
7. Nelson, C. L., London, R. M., Bond, J. R., and Robinson, G. H. Effects of information processing requirements on reaction time of the eye. (to appear) 1978.
8. Robinson, D. A. Eye movement control in primates. Science, 1968, 161, 1219-1224.
9. Robinson, G. H., Koth, B. W., and Ringenback, J. P. Dynamics of the eye and head during an element of visual search. Ergonomics, 1976, 19, 691-709.

10. Robinson, G. H. and Rath, J. R. Dynamics of the eye and head when switching visual attention between two tasks.
Madison: Dept. of Industrial Engineering, the University of Wisconsin, Technical Report TR 76-18, 1976.
11. Welford, A. T. Skilled Performance: Perceptual and Motor Skills.
Glenview, Ill.: Scott, Foresman and Co., 1976.
12. Westheimer, G. Eye movement response to a horizontally moving visual stimulus. American Medical Assoc. Archives of Ophthalmology, 1954b, 52, 932-941.
13. Westheimer, G. Mechanisms of saccadic eye movements. American Medical Assoc. Archives of Ophthalmology, 1954a, 52, 710-724.
14. Yarbus, A. L. Eye Movements and Vision. New York: Plenum Press, 1967.




Figure 1

Distribution of Cones, Relative Visual Acuity, and Identification of a Digital Display as a Function of Degrees from the Fovea (Acuity and density data from Woodson, W. E. and Conover, D. W., Human Engineering Guide, Berkeley, Calif.: Univ. of California Press, 1964, 2nd Edit.; identification data from Koth, B. W. and Robinson, G. H., Peripheral discriminability of one-plane, rear-projection displays. Tech Rep 74-1, Dept. of Ind. Engr., University of Wisconsin, Madison, 1974.)




Figure 2

Eye and Head Responses to Commands to Refixate and Thereby Interrupt a Manual Control Task. (A) 30 deg, bright, certain location; (B) 60 deg, bright, certain location; (C) 30 deg, bright, uncertain location; (D) 30 deg, dim, uncertain location; (E) 60 deg, dim, uncertain location; and (F) 90 deg, dim, uncertain location. Command at $t = 0$. E - Eye, H - Head, F - Fixation. (Some responses begin at other than 0 deg, indicating the status of the display for the manual control task.) All displays at one meter distance in horizontal plane.




Figure 3

Number of Saccades (A) and Time Between Initiation of First Saccade and Subsequent Acquisition of the Next Display (B) as a Function of Inter-Display Angle. Display bright (B) or dim (D) and with known location (C) or unknown location (U). (Same parameters as in Fig 2.)




Figure 3




Figure 4

Illustrative Position and Velocity Patterns for a 25 Degree and 40 Degree Saccade. (One trial with one subject.)




Figure 5

Average Head Velocity as a Function of Inter-Display Angle. Display bright (B) or dim (D) and with known location (C) or unknown location (U). (Same parameters as in Fig 2 and 3.)

OFFICE OF NAVAL RESEARCH, CODE 455
TECHNICAL REPORTS DISTRIBUTION LIST

Director, Engineering Psychology
Programs, Code 455
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217 (5 cys)

Defense Documentation Center
Cameron Station
Alexandria, CA 22314 (12 cys)

Dr. Robert Young
Director, Cybernetics Technology Office
Advanced Research Projects Agency
1400 Wilson Blvd
Arlington, VA 22209

Col. Henry L. Taylor, USAF
OAD(E&LS) ODDR&E
Pentagon, Room 3D129
Washington, D.C. 20301

Office of Naval Research
International Programs
Code 102IP
800 North Quincy Street
Arlington, VA 22217 (6 cys)

Director, Electromagnetics Technology
Programs, Code 221
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

Director, Weapons Technology
Programs, Code 212
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

Director, Physiology Program
Code 441
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

Commanding Officer
ONR Branch Office
ATTN: Dr. J. Lester
495 Summer Street
Boston, MA 02210

Commanding Officer
ONR Branch Office
ATTN: Dr. Charles Davis
536 South Clark Street
Chicago, IL 60605

Commanding Officer
ONR Branch Office
ATTN: Dr. E. Gloye
1030 East Green Street
Pasadena, CA 91106

Dr. Bruce McDonald
Office of Naval Research
Scientific Liaison Group
American Embassy, Room A-407
APO San Francisco 96503

Director, Naval Research Laboratory
Technical Information Division
Code 2627
Washington, D.C. 20375 (6 cys)

Mr. John Hill
Naval Research Laboratory
Code 5707.40
Washington, D.C. 20375

Mr. Arnold Rubinstein
Naval Material Command
NAVMAT 0344
Department of the Navy
Washington, D.C. 20360

Commander
Naval Air Systems Command
Human Factors Programs, AIR 340F
Washington, D.C. 20361

Commander Naval Air Systems Command
Crew Station Design, AIR 5313
Washington, D.C. 20361

Mr. T. Momiyama
Naval Air Systems Command
Advance Concepts Division, AIR 03P34
Washington, D.C. 20361

Commander
Naval Electronics Systems Command
Human Factors Engineering Branch
Code 4701
Washington, D.C. 20360

LCDR T. W. Schropp
Naval Sea Systems Command
NAVSEA 00C-DA
Washington, D.C. 20362

Mr. James Jenkins
Naval Sea Systems Command
Code 06H1-3
Washington, D.C. 20362

Dr. James Curtin
Naval Sea Systems Command
Personnel & Training Analyses Office
NAVSEA 074C1
Washington, D.C. 20362

LCDR R. Gibson
Bureau of Medicine & Surgery
Aerospace Psychology Branch
Code 513
Washington, D.C. 20372

CDR Paul Nelson
Naval Medical R&D Command
Code 44
Naval Medical Center
Bethesda, MD 20014

Director
Behavioral Sciences Department
Naval Medical Research Institute
Bethesda, MD 20014

Dr. George Moeller
Human Factors Engineering Branch
Submarine Medical Research Laboratory
Naval Submarine Base
Groton, CT 06340

Chief, Aerospace Psychology Division
Naval Aerospace Medical Institute
Pensacola, FL 32512

Mr. Phillip Andrews
Naval Sea Systems Command
NAVSEA 0341
Washington, D.C. 20362

Bureau of Naval Personnel
Special Assistant for Research
Liaison
PERS-OR
Washington, D.C. 20370

Naval Personnel Research and
Development Center
Management Support Department
Code 210
San Diego, CA 92152

Dr. Fred Muckler
Navy Personnel Research and
Development Center
Manned Systems Design, Code 311
San Diego, CA 92152

Mr. A. V. Anderson
Navy Personnel Research and
Development Center
Code 302
San Diego, CA 92152

LCDR P. M. Curran
Human Factors Engineering Branch
Crew System Department, Code 4021
Naval Air Development Center
Johnsville
Warminster, PA 18950

LCDR William Moroney
Human Factors Engineering Branch
Code 1226
Pacific Missile Test Center
Point Mugu, CA 93042

Mr. Ronald A. Erickson
Human Factors Branch
Code 3175
Naval Weapons Center
China Lake, CA 93555

Human Factors Section
Systems Engineering Test Directorate
U.S. Naval Air Test Center
Patuxent River, MD 20670

Dr. John Silva
Man-System Interaction Division
Code 823, Naval Ocean Systems Center
San Diego, CA 92152

Human Factors Engineering Branch
Naval Ship Research and Development
Center, Annapolis Division
Annapolis, MD 21402

Dr. Robert French
Naval Ocean Systems Center
San Diego, CA 92132

Dr. Jerry C. Lamb
Display Branch
Code TD112
Naval Underwater Systems Center
New London, CT 06320

Naval Training Equipment Center
ATTN: Technical Library
Orlando, FL 32813

Human Factors Department
Code N215
Naval Training Equipment Center
Orlando, FL 32813

Dr. Gary Poock
Operations Research Department
Naval Postgraduate School
Monterey, CA 93940

Dr. A. L. Slafkosky
Scientific Advisor
Commandant of the Marine Corps
Code RD-1
Washington, D.C. 20380

Mr. J. Barber
Headquarters, Department of the
Army, DAPE-PBR
Washington, D.C. 20546

Dr. Joseph Zeidner
Director, Organization and
Systems Research Laboratory
U.S. Army Research Institute
5001 Eisenhower Avenue
Alexandria, VA 22333

Dr. Edgar M. Johnson
Organization and Systems
Research Laboratory
U.S. Army Research Institute
5001 Eisenhower Avenue
Alexandria, VA 22333

Technical Director
U.S. Army Human Engineering Labs
Aberdeen Proving Ground
Aberdeen, MD 21005

U.S. Army Aeromedical Research Lab
ATTN: CPT Gerald P. Krueger
Ft. Rucker, Alabama 36362

U.S. Air Force Office of Scientific
Research
Life Sciences Directorate, NL
Bolling Air Force Base
Washington, D.C. 20332

Dr. Donald A. Topmiller
Chief Systems Engineering Branch
Human Engineering Division
USAD AMRL/HES
Wright-Patterson AFB, OH 45433

Lt. Col. Joseph A. Birt
Human Engineering Division
Aerospace Medical Research Laboratory
Wright Patterson AFB, OH 45433

Air University Library
Maxwell Air Force Base, AL 36112

Dr. Robert Williges
Human Factors Laboratory
Virginia Polytechnic Institute
130 Whittemore Hall
Blacksburg, VA 24061

Dr. W. S. Vaughan
Oceanautics, Inc.
422 6th Street
Annapolis, MD 21403

Dr. Alphonse Chapanis
The John Hopkins University
Department of Psychology
Charles & 34th Streets
Baltimore, MD 21218

Dr. Arthur I. Siegel
Applied Psychological Services, Inc.
404 East Lancaster Street
Wayne, PA 19087

Dr. Robert R. Mackie
Human Factors Research, Inc.
Santa Barbara Research Park
6780 Cortona Drive
Goleta, CA 93017

Dr. Gershon Weltman
Perceptronics, Inc.
6271 Variel Avenue
Woodland Hills, CA 91364

Dr. Edward R. Jones
McDonnell-Douglas Astronautics
Company-EAST
St. Louis, MO 63166

Dr. J. A. Swets
Bolt, Beranek, and Newman, Inc.
50 Moulton Street
Cambridge, MA 02138

Dr. Ross L. Pepper
Naval Ocean Systems Center
Hawaii Laboratory
P.O. Box 997
Kailua, Hawaii 96734

Dr. Meredith Crawford
5606 Montgomery Street
Chevy Chase, MD 20015

Dr. Thomas L. Harrington
University of Nevada
Department of Psychology
Reno, NV 89507

Dr. Robert G. Pachella
University of Michigan
Department of Psychology
Human Performance Center
330 Packard Road
Ann Arbor, MI 48104

Dr. Robert Fox
Vanderbilt University
Department of Psychology
Nashville, TN 37240

Dr. Jesse Orlansky
Institute for Defense Analyses
400 Army-Navy Drive
Arlington, VA 22202

Dr. Stanley Deutsch
Office of Life Sciences
HQS, NASA
600 Independence Avenue
Washington, D.C. 20546

Journal Supplement Abstract Service
American Psychological Association
1200 17th Street, N.W.
Washington, D.C. 20036 (3 cys)

Dr. William A. McClelland
Human Resources Research Office
300 N. Washington Street
Alexandria, VA 22314

Dr. William R. Uttal
University of Michigan
Institute for Social Research
Ann Arbor, MI 48106

Dr. David J. Getty
Bolt, Beranek & Newman
50 Moulton Street
Cambridge, MA 02139

Dr. Richard R. Rosinski
University of Pittsburgh
Department of Information
Science
Pittsburgh, PA 15260

Director, Human Factors Wing
Defence & Civil Institute of
Environmental Medicine
Post Office Box 2000
Downsville, Toronto, Ontario
CANADA

Dr. A. D. Baddeley
Director, Applied Psychology Unit
Medical Research Council
15 Chaucer Road
Cambridge, CB2 2EF
ENGLAND