

MEMORANDUM REPORT ARBRL-MR-02824

(Supersedes IMR No. 581)

FLIGHT TESTS FOR PROTOTYPE FELT WEDGE/WHITE
PHOSPHOROUS IMPROVED SMOKE CONCEPT

W. P. D'Amico
W. H. Clay

TECHNICAL
LIBRARY

April 1978



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

DTIC QUALITY INSPECTED 8

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.*

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-02824	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) FLIGHT TESTS FOR PROTOTYPE FELT WEDGE/WHITE PHOSPHOROUS IMPROVED SMOKE CONCEPT		5. TYPE OF REPORT & PERIOD COVERED Final
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) W.P. D'Amico W.H. Clay		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Ballistic Research Laboratory (ATTN: DRDAR-BLL) Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS RDT&E 1W663608DE82
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory (ATTN: DRDAR-BL) Aberdeen Proving Ground, MD 21005		12. REPORT DATE APRIL 1978
		13. NUMBER OF PAGES 28
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution limited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES This Memorandum Report supersedes IMR No. 581 dated November 1977.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) White Phosphorous Liquid Payloads Flight Stability		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Four 155mm prototype felt-wedge/phosphorous payload projectiles were tested for flight stability at Charge 4 from an M109A1 weapon. A simulant for liquid white phosphorous was used during this test conducted at Aberdeen Proving Ground, MD. Launch disturbances up to 12.5 degrees were induced. The four projectiles were stable.		

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	5
I. INTRODUCTION	7
II. BACKGROUND	7
III. TEST PROGRAM	8
IV. DISCUSSION	9
V. CONCLUSION	10
REFERENCES	26
DISTRIBUTION LIST	27

LIST OF ILLUSTRATIONS

Figure	Page
1. Felt Wedge Concept.	13
2. XM761 Projectile Assembly	14
3. Sigma N Versus Time - BRL 1042, XM761 PENT.	15
4. Spin Versus Time - BRL 1042, XM761 PENT	16
5. Sigma N Versus Time - BRL 1043, FELT WEDGE CONCEPT.	17
6. Spin Versus Time - BRL 1043, FELT WEDGE CONCEPT	18
7. Sigma N Versus Time - BRL 1044, FELT WEDGE CONCEPT.	19
8. Spin Versus Time - BRL 1044, FELT WEDGE CONCEPT	20
9. Sigma N Versus Time - BRL 1041, XM761 MOD 1D.	21
10. Spin Versus Time - BRL 1041, XM761 MOD 1D	22
11. Sigma N Versus Time - Round NY10G5.	23
12. Sigma N Versus Time - Round 32.	24
13. Sigma N Versus Time - Round 6	25

I. INTRODUCTION

Projectiles with a payload of felt wedges impregnated with a liquid white phosphorous (WP) simulant were tested successfully for flight stability at Charge 4 (see Figure 1). The payload consisted of four stacks of 90-degree wedges, 23 wedges per stack. Approximately 5.5 kg of simulant was absorbed by the felt. The felt wedge payload was inserted into a canister and used on projectile of design similar to the 155mm XM761 wick projectile. Yaw levels between 7 and 12.5 degrees were induced on a four round group of projectiles, and all projectiles were stable. The projectile hardware was fabricated by the Chemical Systems Laboratory (CSL), Edgewood Area; an M109A1 weapon with crew was provided by the Material Test Directorate, TECOM; yawsonde instrumentation, a ground receiving station, and a muzzle chronograph were supplied and operated by the BRL. Based on this initial test and data from a spin fixture built by the Weapons Systems Concepts Team (WSCT-EA)*, Edgewood Area, the felt wedge concept is a viable submunition design for a WP improved smoke projectile.

II. BACKGROUND

The XM761 projectile is shown in Figure 2. This projectile was the first concept for improved smoke obscuration from a 155mm projectile. It employed a WP/cotton wick concept, but flight instabilities resulted when the WP was liquid^{1,2,3}. Development of the XM761 was terminated, but the BRL initiated a diagnostic program to determine the mechanism of the wick instability⁴; and the WSCT-EA has built a spin fixture to test various payload concepts for the presence of a large despin moment (of the type exhibited by wick projectiles). The first phase of the BRL diagnostic program tested hardware similar to the original XM761, but addressed the use of a blended Freon simulant for liquid WP and the importance of a liquid-free surface on wick-type instabilities. It was determined that the Freon simulant reproduced the wick instability and

-
1. W. P. D'Amico, "Early Flight Experiences with the XM761," *Ballistic Research Laboratory Memorandum Report No. 2791, September 1977.* (AD #B024975L)
 2. W. P. D'Amico, "Field Tests of the XM761: First Diagnostic Test," *Ballistic Research Laboratory Memorandum Report No. 2792, September 1977.* (AD #B024976L)
 3. W. P. D'Amico, "Field Tests of the XM761: Second Diagnostic Test," *Ballistic Research Laboratory Memorandum Report in preparation.*
 4. W. P. D'Amico, "Diagnostic Tests for Wick-Type Payloads - Phase I," *Ballistic Research Laboratory Memorandum Report in publication.*

*Contact Mr. Miles Miller.

that fill ratios of 100% did not eliminate the wick instability. Similar conclusions had been reached on the WSCT-EA spin fixture.

As a result of spin fixture tests, two additional WP improved-smoke concepts have been flight tested by the BRL. One concept was the pentamerous (PENT) design which utilized a solid metal cylinder with 18 longitudinal core holes. A wick was placed into each hole. Three decks were assembled in a single canister and loaded into an M687 projectile body. Approximately 5 kg of liquid payload can be loaded into this configuration. Three pentamerous projectiles were tested during the BRL diagnostic program and were launched with approximately 15 degrees of initial yaw. All three projectiles were unstable and exhibited a strong coupling between the spin and yaw of the projectile. In order to provide baseline data for testing the felt-wedge concept, a pentamerous projectile and an XM761 MOD 1D projectile were saved from the BRL diagnostic program and fired during the same test sequence as the four felt-wedge projectiles. Both wick-type projectiles exhibited unstable behavior and detailed data plots are provided in Section III.

III. TEST PROGRAM

Instrumentation for the felt-wedge test was held to a minimum, with primary reliance placed on the BRL-built yawsondes⁵. A yaw inducer similar to the type described in Reference 1 was employed with a side-plate height of 7 cm. Tracking radar and down-range observers were not employed. The program was conducted from a firing position near Mulberry Point (New Barricade) with an azimuth of 53° West of South. Firings were held on two days, 1 and 15 November.

Test conditions on 1 November were not optimum, but an attempt to obtain yawsonde data was requested by CSL. Raw data were received and indicated stable flights with initial launch yaws of approximately 7 degrees, but no reduced data are presented since the quality of the raw data was quite poor. Good test conditions existed on 15 November and good data were obtained. The yawsonde data within this report were produced by a portable processor and a Hewlett Packard 9830 calculator and plotter. This is a system built by the BRL. Yawsonde data are presented in the form of solar angle and spin. Sigma N is the complement of the solar angle, which is the angle between a vector drawn to the sun and the spin axis of the projectile. Spin data are actually in the form of the derivative of the Eulerian roll angle of the projectile but are simply labeled "spin" within this report. Oscillations are superimposed upon the spin history when the associated yawing motion is large, and methods

5. W. H. Mermagen and W. H. Clay, "The Design of a Second Generation Yawsonde," *Ballistic Research Laboratories Memorandum Report No. 2368, April 1974. AD 780064.*

are available to reduce the amplitude of these oscillations⁶. The methods of Reference 6 were not applied to the data within this report, however. Table 1 lists a round-by-round summary of the firing program, while Table 2 lists the physical characteristics of the projectiles tested.

Round 1042, a pentamerous concept, was launched with an initial disturbance of 10 degrees. The solar angle data show that by 4 seconds the motion was rapidly growing and substantial losses in spin occurred (Figures 3 and 4). Round 1043 was a felt-wedge concept projectile and was launched with an initial yaw of 9.5 degrees. The resulting angular motion was quite typical for M483A1-type projectiles, and a precessionally dominated limit cycle characterized the flight history (Figure 5). Figure 6 shows the associated spin data to be quite normal. Round 1044, also a felt-wedge concept projectile, was launched with an initial yaw of 12.5 degrees, and the resulting motion although stable was not identical to Round 1043. The nutational component of yaw induced at launch persisted for almost 8 seconds of flight before giving way to the expected precessional limit cycle. Both rounds were stable, however. The final round tested was an XM761 MOD 1D. This projectile, Round 1041, contained 48 wicks and was filled to 90% of the available canister volume. Figure 9 shows an initial launch disturbance of 11 degrees and unstable behavior is precipitated within 2 seconds of launch. A rapid decrease in spin was also recorded, as Figure 10 indicates.

IV. DISCUSSION

The results of this test indicate that a felt-wedge concept has substantially better flight performance than previously investigated wick concepts. Launches at Charge 4 were selected because of a substantial experience with the wick projectiles at Charge 4 and because of range restrictions. The behavior exhibited by Round 1044, however, should be carefully investigated. This type of rapid precessional damping and slower nutational damping has been observed on other projectile types (Figure 11), but the lack of rapid nutational damping may be caused by the liquid/felt payload. For example, yawsonde data for an XM761 projectile reported in Reference 3 is shown in Figure 12. This projectile was stable, but sluggish nutational damping characterized the flight history and for larger levels of initial yaw unstable flights resulted. Also within Reference 4, natural launch Charge 6 conditions produced dramatic instabilities for wick-type projectiles (Figure 13). Thus, tests should be undertaken with felt payloads at high charges to determine projectile stability.

6. C. H. Murphy, "Effect of Large High-Frequency Angular Motion of a Shell on the Analysis of Its Yawsonde Records," *Ballistic Research Laboratories Memorandum Report No. 2581, February 1976. AD B0094210.*

The strongest reason for a careful ballistic examination of the felt concept is that the mechanism of how the felt wedges avoid the wick-type instability is not understood. Except for a realization that the felt is a closely packed, random fiber matrix, neither a physical or computational model is available and at present only empirical evidence indicates that a stable payload configuration has been found. It is not necessarily the case, however, that the felt wedge concept would be as untractable to analytical methods as the wick concept was. The felt wedges could be represented by a porous media that fills the interior of a cylinder. The details of the x-rib could be omitted in an attempt to isolate important physical parameters. Flow through porous media is a subject of interest in many fields of engineering and science, e.g., ground water hydrology, geophysics, and chemical processes. An excellent introduction to this subject was authored by Bear⁷. Also, highly permeable media have been used to achieve substantial reductions in the time to liquid spin-up for liquid-filled projectiles, and a patent has been awarded for such a process.⁸

V. CONCLUSION

A felt-wedge concept was tested with a WP liquid simulant under the conditions of yaw induction at Charge 4. A substantial increase in flight stability has been achieved at Charge 4 over any other WP submunition concept. Carefully designed ballistic trials should, however, be designed to preclude any unforeseen flight instabilities since an analytical representation of this payload concept is not yet available. The data base that has been established should provide the impetus for continued development of this smoke concept.

7. Jacob Bear, *Dynamics of Fluids in Porous Media*, New York, London, Amsterdam, American Elsevier Publishing Company, Inc., 1972.

8. W. P. D'Amico, "The Application of a Highly Permeable Media to Reduce Spin-Up Time and to Stabilize a Liquid-Filled Shell," *Ballistic Research Laboratory Memorandum Report in publication.*

Table 1. Round-by-Round Summary

<u>BRL Number</u>	<u>Ogive Number</u>	<u>Projectile Type</u>	<u>Muzzle Velocity (m/s)</u>	<u>Quadrant Elevation (deg)</u>	<u>Comments</u>
1038	277	Felt	307.7	15	Stable
1039	278	Felt	327.9	15	Stable
1042	Sm 4	Pentamerous	328.1	30	Unstable
1043	279	Felt	332.3	30	Stable
1044	280	Felt	327.0	30	Stable
1041	Sm 14	XM761 MOD 1D	323.9	30	Unstable

Table 2. Projectile Physical Characteristics

<u>BRL Number</u>	<u>Weight kg</u>	<u>CG (m)</u>	<u>Moment of Inertia</u>	
			<u>Axial (kg·m²)</u>	<u>Transverse (kg·m²)</u>
1038	48.09	0.326	0.1740	1.850
1039	48.21	0.324	0.1745	1.855
1042	45.89	0.324	0.1699	1.793
1043	48.19	0.324	0.1741	1.855
1044	47.93	0.325	0.1731	1.848
1041	42.54	0.330	0.1685	1.704




Figure 1. Felt Wedge Concept




Figure 2. XM761 Projectile Assembly

BRL 1042




Figure 3. Sigma N Versus Time - BRL 1042, XM 761 PENT

BRL 1042




Figure 4. Spin Versus Time - BRL 1042, XM761 PENT




Figure 5. Sigma N Versus Time - BRL 1043, FELT WEDGE CONCEPT

BRL 1043




Figure 6. Spin Versus Time - BRL 1043, FELT WEDGE CONCEPT

BRL 1044




Figure 7. Sigma N Versus Time - BRL 1044, FELT WEDGE CONCEPT




Figure 8. Spin Versus Time - BRL 1044, FELT WEDGE CONCEPT

BRL 1041




Figure 9. Sigma N Versus Time - BRL 1041, XM761 MOD 1D

BRL 1041




Figure 10. Spin Versus Time - BRL 1041, XM761 MOD 1D




FIGURE 11. SIGMA N VS TIME ROUND NY1065




FIGURE 12. SIGMA N VS TIME ROUND 32




FIGURE 13. SIGMA N VS TIME ROUND 6

REFERENCES

1. W. P. D'Amico, "Early Flight Experiences with the XM761," Ballistic Research Laboratory Memorandum Report No. 2791, September 1977. (AD #B024975L)
2. W. P. D'Amico, "Field Tests of the XM761: First Diagnostic Test," Ballistic Research Laboratory Memorandum Report No. 2792, September 1977. (AD #B024976L)
3. W. P. D'Amico, "Field Tests of the XM761: Second Diagnostic Test," Ballistic Research Laboratory Memorandum Report in preparation.
4. W. P. D'Amico, "Diagnostic Tests for Wick-Type Payloads - Phase I," Ballistic Research Laboratory Memorandum Report in publication.
5. W. H. Mermagen and W. H. Clay, "The Design of a Second Generation Yawsonde," Ballistic Research Laboratories Memorandum Report No. 2368, April 1974. AD 780064.
6. C. H. Murphy, "Effect of Large High-Frequency Angular Motion of a Shell on the Analysis of Its Yawsonde Records," Ballistic Research Laboratories Memorandum Report No. 2581, February 1976. AD B0094210.
7. Jacob Bear, Dynamics of Fluids in Porous Media, New York, London, Amsterdam, American Elsevier Publishing Company, Inc., 1972.
8. W. P. D'Amico, "The Application of a Highly Permeable Media to Reduce Spin-Up Time and to Stabilize a Liquid-Filled Shell," Ballistic Research Laboratory Memorandum Report in publication.

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
12	Commander Defense Documentation Center ATTN: DDC-TCA Cameron Station Alexandria, VA 22314	2	Commander US Army Mobility Equipment Research & Development Command ATTN: Tech Docu Cen, Bldg. 315 DRSME-RZT Fort Belvoir, VA 22060
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMA-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299
1	Commander US Army Aviation Research and Development Command ATTN: DRSAB-E 12th and Spruce Streets St. Louis, MO 63166	2	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS DRDAR-LC, Dr. J.T. Frasier Dover, NJ 07801
1	Commander US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	1	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCA-F, Mr. A. Loeb Dover, NJ 07801
1	Commander US Army Electronics Command ATTN: DRSEL-RD Fort Monmouth, NJ 07703	1	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCN, W.R. Benson Dover, NJ 07801
1	Commander US Army Missile Research and Development Command ATTN: DRDMI-R Redstone Arsenal, AL 35809	1	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCU, J. Hathaway Dover, NJ 07801
1	Commander US Army Tank Automotive Development Command ATTN: DRDTA-RWL Warren, MI 48090	1	Commander US Army Harry Diamond Labs ATTN: DRXDO-TI 2800 Powder Mill Road Adelphi, MD 20783

DISTRIBUTION LIST (Continued)

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Project Manager Selected Ammunition ATTN: DRCPM-SA, L. McClellan Dover, NJ 07801	1	Arnold Research Organization Project Support and Special Studies Section ATTN: Dr. John C. Adams, Jr. Arnold AFS, TN 37389
2	Project Manager Cannon Artillery Weapons Sys ATTN: DRCPM-CAWS-TM, Mr. Fissette Dover, NJ 07801		<u>Aberdeen Proving Ground</u> Marine Corps Ln Ofc Dir, USAMSAA PM SMOKE, DRCPM-SMK Cmdr, USACSL, EA ATTN: DRDAR-CLN-D, Mr. Ferriter DRDAR-S, Mr. W. Dee DRDAR-ACW, Mr. M. Miller DRDAR-CLN-SM, Mr. Norton
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL (Tech Lib) White Sands Missile Range NM 88002		