

AD-A057 075

PURDUE UNIV LAFAYETTE IND PROJECT SQUID HEADQUARTERS

F/G 20/4

AXIAL FLOW IN TRAILING LINE VORTICES.(U)

JUN 78 M S UBEROI, B K SHIVAMOGGI, S CHEN

N00014-75-C-1143


UNCLASSIFIED

SQUID-UC-2-PU

NL

| OF |

AD
A057075



END
DATE
FILMED
9-78
DDC

LEVEL #

(11)
NW

AD A057075

AD No. —
DDC FILE COPY

PROJECT SQUID

TECHNICAL REPORT UC-2-PU

AXIAL FLOW IN TRAILING LINE VORTICES

BY

MAHINDER S. UBEROI
BHIMSEN K. SHIVAMOGGI and SIN-SUNG CHEN
UNIVERSITY OF COLORADO
BOULDER, COLORADO 80309

PROJECT SQUID HEADQUARTERS
CHAFFEE HALL
PURDUE UNIVERSITY
WEST LAFAYETTE, INDIANA 47907

JUNE 1978

DDC
RECEIVED
AUG 7 1978
RECEIVED

Project SQUID is a cooperative program of basic research relating to Jet Propulsion. It is sponsored by the Office of Naval Research and is administered by Purdue University through Contract N00014-75-C-1143, NR-098-038.

This document has been approved for public release and sale;
its distribution is unlimited.

78 08 01 004

Technical Report UC-2-PU

P R O J E C T S Q U I D

A COOPERATIVE PROGRAM OF FUNDAMENTAL RESEARCH
AS RELATED TO JET PROPULSION
OFFICE OF NAVAL RESEARCH, DEPARTMENT OF THE NAVY

CONTRACT N00014-75-1143 NR-098-038

AXIAL FLOW IN TRAILING LINE VORTICES

BY

Mahinder S. Uberoi
Bhimsen K. Shivamoggi and Sin-Sung Chen
University of Colorado
Boulder, Colorado 80309

referred to Cooper

June 1978

PROJECT SQUID HEADQUARTERS
CHAFFEE HALL
PURDUE UNIVERSITY
WEST LAFAYETTE, INDIANA 47907

403 617

This document has been approved for public release and sale;
its distribution is unlimited.

78 08 01 004

ABSTRACT

Axial flow in the core of laminar steady trailing vortex from the tip of a semi-infinite lifting wing is analyzed, assuming that the pressure gradient is determined by the swirl velocities of an ideal infinite line vortex. The axial and lateral variations of the axial velocity depend on the strength of the vortex and initial axial velocity distribution which must be specified at some station behind the wing.

ADDITIONAL FOR	
NTIS	White Section ☒
DOC	Half Section ☐
UNANNOUNCED	☐
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

I. INTRODUCTION

Vortices occur naturally and are also of technical interest. As an example, consider the trailing vortex which is formed near the tip of a semi-infinite lifting wing in a uniform steady flow u_0 . The vorticity shed near the tip of the wing rapidly rolls up into a concentrated core along u_0 and the flow becomes axisymmetric, such that at lateral distance $r \rightarrow \infty$ the velocity $u_\theta(r, z) \rightarrow \Gamma_0 / 2\pi r$ where θ refers to the angular coordinate and z is the axial distance along the vortex axis, and Γ_0 is the circulation around the vortex. In the core the swirl velocity decreases with downstream distance z . The pressure is constant at large r and hence the pressure increases along z and in the core there must be an axial velocity difference $u_z(r, z)$ from the prevailing velocity u_0 . These simple considerations show the existence of an axial velocity difference between the core and the surrounding fluid. The theory is needed to find its detailed distributions and dependence on various parameters. This paper is concerned with flows which are laminar everywhere.

Newman¹ has calculated the axial velocity variations in the vortex core by assuming that both u_θ and u_z are small compared with u_0 and the equations governing u_θ and u_z become uncoupled and may be solved separately. Dosanjh² et al have measured the velocities in the turbulent core of a vortex and compared the results with Newman's calculation for the laminar case assuming that the laminar kinematic viscosity may be replaced by an equivalent turbulent exchange coefficient.

Batchelor³ has analyzed the axial velocity in the vortex core which is caused by the axial pressure gradient associated with the decaying vortex. In effect, he assumes that u_θ is independent of u_z but the later is influenced

by the former. We will examine at the end of this paper the validity of this approximation. Betchelor's analysis has been criticized by Tam⁴ which in turn has been criticized by Herron⁵. We show that all three authors have missed some essential points. We give here the correct analysis.

II. GOVERNING EQUATIONS

The equation governing u_θ in trailing vortex under boundary layer (slender vortex) approximation is⁶

$$\frac{\partial}{\partial z} (u_o + u_z) u_\theta r^2 + \frac{\partial}{\partial r} (u_r u_\theta r^2) = \nu \frac{\partial}{\partial r} r^3 \frac{\partial}{\partial r} \left(\frac{u_\theta}{r} \right) \quad (1)$$

where ν is the kinematic viscosity.

All other investigators have invariably assumed that the axial velocity difference $u_z(r, z)$ between the core and the surrounding, and the radial velocity $u_r(r, z)$ may be neglected, which we may call LINE VORTEX approximation. Presently we use these approximations and subsequently we examine the limits of their validity and estimate the effect of the neglected terms on the dynamics of the vortex flow. For the line vortex, Eq. (1) becomes

$$u_o \frac{\partial}{\partial z} u_\theta r^2 = \nu \frac{\partial}{\partial r} r^3 \frac{\partial}{\partial r} \frac{u_\theta}{r} \quad (2)$$

which has a self-similar solution

$$u_\theta(r, z) 2\pi r = \Gamma_o (1 - e^{-\eta}) \quad (3)$$

where

$$\eta = u_0 r^2 / 4\nu z \quad (4)$$

Assuming that u_0 is given by Eq. (3) we calculate u_z in the following approximate manner. We assume that the radial pressure gradient is given approximately by the equation.

$$\frac{1}{\rho} \frac{\partial p}{\partial r} = \frac{u_\theta^2}{r} \quad (5)$$

Using Eqs. (3) - (5) we can calculate axial pressure gradient³, thus

$$\frac{1}{\rho} \frac{\partial p}{\partial z} = \left(\frac{r_0}{2\pi} \right)^2 \frac{u_0}{8\nu z} 2 (P\eta)' \quad (6)$$

where

$$p(\eta) = \int_\eta^\infty \frac{(1-e^{-t})^2}{t^2} dt \quad (7)$$

The linearized equation of motion for u_z is

$$u_0 \frac{\partial}{\partial z} u_z = - \frac{1}{\rho} \frac{\partial p}{\partial z} + \nu \left(\frac{\partial^2}{\partial r^2} + \frac{1}{r} \frac{\partial}{\partial r} \right) u_z \quad (8)$$

III. AXIAL VELOCITY

The axial velocity difference u_z is determined by the initial distribution of u_z and by the pressure gradient along the vortex axis which is due to decaying u_θ in the vortex core. The diffusion Eq. (8) has a unique solution for the sources given by Eq. (6) and an initial condition $u_z^*(r, z_0)$ prescribed at a station z_0 . Using standard Green Function technique, see for example Luikov⁷, the solution due to the sources is given by

$$\frac{u_z(r,z)}{u_0} = \frac{-1}{64\pi^2} \left(\frac{r_0}{v}\right)^2 \int_{t_0}^t \int_0^\infty \frac{\{P(\eta)\eta\}'}{t'^2} e^{-\frac{s^2 + s'^2}{4(t-t')}} I_0\left(\frac{ss'}{2(t-t')}\right) s' ds' dt' \quad (9)$$

where $s = ru_0/v$, $t = u_0 z/v$, $\eta = s^2/4t$ and $t_0 = u_0 z_0/v$ and I_0 is the modified Bessel function.

The contribution $u_z^*(r,z)$ due to the initial $u_z^*(r,z_0)$ is again obtained using standard methods by the relation

$$\frac{u_z^*(r,z)}{u_0} = \frac{1}{2} \int_0^\infty u_z^*(s,t_0) e^{-\frac{s^2 + s'^2}{4(t-t_0)}} I_0\left(\frac{ss'}{2(t-t_0)}\right) s' ds' \quad (10)$$

$$\approx \int_0^\infty u_z^*(r,z_0) 2\pi r dr \cdot \frac{1}{4\pi v z} e^{-\frac{r^2 u_0^2}{4vz}} \quad \text{for } z \gg z_0 \quad (11)$$

In the present notation total axial velocity is the sum of $u_z(r,z)$ and $u_z^*(r,z)$. The sources given by (6) have a non-integrable singularity at $z = 0$, so that z_0 cannot be zero. The initial velocity cannot be prescribed at $z = 0$, and therefore the solution is not independent of z_0 .

Unfortunately, Eq. (9) cannot be integrated in terms of known functions. We have numerically integrated it for $z_0 u_0/v = 1$ and $z/z_0 = 10, 100$, and $1,000$. We have also integrated it for another initial station $z_0 u_0/v = 10$ and for $z/z_0 = 10$, and 100 . The velocity profile $u_z(r,z)/u_z(0,z)$ are shown in Fig. 1. The maximum non-dimensional velocity defect $u_z(0,z)/u_0$, as a function of z , is shown in Fig. 2 and 3.

IV. AXIAL VELOCITY USING EQUIVALENT SOURCES

The function $[P(\eta)\eta]'$ of the source distribution is shown in Fig. 4 together with $e^{-\eta}$. The area under the two curves (i.e., the integral of sources in the radial plane) is the same and the curves are also similar. Therefore, we may approximate Eq. (8) by

$$-\frac{1}{\rho} \left(\frac{\partial p}{\partial z} \right) = - \left(\frac{\Gamma_0}{2\pi} \right)^2 \frac{2u_0}{8\nu z^2} e^{\frac{-r^2 u_0}{4\nu z}} \quad (12)$$

Using (12) as the source Eq. (8) has the solution

$$\frac{u_z(r, z)}{u_0} = \frac{-1}{u_0} \left(\frac{\Gamma_0}{2\pi} \right)^2 \frac{1}{8\nu z} \ln z/z_0 e^{\frac{-r^2 u_0}{4\nu z}} \quad (13)$$

We now find that

$$u_z(r, z)/u_z(0, z) = e^{\frac{-r^2 u_0}{4\nu z}} \quad (14)$$

and

$$u_z(0, z)/u_0 = \left(\frac{\Gamma_0}{2\pi} \right)^2 \frac{1}{8\nu z} \ln z/z_0 \quad (15)$$

The results given by Eqs. (14) and (15) compare favorably with the numerical computation as shown in Fig. 1, 2 and 3, respectively.

We note that u_z is the axial velocity defect due to the pressure gradient in the vortex core starting with uniform axial velocity at z_0 . We may add to it the contribution of any initial axial velocity excess or defect using Eq. (10) or Eq. (11) as appropriate.

We note that for large z the axial velocity due to any initial distribution does not contribute to the above ratio. The approximations used to replace the trailing vortex by a line vortex are valid if the above ratio is much less than unity.

The comparison of this theory with available experiment can only be made when Eq. (18) is satisfied and the flow is laminar. We do not know of any such experiments. In general, the results of analysis based on laminar flow cannot be applied to the flow in the turbulent state. In the case at hand, it is not possible to replace the kinematic viscosity by a turbulent exchange coefficient and use the theoretical results presented here for comparison with experimental results for turbulent trailing vortices. The reasons are not directly relevant here, they are quite extensive and are presented elsewhere.⁹

REFERENCES

1. B. G. Newman, *Aero-Quarterly*, 10, 149, (1959)
2. D. S. Dosanjh, F.P. Gasparek and E. Eskinazi, 13, 167, (1962)
3. G. K. Batchelor, *J. Fluid Mech.*, 20, 645 (1964)
4. K. K. Tam, *J. Engr. Math.*, 7, 1, (1973)
5. J. H. Herron, *J. Engr. Math.*, 8, 339 (1974)
6. M. S. Uberoi, *Phys. Fluids*, 20, 1785, (1977)
7. A. V. Luikov, Analytical Heat Diffusion Theory, Academic Press, N. Y., p. 379, (1968)
8. M. S. Uberoi, *Bulletin of the Am. Phys. Soc.*, 23, 524 (1978)
9. M. S. Uberoi, Mechanisms of Decay of Laminar and Turbulent Vortices, Project Squid Tech. Rep. UC-1-PU, Purdue University, (1977)

Fig. 1. Axial velocity defect distribution as a function η ,
 - $e^{-\eta}$; x $z/z_0 = 1,000$, $z_0 = 1$; Δ $z/z_0 = 100$, $z_0 = 1$;
 0 $z/z_1 = 10$, $z_0 = 1$; $\square$ $z/z_0 = 100$, $z_0 = 10$, + $z/z_0 = 10$

Fig. 2. Axial velocity defect distribution on the vortex axis for
 z/z_0 from 1 to 7; - approximate solution using equivalent sources;
 x numerical solution using exact distribution of sources;

Fig 3. Axial Velocity defect distribution on the vortex axis for
 z/z_0 from 1 to 100; - approximate solution using equivalent sources;
 x numerical solution using exact distribution of sources;

Fig. 4. Comparison of sources with equivalent sources;
 x sources distribuiton; - equivalent source distribution.




Figure 1




Figure 2

$$\frac{-U_Z(0, Z) \cdot Z_0}{U_0 \times 10^{-4} (\Gamma_0/\nu)^2}$$




Figure 3




Figure 4

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

14 SQUID REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER UC-2-PU	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER (9) Technical rpt.	
4. TITLE (and Subtitle) 6 AXIAL FLOW IN TRAILING LINE VORTICES		5. TYPE OF REPORT & PERIOD COVERED Technical-Scientific	
7. AUTHOR(s) 10 Mahinder S. Uberoi, Bhimsen K. Shivamoggi Sin-Sung Chen		8. CONTRACT OR GRANT NUMBER(s) 15 NR0014-75-C-1143	
9. PERFORMING ORGANIZATION NAME AND ADDRESS University of Colorado Boulder, CO 80309		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR-098-038	
11. CONTROLLING OFFICE NAME AND ADDRESS Project SQUID Headquarters Chaffee H11 Purdue University, West Lafayette, Ind. 47907		12. REPORT DATE 11 June 1978	
13. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of Naval Research, Power Program, Code 473 Department of the Navy 800 No. Quincy Street Arlington, VA 22217 12 17 p.		14. NUMBER OF PAGES 16	
		15. SECURITY CLASS. (of this report) Unclassified	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) This document has been approved for public release and sale; its distribution is unlimited.			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) Same			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Trailing Vortices Aircraft Vortices			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Axial flow in the core of laminar steady trailing vortex from the tip of a semi-infinite lifting wing is analyzed, assuming that the pressure gradient is determined by the swirl velocities of an ideal infinite line vortex. The axial and lateral variations of the axial velocity depend on the strength of the vortex and initial axial velocity distribution which must be specified at some station behind the wing.			

40.3677

40