

AD-A065 870

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO
USING LOGARITHMIC CHARACTERISTICS TO CALCULATE BROAD-BAND MATCH--ETC(U)
SEP 77 Y Y YUROV, V A NELEP

F/G 9/5

UNCLASSIFIED

FTD-ID(RS)T-1637-77

NL


OF
A D A
065870

10
11
12



END
DATE
FILMED
4-79
DDC

END
DATE
FILMED
4-79
DDC





AD-A065870


FOREIGN TECHNOLOGY DIVISION




USING LOGARITHMIC CHARACTERISTICS TO CALCULATE
BROAD-BAND MATCHING OF A GENERATOR WITH A LOAD

by

Yu. Ya. Yurov and V. A. Nelep



Approved for public release;
distribution unlimited.



11 09 142

ADDITIONAL TO	
DTIC	With Section <input checked="" type="checkbox"/>
DDI	With Section <input type="checkbox"/>
CLASSIFIED	<input type="checkbox"/>
UNCLASSIFIED	
BY	
DISTRIBUTION/CLASSIFICATION CODE	
DIS.	
A	

EDITED TRANSLATION

FTD-ID(RS)T-1637-77

20 September 1977

MICROFICHE NR: *FD-77-C-001212*

CSP73168095

USING LOGARITHMIC CHARACTERISTICS TO CALCULATE BROAD-BAND MATCHING OF A GENERATOR WITH A LOAD

By: Yu. Ya. Yurov and V. A. Nelep

English pages: 21

Source: Izvestiya Vysshikh Uchebnykh Zavedeniy, Radioelektronika, Vol 15, Nr 7, July, 1972, PP. 826-833

Country of origin: USSR

Translated by: Carol S. Nack

Requester: FTD/ETWR

Approved for public release; distribution unlimited.

<p>THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.</p>	<p>PREPARED BY: TRANSLATION DIVISION FOREIGN TECHNOLOGY DIVISION WP-AFB, OHIO.</p>
---	--

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	<i>А а</i>	A, a	Р р	<i>Р р</i>	R, r
Б б	<i>Б б</i>	B, b	С с	<i>С с</i>	S, s
В в	<i>В в</i>	V, v	Т т	<i>Т т</i>	T, t
Г г	<i>Г г</i>	G, g	У у	<i>У у</i>	U, u
Д д	<i>Д д</i>	D, d	Ф ф	<i>Ф ф</i>	F, f
Е е	<i>Е е</i>	Ye, ye; E, e*	Х х	<i>Х х</i>	Kh, kh
Ж ж	<i>Ж ж</i>	Zh, zh	Ц ц	<i>Ц ц</i>	Ts, ts
З з	<i>З з</i>	Z, z	Ч ч	<i>Ч ч</i>	Ch, ch
И и	<i>И и</i>	I, i	Ш ш	<i>Ш ш</i>	Sh, sh
Й й	<i>Й й</i>	Y, y	Щ щ	<i>Щ щ</i>	Shch, shch
К к	<i>К к</i>	K, k	Ъ ъ	<i>Ъ ъ</i>	"
Л л	<i>Л л</i>	L, l	Ы ы	<i>Ы ы</i>	Y, y
М м	<i>М м</i>	M, m	Ь ь	<i>Ь ь</i>	'
Н н	<i>Н н</i>	N, n	Э э	<i>Э э</i>	E, e
О о	<i>О о</i>	O, o	Ю ю	<i>Ю ю</i>	Yu, yu
П п	<i>П п</i>	P, p	Я я	<i>Я я</i>	Ya, ya

*ye initially, after vowels, and after ъ, ь; e elsewhere.
 When written as ě in Russian, transliterate as yě or ě.
 The use of diacritical marks is preferred, but such marks may be omitted when expediency dictates.

GREEK ALPHABET

Alpha	A	α	α	Nu	N	ν
Beta	B	β		Xi	Ξ	ξ
Gamma	Г	γ		Omicron	Ο	ο
Delta	Δ	δ		Pi	Π	π
Epsilon	E	ε	ε	Rho	Ρ	ρ ϱ
Zeta	Z	ζ		Sigma	Σ	σ ς
Eta	H	η		Tau	Τ	τ
Theta	Θ	θ	θ	Upsilon	Υ	υ
Iota	I	ι		Phi	Φ	φ φ
Kappa	K	κ	κ	Chi	Χ	χ
Lambda	Λ	λ		Psi	Ψ	ψ
Mu	M	μ		Omega	Ω	ω

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English
---------	---------

sin	sin
cos	cos
tg	tan
ctg	cot
sec	sec
cosec	csc
sh	sinh
ch	cosh
th	tanh
cth	coth
sch	sech
csch	csch
arc sin	sin ⁻¹
arc cos	cos ⁻¹
arc tg	tan ⁻¹
arc ctg	cot ⁻¹
arc sec	sec ⁻¹
arc cosec	csc ⁻¹
arc sh	sinh ⁻¹
arc ch	cosh ⁻¹
arc th	tanh ⁻¹
arc cth	coth ⁻¹
arc sch	sech ⁻¹
arc csch	csch ⁻¹

rot	curl
lg	log

GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc.
merged into this translation were extracted
from the best quality copy available.

1637

USING LOGARITHMIC CHARACTERISTICS TO CALCULATE BROAD-BAND MATCHING OF
A GENERATOR WITH A LOAD

Yu. Ya. Yurov and V. A. Nelep

Summary

This report gives a procedure for finding the analytical expression for the frequency dependence of the input impedance of a matching quadrupole loaded by the generator impedance when powered from the side of the load. This frequency function can be given graphically or analytically. Its analytical expression is obtained in standard form convenient for synthesizing a matching quadrupole by using its logarithmic characteristics. The necessary and sufficient condition of the realizability of this impedance in the form of a

passive two-terminal network with lumped parameters is established. This method is used to determine the parameters of a matching quadrupole with a passive load.

Introduction

Broad-band matching of a generator to a load (Fig. 1) which has a resistance frequency dependence is a complex problem. Lengthy computations must be made to determine the parameters of the matching quadrupole by the existing procedures [1-6]. The engineering calculation formulae have only been obtained for loads which can be represented accurately enough by a circuit with lumped parameters containing a maximum of two reactive elements. In these broad-band matching methods, all the functions are considered depending on the complex variable $p = \sigma + i\omega$, and the Chebyshev or Butterworth polynomials are used to approximate the power transfer coefficient. The first condition robs the calculation of its clarity, making it necessary to perform it with excessive accuracy. The second condition complicates the matching quadrupole circuit, since additional conditions which are not usually necessary are imposed on the zero position and the poles of the power transfer coefficient.

In this report, all the functions are considered depending on

the imaginary part of the complex variable, i.e., on the real frequency. We can show (7) that in this case, extremely approximate methods, e.g., graphic, can be used to calculate the parameters of the matching quadrupole which do not require the use of the Chebyshev or Butterworth polynomials. A method of determining the parameters of the matching quadrupole using logarithmic characteristics is proposed. This method makes it possible to considerably reduce the volume of computations and calculate matching for any passive load.

The dependence of the power transfer coefficient on the load and matching quadrupole parameters is [2]:

$$G = 1 - \left| \frac{Z_1 - z_1^*}{Z_1 + z_1} \right|^2 \quad (1)$$

where G is the power transfer coefficient; z_1, z_1^* are the resistance and complex-conjugated load impedance; Z_1 is the input impedance of the matching quadrupole from the load, when its input clips are closed on the internal generator impedance (Fig. 1).

We will designate the ratio of amplitudes $|Z_1|/|z_1|$ by ϵ and we will rewrite (1) as follows:

$$G = \frac{4\epsilon \cos \varphi_2 \cos \varphi_1}{1 + 2\epsilon \cos(\varphi_2 - \varphi_1) + \epsilon^2} \quad (2)$$

where φ_2, φ_1 are the phase angles of impedances Z_1 and z_1 .

Phase angles ϕ_2 and ϕ_H are completely symmetrical in (2) and the value of G does not vary if we substitute ϵ^{-1} for ϵ in (2). Furthermore, the majority of the values of G lie within 0.6-1. Therefore, the curves of dependence $\varphi_n = f(\varphi_1)$ are given in Fig. 2 at $\epsilon = \text{const}$ and $G = 0.6; 0.8; 1$. The curves are easily calculated if the axis of coordinates ϕ_2 and ϕ_H are turned to a 45° angle. Angles ϕ_2 and ϕ_H change within the limits $(-\pi/2; \pi/2)$, since the load and the matching quadrupole are passive. In Fig. 2, $\varphi_n \geq 0$; it is obvious that the curves remain the same if we reverse the signs both on the x- and y-axis.

The curves which were plotted make it possible to find G at a given Z_2 or, assigning G , to find the range of permissible values of the amplitude and phase of Z_2 for any load impedance.

For example, if $\epsilon = -3 \text{ dB}$, $\varphi_1 = -60^\circ$, $\varphi_2 = -40^\circ$, then $G \approx 0.82$; if $G \gg 0.8$, $\phi_H = 60^\circ$, then $-72^\circ < \varphi_1 < -27^\circ$ and $-3 \text{ dB} < \epsilon < 3 \text{ dB}$.

This report considers a matching quadrupole with lumped parameters; therefore, $Z_2(p)$ must be a rational positive real function (PRF) [8]. It follows from the properties of a PRF that it can always be represented by the product of the factors

$T, (Tp)^{\pm 1}, (Tp+1)^{\pm 1}, (T^2p^2+2\epsilon Tp+1)^{\pm 1}$ (here and below T, ϵ are positive real numbers, $0 \leq \epsilon < 1$). In the appendix it is proven that inequalities $\frac{\pi}{2} \leq \varphi_p \leq \frac{\pi}{2}$ are not only necessary, but also sufficient conditions for the positiveness and reality of function $Z_2(p)$, represented in the form of the product of these factors.

The determination of an analytical expression for function Z_2 which satisfies the necessary and sufficient conditions of positiveness and reality and for which the amplitude and phase are within the range of permissible values is the main purpose of this study.

This method can also be used to calculate matching in the SHF range if we find the equivalent matching quadrupole in the form of a circuit with distributed parameters.

Finding the Analytical Expression for Z_2 Using Logarithmic Characteristics

The logarithmic amplitude and phase characteristics (LKh) proposed by Bode [9] are the curves of the amplitude in decibels and phase in degrees of the frequency function plotted depending on $\log \omega$. We will list the LKh properties which will be used later [10].

The amplitude characteristic $(T\omega)^{-1}$ is a straight line with slope of -6 dB per octave, while the phase characteristic is straight line $\phi = -90^\circ$. The amplitude characteristics $(T\omega+1)^{-1}$ (broken lines) and $[(T\omega)^2+2T\omega+1]^{-1}$, shown in Fig. 3., have asymptotes. One asymptote is the x-axis, and the other is a straight line with a slope of -6 dB per octave for $(T\omega+1)^{-1}$ and -12 dB per octave for $[(T\omega)^2+2T\omega+1]^{-1}$. The asymptotes intersect each other at point $\omega = 1/T$ from the abscissa. The LKh of the inverses of the functions under consideration, which are shown in Fig. 3, are symmetrical to the x-axis of the LKh. Multiplication is replaced by the addition of the LKh; therefore, it is easy to find the curves of the complex function which consists of multiplying the factors in question. The properties of the LKh make it possible to plot the curves of the dependence of the amplitude and phase of Z_2 on frequency so that they satisfy the above conditions, as well as to find the analytical expression for Z_2 from the curves obtained.

This problem is solved in three steps (Fig. 4, which shows an example of calculating matching, can be used as an illustration).

1. The amplitude is plotted in decibels and the phase in degrees of the normalized load impedance depending on $\log \omega$. Given the

transfer coefficient G equal to 0.6 or 0.8, we will select the contour $\mathcal{E} = \text{const}$ in Fig. 2 so that the permissible limits of the change in ϕ_2 are sufficiently great. The boundary values of ϕ_2 are plotted on the phase curve, while \mathcal{E} and $-\mathcal{E}$ in decibels are added to amplitude $|z_2|$. If we do this at the row of points on the frequency axis, we obtain the range of permissible values of the amplitude and phase of Z_2 .

We should not assign a large G , since the ranges of permissible values play a secondary role in the calculation and are only used to estimate the value of the transfer coefficient. The broader the matching band and the greater the limits of the change in the amplitude and phase of the load impedance, the smaller the value of G which must be selected.

2. The ranges of permissible values obtained are analyzed by comparing them with the LKh of standard factors (Fig. 3). Then, beginning with the simplest functions (consisting of constant factor T from linear factor $(Tj\omega+1)$ in the numerator or denominator of Z_2 , etc.), the asymptotic curve of the amplitude of Z_2 is plotted within the corresponding range. Possible deviations of the precise curves from the asymptote in Fig. 3 are considered here. Beginning with zero, the slope of the asymptote has a factor of 6 dB per octave. In order to make the corresponding asymptotic curve of the phase

characteristic fall in the range of permissible values of ϕ_2 , it is necessary to consider the following: if the asymptote has a zero slope, the phase in this section approaches zero if the slope of the asymptote is equal to $\pm 6n$ dB per octave ($n = 1, 2, 3, \dots$), and the phase characteristic approaches ± 90 n°. Furthermore, the longer the asymptote, the closer the phase characteristic is to these values (Fig. 3). At high and low frequencies, i.e., at $\omega \rightarrow \infty$ and $\omega \rightarrow 0$, the slope of the asymptote should be 0 dB per octave or ± 6 dB per octave, since $\frac{\pi}{2} \leq \phi_2 \leq \frac{\pi}{2}$.

It should be pointed out that: a) if the amplitude and (or) phase of Z_2 is inside the range of permissible values, the transfer coefficient will be **greater than** on the boundaries of the range; b) if the amplitude of $|Z_2|$ turns out to be outside the range of permissible values, the **decrease** in the transfer coefficient can be compensated for within certain limits by the appropriate selection of ϕ_2 , and vice versa (Fig. 2).

The precise curves of the amplitude and phase of Z_2 are plotted and the points of intersection of the asymptote and coefficient ϵ of the quadratic factors are refined from the asymptotic curve. The phase of each factor is plotted without consideration of sign (Fig. 3 can be used as model in this case), and is designated by a "+" sign for a factor in the numerator and a "-" sign in the denominator. This

facilitates the process of determining the resulting phase and checking to see that inequality $\frac{\pi}{2} < \varphi_1 < \frac{\pi}{2}$ is satisfied throughout the frequency range. Corrections in the asymptotic curve are determined from Fig. 3 and are plotted on the upper part of the calculated curve in accordance with the points of intersection of the asymptotes, then they are added and plotted from the asymptotic curve.

The frequency dependence of G for assigned Z_2 and Z_H is plotted using the curves in Fig. 2. When necessary, Z_2 is corrected by introducing a constant factor, displacing the curves along the x -axis, or selecting new values of coefficients T , ξ .

If the matching band is narrow enough and it is inconvenient to use asymptotes, the curves of standard factors (Fig. 3) are combined with the calculated curve and factors are selected directly to make the resultant LKh fall in the range of permissible values and the phase satisfy inequalities $\frac{\pi}{2} < \varphi_1 < \frac{\pi}{2}$.

It may be necessary to plot two or three versions of the curves of the function of Z_2 from the simplest to more complex in order to determine how the frequency dependence of the transfer coefficient changes when Z_2 is complicated. Then the function which best satisfies the conditions of the problem is selected from the

available functions of Z_2 .

3. $T_i = 1/\omega_i$ are determined from the abscissas of the points of intersection of asymptote ω_i and the analytical expression for $Z_2(p)$ is written, by which a two-terminal network consisting of a reactive (in this case, matching) quadrupole loaded by effective resistance is realized [8, 11]. If the effective resistance is not equal to the internal impedance of the generator, the matching transformer is activated.

We will consider an example which illustrates the use of this method.

Example. Calculate a matching generator with a load in the frequency band $0.6 \leq \omega \leq 4$. Figure 4 shows the load circuit and its normalized impedance, measured on a mock-up (normalization condition $R_r = 1$).

Since the matching band is broad enough and the frequency dependence of the load impedance is complex, we will set $G = 0.6$ and we will plot the range of permissible values of Z_2 (dot-dashed lines).

Analyzing this region, we can conclude that amplitude $|Z_2|$ can

be virtually constant in the matching band, while phase ϕ_2 should be close to zero at low frequencies and negative at high frequencies.

Function $Z_2 = 3.09$ (9.8 dB) falls in the range of permissible values of the amplitude. The phase is equal to zero throughout the frequency range. The corresponding transfer coefficient is shown by the dot-dashed line in Fig. 4.

In order to raise the transfer coefficient at high frequencies, phase ϕ_2 must be made negative in this region. To do this, we make Z_2 more complex by adding the curve of the asymptote amplitude drawn at an angle of -6 dB per octave. The asymptotes intersect the abscissa at point $\omega = 6$. If $\omega > 6$, the phase in the matching band will not differ greatly from zero, and the transfer function virtually does not change. If $\omega < 6$, the matching band obtained is narrow, since the amplitude and phase of Z'_2 turn out to be beyond the range of permissible values at high frequencies. The broken line in Fig. 4 shows the amplitude and phase of Z'_2 , as well as the frequency dependence of the transfer coefficient.

We can plot the curves of a more complex function of Z_2'' , consisting of a linear factor in the numerator and a quadratic factor in the denominator, for example. Coefficients T and ϵ are selected so that
$$\frac{\pi}{2} < \phi_2 < \frac{\pi}{2}$$
 is satisfied throughout the frequency range.

The corrections in the asymptotic curve, as well as the phase of the numerator and denominator, are designated as (1) and (2), respectively. The amplitude and phase of Z_2'' and the calculated transfer coefficient are shown by the solid lines in Fig. 4.

As Fig. 4 shows, the transfer coefficients differ insignificantly in the last two cases. The analytical expressions for the functions of Z_2' and Z_2'' can easily be written as follows:

$$Z_2' = \frac{3.09}{\frac{1}{6}p+1}; \quad Z_2'' = \frac{2.82\left(\frac{1}{6}p+1\right)}{\left(\frac{1}{6}p\right)^2 + 2 \cdot 0.71 \frac{1}{6}p+1}.$$

Conclusions

1. This method makes it possible to calculate the parameters of a matching quadrupole for passive loads of any complexity with both lumped and distributed parameters. The necessary information on the load is limited to the value of the frequency dependence of its impedance in the matching band.

2. This method eliminates the need for using the Chebyshev or Butterworth polynomials to approximate the power transmission coefficient, which makes it possible to obtain good agreement at low

orders of $Z_2(p)$, i.e., with a small number of elements of the matching quadrupole.

3. The curves given in Figures 2-3 in this report are sufficient for the calculation.

APPENDIX

Conditions of Physical Realizability of Z_2

As we noted above, function $Z_2(p)$ should be a PRF. The necessary and sufficient conditions of the positiveness and reality of rational function $Z(p)$ are [8]:

1) the function is real at real values of the variable $p = \sigma$; 2) at $p = i\omega$ there is a nonnegative real part; 3) there are no poles in the right half-plane of the complex variable; 4) there are only simple poles with real positive remainders on axis $p = i\omega$.

The sufficient conditions of positiveness and reality are

established in the theorem below based on these generally-accepted conditions. These conditions are convenient if the analytical expression of the function is found from the logarithmic characteristics.

Theorem. Let function $Z(p)$ be represented by the product of factors $T_1 (Tp)^{-\epsilon_1} \cdot (Tp+1)^{\epsilon_1}$, $(T_2 p + 2Tp+1)^{-\epsilon_2}$ (T_i are real positive numbers, $0 \leq \epsilon_i < 1$). If we designate $Z(i\omega) = |Z(i\omega)| e^{i\phi}$ at $p = i\omega$ and ϕ satisfies inequalities $\frac{\pi}{2} < \phi < \frac{3\pi}{2}$, then $Z(p)$ is a PRF.

Proof. We will show that if the conditions of the theorem are satisfied, the necessary and sufficient conditions of the positiveness and reality of the functions cited above are satisfied.

1. At real values of the variable $p = \sigma$, function $Z(p)$ is real, since all coefficients T and ϵ are real numbers.

2. The real part of $Z(i\omega)$ is nonnegative on axis $p = i\omega$. It is determined by the following expression:

$$\operatorname{Re} Z(i\omega) = |Z(i\omega)| \cos \phi.$$

According to the condition of the theorem $\frac{\pi}{2} < \phi < \frac{3\pi}{2}$:
therefore, $\operatorname{Re} Z(i\omega) \geq 0$.

3. $Z(p)$ does not have poles on the right side of the complex plane. Actually, from the condition of the theorem $T > 0$, $\varepsilon \geq 0$; therefore, the zeroes and poles in $Z(p)$ will only be located on the left side of the half-plane or on axis $i\omega$.

4. Poles $Z(p)$ on axis $i\omega$ should be simple with real and positive remainders.

Suppose that at point $p = i\omega_0$ function $Z(p)$ has pole n of series ($n \neq 1$). Then the expansion of $Z(p)$ into the Laurent series relative to point $i\omega_0$ will be [8]:

$$Z(p) = \frac{a_{-n}}{(p - i\omega_0)^n} + \dots + \frac{a_{-1}}{p - i\omega_0} + a_0 + \dots$$

We will draw a circle with its center at point $p = i\omega_0$ and a radius as conveniently small as possible, but not equal to zero. We will designate:

$$\begin{aligned} p - i\omega_0 &= \rho e^{i\theta}, \\ a_{-n} &= A_{-n} e^{i\psi}. \end{aligned}$$

At $p \rightarrow i\omega_0$, disregarding all the terms of the series except the first on the circumference of radius ρ , we will have

$$Z(p) = \frac{A_{-n}}{\rho^n} e^{i(n\theta - \psi)}.$$

Moving over the circumference, we will intersect axis $i\omega$ twice: above point $i\omega_0$ - at point $i\omega_1$, where $\theta_1 = \pi/2$, and below $i\omega_0$ - at point $i\omega_2$, where $\theta_2 = \pi/2$.

From the condition of the theorem, angles $\varphi_1 = \Psi - n\theta_1$ and $\varphi_2 = \Psi - n\theta_2$ at $\Psi = \text{const}$ should satisfy the inequalities:

$$-\frac{\pi}{2} < \Psi - n \frac{\pi}{2} < \frac{\pi}{2}, \quad (1)$$

$$-\frac{\pi}{2} < \Psi + n \frac{\pi}{2} < \frac{\pi}{2}. \quad (2)$$

We will assume that $\Psi > 0$; then (2) is not satisfied at any $n \geq 1$. If $\Psi < 0$, (1) is not satisfied at any $n \geq 1$. Therefore, it is necessary to set $\Psi = 0$; then we will obtain $n = 1$ from (1) and (2).

Thus, the pole at point $i\omega_0$ is simple ($n = 1$), and coefficient a_{-1} is the remainder of $Z(p)$ in this pole, whereupon the remainder is real and positive ($\Psi = 0$).

The sufficiency of the conditions of the theorem to make function $Z(p)$ a PRF has been proven. The need for these conditions was shown in the introduction.

Bibliography

1. R. M. Fano. Theoretical Limitations on the Matching Bands of Random Impedances. Izd. "Sovetskoye radio," 1965.
2. D. C. Youla. A New Theory of Broad-Band Matching. IEEE Trans., 1964, CT-11, No. 1, 30.
3. O. V. Alekeseyev, A. I. Zhivotovskiy, G. G. Chavka. Broad-Band Matching of Simple Types of Loads. "Problems of Electronics" [Voprosy elektroniki], TRC, 1965, No. 2, 3.
4. G. L. Matthaei. Synthesis of Chebyshev Impedance-Matching Networks, Filters and Intestages. IRE Trans., 1956, CT-3, No. 3, 163.
5. N. Z. Shvarts, V. I. Uvbarkh. New Relationships for the Synthesis of Chebyshev Band-Matching Circuits with Nonresonant Links. "Radio Engineering" [Radiotekhnika], 1968, 23, No. 10, 5.
6. N. Z. Shvarts. Synthesis of Matching Circuits with the Maximum Possible Plane Characteristics. "Radio Engineering," 1969, 24, No. 1, 104.
7. Yu. Ya. Yurov, V. A. Nelep. Permissible Changes in the Parameters of a Matching Quadrupole. Bulletin of the Higher Educational Institutes of the USSR [Izv. vuzov SSSR] - Radio

Engineering, 1972, 15, No. 2.

8. E. A. Gillemain. Synthesis of Passive Circuits, Izd. "Svyaz'," 1970.

9. G. Bode. Theory of Circuits and Designing Amplifiers with Feedback. Foreign Press Publications [Izd. in. lit-ry], 1948.

10. J. A. Greenwood, J. V. Holdam, D. Macrae (editors). Electronic Instruments, McGraw-Hill Book Co., 1948.

11. D. C. Youla. A New Theory of Cascade Synthesis. IRE Trans., 1961, PGGT-8, No. 3, 244.

Received 24 May 1971

Fig. 1. General broad-band matching circuit.




Fig. 2. Curves of dependence $\psi_n(\psi_2)$ for different values of ϵ and G
 (— $G = 0.6$; - - - $G = 0.8$; -.-.- $G = 1$).

KEY: (1) dB.




Fig. 3. Logarithmic characteristics of function: --- $(T\omega + 1)^{-1}$ and
 — $[(T\omega)^2 + 2\zeta T\omega + 1]^{-1}$.





Fig. 4. Diagram of load and its normalized impedance (--- - module, phase and frequency dependence of transfer coefficient Z_2' ; - module, phase and calculated transfer coefficient of Z_2'').

KEY: (1) dB.



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER FTD-ID(RS)T-1637-77	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) USING LOGARITHMIC CHARACTERISTICS TO CALCULATE BROAD-BAND MATCHING OF A GENERATOR WITH A LOAD	5. TYPE OF REPORT & PERIOD COVERED Translation	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) Yu. Ya. Yurov and V. A. Nelep	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Foreign Technology Division Air Force Systems Command U. S. Air Force	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE July 1972	
	13. NUMBER OF PAGES 21	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) 09		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

ORGANIZATION	MICROFICHE	ORGANIZATION	MICROFICHE
A205 DMATC	1	E053 AF/INAKA	1
A210 DMAAC	2	E017 AF/RDXTR-W	1
B344 DIA/RDS-3C	8	E404 AEDC	1
C043 USAMIIA	1	E408 AFWL	1
C509 BALLISTIC RES LABS	1	E410 ADTC	1
C510 AIR MOBILITY R&D LAB/FIO	1	E413 ESD	2
C513 PICATINNY ARSENAL	1	FTD	
C535 AVIATION SYS COMD	1	CCN	1
C557 USAIIC	1	ETID	1
C591 FSTC	5	NIA/PHS	1
C619 MIA REDSTONE	1	NICD	5
D008 NISC	1		
H300 USAICE (USAREUR)	1		
P005 ERDA	1		
P055 CIA/CRS/ADD/SD	1		
NAVORDSTA (50L)	1		
NASA/KSI	1		
AFIT/LD	1		