

UNCLASSIFIED
~~CONFIDENTIAL~~

Copy 3

Contract N123(953)54996A
TRACOR Project 002-009-23
Document Number
TRACOR-SD-67-013-C

MON 19 JUL 1967

LEVEL II

K1969

OOVI LIBRARY COPY

(1)

MOST Project -3

ADAO 67394

TECHNICAL NOTE

C/P ARRAY BEAM PATTERN WITH AMPLITUDE SHADING
CONSISTING OF COSINE-SQUARED ON A PEDESTAL (U)

DDC FILE COPY

Submitted to
U. S. Navy Electronics Laboratory
San Diego, California 92152

Attention: Code 2110

DDC
RECEIVED
APR 3 1979
F

690425 0260

690425 JUN 12, 1967

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

6500 TRACOR LANE • AUSTIN, TEXAS 78721 • 512 926-2800

TRACOR

INC.

UNCLASSIFIED

GROUP - 4
DOWNGRADED AT 3 YEAR INTERVALS:
DECLASSIFIED AFTER 12 YEARS.

~~CONFIDENTIAL~~

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Sec. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

UNCLASSIFIED
~~CONFIDENTIAL~~

Copy 3

TRACOR, INC. 3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

(15)
Contract N123(953)54996
TRACOR Project 002-009-23
Document Number
TRACOR-SD-67-013-C

(14)

(12) 1

(1) TECHNICAL NOTE

(C) C/P ARRAY BEAM PATTERN WITH AMPLITUDE SHADING
CONSISTING OF COSINE-SQUARED ON A PEDESTAL

Submitted to
U. S. Navy Electronics Laboratory
San Diego, California 92152
Attention: Code 2110

(11) 12 Jun 1967

ADDITIONAL TO	
NTIS	White Section ☒
DOC	Buff Section ☐
UNANNOUNCED	☐
BY <i>Robert Mador</i>	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

Approved:

D.V. Holliday
D. V. Holliday
Project Director

Prepared by:

(10) *Robert Mador*
Robert Mador
Senior Scientist

This document contains information affecting the national defense of the United States, within the meaning of the Espionage Laws, Title 18, U. S. C., Sections 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

GROUP - 4
DOWNGRADED AT 3 YEAR INTERVALS:
DECLASSIFIED AFTER 12 YEARS.

~~CONFIDENTIAL~~
UNCLASSIFIED

403 906

gwr

UNCLASSIFIED

TRACOR, INC. 3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

C/P ARRAY BEAM PATTERN WITH AMPLITUDE SHADING CONSISTING OF COSINE-SQUARED ON A PEDESTAL

↙ In calculating C/P Array beam patterns, certain time-consuming summations can be avoided if they can be expressed in closed analytical form. Such is known to be the case, for example, for uniform amplitude shading plus the phasing required to steer the beam in some particular direction. Even for some types of non-uniform shading it appears that the summations involved in the beam pattern analysis can be carried out to closed form. One such type is that of shading consisting of cosine-squared on a pedestal. The purpose of this note is to derive the beam pattern equations in closed form for cosine-squared on a pedestal amplitude shading (plus phasing for steering) and to present some patterns computed from the results obtained.

↖ Our starting point is the total far-field pressure expressed as

$$P(\varphi, \theta) = \rho(\varphi, \theta) \left[\sum_{x=-\frac{M-1}{2}}^{\frac{M-1}{2}} (p_{11} + p_{12} \cos^2 \frac{\pi x}{M-1}) e^{-jAx} \right] \left[\sum_{z=-\frac{N-1}{2}}^{\frac{N-1}{2}} (p_{21} + p_{22} \cos^2 \frac{\pi z}{N-1}) e^{-jBz} \right] \quad (1)$$

in the direction (φ, θ) , where φ is the usual depression look angle and θ is the azimuthal look angle (measured from dead ahead). The function $\rho(\varphi, \theta)$ is the cardioid response function given by

$$\rho = \frac{1}{2}(1 + \cos w \cos \varphi \sin \theta + \sin w \sin \varphi) \quad (2)$$

w being the array tilt angle. Other pertinent relations and

UNCLASSIFIED

UNCLASSIFIED

TRACOR, INC. 3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

definitions are:

$$A = ka(\cos \varphi \cos \theta - \cos \varphi_0 \cos \theta_0) \quad (3)$$

$$B = kb[\cos w(\sin \varphi - \sin \varphi_0) - \sin w(\cos \varphi \sin \theta - \cos \varphi_0 \sin \theta_0)] \quad (4)$$

(φ_0, θ_0) = steered direction

$k = 2\pi f/c$ = wave number

f = frequency

c = speed of sound

a = column spacing

b = row spacing

M = number of columns

N = number of rows

P_{11} = pedestal value for horizontal direction

P_{12} = cosine-squared amplitude (horizontal direction)

P_{21} = pedestal value for vertical direction

P_{22} = cosine-squared amplitude (vertical direction)

The functions A and B above incorporate the phasing considerations required for steering such that the individual element pressures are all in phase in the steered direction (φ_0, θ_0) . It should be

UNCLASSIFIED

TRACOR, INC. 3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

noted that in (1) M and N may be odd or even.

Since the summations contained in (1) are both of the same form, it will suffice to work with only one of them. Let us consider

$$S_1 = \sum_x (p_{11} + p_{12} \cos^2 \frac{\alpha x}{2}) e^{-jAx} \quad (5)$$

$$= \sum_x (p_{11} + p_{12} \cosh^2 \frac{j\alpha x}{2}) e^{-jAx}$$

where the summation limits are as indicated in (1) and $\alpha/2 = \pi/(M-1)$.
Now

$$\cosh^2 \frac{j\alpha x}{2} = \frac{1}{2} (2 + e^{j\alpha x} + e^{-j\alpha x})$$

so that S_1 becomes

$$S_1 = (p_{11} + \frac{1}{2} p_{12}) \sum_x e^{-jAx} + \frac{1}{2} p_{12} \left[\sum_x e^{-j(A+\alpha)x} + \sum_x e^{-j(A-\alpha)x} \right]$$

$$= (p_{11} + \frac{1}{2} p_{12}) \frac{\sin MA/2}{\sin A/2} + \frac{1}{2} p_{12} \left\{ \frac{\sin [M(A+\alpha)/2]}{\sin [(A+\alpha)/2]} + \frac{\sin [M(A-\alpha)/2]}{\sin [(A-\alpha)/2]} \right\} \quad (6)$$

each of the three sums above being directly summable as a geometric series. Since

$$M\alpha/2 = \pi M/(M-1) = \pi + \pi/(M-1)$$

UNCLASSIFIED

TRACOR, INC. 3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

we may rewrite (6) as

$$S_1 = (p_{11} + \frac{1}{2} p_{12}) \frac{\sin MA/2}{\sin A/2} - \frac{1}{2} p_{12} \left[\frac{\sin(\frac{MA}{2} + \frac{\pi}{M-1})}{\sin(\frac{A}{2} + \frac{\pi}{M-1})} + \frac{\sin(\frac{MA}{2} - \frac{\pi}{M-1})}{\sin(\frac{A}{2} - \frac{\pi}{M-1})} \right] \quad (7)$$

An analogous expression holds for S_2 , the other sum contained in (1).

To find the beam pattern in conventional form, we normalize with respect to the pressure in the steered direction (φ_0, θ_0) . In this direction $A=B=0$, and S_1 becomes

$$S_{10} = (p_{11} + \frac{1}{2} p_{12})M - \frac{1}{2} p_{12}$$

with an analogous expression for S_{20} . Defining $R_1 = S_1/S_{10}$ and $R_2 = S_2/S_{20}$, we have:

$$R_1 = \frac{\frac{\sin MA/2}{\sin A/2} - K_1 \left[\frac{\sin(\frac{MA}{2} + \frac{\pi}{M-1})}{\sin(\frac{A}{2} + \frac{\pi}{M-1})} + \frac{\sin(\frac{MA}{2} - \frac{\pi}{M-1})}{\sin(\frac{A}{2} - \frac{\pi}{M-1})} \right]}{M - 2K_1} \quad (8)$$

$$R_2 = \frac{\frac{\sin NB/2}{\sin B/2} - K_2 \left[\frac{\sin(\frac{NB}{2} + \frac{\pi}{N-1})}{\sin(\frac{B}{2} + \frac{\pi}{N-1})} + \frac{\sin(\frac{NB}{2} - \frac{\pi}{N-1})}{\sin(\frac{B}{2} - \frac{\pi}{N-1})} \right]}{N - 2K_2} \quad (9)$$

where $K_1 = p_{12}/(4 p_{11} + 2 p_{12})$ and $K_2 = p_{22}/(4 p_{21} + 2 p_{22})$.

Additionally,

CONFIDENTIAL

TRACOR, INC. 3065 ROSECRANS PLACE, SAN DIEGO, CALIFORNIA 92110

$$\frac{\rho}{\rho_0} = \frac{1 + \cos w \cos \varphi \sin \theta + \sin w \sin \varphi}{1 + \cos w \cos \varphi_0 \sin \theta_0 + \sin w \sin \varphi_0} \quad (10)$$

The beam pattern equation in dB relative to the intensity in the steered direction is


$$\theta(\varphi, \theta) = 20 \log (R_1 R_2 \rho / \rho_0) \quad (11)$$

where the constituent factors are given by (8) through (10) and other pertinent definitions and relations are as stated earlier in this paper. Note that with appropriate values assigned to the shading constants the results obtained here cover the cases of natural beams and cosine-squared amplitude shading with or without pedestals.

The foregoing beam pattern equations were programmed for the computer by TRACOR and several runs made to produce the patterns plotted in Figs. 1 through 5. Inputs common to all these patterns are:

$$\begin{aligned} c &= 4900.36 \text{ ft/sec.} \\ M &= 224 \\ N &= 12 \\ a &= b = 0.656 \text{ ft.} \\ w &= 25^\circ \end{aligned}$$

Uniquely identifying information is shown in each figure. In general, the angle scales in the figures are different in order to present the detail of sidelobe structure.



CONFIDENTIAL




FIG. 2: AZIMUTHAL BEAM PATTERNS
2500 cps, $\varphi_0=0^\circ$, $\theta_0=5^\circ$

CONFIDENTIAL

CONFIDENTIAL




FIG. 3: AZIMUTHAL BEAM PATTERNS
800 cps, $\varphi_0=0^\circ$, $\theta_0=90^\circ$

CONFIDENTIAL




FIG. 4: AZIMUTHAL BEAM PATTERNS
800 cps, $\varphi_0=0^\circ$, $\theta_0=5^\circ$

CONFIDENTIAL




FIG. 5: VERTICAL BEAM PATTERNS
2500 cps, $\phi_0=0^\circ$, $\theta_0=90^\circ$