

AD-A072 110

PURDUE UNIV LAFAYETTE IND SCHOOL OF ELECTRICAL ENGI--ETC F/G 17/1
APPLICATION OF CIRCULAR TOLERANCE REGIONS TO TRESSI FEATURE VEC--ETC(U)
JUL 67 E A PATRICK, L SHEN N00024-67-C-1162

UNCLASSIFIED


NL

| OF |
AD
A072110



END
DATE
FILMED

9 - 79
DDC



Nobsr - 93124 (on loan)

32545

Copy #1

DCC NO. 18340

~~CONFIDENTIAL~~
DDI LIBRARY COPY

UNCLASSIFIED FOR RETENTION

PURDUE UNIVERSITY

SCHOOL OF ELECTRICAL ENGINEERING

MOST Project -3

RECEIVED

OCT 4 1967

LIBRARY
DEFENSE RESEARCH LABORATORY

LEVEL

6 APPLICATION OF CIRCULAR TOLERANCE
REGIONS TO TRESSI FEATURE VECTORS (U)

Prepared for

Naval Ship Systems Command Code 1622C

on

Contract No. N00024-67-C-1162, Nobsr - 93124

Project Serial No. F101-0316, Task 8637

17 SF 1010316

by

11 4 JUL 67

10

E. A./Patrick - Principal Investigator
Leon/Shen

12

9p.

Period Covered

9 Rept for 4 May 1966 through 4 Jul 1967

DDC

AUG 1 1979

A

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

~~CONFIDENTIAL~~

RECEIVED

OCT 5 1966

DRL

DCC

UNCLASSIFIED

292 000

ENCL (,) TO SHIPS SER 00VIC-0536

070017-0174

ADA072110

DDC FILE COPY

000530

000530

UNCLASSIFIED

~~CONFIDENTIAL~~

DOWNGRADED AT 3-YEAR INTERVALS • DECLASSIFIED AFTER 12 YEARS

PAGES IN THIS REPORT ARE TO BE
CONSIDERED UNCLASSIFIED UNLESS
OTHERWISE MARKED WITH THEIR
INDIVIDUAL CLASSIFICATION.

This material contains information
affecting the national defense of
the United States within the meaning
of the Espionage Laws, Title 18,
U.S.C., Sections 793 and 794, the
transmission or revelation of which
in any manner to an unauthorized
person is prohibited by law.

Accession For	
NTIS GINA	☒
DOC TAB	☐
Unannounced	☐
Justification	☐
<i>Atties on file</i>	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or special
<i>A</i>	

UNCLASSIFIED

~~CONFIDENTIAL~~

651208-1398

670817-0174

UNCLASSIFIED

- 1 -

~~CONFIDENTIAL~~

Introduction

A new learning decision rule, the "Distribution Free, Minimum Conditional Risk Learning System" (DFMCR), is introduced to the sonar problem in reference [1]. There, its performance in processing four classes of Tressi feature vectors, is experimentally determined for one type of tolerance region construction. The tolerance region concept is a basic distribution free concept used in the definition of the DFMCR decision rule. The type of tolerance region construction used in reference [1] is a sequential construction called "bounding, binning, and sub-binning." This tolerance region construction technique has the advantage that it involves straight lines which are easy to implement in a generalized digital computer or using a small, special purpose computer.

Performance calculations for the DFMCR decision rule are given in reference [2]. These performance calculations assume that tolerance regions can be constructed from supervised samples such that a tolerance region is sufficiently small such that the underlying probability density function can be assumed uniform within the region. It is not necessary that the probability density function be uniform within the region--only that the uniformity assumption does not significantly increase the probability of error.

The tolerance regions constructed using straight lines in reference [1] become "small" as the number of training samples becomes large; however, for "small" sample sizes (such as 200, four-dimensional tressi vectors), these tolerance regions may not be as small as possible or desired. Therefore it is desirable to find tolerance regions which are "relatively small" for small sample sizes.

In reference [2] an example is given using circular tolerance regions. These tolerance regions are relatively small for small sample sizes. It is

~~CONFIDENTIAL~~

UNCLASSIFIED

CONFIDENTIAL

shown in reference [2] that a DFMCR decision rule using circular tolerance regions includes such decision rules as the "nearest neighbor" decision rule as special case--thus demonstrating another powerful characteristic of the DFMCR decision rule. A disadvantage of the circular tolerance region, however, is that it is more complex to implement than the tolerance region using straight lines. The circular tolerance region offers no complexity reduction and can't be used for large sample sizes. For large sample sizes, a complexity reducing tolerance region such as constructed using straight lines is necessary.

If the classes concerned are separable, then it is expected that almost any method of constructing tolerance regions would cause the DFMCR decision rule to perform with zero probability of error. Because the sonar classes represented by the Tressi feature vectors are not separable, a circular tolerance region should produce a lower probability of error than a tolerance region constructed using straight lines. This report includes experimental results for the performance of the DFMCR decision rule, using circular tolerance regions when processing Tressi feature vectors.

CONFIDENTIAL

CONFIDENTIAL

Circular Tolerance Regions and DFMCR Decision Rule

The DFMCR decision rule using circular tolerance regions is described as follows: Suppose there are four sets of training vectors indexed by w_1, w_2, w_3 , and w_4 respectively. Let n_i training vectors be available for each class w_i , $i=1, 2, 3, 4$ such that $n=n_1+n_2+n_3+n_4$. Then a $n+1^{st}$ vector sample (called the candidate sample) is presented for recognition. The decision rule provides for storing the n_i vector samples for each class as shown for classes w_1 and w_2 in Figure 1, for a two-dimensional example. Suppose that the candidate sample, denoted by X^C , is as shown in Figure 1. Then, for class w_1 , construct a circle centered at X^C and passing through the v^{th} nearest sample to X^C . The example in Figure 1 is for $v=3$. Then the resulting circles have all the properties of tolerance regions containing 3 samples. In reference [2] it is shown that to make a decision as to which class caused X^C , decide that class whose tolerance region has the smallest volume (minimizes probability of error assuming equal class probabilities and zero-one loss functions).

Circular tolerance regions, constructed as above, were used in the DFMCR to process the same Tressi vectors previously processed using tolerance regions constructed using straight lines. The experimental performance is shown in Table 1. For all cases considered in Table 1, 150 training samples were used for each class. For recognition, 50 samples were used which were not part of the training set.

The results shown in Table 1 should be compared with those in Table 4 of reference [1]. By doing this it is seen that circular tolerance regions result in considerable improvement in performance over tolerance regions constructed using straight lines.

CONFIDENTIAL

691208-348
THIS PAGE IS BEST QUALITY PRACTITIONER
FROM COPY FURNISHED TO DDC

CONFIDENTIAL

The experimental procedure used in obtaining the results in Table 1 are as follows. If X^c is from a submarine class (w_1 , w_2 , or w_3), an error is recorded only if X^c is decided from class w_4 (non sub).

Conclusions

Circular tolerance regions give greater performance for small sample sizes than tolerance regions constructed using straight lines. For situations where the vector samples are not separable and/or the number of sample vectors available for training is "relatively small," circular tolerance regions should be used instead of tolerance regions constructed using straight lines. The circular tolerance regions used in the experiments reported were constructed with $v=3$. It was found experimentally that $v < 3$ or $v > 3$ resulted in poorer experimental performance. Theoretical results, with v as a parameter, would be desirable.

The Tressi feature vectors were used in the experiments reported herein for the purpose of comparison.

CONFIDENTIAL




Figure 1. Two-dimensional, two class example of DFMC decision rule using circular tolerance regions.

CS1200-328

CONFIDENTIAL

Training Samples				Percent Correct For 50 Recognition Samples				v : Number of Samples in Circular Tolerance Region
w_1	w_2	w_3	w_4	w_1	w_2	w_3	w_4	
150	0	0	150	92%	---	---	80%	3
150	150	0	150	88%	70%	---	64%	3
150	0	150	150	88%	---	84%	68%	3
150	150	150	150	88%	76%	92%	62%	3
0	0	150	150	---	---	78%	76%	3
0	150	0	150	---	62%	---	78%	3

w_1 : 0551 2 ms, complete, sub, snorkling, constant aspect beam, high speed, short range
 w_2 : 0634 2 ms, complete, sub, shallow, changing aspect unknown, low speed, short range
 w_3 : 0655 2 ms, complete, sub, shallow, constant aspect quarter, high speed, short range
 w_4 : 0030 2 ms, complete, non-sub, unknown

Table 1. Decision based on one Tressl vector. Vectors used for recognition different from vectors used for training.

CONFIDENTIAL

601208-328

UNCLASSIFIED

REFERENCES

- [1] "Nonsupervised Sampleset Construction Techniques" (U), Final report on Contract No. NObsr 95285 Ser 0253-524, E. A. Patrick Principal Investigator, March 1, 1967.
- [2] "Introduction to the Performance of Distribution Free Minimum Conditional Risk Learning Systems," Purdue University, TR-EE 67-12, July 1967, performed on Contract No. N00024-67-C-1162.

UNCLASSIFIED

681208-0228