

AD-A072 205

NAVY UNDERWATER SOUND LAB NEW LONDON CT
IMPLANTING OF THE FIXED ACOUSTIC BUOY (FAB) OFF BERMUDA.(U)
FEB 61 P T MISISCO


F/6 20/1

UNCLASSIFIED


USL-TM-953-12

NL

| OF |
AD
A072:05



END
DATE
FILMED
9-79
DDC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

LEVEL

THIS COPY FOR

Hudson Labs. Dr. Troesch

COPY 45 OF 49 COPIES

U. S. NAVY UNDERWATER SOUND LABORATORY
FORT TRUMBULL, NEW LONDON CONNECTICUT

COLUMBIA UNIVERSITY
HUDSON LABORATORIES
CONTRACT Nonr-266(34)

DA 072205

6 IMPLANTING OF THE FIXED ACOUSTIC BUOY (FAB) OFF BERMUDA

by

9 10 Paul T. Misisco

12 25 p.

1 R

USL TECHNICAL MEMORANDUM No. 953-12

11 10 Feb 1961

14 USL-TM-953-12

DDC
RECEIVED
AUG 6 1979
A

DISTRIBUTION STATEMENT A
Approved for public release
Distribution Unlimited

Background

The Fixed Acoustic Buoy (FAB) was designed and constructed by Martin Company (formerly Martin Aircraft Corp., Baltimore, Md.) to study various parameters relating to ambient noise in the deep ocean. In December 1960 the unit was implanted in 13,700 feet of water in an area approximately 19 miles southwest of Plantagenet Bank, Bermuda. This technical memorandum describes the FAB unit and the technique used to place it on the bottom. A 16 mm. motion picture film report of the operations is also available at USN USL Photo-Optical Techniques Branch.

A complete description of the electrical and mechanical features of the array may be found in reference (a), Fig. 1, which is reproduced from that document, gives a schematic representation of the mechanical arrangement involved. The array is described as a "steerable, symmetrical linear array of twenty-one hydrophones with individual inputs to a beam forming system". (Ref. (a)).

The array was designed to study ambient noise in the deep ocean, with respect to "level, spectrum, angle of arrival, sea state and season". (Ref. (a)).

Some mechanical modifications which are not shown in Fig. 1, were made to the system prior to implanting. These include the addition of a 4600 lb. cement anchor; the enlargement of the buoyancy tank to hold 562 gallons of gasoline; and the lengthening of the cable between the float and the mast from 25 feet to 250 feet. There were no reported changes to the electronics.

DDC FILE COPY

116
02
02
00
10

Doc 1 79 USN USL 08 07 394
254200 FEB 2 1961

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. 953-12	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) IMPLANTING OF THE FIXED ACOUSTIC BUOY (FAB) OFF BURMUDA		5. TYPE OF REPORT & PERIOD COVERED Tech memo
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Misisco, Paul T.		8. CONTRACT OR GRANT NUMBER(s) Nonr-266(84)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Underwater Systems Center New London, CT		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research, Code 220 800 North Quincy St. Arlington, VA 22217		12. REPORT DATE 10 FEB 61
		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)		

DD FORM 1473
1 JAN 73

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Fig. 2 shows the mast and the hydrophone arrangement.

Fig. 3 is a detail shot showing the hydrophone placement in the mast and a portion of the wiring harness.

Figs. 4 and 4a present two views of an individual hydrophone. The film box is 4 inches square, and it is included to give some idea of hydrophone size. In Fig. 4a can be seen the preamplifier which was mounted concentric with the axis of the element.

Fig. 5 shows a general view of the pressure-proof sphere which housed the electronics. In the background the cement anchor can be seen.

Fig. 6 shows the arrangement of the electronics nested in the sphere.

Fig. 7 shows the general arrangement of the battery box which housed two sets of Nickel-Cadmium batteries. The main feeder cable to the mast can be seen on the right. The articulated chain in the foreground was connected to the sphere to prevent excessive strain on the feeder cable.

Fig. 8 shows the anchor, sphere, battery box and feeder cable. Note that the cable has been protected against chaffing by several layers of high-pressure steam hose and a manila rope whipping. Note also, the link chain used to join the battery box to the sphere. This was later replaced by the articulated chain shown in Fig. 7.

Fig. 9 shows a general view of the buoyancy tank in its cradle, alongside the launching ship.

Fig. 10 is a close-up view of the tank, and Fig. 11 shows the two pressure-relief valves mounted on the tank to permit continuous equalization of pressure with depth during the implanting operation.

Launch Procedures:

Implanting operations were originally scheduled for mid November, 1960, using the USS AEOLUS and a chartered commercial vessel, the Inagua Ranger. The unit was placed on board at Norfolk Va., and transported to Bermuda. While making detailed photographs of the hydrophone mast, several fractures in the poly-ethylene "tee-joints" used in the wiring harness were noticed. These were reported and promptly repaired.

The AEOLUS then proceeded to the operational area, and laid the first

78 08 07 394

leg of the coaxial cable which was to be used to link the FAB to the monitoring station. While enroute, additional fractures in the polyethylene harness were discovered and the operations were halted. The AEOLUS returned to Norfolk, and the harness was removed and returned to Martin Company for refabrication.

It was ultimately learned that the fractures were due to improper curing of the poly-ethylene.

Because of operational commitments, the AEOLUS was unable to continue its participation and the FAB unit and its associated equipment was transferred to USS NEPTUNE. On November 28, the NEPTUNE departed Norfolk for Bermuda with the repaired FAB unit on board.

While at Bermuda, the unit was checked out electronically and a test launching was made at dockside to familiarize the crew with launch procedures.

On 9 December, the NEPTUNE arrived on station at the FAB site and began **launching operations.**

Fig. 12 is a sketch showing the method of launching.

Fig. 13 shows the unit prior to launching. Two-and-one-half miles of nylon line were attached to the buoy by a corrosive link. The other end of the line was given to the Inagua Ranger which opened range to approximately two and one-half miles.

Fig. 14 shows the buoy being towed from the NEPTUNE by a small PR Boat. Two lines may be seen attached to the nose of the buoy. One leads to the PR Boat, while the other is the nylon line attached to Inagua Ranger.

Once the buoy was afloat the mast was lowered from the NEPTUNE by three lines as shown in Fig. 15. An additional line was attached to the cement anchor and may be seen in Fig. 16. In this manner, the unit was lowered to the bottom.

Two abortive attempts to place the unit were made on December 9. In both instances the corrosive link shown in Fig. 17 broke during the original streaming operation, and had to be replaced.

On December 10 the unit was successfully planted. The coaxial cable link between the FAB and the monitoring station was completed, and the unit began operating.

USL Tech Memo
No. 953-12

Civilian personnel aboard ship to take part in these operations are listed below:

Mr. H. Wyeth	Simplex Co.	Senior Project Leader
Mr. J. Roe	Simplex Co.	Liaison Officer
Mr. Earl Goss	Simplex Co.	Cable Splicer
Mr. L. Blickley	Martin Co.	Project Leader
Mr. D. Webb	Martin Co.	Electronic Engineer
Mr. R. Oberlin	Martin Co.	Electronic Engineer
Mr. G. Gerlach	Martin Co.	Electronic Engineer
Mr. J. Hawkins	Martin Co.	Electronic Technician
Mr. G. Overman	Martin Co.	Electronic Technician
Mr. F. Gibbs	Hastings Raydist Co.	Navigation Equipment Engineer
Mr. P. Misisco	USN USL	Photographer

While aboard the USS AEOLUS and the USS NEPTUNE I arranged to ride the helicopters assigned to assist on these operations. Aerial photographs were taken, of the Naval facilities in Bermuda, the ships assigned to this operation, and Argus Island. Negatives and prints are on file at the USN USL Photo-Optical Techniques Branch office.

Paul T. Misisco
PAUL T. MISISCO
Photographer (Scientific)

THIS PAGE IS BEST QUALITY PRACTICABLE
FROM COPY FURNISHED TO DDC

Accession For	NTIS GRA&I	DDC TAB	Unannounced Justification
By			
Distribution/			
Availability Codes			
Dist	A		Avail and/or special

USL Tech Memo
No. 953-12

List of References:

(a) Fixed Acoustic Buoy, by L. Buckley, Martin Co.
Baltimore, Md.

Engineering Report 11213,
USL Acc. #34807, of May 1960

THIS PAGE IS NOT REPRODUCIBLE
FROM COPY FURNISHED TO DDC

NOMENCLATURE:-

1. LOWERING CABLE
 2. DISCONNECT FOR LOWERING CABLE (Coaxial Link)
 3. BUOYANCY TANK
 4. MILLER BALL BEARING SWIVEL
 5. WIRE ROPE CLIP
 6. GALVANIZED WIRE ROPE (1/2" DIAM)
 7. HYDROPHONE
 8. HYDROPHONE SUPPORT STRUCTURE
 9. TILT INDICATOR & CONTAINER
 10. BATTERIES & CANNISTER (EXISTING)
 11. CHAIN & ANCHOR SHACKLES
 12. COAX CABLE RUBBING WEAR SHIELD
 13. SOLID STEEL CABLE THIMBLE
 14. LINK PLATES
 15. ARMORED SUBMARINE CABLE
 16. PRESSURE VESSEL (EXISTING)
 17. CABLE TERMINAL SUPPORT BRACKET
 18. HOISTING FITTING
 19. SHIELD & SUPPORT FOR ELECT WIRING
 20. STEEL TUBE FOR ELECTRICAL CONDUIT
 21. FLEXIBLE CONDUIT TUBE
 22. NUT - CABLE ARMOR SUPPORT
 23. TAPERED-HOLE CABLE FITTING
 24. LOCK SCREW
 25. CABLE ARMOR HOOK SHAPE
 26. ANTI-ROTATION KEY WAY
 27. THREADED STRUCTURAL NIPPLE
 28. CONICAL BUSHING
 29. LOCK RING AN 996
 30. COAX CABLE
- FIXED ACOUSTIC BUOY
 WET NET WEIGHT 690 LB
 TOTAL DRY WEIGHT 4390 LB
 BUOYANCY OF BUOY 450 LB
 CAPACITY OF BUOY 365 GAL.

THE MARTIN COMPANY	
BALTIMORE, MARYLAND	
DRAWN BY	CHECKED BY
DESIGNED BY	APPROVED BY
DEEP WATER STATION	
FIXED ACOUSTIC BUOY	
PROGRAM FIGURE 1	
400-000036	






Fig. 1



Fig. 2

**U. S. Navy Underwater Sound Laboratory
NP24 - 19857 - 3 - 61**

USL Tech Memo No. 953-12-61

Official Photograph




Fig. 3

USL Tech Memo No. 953-12-61

**U. S. Navy Underwater Sound Laboratory
NP 24 - 19858 - 3 - 61**

Official Photograph



Fig. 4

USL Tech Memo No. 953-12-61

U. S. Navy Underwater Sound Laboratory
NP24 - 19859 - 3 - 61

Official Photograph




Fig. 4A

USL Tech Memo No. 953-12-61

U. S Navy Underwater Sound Laboratory
NP24 - 19860 - 3 - 61

Official Photograph



Fig. 5

USL Tech Memo No. 953-12-61

U. S. Navy Underwater Sound Laboratory
NP24 - 19861 - 3 - 61

Official Photograph





Fig. 6

USL Tech Memo No. 953-12-61

**U. S. Navy Underwater Sound Laboratory
NP24 - 19862 - 3 - 61**

Official Photograph



USL Tech Memo No. 953-12-61

Fig. 7

Official Photograph

U. S. Navy Underwater Sound Laboratory
NP24 - 19863 - 3 - 61

COLUMBIA UNIVERSITY
HUDSON LABORATORIES
CONTRACT Nonr-265(C4)





Fig. 8

USL Tech Memo No. 953-12-61



USL Tech Memo No. 953-12-61

Fig. 9

Official Photograph

U. S. Navy Underwater Sound Laboratory
NP24 - 19865 - 3 - 61




Fig. 10

USL Tech Memo No. 953-12-61

**U. S. Navy Underwater Sound Laboratory
NP24 - 19866 - 3 - 61**

Official Photograph




Fig. 11

USL Tech Memo No. 953-12-61

Official Photograph

U. S. Navy Underwater Sound Laboratory
NP24 - 19867 - 3 - 61




Fig. 12

USL Tech Memo No. 953-12-61

U. S. Navy Underwater Sound Laboratory
NP24 - 19868 - 3 - 61

Official Photograph




Fig. 13

USL Tech Memo No. 953-12-61

**U. S. Navy Underwater Sound Laboratory
NP24 - 19869 - 3 - 61**

Official Photograph



Fig. 14

USL Tech Memo No. 953-12-61

U. S. Navy Underwater Sound Laboratory
NP24 - 19870 - 3 - 61

Official Photograph




Fig. 15

USL Tech Memo No. 953-12-61

**U. S. Navy Underwater Sound Laboratory
NP24 - 19871 - 3 - 61**

Official Photograph




Fig. 16

USL Tech Memo No. 953-12-61

U. S. Navy Underwater Sound Laboratory
NP24 - 19872 - 3 - 61

Official Photograph




Fig. 17

USL Tech Memo No. 953-12-61

U. S. Navy Underwater Sound Laboratory
NP24 - 19873 - 3 - 61

Official Photograph

Not Artemis Trident file

Send to my office

U. S. NAVY UNDERWATER SOUND LABORATORY
FORT TRUMBULL, NEW LONDON CONNECTICUT

ARTEMIS ROUTING

NAME	INT'S.
Dr. Froesch	<i>[initials]</i>
Mr. Johnson	
Mr. Sonnemann	<i>Has copy</i>
Mr. Hohn	
Project 130-00-00	
Serial 953-28-61	
Mr. Stiner	
28 MAR 1961	<i>Has copy</i>
Mr. Gregory	
Mr. Mongelli	<i>[initials]</i>
J. Costone	

From: Commanding Officer and Director
U. S. Navy Underwater Sound Laboratory
Fort Trumbull, New London Connecticut

To: Department of the Navy
Chief, Bureau of Ships (Code 370)
Washington D. C.

Subj: USL Technical Memorandum, forwarding of

Encl: (1) Subject Technical Memorandum Serial 953-12-61, dtd Feb 10, 1961
Unclassified Copy #42

1. Subject USL Technical Memorandum is forwarded as enclosure (1) to this letter, for your information and retention.
2. This Technical Memorandum was written by Paul T. Misisco of this Laboratory, and is unclassified.

F. H. Hunt
By direction

- Copy to:
- Code 689A4, BuShips (Mr. Kinellian), Copy #49
 - Martin Company (Mr. Bonner) Copy #41
 - NEL (D. Wilson) Copy #43
 - NRL (Dr. Saxton) Copy #44
 - Hudson Laboratory (Dr. Froesch) Copy #45
 - Tudor Hill Lab., Bermuda (F. Weigle) Copy #46
 - ONR rep. (CDR. Tyler) Copy #47
 - ONR (Mr. A. O'Neal) Copy #48

