

AD-A072 981

CENTER FOR NAVAL ANALYSES ALEXANDRIA VA NAVAL WARFARE--ETC F/G 15/7
A MODEL FOR ANALYZING A STRAIGHT-RUNNING TORPEDO ATTACK ON A NO--ETC(U)
MAR 79 J M COOK, T C WINANT N00014-76-C-0001

UNCLASSIFIED


CRC-374

NL

| OF |

ADA
072981





ADA072981

CRC 374 / March 1979

LEVEL

(12) B.S.

A MODEL FOR ANALYZING A STRAIGHT-RUNNING TORPEDO ATTACK ON A NONEVADING SURFACE SHIP

By Cdr. John M. Cook, SC, USN;
LCdr. Thomas C. Winant, USN

Approved for public release; distribution unlimited

DDC
REF ID: A72981
AUG 29 1979
NATIONAL ARCHIVES

DDC FILE COPY



Naval Warfare Analysis Group

CENTER FOR NAVAL ANALYSES

2000 North Beauregard Street, Alexandria, Virginia 22311

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 14 CRC-374	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) 6 A Model for Analyzing a Straight-Running Torpedo Attack on a Nonevading Surface Ship		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) 15 Cdr. John M./Cook/SC, USN; LCdr. Thomas C./Winant/USN		6. PERFORMING ORG. REPORT NUMBER
8. PERFORMING ORGANIZATION NAME AND ADDRESS Center for Naval Analyses 2000 N. Beauregard Street Alexandria, Virginia 22311		9. CONTRACT OR GRANT NUMBER(s) 15 N00014-76-C-0001
10. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Department of the Navy Arlington, Virginia 22217		11. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 12 31P
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of the Chief of Naval Operations (Op96) Department of the Navy Washington, D.C. 20350		13. REPORT DATE 11 Mar 1979
14. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		15. NUMBER OF PAGES 23
16. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		17. SECURITY CLASS. (of this report) Unclassified
18. SUPPLEMENTARY NOTES This Research Contribution does not necessarily represent the opinion of the Department of the Navy.		18a. DECLASSIFICATION/DOWNGRADING SCHEDULE
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) computer programs, computerized simulation, submarines, torpedo attack, torpedo models, torpedoes		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This Research Contribution presents a methodology and a set of computer programs for analyzing an attack on a nonevading surface ship by submarine(s) firing straight-running torpedoes. The model is compatible with ship vulnerability curves and may be used to compute the probability the target sustains a particular level of damage.		

252 950

1401 Wilson Boulevard . Arlington, Virginia 22209 703/524-9400

An Equal Opportunity Employer

**Center
for
Naval
Analyses**

*an affiliate of the
University of Rochester*

10 May 1979

MEMORANDUM FOR DISTRIBUTION LIST

Subj: Center for Naval Analyses Research Contribution 374

Encl: (1) CRC 374, "A Model for Analyzing a Straight-Running Torpedo Attack on a Nonevading Surface Ship," by Cdr. John M. Cook, USN; and LCdr Thomas C. Winant, USN, March 1979

1. Enclosure (1) is forwarded as a matter of possible interest. The authors of enclosure (1) are two of a select number of naval officers and enlisted men with advanced degrees who, through a unique contract provision, are assigned to CNA for a normal tour of shore duty to participate in the Navy Study Program.

2. This Research Contribution presents a methodology and a set of computer programs for analyzing an attack on a nonevading surface ship by submarine(s) firing straight-running torpedoes. The model is compatible with ship vulnerability curves and may be used to compute the probability the target sustains a particular level of damage.

3. Research Contributions are distributed for their potential value in other studies and analyses. They do not necessarily represent the opinion of the Department of the Navy.

DAVID A. PERIN

DAVID A. PERIN
Director
Naval Warfare Analysis Group

Distribution List
Reverse page

Accession For	
NTIS GRA&I	☒
DDC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or special

Subj: Center for Naval Analyses Research Contribution 374

DISTRIBUTION LIST

Department of the Navy

21A1	CINCLANTFLT	28K2	COMSUBDEVGRU ONE
21A2	CINCPACFLT		DET ALAMEDA
21A3	CINCUSNAVEUR	28K2	COMSUBRON FIFTEEN REP
22A1	COMSECONDFLT		PEARL HARBOR
22A2	COMTHIRDFLT	28K2	COMSUBDEVGRU ONE
22A2	COMSEVENTHFLT		DET MARE ISLAND
22A3	COMSIXTHFLT	41A	COMSC
23B3	COMAREASWFORSIXTHFLT	51A	SACEUR
24D1	COMNAVSURFLANT	51A	SACLANT
24D2	COMNAVSURFPAC	A1	ASST SECNAV (RE&S)
24G1	COMSUBLANT	A2A	OPA
24G2	COMSUBPAC	A2A	CNR
24H1	COMTRALANT	A4A	CHNAVMAT
24H2	COMTRAPAC	B5	COMDT COGARD
26F1	COMOPTEVFOR	C4F9	Annapolis Lab, DTNSRDC
26F2	DEPCOMOPTEVFORPAC	C4F9	Carderock Lab, DTNSRDC
28A1	COMCARGRU 2	C4F9	New London Lab, NUSC
28A1	COMCARGRU 4	C4F9	AUTEC WPalm Det, NUSC
28A1	COMCARGRU 6	C4F9	AUTEC Andros Ranges Det, NUSC
28A1	COMCARGRU 8	C4F9	NAWSWCLAB, White Oak
28A2	COMCARGRU 1	C4F9	Newport Lab, NUSC
28A2	COMCARGRU 3	C4J	NAV TACSUPPACT
28A2	COMCARGRU 5	C4K	PM-4 (ASW Sys Proj)
28A2	COMCARGRU 7	E3A	NRL
28B1	COMCRUDESGRU 2	FF38	USNA Nimitz Library
28B1	COMCRUDESGRU 8	FF44	NAVWARCOL
28B1	COMCRUDESGRU 12	FKA1B	COMNAVELEXSYSCOMHQ
28B2	COMCRUDESGRU 1	FKA1G	COMNAVSEASYSYSCOMHQ
28B2	COMCRUDESGRU 3	FKA6A2	NAVWPNSCEN
28D2	COMCRUDESGRU 5	FKA6A3A	DTNSRDC
28K1	COMSUBGRU 2	FKA6A9	NAVSWC
28K1	COMSUBGRU 6	FKA6A12	NAVOCEANSYSCEN
28K1	COMSUBGRU 8	FKA6A15	NUSC NPT
28K1	COMSUBRON 4	FKP1G	NAVSHIPWPNSYSENGSTA
28K1	COMSUBRON 6	FKP13	NAVSEC
28K1	COMSUBRON 10	FL3	DODCI
28K1	COMSUBRON 14	FS1	NAVINTCOMHQ
28K1	COMSUBRON 16	FS3	NISC
28K1	COMSUBRON 18	FS5	NFOIO
28K1	COMSUBDEVRON 12	FT43	SWOSCOLCOM
28K2	COMSUBGRU 5	FT46	FLEASWTRACENLANT
28K2	COMSUBGRU 7	FT46	FLEASWTRACENPAC
28K2	COMSUBRON 1	FT54	NAV SUBSCOL
28K2	COMSUBRON 3	FT73	NAVPGSCOL
28K2	COMSUBRON 7		

Subj: Center for Naval Analyses Research Contribution 374

DISTRIBUTION LIST

Department of the Navy

OpNav:	Op-09BH	Op-098
	Op-96	Op-02
	Op-094	Op-22
	Op-095	Op-03
	Op-951	Op-32
	Op-953	Op-35
	Op-957	

Other

Under Secretary of Defense, Research and Engineering
Ass't Secretary of Defense, Program Analysis & Evaluation (2 copies)
Defense Advanced Research Projects Agency
Defense Documentation Center
Central Intelligence Agency
Analytic Services, Inc.
Applied Physics Laboratory/University of Washington
Applied Physics Laboratory/Johns Hopkins University
Applied Research Laboratory
Institute for Defense Analyses
Lincoln Laboratory
The Mitre Corporation
The Rand Corporation
Stanford Research Institute
TRW Defense and Space Systems Group
National Academy of Sciences

TABLE OF CONTENTS

	Page
Introduction	1
Modeling a torpedo attack	1
The torpedo problem	1
The model	3
Computer program	12
References	15
Appendix A - APL computer programs.....	A-1 - A-3
Appendix B - Example of use of the interactive program ATTACK.....	B-1
Appendix C - Examples of APL program use	C-1 - C-3

INTRODUCTION

When analyzing engagements between submarines and surface ships, it is often necessary to estimate the effectiveness of the submarine's torpedo attack. Although sophisticated homing torpedoes are being used by many of the world's navies, there continue to be large inventories of straight-running torpedoes. This research contribution presents a methodology and a set of computer programs for analyzing an attack on a nonevading surface ship by submarine(s) firing straight-running torpedoes. It explicitly assumes a triangular horizontal cross section for target ship geometry. We believe this approximation is more applicable to combatants than previously assumed geometries and provides reasonably accurate results for bow and stern shots as well as beam shots. The programs provided make it possible to analyze the effects of several simultaneous, independent submarine attacks. The user must provide some of the torpedo and target ship characteristics and submarine firing doctrine. These are:

- Torpedo
 - speed (knots)
 - maximum run distance (yards)
 - reliability
- Target
 - length at waterline (feet)
 - maximum beam (feet)
 - speed (knots)
- Firing doctrine
 - number of torpedoes in the salvo
 - salvo spread (expressed as a multiple of ship length).

The submarine's position relative to the target is a control variable. The position is expressed as a range and bearing measured clockwise relative to the target's heading.

If a vulnerability curve is available, it is possible to compute the probability that the target sustains a particular level of damage. The David Taylor Ship Research and Development Center, Carderock, is one source that provides vulnerability curves for a ship being put out of action, sunk, or immobilized.

MODELING A TORPEDO ATTACK

The Torpedo Problem

The classical torpedo problem is in three parts:

- (1) Given that a salvo of n torpedoes is fired at a ship, calculate the probability that $0, 1, 2, \dots, n$ torpedo tracks intersect the target if all torpedoes function properly.
- (2) Given the results in (1), calculate the probability that $0, 1, 2, \dots, n$ torpedoes reach the target and explode.
- (3) Given that $0, 1, 2, \dots, n$ torpedoes hit the target and explode, calculate the probability that the target is out of action, severely mission degraded, or sunk.

To solve the first part, consider the typical fire control triangle shown in figure 1. It is easily seen from this figure that torpedo lead angle, λ , is

$$\lambda = \arcsin \left[\frac{u}{v} \sin \beta \right] . \quad (1)$$




FIG. 1: TYPICAL FIRE CONTROL TRIANGLE

Although λ does not depend directly on range, errors in measuring range (to estimate u and β) result in lead angle errors. Lead angle error is derived as:

$$E_{\lambda}^2 = \frac{\left(\frac{E_u}{u}\right)^2 \sin^2 \beta + E_{\beta}^2 \cos^2 \beta}{\left(\frac{v}{u}\right)^2 - \sin^2 \beta} + E_i^2 \quad (2)$$

where:

E_{λ} = standard deviation of the lead angle error,

E_u = standard deviation of the errors in estimating u ,

E_{β} = standard deviation of the errors in estimating β ,

E_i = standard deviation of incidental errors.

Values for these standard deviations have been estimated in reference 1 from short-range (less than 4,000 yards) attacks on Japanese ships during World War II as follows:

$$\frac{E_u}{u} = 0.15,$$

$$E_{\beta} = 10 \text{ degrees } (0.1745 \text{ radians}), \text{ and}$$

$$E_i = 0.05, 0.03, \text{ and } 0.015 \text{ radians for } 1,000, 2,000, \text{ and } 3,000\text{-yard ranges to the target at the time of firing.}$$

Other values of E_i , where needed, are taken from the continuous function:

$$E_i = \exp \{ -0.0006 \text{ RA} - 2.4 \} \quad (3)$$

where RA = firing range in yards.

These parameters are used in the computer program presented later. Data from more recent experience with straight-running torpedoes can be easily inserted into the program, if it is available.

The Model

E_{λ} is used to estimate torpedo hit probabilities, assuming that the torpedo track has a Gaussian (normal) distribution about its intended course with mean zero and standard deviation E_{λ} . The probability of a hit on a ship by a single torpedo aimed at the center of the target is the integral from $-L_{\text{eff}}/2E_{\lambda} \text{ RT}$ to $+L_{\text{eff}}/2E_{\lambda} \text{ RT}$ of the standard normal distribution. L_{eff} is the effective length of the target measured perpendicular to the torpedo track, and RT is the length of the torpedo track.

For a salvo of torpedoes, the limits of integration for 0, 1, 2, or more hits are a function of $L_{\text{eff}}/E_{\lambda} RT$, the spread of the salvo, and the number of torpedoes in the salvo. When a salvo of more than one torpedo is fired at a target, it will be assumed that the center of the salvo is fired at the center of the ship, the torpedoes are equally spaced, and the individual torpedoes within the salvo run in parallel with no error between torpedoes. The only error, E_{λ} , is the placement of the center of the salvo on the target.

A formula for E_{λ} was presented in equation 2. From figure 1, it is apparent that $RT = vt$. We next need to determine L_{eff} .

Target Ship Geometry

To obtain an exact formula for L_{eff} requires a description of the horizontal cross section of the target ship at torpedo running depth. This is impractical. Prior models generally use approximations based only on length, with the beam assumed to be zero. This produces severe errors for bow and stern shots. Often implicitly rather than explicitly, some geometric shape is assumed for the waterline cross section. In many cases, the shape is a rectangle of length L and width B , clearly applicable to barges and to a lesser extent merchant vessels and auxiliaries, but not to combatants. Modern combatant hulls tend to have fine lines at the bow and nearly uniform width aft of the maximum beam.

We considered several geometric shapes. For example, the combination of a rectangle plus an isosceles triangle provides an excellent approximation, but a combination of geometric shapes complicates the mathematical formulation considerably. In general, compound shapes result in complex mathematics. A triangle alone, however, provides results that are nearly as good with much simpler mathematics. Therefore, we used an approximation based on a triangular shape, with the small angle pointed forward and the base as wide as the ship's beam aft (see figure 2). This explicitly assumed triangular ship geometry is the basis for the computation of L_{eff} in this research contribution and the computer program.

A triangular configuration provides a reasonable approximation of the shape of most modern combatants in the critical locations near the bow and stern. The small errors that result from using this configuration take effect principally at small non-zero torpedo angles and to a lesser degree for near-180 degree stern shots. Typical beam-to-length ratios result in an angle at the bow of 3-1/2 to 4 degrees relative to the ship's centerline. A modern combatant has an angle of approximately 10 to 12 degrees. With a track angle between these values, the model understates hits at the bow. Except at track angles of exactly 0, 90, and 180 degrees, the model overstates hits at the stern. These




FIG. 2: ASSUMED SHIP GEOMETRY

errors partially compensate for one another. The model is correctly biased to the extent that torpedoes traveling at a high relative velocity at angles of 3 to 12 degrees relative to ship's track would be subject to hydrodynamic forces at the bow and/or not detonate because the angle of incidence relative to hull plating is very small.

The mathematical approximation of L_{eff} for a triangular shape, including a first-order adjustment for relative motion, is:

$$L_{eff} = \left[\max \left\{ \begin{array}{l} L \times |\sin \tau| \\ \frac{B}{2} \times \left| \frac{u}{v} + \cos \tau \right| \end{array} \right\} + \frac{B}{2} \times \left| \frac{u}{v} + \cos \tau \right| \right] \div \left(1 + \frac{u}{v} \cos \tau \right) \quad (4)$$

This approximation is used in the APL computer program described later.

Torpedo Salvos

To develop the limits of integration for multiple hits on a target, the effective length of the target is converted to an angular measure (the angle subtended from the aim point when the torpedo is at the end of its intended run, L_{eff}/RT) and defined as a ratio to the standard deviation of the lead angle error: $TL = L_{\text{eff}}/E_{\lambda} RT$. The coverage factor, CF , is expressed as a multiple of TL .

It will be necessary to integrate the standard normal distribution between some limits a_i and b_i , to compute the probability of i tracks intersecting the target. From this, the probability of h hits can be calculated using torpedo reliability.

The limits of integration, a_i and b_i , can be represented algebraically in terms of TL , CF , and n (number of torpedoes in the salvo). For convenience we will also define the spacing between torpedoes as $SP = (CF \times TL) / (n-1)$.

Under the assumptions of this model, a target is missed (no track intersections), when the center of the salvo is displaced from the aimpoint by at least $TL/2 + 1/2$ the salvo width; that is, $(CF + 1) \times TL/2 = a_0$, $\infty = b_0$ (see figure 3).




FIG. 3: LIMITS OF INTEGRATION: 5 TORPEDOES, NO HITS

We will get one track intersection if the center of the salvo is displaced from target center less than $a_0 = b_1$ and more than $a_0 - SP = a_1$ (see figure 4). Similarly, we will get two track intersections if the center of the salvo is displaced less than $b_2 = a_1$, but more than $a_2 = a_1 - SP = a_0 - 2 \times SP$ (see figure 5). This leads to the general form:

$$a_i = a_0 - i \times SP;$$

$$b_i = a_{i-1} = a_0 - (i - 1) \times SP.$$

Since there are only $n-1$ spaces, $0 < i \leq n-1$. However, these values are not exactly correct because of two limitations:

First: If the coverage factor is greater than 1 (i.e., the salvo spread is wider than the effective length of the ship), then a point will come at which $a_i > 0$ but $i \times SP > TL$.

That is, torpedoes will miss both ahead and behind the target ship (see figure 6). Beyond this point, the number of track intersections alternates between i and $i-1$. This fluctuation can be visualized by thinking of the center of the salvo moving from bow to stern across the target. At some point, a torpedo "falls off" the stern (there are now $i-1$ intersections) and then another "comes on" at the bow (i intersections), and so on. After the salvo center passes the target's mid point, the number of intersections will continue to fluctuate for a while and then diminish until eventually no tracks intersect the target.

The limits of integration are handled in the following manner. When $i \times SP > TL$ for the first time, the limits of integration for i track intersections are:

$$a_i = a_0 - TL \text{ and } b_i = a_{i-1}.$$

After the point when the center of the salvo is at $a_0 - TL$, we get one less track intersection because one torpedo misses astern as the salvo moves aft. As the salvo continues to move aft, the next torpedo "comes on" at the bow when the salvo center is at $a_0 - (i) \times SP$ (recall $i \times SP > TL$). Thus integration between the limits $a_0 - (i) \times SP$ and $a_0 - TL$ contributes to the probability of $(i-1)$ hits.

As the salvo moves aft, we get i hits until the second torpedo "falls off" the stern when the salvo center is at $a_0 - (TL + SP)$. We then get $i-1$ hits until another "comes on" at the bow when salvo center is at $a_0 - (i+1)SP$. Continuing in this pattern, we see that for $i > (TL \div SP)$, we end up with alternate intervals contributing to the probability of i and $i-1$ hits.




FIG. 4: LIMITS OF INTEGRATION: 5 TORPEDOES, 1 HIT







FIG. 5: LIMITS OF INTEGRATION: 5 TORPEDOES, 2 HITS



Note: $3 \times SP > TL$, so $a_3 = a_0 - TL$ not $a_0 - 3SP$



Note: Misses to both left and right of target

FIG. 6: INTEGRATION LIMITS FOR $CF > 1$: 6 TORPEDOES, $CF = 1.8$

Intervals of the form $a_0 - (i+j)SP$ to $a_0 - (TL + (j)SP)$ contribute to the probability of $i-1$ hits.

Intervals of the form $a_0 - (TL + (j)SP)$ to $a_0 - (i-1 + j)SP$ contribute to the probability of i hits.

That is

$$\text{Prob of } i \text{ hits} = \int_{a_0 - (TL + (0)SP)}^{a_0 - (i-1+0)SP} N(0, 1) + \int_{a_0 - (TL + (1)SP)}^{a_0 - (i-1+1)SP} N(0, 1) + \int_{a_0 - (TL + (2)SP)}^{a_0 - (i-1+2)SP} N(0, 1) + \dots$$

and

$$\text{Prob of } i-1 \text{ hits} = \int_{a_0 - (i+0)SP}^{a_0 - TL + (0)SP} N(0, 1) + \int_{a_0 - (i+1)SP}^{a_0 - (TL + (1)SP)} N(0, 1) + \int_{a_0 - (i+2)SP}^{a_0 - (TL + (2)SP)} N(0, 1) + \dots$$

where $N(0, 1)$ is the standard unit normal distribution. These are still not exactly co values. Each series must be stopped after a limited number of terms. This leads to second limitation.

Second: We will eventually multiply the derived probabilities by 2 because the aim point was assumed to be the center of the target and the standard normal distribution is symmetric. This means we must integrate only over intervals to one side or the other of target center (see figure 7).



A check must be made at each step to insure the limits of integration are all non-negative.

The smallest integer value of i for which $i \times SP \geq TL$ is an upper limit on the number of intersecting tracks, along with n (the number of torpedoes in the salvo). The same constraint can also be expressed as follows: the maximum number of tracks is the smallest integer i , such that $i \geq n/CF$ and $i \leq n$.

Reliable Hits on a Target

Once the probabilities of $0, 1, 2, \dots, n$ intersecting tracks are computed as previously described, the next step is to determine the probabilities of $0, 1, 2, \dots, n$ reliable torpedo hits. To make a hit, a torpedo must travel an intersecting track and perform reliably. If we use the symbol $P(T=i)$ for the probability that there are i intersecting tracks and θ for the reliability of an individual torpedo, then the probability of h reliable hits $P(H=h)$ where $h \leq i$ can be computed as:

$$P(H=h) = \sum_{i=h}^n P(T=i) \times P(H=h | T=i) \quad (5)$$



Note: $a_3 < 0$ so $a'_3 = 0$

FIG. 7: INTEGRATION LIMITS FOR $i \times SP > \frac{1}{2}(CF+1)TL$

Assuming that the reliability of one torpedo is independent from that of another, we can use a binominal distribution for $P(H=h | T=1)$, and then

$$P(H=h) = \sum_{i=h}^n P(T=i) \left\{ \binom{i}{h} (1-\theta)^{i-h} \theta^h \right\} . \quad (6)$$

Target Vulnerability

The probability that a ship receives a particular level of damage is the probability of a particular level of damage given h reliable hits times the probability of h reliable hits summed over the range of possible values for h . If we symbolize the vulnerability vector providing the probabilities of damage given h hits as $V(h)$, $h=1, 2, \dots, n$, we can compute the probability of damage (PD) to a ship by the formula

$$PD = \sum_{h=1}^n P(H=h) \times V(h) . \quad (7)$$

The damage probability can also be interpreted as the expected fraction of attacked ships in a force that are damaged.

Simultaneous Attacks

To properly account for simultaneous, independent attacks by more than one submarine, the probabilities of reliable hits for each submarine must be combined into a probability of reliable hits by all submarines, before performing the step indicated in equation 7 above. For example, when there are two submarines, we first compute $P_1(H=h)$ and $P_2(H=h)$ for each submarine. Then

$$P(H=h) = \sum_{i=0}^h P_1(H=i) \times P_2(H=h-i) . \quad (8)$$

Although equation 8 assumes attacks by only two submarines, it can be extended to any arbitrary number of simultaneous, independent attacks.

COMPUTER PROGRAM

The APL computer programs and subroutines in appendix A provide a variety of techniques for computing intersecting tracks, hits, and/or damage probabilities for one or more attacking submarines.

The first program listed, and the simplest to use, is Program ATTACK. This program is limited to computing results for attacks by one submarine; it requires only limited knowledge of the program and APL. ATTACK is a conversational program that

computes and displays intersecting track probabilities, hit probabilities, and/or damage probability. It also displays, on request, the results of such intermediate calculations as track angle, torpedo run time and distance, effective ship length, and the value of TL. Intersecting tracks and hits are displayed as probability vectors (the probability of 0, 1, 2, ..., n tracks or hits). Appendix B shows a sample ATTACK run in which user inputs are underlined.

Appendix A also contains 7 additional programs that do the same computations as program ATTACK, but with more flexibility. These programs permit the analysis of more complex tactical situations (i.e., multiple submarines). These programs are more complex than ATTACK, however, and familiarity with APL is essential to use them effectively. The basic use of each of the programs is shown in table 1. Several examples are shown in appendix C.

TABLE 1
TORPEDO ATTACK PROGRAMS

PROGRAM	USE	INPUT REQUIRED	OUTPUT
ATTACK	Computes intersecting tracks, hits and damage probability for one submarine	Response to conversational inquiry	Labeled displays as requested
TRACKS	Computes probabilities of 0,1,2,...,n intersecting tracks	A vector of target, torpedo and tactical parameters. See page C-1.	A vector of intermediate calculations, and intersecting track probabilities. See page C-1.
HITS	Computes probabilities of 0,1,2,...,n hits	Track intersection probabilities (part of the output of TRACKS) plus torpedo reliability	A vector of hit probabilities. See page C-2.
ELOSS	Computes probability of damage	Output of HITS (or SUBS or COMBINE) plus a vulnerability vector (probability) of damage given 0,1,2,... hits ^a . See page C-2.	The probability of damage (expected fraction of target ships damaged)
SUBS	Computes a track or hit probability vector for two or more submarines firing from the same or from symmetric positions, or for two or more salvos from the same (relative) position	The output of HITS or the probability vector output of TRACKS and number of submarines (or salvos).	The probability vector for 0,1,2,...,z hits or tracks where z=number of submarines (or salvos) times the size of salvo
COMBINE	Combines two ^b probability vectors from TRACKS or HITS into a single probability vector (to combine hit probabilities for non-identical attacks)	Two probability vectors of length L_1 and L_2	One probability vector of length $L_1 + L_2 - 1$
BINAPPROX	Computes a vector of binomial probabilities (by normal approximation if necessary)	N, P -- the binomial parameters	A probability vector of length N+1
NORM	Computes areas under the standard (unit) normal curve by approximation	One or more values representing distances from the mean measured in standard deviations	A left-hand cumulative normal probability for each input

^a If the vulnerability vector does not contain probabilities for all possible numbers of hits, it is extended by projecting a straight line through the last two values given until reaching an upper bound of 1.0.

^b COMBINE can be chained to handle a combination of more than two vectors.

REFERENCES

1. Center for Naval Analyses, Submarine Operations Research Group, Research Report NR 2, "Effect of Firing Position on the Success of Torpedo Attacks," Unclassified, Mar 1944

APPENDIX A

APL COMPUTER PROGRAMS

```

▼ ATTACK;X;SW;HEAD;R;VUL
[1]  'WHAT IS TARGET SHIP LENGTH IN FEET?'
[2]  X+0
[3]  'WHAT IS TARGET SHIP BEAM IN FEET?'
[4]  X+X,0
[5]  'WHAT IS TARGET SHIP SPEED IN KNOTS?'
[6]  X+X,0
[7]  'WHAT IS RANGE TARGET TO SUB IN YARDS?'
[8]  X+X,0
[9]  'WHAT IS ASPECT ANGLE (ANGLE ON THE TARGET BOW) IN DEGREES?'
[10] X+X,0
[11] 'HOW MANY TORPEDOS IN A SALVO?'
[12] X+X,0
[13] 'WHAT IS THE COVERAGE FACTOR? (TORPEDO SPREAD ÷ TARGET SHIP
      LENGTH)'
[14] X+X,0
[15] 'WHAT IS TORPEDO SPEED IN KNOTS?'
[16] X+X,0
[17] 'WHAT IS TORPEDO MAXIMUM RANGE IN YARDS?'
[18] X+X,0
[19] 'YOUR ANSWERS IN ORDER WERE:',OR;X;OR,'ARE THEY OK?'
[20] +1;1^/'NO '=5+0
[21] 'DO YOU WANT TRACK PROBABILITIES DISPLAYED?'
[22] SW+^/'YES '=5+0
[23] 'DO YOU WANT TRACK ANGLE, RUN DISTANCE, RUN TIME, EFFECTIVE
      LENGTH, AND TL DISPLAYED?'
[24] SW+SW,^/'YES '=5+0
[25] 'DO YOU WANT HITS DISPLAYED?'
[26] SW+SW,^/'YES '=5+0
[27] 'IF YOU HAVE A VULNERABILITY VECTOR I'LL COMPUTE EXPECTED
      LOSSES.'
[28] 'INPUT THE VECTOR STARTING WITH PROB OF LOSS GIVEN ONE HIT,PROB
      OF LOSS GIVEN TWO HITS, ...ETC, IF AVAILABLE. OTHERWISE HIT THE
      RETURN.'
[29] +0;10=+/SW+SW,1≠rVUL+,z'0 ',100+0
[30] +L1;10=+/SW[3,4]
[31] 'I'LL NEED TORPEDO RELIABILITY:'
[32] R+0
[33] L1;TEMP+TRACKS X
[34] +NOSHOT;11=^/(180,(2*10*7),0,0,1)=6+TEMP
[35] +L2;1SW[1]=0
[36] 'TRACK PROBABILITIES',OR,((5 0+0),10 0+1XC[6]),OR,10 5+5+TEMP
[37] L2;+L3;1SW[2]=0
[38] 'TRACK ANGLE    RUN DISTANCE    RUN TIME    EFFECTIVE SHIP
      LENGTH',OR,' (DEGREES)    (YARDS)    (SECONDS)    (FEET)
      TL(STD.DEV.)'
[39] 7 1 15 0 15 1 13 0 15 4+5+TEMP
[40] L3;+L4;1SW[3]=0
[41] 'HIT PROBABILITIES',OR,((5 0+0),10 0+1XC[6]),OR,10 5+R HITS 5+
      TEMP
[42] L4;+0;1SW[4]=0
[43] 'EXPECTED LOSS PROBABILITY: 'rVUL ELOSS R HITS 5+TEMP
[44] +0
[45] NOSHOT:'THERE IS NO CHANCE OF A HIT GIVEN THIS SET OF DATA.'

```

▽ Z+TRACKS X:SL:SB:SS:RA:AN:NT:CF:TS:MR:LA:TL:RT:K:SP:M:T:EI:IEL
 [1] →0x19*P X
 [2] SL+X[1]
 [3] →NOSHOTx10=SL+SB+X[2]
 [4] SS+X[3]
 [5] →NOSHOTx10=RA+X[4]
 [6] AN+0X[5]+180
 [7] →NOSHOTx10=NT+X[6]
 [8] CF+X[7]
 [9] →NOSHOTx10=TS+X[8]
 [10] →NOSHOTx10=MR+X[9]
 [11] →NOSHOTx11<(SS+TS)x10AN
 [12] LA+~10(SS+TS)x10AN
 [13] →NOSHOTx10≥T+1+(SS+TS)x20AN+LA
 [14] Z+180x(AN+LA)÷01
 [15] →LOx1SS=0xE+*~2.4-0.0006xRA
 [16] E+((E*2)+((0.0225x(10AN)*2)+0.03045025x(20AN)*2)+((TS+SS)*2)-(10AN)*2)*0.5
 [17] LO:→L1x10=1|AN÷01+0xRT+RA+T
 [18] RT+RAX(10AN)÷10(01)-AN+LA
 [19] L1:→NOSHOTx1MR<RT
 [20] EL+(T+(SLx110AN+LA)|T+SBx0.5x1(SS+TS)+20AN+LA)+1+(SS+TS)x20AN+LA
 [21] Z+Z,RT,(RT+TSx0.5626032861),EL,TL+EL÷E×3×RT
 [22] →ONEx1(NT=1)∨CF=0
 [23] M+(1+CF)xTL÷2
 [24] SP+(CFxTL)÷NT-1
 [25] →CFLx1CF≤1
 [26] K+LTL÷SP
 [27] X+NORM M,M-SPx1K
 [28] X+(1,X)-X,NORM M-TL
 [29] I+0
 [30] AGAIN:X[~1+P X]+X[~1+P X]-(NORM T+0FM-SPxK+I+I+1)-NORM M-TL+I×SP
 [31] →ENDx1T=0
 [32] X[P X]+X[P X]+(NORM T)-NORM 0FM-TL+I×SP
 [33] →ENDx10≥M-TL+I×SP
 [34] →AGAIN
 [35] CFL:K+NT-1+CF=1
 [36] X+NORM M,M-SPx1K
 [37] X+(1,X)-X,0.5
 [38] END:Z+Z,(NT+1)↑2×X
 [39] →0
 [40] ONE:Z+Z,(1-SP),((NT-1)÷0),SP+2x(NORM TL÷2)-0.5
 [41] →0
 [42] NOSHOT:Z+(6+NT)↑180,(2÷10×7),0,0,1

▼ Z+P HITS V;N;I
 [1] N+P
 [2] Z+N+VCI+1
 [3] AGAIN:Z+Z+N+VCI+1)xBINAPPROX I,P
 [4] →AGAINx1N>I+I+1

▼ R+VUL ELOSS PROB
 [1] →(L1,L2,L3)[2+x(pVUL)-pPROB]
 [2] L1:→L2x11=VUL(pVUL)
 [3] →L3x10=pVUL+(pPROB)†1LVUL,VUL(pVUL)+(VUL(pVUL)-VUL(-1+pVUL))x1p
 PROB
 [4] L2:VUL+(pPROB)†VUL,(pPROB)p1
 [5] L3:R+VULxPROB

▼ R+N SUBS P
 [1] →0x1(N+LN)<1,0pR+1 0
 [2] →0x1N=1,0pR+P
 [3] R+P COMBINE R
 [4] →3x11<N+N-1

▼ R+P COMBINE Q
 [1] R+V/[1](0,-1+P)φ(P,xQ),(X0,-1)+pP)p0

▼ V+BINAPPROX Y;X;N;P;M;VAR
 [1] →0x1(P≥1)∨P≤0,0pV+(N+1)†(1≤P+Y[2])†1,(Np0),1,X+0,1N+LY[1]+0.5
 [2] →3+(N>200)∨(N>50)^N>25x(P+1-P)†(1-P)+P
 [3] →0xV+(P×X)x(X;N)x(1-P)xN-X
 [4] V+((VARx0.2)*0.5)x*-((X-M)*2)+2xVAR+(1-P)xM+N×P

▼ P+NORM X;N
 [1] N+1,P+0pX+,X
 [2] P+P,1-(((2x0.1)*0.5)x*-0.5xX[N]*2)x+/0.31938153 -0.356563782
 1.781477937 -1.821255978 1.330274429x(+1+0.2316419xX[N])*15
 [3] →2x1(pX)≥N+N+1

APPENDIX B

EXAMPLE OF USE OF THE INTERACTIVE PROGRAM ATTACK

Note: Underlines indicate user entries.

ATTACK

WHAT IS TARGET SHIP LENGTH IN FEET?

Q:

1000

WHAT IS TARGET SHIP BEAM IN FEET?

Q:

120

WHAT IS TARGET SHIP SPEED IN KNOTS?

Q:

20

WHAT IS RANGE TARGET TO SUB IN YARDS?

Q:

3500

WHAT IS ASPECT ANGLE (ANGLE ON THE TARGET BOW) IN DEGREES?

Q:

135

HOW MANY TORPEDOS IN A SALVO?

Q:

6

WHAT IS THE COVERAGE FACTOR? (TORPEDO SPREAD ÷ TARGET SHIP LENGTH)

Q:

2.5

WHAT IS TORPEDO SPEED IN KNOTS?

Q:

50

WHAT IS TORPEDO MAXIMUM RANGE IN YARDS?

Q:

10000

YOUR ANSWERS IN ORDER WERE:

1000 120 20 3500 135 6 2.5 50 10000

ARE THEY OK?

YES

DO YOU WANT TRACK PROBABILITIES DISPLAYED?

YES

DO YOU WANT TRACK ANGLE, RUN DISTANCE, RUN TIME, EFFECTIVE LENGTH, AND TL DISPLAYED?

YES

DO YOU WANT HITS DISPLAYED?

YES

IF YOU HAVE A VULNERABILITY VECTOR I'LL COMPUTE EXPECTED LOSSES.

INPUT THE VECTOR STARTING WITH PROB OF LOSS GIVEN ONE HIT, PROB OF LOSS GIVEN TWO HITS, ...ETC. IF AVAILABLE. OTHERWISE HIT THE RETURN.

.5 .75 1

I'LL NEED TORPEDO RELIABILITY:

Q:

.85

TRACK PROBABILITIES

0	1	2	3	4	5	6
0.20017	0.16000	0.63983	0.00000	0.00000	0.00000	0.00000
TRACK ANGLE	RUN DISTANCE	RUN TIME	EFFECTIVE	SHIP LENGTH		
(DEGREES)	(YARDS)	(SECONDS)	(FEET)	TL(STD.DEV.)		
151.4	5175	184.0	781	0.7320		

HIT PROBABILITIES


0	1	2	3	4	5	6
0.23857	0.29915	0.46228	0.00000	0.00000	0.00000	0.00000
EXPECTED LOSS PROBABILITY: 0.4962868154						

APPENDIX C

EXAMPLES OF APL PROGRAM USE


APPENDIX C EXAMPLES OF APL PROGRAM USE

Example 1: Torpedo tracks (program TRACKS)




APPENDIX C EXAMPLES OF APL PROGRAM USE

Example 2: Torpedo hits and tracks (programs HITS and TRACKS)



Example 3: Expected losses from torpedoes (programs ELOSS, HITS, and TRACKS)



APPENDIX C EXAMPLES OF APL PROGRAM USE

Example 4: Torpedo hits by multiple submarines (programs SUBS, HITS, and TRACKS)

2 SUBS .85 HITS 5+ TRACKS 1000 120 20 3500 135 6 2.5 50 10000

0.05691381074 0.1427361672 0.3100617983 0.2745858156 0.213702406
0 0 0 0 0 0 0 0

Probability of 0, 1, 2, . . . , 2xn hits with two submarines attacking from the same relative position.

Example 5: Expected losses from a multiple submarine attack; (programs ELOSS, SUBS, HITS, and TRACKS)

0 0.5 0.75 1 ELOSS 3 SUBS 0.85 HITS 5+TRACKS 1000 120 20 3500 135
6 2.5 50 10000

0.9251381545

Probability of damage with three submarines attacking from the same relative position.

Example 6: Expected losses from a multiple submarine attack; submarines in different relative positions (programs ELOSS, SUBS, HITS, TRACKS, and COMBINE)

0 0.5 0.75 1 ELOSS (3 SUBS 0.85 HITS 5+TRACKS 1000 120 20 3500 135
6 2.5 50 10000) COMBINE .9 HITS 5+ TRACKS 1000 120 20 4000 60 5 1.5 6
0 8000

0.9900551757

Probability of damage with three submarines attacking from the same relative position and one submarine attacking from a different position with a different torpedo type.