

AD-A074 454

BOEING AEROSPACE CO SEATTLE WA BOEING MILITARY AIRPL--ETC F/G 5/1
AN EXTENSION OF ENGINE WEIGHT ESTIMATION TECHNIQUES TO COMPUTE --ETC(U)
AUG 79 E ONAT, F F TOLLE N62269-78-C-0286


UNCLASSIFIED

NADC-78103-60

NL

| OF |
ADA
074454





MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS-1963-A

AU74454

Report No. NADC -78103-60

12
SC

LEVEL II



AN EXTENSION OF ENGINE WEIGHT ESTIMATION TECHNIQUES TO COMPUTE ENGINE PRODUCTION COST

E. Onat and F. F. Tolle

Boeing Military Airplane Development
Boeing Aerospace Company
Seattle, Washington 98124

31 August 1979

FINAL REPORT
CONTRACT NO. N62269-78-C-0286

UNLIMITED DISTRIBUTION

DDC
OCT 1 1979
A

DDC FILE COPY

DISTRIBUTION STATEMENT A
Approved for public release
Distribution Unlimited

Prepared for
NAVAL AIR SYSTEMS COMMAND
Department of the Navy
Washington, D.C. 20360

00-00-00-048

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

19 REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER 18 NADC-78103-60	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) 6 AN EXTENSION OF ENGINE WEIGHT ESTIMATION TECHNIQUES TO COMPUTE ENGINE PRODUCTION COST.		5. TYPE OF REPORT & PERIOD COVERED FINAL REPORT.	
6. PERFORMING ORG. REPORT NUMBER		8. CONTRACT OR GRANT NUMBER(s) 15 N62269-78-C-0286	
7. AUTHOR(s) 10 E. / ONAT F. F. / TOLLE		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NPRC 1939D/XS901	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Boeing Military Airplane Development P.O. Box 3707 Seattle, Washington 98124		12. REPORT DATE 11 31 August 1979	
11. CONTROLLING OFFICE NAME AND ADDRESS NASA Lewis Research Center 21000 Brookpark Road Cleveland, Ohio 44135		13. NUMBER OF PAGES 33 12 38	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Aircraft and Crew Systems Technology Directorate Code 6052 Naval Air Development Center Warminster, Pennsylvania 18974		15. SECURITY CLASS. (of this report) UNCLASSIFIED	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Engine Cost Aircraft Propulsion Engine Weight Computer Code Gas Turbines			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) As a follow-on to previously developed engine weight estimation work, a preliminary design quality engine cost estimating code has been produced. The code relies on engine thermodynamic characteristics and weight as computed by earlier developed codes to select raw material types and quantities required to produce the engine. An existing Navy technique is then used to convert this data into engine cost. The code was used to predict the cost of three existing engines; errors ranged from 1 to 8% of actual costs as reported to NADC.			

JOB

TABLE OF CONTENTS

	<u>PAGE</u>
LIST OF FIGURES	iii
1.0 INTRODUCTION AND SUMMARY	1
1.1 Introduction	1
1.2 Summary	3
2.0 MATERIALS USAGE	5
2.1 Current Technology Material Classification	5
2.1.1 Fans and Compressors	6
2.1.2 Combustor (Class B)	7
2.1.3 Turbine (Class D)	8
2.1.4 Shafts (Class A or Class C)	8
2.1.5 Ducts and Nozzles (Class Ti or Class B)	9
2.2 Advanced Technology Material Classification	9
2.2.1 Fans and Compressors (Class Ti)	10
2.2.2 Turbines (Class D)	11
2.2.3 Combustors (Class B)	11
2.2.4 Other High Temperature Materials	12
2.3 COST Computer Code	12
2.4 Program Validation	17
3.0 USER'S MANUAL	19
3.1 "Navy Code" Program Structure	19
3.1.1 Input Description and Format	21
3.1.2 Mode Indicators	21
3.1.3 User Technology Inputs	21
3.1.3.1 Fan or Compressor	22
3.1.3.2 Turbine	23
3.1.3.3 Burner	23
3.1.3.4 Nozzle and Thrust Reverser	23
3.1.3.5 Ducts	23

Accession For	
NTIS CR&I	<input checked="" type="checkbox"/>
DDC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<input type="checkbox"/>
By _____	
Distribution/ _____	
Availability Codes	
Dist	Avail and/or special
A	

TABLE OF CONTENTS (CONCLUDED)

	<u>PAGE</u>
3.1.3.6 Air Inverting Valve (AIV), Mixer, Heat Exchanger	24
3.1.4 Navy Cost Subroutine Inputs	24
3.2 NASA/COST Program Structure	25
3.2.1 Input Description and Format	25
3.2.2 Mode Indicators	25
3.2.3 User Technology Inputs	29
3.2.3.1 Fan and Compressor	29
3.2.3.2 Turbine	30
3.2.3.3 Burner	30
3.2.3.4 Nozzle and Thrust Reverser	30
3.2.3.5 Shaft	31
3.2.3.6 Duct	31
3.2.3.7 AIV, MIXER, Heat Exchanger	31
3.2.4 Navy Cost Subroutine Inputs	31
REFERENCES	33

LIST OF FIGURES

	<u>PAGE</u>
1-1 Maurer Factor Correlation with COST	3
2-1 Material Classes for Current Technology Engines	6
2-2 Additional State-of-the-Art Material by Class	12
2-3 Manufacturing Efficiency	13
2-4 Primary Burner Output	15
2-5 Material Classification Output	16
2-6 Program Results in Estimating Maurer Factor	18
3-1 Overall "Navy Code" Program Structure	19
3-2 Diagram of Subroutine Connectivity	20
3-3 NASA/COST Overall Program Structure	26
3-4 Diagram of Subroutine Connectivity	27
3-5 User Input	28

1.0 INTRODUCTION AND SUMMARY

1.1 Introduction

The COST computer code is a preliminary design tool used to estimate the production cost and selling price of military aircraft gas turbine engines. Production cost does not include overhead and profit (which enter into engine selling price) which vary between manufacturers; if data on overhead and profit is available, the user can combine them with the COST product to estimate engine price. Often production cost estimates alone will suffice to determine the cost ranking of competing engine concepts in a preliminary design study.

COST first estimates the weight of each major component in the engine, using the method developed by the WATE-2 computer code (Ref. 1-1). The WATE-2 technique determines the weight of compressors, burners, turbines, ducts, frames, shafts, and nozzles by a preliminary design approach through consideration of thermodynamic and mechanical design variables such as: airflow, pressure ratio, maximum temperature, material density, stage loading, hub tip ratio, and shaft mechanical overspeed of each component. These variables may be determined from the thermodynamic cycle analysis of the engine or may be input by the user.

The estimated weight is transferred to cost estimating routines which are based on correlations developed by Naval Air Development Center and Naval

Air Systems Command. The correlation parameter is based on a system of classifying materials by similarity of applications in engines (Ref. 1-2). In this procedure, materials used in jet engines are placed in one of a total of six relative cost categories having to do with a combination of manufacturing cost and raw materials cost. Carbon steel and aluminum are assigned the lowest classification and used as a reference. High strength high temperature nickel cobalt alloys which are costly and difficult to machine are placed in the highest (fifth) classification. Because of differences in cost and machinability, titanium alloys are assigned a separate (sixth) classification. Two indices are developed for each material class, namely

- o relative material cost
- o relative machining cost.

The product of these two indices is called the "relative weighting factor".

In the cost estimation procedure, the estimated weight of each engine component is first converted to raw material weight. A raw material weight to finished material weight scaling factor, commonly referred to as "Buy/Fly" ratio, has been estimated for each component for state-of-the-art and for advanced production methods. Raw material weight is then multiplied by the relative weighting factor, and the sum of all such component products is formed. The summation for all engine components is called the "Maurer factor" in the honor of its originator, R. J. Maurer. The production cost of the engine is estimated by the linear correlation (Fig. 1-1) between engine manufacturing cost and the Maurer factor (Ref. 1-2).

The method of calculation opens the possibility of computing component costs by proportioning the component and engine Maurer factors and engine cost. However, there is little component cost data available to confirm such calculations, so component costs derived by this process could be substantially in error.




FIGURE 1-1 MAURER FACTOR CORRELATION WITH COST

1.2 Summary

A method has been developed to estimate the production cost of aircraft gas turbine engines. This method consists of a combination of a cost estimating method (Ref. 1-2 and 1-3) developed by Naval Air Development Center and Naval Air Systems Command and WATE-2 (Weight Analysis of Turbine Engines, Ref. 1-1) developed by The Boeing Company. This method is incorporated into a new computer code called COST.

COST determines the finished weight of each major component in the engine, and multiplies it by a factor which varies with production methods to produce an estimate of the raw material weight. Estimated component raw material weight is then multiplied by "relative material cost" and "relative machining cost" factors; these products are next summed over all components to arrive at the "Maurer factor", (Ref. 1-2, 1-3). Finally, the Maurer factor is transferred into a cost estimating routine developed by Naval Air Development Center where the production cost of the engine is calculated.

2.0 MATERIALS USAGE

Reports from Naval Air Development Center (Ref. 1-3), Battelle Columbus Laboratories (Ref. 2-1) and Boeing Propulsion Data Files were the principle sources used to determine materials used in major components of a jet engine. During the course of analysis, it became apparent that two classifications were required: one dealing with present state of the art materials, and the other with materials expected to be available for use in 1985 and subsequent years. The advanced materials list was arrived at by discussions with Navy, NASA, Army, and Air Force Material Development Program Managers and by the use of the NASA-MATE (Materials for Advanced Turbine Engines program) Program Reviews. A review of ASTM materials which find use in turbine engines was conducted. For those materials included in the COST program, the output format can be made to list the material generic name and, where assigned, the ASTM number.

2.1 Current Technology Material Classification

Figure 2-1 presents the material classification for current technology materials and is extracted from References 1-2 and 1-3. A separate advanced materials classification presented later includes materials such as those produced by powder metallurgy which are not widely used in current aircraft engines. Actual material selection for a specific engine depends on design factors such as temperature, cooling, or proprietary considerations which are refinements not possible in a preliminary design tool. Accordingly no specific materials are singled out within a particular material class.

		MAJOR MATERIAL CLASSES					
		CONV	A	B	C	D	Ti
RELATIVE MATERIAL COST		1.0	3-4	4-5	5-7	7-10	7
RELATIVE MACHINING COST		1.0	1.9	3.1	4.0	3.5	1.5
MAURER FACTOR			6,7	14.0	24.0	29.8	10.5
TYPICAL MATERIALS		CARBON STEEL 321SS ALUMINUM	A256 17-4PH GREEK ASCOLOY	HASTELLOY-X HASTELLOY-B INCO-706	INCO-713 INCO-625 L-605	WASPALLOY RENE 41 ASTROLOY	6AL-4V 6AL-6V-25 Ti 17

Figure 2-1 Material Classes for Current Technology Engines

2.1.1 Fans and Compressors

The engine component weight estimator selects either titanium or steel, depending on stage inlet temperature, and adjusts material density accordingly. This capability is necessary to estimate the weight of a high pressure compressor where the high temperatures in the later stages make it necessary to use steel alloys. The default changeover temperature limit from titanium to steel is 700°F (371°C). Some of the compressor materials are presented below.

Class Ti (Titanium Alloys) - These alloys are used in stages where the inlet temperature is below the maximum allowable temperature for titanium.

Ti-6AL-4V

Ti-8AL-1MO-1V

Ti-679

Ti-6-2-4-R

Class A (Superalloys) - These alloys are used in stages where the inlet temperature exceeds the allowable temperature for titanium alloys.

Greek Ascoloy

Incoloy-901

Inconel-718

Waspaloy

Inconel-X-750

2.1.2 Combustor (Class B)

The alloys used for combustors and their liners, and for the transition ducts connecting the combustors to the turbine inlet nozzles are formable, weldable sheet alloys. They are capable of 8,000 to 10,000 hours of operation in an oxidizing environment at average material temperatures of 16500F or more. The alloys must be stable for this long time, high temperature service and must have excellent thermal

fatigue and distortion resistance. Some of the alloys used in combustors are

Hastelloy-X

Hastelloy-B

Inconel-600

AISI-310

AISI-321

AISI-347

2.1.3 Turbine (Class D)

The turbine section of the gas turbine engine is one of the most demanding in terms of material properties because of the combination of temperatures and stresses. These materials are either nickel base alloys or carbide strengthened cobalt base alloys for applications up to 2000°F, and dispersion strengthened materials above 2000°F. Some of these materials are:

Rene-41

Astroloy

Diskoloy

Inconel-718

Udimet-500

2.1.4 Shafts (Class A or Class C)

Shafts transmit the torque from the turbines to the compressor sections of the engine. Therefore they must have high fatigue and high yield strength properties. Depending on operating temperature, torque and length, shafts are made of low alloy steels, CR-MO-V steels and occasionally nickel base alloys. Turbine shafts require a combination of

properties that is difficult to get in a single material. High yield and fatigue strength are needed at the cold end, and high yield and creep strength plus oxidation resistance are needed at the hot end. Materials which afford a reasonable compromise are

17-22A

Inconel 718

Waspaloy

A-286

2.1.5 Ducts and Nozzles (Class Ti or Class B)

Titanium, nickel base, and cobalt base alloys are choices for use in ducts and nozzles depending on temperature. Some of these materials are:

Ti-6AL-4V

Inconel-600

AISI-321

AISI-347

Nimonic-75

2.2 Advanced Technology Material Classification

Research programs are being conducted by both industry and government for the purpose of developing alloys with improved hot strength, better micro-structural stability after long time exposure to high temperature, and improved resistance to corrosive and erosive attack by combustion products. From a cost reduction standpoint, new manufacturing methods to improve material properties and to decrease scrap material loss are of

great importance. Powder metallurgy, as an example, offers some important potential advantages over conventional castings:

- o reduces labor and material cost because powder metallurgy parts are closer to finished size
- o produces shapes with a high degree of reproducibility
- o permits blending of otherwise incompatible materials to produce a chemically homogeneous structure with uniform mechanical properties
- o eliminates some processing steps such as forging
- o allows improved grain size and grain growth control by techniques such as the hot isostatic process (HIP)

Powder technology is relatively new and little information on manufacturing costs and material costs are available. In the absence of definitive data, the COST code uses the same relative material cost and relative machining cost for advanced technology materials as are used for conventional materials (Figure 2-1). However, the default buy/fly ratio for powder technology is 2, reflecting near net shape production possibilities. When relative material cost and relative machining cost for any of the advanced materials become known, these values can be inserted into the code using the user input mode.

2.2.1 Fans and Compressors (Class Ti)

Titanium alloy/powder metallurgy compressor blades, vanes, and disks are under research. Some of the advanced alloys under consideration are:

- Ti-6AL-6V-2SN
- Ti-6-2-1.5-1BISI
- Ti-6-2-2-2-2-SI
- Ti-6AL-2SN-42R-2MO

2.2.2 Turbines (Class D)

Superalloy powders that are shaped into turbine disks by hot isostatic process, where the powder is compressed under high temperature and vacuum conditions, show great potential in cost savings.

The controlled solidification process includes directional solidification of conventional alloys and single crystal growth techniques. These processes will contribute significantly to improved blade life by eliminating intercrystalline cracking, one of the common blade failure mechanisms.

Directional solidification of "eutectic" alloys is another area of active research, and shows promise of turbine blade materials in which turbine inlet temperatures can be increased about 1000 to 1500F as compared to conventional nickel base superalloys. Some of the turbine advanced materials under research are:

AF2-1DA

WA2-20

TA2-8B

LDA-204

2.2.3 Combustors (Class B)

Some of the advanced materials under consideration for combustors are:

Hastelloy-S

Hastelloy-T

Inconel-617

TD-NiCrAlY

2.2.4 Other High Temperature Materials

Intermetallic alloys, refractory metal alloys and ceramics have potential use in jet engines, but these materials and processes are not included in the present COST code, because of limited data on cost and use.

2.3 COST Computer Code

The computer model follows the same material classification presented in References 1-2 and 1-3. Figure 2-1 presents the original group of materials used and their corresponding relative machining cost and relative material cost factors. Additional state-of-the-art materials have been added to the referenced lists; the array incorporated into the computer program, in addition to the original group, is shown in Figure 2-2.

MAJOR MATERIAL CLASSES				
A	B	C	D	Ti
AM -355	AISI 310	AISI 4140	IN - 100	Ti - 8AL - 1MO -IV
INCO - 901	AISI 347	AISI 4340	H53V	Ti - 679
RENE - 95	IN 586	NITRALLOY 135	TIMKIN 16 -25 -6	Ti - 6 - 2 - 4 - 8
AISI410	TD NiCRAIY	C455	MAR - M432	Ti - 17

Figure 2-2 Additional State-of-the-Art Material by Class




Figure 2-3 Manufacturing Efficiency

Raw material weight to finished part weight ratio is referred to as the buy/fly ratio in the computer model. Buy/fly ratios for different classes of materials were estimated from data obtained from industry and References 1-3 and 2-4. A summary of manufacturing efficiency (buy/fly data) for the selected material classes drawn from these references is presented in Figure 2-3. After several simulations of engines in the Boeing data base, these buy/fly ratios were felt to be overly pessimistic, and hence were modified. A more representative state-of-the-art buy/fly value for machined castings and forgings is 4 while for sheet material it is 2. When the advanced technology mode is used, the powder manufacturing method buy/fly ratio is 2. These buy/fly values can be modified by the user as more experience is gained with the model or new processes are developed; in the interim, COST default buy/fly values have been set as indicated.

The user has the option to override all the defaulted variables that affect the Maurer factor for the component or the total engine under study. These variables are buy/fly ratio, relative material cost, and relative machining cost.

The COST output presents material class, buy/fly ratio, raw material weight, relative machining cost, relative material cost, a "component" Maurer factor, and an engine aggregate Maurer factor. A sample output for a primary burner is presented in Figure 2-4. Material lists by class can be output as a user option (Figure 2-5).

 * PBUR 8 *
 *
 *****2

MAX CONDITIONS OCCUR AT

 ALT 4N VALUE
 PTOT 0. 0.000 274.8 LB/SQIN
 TTOT C. 0.000 1392.1 DEG F
 CWIN 0. 0.000 12.0 LB/SEC

BURNER NUMBER 2

RIN	ROUT	LENGTH	MACH	VSPEC	WTOT
0.000	9.588	30.720	.071	5.953	
CAS WT	LIN WT	NOZ WT	INC WT	FRAME	
17.6	30.5	29.9	0.0	83.5	161.6

ESTIMATED COMPONENT COST SUMMARY
 CURRENT TECHNOLOGY

BURN

	CASE LINING	NOZZLE
MATERIAL	GROUP B	GROUP B
MANF. METH	SHEET	FORG
FINISHED WT	49.	30.
BUY/FLY	2.00	4.00
RAW MTL WT	95.	120.
MTL COST F	4.50	4.50
MAN COST F	3.10	3.10
MAURER F	1344.	1671.

FRAME 1

 MATERIAL GROUP A
 MANF. METH FORG
 FINISHED WT 83.
 BUY/FLY 4.00
 RAW MTL WT 334.
 MTL COST F 3.50
 MAN COST F 1.90
 MAURER F 2221.

TOTAL MAURER FACTOR FOR THIS COMPONENT IS 5235.

CUMULATIVE MAURER FACTOR 51679.

THIS PAGE IS BEST QUALITY PRINTING
 FROM COPY FURNISHED TO DDC

Figure 2-4 Primary Burner Output

MATERIAL CLASSIFICATION

GROUP T

6AL4V AMS4965
 5AL6V AMS4971
 BAL1MO AMS4973

GROUP A

A-286 GA AMS5525
 17-4PHSS AMS5639
 AM-350 AMS5542

GROUP B

INCO-625 AMS5599
 HASTEL-X AMS5754
 HASTEL-B AMS5755

GROUP C

L-605 AMS5537
 INCO-718 AMS5382
 INCO-625 AMS5599

GROUP D

W6SPOLOY AMS5704
 RENE-41 AMS5712
 DISKOLOY AMS5731

GROUP ADV

TI-6AL-6V-2SN
 TI-6-2-1.5-1BISI
 TI-6-2-2-2-2-SI
 TI-6AL-2SN-42R-2MO
 WAZ 20
 AF2-104
 TAZ88
 LDA 204
 INCONEL 517
 TD-NIRAIY
 MAR-M305
 UNITE4P 300
 PA101
 IN-953HA753
 HASTELLOY S
 HASTELLOY T

COMPRESSOR ALLOY
 COMPRESSOR ALLOY
 COMPRESSOR ALLOY
 COMPRESSOR ALLOY
 BLADE ALLOY
 TURBINE DISKS
 BLADE ALLOY
 CAST BLADES
 COMBUSTOR
 COMBUSTOR
 1400 F SHEET
 1200 F ALLOY
 POWDER ALLOY
 POWDER ALLOY
 CYCLIC HEAT
 LOW EXPANSTON

Figure 2-5 Material Classification Output

2.4 Program Validation

A contractually required verification of the accuracy of the newly developed portion of the code was done by applying it to three engines and comparing the results with Maurer factors furnished by NADC. Results of the COST program estimates for these engines are shown in Figure 2-6. As can be seen, Maurer factors for the three selected engines are within the ±10% accuracy goal for the program.




Figure 2-6. Program Results in Estimating Maurer Factor

3.0 USER'S MANUAL

This section contains a description of input-output data, values of typical inputs, and a sample case. COST has been incorporated into two versions of the earlier weight codes -- the engine component analysis "Navy Stand Alone" program and the "NASA-Navy Engine Program" (Ref. 3-1),

The overall program structures modified to incorporate cost estimation are shown in the flow charts presented in the sections for the two different programs. The COST/Navy Stand Alone code will be referred to as the NAVY/COST code, and the NASA-Lewis code will be referred to as NASA/COST.

3.1 "Navy Code" Program Structure

The overall program structure and connectivity to the earlier engine component analysis code (WTINTR) are shown in Figures 3-1 and 3-2.

ENGINE COMPONENT ANALYSIS

WEIGHT

MAURER
FACTOR

&

COST DATA

FIGURE 3-1 OVERALL "NAVY CODE" PROGRAM STRUCTURE




Figure 3-2 Diagram of Subroutine Connectivity

3.1.1 Input Description and Format

For users of this version of the cost code, reference must be made to the NADC Engine Performance Group for input format and methods of running the engine component analysis code (WTINTR). The following comments describe inputs to WTINTR which are required to run NAVY/COST.

3.1.2 Mode Indicators

- o MODE = 0 Do not do MAURER factor calculation
- = 1 Current technology default values
- = 2 Advanced technology default values
- = 3 User technology utilizing user inputs
- = 4 Current technology default values and list current and advanced materials by material classification

- o MODE 1 = 0 Long output
- = 1 Short output - component MAURER factor and cumulative MAURER factor

- o MODE 2 = 0 Do not execute Navy cost routine
- = 1 Execute Navy cost routine

3.1.3 User Technology Inputs

The user has the option to input certain of the following variables depending on the component that is being simulated.

BFR = Buy/Fly ratio
 MTLF = Material cost factor
 MANF = Manufacturing cost factor
 HDBFR = Buy/Fly ratio for fan, compressor and turbine stages
 that require different material because of high
 temperature

 HDMTLF = Material cost factor for fan, compressor and turbine
 stages that require different material because of high
 temperature

 HDMANF = Manufacturing cost factor for fan, compressor and
 turbine stages that require different material because
 of high temperature

3.1.3.1 Fan or Compressor

The user selectable variables are listed for the major items in the low temperature rotating elements of the engine.

Blades and Vanes

BFR, MTLF, MANF, HDBFR, HDMTLF, HDMANF

Disks

BFR, MTLF, MANF, HDBFR, HDMTLF, HDMANF

Case

BFR, MTLF, MANF

Miscellaneous

BFR, MTLF, MANF

3.1.3.2 Turbine

The user selectable variables for the turbines of the engine are:

Blades and Vanes

BFR, MTLF, MANF, HDBFR, HDMTLF, HDMANF

Disks

BFR, MTLF, MANF, HDBFR, HDMTLF, HDMANF

Case

BFR, MTLF, MANF

Miscellaneous

BFR, MTLF, MANF

3.1.3.3 Burner

The user selectable variables for the combustor and high turbine nozzle are:

Case and Linings

BFR, MTLF, MANF

3.1.3.4 Nozzle and Thrust Reverser

The user selectable variables for the engine nozzle components are:

BFR, MTLF, MANF

3.1.3.5 Ducts

The user selectable variables for the various engine ducts are:

BFR, MTLF, MANF

3.1.3.6 Air Inverting Valve (AIV), Mixer, Heat Exchanger

The user selectable variables for these special purpose engine elements are:

BFR, MTLF, MANF

3.1.4 Navy Cost Subroutine Inputs

Entries and typical values are presented in the following arrays.

Enter

A, B, CURVE, OHDI, PROFIT

<u>VARIABLE</u>	<u>DESCRIPTION</u>	<u>TYPICAL VALUE</u>
A	Slope of MAURER curve	1.875
B	Intercept of MAURER factor curve	48296
CURVE	Learning curve	0.90
OHDI	Manufacturers overhead rate	.12
PROFIT	Manufacturers profit	.10

NYR1, NYR2

Beginning and end of production ie 1, 10 means 10 years of production

Q(1), Q(2), Etc.

Quantity produced each production year; i.e., 100, 100 means 100 units during first and second production year.

3.2 NASA/COST Program Structure

The overall program structure and connectivity are shown in the Figures 3-3 and 3-4. In order to execute the program, it is first necessary to run NNEP to generate thermodynamic data and subsequently enter WATE II inputs as described in Reference 1-1, and to additionally enter COST inputs as described below.

3.2.1 Input Description and Format

The COST inputs are free-field format (NAMELIST), and begin in column 2. There is no specified order to the inputs. Figure 3-5 shows the WATE2/COST input set for a typical case.

3.2.2 Mode Indicators

- o MODEC = 0 Do not calculate MAURER FACTOR
 = 1 Current technology default values
 = 2 Advanced technology default values
 = 3 User technology utilizing user inputs
 = 4 Current technology default values and material
 classification list

- o MODEC1 = 0 Long output
 = 1 Short output-component MAURER factor and cumulative
 MAURER factor

- o ICOST = 0 Do not execute Navy cost routine
 = 1 Execute Navy cost routine




Figure 3-3 NASA/COST Overall Program Structure




Figure 3-4 Diagram of Subroutine Connectivity

```

SW
IWT=2,IPLT=T,
ISII=F,ISID=F,IOUTCO=2,
ILENG(1)=2,3,4,5,6,7,8,9,10,11,12,
DISK4I=0.,
ACCS=.001,
MODEC=4,
ICOST=1,
ICOST1(1)=1,10,
IWMEC(1,2)=11113 ,0,1,1,3*0,
IWMEC(1,3)=99999,6*0,
IWMEC(1,4)=55551,2,5*0,
IWMEC(1,5)=11111 ,1,3*0,15,0,
IWMEC(1,6)=55551,2,5*0,
IWMEC(1,7)=11112 ,1,5*0,
IWMEC(1,8)=22221,1,5*0,
IWMEC(1,9) =33331 ,1,7,0,0,4*0,
IWMEC(1,10)=55551,2,5*0,
IWMEC(1,11)=33332 ,1,2,0,0,2*0,
IWMEC(1,12)=55551,1,5*0,
IWMEC(1,13)=22222,0,5*0,
IWMEC(1,14)=88888 ,2,5*0,
IWMEC(1,15)=66661,1,11,3*0,5,
IWMEC(1,16)=66661,2,9 ,3*0,7,
DESVAL(1,2)=.40,1.4,.32,1.,5.5,5.5,.45,0.,0.,1.,0.,2.,1.544,4*C.,
DESVAL(1,3)=15*0.,2*0.,
DESVAL(1,4)=.5,20.,0.,4.,10*0.,4.2,2*0.,
DESVAL(1,5)=.50,1.28,.32,1.5,1.8,1.5,.45,0.,0.,1.,0.,2.,1.,4*0.,
DESVAL(1,6)=.45,5.5,0.,5.,11*0.,2*0.,
DESVAL(1,7)=.5,1.20,.65,2.5,1.15,1.15,.3,0.,0.,1.,0.,2.,.73,4*0.,
DESVAL(1,8)=12*0.,.0200,15*0.,
DESVAL(1,9) =.23,.29,1.2,1.1,1.1,.4,150000.,1.,1.,12.,7*0.,
DESVAL(1,10)=.5,3.5,0.,-1.,11*0.,2*0.,
DESVAL(1,11)=.50,.3,1.05,1.58,1.58,.4,150000.,3.,1.,12.5,7*0.,
DESVAL(1,12)=.6,.5,0.,14.,11*0.,2*0.,
DESVAL(1,13)=280.,.0274,15*C.,
DESVAL(1,14)=.8,13*0.,0.,2*0.,
DESVAL(1,15)=50000.,.3,.85,12*0.,2*0.,
DESVAL(1,16)=50000.,.3,13*0.,2*0.,
DECJST(1,1)=0.,1.,1.,4.,1.,1.,
DECJST(1,2)=4.,1.,1.,4.,1.,1.,
DECJST(1,3)=2.,1.,1.,
DECJST(1,4)=4.,1.,1.,
DECJST(1,5)=0.,2.,2.,4.,2.,2.,
DECJST(1,6)=4.,2.,2.,4.,2.,2.,
DECJST(1,7)=2.,2.,2.,
DECJST(1,8)=4.,2.,2.,
DECJST(1,9)=0.,
DECJST(1,11)=0.,
DECJST(1,13)=0.,
DECJST(1,14)=0.,
OCJST1(1)=1.875,48276.,0.95,1.25,0.1,5*C.,
OCJST(1)=50.,50.,200.,200.,200.,200.,200.,200.,100.,100.,
SEND

```

Figure 3-5 User Input

3.2.3 User Technology Inputs

DECOST (6, 18) is a NAMELIST array. The input variables are defined as

<u>VARIABLE</u>	<u>DESCRIPTION</u>
BFR	Buy/Fly ratio
MTLF	Material cost factor
MANF	Manufacturing cost factor
HDBFR	Buy/Fly ratio for fan, compressor and turbine stages that require different material because of high temperature
HDMTLF	Material cost factor for fan, compressor and turbine stages that require different material because of high temperature
HDMANF	Manufacturing cost factor for fan, compressor and turbine stage that require different material because of high temperature

3.2.3.1 Fan and Compressor

<u>ARRAY LOCATION</u>	<u>DESCRIPTION</u>	<u>VARIABLE</u>
(1,1) - (6,1)	Blade and Vane	BFR, MTLF, MANF, HDBFR, HDMTLF, HDMANF
(1,2) - (6,2)	Disk	
(1,3) - (3,3)	Case	BFR, MTLF, MANF
(1,4) - (3,4)	Misc	

3.2.3.2 Turbine

<u>ARRAY LOCATION</u>	<u>DESCRIPTION</u>	<u>VARIABLE</u>
(1,5) - (6,5)	Blade and Nozzle	BFR, MTLF, MANF, HDBFR, HDMTLF, HDMANF
(1,6) - (6,6)	Disk	
(1,7) - (3,7)	Case	BFR, MTLF, MANF
(1,8) - (3,8)	Misc	

3.2.3.3 Burner

<u>ARRAY LOCATION</u>	<u>DESCRIPTION</u>	<u>VARIABLE</u>
(1,9) - (3,9)	Case and Lining	BFR, MTLF, MANF
(1,10) - (3,10)	Nozzle	

3.2.3.4 Nozzle and Thrust Reverser

<u>ARRAY LOCATION</u>	<u>DESCRIPTION</u>	<u>VARIABLE</u>
(1,11) - (3,11)	Nozzle	BFR, MTLF, MANF
(4,11) - (6,11)	High Temp Nozzle	
(1,12) - (3,12)	Thrust Reverser	BFR, MTLF, MANF
(4,12) - (6,12)	High Temp Thrust Reverser	

3.2.3.5 Shaft

<u>ARRAY LOCATION</u>	<u>DESCRIPTION</u>	<u>VARIABLE</u>
(1,13) - (3,13)	Shaft	BFR, MTLF, MANF

3.2.3.6 Duct

<u>ARRAY LOCATION</u>	<u>DESCRIPTION</u>	<u>VARIABLE</u>
(1,14) - (3,14)	Duct	BFR, MTLF, MANF
(4,14) - (6, 14)	High Temp Duct	BFR, MTLF, MANF

3.2.3.7 AIV, MIXER, Heat Exchanger

<u>ARRAY LOCATION</u>	<u>DESCRIPTION</u>	<u>VARIABLE</u>
(1,15) - (3,15)	AIV, MIXER or Heat Exchanger	BFR, MTLF, MANF

Array locations (1,16) through (6,16) are for future use.

3.2.4 Navy Cost Subroutine Inputs

- o ICOST1(2) is a NAMELIST Array
ICOST1(1) and ICOST1(2) are total production time indicators
Example Total production time = 10 years
ICOST1(1) = 1,10

- o DECOSTI(10) is a NAMELIST Array
 - DECOSTI(1) = Slope of MAURER factor curve (1.875 TYP)
 - DECOSTI(2) = Intercept of MAURER factor curve (48296 TYP)
 - DECOSTI(3) = Learning curve (.90 TYP)
 - DECOSTI(4) = Manufacturers overhead rate (.12 TYP)
 - DECOSTI(5) = Manufacturers profit (.10 TYP)
 - DECOSTI(6)-(10) = For future use

- o DECOST(20) is a NAMELIST Array
 - DECOST(1) through DECOST(20) = Yearly production rates.

REFERENCES

- 1-1 Onat, E. and Klees, G. W., "A Method to Estimate Weights and Dimensions of Large and Small Gas Turbine Engines", CR159481, January 1979.
- 1-2 Brennan, T. J., and Taylor, R. N., Steinert, A. G., "Cost Estimating Techniques for Advanced Technology Engines", SAE 700271, April 1970.
- 1-3 Brennan, T. J. and Finizie, L T., "Gas Turbine Engine Cost Estimating", AIAA Paper No. 76-752, July 1976.
- 2-1 Simmons, W. F., "Current and Future Materials Usage in Aircraft Gas Turbine Engines", AD-766334, June 1973.
- 3-1 Fishbach, L. H., and Caddy, M. J., "NNEP-The NAVY NASA Engine Program", NASA TM X-71857, December 1975.