

AD-A075 944

NAVAL POSTGRADUATE SCHOOL MONTEREY CA

F/G 13/13

VIBRATION OF A CANTILEVER BEAM THAT SLIDES AXIALLY IN A RIGID F--ETC(U)

SEP 79 A P BORESI , D SALINAS

UNCLASSIFIED

NPS-69-79-009

NL


| OF |

AD
A075944



END
DATE
FILMED
12-79

DDC



NPS-69-79-009

LEVEL

2

AD A 075944

NAVAL POSTGRADUATE SCHOOL
Monterey, California



DDC
RECEIVED
NOV 1 1979
E

DDC FILE COPY

VIBRATION OF A CANTILEVER BEAM THAT
SLIDES AXIALLY IN A RIGID FRICTIONLESS HOLE

by

Arthur P. Boresi and
David Salinas

September 1979

Approved for public release; distribution unlimited.

Prepared for:
Naval Sea Systems Command
Washington, D. C. 20362

79 11 01 020

NAVAL POSTGRADUATE SCHOOL
Monterey, California


Rear Admiral T. F. Dedman
Superintendent

Jack R. Borsting
Provost

The report prepared in conjunction with research supported in part
by the Naval Sea Systems Command under Work Request N002479WR9G103.

Reproduction of all or part of this report is authorized.

Released as a Technical Report by:



W. M. Tolles
Dean of Research

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 14 NPS-69-79-009	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) 6 VIBRATION OF A CANTILEVER BEAM THAT SLIDES AXIALLY IN A RIGID FRICTIONLESS HOLE.	5. TYPE OF REPORT & PERIOD COVERED 9 Technical Report, FY79	
7. AUTHOR(s) 10 Arthur P. Boresi David/Salinas	6. PERFORMING ORG. REPORT NUMBER	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940	8. CONTRACT OR GRANT NUMBER(s) N002479WR9G103	
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62543N N0002479WR9G103	12. REPORT DATE 11 Sep 1979
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 12 24	13. SECURITY CLASS. (of this report) Unclassified	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Vibration, Cantilever Beam, Moving Boundary, Nonlinear P.D.E.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This paper considers a cantilever beam which can move in and out of a rigid frictionless hole. Hamilton's principle is used for the development of two governing equations, and boundary conditions defined over a moving boundary. A transformation of coordinates is used to transform the problem into a system of two nonlinear p.d.e. defined over a fixed region. A discussion of some mathematical and physical considerations is presented. Finally, a finite element formulation of the problem is presented.		

251 450

elt

CONTENTS

	Page
1. Introduction - - - - -	1
2. Analysis of Equations - - - - -	6
3. Method of Solution - - - - -	12
4. Figures - - - - -	17
REFERENCES - - - - -	19
INITIAL DISTRIBUTION LIST - - - - -	20

Accession For	
NTIS GMA&I	<input checked="" type="checkbox"/>
DIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<input type="checkbox"/>
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or special
A	

VIBRATION OF A CANTILEVER BEAM THAT
SLIDES AXIALLY IN A RIGID FRICTIONLESS HOLE

INTRODUCTION

Consider a cantilever beam that fits snugly into a frictionless hole, Fig. 1. Axes x, y are fixed. A force $F(t)$ moves the beam axially. Hence, the length L of the beam outside of the hole is a function of time t . The lateral deflection of the beam is $y(x, t)$, where for $x < 0$, $y = 0$. The axial velocity of the beam is $\dot{L} = dL/dt$.

By Hamilton's principle,

$$\int_0^{t_1} (\delta T + \delta W) dt = 0 \quad (1)$$

where T denotes the kinetic energy of the system and W denotes the work of external and internal forces. The kinetic energy is

$$T = \frac{1}{2} \rho L_0 \dot{L}^2 + \frac{1}{2} \rho \int_0^L y_t^2 dx \quad (2)$$

where the subscript t denotes partial differentiation, ρ = the mass of the beam per unit length = constant, and L_0 = the length of the beam when $t = 0$. The strain energy of the beam (the negative of the work of internal forces for a conservative system) is

$$U = \frac{1}{2} EI \int_0^L y_{xx}^2 dx \quad (3)$$

where E = the modulus of elasticity of the beam and I = the second moment of the beam cross-sectional area. Hence, the virtual work δW is

$$\delta W = F\delta L - \delta U \quad (4)$$

where δU = the first variation of the strain energy (Eq. 3). Because of the inertia, the axial movement of the beam tends to bend the beam by beam-column action. This effect is neglected here, but it could be included.

Equations (1), (2), (3), and (4) yield

$$\int_0^{t_1} [\rho L_0 \dot{L} \delta \dot{L} + \frac{1}{2} \rho y_t^2(L, t) \delta L + F \delta L - \frac{1}{2} EI y_{xx}^2(L, t) \delta L + \rho \int_0^L y_t \delta y_t dx - EI \int_0^L y_{xx} \delta y_{xx} dx] dt = 0 \quad (5)$$

If $L(t)$ is considered as given, the terms with the factors δL and $\delta \dot{L}$ merely determine $F(t)$ to give the prescribed motion $L(t)$. The Euler equation for the lateral motion of the beam is

$$EI y_{xxxx} + \rho y_{tt} = 0 \quad (6)$$

The natural boundary conditions are

$$y_{xx}(L, t) = y_{xxx}(L, t) = 0 \quad (7)$$

The forced boundary conditions are

$$y(0,t) = y_x(0,t) = 0 \quad (8)$$

Adopting Hamilton's viewpoint, we may suppose that $y(x,0)$ and $y(x,t_1)$ are prescribed (Fig. 2). The problem is to determine $y(x,t)$ in region R (Fig. 2) subject to the differential equation (Eq. 6) and the indicated boundary conditions (Fig. 2).

The curved boundary at the right side of region R is troublesome. It is possible to transform coordinates so that this boundary becomes straight.

Let

$$x = x(\xi, \eta), \quad t = t(\xi, \eta) \quad (9)$$

Regard y as a function of (ξ, η) . Then,

$$y = y(\xi, \eta), \quad \xi = \xi(x, t), \quad \eta = \eta(x, t) \quad (10)$$

and

$$\begin{aligned} \left(\frac{\partial y}{\partial x}\right)_t &= \left(\frac{\partial y}{\partial \xi}\right)_\eta \left(\frac{\partial \xi}{\partial x}\right)_t + \left(\frac{\partial y}{\partial \eta}\right)_\xi \left(\frac{\partial \eta}{\partial x}\right)_t \\ \left(\frac{\partial y}{\partial t}\right)_x &= \left(\frac{\partial y}{\partial \xi}\right)_\eta \left(\frac{\partial \xi}{\partial t}\right)_x + \left(\frac{\partial y}{\partial \eta}\right)_\xi \left(\frac{\partial \eta}{\partial t}\right)_x = \dot{y} \\ \left(\frac{\partial^2 y}{\partial t^2}\right)_x &= \left(\frac{\partial \dot{y}}{\partial \xi}\right)_\eta \left(\frac{\partial \xi}{\partial t}\right)_x + \left(\frac{\partial \dot{y}}{\partial \eta}\right)_\xi \left(\frac{\partial \eta}{\partial t}\right)_x \end{aligned} \quad (11)$$

Here, we regard \dot{y} as being a function of (ξ, η) .

Now let

$$\xi = \frac{x}{L}, \quad t = \eta \quad (12)$$

When we write $\frac{\partial y}{\partial \xi}$, $\frac{\partial y}{\partial \eta}$, etc., we imply $y = y(\xi, \eta)$. Hence, $\frac{\partial y}{\partial x} = \left(\frac{\partial y}{\partial \xi}\right) \left(\frac{1}{L}\right)$, and similarly,

$$\frac{\partial^4 y}{\partial x^4} = \frac{1}{L^4} \cdot \frac{\partial^4 y}{\partial \xi^4} \quad (13)$$

Now,

$$\left(\frac{\partial y}{\partial t}\right)_x = \frac{\partial y}{\partial \xi} \left(\frac{\partial \xi}{\partial t}\right)_x + \frac{\partial y}{\partial \eta} = \dot{y}$$

and since

$$\left(\frac{\partial \xi}{\partial t}\right)_x = -\frac{x\dot{L}}{L^2} = -\frac{\xi\dot{L}}{L}, \quad \left(\frac{\partial \eta}{\partial t}\right)_x = 1, \quad (14)$$

we find

$$\dot{y} = -\left(\frac{\partial y}{\partial \xi}\right)_\eta \frac{\xi\dot{L}}{L} + \left(\frac{\partial y}{\partial \eta}\right)_\xi$$

and hence,

$$\begin{aligned} \left(\frac{\partial \dot{y}}{\partial \xi}\right)_\eta &= -\left(\frac{\partial^2 y}{\partial \xi^2}\right)_\eta \frac{\xi\dot{L}}{L} - \left(\frac{\partial y}{\partial \xi}\right)_\eta \frac{\dot{L}}{L} + \frac{\partial^2 y}{\partial \xi \partial \eta} \\ \left(\frac{\partial \dot{y}}{\partial \eta}\right)_\xi &= -\frac{\partial^2 y}{\partial \xi \partial \eta} \frac{\xi\dot{L}}{L} - \left(\frac{\partial y}{\partial \xi}\right)_\eta \frac{\xi\ddot{L}}{L} + \left(\frac{\partial y}{\partial \xi}\right)_\eta \frac{\xi\dot{L}^2}{L} \\ &\quad + \frac{\partial^2 y}{\partial \eta^2} \end{aligned} \quad (15)$$

Thus, by the third of Eqs. (11), Eqs. (12), Eqs. (14), and Eqs. (15), we find

$$\begin{aligned} \left(\frac{\partial^2 y}{\partial t^2}\right)_x &= \left[-\left(\frac{\partial^2 y}{\partial \xi^2}\right)_\eta \frac{\xi\dot{L}}{L} - \left(\frac{\partial y}{\partial \xi}\right)_\eta \frac{\dot{L}}{L} + \frac{\partial^2 y}{\partial \xi \partial \eta}\right] \left(-\frac{\xi\dot{L}}{L}\right) \\ &\quad + \left[-\left(\frac{\partial^2 y}{\partial \xi \partial \eta}\right)_\eta \frac{\xi\dot{L}}{L} - \left(\frac{\partial y}{\partial \xi}\right)_\eta \frac{\xi\ddot{L}}{L} + \left(\frac{\partial y}{\partial \xi}\right)_\eta \frac{\xi\dot{L}^2}{L} + \frac{\partial^2 y}{\partial \eta^2}\right] \end{aligned}$$

and since $\eta = t$, we obtain

$$\begin{aligned} \left(\frac{\partial^2 y}{\partial t^2}\right)_x &= \frac{\partial^2 y}{\partial \xi^2} \frac{\xi^2 L^2}{L^2} + 2 \frac{\partial y}{\partial \xi} \frac{\xi \dot{L}^2}{L^2} - 2 \frac{\partial^2 y}{\partial \xi \partial t} \frac{\xi \dot{L}}{L} \\ &\quad - \frac{\partial y}{\partial \xi} \frac{\ddot{L}}{L} + \frac{\partial^2 y}{\partial t^2} \end{aligned} \quad (16)$$

in which $y = y(\xi, t)$ on the right hand side of Eq. (16).

Consequently, Eqs. (6), (13) and (16) yield

$$\begin{aligned} \frac{EI}{L^4} \frac{\partial^4 y}{\partial \xi^4} + \rho \left[\frac{\partial^2 y}{\partial \xi^2} \frac{\xi^2 L^2}{L^2} + 2 \frac{\partial y}{\partial \xi} \frac{\xi \dot{L}^2}{L^2} \right. \\ \left. - 2 \frac{\partial^2 y}{\partial \xi \partial t} \frac{\xi \dot{L}}{L} - \frac{\partial y}{\partial \xi} \frac{\ddot{L}}{L} + \frac{\partial^2 y}{\partial t^2} \right] = 0 \end{aligned} \quad (17)$$

where y is now regarded as a function of ξ and t . Equations (7) and (8) become

$$y_{\xi\xi}(1, t) = y_{\xi\xi\xi}(1, t) = 0 \quad (18)$$

$$y(0, t) = y_{\xi}(0, t) = 0$$

Equation (17) is much more complicated than Eq. (6). However, the region R is simpler (Fig. 3). The problem remains a linear boundary-value problem if in Eq. (17) we regard $L(t)$ as a given function of time t . If we consider $L(t)$ as unknown, we must obtain another equation which defines $L(t)$. This equation is obtained from Eq. (5) from the terms with the factors δL and $\delta \dot{L}$. Hence, we find

$$\ddot{L} + \frac{1}{2\rho L_0} [EI y_{xx}^2(L,t) - \rho y_t^2(L,t)] = \frac{1}{\rho L_0} F(t) \quad (19)$$

In terms of (ξ, t) , Eq. (19) becomes

$$\begin{aligned} \ddot{L} + \frac{1}{2\rho L_0} \left\{ \frac{EI}{L^4} y_{\xi\xi}^2(\xi, t) - \rho \left[-\frac{\dot{L}}{L} y_\xi(\xi, t) + y_t(\xi, t) \right]^2 \right\} \\ = \frac{1}{\rho L_0} F(t) \end{aligned} \quad (20)$$

Equation (20) is subject to the initial conditions

$$\begin{aligned} L(0) &= L_0 \\ \dot{L}(0) &= 0 \end{aligned} \quad (21)$$

where L_0 is the initial length of the beam at time $t = 0$, (see Fig. 1).

Thus, if $y(x,t)$ and $L(t)$ are considered as the unknowns, Eqs. (17) and (20) subject to the boundary conditions of Eqs. (18) and (21), respectively, represent a complicated nonlinear boundary value problem.

ANALYSIS OF EQUATIONS

(a) $L(t)$ Prescribed. If $L(t)$ is given, then the problem reduces to seeking a solution of Eq. (17) subject to the boundary conditions, Eqs. (18). The problem is still of considerable difficulty. However, the problem is a linear boundary-value problem. The nature of the solutions of Eq. (17) is unknown. Indeed, one must consider whether or not a unique solution of the boundary-value problem exists. Also, is there a unique solution of the corresponding initial value problem in which the condition $y = F_1(\xi)$ on $t = t_1$ is discarded and the functions $y(\xi, 0)$ and $y_t(\xi, 0)$ are prescribed? One way to approach such questions is through the calculus of finite

differences, in which the differential equation is replaced by a linear partial difference equation. The existence of a solution of the difference equation is a question of linear algebra. The most practical way of developing numerical solutions of Eqs. (17) and (18) is an open question. One possible approach is through the calculus of finite differences, or a combination of the calculus of finite differences with the Runge-Kutta method. Another approach is through finite-element methods.

The problem is simplified greatly if the axial motion is so slow that time derivatives of $L(t)$ are negligible. For example, if the beam is vibrating in a natural mode and it is then drawn slowly into the hole, does it continue to vibrate in a natural mode? How do the frequency and amplitude vary with L under these conditions? For a rigid, frictionless hole, the total mechanical energy is constant, since no energy is imparted at the root. This criterion serves to determine how the amplitude varies. However, we should not have to apply this criterion, since constancy of mechanical energy should follow automatically from the solution of Eq. (17).

If \dot{L} and \ddot{L} are negligible, Eq. (17) reduces to

$$\frac{\partial^4 y}{\partial \xi^4} + \frac{\partial L}{\partial t} \frac{\partial^2 y}{\partial t^2} = 0 \quad (22)$$

Equation (22) is much simpler than Eq. (17). However, the fact that L is a prescribed function of t still complicates it. There is a question as to whether the character of the solution is altered by the reduction of Eq. (17) to Eq. (22). Again, does the initial value problem posed by Eqs. (18) and (22) have a unique solution? If so, the constancy of mechanical energy, as a separate principle, is not needed to determine the dependency of amplitude upon L . In fact, constancy of mechanical energy should be a deducible consequence of Eqs. (18) and (22).

Unlike Eq. (17), Eq. (22) allows a theory of natural modes. For example, consider solutions of Eq. (22) of the form $y = f(\xi)g(t)$. Then, Eq. (22) yields

$$\frac{f''''}{f} + \frac{\rho L^4}{EI} \frac{g''}{g} = 0$$

Hence,

$$\frac{f''''}{f} = \beta^4, \quad \frac{\rho L^4}{EI} \frac{g''}{g} = -\beta^4 \quad (23)$$

in which β is a constant. Then,

$$g'' + \frac{\beta^4 EI}{\rho L^4} g = 0 \quad (24)$$

Unfortunately, Eq. (24) does not yield simple harmonic motion, because L is a function of t . However, the equation

$$f'''' - \beta^4 f = 0 \quad (25)$$

can be integrated. With the root conditions (Eqs. 18) $f(0) = f'(0) = 0$, Eq. (25) yields

$$f(\xi) = A(\sinh\beta\xi - \sin\beta\xi) + B(\cosh\beta\xi - \cos\beta\xi) \quad (26)$$

Now, the free-end conditions (Eqs. 18) $f''(1) = f''''(1) = 0$ yield

$$\begin{aligned} A(\sinh\beta + \sin\beta) + B(\cosh\beta + \cos\beta) &= 0 \\ A(\cosh\beta + \cos\beta) + B(\sinh\beta - \sin\beta) &= 0 \end{aligned} \quad (27)$$

and the vanishing of the determinant of Eqs. (27) yields

$$\cosh\beta \cos\beta = -1 \quad (28)$$

These results are exactly like that for natural modes of a cantilever with fixed length. The roots of Eq. (28) are constants $\beta_1, \beta_2, \beta_3, \dots$. They have been tabulated by Young and Felgar (1).

As is customary, let $B = 1$ and $A = -\alpha_n$. Then, by Eq. (27),

$$\alpha_n = \frac{\cosh\beta_n + \cos\beta_n}{\sinh\beta_n + \sin\beta_n} \quad (29)$$

Consequently, $\alpha_1, \alpha_2, \dots$ are constants, independent of L . The values of α_n have been tabulated by Young and Felgar. Equation (26) gives the natural modes,

$$f_n(\xi) = \cosh\beta_n \xi - \cos\beta_n \xi - \alpha_n (\sinh\beta_n \xi - \sin\beta_n \xi) \quad (30)$$

The functions $f_n(\xi)$ are orthogonal in the interval $(0,1)$; in fact, it is easily shown that

$$\int_0^1 f_n f_m d\xi = 0, \int_0^1 f_n'' f_m'' d\xi = 0, m \neq n$$

$$\int_0^1 f_n^2 d\xi = 1, \int_0^1 (f_n'')^2 d\xi = \beta_n^4 \quad (31)$$

The fact that the functions $f_n(\xi)$ satisfy the end conditions (Eq. 18), makes them ideal approximating functions for use in numerical attacks on Eqs. (17) and (22). Presumably, a solution of Eqs. (17) or (22) can be approximated by

$$y(\xi, t) = \sum_{n=1}^N q_n(t) f_n(\xi) \quad (32)$$

This approach reduces the problem to one of a finite number of degrees of freedom. The generalized coordinates are $q_n(t)$. The Lagrange theory of linear vibrations is then applicable. Accordingly, let

$$\omega_n = \frac{\beta_n^2}{L^2} \sqrt{\frac{ET}{\rho}} \quad (33)$$

Then, Eqs. (24) becomes

$$g_n'' + \omega_n^2 g_n = 0 \quad (34)$$

Since L depends on t , note that ω_n depends on t . Consequently, ω_n is not exactly the frequency of a harmonic motion. The general solution of Eq. (34) is

$$g_n = g_n(t, A_n, B_n) \quad (35)$$

in which A_n, B_n are constants of integration. An infinite series solution of Eq. (22) is then

$$y(\xi, t) = \sum_{n=1}^{\infty} f_n(\xi) g_n(t, A_n, B_n) \quad (36)$$

Equation (36) automatically satisfies boundary conditions (Eqs. 18) at the free end and the root. One might expect that the constants (A_n, B_n) can be chosen to satisfy the conditions at $t = 0$ and $t = t_1$; i.e.,

$$\sum_{n=1}^{\infty} f_n(\xi) g_n(0, A_n, B_n) = F_0(\xi) \quad (37)$$

$$\sum_{n=1}^{\infty} f_n(\xi) g_n(t_1, A_n, B_n) = F_1(\xi)$$

Alternatively, the constants A_n, B_n might be chosen so that the beam has a given initial deformation (the first of Eqs. 37) and given initial velocities; i.e., $y_t(\xi, 0)$ might be specified instead of $y(\xi, t_1)$.

If $L(t)$ is a sufficiently slowly varying function of t , the approximate solution of Eq. (34) is

$$g_n = A_n \sin \omega_n t + B_n \cos \omega_n t \quad (38)$$

Then, Eq. (36) becomes

$$y(\xi, t) = \sum_{n=1}^{\infty} (A_n \sin \omega_n t + B_n \cos \omega_n t) f_n(\xi) \quad (39)$$

The initial value problem then reduces to

$$\sum_{n=1}^{\infty} B_n f_n(\xi) = F_0(\xi) \quad (40)$$

$$\sum_{n=1}^{\infty} A_n \omega_n^0 f_n(\xi) = \phi_0(\xi)$$

in which $\phi_0(\xi) = y_t(\xi, 0)$, and ω_n^0 is the initial value of ω_n . Under fairly broad conditions, the constants A_n, B_n can be chosen to satisfy Eq. (40) when $F_0(\xi)$ and $\phi_0(\xi)$ are prescribed functions. Then Eq. (39) represents the solution of the initial value problem.

The kinetic energy and the strain energy are, respectively,

$$T = \frac{1}{2} \rho L \int_0^1 \dot{y}^2 d\xi = \frac{1}{2} \rho L \sum_{n=1}^{\infty} \omega_n^2 (A_n \cos \omega_n t - B_n \sin \omega_n t)^2$$

$$U = \frac{EI}{2L^3} \int_0^1 y_{\xi\xi}^2 d\xi = \frac{EI}{2L^3} \sum_{n=1}^{\infty} \beta_n^4 (A_n \sin \omega_n t + B_n \cos \omega_n t)^2$$

Hence, in view of Eq. (33), the total mechanical energy is

$$T + U = \frac{EI}{2L^3} \sum_{n=1}^{\infty} \beta_n^4 (A_n^2 + B_n^2)$$

Thus, the total mechanical energy is independent of t , provided that A_n and B_n vary as $L^{3/2}$. Apparently, for the conditions stated, this requirement ensures conservation of mechanical energy.

(b) $F(t)$ Prescribed. If one prescribes $F(t)$, then Eqs. (17) and (20) subject to Eqs. (18) and (21) must be solved simultaneously in order to determine $L(t)$. The method of solution for both cases $L(t)$ prescribed and $F(t)$ prescribed is outlined in the following section.

Method of Solution

Equations (17) and (20), together with the initial and boundary conditions given by Eqs. (18) and (21) form a system of two nonlinear partial differential equations in the two unknowns $L(t)$ and $y(x,t)$. An approximate numerical solution of these equations can be obtained by a Galerkin finite element formulation.

Thus, in accordance with the Galerkin FEM, we form the approximate solutions of L and y as ϕ and v which are,

$$\begin{aligned} L(t) &\approx \phi(t) = \beta(t) \\ y(x,t) &\approx v(x,t) = \underline{N}^T(x)\underline{\alpha}(t) \end{aligned} \quad (41)$$

where \underline{N} are a set of quadratic shape functions with local support. A quadratic shape function is associated with each nodal point of the discretized finite element model. Quadratic interpolation over an element requires each element has three nodal points, say one at each end of the element, and a nodal point in the center of each element.

Figure 4 shows that the odd numbered shape functions N_1, N_3, \dots , associated with nodal points at the ends of an element span five nodal points (two elements), while the even numbered shape functions N_2, N_4, \dots , span the three nodal points of one element.

In accordance with the Galerkin FEM, we form the residual function for Eqs. (17) and (20) as,

$$\begin{aligned} R_1(x,t) = & \frac{EI}{\phi} v'''' + \rho [v' \xi^2 \frac{\dot{\phi}^2}{\phi} + 2v' \xi \frac{\dot{\phi}^2}{\phi} \\ & - 2\dot{v}' \xi \frac{\dot{\phi}}{\phi} - v' \xi \frac{\ddot{\phi}}{\phi} + \ddot{v}] \end{aligned} \quad (42)$$

$$\begin{aligned} R_2(l,t) = & \ddot{\phi} + \frac{1}{2\rho L_0} \left[\frac{EI}{\phi} v''^2(l,t) - \rho \left\{ -\frac{\dot{\phi}}{\phi} v'(l,t) + \dot{v}(l,t) \right\}^2 \right] \\ & - \frac{1}{\rho L_0} F(t) \end{aligned} \quad (43)$$

The finite element equations are obtained by requiring that the residual functions, given by Eqs. (42) and (43), be orthogonal to each of the basis functions. That is,

$$\int_0^1 \underline{N} R_1 dx = 0 \quad (44)$$

$$\int_0^1 H R_2 dx = 0 \quad (45)$$

where H is the function given by

$$H = 1 \quad 0 \leq x \leq 1 \quad (46)$$

Substitution of Eq. (41) into (42) and (43) gives

$$R_1(x, t) = \frac{1}{4} (E I \underline{N}'' \underline{N}'' \underline{T}_\alpha)'' + \rho \left[\xi^2 \frac{\dot{\beta}^2}{\beta^2} \underline{N}'' \underline{T}_\alpha + 2 \xi \frac{\dot{\beta}^2}{\beta^2} \underline{N}' \underline{T}_\alpha - 2 \xi \frac{\dot{\beta}}{\beta} \underline{N}' \underline{T}_\alpha - \xi \frac{\ddot{\beta}}{\beta} \underline{N}' \underline{T}_\alpha + \underline{N} \underline{T}_\alpha \right] \quad (47)$$

$$R_2(1, t) = \ddot{\beta} + \frac{1}{2 \rho L_0} \left[\frac{E I}{\beta^4} (\underline{N}' \underline{T}_\alpha)^2 \Big|_{\xi=1} - \rho \left\{ - \frac{\dot{\beta}}{\beta} \underline{N}' \underline{T}_\alpha \Big|_{\xi=1} + \underline{N} \underline{T}_\alpha \Big|_{\xi=1} \right\}^2 \right] - \frac{1}{\rho L_0} F(t) \quad (48)$$

Substitution of Eqs. (47) and (48) into Eqs. (44) and (45) respectively, and performing integration by parts, gives

$$\begin{aligned} & \underline{B} T + \int_0^1 E I \underline{N}'' \underline{N}'' \underline{T}_\alpha \underline{\xi} \underline{\alpha} - \frac{\dot{\beta}^2}{\beta^2} \int_0^1 \rho \xi^2 \underline{N}' \underline{N}' \underline{T}_\alpha \underline{\xi} \underline{\alpha} + 2 \frac{\dot{\beta}^2}{\beta^2} \int_0^1 \xi \underline{N} \underline{N}' \underline{T}_\alpha d \underline{\xi} \underline{\alpha} \\ & - 2 \frac{\dot{\beta}}{\beta} \int_0^1 \xi \underline{N} \underline{N}' \underline{T}_\alpha d \underline{\xi} \underline{\alpha} - \frac{\ddot{\beta}}{\beta} \int_0^1 \xi \underline{N} \underline{N}' \underline{T}_\alpha d \underline{\xi} \underline{\alpha} + \int_0^1 \underline{N} \underline{N}' \underline{T}_\alpha d \underline{\xi} \underline{\alpha} = 0 \end{aligned} \quad (49)$$

and

$$\ddot{B} + \frac{1}{2\rho L_0} \frac{EI}{\beta^4} \left[\left(\frac{4}{\ell_e^2} \alpha_{2n-1} - \frac{8}{\ell_e^2} \alpha_{2n} + \frac{4}{\ell_e^2} \alpha_{2n+1} \right)^2 \right. \\ \left. - \rho \left\{ -\frac{\dot{B}}{\beta} \left(\frac{1}{\ell_e} \alpha_{2n-1} - \frac{4}{\ell_e} \alpha_{2n} + \frac{3}{\ell_e} \alpha_{2n+1} \right) + \dot{\alpha}_{2n+1} \right\}^2 \right] = \frac{1}{\rho L_0} F(t) \quad (50)$$

where \underline{BT} denotes a boundary term.

Letting,

$$\left. \begin{aligned} A &= \int_0^1 EI \underline{N}' \underline{N}'^T d\xi \\ B &= \int_0^1 \rho \xi^2 \underline{N}' \underline{N}'^T d\xi \\ C &= \int_0^1 \xi \underline{N} \underline{N}'^T d\xi \\ D &= \int_0^1 \underline{N} \underline{N}'^T d\xi \end{aligned} \right\} \quad (51)$$

$$a = \left(\frac{4}{\ell_e^2} \alpha_{2n-1} - \frac{8}{\ell_e^2} \alpha_{2n} + \frac{4}{\ell_e^2} \alpha_{2n+1} \right)^2$$

$$b = \left\{ \frac{\dot{B}}{\beta} \left(\frac{1}{\ell_e} \alpha_{2n-1} - \frac{4}{\ell_e} \alpha_{2n} + \frac{3}{\ell_e} \alpha_{2n+1} \right) + \dot{\alpha}_{2n+1} \right\}^2$$




Figure 1. Cantilever Beam Moving Axially in Cylindrical Hole.




Figure 2. Region of Integration for Equation (6).




Figure 3. Region of Integration for Equation (17)




Figure 4. Discretized FEM Model with Quadratic Basis Functions

REFERENCES

1. Young, D. and R. P. Felgar, Jr., Tables of Characteristic Functions Representing Normal Modes of Vibrations of "Beams", The University of Texas Publication No. 4913, July 1, 1949.

DISTRIBUTION LIST

	No. Copies
1. Library, Code 0142 Naval Postgraduate School Monterey, California 93940	2
2. Dean of Research, Code 012 Naval Postgraduate School Monterey, California 93940	2
3. Department of Mechanical Engineering Code 69 Professor P. Marto Professor G. Cantin Professor R. Newton Professor D. Salinas Professor A. Boresi Naval Postgraduate School Monterey, California 93940	2 1 1 10 10
4. Commander ARRADCOM (ATTN: Ed. Larrison DRDAR-SCA-W) Building 3408 Dover, New Jersey 07801	2
5. R. J. Radkiewicz SARRI-EN Chief, Wave Simulation Division Rock Island Arsenal Rock Island, Illinois 61299	2
6. Phillip M. Hoyt, Head Dept. of Civil and Architectural Engineering The University of Wyoming Laramie, Wyoming 82071	1
7. Robert E. Miller Dept. of Theoretical and Applied Mechanics University of Illinois Urbana, Illinois 61801	2
8. Commander, Naval Sea Systems Command, Washington, D. C. 20362	6
9. Defense Documentation Center Cameron Station Alexandria ,Virginia 22314	2