

(12) **LEVEL** III

AD-E 430 321

AD A U 76968

MEMORANDUM REPORT ARBRL-MR-02951

THE HUGONIOT OF 4340 STEEL RC 54-55

Robert E. Franz
Joseph L. Robitaille

September 1979

DDC
RECEIVED
NOV 20 1979
B



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

DDC FILE COPY

Approved for public release; distribution unlimited.

79 10 30 053

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22151.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute endorsement of any commercial product.*

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

DD FORM 1073 EDITION OF 1 NOV 68 IS OBSOLETE

MONTHLY CANCELLATION OF THIS PAGE: Your Date Entered

313 475

TABLE OF CONTENTS

	<u>Page</u>
TABLE OF CONTENTS	3
I. INTRODUCTION	5
II. EXPERIMENTAL	5
III. RESULTS	7
REFERENCES	13
DISTRIBUTION LIST	15

ACCESSION FOR	
NTIS	White Section ☒
DOC	Buff Section ☐
UNANNOUNCED	☐
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
DOI	AFSA and/or SPECIAL
A	

I. INTRODUCTION

For some time the Ballistic Research Laboratory has been measuring and studying the mechanical and physical properties of materials of interest to the Army. This includes a spectrum of tests from slowly applied loads in conventional testing machines to shock loading with light-gas gun impacts or high explosives. This report gives results of shock wave tests on 4340 steel of Rockwell "C" hardness 54-55. It, also, includes ultrasonic and quasi-static data which provide zero points on the high pressure Hugoniot curves. Table I gives a chemical analysis of this material.

Like iron and rolled homogeneous armor (RHA), 4340 steel displays a phase transition under shock loading at approximately 13 GPa. This causes the material to display a one, two, or three wave structure depending on the initial shock strength. Hauver^{1,2} has discussed this phenomenon in two recent reports on the Hugoniot of RHA. The experimental method used for this study is the same as Hauver's and consists of measuring and analyzing the free surface motion of a sample of material shocked in the usual one-dimensional strain experiment. This motion can become complicated when the three wave structure is encountered. The analysis used is the same as in the aforementioned reports. It is based on a mid-point of the wave analysis used by Barker³, in which the wave velocities are measured from the half amplitude points in the wave.

II. EXPERIMENTAL

The experimental specimens were cut out of a 100mm (4-inch) round bar of material and heat-treated to RC 54-55 hardness. They were, then, machined to final dimensions. The heat-treatment consisted of soaking at 860°C for 30 minutes, oil quenching, drawing down at 315°C for 1 hour, and air cooling. The measured density of the material was 7800 kg/m³.

The experiments were performed with the BRL light-gas gun. The free surface motion was measured with a laser velocity interferometer called a VISAR which was developed by Barker⁴. Figure 1 shows the results of five tests performed at different impact velocities. Four are symmetrical impacts of nominal 6.13mm thick plates of 4340 steel 76mm in diameter and

¹G. Hauver, "The Alpha-Phase Hugoniot of Rolled Homogeneous Armor", Ballistic Research Laboratory Memorandum Report No. 2651, August 1976.

²G. Hauver and A. Malani, "The Epsilon-Phase Hugoniot of Rolled Homogeneous Armor", Memorandum Report ARBRL-MR-02909, March 1979.

³L. M. Barker, "Alpha-Phase Hugoniot of Iron", *J. Appl. Phys.*, Vol. 46, No. 6, June 1975, pp 2544-7.

⁴L. M. Barker and R. E. Hollenbach, "Laser Interferometer for Measuring High Velocities of Any Reflecting Surface", *J. Appl. Phys.*, Vol. 43, No. 11, November 1972, pp 4662-75.




FIGURE 1: VISAR Results for 5 Tests with 4340 Steel

one (Test #6) is the result of the impact of a 3.0mm thick tungsten plate on a 9.43mm thick 4340 steel specimen.

The elastic wave velocity was measured using an ultrasonic device constructed by Hauver¹ and called by him "The Thumper". This velocity, which was used in subsequent data analysis, was 5.86 km/s.

The low pressure α -phase goes through the bulk sound velocity at the zero point. This velocity has been calculated from bulk modulus measurements made in quasi-static compression tests in which the volumetric change with load was measured. This was accomplished by measuring both the axial and circumferential strains using resistance strain gages applied directly to circular cylindrical specimens. The volumetric strain was then calculated from equation (1)

$$\frac{\Delta V}{V_0} = (1 + \epsilon_a)(1 + \epsilon_c)^2 - 1, \quad (1)$$

where,

ϵ_a = axial strain

ϵ_c = circumferential strain.

Since in a uniaxial strain experiment the pressure is one-third of the axial stress, the slope of the curve shown in Figure 2 is the bulk modulus. The calculated bulk sound velocity is then 4.67 km/s. Poisson's ratio was also directly calculated using the axial and circumferential strain measurements.

III. RESULTS

Table II shows in tabular form the Hugoniot points deduced from the data and one point measured in an experiment by Hauver in which both RHA and 4340 were shocked to high pressure with an explosively thrown steel plate. For the α or h.c.c. phase the shock velocity-particle velocity line is represented by the least squares equation $U = 4.67 + 1.44 u$ where U is the shock velocity and u the particle velocity. The α to ϵ or h.c.p. phase transition occurred at an average shock pressure of 13.2 GPa. The average dynamic elastic limit was 2.4 GPa. The measured Poisson's ratio was 0.288. This gives, according to Jones and Graham⁵ a hydrostatic transition pressure of 12.2 GPa.

⁵O. E. Jones and R. A. Graham, "Shear Strength Effects on Phase Transition Pressures" Determined from Shock-Compression Experiments", Symposium on the Accurate Characterization of the High Pressure Environment, U.S. Dept. of Commerce, National Bureau of Standards, Gaithersburg, MD., October 14-18, 1968.

The elastic limit measurements varied widely as did measurements by Butcher and Canon⁶ on this material. It is surprising and encouraging that their average value was the same, 2.41 GPa.

Figures 3 and 4 show the U-u plots for 4340 RC 54-55 steel compared to both RHA and iron. It can be seen that the α -phase of each material has practically the same slope but the intercept depends on the bulk sound velocity. The ϵ -phase of RHA and 4340 are the same within the experimental error.

ACKNOWLEDGEMENTS

The authors would like to thank George Hauver for his help with the experiments and especially for his explanations of the data analysis. We would like to thank R. Benck and D. Diberardo for the quasi-static measurements.

TABLE 1

CHEMICAL ANALYSIS OF 4340 STEEL

<u>ELEMENT</u>	<u>RESULTS 1</u>
Carbon	0.40; 0.39
Manganese	0.69
Phosphorus	0.005
Sulfur	0.014
Silicon	0.26
Nickel	1.65
Copper	0.15 - 0.25
Chromium	0.7 - 0.9
Vanadium	0.01
Molybdenum	0.2 - 0.3
Aluminum	0.02

*Dept of Army Materials Laboratory, Frankford Arsenal, 16 September 1976.

⁶D. M. Butcher and J. R. Canon, "Influence of Work-Hardening on the Dynamic Stress-Strain Curves of 4340 Steel", AIAA J., Vol. 2, No. 12, December 1964, pp 2174-9.

TABLE II
HUGONIOT DATA
1 - phase

$$\rho_0 = 7800 \text{ kg/M}^3$$

$$= 7.80 \text{ gm/c.c.}$$

TEST NO.	U km/sec	u km/sec	σ_c GPa	σ_{p1} GPa	σ_1 GPa
1	5.03	0.255	2.29	8.11	10.40
2	5.13	0.319	2.06	11.05	13.11 (a+e)
3	5.12	0.320	2.74	10.49	13.23 (a+e)
5	4.98	0.155	2.63	3.79	
6	5.11	0.320	2.33	10.81	13.14 (a+e)
			ave 2.41		ave (a+e) 13.16

c - phase

Key

	U	u	σ_2
3	2.97	0.498	17.67
6	4.69	0.840	33.39
SC554*	7.60	2.25	133.60

U - shock velocity
u - particle velocity
 σ_c - dynamic elastic limit
 σ_{p1} - 1-phase stress
 σ_1 - total stress in first plastic wave
 σ_2 - total stress in second plastic wave
 ρ_0 - density

*Hauver




FIGURE 2: Pressure vs. Volume Compression for 4340 Steel. The pressure is taken as $-\sigma/3$ where σ is the load divided by the original area of the specimens.

α - PHASE HUGONIOT




FIGURE 3: Comparison of α-Phase Hugoniot Results for Iron, 4340 Steel, and RHA.




FIGURE 4: Comparison of ϵ -Phase Hugoniot Results for Iron, 4340 Steel, and RHA.

REFERENCES

1. G. Hauver, "The Alpha-Phase Hugoniot of Rolled Homogeneous Armor". Ballistic Research Laboratory Memorandum Report No. 2651, August 1976. (AD #B012871L)
2. G. Hauver and A. Melani, "The Epsilon-Phase Hugoniot of Rolled Homogeneous Armor", Memorandum Report ARBRL-MR-02909, March 1979. (AD #A096107)
3. L. M. Barker, "Alpha-Phase Hugoniot of Iron", J. Appl. Phys., Vol. 46, No. 6, June 1975, pp 2544-7.
4. L. M. Barker and R. E. Hollenbach, "Laser Interferometer for Measuring High Velocities of Any Reflecting Surface", J. Appl. Phys., Vol. 43, No. 11, November 1972, pp 4669-75.
5. O. E. Jones and R. A. Graham, "Shear Strength Effects on Phase Transition "Pressures" Determined from Shock-Compression Experiments", Symposium on the Accurate Characterization of the High Pressure Environment, U.S. Dept. of Commerce, National Bureau of Standards, Gaithersburg, MD., October 14-18, 1968.
6. B. M. Butcher and J. R. Canon, "Influence of Work-Hardening on the Dynamic Stress-Strain Curves of 4340 Steel", AIAA J., Vol. 2, No. 12, December 1964, pp 2174-9.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Documentation Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703
1	Deputy Assistant Secretary of the Army (R&D) Department of the Army Washington, DC 20310	1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333	2	Commander US Army Missile Research and Development Command ATTN: DRDMI-R DRDMI-YDL Redstone Arsenal, AL 35809
2	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS Dover, NJ 07801	1	Commander US Army Tank Automotive Rsch and Development Command ATTN: DRDTA-UL Warren, MI 48090
1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range NM 88002
1	Commander US Army Aviation Research and Development Command ATTN: DRSAR-E P. O. Box 209 St. Louis, MO 63166	5	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL DRXMR-H, Mr. J. Dignan DRXMR-H, Dr. D. Dandekar DRXMR-T, Dr. J. Mescall DRXMR-H, Dr. S. C. Chou Watertown, MA 02172
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Research Office P. O. Box 12211 Research Triangle Park NC 27709	3	SRI International ATTN: Dr. G. R. Abrahamson Dr. D. Curran Dr. L. Seaman 333 Ravenswood Avenue Menlo Park, CA 94025
1	Commander US Military Academy ATTN: Library West Point, NY 10996	1	Drexel Institute of Technology Wave Propagation Research Center ATTN: Prof. P. C. Chou 32nd and Chestnut Streets Philadelphia, PA 19104
3	Commander Naval Surface Weapons Center ATTN: Mr. W. H. Holt Mr. W. Mock, Jr. DX-21, Lib Dahlgren, VA 22445	2	University of California Los Alamos Scientific Lab. ATTN: Tech Lib GMX-6, Dr. J. W. Taylor P. O. Box 1663 Los Alamos, NM 87545
2	Commander Naval Surface Weapons Center ATTN: Dr. J. W. Forbes Tech Lib Silver Spring, MD 20910	1	Washington State University Department of Physics ATTN: Prof. G. E. Duvall Pullman, WA 99163
1	Commander Naval Research Laboratory ATTN: Code 2020, Tech Lib Washington, DC 20375		<u>Aberdeen Proving Ground</u> Dir, USAMSAA ATTN: Dr. J. Sperrazza DRXS-MP, H. Cohen Cdr, USATECOM ATTN: DRSTE-TO-F Dir, Wpns Sys Concepts Team, Bldg. E3516, EA ATTN: DRDAR-ACW
1	AFWL (Tech Lib) Kirtland AFB, NM 87117		
1	Director Lawrence Livermore Laboratory ATTN: Dr. M. van Thiel, L-64 P. O. Box 808 Livermore, CA 94550		
3	Sandia Laboratories ATTN: Tech Lib Dr. W. Herrmann Dr. L. D. Bertholf Albuquerque, NM 87115		

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet and return it to Director, US Army Ballistic Research Laboratory, ARRADCGM, ATTN: DRDAR-TSB, Aberdeen Proving Ground, Maryland 21005. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____

2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

