

UNCLASSIFIED

AD NUMBER
ADA078549
CLASSIFICATION CHANGES
TO: unclassified
FROM: secret
LIMITATION CHANGES
TO: Approved for public release, distribution unlimited
FROM: Controlling DoD Organization: Air Force Special Weapon Project, PO Box 2610, Washington, DC
AUTHORITY
AEC, per ltr, document marking, 27 Dec 1979; AEC, per ltr, document marking, 27 Dec 1979

THIS PAGE IS UNCLASSIFIED

AD1078549


PHOTOGRAPH THIS SHEET

ADA 078549

DTIC ACCESSION NUMBER



LEVEL



INVENTORY

REC

WT-519

DOCUMENT IDENTIFICATION

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

DISTRIBUTION STATEMENT

ACCESSION FOR	
NTIS	GRA&I
DTIC	TAB
UNANNOUNCED	
JUSTIFICATION	
Per Hq. on file	
BY	
DISTRIBUTION	
AVAILABILITY CODES	
DIST	AVAIL AND/OR SPECIAL
A	

DDC
RECEIVED
DEC 27 1979
D

DATE ACCESSIONED

DISTRIBUTION STAMP

9 12 10 1979

DATE RECEIVED IN DTIC

PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-DDA-2

UNCLASSIFIED

This document consists of 95 plus 4 pages
No. 104 of 300 copies, Series A

OPERATION TUMBLER

Project 1.9

PRE-SHOCK DUST

REPORT TO THE TEST DIRECTOR

by

E. H. Bouton
C. S. Elder
J. S. Kemper
E. F. Wilsey

October 1952

Chemical Corps
Chemical and Radiological Laboratories
Army Chemical Center

UNCLASSIFIED

Reproduced Direct from Manuscript Copy by
ALC Technical Information Service
Oak Ridge, Tennessee

Inquiries relative to this report may be made to

Chief, Air Forces Special Weapon Project
P. O. Box 2610
Washington, D. C.

ABSTRACT

The objective of Project 1.9 was to determine the concentration and the particle size distribution of the pre-shock dust generated from the surface of the ground by air currents resulting from the incidence of thermal radiation on the surface of the ground.

Cascade impactors and filter samplers were used to sample pre-shock dust for the brief period of time between the time of detonation and the arrival of the shock wave at the station.

The following conclusions are drawn:

1. The presence of pre-shock dust in concentration of from ten to several hundred times background has been established.
2. There was no significant difference between the particle size distribution of pre-shock dust and background dust.
3. Little variation in dust concentrations from shot to shot was shown.

~~SECRET~~

ACKNOWLEDGEMENTS

The project officer wishes to express his appreciation to the personnel in Radiological Division, Chemical and Radiological Laboratories, who assisted in the successful prosecution of this project.

Acknowledgement is also made for the services of M. C. Armacost, L. Totaro, and Pfc B. Jackson for their help in the design of towers and equipment; J. D. Wilcox, W. R. Van Antwerp, Pfc H. N. Beck, and Pfc D. L. Rigotti for their assistance in preparing and analyzing the cascade impactor and molecular filter samples.

Much of the draft copy of this report as submitted by the authors has been revised by Dr. F. A. Hedman of the Radiological Division Publication Writers Group of the Chemical Corps Chemical and Radiological Laboratories.

PRECEDING PAGE BLANK

~~SECRET~~

UNCLASSIFIED

CONTENTS

ABSTRACT	3
ACKNOWLEDGEMENTS	5
ILLUSTRATIONS	8
TABLES	11
CHAPTER 1 INTRODUCTION	13
1.1 Objective	13
1.2 Background	13
1.3 Theory	13
1.3.1 Cascade Impactor	13
1.3.2 The Molecular Filter	14
1.3.3 Factors Influencing the Use of the Molecular Filter and the Cascade Impactor	14
CHAPTER 2 INSTRUMENTATION	16
2.1 Design Requirements	16
2.2 Description	16
2.2.1 Cascade Impactor Sampler	16
2.2.2 Filter Sampler	16
2.2.3 Control Circuit	17
2.3 Station Equipment	22
2.4 Flow Calibration	22
CHAPTER 3 OPERATIONS	25
3.1 Detonation Details	25
3.2 Installation of Sampling Equipment	25
3.3 Removal and Packing of Sampling Equipment	25
3.4 Analysis at Army Chemical Center	26
3.4.1 Cascade Impactor Analysis	26
3.4.2 Molecular Filter Analysis	26
CHAPTER 4 RESULTS	28
4.1 Particle Size and Number Distribution	28
4.1.1 Cascade Impactors	28
4.1.2 Molecular Filters	29
4.1.3 Correlation of Cascade Impactor and Molecular Filter Data	29
4.1.4 External Factors Affecting Results	29

~~SECRET~~

4.2 Ranges to Stations	31
CHAPTER 5 DISCUSSION	32
5.1 Mechanism of Sampling	32
5.2 Difference in Results	32
5.3 Results	32
CHAPTER 6 CONCLUSIONS AND RECOMMENDATIONS	33
6.1 Conclusions	33
6.2 Recommendations	33
APPENDIX A PARTICLE DISTRIBUTION DATA	34
APPENDIX B DAMAGE TO STATIONS	84
B.1 Effects of Shots	84
B.2 Station 7-201	84
B.3 Station 7-202	84
B.4 Station 7-204	84
APPENDIX C DETAILS OF CASCADE IMPACTOR ASSEMBLY	87
BIBLIOGRAPHY	88

ILLUSTRATIONS

CHAPTER 1 INTRODUCTION	
1.1 Expanded View of Cascade Impactor Jets	15
CHAPTER 2 INSTRUMENTATION	
2.1 Cascade Impactor Sampler: left to right the Solenoid Valve, E12 Aerosol Filter, and connecting clamp with the Impactor	17
2.2 Solenoid Valve Open	18
2.3 The Filter Sampler, Showing the Sheet of Molecular Filter Material, Filter Holder, E12 Aerosol Canister, and Solenoid Valve	19
2.4 Schematic Diagram of the Control Circuit	20
2.5 Installation at Frenchman Flat F-202. The blast-closure microswitches are in front. The ground and 10ft. level boxes are to the left of the tower	21
2.6 F-202 Ground Level. View from rear of box	23
2.7 Station 7-202. View of underground pit	23
2.8 Station 7-202 in process of construction before Shot 2	24

~~SECRET~~

CHAPTER 3 TEST SITE OPERATIONS

3.1 Shot 4, Station 7-204, Ground Level Cascade Impactor and Molecular Filter Photomicrographs	27
--	----

APPENDIX A PARTICLE SIZE DISTRIBUTION DATA

A.1 Sample Cascade Impactor Calculation Sheet	35
A.2 Shots 1 and 2, Summary Sheet of Cascade Impactor Data, Individual Jet Sample Parameters	36
A.3 Shots 3 and 4, Summary Sheet of Cascade Impactor Data, Individual Jet Sample Parameters	37
A.4 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station F-202-J	38
A.5 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station F-204-J	39
A.6 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-202-U	40
A.7 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-202-L	41
A.8 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-204-U	42
A.9 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-204-L	43
A.10 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-201-U	44
A.11 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-201-L	45
A.12 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-202-U	46
A.13 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-204-U	47
A.14 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-204-L	48
A.15 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station D-204-U	49
A.16 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station D-204-L	50
A.17 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station F-202-U	51
A.18 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station F-204-U	52
A.19 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-202-U	53
A.20 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-202-L	54
A.21 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-204-U	55

UNCLASSIFIED

A.22 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-204-L	56
A.23 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-201-U	57
A.24 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-201-L	58
A.25 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-202-U	59
A.26 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-204-U	60
A.27 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-204-L	61
A.28 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station D-204-U	62
A.29 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station D-204-L	63
A.30 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station F-202-U	64
A.31 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station F-202-L	65
A.32 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station F-204-U	66
A.33 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station F-204-L	67
A.34 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station B-201-U	68
A.35 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station B-201-L	69
A.36 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station B-202-U	70
A.37 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station B-202-L	71
A.38 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station B-204-U	72
A.39 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station B-204-L	73
A.40 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station C-201-U	74
A.41 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station C-201-L	75
A.42 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station C-202-U	76
A.43 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station C-202-L	77
A.44 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station C-204-U	78
A.45 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station C-204-L	79
A.46 Pre-shock Dust Particle Size Distribution, Molecular Filter, Station D-202-L	80

A.47	Pre-shock Dust Particle Size Distribution, Molecular Filter, Station D-204-U	81
A.48	Pre-shock Dust Particle Size Distribution, Molecular Filter, Station D-204-L	82
A.49	Background Dust Particle Size Distribution, Molecular Filters, Station D-204-B	83

APPENDIX B DAMAGE TO STATIONS

B.1	Station 7-201 After Shot 4	85
B.2	Station 7-201 Blast Closure Microswitches After Shot 4	85
B.3	Station 7-202 Tower and Sampling Equipment After Shot 4	86
B.4	Station 7-204 After Shot 4	86

APPENDIX C DETAILS OF CASCADE IMPACTOR ASSEMBLY

C.1	Cascade Impactor Plastic Slide Assembly	87
-----	---	----

TABLES

CHAPTER 4 RESULTS

4.1	Cascade Impactor and Molecular Filter Concentration Data	30
4.2	Ranges to Stations	31

APPENDIX A PARTICLE DISTRIBUTION DATA

A.1	Particle Concentration from Cascade Impactor.	34
-----	---	----

CHAPTER 1

INTRODUCTION

1.1 OBJECTIVE

The primary objective of Operation TUMBLER was to determine the extent of the loss of theoretical peak overpressure measured on the ground from an atomic bomb detonation and to develop scaling laws for determining the optimum height for such detonations.

The objective of Project 1.9 was to determine the concentration and the particle size distribution of the pre-shock dust generated by the action of thermal radiation on the surface of the ground.

These data will be applied to the determination of the effects of thermal radiation on the loss of theoretical overpressure.

1.2 BACKGROUND

Overpressure results obtained at Operation BUSTER were $1/2$ to $1/3$ of the predicted values. It has been postulated that decay of the air shock wave is due to so-called mechanical and/or thermal effects. The loss of overpressure might be the result of the retarding effect of dust raised from the surface of the ground by thermal radiation. The resulting dust may absorb additional thermal energy and tend to magnify the loss of overpressure.

1.3 THEORY

1.3.1 Cascade Impactor

To determine the particle size distribution of any heterogeneous cloud a size-graded sampling method is desirable. Also to be desired is a minimum amount of physical strain on the particles as they are collected. The cascade impactor, first developed by May¹ is particularly suited to these requirements. The instrument used in these tests was a five-stage instrument designed at the Army Chemical Center ^{2,3,4,5} (Fig. 1.1). It deposits particles in five different size groups in a manner suitable for analysis with the light and/or the electron microscope. The larger particles, which are most likely to shatter, are collected at low velocities. The main disadvantage of the impactor is that it is not an absolute instrument, being that below a certain particle size, the probability of collection decreases in a rather complex manner.

1.3.2 The Molecular Filter

Molecular filters (MF) consist of a loose network of cross-linked molecules of cellulose ester polymers, which appear as bright, white, smooth sheets. Detailed information may be found in Goetz' report.⁶

The effective pore size of an MF can be controlled during the manufacturing process. The pore size can be quite accurately controlled and varied over the range of 1 to 5,000 millimicrons. The pore openings on the influent side are smaller than on the effluent side so that there is a definite "screening action" rather than a "depth action" during filtration.

The cellulose esters used have high dielectric constants. Due to the large difference between the dielectric constants of the esters and air, passage of air through the filter gives a strong and lasting electrostatic charge to the filter. The retention of fine particles on the surface of a MF is believed to be due to these charges.

The molecular filter becomes almost completely transparent when placed in a clear liquid of refractive index of 1.49. The liquid used must not act as a solvent or a swelling agent. Particle deposits on the MF may then be examined optically. A porous plate or a wire mesh screen is necessary to support the MF during filtering operations.

1.3.3 Factors Influencing the Use of the Molecular Filter and the Cascade Impactor

The molecular filter in the sampler allowed a flow rate of 106 liters per minute to pass through a 100 cm² circular sampling area. However, the MF is fragile and it is not practical to analyze particles smaller than one micron with an optical system.

The cascade impactor separates particles into five size groupings which range from 100 microns to 0.1 micron. These groupings may be analyzed with optical and electron microscopes. The instrument however, has a flow rate of about 12.5 liters per minute, which is a disadvantage because of the short sampling time available on this project.




Fig. 1.1 Expanded View of Cascade Impactor Jets

CHAPTER 2

INSTRUMENTATION

2.1 DESIGN REQUIREMENTS

The sampling apparatus was designed to meet the following specifications:

1. A representative dust sample must be obtained.
2. The period of sampling must be limited to the interval between the time of detonation and the time of arrival of the shock wave.
3. The maximum percentage of the available cloud sample must go through the sampling apparatus.
4. The samplers must be easily removable from their mountings in order to minimize exposure of personnel to radiation.

2.2 DESCRIPTION

2.2.1 Cascade Impactor Sampler

The cascade impactor was connected by use of a tee to a solenoid valve and a filter (Chemical Corps Canister, Aerosol, E-12). The connecting pipe fittings were selected so as to have a minimum volume (see Sec. 2.1). A clamp was used to hold the cascade impactor inlet securely against a gasket (Fig. 2.1).

The valve was a Barksdale "Shear-seal" slide-type, quick-closing valve, spring loaded to the closed position. This valve allowed an essentially straight-line flow of dust samples to the samplers; the minimum flow passage diameter was 25/32 in., (Fig. 2.2).

The filter contains Chemical Corps Type 6 paper, which has a mean efficiency of 99.8 per cent when filtering the gross particulate contaminant existing in an atomic bomb cloud a few minutes after detonation.⁷ Air cleaned by this filter swept the remaining dust samples out of the intake sampling line and on to the sampling surface. When the vacuum pump was operating with the solenoid valve closed, air, after passing through the filter, was drawn through the sampler. When the solenoid valve opened, all of the air was drawn through the valve inlet, because of the high resistance to air flow offered by the filter.

2.2.2 Filter Sampler

When using the molecular filter material, the filter sampler replaced the cascade impactor in the assembly shown in Fig. 2.1. The

~~SECRET~~




Fig.2.1 Cascade Impactor Sampler: Left to Right the Solenoid Valve, Filter, Connecting Clamp With the Impactor

effluent side of the sampler was connected to a vacuum pump (capacity is 4.8 cfm, at 20 inches of mercury). See Appendix C.

The molecular filter material used (Type HA, "Millipore") was made by the Lovell Chemical Co., Watertown, Mass., using the Goetz process.⁶ This filter material was placed in a filter holder having "back-up" screens to support both sides of the filters during use. The sampling surface was a circular area of 100 sq. cm. (See Fig. 2.3.)

2.2.3 Control Circuit

The 110 volt power available at each sampling pit was brought in from a central power source by underground cables. The circuit (Fig. 2.4) was used to obtain properly controlled operation of the sampling equipment during the time interval between the arrival of the thermal wave and the arrival of the shock wave at each station. The

~~SECRET~~

~~RESTRICTED DATA~~




Fig. 2.2 Solenoid Valve Open. There Is No Obstruction to "Straight Through" Flow




Fig. 2.3 The Filter Sampler, Aerosol Canister, and Solenoid Valve (A sheet of Molecular Filter Material is shown in the foreground)

coils of relays E_1 and E_2 of equipment supplied by Edgerton, Germeshausen, and Grier were activated by the arrival at the station of an electrical impulse.

The electrical impulse received by coil E_1 at H-15 second closed switch E_1 , operating relay J_1 which closed switches J_{11} and J_{12} , thus starting the vacuum pump motors. A second signal was received by coil E_2 at H-2.5 seconds. This time interval of 12.5 seconds permitted the motors to attain rated speed conditions and attain rated vacuum on the samplers. Air was drawn through the aerosol canister and sampling lines during this period but since the valves were closed, the sample collecting devices received no particulate matter.




Fig. 2.4 Schematic Diagram of the Control Circuit

The electrical impulse at H-2.5 seconds energized coil (E_2), closing switch (E_2), and energizing relay coil (J_3) which closed switches (J_{31}) and (J_{32}), thus opening the solenoid operated valves. This was the beginning of the sampling period which was recorded by the clock (C). This clock, having one second sweep hand, could be read to one thousandth of a second.

The blast-closure device (Fig. 2.5) was located a short distance toward ground zero from the sampling station. The exact location of this device was chosen so that the sampling would stop immediately prior to the arrival of the shock wave at the sampling ports.

The shock wave acting on the blast-closure device mechanically closed the micro switch, thus energizing the three parallel relay coils (J_2 , the thermal delay relay, and L_2). Electrically locking relay J_2 insured operation after the micro switch had closed. Relay L_2 opened switch L_2 , thus de-energizing the solenoid valves, stopping the clock, and ending the collection of samples. However, the thermal delay relay kept the vacuum pump in operation until the part of the sample still in the sampling lines had been transferred to the collecting surface. After a delay of seven seconds, the entire circuit was de-energized.




Fig. 2.5 Installation at Frenchman Flat F-203. The blast-closure microswitches are in the foreground. The ground and 10-ft. level boxes are to the left.

2.3 STATION EQUIPMENT

For Shot 1 at Frenchman Flat, identical installations were made at ground and 10 ft. levels at stations F-202 and F-204. The samplers were mounted inside metal boxes (Fig. 2.6) so that samples entered through pipe nipples located in the box side six inches above the box bottom. The ground level samples were obtained by samplers in boxes which were bolted onto a concrete base, while the sample at the 10 ft. level was taken directly above the ground level sample (Fig. 2.8).

A wood-lined underground pit (Fig. 2.7), 10 ft. to the rear of the ground level sampler, contained the vacuum pumps, relays, and timing equipment.

Area 7 was used for Shots 2, 3, and 4. Three stations, 7-201, 7-202, and 7-204, were instrumented in this area. However, on Shot 3, station 7-201 was used for background measurements. At station 7-204, on Shot 4, an extra filter sampler was installed in the ground level box for background measurements. The stations in this area were 215 ft. east of the corresponding stations on the main blast line.

A box at ground level in area 7 was mounted as at Frenchman Flat. However, the sampler collecting the 10 ft. level sample was in a box on top of a 7-ft. tower of the type used by the Chemical Corps in Operation JANGLE. The tower was mounted on a foundation extending one foot above ground level (Fig. 2.8).

Wires and tubing to the boxes were enclosed in iron pipe. All boxes were covered with aluminum sheeting to reflect part of the thermal wave.

2.4 FLOW CALIBRATION

The samplers (Molecular Filter and Cascade Impactor) were calibrated in the field, using a dry test meter.

UNCLASSIFIED




Fig. 2.6 F-202 Ground Level. View From Rear of Box




Fig. 2.7 Station 7-202. View of Underground Pit

UNCLASSIFIED

[REDACTED]




Fig. 2.8 Station 7-202 in Process of Construction Before Shot 2

[REDACTED]

[REDACTED]

[REDACTED]

CHAPTER 3

TEST SITE OPERATIONS

3.1 DETONATION DETAILS

This series of tests was run as a portion of the study of the four atomic bomb detonations comprising Operation TUMBLER. A 1.05 kiloton bomb was detonated at 793 ft. elevation, at 0900 hrs., 1 April 1952; a 1.15 kiloton bomb at 1109 ft., at 0930 hrs., 15 April 1952; a 30 kiloton bomb at 3447 ft., at 0930 hrs., 22 April 1952; and a 19.6 kiloton bomb at 1040 ft., at 0830 hrs., 1 May 1952. All times given are Pacific Standard Time.

3.2 INSTALLATION OF SAMPLING EQUIPMENT

During the night before Shot 1, the ground around the blast line stations was thoroughly watered down. Particular care had been taken to see that ground was smoothed and hardened around the ground level boxes. This was not done on the last three shots in order that the area would be in approximately the same condition as it was during Operation BUSTER. The ground was mostly bare, ungraded, and loosely packed.

The cascade impactors used in this project were cleaned, assembled, and loaded with the plastic slides and electron microscope films at Army Chemical Center before shipment to the Nevada Proving Grounds. The ends of the cascade impactors were sealed to prevent contamination.

The filter samplers were loaded with the molecular filters at the site. The intakes and exhausts of all sampling equipment were sealed until they were actually mounted in the station boxes.

No impactors or filter samplers were actually installed at the stations until all timing signal "dry runs" had been completed.

After the first shot, a large amount of grease was noticed in the interior of the valves. Before each succeeding shot, the entire sampling train was cleaned with carbon tetrachloride or acetone. The inlets of the valves were then kept sealed until shortly before use.

Before each shot, the underground pits were covered with sandbags and dirt.

3.3 REMOVAL AND PACKING OF SAMPLING EQUIPMENT

The equipment was removed from the sampling stations as soon as

~~SECRET~~

permitted after each shot. Sampler intakes and exhausts were immediately sealed to prevent contamination.

At Yucca Flat Airstrip, the cascade impactors were placed in shipping boxes. Each molecular filter used with Shot 1 was put into a vinyl bag before being placed in a shipping box. All other used molecular filters were mounted on a rigid plastic plate, influent side out, and then packed and sealed in a dust free box. All operations in which the sampling surfaces were exposed to the atmosphere were performed in the closed cab of a truck. Within four hours after removal from the sampling station, each sample was placed aboard a courier plane and rushed to Army Chemical Center for study.

3.4 ANALYSIS AT ARMY CHEMICAL CENTER

3.4.1 Cascade Impactor Analysis

When exposed impactors were received from the test site they were monitored for radiation, and if safe were unloaded. The impaction areas of all jets were measured using scattered light. The first and second jet samples were examined, projected, and counted at 1,000X using a light microscope. The third and fourth jet samples were photographed using the electron microscope; the electron micrographs were then projected and counted at 10,000X. The fifth jet samples were photographed using the electron microscope; the electron micrographs were projected and counted at 50,000X. Heavy oil-like deposits and oversampling, combined with a large concentration of fibres, made the analysis of a few samples impossible.

3.4.2 Molecular Filter Analysis

One half of each filter was mounted on a clean, polished glass plate. Several drops of acetone were placed, at random spots, on the filter dissolving small areas of the filter. This treatment left the particulate material in an ideal form for microscopic examination using transmitted light. With the use of the light microscope projection apparatus, the areas cleared by acetone were then projected at 1,000X and counted. As in the case of the cascade impactor samples, fibers were also noted on the molecular filters; however, in no case was the fiber concentration great enough to hinder analysis.

Microphotographs of the five stages of a representative cascade impactor and a molecular filter are shown in Figure 3.1. The molecular filter and the first and second impactor stages were magnified 280X, the third and fourth stages 2,800X, and the fifth 7,500X. Asbestos fibers are seen in stages 2, 3, 4, and 5. The foggy background on the 5th stage is due to oil deposits. The porelike background on the molecular filter microphotograph is characteristic of the filter after the addition of acetone.



1st Stage




2nd Stage



3rd Stage



4th Stage



5th Stage



Molecular Filter

Fig. 3.1 Shot 4, Station 7-204, Ground Level Cascade Impactor and Molecular Filter Photomicrographs

~~SECRET~~
CHAPTER 4

RESULTS

4.1 PARTICLE SIZE AND NUMBER DISTRIBUTION

4.1.1 Cascade Impactors

The cascade impactor samples were analyzed for particle size data only. Figure A.1 is a sample calculation sheet for a complete cascade impactor sample. The number of particles in each class interval on each jet, corrected by the jet area factor, has been entered in the appropriate position in the first five columns. The total number of particles in each class interval was then obtained by adding the entries in each row. The remainder of the sheet consists of the calculations leading to cumulative per cent undersize by number, by surface, and by mass. The average diameter, D_{av} , was calculated from the size and the total number columns. Previous to the analysis of the complete impactor sample, each individual jet was analyzed in the manner just described. The number, median diameter, surface median diameter, mass median diameter, geometric standard deviation, average diameter, total number, summation of median diameter squared, and summation of median diameter cubed for each jet and each impactor are shown in Figures A.2 and A.3. Log-probability plots were made for each complete impactor sample. These plots are shown in Figures A.4 through A.16. Plots of particle size distribution for each impactor, on log-linear paper, are shown in Figures A.17 through A.29. The mean size of each range, where a range of one half to twice the stated size was used, has been plotted against the average number/cc of air in the range. Table 4.1 lists the particle concentration of each impactor; how this concentration was determined is shown in Table A.1.

In general, calculations were carried out to four significant figures and the final values were then reduced to three significant figures. The use of two significant figures would be more in keeping with the accuracies expected. The impaction area measurements have a possible error of $\pm 10\%$ due to their imperfect definition; and, the possible error arising from misclassifying a particle by one class interval is also about $\pm 10\%$. Since a large number of particles (approximately 500/jet or 2,500 impactions) were measured, it is probable that values based on calculations (average diameter, total number, etc.) are accurate to $\pm 10\%$. The median diameters and the geometric standard deviation for each sample were obtained from lines drawn to represent the trend of the data.

4.1.2 Molecular Filters

The number of particles with diameters of one micron or more per square centimeter of molecular filter was determined and the number of such particles per cubic centimeter of air calculated. The results are shown in Table 4.1. Particles below one micron in diameter were not counted because this size is near the limit of resolution of the light microscope and therefore difficult to examine. Figures A.30 through A.49 are graphs showing the number of particles per cubic centimeter of air as a function of particle size.

4.1.3 Correlation of Cascade Impactor and Molecular Filter Data

Dust concentration on filter samplers and cascade impactors are in fair agreement. For example, at Station F-204-U, 6.2 per cent of the impactor particles were greater than one micron in diameter. From Table 4.1, 7.65×10^4 particles/cc of air greater than one micron were counted on the filter, giving $7.65 \times 10^4 \div 0.062 = 1.2 \times 10^6$ particles/cc of air on the filter. The impactor results from this station are 1.72×10^6 particles/cc of air.

4.1.4 External Factors Affecting Results

Throughout the operation, cascade impactor samples were more easily spoiled by foreign material than were the molecular filter samples.

Cascade impactor samples for Shot 1 at the ground level of both stations were rendered useless by an oily mist. It was suspected that this oil was from the cables supporting the 50-ft. towers. During succeeding shots, these cables were wrapped with aluminum foil to prevent vaporization of oil. However, both of the impactors at station 7-201 collected oil during Shot 2.

Carbon particles, mixed with the sample obtained during Shot 3 by the station 7-202 impactor at ground level, made analysis impossible. The carbon probably came from burning sagebrush fragments.

The shock wave of Shot 4 destroyed the impactor samples at station 7-202 and station 7-204 and also the filter samplers at the 10 ft. level. The filter sampler at the station 7-202 ground level collected a large amount of dust.

Fibers were found on several cascade impactor slides, thereby making analysis of the slides difficult. These fibers were found to be crocidolite asbestos fibers which are a component of the filter material used in the Chemical Corps Aerosol Canister, E-12.

UNCLASSIFIED

TABLE 4.1

Cascade Impactor and Molecular Filter Concentration Data

Station	Particles Per cc (by impactor)	Particles Per cc (by filter)	Percentage of Particles Over 1 Micron (by impactor)	Total Particles on Filter	Condition of MF when Removed From Holder
F-202U	1.06×10^6	3.52×10^4	10.5	3.4×10^5	Traces of loose dust
F-202L	oil deposit	4.19×10^4			
F-204U	1.72×10^5	7.65×10^4	6.2	1.2×10^6	Grayish
F-204L	oil deposit	2.44×10^4			
B-201U	oil deposit	1.05×10^4			Traces of loose dust
B-201L	oil deposit	3.15×10^4			
B-202U	1.41×10^5	1.02×10^4	3.3	3.1×10^5	Traces of loose sand
B-202L	3.57×10^5	9.74×10^3	3.5	2.1×10^5	
B-204U	2.86×10^4	2.97×10^3	5.3	5.6×10^4	Traces of loose sand
B-204L	2.95×10^4	2.60×10^3	3.8	6.8×10^4	
C-201U	$2.53 \times 10^3*$	$2.12 \times 10^2*$	3.4	$6.2 \times 10^3*$	Traces of loose sand
C-201L	$1.65 \times 10^3*$	$2.10 \times 10^2*$	2.0	$1.1 \times 10^4*$	
C-202U	4.10×10^4	1.02×10^4	5.0	2.0×10^5	Traces of loose sand
C-202L	carbon deposits	1.10×10^5			
C-204U	9.34×10^4	2.77×10^3	1.1	2.5×10^5	Traces of loose sand
C-204L	9.07×10^4	5.22×10^4	7.2	7.2×10^5	
D-201U	Smashed	Blast			Burned
D-201L	Full of Dirt	Blast			Burned
D-202U	Smashed	Blast			Broken
D-202L	Damaged	8.31×10^6			Scorched
D-204U	1.19×10^5	3.91×10^3	2.4	1.6×10^5	Loose sand
D-204L	2.22×10^5	2.49×10^4	4.0	6.2×10^5	
D-204BG	Not used	$1.20 \times 10^3*$	4.0	3.0×10^4	

U refers to 10 ft. level stations

L refers to ground level stations

BG or * refers to background

F, B, C, and D refer to Shots 1 (Frenchman Flat), 2, 3, and 4, respectively.

~~CONFIDENTIAL~~

4.2 Ranges to Stations

The nominal, ground and slant ranges to each station are shown in Table 4.2.

TABLE 4.2

Ranges to Stations

Station	Nominal Ground Range Ft	Actual Ground Range Ft	Actual Slant Range Ft
F-202J	500	580	980
F-202L	500	580	980
F-204U	1000	1070	1330
F-204L	1000	1070	1340
B-201U	750	830	1270
B-201L	750	830	1270
B-202U	1500	1380	1770
B-202L	1500	1380	1770
B-204U	3000	2890	3100
B-204L	3000	2890	3100
C-201U	750	860	3500
C-201L	750	860	3500
C-202U	1500	1400	3710
C-202L	1500	1400	3720
C-204U	3000	2900	4500
C-204L	3000	2900	4510
D-201U	750	680	1240
D-201L	750	680	1250
D-202U	1500	1390	1730
D-202L	1500	1390	1740
D-204U	3000	2870	3050
D-204L	3000	2870	3050
D-204BG	3000	2870	3050

U refers to 10 ft. level stations

L refers to ground level stations

BG or * refers to background

F, B, C, and D refer to Shots 1 (Frenchman Flat), 2, 3, and 4, respectively.

UNCLASSIFIED

CHAPTER 5

DISCUSSION

5.1 MECHANISM OF SAMPLING

The technique of sampling the pre-shock dust using sampling periods of the order of one second was entirely successful. All sampling stations operated as planned.

5.2 DIFFERENCE IN RESULTS

The number of particles per cubic centimeter of air as determined by the impactor analysis was usually one-half to one-third of the estimated number of particles on the corresponding filter sampler. The disparity in the results may be due to non-isokinetic sampling, the effect of which cannot be estimated.

5.3 RESULTS

The data show the order of magnitude of the pre-shock dust concentration at ground and 10 feet levels and also background or normal dust concentrations. No information was obtained on the particle concentration at heights greater than 10 ft. above the ground; consequently no estimate could be made of the total number of particles raised by the thermal wave.

Table 4.1 shows that the pre-shock dust concentrations are generally ten to several hundred times the background or normal dust concentrations. As an example, for Shot 3, the pre-shock dust concentrations as determined from filter samples range from a minimum of 2.77×10^3 to a maximum of 1.1×10^5 particles/cc while the background concentrations are 2.1×10^2 . The ratios of pre-shock to background dust concentrations for these stations range from approximately 10 to 500.

UNCLASSIFIED

CHAPTER 6

CONCLUSIONS AND RECOMMENDATIONS

6.1 CONCLUSIONS

The presence of pre-shock dust with concentrations of from ten to several hundred times background or normal dust concentration has been established. The depth of the dust layer extends to at least 10 ft. above the ground surface. Dust concentrations decreased slightly between stations 7-202 and 7-204 at both sampling levels. Little variation of dust concentrations from shot to shot was shown.

Although the soil moisture content was usually abnormally high, dust concentrations several hundred times background were obtained. This was particularly true for Shot 4. The ground was thoroughly soaked from rainfall and a heavy dew, and yet, as much dust was produced at station 7-204 as on Shot 3. However, the thermal radiation was higher on Shot 4 than on any other shot.

There was no significant difference between the particle size distribution of pre-shock dust and background dust. The pre-shock dust particles appeared to be similar to the background particles although on some samples from Shots 3 and 4 there appeared to be traces of transparent, spherical particles. These were probably particles of fused sand.

6.2 RECOMMENDATIONS

If analysis of the blast phenomena indicates a need for the data, improved techniques should be developed to sample pre-shock dust on future atomic weapons tests. In order to determine the depth of the dust layer, samples should be collected at several heights ranging from zero to considerably more than 10 ft. above the ground.

UNCLASSIFIED

APPENDIX A

PARTICLE DISTRIBUTION DATA

TABLE A.1

Particle Concentration From Cascade Impactors

Station	Sampling Time (Sec) ***	Flow Rate cc/sec	Sample Volume cc*	Total Particles On Impactor	Particles Per cc**
F-202U	0.45	215	19	2.90×10^7	1.06×10^6
F-202L	0.48	223			
F-204U	0.72	208	72	1.24×10^7	1.72×10^5
F-204L	0.72	223			
B-201U	0.34	203			
B-201L	0.32	210			
B-202U	0.64	223	65	9.14×10^3	1.41×10^5
B-202L	0.65	217	63	2.25×10^7	3.57×10^5
B-204U	1.70	227	308	8.80×10^6	2.86×10^4
B-204L	1.71	210	281	8.29×10^6	2.95×10^4
C-201U	12.5	208	2522	6.38×10^6	2.53×10^3
C-201L	12.5	210	2522	4.20×10^6	1.65×10^3
C-202U	1.47	208	228	9.35×10^6	4.10×10^4
C-202L	1.46	215			
C-204U	2.05	218	369	2.45×10^7	9.34×10^4
C-204L	2.04	202	334	3.09×10^7	9.07×10^4
D-201U					
D-201L					
D-202U	0.03				
D-202L	0.04				
D-204U	0.89	227	124	1.47×10^7	1.19×10^5
D-204L	0.89	210	109	2.42×10^7	2.22×10^5

* This volume equals the product of flow rate and sampling time minus the 78 cc volume of sample trapped between the inlet and the closed gate valve, which did not reach the impactor. Because of the much larger flow rates through the molecular filters, this 78 cc volume correction was not made for such flow.

** Particle concentration on molecular filters was similarly calculated.

*** Detonation to time of blast arrival.

F-202-U

Item	QTY	UNIT	PRICE	TOTAL	REMARKS
1	1	EA	1.00	1.00	1.00
2	1	EA	1.00	1.00	1.00
3	1	EA	1.00	1.00	1.00
4	1	EA	1.00	1.00	1.00
5	1	EA	1.00	1.00	1.00
6	1	EA	1.00	1.00	1.00
7	1	EA	1.00	1.00	1.00
8	1	EA	1.00	1.00	1.00
9	1	EA	1.00	1.00	1.00
10	1	EA	1.00	1.00	1.00
11	1	EA	1.00	1.00	1.00
12	1	EA	1.00	1.00	1.00
13	1	EA	1.00	1.00	1.00
14	1	EA	1.00	1.00	1.00
15	1	EA	1.00	1.00	1.00
16	1	EA	1.00	1.00	1.00
17	1	EA	1.00	1.00	1.00
18	1	EA	1.00	1.00	1.00
19	1	EA	1.00	1.00	1.00
20	1	EA	1.00	1.00	1.00
21	1	EA	1.00	1.00	1.00
22	1	EA	1.00	1.00	1.00
23	1	EA	1.00	1.00	1.00
24	1	EA	1.00	1.00	1.00
25	1	EA	1.00	1.00	1.00
26	1	EA	1.00	1.00	1.00
27	1	EA	1.00	1.00	1.00
28	1	EA	1.00	1.00	1.00
29	1	EA	1.00	1.00	1.00
30	1	EA	1.00	1.00	1.00
31	1	EA	1.00	1.00	1.00
32	1	EA	1.00	1.00	1.00
33	1	EA	1.00	1.00	1.00
34	1	EA	1.00	1.00	1.00
35	1	EA	1.00	1.00	1.00
36	1	EA	1.00	1.00	1.00
37	1	EA	1.00	1.00	1.00
38	1	EA	1.00	1.00	1.00
39	1	EA	1.00	1.00	1.00
40	1	EA	1.00	1.00	1.00
41	1	EA	1.00	1.00	1.00
42	1	EA	1.00	1.00	1.00
43	1	EA	1.00	1.00	1.00
44	1	EA	1.00	1.00	1.00
45	1	EA	1.00	1.00	1.00
46	1	EA	1.00	1.00	1.00
47	1	EA	1.00	1.00	1.00
48	1	EA	1.00	1.00	1.00
49	1	EA	1.00	1.00	1.00
50	1	EA	1.00	1.00	1.00
51	1	EA	1.00	1.00	1.00
52	1	EA	1.00	1.00	1.00
53	1	EA	1.00	1.00	1.00
54	1	EA	1.00	1.00	1.00
55	1	EA	1.00	1.00	1.00
56	1	EA	1.00	1.00	1.00
57	1	EA	1.00	1.00	1.00
58	1	EA	1.00	1.00	1.00
59	1	EA	1.00	1.00	1.00
60	1	EA	1.00	1.00	1.00
61	1	EA	1.00	1.00	1.00
62	1	EA	1.00	1.00	1.00
63	1	EA	1.00	1.00	1.00
64	1	EA	1.00	1.00	1.00
65	1	EA	1.00	1.00	1.00
66	1	EA	1.00	1.00	1.00
67	1	EA	1.00	1.00	1.00
68	1	EA	1.00	1.00	1.00
69	1	EA	1.00	1.00	1.00
70	1	EA	1.00	1.00	1.00
71	1	EA	1.00	1.00	1.00
72	1	EA	1.00	1.00	1.00
73	1	EA	1.00	1.00	1.00
74	1	EA	1.00	1.00	1.00
75	1	EA	1.00	1.00	1.00
76	1	EA	1.00	1.00	1.00
77	1	EA	1.00	1.00	1.00
78	1	EA	1.00	1.00	1.00
79	1	EA	1.00	1.00	1.00
80	1	EA	1.00	1.00	1.00
81	1	EA	1.00	1.00	1.00
82	1	EA	1.00	1.00	1.00
83	1	EA	1.00	1.00	1.00
84	1	EA	1.00	1.00	1.00
85	1	EA	1.00	1.00	1.00
86	1	EA	1.00	1.00	1.00
87	1	EA	1.00	1.00	1.00
88	1	EA	1.00	1.00	1.00
89	1	EA	1.00	1.00	1.00
90	1	EA	1.00	1.00	1.00
91	1	EA	1.00	1.00	1.00
92	1	EA	1.00	1.00	1.00
93	1	EA	1.00	1.00	1.00
94	1	EA	1.00	1.00	1.00
95	1	EA	1.00	1.00	1.00
96	1	EA	1.00	1.00	1.00
97	1	EA	1.00	1.00	1.00
98	1	EA	1.00	1.00	1.00
99	1	EA	1.00	1.00	1.00
100	1	EA	1.00	1.00	1.00

Fig. A.1 Sample Cascade Impactor Calculation Sheet

UNCLASSIFIED




Fig. A.4 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station F-202-J




Fig. A.5 Pre-shock Dust Particle Size Distribution, Cascade Impactor Station F-204-J




Fig. A.6 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-202-U




Fig. A.7 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-202-L




Fig. A.8 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-204-U




Fig. A.9 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-204-L




Fig. A.10 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-201-U




Fig. A.11 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-201-L




Fig. A.12 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-202-U




Fig. A.13 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-204-U




Fig. A.14 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station C-204-L




Fig. A.16 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station D-204-U




Fig. A.16 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station D-204-L

UNCLASSIFIED




Fig. A.17 Pre-shock Dust Particle Size Distribution
Cascade Impactor, Station F-202-U

CLASSIFIED




Fig. A.18 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station F-204-U




Fig. A.19 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station B-202-U

UNCLASSIFIED




Fig. A.20 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station B-202-L




Fig. A.21 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station B-204-U

UNCLASSIFIED

Security Information

B-204-L (J)




Fig. A.22 Pre-shock Dust Particle Size Distribution, Cascade Impactor, Station B-204-L




Fig. A.23 Pre-shock Dust Particle Size Distribution
Cascade Impactor, Station C-201-U

UNCLASSIFIED




Fig. A.24 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station C-201-L




Fig. A.25 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station C-202-U

UNCLASSIFIED

[REDACTED]




Fig. A.26 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station C-204-U

[REDACTED]

[REDACTED]

UNCLASSIFIED

C-204-L (0)




Fig. A.27 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station C-204-L

UNCLASSIFIED




Fig. A.28 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station D-204-U




Fig. A.29 Pre-shock Dust Particle Size Distribution,
Cascade Impactor, Station D-204-L

UNCLASSIFIED




Fig. A.30 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station F-202-U

F-202-L




Fig. A.31 Pre-shook Dust Particle Size Distribution,
Molecular Filter, Station F-202-L

UNCLASSIFIED




Fig. A.32 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station F-204-U




Fig. A.35 Pre-shook Dust Particle Size Distribution,
Molecular Filter, Station F-204-L

UNCLASSIFIED




Fig. A.34 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station B-201-U




Fig. A.35 Pre-shook Dust Particle Size Distribution,
Molecular Filter, Station B-201-L

UNCLASSIFIED

B-202-U




Fig. A.36 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station B-202-U

B-202-L




Fig. A.37 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station B-202-L

UNCLASSIFIED




Fig. A.38 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station B-204-U




Fig. A.39 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station B-204-L

UNCLASSIFIED




Fig. A.40 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station C-201-U




Fig. A.41 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station C-201-L

UNCLASSIFIED




Fig. A.42 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station C-202-U

CONFIDENTIAL

C-202-L




Fig. A.43 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station C-202-L

CONFIDENTIAL

CONFIDENTIAL

UNCLASSIFIED




Fig. A.44 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station C-204-U

UNCLASSIFIED
[REDACTED]




Fig. A.45 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station C-204-L

UNCLASSIFIED




Fig. A.46 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station D-202-L

D-204-U




Fig. A.47 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station D-204-U

UNCLASSIFIED




Fig. A.48 Pre-shock Dust Particle Size Distribution,
Molecular Filter, Station D-204-L




Fig. A.49 Background Dust Particle Size Distribution,
Molecular Filters, Station D-204-B

[REDACTED]

APPENDIX B

DAMAGE TO STATIONS

B.1 EFFECT OF SHOTS

No damage was caused by the first three shots; however, the fourth shot caused almost completely demolished stations 7-201 and 7-202.

B.2 STATION 7-201

At station 7-201, the sampling box at the 10 ft. level was moved 50 ft. to the rear of the foundation and the impactor and filter sampler broken. The ground level box stayed on its foundation and the samplers remained on their mountings, but samples could be obtained. Both molecular filters were apparently burned up by thermal radiation. The canisters were blown away from the upper samplers. The lower canister paper was scorched.

B.3 STATION 7-202

At station 7-202, the upper sampling box was blown about 300 ft. from the foundation. The only usable sample obtained at this station was on the molecular filter at ground level.

At both stations, the aluminum covering the boxes and guy wires disappeared, presumably by burning. Also, the pressure actuated microswitch supports were bent to the ground.

B.4 STATION 7-204

At station 7-204, some aluminum sheeting was stripped off the guy wires. No other damage was done.

CLASSIFIED




Fig. B.1 Station 7-201 After Shot 4



Fig. B.2 Station 7-201 Blast Closure Microswitches After Shot 4

UNCLASSIFIED




Fig. B.3 Station 7-202 Tower and Sampling Equipment After Shot 4



Fig. B.4 Station 7-204 After Shot 4

APPENDIX C

DETAILS OF CASCADE IMPACTOR ASSEMBLY

For Shot 1, the first and second jets of the impactor were loaded with plain plastic slides, however, for the rest of the shots, plain glass slides were used in the first and second jets because of difficulties encountered in cleaning the plastic slides. The third and fourth jets were loaded with plastic slides. Into each slide, Figure C.1, are fastened two electron microscope screw-cap-screen assemblies. The 200-mesh screen supported a formvar film. The fifth jet of each impactor was loaded with a plastic slide, which contained a formvar film in an electron microscope screw-cap-400-mesh screen assembly. This use of 400-mesh screen and formvar film is new. The formvar film was used because it is very tough and apparently unaffected by the electron beam in the electron microscope.




Fig. C.1 Cascade Impactor Plastic Slide Assembly

UNCLASSIFIED

BIBLIOGRAPHY

1. K. R. May "The Cascade Impactor", Journal of Scientific Instruments, Vol. 22 #10, p. 187, Oct. 45.
2. J. D. Wilcox "The Design and Development of a New Five-Stage Cascade Impactor", CRLIR #92, Army Chemical Center, Md.
3. J. D. Wilcox and W. R. Van Antwerp "A New Sampling Technique Particle Size Distribution by Combined Use of the Optical and Electron Microscope", CRLIR #70, Army Chemical Center, Md.
4. E. H. Engquist and T. C. Goodale Scientific Director's Report, "Cloud Phenomena: Study of Particulate and Gaseous Matter", Operation GREENHOUSE, Annex 6.1
5. C. R. Robbins, H. B. Lehman, D. R. Powers, and J. D. Wilcox "Airborne Particle Studies", Operation JANGLE, Project 2.5a-1.
6. A. Goetz "Molecular Filter Membranes", Report of Symposium 3, Aerosols, p. 77, Technical Command, Army Chemical Center, Md., April, 1950.
7. E. H. Engquist Scientific Director's Report, "Evaluation of Filter Material", Operation GREENHOUSE, Annex 6.6.

DISTRIBUTION

	Copy No.
ARMY ACTIVITIES	
Aast. Chief of Staff, G-2, D/A, Washington 25, D. C.	1
Aast. Chief of Staff, G-3, D/A, Washington 25, D. C.	2
ATTN: DACofS, G-3, (RR&SW)	3
Aast. Chief of Staff, G-4, D/A, Washington 25, D. C.	4
Chief of Ordnance, D/A, Washington 25, D. C. ATTN: ORDTX-AR	5- 7
Chief Signal Officer, D/A, P&O Division, Washington 25, D. C. ATTN: SIGOP	8
The Surgeon General, D/A, Washington 25, D. C.	9- 10
ATTN: Chairman, Medical R&D Board	11
Chief Chemical Officer, D/A, Washington 25, D. C.	12
Chief of Engineers, D/A, Military Construction Division, Protective Construction Branch, Washington 25, D. C.	13
ATTN: ENGEB	14- 16
Chief of Engineers, D/A, Civil Works Division, Washington 25, D. C. ATTN: Engineering Division, Structural Branch	17
The Quartermaster General, CBR, Liaison Office, Research and Development Division, D/A, Washington 25, D. C.	18
Chief, Army Field Forces, Ft. Monroe, Va.	19
Army Field Forces Board #1, Ft. Bragg, N. C.	20- 21
Army Field Forces Board #2, Ft. Knox, Ky.	22
Army Field Forces Board #4, Ft. Bliss, Tex.	23
Commanding General, First Army, Governor's Island, New York, N. Y.	24
Commanding General, Second Army, Ft. George G. Meade, Md.	25- 26
ATTN: AIABB	27- 28
Commanding General, Second Army, Ft. George G. Meade, Md.	29- 34
ATTN: AIAME	35
Commanding General, Second Army, Ft. George G. Meade, Md.	36
ATTN: AIACM	37- 41
Commanding General, Third Army, Ft. McPherson, Ga.	
ATTN: ACofS, G-3	
Commanding General, Fourth Army, Ft. Sam Houston, Tex.	
ATTN: G-3 Section	
Commanding General, Fifth Army, 1660 E. Hyde Park Blvd., Chicago 15, Ill.	
Commanding General, Sixth Army, Presidio of San Francisco, Calif. ATTN: AMCCT-4	
Commander-in-Chief, European Command, APO 403, c/o PM, New York, N. Y.	
Commander-in-Chief, Far East Command, APO 500, c/o PM, San Francisco, Calif. ATTN: ACofS, G-3	

UNCLASSIFIED

SECRET

DISTRIBUTION (Continued)

Copy No.

Commanding General, U. S. Army Alaska, APO 942, c/o PM, Seattle, Wash.	42
Commanding General, U. S. Army Caribbean, APO 834, c/o PM, New Orleans, La. ATTN: CG, USARCARIB	43
Commanding General, U. S. Army Caribbean, APO 834, c/o PM, New Orleans, La. ATTN: CG, USARFANT	44
Commanding General, U. S. Army Caribbean, APO 834, c/o PM, New Orleans, La. ATTN: Cml Off, USARCARIB	45
Commanding General, U. S. Army Caribbean, APO 834, c/o PM, New Orleans, La. ATTN: Surgeon, USARCARIB	46
Commanding General, USAR Pacific, APO 958, c/o PM, San Francisco, Calif. ATTN: Cml Off	47- 48
Commandant, Command and General Staff College, Ft. Leavenworth, Kan. ATTN: ALLIS(AS)	49- 50
Commandant, The Infantry School, Ft. Benning, Ga. ATTN: C.D.S.	51- 52
Commandant, The Artillery School, Ft. Sill, Okla.	53
Commandant, The AA&GM Branch, The Artillery School, Ft. Bliss, Tex.	54
Commandant, The Armored School, Ft. Knox, Ky. ATTN: Classi- fied Document Section, Evaluation and Res. Div.	55- 56
Commanding General, Medical Field Service School, Brooke Army Medical Center, Ft. Sam Houston, Tex.	57
Commandant, Army Medical Service School, Walter Reed Army Medical Center, Washington 25, D. C. ATTN: Dept. of Biophysics	58
The Superintendent, United States Military Academy, West Point, N. Y. ATTN: Professor of Ordnance	59- 60
Commandant, Chemical Corps School, Chemical Corps Training Command, Ft. McClellan, Ala. ATTN: Radiological Section	61- 62
Commanding General, Research and Engineering Command, Army Chemical Center, Md. ATTN: Special Projects Officer	63
RD Control Officer, Aberdeen Proving Ground, Md. ATTN: Director, Ballistic Research Laboratories	64- 65
Commanding General, The Engineer Center, Ft. Belvoir, Va. ATTN: Asst. Commandant, The Engineer School	66- 68
Commanding General, Aberdeen Proving Ground, Md.	69- 70
Chief of Research and Development, D/A, Washington 25, D. C.	71
Commanding Officer, Engineer Research and Development Laboratory, Ft. Belvoir, Va. ATTN: Chief, Technical Intelligence Branch	72
Commanding Officer, Picatinny Arsenal, Dover, N. J. ATTN: ORDBB-TK	73
Commanding Officer, Army Medical Research Laboratory, Ft. Knox, Ky.	74

[REDACTED]

DISTRIBUTION (Continued)

Copy No.

Commanding Officer, Chemical Corps Chemical and Radiological Laboratory, Army Chemical Center, Md. ATTN: Technical Library	75- 76
Commanding Officer, Psychological Warfare Center, Ft. Bragg, N. C. ATTN: Library	77
Asst. Chief, Military Plans Division, Rm 516, Bldg 7, Army Map Services, 6500 Brooks Lane, Washington 25, D. C. ATTN: Operations Plans Branch	78
Director, Technical Documents Center, Evans Signal Lab., Belmar, N. J.	79
Director, Waterways Experiment Station, PO Box 631, Vicksburg, Miss. ATTN: Library	80
Director, Operations Research Office, Johns Hopkins University, 6410 Connecticut Ave., Chevy Chase, Md. ATTN: Library	81

NAVY ACTIVITIES

Chief of Naval Operations, D/N, Washington 25, D. C. ATTN: OP-36	82- 83
Chief of Naval Operations, D/N, Washington 25, D. C. ATTN: OP-51	84
Chief of Naval Operations, D/N, Washington 25, D. C. ATTN: OP-53	85
Chief of Naval Operations, D/N, Washington 25, D. C. ATTN: OP-374 (OEG)	86
Chief, Bureau of Medicine and Surgery, D/N, Washington 25, D. C. ATTN: Special Weapons Defense Division	87- 88
Chief, Bureau of Ordnance, D/N, Washington 25, D. C.	89
Chief, Bureau of Personnel, D/N, Washington 25, D. C. ATTN: Pers 15	90
Chief, Bureau of Ships, D/N, Washington 25, D. C. ATTN: Code 348	91
Chief, Bureau of Supplies and Accounts, D/N, Washington 25, D. C.	92
Chief, Bureau of Yards and Docks, D/N, Washington 25, D. C. ATTN: P-312	93
Chief, Bureau of Aeronautics, D/N, Washington 25, D. C.	94- 95
Chief of Naval Research, D/N, Washington 25, D. C.	96- 97
Commander-in-Chief, U. S. Atlantic Fleet, Fleet Post Office, New York, N. Y.	98- 99
Commander-in-Chief, U. S. Pacific Fleet, Fleet Post Office, San Francisco, Calif.	100-101
Commander, Operation Development Force, U. S. Atlantic Fleet, U. S. Naval Base, Norfolk 11, Va. ATTN: Tactical Development Group	102
Commander, Operation Development Force, U. S. Atlantic Fleet, U. S. Naval Base, Norfolk 11, Va. ATTN: Air Dept.	103

CLASSIFIED

Security Information

DISTRIBUTION (Continued)

Copy No.

Commandant, U. S. Marine Corps, Headquarters, USMC, Washington 25, D. C. ATTN: (AO3H)	104-107
President, U. S. Naval War College, Newport, Rhode Island	108
Superintendent, U. S. Naval Postgraduate School, Monterey, Calif.	109
Commanding Officer, U. S. Naval Schools Command, Naval Station, Treasure Island, San Francisco, Calif.	110-111
Director, USMC Development Center, USMC Schools, Quantico, Va. ATTN: Marine Corps Tactics Board	112
Director, USMC Development Center, USMC Schools, Quantico, Va. ATTN: Marine Corps Equipment Board	113
Commanding Officer, Fleet Training Center, Naval Base, Norfolk 11, Va. ATTN: Special Weapons School	114-115
Commanding Officer, Fleet Training Center, (SPWP School), Naval Station, San Diego 36, Calif.	116-117
Commander, Air Force, U. S. Pacific Fleet, Naval Air Sta- tion, San Diego, Calif.	118
Commander, Training Command, U. S. Pacific Fleet, c/o U. S. Fleet Sonar School, San Diego 47, Calif.	119
Commanding Officer, Air Development Squadron 5, USN Air Station, Moffett Field, Calif.	120
Commanding Officer, Naval Damage Control Training Center, U. S. Naval Base, Philadelphia 12, Pa. ATTN: ABC Defense Course	121
Commanding Officer, Naval Unit, Chemical Corps School, Ft. McClellan, Ala.	122
Joint Landing Force Board, Marine Barracks, Camp Lejeune, N. C.	123
Commander, U. S. Naval Ordnance Laboratory, Silver Spring 19, Md. ATTN: EE	124
Commander, U. S. Naval Ordnance Laboratory, Silver Spring 19, Md. ATTN: Alias	125
Commander, U. S. Naval Ordnance Laboratory, Silver Spring 19, Md. ATTN: Alias	126
Commander, U. S. Naval Ordnance Test Station, Inyokern, China Lake, Calif.	127
Officer-in-Charge, U. S. Naval Civil Engineering Research and Evaluation Laboratory, Construction Battalion Center, Port Hueneme, Calif. ATTN: Code 753	128-129
Commanding Officer, USN Medical Research Institute, National Naval Medical Center, Bethesda 14, Md.	130
Director, U. S. Naval Research Laboratory, Washington 25, D. C.	131
Commanding Officer and Director, USN Electronics Labo- ratory, San Diego 52, Calif. ATTN: Code 210	132

DISTRIBUTION (Continued)

Copy No.

Commanding Officer, USN Radiological Defense Laboratory, San Francisco, Calif. ATTN: Technical Information Division	133-134
Commanding Officer and Director, David W. Taylor Model Basin, Washington 7, D. C. ATTN: Library	135
Commander, Naval Air Development Center, Johnsville, Pa.	136
Commanding Officer, Office of Naval Research Branch Office, 1000 Geary St., San Francisco, Calif.	137-138

AIR FORCE ACTIVITIES

Special Asst. to Chief of Staff, Headquarters, USAF, Rm 5E1019, Pentagon, Washington 25, D. C.	139
Assistant for Atomic Energy, Headquarters, USAF, Washington 25, D. C. ATTN: DCS/O	140
Assistant for Development Planning, Headquarters, USAF, Washington 25, D. C.	141-142
Director of Operations, Headquarters, USAF, Washington 25, D. C.	143-144
Director of Plans, Headquarters, USAF, Washington 25, D. C. ATTN: War Plans Division	145
Directorate of Requirements, Headquarters, USAF, Washing- ton 25, D. C. ATTN: AFDRQSA/M	146
Directorate of Research and Development, Armament Divi- sion, DCS/D, Headquarters, USAF, Washington 25, D. C.	147
Directorate of Intelligence, Headquarters, USAF, Washing- ton 25, D. C.	148-149
The Surgeon General, Headquarters, USAF, Washington 25, D. C.	150-151
Commanding General, U. S. Air Forces in Europe, APO 633, c/o PM, New York, N. Y.	152
Commanding General, Far East Air Forces, APO 925, c/o PM, San Francisco, Calif.	153
Commanding General, Alaskan Air Command, APO 942, c/o PM, Seattle, Wash.	154
Commanding General, Northeast Air Command, APO 862, c/o PM, New York, N. Y.	155
Commanding General, Strategic Air Command, Offutt AFB, Omaha, Neb. ATTN: Chief, Operations Analysis	156
Commanding General, Tactical Air Command, Langley AFB, Va. ATTN: Documents Security Branch	157-159
Commanding General, Air Defense Command, Ent AFB, Colo.	160-161
Commanding General, Air Materiel Command, Wright-Patterson AFB, Dayton, Ohio	162-164
Commanding General, Air Training Command, Scott AFB, Belleville, Ill.	165-166
Commanding General, Air Research and Development Command, PO Box 1395, Baltimore, Md. ATTN: RDDW	167-169

UNCLASSIFIED

~~SECRET~~

DISTRIBUTION (Continued)

Copy No.

Commanding General, Air Proving Ground, Eglin AFB, Fla. ATTN: AG/TRB	170
Commanding General, Air University, Maxwell AFB, Ala.	171-175
Commandant, Air Command and Staff School, Maxwell AFB, Ala.	176-177
Commandant, Air Force School of Aviation Medicine, Randolph AFB, Tex.	178-179
Commanding General, Wright Air Development Center, Wright- Patterson AFB, Dayton, Ohio. ATTN: WCOESP	180-185
Commanding General, Air Force Cambridge Research Center, 230 Albany St., Cambridge 39, Mass. ATTN: Atomic Warfare Directorate	186
Commanding General, Air Force Cambridge Research Center, 230 Albany St., Cambridge 39, Mass. ATTN: CRTSL-2	187
Commanding General, AF Special Weapons Center, Kirtland AFB, N. Mex. ATTN: Chief, Technical Library Branch	188-190
Commandant, USAF Institute of Technology, Wright-Patterson AFB, Dayton, Ohio. ATTN: Resident College	191
Commanding General, Lowry AFB, Denver, Colo. ATTN: Dept. of Armament Training	192-193
Commanding General, 1009th Special Weapons Sq., 1712 G St., NW, Washington 25, D. C.	194-196
The RAND Corporation, 1500-4th St., Santa Monica, Calif. ATTN: Nuclear Energy Division	197-198

OTHER DEPTS. OF DEFENSE ACTIVITIES

Executive Secretary, Joint Chiefs of Staff, Washington 25, D. C. ATTN: Joint Strategic Plans Committee	199
Director, Weapons Systems Evaluation Group, OSD, Rm 2E1006, Pentagon, Washington 25, D. C.	200
Assistant for Civil Defense, OSD, Washington 25, D. C.	201
Chairman, Armed Services Explosives Safety Board, D/D, Rm 2403, Barton Hall, Washington 25, D. C.	202
Chairman, Research and Development Board, D/D, Wash- ington 25, D. C. ATTN: Technical Library	203
Executive Secretary, Committee on Atomic Energy, Research and Development Board, Rm 3E1075, Pentagon, Washington 25, D. C.	204-205
Executive Secretary, Military Liaison Committee, PO Box 1814, Washington 25, D. C.	206
Commandant, National War College, Washington 25, D. C. ATTN: Classified Records Section, Library	207
Commandant, Armed Forces Staff College, Norfolk 11, Va. ATTN: Secretary	208
Commanding General, Field Command, AFSWP, PO Box 5100, Albuquerque, N. Mex.	209-214

~~SECRET~~

~~SECRET~~

UNCLASSIFIED

DISTRIBUTION (Continued)

Copy No.

Commanding General, AFSWP, PO Box 2610, Washington 13,
D. C.

215-223

Director of Military Application, U. S. Atomic Energy
Commission, Classified Document Room, 1901 Con-
stitution Ave., Washington 25, D. C.

224-226

Los Alamos Scientific Laboratory, Report Library, PO
Box 1663, Los Alamos, N. Mex. ATTN: Helen Redman

227-229

Sandia Corporation, Classified Document Division, Sandia
Base, Albuquerque, N. Mex. ATTN: Wynne K. Cox

230-249

Weapon Test Reports Group, TIS

250

Surplus in TISOR for AFSWP

251-300