

AD-A078 720

ENVIRONMENTAL RESEARCH INST OF MICHIGAN ANN ARBOR
SYNTHETIC APERTURE IMAGING TECHNIQUES AT SHORT WAVELENGTHS.(U)
NOV 79 C C ALEKSOFF
ERIM-122000-14-F

F/G 17/8

DAAG29-76-G-0184

UNCLASSIFIED

ARO-13735.4-ELX

NL

| OF |
AD
A078720



END
DATE
FILMED
1-80
DDC

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER

2. GOVT ACCESSION NO.

3. RECIPIENT'S CATALOG NUMBER

18 AR 89
19 13735.4-ELX

5. TYPE OF REPORT & PERIOD COVERED

9 Final Report
1 Apr 76 - 30 Sep 79

TITLE (and Subtitle)

6 Synthetic Aperture Imaging Techniques at Short Wavelengths

6. PERFORMING ORG. REPORT NUMBER

AUTHOR(s)

10 Carl C. Aleksoff

8. CONTRACT OR GRANT NUMBER(s)

15
✓ DAAG29-76-G-0184

PERFORMING ORGANIZATION NAME AND ADDRESS

Environmental Research Institute of Michigan
PO Box 8618
Ann Arbor, Michigan 48107

10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS

CONTROLLING OFFICE NAME AND ADDRESS

U. S. Army Research Office
P. O. Box 12211

12. REPORT DATE

11 Nov 79

Research Triangle Park, NC 27709

13. NUMBER OF PAGES

4

14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)

12/6

15. SECURITY CLASS. (of this report)

Unclassified

15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

14 ERIM-122000-14-F

DDC
R
DEC 26 1979
E

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

The view, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

synthetic aperture imaging techniques
light
millimeter waves
short wavelength radiation

electromagnetic scattering
phase(electronics)
amplitude

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

A number of bistatic synthetic aperture(SA) imaging techniques applicable to short wavelength radiation have been analyzed, and near real time two-dimensional SA imaging using visible light has been demonstrated.

19 12 16 001

ADA 078720

DDC FILE COPY



November 1979

SYNTHETIC APERTURE IMAGING TECHNIQUES
AT SHORT WAVELENGTHS

Environmental Research Institute of Michigan
P.O. Box 8618, Ann Arbor, Michigan 48107

122000-14-F

FINAL REPORT

Period Covered: 1 April 1976 to 30 September 1979
Grant Number: DAAG29-76-G-0184
ARO Project Number: P13735-ELX
Author and Principal Investigator: Carl C. Aleksoff

STATEMENT OF THE PROBLEM STUDIED

The goal of this study was to theoretically develop and experimentally investigate synthetic aperture (SA) imaging techniques applicable from the visible to submillimeters wavelength region of the spectrum (i.e., "short" wavelengths in the interval of 0.4 μ m to 1 mm). In this short wavelength region it is assumed that only intensity (square law or photon) detectors exist, and hence, that the amplitude and phase of the scattered radiation can not be detected directly as with SA microwave radars. Two dimensional imaging was to be demonstrated using whatever SA data gathering techniques are applicable for this short wavelength region, e.g., interferometric, ranging, doppler, etc. Emphasis was to be on multi-static configurations, i.e., where source(s) and detector(s) are physically separated by significant distances.

SUMMARY OF RESULTS

We have developed a number of different synthetic aperture (SA) imaging techniques applicable to short wavelength radiation. The SA data can be obtained using doppler, interferometric, or ranging techniques in bistatic configurations. The synthetic aperture data history can be realized through relative motion between the object and the sensor system. In a broadened context of SA concepts, the use of temporally modulated signal transmission or the use of a scanning illumination beam can also provide an extended received signal history which may be processed for high resolution performance. A critical feature is designing the proper system configuration and SA format that simplifies the subsequent data processing, i.e., imaging. In fact, for example, the development of polar formatting for SA imaging of rotating objects overcame a previous limitation in resolution that was, in essence, limited by the difficulty of processing.

Dist **A**

By _____

Amplitude Modulation

Frequency Modulation

Phase Modulation

Time Modulation

Other _____

Approved for _____

Signature _____

Date _____

Special _____

We have typically emphasized interferometric SA imaging at visible wavelengths with proper formatting for subsequent optical processing via holographic techniques. In such an interferometric SA system it is the instantaneous relative position of the object in the interference field that determine the position of the instantaneous data point in the SA. In general, good two-dimensional imaging requires a combination of field scanning along with object motion in order to fill the SA. The recorded SA data is simply the intensity of the scattered light from the object as detected with a large area detector. In the ideal situation the SA data is in holographic form and the image is formed by simply illuminating the SA with a proper reconstruction wave.

A laboratory for demonstrating SA imaging in visible light was assembled under this grant's funding. Special electronics, interferometer, translation stages, rotating tables, optical modulation, and polar format film recorders were part of the system. Accurate registration between the relative position of the object to the interference field and the data point position in the SA was the most difficult requirement. Successful SA imaging was demonstrated for objects with linear motion and that for objects with rotating motion.

In the early stages of the work, the SA data was recorded onto photographic film with a laser beam, the film was next developed, and then illuminated (as a hologram) to construct the image. In the latter stages of the grant, a near real time SA system was demonstrated. Here the SA data was directly electronically written onto a thermoplastic light modulator (TLM). (The TLM is a two-dimensional spatial phase-modulator that uses an electron gun to write the data onto the thermoplastic as a charge induced deformation.) The TLM was the input transducer to a coherent optical processor and was set up to receive data directly from the laboratory as it was being generated for a rotating object. The image could be observed to form in real time in the output plane of the processor.

SA imaging for the case of generalized object motion suggests that extension of processing techniques to a third dimension may be quite useful and possibly essential. Though algorithms for this purpose were not established, it is expected that such processing could be handled digitally (and possibly with future special-purpose hybrid processor designs. As we demonstrated, certain relative motions, such as linear or circular, are elegantly and efficiently handled with presently available optical processing methods.

In conclusion, we point out that we have analyzed a number of different bistatic SA imaging techniques applicable to short wavelength radiation and have experimentally demonstrated near real time two-dimensional SA imaging using visible light.

APPENDIX
PUBLICATION LIST

- C. C. Aleksoff, "Synthetic Interferometric Imaging Techniques for Moving Objects", Applied Optics, 15, 1923, August 1976.
- C. C. Aleksoff, "Synthetic Interferometric Imaging", JOSA, 66, 1089, October 1976.
- K. L. Van Voorhies & C. C. Aleksoff, "Synthetic Model Interferometric Imaging," Applied Optics, 16, 2441, September 1977.
- C. C. Aleksoff, "Interferometer Two-Dimensional Imaging of Rotating Objects," Optics Letters, 1, 54, August 1977.
- C. C. Aleksoff, "Synthetic Aperture Imaging of Rotating Objects," JOSA, 67, 1433, October 1977.
- C. C. Aleksoff, "Synthetic Aperture Imaging in Real Time Using the Thermoplastic Modulator," Proc. of the Symposium on Optical Display, Processing and Storage, 41, January 1979. (Society of Photographic Scientists and Engineers)

SCIENTIFIC PERSONNEL SUPPORT

This grant was used in support of Dr. C. C. Aleksoff.

Experimental support and direction was given to K. L. VanVoorhies for his M.S. thesis research. His thesis title was "Synthetic Modal Interferometric Laser Imaging". His degree was a combined degree from both General Motors Institute and The University of Michigan.