

TECHNICAL
LIBRARY

AD

MEMORANDUM REPORT ARBRL-MR-02969

ON THE UTILITY OF PLANE STRAIN
APPROXIMATIONS FOR OBLIQUE
IMPACT COMPUTATIONS

J. A. Zukas
G. H. Jonas
J. J. Misey

October 1979



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

DTIC QUALITY INSPECTED 3

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22151.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-02969	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ON THE UTILITY OF PLANE STRAIN APPROXIMATIONS FOR OBLIQUE IMPACT COMPUTATIONS		5. TYPE OF REPORT & PERIOD COVERED Final
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) J. A. Zukas G. H. Jonas J. J. Misey		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: DRDAR-BLT Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L162618AH80
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory (DRDAR-BL) Aberdeen Proving Ground, MD 21005		12. REPORT DATE OCTOBER 1979
		13. NUMBER OF PAGES 44
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Hydrodynamic Eulerian Code Oblique KE Penetration PHERMEX HELP Plane Strain Approximation		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A study was made to determine the feasibility of using the plane strain mode of a 2D code in lieu of a 3D code for this oblique kinetic energy penetration problem. First, a comparison in a normal impact problem was made between the axisymmetric and the plane strain modes of the two dimensional HELP code. A volumetric relationship was given for the kinetic energy and the axial momentum of the projectile, but data scaling for other variables of the projectile and those of the target were not determined. Next, HELP in the plane strain mode was utilized to solve a long rod impact at 60° obliquity and the results were		

20. Abstract (cont'd)

compared with experimental data obtained at Los Alamos Scientific Laboratory. Finally, the oblique impact problem was also modeled with a three dimensional version of the EPIC code. A comparison of rod loss penetration depth, and penetrator and target profiles revealed very good agreement at early times when the penetrator density was greater than that of the target.

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	5
LIST OF TABLES	7
I. INTRODUCTION	9
II. PLANE STRAIN APPROXIMATIONS	9
III. RESULTS	12
IV. CONCLUSIONS	22
REFERENCES	23
APPENDIX - AXISYMMETRIC/PLANE STRAIN COMPARISONS	25
DISTRIBUTION LIST	39

LIST OF ILLUSTRATIONS

Figure	Page
1. Penetration Profiles for Axisymmetric Impact at 50 Microseconds	11
2. Computational Elements for Axisymmetric and Plane Strain Calculations	13
3. Multi-material Penetrator	14
4. Comparison of Plane Strain and Experimental Results at 12 Microseconds	18
5. Comparison of Plane Strain and Experimental Results at 25.6 Microseconds	19
6. Penetration Depth and Rod Loss vs. Time for 60° Oblique Impact	20
7. Comparison of Experimental Three-Dimensional and Plane Strain Results at 25 Microseconds	21
A-1. Penetrator/Target Profiles at 0 Microseconds for Axisymmetric and Plane Strain Cases	26
A-2. Penetrator/Target Profiles at 2 Microseconds for Axisymmetric and Plane Strain Cases	27
A-3. Penetrator/Target Profiles at 4 Microseconds for Axisymmetric and Plane Strain Cases	28
A-4. Penetrator/Target Profiles at 6 Microseconds for Axisymmetric and Plane Strain Cases	29
A-5. Penetrator/Target Profiles at 8 Microseconds for Axisymmetric and Plane Strain Cases	30
A-6. Penetrator/Target Profiles at 10 Microseconds for Axisymmetric and Plane Strain Cases	31
A-7. Penetrator/Target Profiles at 15 Microseconds for Axisymmetric and Plane Strain Cases	32
A-8. Penetrator/Target Profiles at 20 Microseconds for Axisymmetric and Plane Strain Cases	33

LIST OF ILLUSTRATIONS (Cont)

Figure	Page
A-9. Penetration and Target Kinetic Energy as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations	34
A-10. Penetration and Target Axial Momentum as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations	35
A-11. Penetration and Target Radial Momentum as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations	36
A-12. Penetration and Target Plastic Work as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations	37
A-13. Penetration and Target Internal Energy as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations	38

LIST OF TABLES

Table	Page
I. Computations versus Experiments	10
II. Material Parameters	15

I. INTRODUCTION

Long rod kinetic energy penetrators pose an important threat to armor. The analysis of the impact of a kinetic energy projectile, typically a cylindrical rod with large length-to-diameter ratio made of a high-density material, should account for the three-dimensional aspects of the impact and the failure of materials involved in the velocity range of interest. For reasons discussed elsewhere¹, very little analysis of oblique impacts has been done. Most of the effort in this area has been confined to experimental studies. Experiments, however, are complex, expensive, difficult to control and yield only minimal information. Time resolved data for ballistic experiments was generally unavailable. The need to understand the phenomenology and details involved in an oblique impact has led to the use of plane strain (two-dimensional) computations in the hope of deriving information useful to kinetic energy penetrator and armor designers. The use of codes in general has provided greater detail than can be obtained from experiments, but this approach leads to another series of complications (Table I).

In this report, we will discuss briefly the nature of the plane strain approximation and illustrate its successes and limitations with two applications. While some useful information can be extracted from plane strain simulation of oblique impact phenomena, much work needs to be done before such calculations can be used to support design efforts.

II. PLANE STRAIN APPROXIMATIONS

Computations at normal incidence can be performed routinely and economically and can yield excellent results for deformation fields when compared with experiments. Figure 1, for example, shows a comparison between a HELP² code computation of a staballoy rod striking 5.08 cm RHA plate at 1.0 km/s with results obtained at the PHERMEX facility of Los Alamos Scientific Laboratory³. The agreement is generally excellent.

¹Jonas, G. H. and Zukas, J. A., "Mechanics of Penetration: Analysis and Experiment," *Int. J. Eng. Sci.*, V16, pp. 879-903, 1978.

²Hageman, L. J., Wilkins, D. E., Sedgwick, R. T., and Waddell, J., "HELP, a Multi-Material Eulerian Program for Compressible Fluid and Elastic-Plastic Flows in Two Space Dimensions and Time, Revised Edition," *Systems, Science and Software*, SSS-R-75-2654, Topical Report, July 1975.

³Private Communication from E. Fugleso, J. W. Taylor and L. W. Hantel of Los Alamos Scientific Laboratory.

The bulge at the target impact face in the computational results consists mostly of failed material - computational cells which have suffered a density reduction of 40% or more. This would normally be seen in a radiograph as a cloud of debris particles. However, the masking used in the experimental setup precludes recording of either front or rear bulging of the target plate. Such computations can be done routinely today. The quality of results depends primarily on the availability of dynamic material properties and on the material model employed in the code.

Table I. Computations versus Experiments

Constraints	Computer Simulation	Field Experiments
Cost	Typical 3D simulation costs ~\$6000 for penetration simulation. Typical 2D (plane strain) simulation costs ~\$1500.	Typical cost for one shot is \$7500 (including materials and fabrication costs and data reduction).
Time	Up to one week may be needed to grid and debug problem, several weeks to obtain and analyze results.	Once materials have been fabricated, one to two shots per day can be obtained.
Information	Maximal output - displacements, stress, strain, strain rate, momenta, energies, forces and moments.	Minimal - initial and final velocity and orientation for projectile; residual projectile mass; target hole size and mass loss.
Unknowns	Results depend on material model, material properties, failure model.	Uncertainties in material properties, initial conditions and boundary conditions manifested as data scatter.
Utility	Excellent base for construction of approximate analytical models for parametric studies.	Time and cost constraints almost never permit acquisition of data base with enough variation of parameters to construct unambiguous models.




Figure 1. Penetration Profiles for Axisymmetric Impact at 50 Microseconds

Oblique impact, however, is clearly the problem of greater practical importance in the design of projectiles and evaluation of their effectiveness. Oblique incidence is a three-dimensional problem, i.e., the geometry involves specification of three space coordinates. There are pitifully few analytical models¹ which treat oblique incidence and these tend to be extremely simple while also relying heavily on empirical input. Hence recourse is frequently made to 3D numerical solutions and 2D plane strain approximations.

Three-dimensional codes, both finite element and finite difference, exist and have been used successfully to study problems involving penetration, ricochet, crack propagation and the like^{1,4,5}. However, they make severe demands on computer storage and are quite costly, although this latter aspect will become less of a problem with the advent of the next generation of computers. The codes at present are invaluable for phenomenological studies but are not yet working tools for designers working in the area of ballistic impact.

Two-dimensional plane strain calculations are straightforward enough, relatively inexpensive and provide some interesting information. However, when oblique impact of a long rod penetrator is treated as the impact of an infinitely long wedge (Figure 2), important physical phenomena are being neglected, i.e., the out-of-plane motions leading to lateral stress relaxations. Useful qualitative information (and, as will be shown, limited quantitative information) about the early stages of an oblique impact can be obtained from plane strain solutions. Their utility, however, degrades with increasing time after impact so that for late times, when important aspects of penetration and target response (i.e., bending, shear failure) are being determined, plane strain solutions are speculative at best.

III. RESULTS

Several calculations were undertaken to obtain a better appreciation of the utility of plane strain approximations. The first set involved the multi-material projectile of Figure 3, a long rod consisting of a maraging steel sheath and tungsten alloy core. Computations were made with the HELP code in both the axisymmetric and plane strain modes with the projectile striking a 2.37 cm RHA target at 0° with a velocity of 1.45 km/s. The second set involved the impact of a 65 gram, L/D = 10, hemispherical nose, staballoy penetrator against a 1.91 cm RHA plate at 60° obliquity with a striking velocity of 1.5 km/s.

⁴Johnson, G. R., "A New Computational Technique for Intense Impulsive Loads," *Proc. 3d Intl. Symp. on Ballistics*, Karlsruhe, Germany, March 1977.

⁵Chen, Y. M., "Numerical Solutions of Three-Dimensional Dynamic Crack Problems and Simulation of Dynamic Fracture Phenomena by a 'Non-Standard' Finite Difference Method," *Engr. Fract. Mech.*, V10, pp. 699-708, 1978.




Figure 2. Computational Elements for Axisymmetric and Plane Strain Calculations




Figure 3. Multi-material Penetrator (units in cm)

All computational results were obtained with the HELP code, a two-dimensional, multi-material Eulerian code for solving material flow problems in the hydrodynamic and elasto-plastic regimes. Although the code is basically Eulerian, material interfaces and free surfaces are propagated in a Lagrangian manner through the calculational mesh as discrete interfaces across which material is not allowed to diffuse. The material model employed in HELP includes the Tillotson equation of state⁶, modified to give a smooth transition between condensed and expanded states, a deviatoric constitutive relation, a yield criterion defined to account for the increase in strength at high compressions and decrease with increases in internal energy, and failure criteria. Failure in tension is based on relative volume. When the relative volume in a cell reaches a certain value greater than a specified maximum distension, that cell is said to fail and any computed tensions are zeroed out. Failure can also occur when the internal energy is greater than the melt energy. Material properties used for the computations are given in Table II. The projectile material parameters were obtained from Dr. Ernest Bloore while a member of the Penetration Mechanics Branch and the RHA parameters from the Solid Mechanics Branch, TBD, BRL.

Table II. Material Parameters

Material	E (GPa)	ν	σ_y (GPa)	σ_u (GPa)	ρ (kg/m ³)
Staballoy	195.8	0.203	1.036	1.45	18.62x10 ³
90-7-3 tungsten	372.0	0.269	0.553	1.14	17.04x10 ³
MAR-M-300 steel	180.7	0.264	1.827	1.945	8.07x10 ³
RHA	209.9	0.3	1.220	1.35	7.8x10 ³

E - Young's modulus

ν - Poisson's ratio

σ_y - yield strength

σ_u - ultimate strength

ρ - density

Computed deformation profiles for the normal impact multi-material penetrator from the axisymmetric and plane strain computations are shown in the Appendix. Shown also are plots of state variables (kinetic energy,

⁶Tillotson, J. H., "Metallic Equations of State for Hypervelocity Impact," General Atomic Report GA-3216, July 1962.

momenta, plastic work, and internal energy) as functions of time. The differences between the exact (axisymmetric) and plane strain cases are readily apparent. Differences between the two computations become quite pronounced with time, as is evident from both the state variable plots and deformation plots. At late times, the plane strain calculation clearly shows greater deformation and failure than the axisymmetric case. The plots of penetrator kinetic energy and axial momentum also indicate a relationship between plane strain and axisymmetric results exists and can readily be found by considering the difference in volumes for the two cases. Denoting by V_p the volume per unit depth of the round under the plane strain approximation (unit thickness slab) and by V_a the actual volume (axisymmetric case), then the kinetic energy and linear momentum of the projectile become coincident upon application of a scaling factor of

$$\lambda = \frac{(V_a/V_p)_{M_1} \rho_{M_1} + (V_a/V_p)_{M_2} \rho_{M_2}}{\rho_{M_1} + \rho_{M_2}} \quad (1)$$

where ρ represents density and M_1 and M_2 refer to the two materials of the composite round. Note that for a single material projectile ($\rho_{M_1} = \rho_{M_2} = \rho$), the scaling factor reduces to

$$\lambda = V_a/V_p \quad (2)$$

If actual dimensions are used in (1), one is led to the conclusion that the plane strain velocity should be reduced by $\sim\sqrt{2}$, i.e.,

$$v_p \sim v_a/\sqrt{2} \quad (3)$$

to achieve comparable energies (and therefore, hopefully, damage levels). This is in agreement with conclusions reached by Bertholf et al⁷ who obtained the same expression based on considerations of comparable target damage for the two cases.

The results for the target behavior and for projectile plastic work and internal energy indicate that there is no simple relationship between

⁷Bertholf, L. D., Kipp, M. E., Brown, W. T., "Two-Dimensional Calculations for the Oblique Impact of Kinetic Energy Projectiles with a Multi-Layered Target", BRL-CR-333, March 1977. (AD #B017358L)

plane strain and exact results for these state variables, and that considerable additional work needs to be done before plane strain calculations can supplant fully three-dimensional calculations in assisting kinetic energy projectile designers, a point made also by others^{8,9}.

The stated data in the Appendix also shows that, for sufficiently energetic impacts, which in this case is a projectile at ordnance velocity and considerable higher density than the target, and for short time intervals after impact, good quantitative, as well as qualitative, information may be extracted from plane strain results. Another example of this is the near-perfect agreement between plane-strain results and experiment for deformation fields obtained by Norris et al¹⁰ who were able to establish the mechanisms leading to target defeat and ricochet in long rod impacts. Once the effects of lateral relief waves (not accounted for in plane strain computations) become significant, increasing divergence between plane strain and exact results is to be expected.

Results for the oblique impact computation and their PHERMEX³ counterpart are shown in Figures 4 through 6. At the later time (Figure 5) they are both surprising and fortuitous considering the underlying differences between the slab approximation and the exact three-dimensional case. It is probable that such excellent agreement can be partially attributed to the tendency of the projectile material (depleted uranium) to erode continuously at the impact end. This computation was repeated with EPIC3, a three-dimensional finite element Lagrangian code¹. The agreement between experiment, plane strain and three-dimensional results for deformation fields, residual length and velocity is excellent, the measured quantities being within a few percent of each other. Profile comparisons of these three results are shown in Figure 7.

Although at early times agreement for hole profiles and residual length of the penetrator was quite good, it should be noted that the tabular data arising from the computer runs showed spurious signals in the form of small radial velocities within the first microsecond in regions where no genuine signal could have propagated. Also found for the multimaterial penetrator were regions where internal energy and plastic work were negative. These anomalies affect the values of pressure, stress and energy in some areas of the calculation. A more thorough discussion of HELP code problems can be found elsewhere¹¹. It can be concluded that although useful results have been obtained with

⁸Kipp, M. E. and Bertholf, L. D., private communication.

⁹Sedgwick, R. T., Waddell, J., and Hageman, J. L., "A Comparison of Results from Two Long Rod Oblique Impact Calculations," BRL-CR-288, February 1976. (AD #B009783L)

¹⁰Norris, D. M., Scudder, J. K., McMaster, W. A., Wilkins, M. L., "Mechanics of Long Rod Penetration at High Obliquity," in Proc. High Density Alloy Penetrator Materials Conf., AMMRC-SP-77-3, 1977.

¹¹Jonas, G. H., and Zukas, J. A., "Cap Design for Kinetic Energy Penetrators," BRL-R-1813, August 1975. (AD #B006902L)




Figure 4. Comparison of Plane Strain and Experimental Results at 12 Microseconds





Figure 5. Comparison of Plane Strain and Experimental Results at 25.6 Microseconds





Figure 6. Penetration Depth and Rod Loss vs. Time for 60° Oblique Impact





Figure 7. Comparison of Experimental Three-Dimensional and Plane Strain Results at 25 Microseconds

HELP, the code is essentially unreliable in its present form for ordnance velocity impacts. It also requires excessive human intervention for readjusting tracer points, correcting pure cell problems and other anomalies during long computations. A reformation of the basic equations to make them second-order accurate might do much to enhance the code's stability and utility.

IV. CONCLUSIONS

Based on the results shown here and the findings of other researchers, we may conclude that a fair amount of qualitative insight may be obtained from plane strain simulation of oblique impact phenomena and such studies, with suitable caution, can be profitably employed for parametric studies. At sufficiently early times after impact, reasonable quantitative results for deformation and projectile orientation can be obtained. However, for computation of local variables (stress, strain, temperature), recourse must be made to three-dimensional calculations. These in turn will be useful only if the materials in question have been adequately characterized at the strain rates in question.

Additional work needs to be done to relate plane strain to exact results in order to make plane strain computational results useful to projectile and armor designers. Since the cost of plane strain computations is some one-quarter those for three-dimensional calculations, the incentive for such work should be self-evident.

REFERENCES

1. Jonas, G. H. and Zukas, J. A., "Mechanics of Penetration: Analysis and Experiment," *Int. J. Eng. Sci.*, V16, pp. 879-903, 1978.
2. Hageman, L. J., Wilkins, D. E., Sedgwick, R. T. and Waddell, J., "HELP, a Multi-Material Eulerian Program for Compressible Fluid and Elastic-Plastic Flows in Two Space Dimensions and Time, Revised Edition," Systems, Science and Software, SSS-R-75-2654, Topical Report, July 1975.
3. Printed Communication from E. Fugleso, J. W. Taylor and L. W. Hantel of Los Alamos Scientific Laboratory.
4. Johnson, G. R., "A New Computational Technique for Intense Impulsive Loads," Proc. 3d Intl. Symp. on Ballistics, Karlsruhe, Germany, March 1977.
5. Chen, Y. M., "Numerical Solutions of Three-Dimensional Dynamic Crack Problems and Simulation of Dynamic Fracture Phenomena by a 'Non-Standard' Finite Difference Method," *Engr. Fract. Mech.*, V10, pp. 699-708, 1978.
6. Tillotson, J. H., "Metallic Equations of State for Hypervelocity Impact," General Atomic Report GA-3216, July 1962.
7. Bertholf, L. D., Kipp, M. E. and Brown, W. T., "Two-Dimensional Calculations for the Oblique Impact of Kinetic Energy Projectiles with a Multi-Layered Target," BRL-CR-333, (AD B017358L), March 1977.
8. Kipp, M. E. and Bertholf, L. D., private communication.
9. Sedgwick, R. T., Waddell, J. and Hageman, J. L., "A Comparison of Results from Two Long Rod Oblique Impact Calculations," BRL-CR-288, (AD B009783L), February 1976.
10. Norris, D. M., Scudder, J. K., McMaster, W. A. and Wilkins, M. L., "Mechanics of Long Rod Penetration at High Obliquity," in Proc. High Density Alloy Penetrator Materials Conf., AMMRC-SP-77-3, 1977.
11. Jonas, G. H. and Zukas, J. A., "Cap Design for Kinetic Energy Penetrators," BRL-R-1813, August 1975. (AD #B006902L)

APPENDIX

AXISYMMETRIC/PLANE STRAIN COMPARISONS

The following pages consist of deformation profile plots and graphs of the state variables as functions of time for the axisymmetric and plane strain calculations of a normal impact by a long rod consisting of a maraging steel sheath and tungsten alloy core against a 2.37 cm RHA target at 1.45 km/s. It should be noted that the HELP code being Eulerian is set up with a computational grid in which the material passes through the cells. Because of limited storage the grid is set up so that there is a fine zone where most of the activity occurs and a coarser grid elsewhere. Deformation plots can be obtained either in actual dimensions or cell dimensions. The choice of cell dimensions was made for a clearer picture of what is happening at the interface. For each failed cell an x is placed in that cell. Furthermore, the option was made to draw only the exterior of the projectile.




Figure A-1. Penetrator/Target Profiles at 0 Microseconds for Axisymmetric and Plane Strain Cases




Figure A-2. Penetrator/Target Profiles at 2 Microseconds for Axisymmetric and Plane Strain Cases




Figure A-3. Penetrator/Target Profiles at 4 Microseconds for Axisymmetric and Plane Strain Cases




Figure A-4. Penetrator/Target Profiles at 6 Microseconds for Axisymmetric and Plane Strain Cases




Figure A-5. Penetrator/Target Profiles at 8 Microseconds for Axisymmetric and Plane Strain Cases






Figure A-6. Penetrator/Target Profiles at 10 Microseconds for Axisymmetric and Plane Strain Cases




Plane Strain



Axisymmetric

Figure A-7. Penetrator/Target Profiles at 15 Microseconds for Axisymmetric and Plane Strain Cases



Plane Strain

Axisymmetric

Figure A-8. Penetrator/Target Profiles at 20 Microseconds for Axisymmetric and Plane Strain Cases





Figure A-9. Penetration and Target Kinetic Energy as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations





Figure A-10. Penetration and Target Axial Momentum as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations





Figure A-11. Penetration and Target Radial Momentum as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations





Figure A-12. Penetration and Target Plastic Work as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations





Figure A-13. Penetration and Target Internal Energy as a Function of Time for the Axisymmetric and Plane Strain Mode Calculations

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
12	Commander Defense Documentation Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	1	Commander US Army Materiel Development and Readiness Command ATTN: DRCMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333
1	Director Defense Advanced Research Projects Agency ATTN: Tech Info 1400 Wilson Boulevard Arlington, VA 22209	2	Commander US Army Materiel Development and Readiness Command ATTN: DRCRD-W, J. Corrigan 5001 Eisenhower Avenue Alexandria, VA 22333
1	Director Defense Nuclear Agency Arlington, VA 22209	11	Commander US Army Armament Research and Development Command ATTN: DRDAR-TD, Dr. R. Weigle DRDAR-LC, Dr. J. Frasier DRDAR-SC, Dr. D. Gyorog DRDAR-LCF, G. Demitrack DRDAR-LCA, G. Randers-Pehrson DRDAR-SCS-M, R. Kwatnoski DRDAR-SCA-T, H. Kahn, P. Ehle DRDAR-LCU, E. Barrieres DRDAR-TSS (2 cys) Dover, NJ 07801
1	Deputy Assistant Secretary of the Army (R&D) Department of the Army Washington, DC 20310		
1	Commander US Army BMD Advanced Technology Center ATTN: BMDATC-M, Mr. P. Boyd PO Box 1500 Huntsville, AL 35807		
1	HQDA (DAMA-ARP) WASH DC 20310		
1	HQDA (DAMA-MS) WASH DC 20310	1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299
2	Commander US Army Engineer Waterways Experiment Station ATTN: Dr. P. Hadala Dr. B. Rohani PO Box 631 Vicksburg, MS 39180	1	Commander US Army Aviation Research and Development Command ATTN: DRSV-E 12th and Spruce Streets St. Louis, MO 63166

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	1	Commander TARADCOM Tank-Automotive Systems Laboratory ATTN: T. Dean Warren, MI 48090
1	Commander US Army Communications Research and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703	7	Director US Army Materials and Mechanics Research Center ATTN: DRXMR-T, Mr. J. Bluhm Mr. J. Mescall Dr. M. Lenoe R. Shea F. Mascianica E. Quigley DRXMR-ATL Watertown, MA 02172
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703		
2	Commander US Army Missile Research and Development Command ATTN: DRDMI-R DRDMI-RBL Redstone Arsenal, AL 35809	1	Commander US Army Research Office ATTN: Dr. E. Saibel Dr. G. Mayer PO Box 12211 Research Triangle Park NC 27709
1	Commander US Army Missile Research and Development Command ATTN: DRDMI-YDL Redstone Arsenal, AL 35809	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL (Tech Lib) White Sands Missile Range NM 88002
1	Commander US Army Tank-Automotive Re- search and Development Command ATTN: DRDTA-UL Warren, MI 48090	1	Office of Naval Research Department of the Navy ATTN: Code ONR 439, N. Perrone 800 North Quincy Street Arlington, VA 22217
1	Commander US Army Tank-Automotive Re- search and Development Command ATTN: V. H. Pagano Warren, MI 48090	3	Commander Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
3	Commander Naval Ordnance Systems Command Washington, DC 20360	3	Director Naval Research Laboratory ATTN: Dr. C. Sanday Dr. H. Pusey Dr. F. Rosenthal Washington, DC 20375
2	Commander Naval Air Development Center, Johnsville Warminster, PA 18974	2	Superintendent Naval Postgraduate School ATTN: Dir of Lib Dr. R. Ball Monterey, CA 93940
1	Commander Naval Missile Center Point Mugu, CA 93041	2	ADTC/DLJW (Ms. C. Westmoreland/ Mr. W. Cook) Eglin AFB, FL 32542
2	Naval Ship Engineering Center ATTN: J. Schell Tech Lib Washington, DC 20362	1	AFML/LLN (Dr. T. Nicholas) Wright-Patterson AFB, OH 45433
1	Commander & Director David W. Taylor Naval Ship Research & Development Center Bethesda, MD 20084	1	Lawrence Livermore Laboratory PO Box 808 ATTN: Dr. D. M. Norris Livermore, CA 94550
2	Commander Naval Surface Weapons Center ATTN: Dr. W. G. Soper Mr. N. Rupert Dahlgren, VA 22448	1	Lawrence Livermore Laboratory PO Box 808 ATTN: Dr. M. L. Wilkins Livermore, CA 94550
2	Commander Naval Surface Weapons Center Silver Spring, MD 20084	1	Lawrence Livermore Laboratory PO Box 808 ATTN: Dr. R. Werne Livermore, CA 94550
7	Commander Naval Weapons Center ATTN: Code 31804, Mr. M. Keith Code 326, Mr. P. Cordle Code 3261, Mr. T. Zulkoski Code 3181, John Morrow Code 3261, Mr. C. Johnson Code 3171, Mr. B. Galloway Code 3831, Mr. M. Backman China Lake, CA 93555	4	Los Alamos Scientific Laboratory PO Box 1663 ATTN: Dr. R. Karpp Dr. J. Dienes Dr. J. Taylor Dr. E. Fugelso Los Alamos, NM 87545

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
3	Sandia Laboratories ATTN: Dr. W. Herrmann Dr. L. Bertholf Dr. A. Chabai Albuquerque, NM 87115	1	Computer Code Consultants, Inc. 1680 Camino Redondo ATTN: Dr. Wally Johnson Los Alamos, NM 87544
1	Headquarters National Aeronautics and Space Administration Washington, DC 20546	1	Dupont Experimental Labs ATTN: Dr. Carl Zweben Wilmington, DE 19801
1	Director National Aeronautics and Space Administration Langley Research Center Langley Station Hampton, VA 23365	1	Effects Technology Inc 5383 Hollister Avenue PO Box 30400 Santa Barbara, CA 93105
1	Aeronautics Research Associates of Princeton, Inc 50 Washington Road Princeton, NJ 08540	2	Falcon R&D Thor Facility ATTN: Mr. D. Malick Mr. J. Wilson 696 Fairmount Avenue Baltimore, MD 21204
2	Aerospace Corporation 2350 E. El Segundo Blvd ATTN: Mr. L. Rubin Mr. L. G. King El Segundo, CA 90009	1	FMC Corporation Ordnance Engineering Div San Jose, CA 95114
2	Battelle Columbus Laboratories ATTN: Dr. M. F. Kanninen Dr. G. T. Hahn 505 King Avenue Columbus, OH 43201	1	General Electric Company Armament Systems Dept Burlington, VT 05401
1	Boeing Aerospace Company ATTN: Mr. R. G. Blaisdell (M.S. 40-25) Seattle, WA 98124	1	President General Research Corporation ATTN: Lib McLean, VA 22101
		1	Goodyear Aerospace Corp. 1210 Massillon Rd Akron, OH 44315
		1	H. P. White Laboratory 3114 Scarboro Road Street, MD 21154

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
3	Honeywell, Inc Government & Aerospace Products Division ATTN: Mr. J. Blackburn Dr. G. Johnson Mr. R. Simpson 600 Second Street, NE Hopkins, MN 55343	1	Science Applications Inc 101 Continental Blvd Suite 310 El Segundo, CA 90245
1	International Applied Physics, Inc 2400 Glenheath Drive ATTN: Mr. H. F. Swift Kettering, OH 45440	1	Ship Systems, Inc. 11750 Sorrento Valley Road ATTN: Dr. G. G. Erickson San Diego, CA 92121
1	Kaman Sciences Corp 1500 Garden of the Gods Road ATTN: Dr. P. Snow Colorado Springs, CO 80933	1	Systems, Science and Software, Inc PO Box 1620 ATTN: Dr. R. Sedgwick La Jolla, CA 92038
1	Lockheed Palo Alto Research Laboratory 3251 Hanover Street ATTN: Org. 5230, Bldg. 201 Mr. R. Roberson Palo Alto, CA 94394	1	US Steel Corp Research Center 125 Jamison Lane Monroeville, Pa 15146
1	Materials Research Laboratory Inc 1 Science Road Glenwood, IL 60427	1	Drexel University Department of Mechanical Engineering ATTN: Dr. P. C. Chou 32d and Chestnut Streets Philadelphia, PA 19104
2	McDonnell-Douglas Astronautics Co 5301 Bolsa Avenue ATTN: Dr. L. B. Greszczuk Dr. J. Wall Huntington Beach, CA 92647	1	New Mexico Institute of Mining and Technology ATTN: TERA Group Socorro, NM 87801
1	Pacific Technical Corp 460 Ward Drive ATTN: Dr. F. K. Feldmann Santa Barbara, CA 93105	1	Forrestall Research Center Aeronautical Engineering Laboratory Princeton University ATTN: Dr. A. Eringen Princeton, NJ 08540

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
3	Southwest Research Institute Department of Mechanical Sciences ATTN: Dr. U. Lindholm Dr. W. Baker Dr. R. White 8500 Culebra Road San Antonio, TX 78228		<u>Aberdeen Proving Ground</u> Cdr, USATECOM ATTN: Mr. W. Pless Mr. S. Keithley DRSTE-TO-F Dir, USAMSAA ATTN: Director, AMSAA DRXSYP-MP, H. Cohen
3	SRI International 333 Ravenswood Avenue ATTN: Dr. L. Seaman Dr. L. Curran Dr. D. Shockey Menlo Park, CA 94025		Dir, Wpns Sys Concepts Team Bldg. E3516, EA ATTN: DRDAR-ACW
2	University of Arizona Civil Engineering Department ATTN: Dr. D. A. DaDeppo Dr. R. Richard Tucson, AZ 86721		
1	University of California Department of Physics ATTN: Dr. Harold Lewis Santa Barbara, CA 93106		
2	University of Delaware Department of Mechanical Engineering ATTN: Prof. J. Vinson Dean I. Greenfield Newark, DE 19711		
1	University of Denver Denver Research Institute ATTN: Mr. R. F. Recht 2390 South University Boulevard Denver, CO 80210		

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet and return it to Director, US Army Ballistic Research Laboratory, ARRADCOM, ATTN: DRDAR-TSB, Aberdeen Proving Ground, Maryland 21005. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____
2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

