


AD-A081 535


OGDEN AIR LOGISTICS CENTER HILL AFB UT PROPELLANT LAB--ETC F/G 21/9.2
SURVEILLANCE REPORT. STAGE I DISSECTED MOTORS, PHASE XI. PROPEL--ETC(U)
NOV 79 J A THOMPSON
MANCP-427(79)

UNCLASSIFIED

NL

1 1
1 1
1 1





DISCLAIMER NOTICE

**THIS DOCUMENT IS BEST QUALITY
PRACTICABLE. THE COPY FURNISHED
TO DDC CONTAINED A SIGNIFICANT
NUMBER OF PAGES WHICH DO NOT
REPRODUCE LEGIBLY.**

MANCP REPORT NR 427(79)
MMWRM PROJECT M82934C

(6) SURVEILLANCE REPORT.
STAGE I DISSECTED MOTORS.
PHASE XI, PROPELLANT & COMPONENT TESTING.

Author

(12) 952 *John A. Thompson* (10) John A. Thompson
JOHN A. THOMPSON, Chemist
Component & Combustion Test Unit

(9) Semi-annual rept.

Engineering & Statistical Review By

John K. Scambia
JOHN K. SCAMBIA, Project Engineer
Service Engineering

Edward J. Erickson
EDWARD J. ERICKSON, Statistician
Data Analysis Unit

Recommended Approval By

Ronald F. Larsen
RONALD F. LARSEN, Chief
Physical & Mechanical Test Unit

Leonidas A. Brown
LEONIDAS A. BROWN, Chief
Component & Combustion Test Unit

Approved By

Don F. Woods
DON F. WOODS, Chief
Propellant Laboratory Section

(14) MANCP-427(79)

(11) Nov 1979

Industrial Products & Ldg Gear Division
Directorate of Maintenance
Ogden Air Logistics Center
United States Air Force
Hill Air Force Base, Utah 84056

407387

ABSTRACT

Testing was performed to determine the useful shelf/service life for LGM-30 Stage I Rocket Motors. A three year storage program for propellant and components was started in May 1961. This program was then extended to a ten year study and later continued indefinitely to assure that a deterioration in motor physical characteristics could be detected in time to take some corrective actions before the weapon system performance deteriorated below an acceptable level.

This report covers only propellant data and limited case bond data. The malfunction of an environmental chamber destroyed component samples that had originally been part of this testing program (and the inadvertent burning of some motors during dissection reduced the material available for testing). Planned dissection of selected motors in the future will provide samples for continued component testing. Test specimens for this reporting period were obtained from motors STM-012, 0012099, and 0012199. UP-7775 block propellant was not tested since that propellant has been used up.

Regression analyses were made using all data accumulated through this test period. Unique plotting symbols were used so that each motor and block propellant can be identified in the regression analysis. The plotting symbols for each motor and block propellant are listed in the statistical analyses section.

The data from this test period was combined with data from previous testing and entered into the G085 computer for storage, analysis, and regression analysis. From the statistical analysis of all data tested to date, significant degradation of the propellant does not appear likely for at least two years past the oldest data point.

Future testing will be conducted on dissected motors.

TABLE OF CONTENTS

	<u>Page</u>
Abstract	ii
List of Figures	iv
Glossary of Terms and Abbreviations	vii
Introduction	1
Table 1, Test Program	3
Statistical Approach	5
Test Results	7
Conclusions	10
Recommendations	11
Distribution List	84
DD1473	85

Account No. 1

Account No. 2

Account No. 3

Account No. 4

Account No. 5

Account No. 6

Account No. 7

Account No. 8

Account No. 9

Account No. 10

Account No. 11

Account No. 12

Account No. 13

Account No. 14

Account No. 15

Account No. 16

Account No. 17

Account No. 18

Account No. 19

Account No. 20

Account No. 21

Account No. 22

Account No. 23

Account No. 24

Account No. 25

Account No. 26

Account No. 27

Account No. 28

Account No. 29

Account No. 30

Account No. 31

Account No. 32

Account No. 33

Account No. 34

Account No. 35

Account No. 36

Account No. 37

Account No. 38

Account No. 39

Account No. 40

Account No. 41

Account No. 42

Account No. 43

Account No. 44

Account No. 45

Account No. 46

Account No. 47

Account No. 48

Account No. 49

Account No. 50

Account No. 51

Account No. 52

Account No. 53

Account No. 54

Account No. 55

Account No. 56

Account No. 57

Account No. 58

Account No. 59

Account No. 60

Account No. 61

Account No. 62

Account No. 63

Account No. 64

Account No. 65

Account No. 66

Account No. 67

Account No. 68

Account No. 69

Account No. 70

Account No. 71

Account No. 72

Account No. 73

Account No. 74

Account No. 75

Account No. 76

Account No. 77

Account No. 78

Account No. 79

Account No. 80

Account No. 81

Account No. 82

Account No. 83

Account No. 84

Account No. 85

Account No. 86

Account No. 87

Account No. 88

Account No. 89

Account No. 90

Account No. 91

Account No. 92

Account No. 93

Account No. 94

Account No. 95

Account No. 96

Account No. 97

Account No. 98

Account No. 99

Account No. 100

Account No. 101

Account No. 102

Account No. 103

Account No. 104

Account No. 105

Account No. 106

Account No. 107

Account No. 108

Account No. 109

Account No. 110

Account No. 111

Account No. 112

Account No. 113

Account No. 114

Account No. 115

Account No. 116

Account No. 117

Account No. 118

Account No. 119

Account No. 120

Account No. 121

Account No. 122

Account No. 123

Account No. 124

Account No. 125

Account No. 126

Account No. 127

Account No. 128

Account No. 129

Account No. 130

Account No. 131

Account No. 132

Account No. 133

Account No. 134

Account No. 135

Account No.

LIST OF FIGURES

<u>Figure Nr</u>		<u>Page</u>
	Regression Plot, Low Rate Tensile, 2 in/min	
1	Strain at Maximum Stress	13
2	Maximum Stress	14
3	Strain at Rupture	15
4	Stress at Rupture	16
5	Modulus	18
	Regression Plot, Low Rate Tensile, 20 in/min	
6	Strain at Maximum Stress	20
7	Maximum Stress	21
8	Strain at Rupture	22
9	Stress at Rupture	23
10	Modulus	24
	Regression Plot, High Rate Tensile	
11	Strain at Maximum Stress	26
12	Maximum Stress	27
13	Strain at Rupture	28
14	Stress at Rupture	29
15	Modulus	30
	Regression Plot, High Rate Triaxial Tensile, 600 psi	
16	Strain at Maximum Stress	32
17	Maximum Stress	33
18	Strain at Rupture	34

LIST OF FIGURES (cont)

<u>Figure Nr</u>		<u>Page</u>
19	Stress at Rupture	35
20	Modulus	36
21	Regression Plot, Casebond Tensile	38
	Regression Plot, Creep, 10 lb load	
22	Compliance at 10 sec	40
23	Compliance at 20 sec	41
24	Compliance at 1000 sec	42
25	Compliance at 10,000 sec	44
	Regression Plot, Creep, 12 lb load	
26	Compliance at 10 sec	46
27	Compliance at 20 sec	47
28	Compliance at 1000 sec	48
29	% Strain at Rupture	50
	Regression Plot, Stress Relaxation 3% Strain	
30	Modulus at 10 sec	52
31	Modulus at 50 sec	53
32	Modulus at 100 sec	54
33	Modulus at 1000 sec	55
	Regression Plot, Stress Relaxation 5% Strain	
34	Modulus at 10 sec	57
35	Modulus at 50 sec	58
36	Modulus at 100 sec	59
37	Modulus at 1000 sec	60

LIST OF FIGURES (cont)

<u>Figure Nr</u>		<u>Page</u>
38	Regression Plot, Constant Strain	62
39	Regression Plot, Hardness, Shore A, 10 sec	64
	Regression Plot, Dynamic Response	
40	Loss Tangent at 200 Hz	66
41	Loss Tangent at 400 Hz	67
42	Storage Shear Modulus at 200 Hz	68
43	Storage Shear Modulus at 400 Hz	69
44	Regression Plot, Burn Rate, 500 psi	71
45	Regression Plot, Burn Rate, 1000 psi	73
46	Regression Plot, Heat of Explosion	75
47	Regression Plot, Ignitability	77
	Regression Plot, Differential Thermal Analysis, 12°C rise/min	
48	Endotherm 1	79
49	Exotherm 1	80
50	Ignition Temperature	82
51	Failure Envelope, Motor S/N STM-012	83

GLOSSARY OF TERMS AND ABBREVIATIONS

Aging Trend	A change in properties or performance resulting from aging of material or component
CSA	Cross Sectional Area
DB	Dogbone
Degradation	Gradual deterioration of properties or performance
E	Modulus (psi), defined as stress divided by strain along the initial linear portion of the curve.
EB	End Bonded
EGL	Effective Gage Length
em	Strain at maximum stress
er	Strain at rupture
"F" ratio	The ratio of the variance accounted for by the regression function to the random unexplained variance. The regression function having the most significant "F" ratio is used for plotting data. The ratio is also used in detecting significant changes in random variation between succeeding time points
JANNAF	Joint Army, Navy, NASA, Air Force Committee
MANCP	Propellant Lab Section at Ogden Air Logistics Center
Ogden ALC	Ogden Air Logistics Center, Air Force Logistics Command
r or R	The Correlation Coefficient is a measure of the degree of closeness of the linear relationship between two variables
Regression Equation	The general form of the regression equation is $Y = a + bx$
Regression Line	Line representing mean test values with respect to time
S_b	Standard error of estimate of the regression coefficient

GLOSSARY OF TERMS AND ABBREVIATIONS (cont)

S_e or $S_{y.X}$	Standard deviation of the data about the regression line
S_m	Maximum Stress
S_r	Stress at rupture
Standard Deviation (S_y)	Square root of variance
Strain Rate	Crosshead speed divided by the EGL
"t" test	A statistical test used to detect significant differences between a measured parameter and an expected value of the parameter (determines if regression slope differs from zero at the 95% confidence level)
Variance	The sum of squares of deviations of the test results from the mean of the series after division by one less than the total number of test results
3 Sigma Band	The area between the upper and lower 3 sigma limit. It can be expected that 99.73% of the inventory represented by the test samples would fall within this range assuming that the population is normally distributed.
90-90 Band	It can be stated with 90% confidence that 90% of the inventory represented by the test samples would fall within this range assuming that the population is normally distributed

INTRODUCTION

A. PURPOSE:

This report contains test data from samples of LGM-30 Stage I, Wings I-V TP-H1011 propellant and case bond specimens. Testing was performed by the Propellant Laboratory Section (MANCP) for the Engineering and Reliability Branch of the Airmunitions Management Division (MMWRM) under Project M82934C-WNL17514. This report is the eleventh in this series. Data from this test period and propellant test data from the ten previous reports were entered into the G085 computer for regression analysis. The regressions are shown in this report.

B. TEST PROGRAM:

The LGM-30 Laboratory and Component Program includes the testing of materials used in the main case and main grain propellant. This report covers TP-H1011 propellant and case bond specimens. Table I outlines the test program.

Propellant for testing was obtained from three dissected motors; STM-012, a motor prepared by Thiokol specifically for dissection; S/N 0012099, a SLIM motor and S/N 0012199 which was selected for dissection. UP-7775 block propellant which had been tested during previous test periods was not tested at this test period as it was used up during the last test period.

C. HISTORICAL BACKGROUND:

In May 1961, Thiokol began a three year LGM-30 laboratory storage and test program to determine the rate of degradation with age for Stage I materials. During June 1962 and again in August 1963, additional samples were included. New samples were added in July and August 1964 when the

surveillance testing program was extended to ten years (Test Plan 0717-62-0967, 53-8). Carton block propellant, batch UP-7775, containing TP-H1011 propellant cast in March 1962 was added to the program in 1964.

Samples added to the inventory in 1964 were considered to be a new population, but were combined in regression analysis with the three dissected motors. The history of testing of these materials is found in MQQP Report Nrs. 109A(67), 144(68), 208(71), and MANCP Report 358(76). Physical transfer of the specimens from Thiokol to Ogden ALC was made in June 1967.

TABLE I
TEST PROGRAM

All Temperatures in Fahrenheit
Motors STM-012, S/N 0012099, S/N 0012199

(Block Propellant UP-7775 was included in this portion
of the test program in previous test periods)

<u>Test</u>	<u>Conditions</u>	<u>Spec/Cond</u>	<u>Spec Config</u>
Tensile	77°, 2.0 & 20 in/min	5 ea	JANNAF Dogbone
Creep	77°, 10 & 12 lb load	3 ea	JANNAF Dogbone
Stress Relax	77°, 3 & 5% strains	3 ea	1/2" x 1/2" x 4"
Strain Dilatation	77°, .25 in/ in/min	3 ea	1/2" x 1/2" x 4"
Hardness	77°, initial & 10 seconds	5 ea	Dogbone Ends
HOE	77°	3 ea	1/2' x 3/8" x 1"
Burning Rate	77°, 500 & 1000 psi	5 ea	.156" x .156" x 5"
DTA	77° start	3 ea	0.040" wafer
Ignitability	77°, 168 cal/ cm ² - sec	3 ea	0.050" wafer
Sol Gel	77°	6 ea	1/2" x 1/2" x 1/2"

UP-7775 was NOT included in this portion of the test program
in previous test periods.

High Rate Tensile	77°, 1000 in/in/min	5 ea	3/4" GL Dogbone
High Rate Triaxial Ten	77°, 1000 in/in/ min, 600 psi	3 ea	3/4" GL Rail
Dynamic Response	77°, 70 gm ct. wt.	3 ea	3.3" x 3.3" x 0.690" disc
Biaxial Constant Strain	77°	3 ea	3/4" GL Rail

TABLE I (cont)

<u>Test</u>	<u>Conditions</u>	<u>Spec/Cond</u>	<u>Spec Config</u>
Failure Envelope	Temp: -50°, -20°, 10°, 40°, 77°, 130° & 180°F at a rate of 0.2, 2.0 & 20 in/min	3 ea	JANNAF Dogbone
STM-012 and S/N 0012199 only were used for the following tests:			
Case Bond Tensile	77°, 0.2 in/min	10 ea	1" x 5/8" x 3/4"
Tear Energy	77°F ± 2°	8 ea	0.1" x 1.18" x 3"
Poisson's Ratio (Strain Dila- tation)	77°F ± 2° 10, 15, 20, 25, 30%	6 per/ condition	0.50" x 0.50" x 4"

STATISTICAL ANALYSIS

The objective of this statistical analysis was to determine whether or not any aging trends are demonstrated by accumulated test data in order to assist Service Engineering to more accurately predict motor serviceability.

Propellant was made available for testing and statistical analysis was performed on the resultant data in order to obtain an overall view of the aging trends affecting the First Stage Dissected Motor Program. The sampling consisted of data from two dissected operational motors (0012099 and 0012199), and one motor (STM-012) which was prepared by Thiokol specifically for the dissection program. In addition, carton propellant data (batch UP-7775) which was tested previously was included in the regression analyses.

A Multi-symbol Regression Analysis Program was used to determine aging trends. The sampling is combined for each test parameter in a single regression analysis. The linear equation ($Y = a + bX$) was found to be the best fit model for the data in this report. A composite population aging trend line is then calculated accepting the fact that individual aging of different populations may be masked.

The Multi-symbol Program uses a unique plotting code for each motor and carton data on the regression plots. This method of data plotting allows a visual display of the overall relationship between the various origins of data and how they relate to the overall least square aging trend line.

The regression program uses an analysis with individual data points from different time periods combined to establish a least squares aging trend line for the overall data. The variance about the regression line, obtained using individual values of the dependent variable, was used to compute a tolerance interval such that at the 90% confidence level 90% of the population falls within this interval. This tolerance interval was

extrapolated to a maximum of 24 months to give an indication of the statistical significance of the slope of any aging trends. The computer tolerance interval about the composite regression line is wider than what the tolerance interval would be about any individual motor or carton regression line because of the increased data spread introduced by combining different populations of data. The "t" values and the significance of this statistic, which are reported for each regression model, gives an indication of the "statistical significance" of the slope of the aging trend in the Y-axis. Data and regression trend lines were plotted utilizing an IBM-360/65 computer.

ORIGIN SYMBOL TABLE

<u>Origin</u>	<u>DOM</u>	<u>Wing</u>	<u>Symbol</u>
Motor 0012099	63166	2	0
Motor 0012199	63227	2	1
Motor STM-012	61221	1	S
* Carton UP-7775	62075	1	U

* The last of carton UP-7775 block propellant was used up on the previous testing period. No new data for UP-7775 will appear in this report.

TEST RESULTS

Regression analysis is the method of evaluation used in the analysis of the test results.

A. TENSILE:

Low rate tensile test data at 2.0 in/min shows a statistically significant gradual decrease for strain at maximum stress and strain at rupture. Maximum stress and stress at rupture do not show a significant change. The modulus shows a statistically significant increase (Figures 1 thru 5).

The 20 in/min low rate tensile test data shows a statistically significant decrease for the strain at maximum stress, strain at rupture and stress at rupture. Maximum stress and modulus do not show a significant change (Figures 6 thru 10).

No significant change is shown for the high rate regressions (Figures 11 thru 15).

High rate triaxial testing shows a statistically significant increase for the strains with the stresses showing no significant change. Modulus shows a statistically significant decrease (Figures 16 thru 20).

Case bond tensile data shows no significant change (Figure 21). For this test period 10 specimens were tested. The failure mode for all specimens was 100% adhesive, liner to propellant.

B. CREEP:

For the 10 pound load test data the regressions show a statistically significant decrease except for the 1000 second regression which shows no significant change (Figures 22 thru 25).

For the 12 pound load a statistically significant decrease in creep compliance is shown for the 10 and 20 second regressions (Figures 26 and 27). The 1000 second and strain at rupture regressions do not show a significant change (Figures 28 and 29).

C. STRESS RELAXATION:

Stress relaxation modulus for both 3% and 5% strain shows no significant change except for 5% strain at 10 seconds which shows a statistically significant increase (Figures 30 thru 37).

D. CONSTANT STRAIN:

A statistically significant decrease is shown for constant strain (Figure 38).

E. SHORE HARDNESS:

The Shore A ten second hardness shows no significant change (Figure 39).

F. DYNAMIC RESPONSE:

The loss tangent regression for 200 and 400 Hz show a non-significant trend. The storage shear modulus at 200 and 400 Hz shows a statistically significant decrease (Figures 40 thru 43).

PHYSICAL TESTING SUMMARY:

Where statistically significant changes are shown, the trends are gradual. These trends indicate that the propellant's physical properties have a higher tensile strength with less elasticity.

G. BURNING RATE:

A statistically significant decrease is shown for both the 500 and 1000 psi testing (Figures 44 and 45).

H. HEAT OF EXPLOSION (HOE):

The HOE regression does not show a significant change (Figure 46).

I. IGNITABILITY:

No significant change is seen in the data (Figure 47).

J. DIFFERENTIAL THERMAL ANALYSIS (DTA):

The endotherm does not show a significant change (Figure 48). The exotherm shows a statistically significant decrease and the ignition temperature shows a statistically significant increase (Figures 49 and 50).

K. FAILURE ENVELOPE:

The failure envelope for Motor STM-012 is shown in Figure 51.

CONCLUSIONS

The test results show that, under present storage conditions, some of the physical/mechanical and combustion properties of the propellant indicate statistically significant aging trends. On some regressions where a significant trend is indicated, the slope of the trend line is quite gradual and no operational problems are expected. On other regressions, i.e., triaxial tensile and burning rate, the slope of the trend line appears quite steep although, in reality, the percent change is minor as indicated by the formulas found at the top of each figure. The Y-axis range is automatically varied by the data spread to provide visibility between individual data means. As a result, the range values (on Y-axis) must be considered when visually analyzing regression slopes.

Although some aging trends have been observed, it does not appear that any significant degradation will occur in the propellant within the next two years.

RECOMMENDATIONS

It is recommended that continued testing be conducted on the three dissected motors presently being tested and also on those motors selected for future dissection and testing by Service Engineering. On those motors selected for future dissection, testing should include the propellant, casebond specimens, and component materials.


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES	AGE (MONTHS)	NR SAMPLES
54.0	46	155.0	44
73.0	44	160.0	5
75.0	2	166.0	5
82.0	5	167.0	5
87.0	5	168.0	16
94.0	16	173.0	5
97.0	7	176.0	5
104.0	5	177.0	5
106.0	5	179.0	8
108.0	5	190.0	5
116.0	5	191.0	13
118.0	5	200.0	5
123.0	4	201.0	5
130.0	5	203.0	5
133.0	15	205.0	5
135.0	3	215.0	5
140.0	5		
144.0	5		
145.0	5		
146.0	2		
149.0	3		
150.0	10		
152.0	5		
153.0	5		
157.0	3		

STAGE 1 DISSECTED MUTUUS LOW NAFL CHSE-2.0 IN/MIN. STRAIN MAX STRESS


This sample size summary is applicable to figures 1 thru 4

$Y = ((+2.4330106E-01) + (-1.1451791E-04) * X)$
 $F = +1.5536899E+01$ SIGNIFICANCE OF F = SIGNIFICANT
 $R = -2.2513384E-01$ SIGNIFICANCE OF R = SIGNIFICANT
 $t = +3.9416873E+00$ SIGNIFICANCE OF t = SIGNIFICANT
 $N = 293$ DEGREES OF FREEDOM = 291
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH




STAGE 1 DISSECTED MOTORS, LOW RATE CHS=2.0 IN/MIN, STRAIN MAX STRESS

$Y = ((+1.1569131E+02) + (+1.4973637E-02) * X)$
 $F = +1.5338603E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $\sigma_r = +9.4346993E+00$
 $R = +7.2411047E-02$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_e = +1.2090225E-02$
 $t = +1.2384911E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_t = +9.4260864E+00$
 $N = 293$ DEGREES OF FREEDOM = 291
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH




$Y = ((+3.0434182E-01) + (-1.0860184E-04) * X)$
 $F = +9.1856379E+00$ SIGNIFICANCE OF F = SIGNIFICANT $\sigma = +2.8325859E-02$
 $R = -1.7492815E-01$ SIGNIFICANCE OF R = SIGNIFICANT $S_e = +3.5832949E-05$
 $t = +3.0307817E+00$ SIGNIFICANCE OF t = SIGNIFICANT $S_e = +2.7936986E-02$
 $N = 293$ DEGREES OF FREEDOM = 291
 STORAGE CONDITIONS = AMB TEMP/AH TEST CONDITIONS = 77 DEG/F AMB-AH



STAGE 1 DISSECTED MOTORS, LOW RATE CHS=2.0 IN/MIN, STRAIN AT RUPTURE

$Y = ((+1.1023772E+02) + (-1.5740562E-02) * X)$
 $F = +1.6116595E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $\sigma = +9.5874470E+00$
 $R = -7.4857169E-02$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_e = +1.2398912E-02$
 $t = +1.2695115E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_e = +9.5772468E+00$
 $N = 288$ DEGREES OF FREEDOM = 286
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



STAGE 1 DISSECTED MOTORS, LOW RATE CHS=2.0 IN/MIN, STRESS AT RUPTURE


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES	AGE (MONTHS)	NR SAMPLES
54.0	26	168.0	10
73.0	24	175.0	8
82.0	5	176.0	3
87.0	5	177.0	5
94.0	12	179.0	8
97.0	5	190.0	3
104.0	5	191.0	13
106.0	5	200.0	5
108.0	5	201.0	3
123.0	4	203.0	5
130.0	5	205.0	3
133.0	5	215.0	8
135.0	3		
144.0	5		
145.0	3		
146.0	2		
149.0	3		
150.0	10		
152.0	5		
153.0	5		
157.0	3		
159.0	24		
160.0	5		
166.0	5		
167.0	5		

STAGE 1 DISSECTED MOTORS, LOW RATE CHS=2.0 IN/MIN, MODULUS

This sample size summary is applicable to figure 5

$Y = ((+9.5653934E+02) + (+1.3464231E+00) * X)$
 $F = +2.0014327E+01$ SIGNIFICANCE OF F = SIGNIFICANT
 $R = +2.6640042E-01$ SIGNIFICANCE OF R = SIGNIFICANT
 $t = +4.4737375E+00$ SIGNIFICANCE OF t = SIGNIFICANT
 $N = 264$ DEGREES OF FREEDOM = 262
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



STAGE 1 DISSECTED MOTORS, LOW RATE CHS=2.0 IN/MIN, MODULUS


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES	AGE (MONTHS)	NR SAMPLES
82.0	2	177.0	2
97.0	5	179.0	8
104.0	2	190.0	3
106.0	5	191.0	13
108.0	5	200.0	3
110.0	5	201.0	3
118.0	5	203.0	5
123.0	5	205.0	3
130.0	5	215.0	9
133.0	14		
135.0	3		
140.0	5		
144.0	4		
145.0	3		
146.0	2		
150.0	9		
152.0	3		
153.0	5		
157.0	7		
160.0	5		
166.0	2		
167.0	7		
168.0	15		
175.0	8		
176.0	3		

STAGE 1 DISSECTED METERS, LOW RATE CHS=20.0 IN/MIN, STAIN MAX STRESS


This sample size summary is applicable to figures 6 thru 10

$F = +2.5942273E+01$
 $R = -3.4903829E-01$
 $t = +5.0933558E+00$
 $N = 189$
 $Y = ((+2.8922151E-01) + (-2.5776174E-04) * X)$
 SIGNIFICANCE OF F = SIGNIFICANT
 SIGNIFICANCE OF R = SIGNIFICANT
 SIGNIFICANCE OF t = SIGNIFICANT
 DEGREES OF FREEDOM = 187
 STORAGE CONDITIONS = AMB TEMP/AH
 TEST CONDITIONS = AMB TEMP/AH




STAGE 1 DISSECTED MOTORS, LOW RATE CHS=20.0 IN/MIN, STRAIN MAX STRESS

$F = +1.1954123E+00$
 $R = -7.9699271E-02$
 $t = +1.0933491E+00$
 $N = 189$
 $Y = ((+1.5185560E+02) + (-3.4969619E-02) * X)$
 SIGNIFICANCE OF F = NOT SIGNIFICANT
 SIGNIFICANCE OF R = NOT SIGNIFICANT
 SIGNIFICANCE OF t = NOT SIGNIFICANT
 DEGREES OF FREEDOM = 187
 STORAGE CONDITIONS = AMB TEMP/RH
 TEST CONDITIONS = AMB TEMP/RH




STAGE 1 DISSECTED MOTORS, LOW RATE CHS=20.0 IN/MIN, MAXIMUM STRESS

$Y = ((+3.5128347E-01) + (-2.0961681E-04) \cdot X)$
 $F = +1.2051920E+01$ SIGNIFICANCE OF F = SIGNIFICANT
 $R = -2.4606222E-01$ SIGNIFICANCE OF R = SIGNIFICANT
 $t = +3.4715875E+00$ SIGNIFICANCE OF t = SIGNIFICANT
 $N = 189$ DEGREES OF FREEDOM = 187
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH




STAGE 1 DISSECTED MOTORS, LOW RATE CHS=20.0 IN/MIN, STRAIN AT RUPTURE

$Y = ((+1.5097648E+02) + (-7.6137325E-02) * X)$
 $F = +5.7450317E+00$ SIGNIFICANCE OF F = SIGNIFICANT $\sigma = +1.3915751E+01$
 $R = -1.7264524E-01$ SIGNIFICANCE OF R = SIGNIFICANT $S_0 = +3.1765185E-02$
 $t = +2.3968795E+00$ SIGNIFICANCE OF t = SIGNIFICANT $S_t = +1.3743393E+01$
 $N = 189$ DEGREES OF FREEDOM = 187
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



STAGE 1 DISSECTED MOTORS, LOW RATE CHS=20.0 IN/MIN, STRESS AT RUPTURE

$Y = ((+1.4525591E+03) + (+1.8641017E+00) \times X)$
 $F = +1.9694886E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G = +4.6785490E+02$
 $R = +1.1498152E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +1.3282899E+00$
 $t = +1.4033847E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_1 = +4.6633003E+02$
 $N = 149$ DEGREES OF FREEDOM = 147
 STORAGE CONDITIONS = AMB TEMP/AH TEST CONDITIONS = AMB TEMP/AH



STAGE 1 DISSECTED MOTORS, LOW RATE CHS=20.0 IN/MIN, MODULUS


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
60.0	5
71.0	4
80.0	16
83.0	5
93.0	5
105.0	5
107.0	5
109.0	5
116.0	5
118.0	6
131.0	5
134.0	5
136.0	4
141.0	5
144.0	5
146.0	5
151.0	5
154.0	5
158.0	5
176.0	5
177.0	5
179.0	5
191.0	5
201.0	5

STAGE 1 DISSECTED MUTJRS, HIGH RATE. CHE=1/50 IN/MIN, STRAIN MAX STRESS

This sample size summary is applicable to figures 11 thru 15


F = +2.9887453E-01
 R = -4.7529843E-02
 t = +5.4669418E-01
 N = 134
 STORAGE CONDITIONS = AMB TEMP/RH
 Y = ((+1.9805905E-01) + (-6.5086470E-05) * X)
 SIGNIFICANCE OF F = NOT SIGNIFICANT
 SIGNIFICANCE OF R = NOT SIGNIFICANT
 SIGNIFICANCE OF t = NOT SIGNIFICANT
 DEGREES OF FREEDOM = 132
 TEST CONDITIONS = AMB TEMP/RH
 G₁ = +5.2902575E-02
 S₁ = +1.1905462E-04
 S₂ = +5.3042570E-02



STAGE 1 DISSECTED MOTORS, HIGH RATE (HS-1750 IN/MIN, STRAIN MAX STRESS

$Y = ((+3.3004735E+02) + (+5.0355839E-02) * X)$
 $F = +3.2981531E-01$ SIGNIFICANCE OF F = NOT SIGNIFICANT $\sigma_e = +3.8966891E+01$
 $R = +4.9923676E-02$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_e = +8.7682804E-02$
 $t = +5.7429549E-01$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_e = +3.9065440E+01$
 $N = 134$ DEGREES OF FREEDOM = 132
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH


PARAMETER = MAXIMUM STRESS
 UNIT OF MEASURE = PSI



STAGE 1 DISSECTED MOTORS, HIGH RATE CHS=1750 IN/MIN, MAXIMUM STRESS


Figure 12

$F = +1.5721399E-02$ SIGNIFICANCE OF $F =$ NOT SIGNIFICANT $G_r = +2.9858110E-02$
 $R = +1.0912713E-02$ SIGNIFICANCE OF $R =$ NOT SIGNIFICANT $S_0 = +6.7266219E-05$
 $t = +1.2538500E-01$ SIGNIFICANCE OF $t =$ NOT SIGNIFICANT $S_t = +2.9969211E-02$
 $N = 134$ DEGREES OF FREEDOM = 132
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH




STAGE 1 DISSECTED MOTORS, HIGH RATE CHS-1750 IN/MIN, STRAIN AT RUPTURE

$Y = ((+2.9059879E+02) + (+1.0627994E-02) * X)$
 $F = +1.3780131E-02$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G_1 = +4.0187108E+01$
 $R = +1.0216850E-02$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +9.0536696E-02$
 $t = +1.1738880E-01$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_E = +4.0336939E+01$
 $N = 134$ DEGREES OF FREEDOM = 132
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



STAGE 1 DISSECTED MOTORS, HIGH RATE CHS=1750 IN/MIN, STRESS AT RUPTURE

$Y = ((+6.8196621E+03) + (-1.3850396E+00) * X)$
 $F = +9.7651643E-02$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G_r = +1.9679880E+03$
 $R = -2.7188937E-02$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_g = +4.4322315E+00$
 $t = +3.1249262E-01$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_r = +1.9746982E+03$
 $N = 134$ DEGREES OF FREEDOM = 132
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



STAGE 1 DISSECTED MOTORS, HIGH RATE CHS-1750 IN/MIN, MODULUS


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
71.0	2
72.0	8
83.0	2
93.0	2
105.0	2
108.0	2
110.0	2
132.0	2
134.0	4
136.0	2
144.0	2
146.0	2
151.0	2
153.0	2
158.0	2
168.0	2
175.0	2
177.0	2
179.0	3
191.0	2
201.0	2
215.0	2

DISSECTED TP-F1011, H.R. TRIAXIAL CHS=1750 IN/MIN, 600 PSI, STRAIN MAX STRESS

This sample size summary is applicable to figures 16 thru 20


$Y = ((+1.1261087E-01) + (+8.0573295E-04) * X)$
 $F = +9.0832291E+01$ SIGNIFICANCE OF F = SIGNIFICANT $G_1 = +4.5605798E-02$
 $R = +7.8121675E-01$ SIGNIFICANCE OF R = SIGNIFICANT $S_0 = +8.4541702E-05$
 $t = +9.5305976E+00$ SIGNIFICANCE OF t = SIGNIFICANT $S_t = +2.8714250E-02$
 $N = 60$ DEGREES OF FREEDOM = 58
 STORAGE CONDITIONS = 9MB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



DISSECTED TP-HIC11 4.R. TRIAXIAL CHS-1750 IN/MIN. 600 PSI. STRAIN MAX STRESS

Figure 16

$F = +7.7969329E-01$
 $R = +1.1517235E-01$
 $t = +8.8300243E-01$
 $N = 60$
 $Y = ((+5.7870198E+02) + (+1.2683691E-01) * X)$
 SIGNIFICANCE OF F = NOT SIGNIFICANT
 SIGNIFICANCE OF R = NOT SIGNIFICANT
 SIGNIFICANCE OF t = NOT SIGNIFICANT
 DEGREES OF FREEDOM = 58
 STORAGE CONDITIONS = AMB TEMP/RH
 TEST CONDITIONS = AMB TEMP/RH




DISSECTED TP-H1011, H.R. TRIAXIAL CHS-1750 IN/MIN, 600 PSI, MAXIMUM STRESS

Figure 17

$F = +6.1982806E+01$
 $R = +7.1874710E-01$
 $t = +7.8729160E+00$
 $N = 60$

$Y = ((+1.7521722E-01) + (+6.8298188E-04) * X)$
 SIGNIFICANCE OF F = SIGNIFICANT
 SIGNIFICANCE OF R = SIGNIFICANT
 SIGNIFICANCE OF t = SIGNIFICANT
 DEGREES OF FREEDOM = 58


STORAGE CONDITIONS = AMB TEMP/RH
 TEST CONDITIONS = AMB TEMP/RH



DISSECTED TP-H1011, H.R. TRIAXIAL CHS-1750 IN/MIN, 600 PSI, STRAIN AT RUPTURE

Figure 18

$F = +2.0776780E+00$ SIGNIFICANCE OF $F =$ (+2.2843569E-01) * X)
 $R = +1.8596557E-01$ SIGNIFICANCE OF $R =$ NOT SIGNIFICANT
 $t = +1.4414152E+00$ SIGNIFICANCE OF $t =$ NOT SIGNIFICANT
 $N = 60$ DEGREES OF FREEDOM = 58
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH




DISSECTED TP-H1011, H.R. TRIAXIAL CHS-1750 IN/MIN, 600 PSI, STRESS AT RUPTURE

Figure 19

$F = +4.5405634E+01$ SIGNIFICANCE OF F = SIGNIFICANT $G = +1.6750121E+03$
 $R = -6.6264781E-01$ SIGNIFICANCE OF R = SIGNIFICANT $S_0 = +3.7251636E+00$
 $t = +6.7383703E+00$ SIGNIFICANCE OF t = SIGNIFICANT $S_t = +1.2652369E+03$
 $N = 60$ DEGREES OF FREEDOM = 58
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH

UNIT OF MEASURE =
 MODULUS = PSI
 *10²



DISSECTED TP-H1011, H.R. TRIAXIAL CHS=1750 IN/MIN, 500 PSI, MODULUS

Figure 20


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
80.0	27
94.0	2
104.0	10
113.0	12
116.0	12
141.0	11
154.0	9
156.0	22
166.0	9
177.0	10
178.0	8
189.0	11
201.0	12
216.0	10

CASEBOND TENSILE, STAGE 1 DISSECTED, CHS 0.2, CSA 0.75

This sample size summary is applicable to figure 21

$F = +1.6712227E+01$ SIGNIFICANCE OF $F = (-1.4004663E-01) \times X)$
 $R = -3.0494980E-01$ SIGNIFICANCE OF $R =$ SIGNIFICANT
 $t = +4.0880591E+00$ SIGNIFICANCE OF $t =$ SIGNIFICANT
 $N = 165$ DEGREES OF FREEDOM = 163
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



CASEBOND TENSILE, STAGE 1 DISSECTED, CHS 0.2, CSA 0.75

Figure 21


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	N SAMPLES
72.0	2
76.0	3
84.0	2
87.0	2
94.0	2
99.0	2
106.0	3
108.0	1
123.0	1
130.0	1
132.0	2
134.0	2
144.0	2
146.0	2
149.0	2
151.0	4
153.0	3
157.0	1
160.0	2
166.0	3
167.0	4
168.0	2
173.0	2
176.0	1
196.0	3

DISSECTED MOUTH TP-H1011, CREEP 10 LB LOAD, COMPLIANCE AT 10 SEC.

This sample size summary is applicable to figures 22, 23 and 24


$Y = ((+1.4358396E-03) + (-2.5076507E-06) * X)$
 $F = +5.2549770E+00$ SIGNIFICANCE OF F = SIGNIFICANT $\sigma_r = +2.9806981E-04$
 $R = -2.9289686E-01$ SIGNIFICANCE OF R = SIGNIFICANT $S_e = +1.0939101E-06$
 $t = +2.2923736E+00$ SIGNIFICANCE OF t = SIGNIFICANT $S_f = +2.8753103E-04$
 $N = 58$ DEGREES OF FREEDOM = 56
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



DISSECTED MOTOR TP-H1011, CREEP 10 LB LOAD, COMPLIANCE AT 10 SEC.

Figure 22

$Y = ((+1.7160942E-03) + (-3.4971202E-06) * X)$
 F = +8.7004637E+00 SIGNIFICANCE OF F = SIGNIFICANT $\sigma_t = +3.3201578E-04$
 R = -3.6670556E-01 SIGNIFICANCE OF R = SIGNIFICANT $S_e = +1.1856032E-06$
 t = +2.9496548E+00 SIGNIFICANCE OF t = SIGNIFICANT $S_t = +3.1163230E-04$
 N = 58 DEGREES OF FREEDOM = 56
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



DISSECTED MOTOR TP-H1011, CREEP 10 LB LOAD, COMPLIANCE AT 20 SEC.

Figure 23

$F = +2.7021144E+00$
 $R = -2.1454826E-01$
 $t = +1.6438109E+00$
 $N = 58$

$Y = ((+2.3591670E-03) + (-3.0793456E-06) * X)$
 SIGNIFICANCE OF F = NOT SIGNIFICANT
 SIGNIFICANCE OF R = NOT SIGNIFICANT
 SIGNIFICANCE OF t = NOT SIGNIFICANT
 DEGREES OF FREEDOM = 56

STORAGE CONDITIONS = AMB TEMP/RH
 TEST CONDITIONS = AMB TEMP/RH




Figure 24


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
72.0	2
76.0	3
84.0	2
87.0	2
94.0	2
99.0	2
106.0	3
108.0	1
123.0	1
130.0	1
151.0	1
166.0	3
168.0	2
190.0	3

DISSECTED MOTOR TP-H1011, CREEP 10 LB LOAD, COMPLIANCE AT 10.000 SEC.

This sample size summary is applicable to figure 25

$Y = ((+3.3347181E-03) + (-5.7786479E-06) * X)$
 $F = +5.2715154E+00$ SIGNIFICANCE OF F = SIGNIFICANT
 $R = -4.0416440E-01$ SIGNIFICANCE OF R = SIGNIFICANT
 $t = +2.2959780E+00$ SIGNIFICANCE OF t = SIGNIFICANT
 $N = 29$ DEGREES OF FREEDOM = 27
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



DISSECTED MOTOR TP-H1011, CREEP 10 LB LOAD, COMPLIANCE AT 10,000 SEC.

Figure 25


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
72.0	2
76.0	2
84.0	2
87.0	2
94.0	2
99.0	2
106.0	2
108.0	1
123.0	1
130.0	1
132.0	2
134.0	2
144.0	2
146.0	2
149.0	2
151.0	2
153.0	3
157.0	2
160.0	2
166.0	3
167.0	1
168.0	6
175.0	2
190.0	3

DISSECTED MUTH TP-H1011, CREEP 12 LB LOAD, COMPLIANCE AT 10 SEC.

This sample size summary is applicable to figures 26, 27 and 28


$Y = ((+1.6931521E-03) + (-2.9228175E-06) * X)$
 $F = +4.5122739E+00$ SIGNIFICANCE OF F = SIGNIFICANT
 $R = -2.8510394E-01$ SIGNIFICANCE OF R = SIGNIFICANT
 $t = +2.1242113E+00$ SIGNIFICANCE OF t = SIGNIFICANT
 $N = 53$ DEGREES OF FREEDOM = 51
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



DISSECTED MOTOR TP-H1011, CREEP 12 LB LOAD, COMPLIANCE AT 10 SEC.

Figure 26

$F = +6.0666768E+00$
 $R = -3.2604995E-01$
 $t = +2.4630624E+00$
 $N = 53$
 $Y = ((+1.9888073E-03) + (-3.7685371E-06) * X)$
 SIGNIFICANCE OF F = SIGNIFICANT
 SIGNIFICANCE OF R = SIGNIFICANT
 SIGNIFICANCE OF t = SIGNIFICANT
 DEGREES OF FREEDOM = 51
 STORAGE CONDITIONS = AMB TEMP/RH
 TEST CONDITIONS = AMB TEMP/RH



DISSECTED MOTOR IP-H1011, CREEP 12 LB LOAD, COMPLIANCE AT 20 SEC.

Figure 27


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
84.0	2
87.0	2
99.0	2
106.0	3
108.0	1
123.0	1
130.0	1
160.0	3
168.0	3
190.0	3

TP-H1011 DISSECTED MOTORS, CREEP, X STRAIN AT RUPTURE, 12 LB LCAD

This sample size summary is applicable to figure 29

$Y = (1 + 2.4760104E+01) + (-1.8581941E-02) * X$
 $F = +2.8031291E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G_1 = +2.0388488E+00$
 $R = -3.5856024E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +1.1098634E-02$
 $t = +1.6742548E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_1 = +1.9527229E+00$
 $N = 21$ DEGREES OF FREEDOM = 19
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TMP/RH 12 LB



TP-H1011 DISSECTED MOTORS, CREEP, % STRAIN AT RUPTURE, 12 LB LOAD

*** SAMPLE SIZE SUMMARY ***


AGE (MONTHS)	NK SAMPLES	AGE (MONTHS)	NK SAMPLES
57.0	3	166.0	3
60.0	3	168.0	3
73.0	3	175.0	3
82.0	3	179.0	3
84.0	3	183.0	3
88.0	3	190.0	3
95.0	4	191.0	3
95.0	3	201.0	3
106.0	6	215.0	3
108.0	3		
116.0	3		
118.0	3		
123.0	3		
130.0	3		
132.0	3		
133.0	3		
134.0	3		
140.0	3		
144.0	4		
145.0	3		
150.0	3		
151.0	3		
153.0	3		
157.0	3		
160.0	3		

TP-H1011 DISSECTED MRS. STRESS RELAXATION MODULUS, 3 PERCENT STRAIN, 10 SEC

This sample size summary is applicable to figures 30 thru 33

$Y = ((+5.8790355E+02) + (+6.9088596E-01) * X)$
 $F = +3.7708901E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $\sigma_r = +1.5143158E+02$
 $R = +1.8126170E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +3.5578237E-01$
 $t = +1.9418790E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_t = +1.4959242E+02$
 $N = 113$ DEGREES OF FREEDOM = 111
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH

PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI
 *10¹




TP-H1011 DISSECTED MTR. STRESS RELAXATION MODULUS, 3 PERCENT STRAIN, 10 SEC

Figure 30

$Y = ((+4.6517958E+02) + (+4.4098723E-01) \times X)$
 $F = +2.3126787E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G = +1.2263763E+02$
 $R = +1.4286255E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +2.8998021E-01$
 $t = +1.5207494E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_1 = +1.2192521E+02$
 $N = 113$ DEGREES OF FREEDOM = 111
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH

PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI
 $\times 10^1$




TP HIGH DISSECTED MTRS. STRESS RELAXATION MODULUS, 3 PERCENT STRAIN, 50 SEC

Figure 31

$Y = ((+4.3269229E+02) + (+4.0101222E-01) * X)$
 $F = +2.2239511E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G_1 = +1.1367901E+02$
 $R = +1.4015011E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_1 = +2.6890259E-01$
 $t = +1.4912917E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_2 = +1.1306291E+02$
 $N = 113$ DEGREES OF FREEDOM = 111
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH


PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI
 *10¹



TP-H1011 DISSECTED MBS, STRESS RELAXATION MODULUS, 3 PERCENT STRAIN, 100 SEC

$Y = ((+3.4776978E+02) + (+2.9294790E-01) * X)$
 $F = +1.5693444E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G_4 = +9.3043753E+01$
 $R = +1.1967807E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +2.3384670E-01$
 $t = +1.2527348E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_1 = +9.2801701E+01$
 $N = 110$ DEGREES OF FREEDOM = 108
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH

PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI $\times 10^1$



TP-H1011 DISSEI IFD MTR. STRESS RELAXATION MODULUS, 3 PERCENT STRAIN, 1000 SEC

Figure 33

*** SAMPLE SIZE SUMMARY ***


AGE (MONTHS)	NR SAMPLES	AGE (MONTHS)	NR SAMPLES
57.0	3	166.0	3
60.0	3	168.0	3
73.0	3	175.0	3
82.0	3	179.0	3
84.0	3	183.0	3
88.0	3	190.0	3
95.0	4	191.0	3
99.0	3	201.0	3
106.0	3	215.0	3
108.0	3		
110.0	3		
118.0	3		
123.0	3		
130.0	3		
132.0	3		
133.0	3		
134.0	3		
140.0	3		
143.0	3		
145.0	3		
150.0	3		
151.0	3		
153.0	3		
157.0	3		
160.0	3		

TP-H1011 DISSECTED MTRG, STRESS RELAXATION MODULUS, 5 PERCENT STRAIN, 10 SEC

This sample size summary is applicable to figures 34 thru 37

$Y = ((+6.0175312E+02) + (+9.8159948E-01) * X)$
 F = +7.2317095E+00 SIGNIFICANCE OF F = SIGNIFICANT $G_1 = +1.5767702E+02$
 R = +2.4836931E-01 SIGNIFICANCE OF R = SIGNIFICANT $S_0 = +3.6501762E-01$
 t = +2.6891838E+00 SIGNIFICANCE OF t = SIGNIFICANT $S_1 = +1.5342896E+02$
 N = 112 DEGREES OF FREEDOM = 110
 STORAGE CONDITIONS = AMB TEMP/AH TEST CONDITIONS = AMB TEMP/AH

PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI
 *10¹




TP-H1011 DISSECTED MRS. STRESS RELAXATION MODULUS, 5 PERCENT STRAIN, 10 SEC

Figure 34

$Y = ((+4.6986566E+02) + (+4.3259681E-01) * X)$
 $F = +3.0296251E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G_r = +1.0541855E+02$
 $R = +1.6371870E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_g = +2.4853574E-01$
 $t = +1.7405818E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_t = +1.0446778E+02$
 $N = 112$ DEGREES OF FREEDOM = 110
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH

PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI
 *10¹




TP-H1011 DISPERSED MRS. STRESS RELAXATION MODULUS, 5 PERCENT STRAIN, 50 SEC

Figure 35

$Y = ((+4.371000E+02) + (+3.7731684E-01) * X1)$
 $F = +2.6511885E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $\sigma_1 = +9.8126386E+01$
 $R = +1.5340955E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +2.3173193E-01$
 $t = +1.6282470E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_1 = +9.7404585E+01$
 $N = 112$ DEGREES OF FREEDOM = 110
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH


PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI
 $\times 10^1$



TP-H1011 DISSECTED MTRS, STRESS RELAXATION MODULUS, 5 PERCENT STRAIN, 100 SEC

$Y = ((+3.4627346E+02) + (+2.9898389E-01) * X)$
 $F = +2.2535999E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $G_1 = +7.9478755E+01$
 $R = +1.4362185E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +1.9916333E-01$
 $t = +1.5011994E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_t = +7.9021461E+01$
 $N = 109$ DEGREES OF FREEDOM = 107
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH

PARAMETER = STRESS RELAX MODULUS
 UNIT OF MEASURE = PSI
 *10¹



TP-H1011 DISSECTED MTRS, STRESS RELAXATION MODULUS, 5 PERCENT STRAIN, 1000 SFC

Figure 37

*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NK SAMPLES
72.0	10
83.0	1
94.0	1
105.0	1
107.0	1
109.0	1
117.0	1
120.0	1
131.0	1
135.0	2
137.0	2
142.0	1
159.0	2

STAGE 1 USSCTU MTRS. CUNSTANT STRAIN. STRAIN 0.1 INIT AND 0.01 EVERY 48 HRS

This sample size summary is applicable to figure 38

$Y = ((+3.3048871E+01) + (-1.2955493E-01) * X)$
 $F = +5.2947397E+01$ SIGNIFICANCE OF F = SIGNIFICANT $G_1 = +4.9583209E+00$
 $R = -8.0381244E-01$ SIGNIFICANCE OF R = SIGNIFICANT $S_0 = +1.7804576E-02$
 $t = +7.2764962E+00$ SIGNIFICANCE OF t = SIGNIFICANT $S_1 = +3.0000443E+00$
 $N = 31$ DEGREES OF FREEDOM = 29
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH




Figure 38

*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES	AGE (MONTHS)	NR SAMPLES
71.0	5	175.0	5
82.0	5	178.0	10
86.0	5	183.0	10
93.0	1	188.0	10
97.0	5	189.0	10
104.0	5		
105.0	5		
107.0	5		
115.0	5		
117.0	5		
122.0	5		
130.0	5		
132.0	10		
134.0	5		
140.0	5		
143.0	5		
145.0	5		
149.0	5		
150.0	5		
152.0	5		
156.0	5		
160.0	5		
164.0	10		
167.0	5		
168.0	20		

STAGE 1 DISSECTED MTAS. SHOWED A PARABOLIC, 10 SECOND

This sample size summary is applicable to figure 39

$Y = ((+6.5521887E+01) + (+5.4514884E-03) \times X)$
 $F = +4.3875789E-01$ SIGNIFICANCE OF F = NOT SIGNIFICANT $\sigma^2 = +3.7754288E+00$
 $R = +4.8908537E-02$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_e = +8.2300499E-03$
 $t = +6.8238802E-01$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_t = +3.7811997E+00$
 $N = 185$ DEGREES OF FREEDOM = 183
 STORAGE CONDITIONS = AMB TEMP/AH TEST CONDITIONS = AMB TEMP/AH




Figure 39


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
71.0	3
83.0	2
93.0	1
103.0	2
108.0	2
111.0	2
127.0	2
129.0	2
133.0	2
135.0	2
137.0	2
151.0	2
152.0	2
153.0	2
159.0	2
169.0	1
170.0	2
173.0	1
176.0	1
178.0	2
180.0	1
202.0	2

STAGE I DISSECTED MUTING DYNAMIC RESPONSE CENTER-PT 70 GM LOSS TANG AT 200 HZ


This sample size summary is applicable to figures 40 thru 43

$F = +1.5163324E+00$ SIGNIFICANCE OF $F =$ (+2.4106331E-04) $\times X$ $\sigma_f = +4.3336176E-02$
 $A = +1.9357673E-01$ SIGNIFICANCE OF $A =$ NOT SIGNIFICANT $S_o = +1.9565174E-04$
 $i = +1.2322069E+00$ SIGNIFICANCE OF $i =$ NOT SIGNIFICANT $S_i = +4.3060061E-02$
 $N = 41$ DEGREES OF FREEDOM = 39
 STORAGE CONDITIONS = AMB TEMP/AM TEST CONDITIONS = AMB TEMP/AM



STAGE I DISSECTED MOTORS, DYNAMIC RESPONSE, CENTER-WT 70 GM, LOSS TANG AT 200 HZ


$Y = ((+5.9586513E-01) + (+5.2736039E-04) \times X)$
 F = +2.4892484E+00 SIGNIFICANCE OF F = NOT SIGNIFICANT $\alpha = +7.4779749E-02$
 R = +2.4540587E-01 SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +3.3358211E-04$
 t = +1.5808011E+00 SIGNIFICANCE OF t = NOT SIGNIFICANT $S_1 = +7.3416535E-02$
 N = 41 DEGREES OF FREEDOM = 39
 STORAGE CONDITIONS = AMB TEMP/PH TEST CONDITIONS = AMB TEMP/PH



STAGE 1 DISSECTED MOTORS, DYNAMIC RESPONSE, CENTER-NT 70 CM, LOSS TANG AT 400 HZ

Figure 41

$Y = ((+5.7460319E+03) + (-8.0604903E+00) \times X)$
 F = +4.9798307E+00 SIGNIFICANCE OF F = SIGNIFICANT $\sigma_1 = +8.3563830E+02$
 R = -3.3649647E-01 SIGNIFICANCE OF R = SIGNIFICANT $S_1 = +3.6210158E+00$
 t = +2.2315534E+00 SIGNIFICANCE OF t = SIGNIFICANT $S_2 = +7.9693253E+02$
 N = 41 DEGREES OF FREEDOM = 38
 STORAGE CONDITIONS = AMB TEMP/AM TEST CONDITIONS = AMB TEMP/AM



STAGE I DISSECTED MOTORS, DYNAMIC RESPONSE, CENTER-NT 70 GM, STOR SHEAR AT 400 HZ

Figure 43


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
74.0	18
83.0	6
89.0	6
97.0	6
98.0	6
103.0	6
106.0	5
108.0	5
118.0	5
120.0	5
123.0	5
135.0	5
142.0	5
152.0	6
154.0	6
168.0	6
169.0	6
170.0	6
176.0	6
179.0	6
181.0	6
185.0	6
193.0	6
204.0	6

STAGE 1 DISSECTED MOTORS, BURNING RATE AT 500 PSI INITIAL PRESSURE

This sample size summary is applicable to figure 44

$Y = ((+2.9725563E-01) + (-3.1024938E-04) * X)$
 $F = +1.0943720E+02$ SIGNIFICANCE OF F = SIGNIFICANT
 $R = -6.5326889E-01$ SIGNIFICANCE OF R = SIGNIFICANT
 $t = +1.0461223E+01$ SIGNIFICANCE OF t = SIGNIFICANT
 $N = 149$ DEGREES OF FREEDOM = 147
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



STAGE 1 DISSECTED MOTORS. BURNING RATE AT 500 PSI INITIAL PRESSURE


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES	AGE (MONTHS)	NR SAMPLES
74.0	6	176.0	6
83.0	6	179.0	6
85.0	6	181.0	6
97.0	6	185.0	6
98.0	6	193.0	6
105.0	6	204.0	6
106.0	5		
108.0	5		
118.0	5		
120.0	5		
123.0	5		
130.0	5		
135.0	5		
137.0	8		
139.0	5		
142.0	5		
145.0	6		
147.0	5		
152.0	5		
154.0	11		
161.0	5		
162.0	5		
164.0	6		
169.0	11		
170.0	6		

STAGE 1 DISSECTED MOTORS. TURNING RATE AT 1000 PSI INITIAL PRESSURE

This sample size summary is applicable to figure 45

$Y = ((+3.6623649E-01) + (-4.0923384E-04) * X)$
 $F = +1.3270419E+02$ SIGNIFICANCE OF F = SIGNIFICANT
 $R = -6.4833900E-01$ SIGNIFICANCE OF R = SIGNIFICANT
 $t = +1.1519730E+01$ SIGNIFICANCE OF t = SIGNIFICANT
 $N = 185$ DEGREES OF FREEDOM = 183
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH



STAGE 1 DISSECTED MOTORS, BURNING RATE AT 1000 PSI INITIAL PRESSURE

Figure 45

*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
74.0	3
76.0	3
83.0	3
91.0	3
98.0	6
105.0	3
108.0	1
110.0	1
125.0	1
132.0	1
136.0	3
138.0	3
152.0	3
153.0	3
154.0	3
160.0	3
167.0	3
169.0	6
175.0	3
176.0	3
184.0	3
191.0	3
200.0	3

STAGE 1 DISSECTED MUTUHS. HEAT OF EXPLCSION

This sample size summary is applicable to figure 46

$Y = ((+1.5410055E+03) + (+4.8457936E-02) * X)$
 F = +3.0331898E+00 SIGNIFICANCE OF F = NOT SIGNIFICANT $\sigma^2 = +8.9653095E+00$
 R = +2.1114917E-01 SIGNIFICANCE OF R = NOT SIGNIFICANT $S_e = +2.7823715E-02$
 t = +1.7416055E+00 SIGNIFICANCE OF t = NOT SIGNIFICANT $S_e = +8.8303280E+00$
 N = 67 DEGREES OF FREEDOM = 65
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = AMB TEMP/RH




Figure 46


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
73.0	1
88.0	1
90.0	1
108.0	1
110.0	1
115.0	1
118.0	1
125.0	1
133.0	1
134.0	2
136.0	1
140.0	1
143.0	1
147.0	1
151.0	1
152.0	1
154.0	1
158.0	1
162.0	1
169.0	2
176.0	1

STAGE 1 DISSECTED MIRS. IGNITABILITY, IGNIN THRESHLD FCINT 100 (CAL/SOCM)/SEC

This sample size summary is applicable to figure 47

$Y = ((+5.7692488E+01) + (-3.8549585E-03) * X)$
 SIGNIFICANCE OF F = NOT SIGNIFICANT $G_1 = +6.3507492E+00$
 SIGNIFICANCE OF R = NOT SIGNIFICANT $S_0 = +5.1212708E-02$
 SIGNIFICANCE OF t = NOT SIGNIFICANT $S_t = +6.4993223E+00$
 DEGREES OF FREEDOM = 21
 STORAGE CONDITIONS = AMB TEMP/RH TEST CONDITIONS = 168 CAL/SQCM/SEC



STAGE 1 DISSECTED MTRS. IGNITABILITY. IGNTN THRESHLD POINT 168 (CAL/SQCM)/SEC

Figure 47


*** SAMPLE SIZE SUMMARY ***

AGE (MONTHS)	NR SAMPLES
73.0	4
75.0	4
83.0	2
90.0	3
98.0	5
105.0	5
114.0	3
118.0	3
133.0	4
135.0	3
137.0	3
143.0	3
152.0	2
154.0	3
160.0	3
167.0	4
169.0	5
176.0	4
177.0	3
179.0	4
184.0	5
192.0	3
201.0	3

STAGE 1 DISPERSED MOTURE, DIA. CIRCUMFEREN 1. 1. DEGREE C RISE/MINUTE


This sample size summary is applicable to figures 48 and 49

$Y = ((+2.434465E+02) + (-1.3501864E-02) \times X)$
 $F = +3.6479677E+00$ SIGNIFICANCE OF F = NOT SIGNIFICANT $\alpha = +2.4607066E+00$
 $R = -2.1171507E-01$ SIGNIFICANCE OF R = NOT SIGNIFICANT $S_e = +6.8629861E-03$
 $t = +1.9616286E+00$ SIGNIFICANCE OF t = NOT SIGNIFICANT $S_e = +2.4195457E+00$
 $N = 84$ DEGREES OF FREEDOM = 82
 STORAGE CONDITIONS = AMB TEMP/AM TEST CONDITIONS = AMB TEMP/AM



STAGE 1 DISSECTED MOTORS, DTA, ENDOTHERM 1, 12 DEGREE C RISE/MINUTE

$F = +7.1198556E+00$
 $A = -2.8264958E-01$
 $I = +2.6683057E+00$
 $N =$
 $Y = (1 + 2.9995088E+02) + (-3.9803851E-02) \times X$
 SIGNIFICANCE OF F = SIGNIFICANT
 SIGNIFICANCE OF A = SIGNIFICANT
 SIGNIFICANCE OF I = SIGNIFICANT
 DEGREES OF FREEDOM = 82
 STORAGE CONDITIONS = AMB TEMP/AM
 TEST CONDITIONS = AMB TEMP/AM



STAGE 1 DISSECTED MOTORS, DTA, EXOTHERM 1, 12 DEGREE C RISE/MINUTE

*** SAMPLE SIZE SUMMARY ***


AGE (MONTHS)	NR SAMPLES
73.0	4
75.0	3
83.0	2
90.0	5
96.0	5
103.0	5
114.0	2
133.0	2
135.0	2
140.0	3
152.0	2
154.0	1
167.0	1
169.0	3
176.0	2
177.0	2
179.0	2
184.0	3
192.0	3
201.0	3

STAGE 1 DISSECTED MOUTHS, 27.0 IGNITION TEMP, 12 DEG C RISE/MINUTE

This sample size summary is applicable to figure 50


90

$F = +1.2635442E+01$
 $R = +4.1140475E-01$
 $t = +3.5826565E+00$
 $N = 65$
 $Y = ((+3.5261042E+02) + (+1.0660286E-01) * X)$
 SIGNIFICANCE OF F = SIGNIFICANT
 SIGNIFICANCE OF R = SIGNIFICANT
 SIGNIFICANCE OF t = SIGNIFICANT
 DEGREES OF FREEDOM = 63
 STORAGE CONDITIONS = AMB TEMP/AH
 TEST CONDITIONS = AMB TEMP/AH



STAGE 1 DISSECTED MOTORS, DTA IGNITION TEMP, 12 DEG C RISE/MINUTE

TEMPERATURE CORRECTED FAILURE ENVELOPE



FAILURE ENVELOPE (MOTOR/SN STM-012) DISSECTED MOTOR, STAGE 1, TP-H1011, 1979

DISTRIBUTION

	NR <u>COPIES</u>
OOALC	
MMWRME	1
MMWRMT	1
DDC (TISIR) Cameron Station, Alexandria, VA 22314	2
AFFRO, Thiokol Chemical Corporation Wasatch Division P.O. Box 524 Brigham City, UT 84302 (Cy to R. E. Keating)	2
AFRPL (MKPB) Edwards AFB, CA 93523	1
SAC (LGMB) Offutt AFB, NB 68113	1
U. S. Naval Ordinance Station, Indian Head, MD 20640 Attn: Dr. James H. Wiegand Fleet Support Dept., Propulsion System Development Division, Code FS7	1
CPIA, Johns Hopkins University Attn: Dr. P. L. Nichols Applied Physics Laboratory Johns Hopkins Road Laurel, MD 20810	1
Naval Plant Branch Representative Attn: Mr. David W. Pratt P. O. Box 157, Bacchus Works Magna, UT 84044	1

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MANCP Report Nr 427(79)	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Surveillance Report, Stage I Dissected Motors, Phase XI		5. TYPE OF REPORT & PERIOD COVERED Test Results - Semi annual
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) John A. Thompson		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Propellant Lab Section Directorate of Maintenance Hill AFB, UT 84056		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Service Engineering Division Directorate of Materiel Management Hill AFB, UT 84056		12. REPORT DATE November 1979
		13. NUMBER OF PAGES 95
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for Public Release, Distribution Unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Minuteman Solid Propellant		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Testing was performed to determine the useful shelf/service life for LGM-30 Stage I Rocket Motors. A three year storage program for propellant and components was started in May 1961. This program was then extended to a ten year study and later continued indefinitely to assure that a deterioration in motor physical characteristics could be detected in time to take some corrective actions before the weapon system performance deteriorated below an acceptable level.		

→ This report covers only propellant data and limited case bond data. The malfunction of an environmental chamber destroyed component samples that had originally been part of this testing program (and the inadvertent burning of some motors during dissection reduced the material available for testing). Planned dissection of selected motors in the future will provide samples for continued component testing. Test specimens for this reporting period were obtained from motors STM-012, 0012099, and 012199. Up-7775 block propellant was not tested since the propellant has been used up.

Separate analyses were made on the respective motors and block propellant for the second time in this report and are shown in the regressions. The plotting symbols for each motor and block propellant are listed in the statistical analyses section.

→ The data from this test period was combined with data from previous testing and entered into the G085 computer for storage, analysis, and regression analysis. From the statistical analysis of all data tested to date, significant degradation of the propellant does not appear likely for at least two years past the oldest data point.

Future testing will be conducted on dissected motors.

END