

AD-A081 557

DREXEL UNIV PHILADELPHIA PA DEPT OF PHYSICS AND ATMOS--ETC F/6 20/5
EXTENSION FOR INCREASED DATA COLLECTION OF QUASI-HOMOGENEOUS SO--ETC(U)
FEB 80 L M NARDUCCI

DAA629-78-6-0098

UNCLASSIFIED

ARO-16054.2-A-P-ADD

NL

1-1
20-100

■






END
DATE
FILMED
4-80
DRC

ARD 10004, 2-A-1
all

LEVEL *11*

12
NW

ADA081557



PTIC
ECTE
MAR 11 1980
S *D*

DDG FILE COPY

This document has been approved
for public release and sale; its
distribution is unlimited.

80 3 7 057

EXTENSION FOR INCREASED DATA COLLECTION OF
QUASI-HOMOGENEOUS SOURCES

Accession For	
NTIS GRA&I	☒
DDC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/_____	
Availability Codes	
Dist	Avail and/or special
A	

DTIC
ELECTE
MAR 11 1980
C

This document has been approved
for public release and sale; its
distribution is unlimited.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER <i>Rept. for 1 Jul - 30 Sep 79</i>	2. GOVT ACCESSION NO.	3. REPORT'S CATALOG NUMBER
4. TITLE (and Subtitle) <i>Extension for Increased Data Collection of Quasi-homogeneous Sources. Addendum.</i>	5. TYPE OF REPORT & PERIOD COVERED <i>7/1/79-9/30/79</i>	
6. PERFORMING ORG. REPORT NUMBER		7. CONTRACT OR GRANT NUMBER(s) <i>DAAG-29-78G-0098</i>
8. AUTHOR(s) <i>Lorenzo M. Narducci, Ph.D.</i>	9. PERFORMING ORGANIZATION NAME AND ADDRESS <i>Physics Department, Drexel University Philadelphia, PA 19104</i>	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS <i>Army Research Office, Research Triangle Pk., NC</i>	12. REPORT DATE <i>February 1, 1980</i>	13. NUMBER OF PAGES <i>5 pages & 6 figures</i>
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report)	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) <i>Distribution of this report is unlimited</i>		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES <i>Some sections of this report have been completed in collaboration with Mr. J.D. Farina.</i>		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) <i>Lasers, Coherence Theory, Electromagnetic Propagation, Highly Directional Beams, Variable Coherence Sources.</i>		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <i>This report summarizes our experimental findings. It is divided into 3 sections: the first provides a general introduction to the main problem of quasi-homogeneous sources. The second section contains the important experimental findings from far field measurements. The third summarizes our efforts to perform near field coherence measurements.</i>		

DD FORM 1 JAN 79 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0103-010-0001

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

405-336

JP

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

INSTRUCTIONS FOR PREPARATION OF REPORT DOCUMENTATION PAGE

RESPONSIBILITY. The controlling DoD office will be responsible for completion of the Report Documentation Page, DD Form 1473, in all technical reports prepared by or for DoD organizations.

CLASSIFICATION. Since this Report Documentation Page, DD Form 1473, is used in preparing announcements, bibliographies, and data banks, it should be unclassified if possible. If a classification is required, identify the classified items on the page by the appropriate symbol.

COMPLETION GUIDE

General. Make Blocks 1, 4, 5, 6, 7, 11, 13, 15, and 16 agree with the corresponding information on the report cover. Leave Blocks 2 and 3 blank.

Block 1. Report Number. Enter the unique alphanumeric report number shown on the cover.

Block 2. Government Accession No. Leave blank. This space is for use by the Defense Documentation Center.

Block 3. Recipient's Catalog Number. Leave blank. This space is for the use of the report recipient to assist in future retrieval of the document.

Block 4. Title and Subtitle. Enter the title in all capital letters exactly as it appears on the publication. Titles should be unclassified whenever possible. Write out the English equivalent for Greek letters and mathematical symbols in the title (see "Abstracting Scientific and Technical Reports of Defense-sponsored RDT/E," AD-667 000). If the report has a subtitle, this subtitle should follow the main title, be separated by a comma or semicolon if appropriate, and be initially capitalized. If a publication has a title in a foreign language, translate the title into English and follow the English translation with the title in the original language. Make every effort to simplify the title before publication.

Block 5. Type of Report and Period Covered. Indicate here whether report is interim, final, etc., and, if applicable, inclusive dates of period covered, such as the life of a contract covered in a final contractor report.

Block 6. Performing Organization Report Number. Only numbers other than the official report number shown in Block 1, such as series numbers for in-house reports or a contractor/grantee number assigned by him, will be placed in this space. If no such numbers are used, leave this space blank.

Block 7. Author(s). Include corresponding information from the report cover. Give the name(s) of the author(s) in conventional order (for example, John R. Doe or, if author prefers, J. Robert Doe). In addition, list the affiliation of an author if it differs from that of the performing organization.

Block 8. Contract or Grant Number(s). For a contractor or grantee report, enter the complete contract or grant number(s) under which the work reported was accomplished. Leave blank in in-house reports.

Block 9. Performing Organization Name and Address. For in-house reports enter the name and address, including office symbol, of the performing activity. For contractor or grantee reports enter the name and address of the contractor or grantee who prepared the report and identify the appropriate corporate division, school, laboratory, etc., of the author. List city, state, and ZIP Code.

Block 10. Program Element, Project, Task Area, and Work Unit Numbers. Enter here the number code from the applicable Department of Defense form, such as the DD Form 1498, "Research and Technology Work Unit Summary" or the DD Form 1634, "Research and Development Planning Summary," which identifies the program element, project, task area, and work unit or equivalent under which the work was authorized.

Block 11. Controlling Office Name and Address. Enter the full, official name and address, including office symbol, of the controlling office. (Equates to funding/sponsoring agency. For definition see DoD Directive 5200.20, "Distribution Statements on Technical Documents.")

Block 12. Report Date. Enter here the day, month, and year or month and year as shown on the cover.

Block 13. Number of Pages. Enter the total number of pages.

Block 14. Monitoring Agency Name and Address (if different from Controlling Office). For use when the controlling or funding office does not directly administer a project, contract, or grant, but delegates the administrative responsibility to another organization.

Blocks 15 & 15a. Security Classification of the Report: Declassification/Dowgrading Schedule of the Report. Enter in 15 the highest classification of the report. If appropriate, enter in 15a the declassification/dowgrading schedule of the report, using the abbreviations for declassification/dowgrading schedules listed in paragraph 4-207 of DoD 5200.1-R.

Block 16. Distribution Statement of the Report. Insert here the applicable distribution statement of the report from DoD Directive 5200.20, "Distribution Statements on Technical Documents."

Block 17. Distribution Statement (of the abstract entered in Block 20, if different from the distribution statement of the report). Insert here the applicable distribution statement of the abstract from DoD Directive 5200.20, "Distribution Statements on Technical Documents."

Block 18. Supplementary Notes. Enter information not included elsewhere but useful, such as: Prepared in cooperation with ... Translation of (or by) ... Presented at conference of ... To be published in ...

Block 19. Key Words. Select terms or short phrases that identify the principal subjects covered in the report, and are sufficiently specific and precise to be used as index entries for cataloging, conforming to standard terminology. The DoD "Thesaurus of Engineering and Scientific Terms" (TESST), AD-672 000, can be helpful.

Block 20. Abstract. The abstract should be a brief (not to exceed 200 words) factual summary of the most significant information contained in the report. If possible, the abstract of a classified report should be unclassified and the abstract to an unclassified report should consist of publicly releasable information. If the report contains a significant bibliography or literature survey, mention is here. For information on preparing abstracts see "Abstracting Scientific and Technical Reports of Defense-Sponsored RDT/E," AD-667 000.

INTRODUCTION

In the final report entitled "Development of Quasi-homogeneous Optical Sources" (Grant DAAG29 78 G 0098) we have summarized the theoretical background related to the field of partially coherent sources and discussed the procedure adopted in our laboratory to construct a quasi-homogeneous source.

It is worth emphasizing that the quasi-homogeneity requirements¹ refer to statistical properties of the radiated field. Such properties are not necessarily verified just because reasonable precautions are exercised in the manufacturing of the source. For example, it is intuitively obvious that if the partially coherent source in question is to be produced by illumination of a phase screen with the laser, one should take special care to insure a homogeneous distribution of surface inhomogeneities on the phase screen. Also one would intuitively expect that if the field coherence length is to be much larger than the wavelength of light, a similar constraint should hold for the typical transverse dimensions of the surface roughness of the phase screen. On the contrary, our intuition does not provide much help in interpreting the role played by the rms thickness of the surface roughness in setting the properties of the scattered light.

The above comments serve to emphasize that while the construction of our phase screens was carried out with certain reasonable requirements in mind, the quasi-homogeneous nature of the source had to be tested as critically as if the laser-plus-phase screen combination was actually just a black box containing an unknown radiator.

The most apparent feature of a quasi-homogeneous source is the highly unidirectional aspect of the emitted radiation. Qualitative and quantitative evidence of this effect has already been provided in our previous final report. Two additional theoretical predictions which are expected to hold under quasi-homogeneity conditions concern the independence of the far zone angular

intensity distribution on the shape and size of the illumination profile at the source and the dependence of the far field degree of coherence on the source intensity distribution. The latter property is a consequence of a reciprocity theorem which was first established by Carter and Wolf².

The verification of these properties of a quasi-homogeneous source has been the main goal of our experimental efforts during the period July 1, 1979 thru September 30, 1979. In addition, we have nearly completed the assembly of a microcomputer control and data collection unit which is presently operating in our laboratory.

A detailed description of these activities is provided in the three sections of this report.

FAR FIELD MEASUREMENTS

The independence of the far field intensity distribution on the size and shape of the illumination area at the source plane is one of the most striking properties of quasi-homogeneous sources which have been demonstrated experimentally. The experimental set up which we used to demonstrate this effect is shown in figure 1. As described in our final report for contract #DAAG29-78G-0098, we illuminated a rotating phase screen at normal incidence with various intensity distributions while monitoring the far field intensity as a function of scattering angle. In our previous work we used Gaussian intensity distributions of various widths to verify that the sources which we produced were indeed quasi-homogeneous sources.

Our most recent effort was to investigate the behavior of quasi-homogeneous sources illuminated with intensity distributions other than Gaussian. To study this effect we used several different intensity distributions including Gaussians, truncated Gaussians, rectangular and the TEM_{01}^* transverse mode of our HeNe laser. In each case, the intensity distribution in the far field remained unchanged to the accuracy with which we were able to measure. Some of the source illumination functions along with the corresponding far field intensity distributions are

shown in Figures 2-5. For each of the cases shown in these figures, the effect of changing the illumination function is unmeasurable. It is worth noting that even when the conditions for quasi-homogeneity are not satisfied, as in Figure 4, where the intensity across the source plane varies quite rapidly, the far field invariance is still achieved. This suggests that the condition which states that the intensity must be slowly varying everywhere in the source plane is too stringent and could be restated to say that the intensity at the source should be slowly varying over the majority of the source plane.

The computer system which was outlined in our proposal is designed to automate data collection and enable high resolution large angular scans. The implementation of the computer system was delayed because of long delivery times (i.e. the delivery time for the memory was about two months). At present, the computer is operating in our laboratory but since software still must be refined, the system will not be operating as the primary measuring device until mid-February. This system seems to be very promising for studies of quasi-homogeneous sources not only in the far field, but also in the analysis of coherence data in the near field, and statistical studies of the rotating disk system which will provide insight into the ensemble averaging performed by the rotation of the disk. A schematic drawing of this system is shown in Figure 6 along with a block diagram of the stepper motor controllers which are now in use and will be interfaced with the computer in the future.

COHERENCE MEASUREMENTS

As stated in our proposal, one of the important properties which governs the behavior of quasi-homogeneous sources is the mutual coherence function at the source. We had proposed to measure this function using an improved version of the reversing front interferometer which is a modified Michelson interferometer. The improvements which we made consisted of using high quality optical

components for the retroreflector and beam splitter. Our attempt to redesign our own reversing front interferometer failed to overcome the limitations of our original design which seem to be inherent in an instrument of this type. The resolution which we were able to attain was approximately $100\text{ }\mu\text{m}$ which is at least an order of magnitude larger than would be acceptable for this measurement. Since we believe that the shortcomings of the reversing front interferometer would be present in any reasonable design, we have abandoned its use for the coherence measurements. To carry out these measurements we have designed a new type of instrument which does not possess the same inherent limitations as the reversing front interferometer.

The new instrument is a modified Mach-Zehnder interferometer. The modification consists of an imaging system used in conjunction with the standard Mach-Zehnder interferometer to allow mixing between images to obtain an interference pattern. The resulting interference pattern can easily be analyzed to obtain the mutual coherence function. Although it is still in the construction stages, we feel that this device is very promising based on our experience with the reversing front interferometer. We will report on this in the near future.

FIGURE CAPTIONS

1) A schematic drawing of the experimental set up used to measure the far field intensity distributions.

2) A typical far field intensity distribution obtained with a Gaussian intensity distribution in the source plane. The variance of the mutual coherence function σ_g , of the source is $8.8 \mu\text{m}$ and these measurements were obtained at a distance of 12.5 meters from the source.

3) The far field intensity distribution obtained by illuminating the same source as in Figure 2 with a truncated Gaussian (upper right). The horizontal scale is the same as in Figure 2.

4) The far field intensity distribution obtained by illuminating the same source as in Figure 2 with a rectangular intensity distribution (upper right). The horizontal scale is the same as in Figure 2.

5) The far field intensity distribution obtained by illuminating the same source in Figure 2 with the TEM_{01}^* mode of our laser. The horizontal scale is the same as in Figure 2.

6) a. A block diagram of the computer system used to control scanning in the far field measurements.

b. A block diagram of the stepper motor controllers which can be interfaced with the computer. Both rotation and translation stages are driven by similar controllers.




FIGURE #1

$$\sigma_g = 2.8 \mu m$$

$$Z = 12.5 \text{ meters}$$

$$2\sigma_I \sim 7 \mu m$$




FIGURE #2

1000 Gauss

$\sigma_y = 8.8 \mu m$
 $z = 12.5 \text{ microns}$






FIGURE #3



$V_g = 0.84 \text{ m}$
 $z = 12.5 \text{ m}$




FIGURE #4

$\sigma_y = 8.8 \mu m$
 $z = 12.5 \text{ metre}$





FIGURE #5





FIG. 6A

FIG. 6B



ROTATION/TRANSLATION STAGE CONTROLLER